

EXAMPLE **C** *PROGRAMMING CODES*

Raihan Ahamed2012-15

Program

```
main( )
{
/*.....printing begins.....*/

    printf("I see, I remember");

/*.....printing ends.....*/
}
```

Fig 1.2 A program to print one line of text

Addition of Two Numbers

Program

```
/* Programm ADDITION                                line-1 */
/* Written by EBG                                   line-2 */
main()                                              /* line-3 */
{                                                  /* line-4 */
    int    number;                                /* line-5 */
    float  amount;                                /* line-6 */
                                                /* line-7 */
    number = 100;                                  /* line-8 */
                                                /* line-9 */
    amount = 30.75 + 75.35;                        /* line-10 */
    printf("%d\n",number);                          /* line-11 */
    printf("%5.2f",amount);                         /* line-12 */
}                                                  /* line-13 */
```

Fig.1.4 Program to add two numbers

Program

```
/*----- INVESTMENT PROBLEM -----*/
#define PERIOD    10
#define PRINCIPAL 5000.00
/*----- MAIN PROGRAM BEGINS -----*/
main()
{ /*----- DECLARATION STATEMENTS -----*/
    int year;
    float amount, value, inrate;
/*----- ASSIGNMENT STATEMENTS -----*/
    amount  = PRINCIPAL;
    inrate  = 0.11;
    year    = 0;
```

```

/*----- COMPUTATION STATEMENTS -----*/
/*----- COMPUTATION USING While LOOP -----*/
    while(year <= PERIOD)
    {
        printf("%2d          %8.2f\n",year, amount);
        value =    amount + inrate * amount;
        year    =    year + 1;
        amount   =    value;
    }
/*----- while LOOP ENDS -----*/
}
/*----- PROGRAM ENDS -----*/

```

Fig. 1.5 Program for investment problem

Program

```

/*----- PROGRAM USING FUNCTION -----*/

int mul (int a, int b);      /*----- DECLARATION -----*/

/*----- MAIN PROGRAM BEGINS -----*/
    main ()
    {
        int a, b, c;

        a = 5;
        b = 10;
        c = mul (a,b);

        printf ("multiplication of %d and %d is %d",a,b,c);
    }

/* ----- MAIN PROGRAM ENDS
      MUL() FUNCTION STARTS -----*/

    int mul (int x, int y)
    int p;

    p = x*y;
    {
        return(p);
    }

/* ----- MUL () FUNCTION ENDS -----*/

```

Fig.1.7 A Program using a user-defined function

Program

```
/*----- PROGRAM USING COSINE FUNCTION ----- */
#include <math.h>
#define PI      3.1416
#define MAX     180

main ( )
{

    int angle;
    float x,y;

    angle = 0;
    printf("          Angle      Cos(angle)\n\n");

    while(angle <= MAX)
    {
        x = (PI/MAX)*angle;
        y = cos(x);
        printf("%15d %13.4f\n", angle, y);
        angle = angle + 10;
    }
}
```

1. Calculation of Average of Numbers

A program to calculate the average of a set of N numbers is given in Fig.2.11.

AVERAGE OF n VALUES

Program

```
#define      N      10                /* SYMBOLIC CONSTANT */

main()
{
    int      count ;                  /* DECLARATION OF */
    float    sum, average, number ;  /* VARIABLES      */

    sum      = 0 ;                    /* INITIALIZATION */
    count     = 0 ;                    /* OF VARIABLES   */

    while( count < N )
    {
        scanf("%f", &number) ;
        sum    = sum + number ;
        count  = count + 1 ;
    }

    average = sum/N ;
    printf("N = %d  Sum = %f", N, sum);
    printf("  Average = %f", average);
}
```

Output

```
1
2.3
4.67
1.42
7
3.67
4.08
2.2
4.25
8.21
N = 10  Sum = 38.799999  Average = 3.880000
```

Fig. 2.11 Average of N numbers

The variable **number** is declared as **float** and therefore it can take both integer and real numbers. Since the symbolic constant **N** is assigned the value of 10 using the **#define** statement, the program accepts ten values and calculates their sum using the **while** loop. The

variable **count** counts the number of values and as soon as it becomes 11, the **while** loop is exited and then the average is calculated.

Notice that the actual value of sum is 38.8 but the value displayed is 38.799999. In fact, the actual value that is displayed is quite dependent on the computer system. Such an inaccuracy is due to the way the floating point numbers are internally represented inside the computer.

2. Temperature Conversion Problem

The program presented in Fig.2.12 converts the given temperature in fahrenheit to celsius using the following conversion formula:

$$C = \frac{F - 32}{1.8}$$

FAHRENHEIT - CELSIUS CONVERSION TABLE

Program

```
#define F_LOW      0      /* ----- */
#define F_MAX      250    /* SYMBOLIC CONSTANTS */
#define STEP       25     /* ----- */

main()
{
    typedef float REAL ;      /* TYPE DEFINITION */
    REAL fahrenheit, celsius ; /* DECLARATION */

    fahrenheit = F_LOW ;      /* INITIALIZATION */
    printf("Fahrenheit Celsius\n\n") ;
    while( fahrenheit <= F_MAX )
    {
        celsius = ( fahrenheit - 32.0 ) / 1.8 ;
        printf(" %5.1f %7.2f\n", fahrenheit, celsius);
        fahrenheit = fahrenheit + STEP ;
    }
}
```

Output

Fahrenheit	Celsius
0.0	-17.78
25.0	-3.89
50.0	10.00
75.0	23.89

100.0	37.78
125.0	51.67
150.0	65.56
175.0	79.44
200.0	93.33
225.0	107.22
250.0	121.11

Fig. 2.12 Temperature conversion

The program prints a conversion table for reading temperature in celsius, given the fahrenheit values. The minimum and maximum values and step size are defined as symbolic constants. These values can be changed by redefining the **#define** statements. An user-defined data type name **REAL** is used to declare the variables **fahrenheit** and **celsius**.

The formation specifications **%5.1f** and **%7.2** in the second **printf** statement produces two-column output as shown.

Example 2.1

Representation of integer constants on a 16-bit computer.

The program in Fig.2.9 illustrates the use of integer constants on a 16-bit machine. The output in figure 2.3 shows that the integer values larger than 32767 are not properly stored on a 16-bit machine. However, when they are qualified as long integer (by appending L), the values are correctly stored.

 INTEGER NUMBERS ON 16-BIT MACHINE

Program

```
main()
{
    printf("Integer values\n\n");
    printf("%d %d %d\n", 32767, 32767+1, 32767+10);
    printf("\n");
    printf("Long integer values\n\n");
    printf("%ld %ld %ld\n", 32767L, 32767L+1L, 32767L+10L);
}
```

Output

```
Integer values

32767 -32768 -32759

Long integer values

32767 32768 32777
```

Fig. 2.3 Representation of integer constants

Example 2.2

Program in Figure 2.8 shows typical declarations, assignments and values stored in various types of variables.

The variables **x** and **p** have been declared as floating-point variables. Note that the way the value of 1.234567890000 that we assigned to **x** is displayed under different output formats. The value of **x** is displayed as 1.234567880630 under %.12lf format, while the actual value assigned is 1.234567890000. This is because the variable **x** has been declared as a **float** that can store values only upto six decimal places.

The variable **m** that has been declared as **int** is not able to store the value 54321 correctly. Instead, it contains some garbage. Since this program was run on a 16-bit machine, the maximum value that an **int** variable can store is only 32767. However, the variable **k** (declared as **unsigned**) has stored the value 54321 correctly. Similarly, the **long int** variable **n** has stored the value 1234567890 correctly.

The value 9.87654321 assigned to **y** declared as double has been stored correctly but the value

is printed as 9.876543 under %lf format. Note that unless specified otherwise, the **printf** function will always display a **float** or **double** value to six decimal places. We will discuss later the output formats for displaying numbers.

EXAMPLES OF ASSIGNMENTS

Program

```
main()
{
    /*.....DECLARATIONS.....*/

    float      x, p ;
    double     y, q ;
    unsigned   k ;

    /*.....DECLARATIONS AND ASSIGNMENTS.....*/

    int        m = 54321 ;
    long int    n = 1234567890 ;

    /*.....ASSIGNMENTS.....*/

    x = 1.234567890000 ;
    y = 9.87654321 ;
    k = 54321 ;
    p = q = 1.0 ;

    /*.....PRINTING.....*/

    printf("m = %d\n", m) ;
    printf("n = %ld\n", n) ;
    printf("x = %.12lf\n", x) ;
    printf("x = %f\n", x) ;
    printf("y = %.12lf\n", y) ;
    printf("y = %lf\n", y) ;
    printf("k = %u  p = %f  q = %.12lf\n", k, p, q) ;
}
```

Output

```
m = -11215
n = 1234567890
x = 1.234567880630
x = 1.234568
y = 9.876543210000
y = 9.876543
k = 54321  p = 1.000000  q = 1.000000000000
```

Fig. 2.8 Examples of assignments

Example 2.3

The program in Fig.2.9 illustrates the use of **scanf** function.

The first executable statement in the program is a **printf**, requesting the user to enter an integer number. This is known as "prompt message" and appears on the screen like

Enter an integer number

As soon as the user types in an integer number, the computer proceeds to compare the value with 100. If the value typed in is less than 100, then a message

Your number is smaller than 100

is printed on the screen. Otherwise, the message

Your number contains more than two digits

is printed. Outputs of the program run for two different inputs are also shown in Fig.2.9.

INTERACTIVE COMPUTING USING **scanf** FUNCTION

Program

```
main()
{
    int  number;

    printf("Enter an integer number\n");
    scanf ("%d", &number);

    if ( number < 100 )
        printf("Your number is smaller than 100\n\n");
    else
        printf("Your number contains more than two digits\n");
}
```

Output

```
Enter an integer number
54
Your number is smaller than 100

Enter an integer number
108
Your number contains more than two digits
```

*Fig.2.9 Use of **scanf** function*

Example 2.4

Sample Program 3 discussed in Chapter 1 can be converted into a more flexible interactive program using **scanf** as shown in Fig.2.10.

In this case, computer requests the user to input the values of the amount to be invested, interest rate and period of investment by printing a prompt message

Input amount, interest rate, and period

and then waits for input values. As soon as we finish entering

INTERACTIVE INVESTMENT PROGRAM

Program

```
main()
{
    int    year, period ;
    float  amount, inrate, value ;

    printf("Input amount, interest rate, and period\n\n") ;
    scanf ("%f %f %d", &amount, &inrate, &period) ;
    printf("\n") ;
    year = 1 ;

    while( year <= period )
    {
        value = amount + inrate * amount ;
        printf("%2d  Rs %8.2f\n", year, value) ;
        amount = value ;
        year = year + 1 ;
    }
}
```

Output

Input amount, interest rate, and period

10000 0.14 5

```
1  Rs 11400.00
2  Rs 12996.00
3  Rs 14815.44
4  Rs 16889.60
5  Rs 19254.15
```

Input amount, interest rate, and period

20000 0.12 7

1	Rs	22400.00
2	Rs	25088.00
3	Rs	28098.56
4	Rs	31470.39
5	Rs	35246.84
6	Rs	39476.46
7	Rs	44213.63

Fig.2.10 Interactive investment program

CASE STUDIES

1. SALESMAN'S SALARY

A computer manufacturing company has the following monthly compensation policy to their salespersons:

Minimum base salary : 1500.00
Bonus for every computer sold : 200.00
Commission on the total monthly sales : 2 per cent

Since the prices of computers are changing, the sales price of each computer is fixed at the beginning of every month. A program to compute a sales-person's gross salary is given in Fig.3.9.

PROGRAM TO CALCULATE A SALESMAN'S SALARY

Program

```
#define BASE_SALARY 1500.00
#define BONUS_RATE 200.00
#define COMMISSION 0.02

main()
{
    int    quantity ;
    float  gross_salary, price ;
    float  bonus, commission ;

    printf("Input number sold and price\n") ;
    scanf("%d %f", &quantity, &price) ;

    bonus      = BONUS_RATE * quantity ;
    commission  = COMMISSION * quantity * price ;
    gross_salary = BASE_SALARY + bonus + commission ;

    printf("\n");
    printf("Bonus      = %6.2f\n", bonus) ;
    printf("Commission  = %6.2f\n", commission) ;
    printf("Gross salary = %6.2f\n", gross_salary) ;
}
```

Output

```
Input number sold and price
5 20450.00

Bonus      = 1000.00
Commission = 2045.00
Gross salary = 4545.00
```

Fig. 3.9 Program of salesman's salary

Given the base salary, bonus, and commission rate, the inputs necessary to calculate the gross salary are, the price of each computer and the number sold during the month.

The gross salary is given by the equation :

$$\text{Gross salary} = \text{base salary} + (\text{quantity} * \text{bonus rate}) + (\text{quantity} * \text{Price}) * \text{commission rate}$$

2. SOLUTION OF THE QUADRATIC EQUATION

An equation of the form

$$ax^2 + bx + c = 0$$

is known as the *quadratic equation*. The values of x that satisfy the equation are known as the *roots* of the equation. A quadratic equation has two roots which are given by the following two formulae:

$$\text{root 1} = \frac{-b + \sqrt{b^2 - 4ac}}{2a}$$

$$\text{root 2} = \frac{-b - \sqrt{b^2 - 4ac}}{2a}$$

A program to evaluate these roots is given in Fig.3.10. The program requests the user to input the values of **a**, **b** and **c** and outputs **root1** and **root2**.

Program

```
#include <math.h>

main()
{
    float  a, b, c, discriminant,
           root1, root2;

    printf("Input values of a, b, and c\n");
    scanf("%f %f %f", &a, &b, &c);

    discriminant = b*b - 4*a*c ;

    if(discriminant < 0)
        printf("\n\nROOTS ARE IMAGINARY\n");
    else
    {
        root1 = (-b + sqrt(discriminant))/(2.0*a);
        root2 = (-b - sqrt(discriminant))/(2.0*a);
        printf("\n\nRoot1 = %5.2f\n\nRoot2 = %5.2f\n",
               root1, root2 );
    }
}
```

Output

```
Input values of a, b, and c
2 4 -16

Root1 =  2.00

Root2 = -4.00

Input values of a, b, and c
1 2 3

ROOTS ARE IMAGINARY
```

Fig.3.10 Solution of a quadratic equation

The term (b^2-4ac) is called the *discriminant*. If the discriminant is less than zero, its square roots cannot be evaluated. In such cases, the roots are said to be imaginary numbers and the program outputs an appropriate message.

Example 3.1

The program in Fig.3.1 shows the use of integer arithmetic to convert a given number of days into months and days.

PROGRAM TO CONVERT DAYS TO MONTHS AND DAYS

Program

```
main ()
{
    int    months, days ;

    printf("Enter days\n") ;
    scanf("%d", &days) ;

    months = days / 30 ;
    days    = days % 30 ;

    printf("Months = %d    Days = %d", months, days) ;
}
```

Output

```
Enter days
265
Months = 8    Days = 25

Enter days
364
Months = 12    Days = 4

Enter days
45
Months = 1    Days = 15
```

Fig. 3.1 Illustration of integer arithmetic

Example 3.2

Program of Fig.3.2 prints a sequence of squares of numbers. Note the use of the shorthand operator `*=`.

The program attempts to print a sequence of squares of numbers starting from 2. The statement

```
a *= a;
```

which is identical to

```
a = a*a;
```

replaces the current value of **a** by its square. When the value of **a** becomes equal or greater than **N** (=100) the **while** is terminated. Note that the output contains only three values 2, 4 and 16.

USE OF SHORTHAND OPERATORS

Program

```
#define    N    100
#define    A    2

main()
{
    int  a;

    a  =  A;
    while( a < N )
    {
        printf("%d\n", a);
        a *= a;
    }
}
```

Output

```
2
4
16
```

Fig. 3.2 Use of shorthand operator `=`*

Example 3.3

In Fig.3.3, the program employs different kinds of operators. The results of their evaluation are also shown for comparison.

Notice the way the increment operator **++** works when used in an expression. In the statement

```
c = ++a - b;
```

new value of **a** (= 16) is used thus giving the value 6 to **c**. That is, **a** is incremented by 1 before it is used in the expression. However, in the statement

```
d = b++ + a;
```

the old value of **b** (=10) is used in the expression. Here, **b** is incremented by 1 after it is used in the expression.

We can print the character **%** by placing it immediately after another **%** character in the control string. This is illustrated by the statement

```
printf("a%%b = %d\n", a%b);
```

The program also illustrates that the expression

```
c > d ? 1 : 0
```

assumes the value 0 when **c** is less than **d** and 1 when **c** is greater than **d**.

ILLUSTRATION OF OPERATORS

Program

```
main()
{
    int a, b, c, d;

    a = 15;
    b = 10;
    c = ++a - b;

    printf("a = %d  b = %d  c = %d\n", a, b, c);

    d = b++ + a;

    printf("a = %d  b = %d  d = %d\n", a, b, d);

    printf("a/b = %d\n", a/b);
    printf("a%%b = %d\n", a%b);
    printf("a *= b = %d\n", a*=b);
    printf("%d\n", (c>d) ? 1 : 0);
    printf("%d\n", (c<d) ? 1 : 0);
}
```

Output

```
a = 16  b = 10  c = 6
a = 16  b = 11  d = 26
a/b = 1
a%b = 5
a *= b = 176
0
1
```

Fig. 3.3 Further illustration of arithmetic operators

Example 3.4

The program in Fig.3.4 illustrates the use of variables in expressions and their evaluation.

Output of the program also illustrates the effect of presence of parentheses in expressions. This is discussed in the next section.

EVALUATION OF EXPRESSIONS

Program

```
main()
{
    float  a, b, c, x, y, z;

    a = 9;
    b = 12;
    c = 3;

    x = a - b / 3 + c * 2 - 1;
    y = a - b / (3 + c) * (2 - 1);
    z = a - (b / (3 + c) * 2) - 1;

    printf("x = %f\n", x);
    printf("y = %f\n", y);
    printf("z = %f\n", z);
}
```

Output

```
x = 10.000000
y = 7.000000
z = 4.000000
```

Fig.3.4 Illustrations of evaluation of expressions

Example 3.5

Output of the program in Fig.3.6 shows round-off errors that can occur in computation of floating point numbers.

PROGRAM SHOWING ROUND-OFF ERRORS

Program

```
/*----- Sum of n terms of 1/n -----*/
main()
{
    float  sum, n, term ;
    int    count = 1 ;

    sum = 0 ;
    printf("Enter value of n\n") ;
    scanf("%f", &n) ;
    term = 1.0/n ;
    while( count <= n )
    {
        sum = sum + term ;
        count++ ;
    }
    printf("Sum = %f\n", sum) ;
}
```

Output

```
Enter value of n
99
Sum = 1.000001
Enter value of n
143
Sum = 0.999999
```

Fig.3.6 Round-off errors in floating point computations

We know that the sum of n terms of $1/n$ is 1. However, due to errors in floating point representation, the result is not always 1.

Example 3.6

Figure 3.8 shows a program using a cast to evaluate the equation

$$\text{sum} = \sum_{i=1}^n (1/i)$$

PROGRAM SHOWING THE USE OF A CAST

Program

```
main()
{
    float  sum ;
    int    n ;

    sum = 0 ;

    for( n = 1 ; n <= 10 ; ++n )
    {
        sum = sum + 1/(float)n ;
        printf("%2d  %6.4f\n", n, sum) ;
    }
}
```

Output

```
1  1.0000
2  1.5000
3  1.8333
4  2.0833
5  2.2833
6  2.4500
7  2.5929
8  2.7179
9  2.8290
10 2.9290
```

Fig. 3.8 Use of a cast

CASE STUDIES

1. Inventory Report

Problem: The ABC Electric Company manufactures four consumer products. Their inventory position on a particular day is given below:

Code	Quantity	Rate (Rs)
F105	275	575.00
H220	107	99.95
I019	321	215.50
M315	89	725.00

It is required to prepare the inventory report table in the following format:

INVENTORY REPORT			
Code	Quantity	Rate	Value
----	----	----	----
----	----	----	----
----	----	----	----
----	----	----	----
Total Value:			-----

The value of each item is given by the product of quantity and rate.

Program: The program given in Fig.4.12 reads the data from the terminal and generates the required output. The program uses subscripted variables which are discussed in Chapter 7.

INVENTORY REPORT

Program

```
#define ITEMS 4

main()
{ /* BEGIN */

    int i, quantity[5];
    float rate[5], value, total_value;
    char code[5][5];

    /* READING VALUES */

    i = 1;
    while ( i <= ITEMS)
    {
        printf("Enter code, quantity, and rate:");
        scanf("%s %d %f", code[i], &quantity[i], &rate[i]);
        i++;
    }
    /*.....Printing of Table and Column Headings.....*/

    printf("\n\n");
    printf("                INVENTORY REPORT                \n");
    printf("-----\n");
    printf(" Code      Quantity      Rate      Value      \n");
    printf("-----\n");

    /*.....Preparation of Inventory Position.....*/

    total_value = 0;
    i = 1;
    while ( i <= ITEMS)
    {
        value = quantity[i] * rate[i];
        printf("%5s %10d %10.2f %e\n", code[i], quantity[i],
            rate[i], value);
        total_value += value;
        i++;
    }
    /*.....Printing of End of Table.....*/

    printf("-----\n");
    printf("                Total Value = %e\n", total_value);
    printf("-----\n");

} /* END */
```

Output

```
Enter code, quantity, and rate:F105  275  575.00
Enter code, quantity, and rate:H220  107   99.95
Enter code, quantity, and rate:I019  321  215.50
Enter code, quantity, and rate:M315   89  725.00
```

INVENTORY REPORT			
Code	Quantity	Rate	Value
F105	275	575.00	1.581250e+005
H220	107	99.95	1.069465e+004
I019	321	215.50	6.917550e+004
M315	89	725.00	6.452500e+004
Total Value = 3.025202e+005			

Fig.4.12 Program for inventory report

2. Reliability Graph

Problem: The reliability of an electronic component is given by

$$\text{reliability (r)} = e^{-\lambda t}$$

where λ is the component failure rate per hour and t is the time of operation in hours. A graph is required to determine the reliability at various operating times, from 0 to 3000 hours. The failure rate λ (lamda) is 0.001.

Problem

```
#include <math.h>
#define LAMDA 0.001

main()
{
    double t;
    float r;
    int i, R;

    for (i=1; i<=27; ++i)
    {
        printf("--");
    }

    printf("\n");

    for (t=0; t<=3000; t+=150)
    {
        r = exp(-LAMDA*t);
        R = (int) (50*r+0.5);
        printf(" |");

        for (i=1; i<=R; ++i)
        {
            printf("*");
        }

        printf("#\n");
    }

    for (i=1; i<3; ++i)
    {
        printf(" |\n");
    }

}
```

Output

[illegible]

Fig.4.13 Program to draw reliability graph

Program: The program given in Fig. 4.13 produces a shaded graph. The values of t are self-generated by the **for** statement

```
for (t=0; t <= 3000; t = t+150)
```

in steps of 150. The integer 50 in the statement

$$R = (\text{int})(50 \cdot r + 0.5)$$

is a scale factor which converts r to a large value where an integer is used for plotting the curve. Remember r is always less than 1.

Example 4.1

The program in Fig.4.1 shows the use of **getchar** function in an interactive environment.

The program displays a question of YES/NO type to the user and reads the user's response in a single character (Y or N). If the response is Y, it outputs the message

My name is BUSY BEE

otherwise, outputs.

You are good for nothing

Note there is one line space between the input text and output message.

*READING A **CHARACTER** FROM KEYBOARD*

Program

```
#include <stdio.h>

main()
{
    char answer;

    printf("Would you like to know my name?\n");
    printf("Type Y for YES and N for NO:  ");

    answer = getchar(); /* .... Reading a character...*/

    if(answer == 'Y' || answer == 'y')
        printf("\n\nMy name is BUSY BEE\n");
    else
        printf("\n\nYou are good for nothing\n");
}
```

Output

```
Would you like to know my name?
Type Y for YES and N for NO:  Y

My name is BUSY BEE

Would you like to know my name?
Type Y for YES and N for NO:  n

You are good for nothing
```

Fig.4.1 Use of *getchar* function

Example 4.2

The program of Fig.4.2 requests the user to enter a character and displays a message on the screen telling the user whether the character is an alphabet or digit, or any other special character.

This program receives a character from the keyboard and tests whether it is a letter or digit and prints out a message accordingly. These tests are done with the help of the following functions:

isalpha(character)
isdigit(character)

For example, **isalpha** assumes a value non-zero (TRUE) if the argument **character** contains an alphabet; otherwise it assumes 0 (FALSE). Similar is the case with the function **isdigit**.

TESTING CHARACTER TYPE

Program:

```
#include <stdio.h>
#include <ctype.h>

main()
{
    char character;
    printf("Press any key\n");
    character = getchar();
    if (isalpha(character) > 0)
        printf("The character is a letter.");
    else
        if (isdigit (character) > 0)
            printf("The character is a digit.");
        else
            printf("The character is not alphanumeric.");
}
```

Output

```
Press any key
h
The character is a letter.

Press any key
5
The character is a digit.

Press any key
*
The character is not alphanumeric.
```

Fig.4.2 Program to test the *character* type

Example 4.3

A program that reads a character from keyboard and then prints it in reverse case is given in Fig.4.3. That is, if the input is upper case, the output will be lower case and vice versa.

The program uses three new functions: **islower**, **toupper**, and **tolower**. The function **islower** is a conditional function and takes the value TRUE if the argument is a lower case alphabet; otherwise takes the value FALSE. The function **toupper** converts the lower case argument into an upper case alphabet while the function **tolower** does the reverse.

WRITING A **CHARACTER** TO THE SCREEN

Program

```
#include <stdio.h>
#include <ctype.h>

main()
{
    char alphabet;
    printf("Enter an alphabet");
    putchar('\n');    /* move to next line */
    alphabet = getchar();
    if (islower(alphabet))
        putchar(toupper(alphabet));
    else
        putchar(tolower(alphabet));
}
```

Output

```
Enter an alphabet
a
A
Enter an alphabet
Q
q
Enter an alphabet
z
Z
```

Fig.4.3 Reading and writing of alphabets in reverse case

Example 4.4

Various input formatting options for reading integers are experimented in the program shown in Fig. 4.4.

The first **scanf** requests input data for three integer values **a**, **b**, and **c**, and accordingly three values 1, 2, and 3 are keyed in. Because of the specification `%*d` the value 2 has been skipped and 3 is assigned to the variable **b**. Notice that since no data is available for **c**, it contains garbage.

The second **scanf** specifies the format `%2d` and `%4d` for the variables **x** and **y** respectively. Whenever we specify field width for reading integer numbers, the input numbers should not contain more digits than the specified size. Otherwise, the extra digits on the right-hand side will be truncated and assigned to the next variable in the list. Thus, the second **scanf** has truncated the four digit number 6789 and assigned 67 to **x** and 89 to **y**. The value 4321 has been assigned to the first variable in the immediately following **scanf** statement.

Program:

```
main()
{
    int a,b,c,x,y,z;
    int p,q,r;

    printf("Enter three integer numbers\n");
    scanf("%d %*d %d",&a,&b,&c);
    printf("%d %d %d \n\n",a,b,c);

    printf("Enter two 4-digit numbers\n");
    scanf("%2d %4d",&x,&y);
    printf("%d %d\n\n", x,y);

    printf("Enter two integers\n");
    scanf("%d %d", &a,&x);
    printf("%d %d \n\n",a,x);

    printf("Enter a nine digit number\n");
    scanf("%3d %4d %3d",&p,&q,&r);
    printf("%d %d %d \n\n",p,q,r);

    printf("Enter two three digit numbers\n");
    scanf("%d %d",&x,&y);
    printf("%d %d",x,y);
}
```

Output

```
Enter three integer numbers
1 2 3
1 3 -3577

Enter two 4-digit numbers
6789 4321
67 89

Enter two integers
44 66
4321 44

Enter a nine-digit number
123456789
66 1234 567

Enter two three-digit numbers
123 456
89 123
```

Fig.4.4 Reading integers using **scanf**

Example 4.5

Reading of real numbers (in both decimal point and exponential notation) is illustrated in Fig.4.5.

READING OF **REAL** NUMBERS

Program:

```
main()
{
    float x,y;
    double p,q;

    printf("Values of x and y:");
    scanf("%f %e", &x, &y);
    printf("\n");
    printf("x = %f\ny = %f\n\n", x, y);

    printf("Values of p and q:");
    scanf("%lf %lf", &p, &q);
    printf("\np = %lf\nq = %e",p,q);
    printf("\n\np = %.12lf\nq = %.12e", p,q);
}
```

Output

```
Values of x and y:12.3456  17.5e-2
x = 12.345600
y = 0.175000

Values of p and q:4.142857142857  18.5678901234567890
p = 4.142857142857
q = 1.856789012346e+001
```

Fig.4.5 Reading of *real* numbers

Example 4.6

Reading of strings using **%wc** and **%ws** is illustrated in Fig.4.6.

The program in Fig.4.6 illustrates the use of various field specifications for reading strings. When we use **%wc** for reading a string, the system will wait until the w^{th} character is keyed in.

Note that the specification **%s** terminates reading at the encounter of a blank space. Therefore, **name2** has read only the first part of "New York" and the second part is automatically assigned to **name3**. However, during the second run, the string "New-York" is correctly assigned to **name2**.

Program

```
main()
{
    int no;
    char name1[15], name2[15], name3[15];

    printf("Enter serial number and name one\n");
    scanf("%d %15c", &no, name1);
    printf("%d %15s\n\n", no, name1);

    printf("Enter serial number and name two\n");
    scanf("%d %s", &no, name2);
    printf("%d %15s\n\n", no, name2);

    printf("Enter serial number and name three\n");
    scanf("%d %15s", &no, name3);
    printf("%d %15s\n\n", no, name3);
}
```

Output

```
Enter serial number and name one
1 123456789012345
1 123456789012345r

Enter serial number and name two
2 New York
2          New

Enter serial number and name three
2          York

Enter serial number and name one
1 123456789012
1 123456789012   r

Enter serial number and name two
2 New-York
2 New-York

Enter serial number and name three
3 London
3 London
```

Fig. 4.6 Reading of strings

Example 4.7

The program in Fig. 4.7 illustrates the function of %[] specification.

ILLUSTRATION OF %[] SPECIFICATION

Program-A

```
main()
{
    char address[80];
    printf("Enter address\n");
    scanf("%[a-z']", address);
    printf("%-80s\n\n", address);
}
```

Output

```
Enter address
new delhi 110002
new delhi
```

ILLUSTRATION OF %[^] SPECIFICATION

Program-B

```
main()
{
    char address[80];

    printf("Enter address\n");
    scanf("%[^\\n]", address);
    printf("%-80s", address);
}
```

Output

```
Enter address
New Delhi 110 002
New Delhi 110 002
```

Fig.4.7 Illustration of conversion specification %[] for strings

Example 4.8

The program presented in Fig.4.8 illustrates the testing for correctness of reading of data by **scanf** function.

The function **scanf** is expected to read three items of data and therefore, when the values for all the three variables are read correctly, the program prints out their values. During the third run, the second item does not match with the type of variable and therefore the reading is terminated and the error message is printed. Same is the case with the fourth run.

In the last run, although data items do not match the variables, no error message has been printed. When we attempt to read a real number for an **int** variable, the integer part is assigned to the variable, and the truncated decimal part is assigned to the next variable. Note that the character '2' is assigned to the character variable c.

TESTING FOR CORRECTNESS OF INPUT DATA

Program

```
main()
{
    int a;
    float b;
    char c;

    printf("Enter values of a, b and c\n");
    if (scanf("%d %f %c", &a, &b, &c) == 3)
        printf("a = %d  b = %f  c = %c\n" , a, b, c);
    else
        printf("Error in input.\n");
}
```

Output	Enter values of a, b and c 12 3.45 A a = 12 b = 3.450000 c = A Enter values of a, b and c 23 78 9 a = 23 b = 78.000000 c = 9 Enter values of a, b and c 8 A 5.25 Error in input. Enter values of a, b and c Y 12 67 Error in input. Enter values of a, b and c 15.75 23 X a = 15 b = 0.750000 c = 2
---------------	---

Fig.4.8 Detection of errors in **scanf** input

Example 4.9

The program in Fig.4.9 illustrates the output of integer numbers under various formats.

PRINTING OF **INTEGER** NUMBERS

Program:

```
main()
{
    int m = 12345;
    long n = 987654;

    printf("%d\n",m);
    printf("%10d\n",m);
    printf("%010d\n",m);
    printf("%-10d\n",m);
    printf("%10ld\n",n);
    printf("%10ld\n",-n);
}
```

Output

```
12345
      12345
0000012345
12345
      987654
     -987654
```

Fig.4.9 Formatted output of integers

Example 4.10

All the options of printing a real number are illustrated in Fig.4.10.

PRINTING OF **REAL** NUMBERS

Program:

```
main()
{
    float y = 98.7654;

    printf("%7.4f\n", y);
    printf("%f\n", y);
    printf("%7.2f\n", y);
    printf("%-7.2f\n", y);
    printf("%07.2f\n", y);
}
```

```

printf("%*.*f", 7, 2, y);
printf("\n");
printf("%10.2e\n", y);
printf("%12.4e\n", -y);
printf("%-10.2e\n", y);
printf("%e\n", y);
}

```

Output	98.7654
	98.765404
	98.77
	98.77
	0098.77
	98.77
	9.88e+001
	-9.8765e+001
	9.88e+001
	9.876540e+001

Fig.4.10 Formatted output of *real* numbers

Example 4.11

Printing of characters and strings is illustrated in Fig.4.11.

PRINTING OF CHARACTERS AND STRINGS

Program

```

main()
{
    char x = 'A';
    static char name[20] = "ANIL KUMAR GUPTA";

    printf("OUTPUT OF CHARACTERS\n\n");
    printf("%c\n%3c\n%5c\n", x,x,x);
    printf("%3c\n%c\n", x,x);
    printf("\n");

    printf("OUTPUT OF STRINGS\n\n");
    printf("%s\n", name);
    printf("%20s\n", name);
    printf("%20.10s\n", name);
    printf("%.5s\n", name);
    printf("%-20.10s\n", name);
    printf("%5s\n", name);
}

```

Output

OUTPUT OF CHARACTERS

```
A
  A
    A
  A
A
```

OUTPUT OF STRINGS

```
ANIL KUMAR GUPTA
      ANIL KUMAR GUPTA
            ANIL KUMAR
ANIL
ANIL KUMAR
ANIL KUMAR GUPTA
```

Fig.4.11 *Printing of characters and strings*

CASE STUDIES

1. Range of Numbers

Problem: A survey of the computer market shows that personal computers are sold at varying costs by the vendors. The following is the list of costs (in hundreds) quoted by some vendors:

35.00,	40.50,	25.00,	31.25,	68.15,
47.00,	26.65,	29.00	53.45,	62.50

Determine the average cost and the range of values.

Problem analysis: Range is one of the measures of dispersion used in statistical analysis of a series of values. The range of any series is the difference between the highest and the lowest values in the series. That is

Range = highest value - lowest value

It is therefore necessary to find the highest and the lowest values in the series.

Program: A program to determine the range of values and the average cost of a personal computer in the market is given in Fig.5.14.

RANGE OF NUMBERS

Program

```
main()
{
    int count;
    float value, high, low, sum, average, range;

    sum = 0;
    count = 0;

    printf("Enter numbers in a line :
           input a NEGATIVE number to end\n");
input:
    scanf("%f", &value);
    if (value < 0) goto output;
    count = count + 1;
    if (count == 1)
        high = low = value;
    else if (value > high)
        high = value;
    else if (value < low)
        low = value;

    sum = sum + value;
    goto input;

output:
    average = sum/count;
    range = high - low;
    printf("\n\n");
```

```
printf("Total values : %d\n", count);
printf("Highest-value: %f\nLowest-value : %f\n",
      high, low);
printf("Range          : %f\nAverage          : %f\n",
      range, average);
}
```

Output

```
Enter numbers in a line : input a NEGATIVE number to end
35 40.50 25 31.25 68.15 47 26.65 29 53.45 62.50 -1
```

```
Total values : 10
Highest-value: 68.150002
Lowest-value  : 25.000000
Range         : 43.150002
Average       : 41.849998
```

Fig.5.14 Calculation of range of values

When the value is read the first time, it is assigned to two buckets, **high** and **low**, through the statement

high = low = value;

For subsequent values, the value read is compared with high; if it is larger, the value is assigned to high. Otherwise, the value is compared with low; if it is smaller, the value is assigned to low. Note that at a given point, the buckets high and low hold the highest and the lowest values read so far.

The values are read in an input loop created by the **goto** input; statement. The control is transferred out of the loop by inputting a negative number. This is caused by the statement

if (value < 0) goto output;

Note that this program can be written without using **goto** statements. Try.

2. Pay-Bill Calculations

Problem: A manufacturing company has classified its executives into four levels for the benefit of certain perks. The levels and corresponding perks are shown below:

Level	Perks	
	Conveyance allowance	Entertainment allowance
1	1000	500
2	750	200
3	500	100
4	250	-

An executive's gross salary includes basic pay, house rent allowance at 25% of basic pay and other perks. Income tax is withheld from the salary on a percentage basis as follows:

Gross salary	Tax rate
Gross \leq 2000	No tax deduction
2000 < Gross \leq 4000	3%
4000 < Gross \leq 5000	5%
Gross > 5000	8%

Write a program that will read an executive's job number, level number, and basic pay and then compute the net salary after withholding income tax.

Problem analysis:

Gross salary = basic pay + house rent allowance + perks

Net salary = Gross salary - income tax.

The computation of perks depends on the level, while the income tax depends on the gross salary. The major steps are:

1. Read data.
2. Decide level number and calculate perks.
3. Calculate gross salary.
4. Calculate income tax.
5. Compute net salary.
6. Print the results.

Program: A program and the results of the test data are given in Fig. 5.15. Note that the last statement should be an executable statement. That is, the label **stop:** cannot be the last line.

PAY-BILL CALCULATIONS

Program

```
#define      CA1      1000
#define      CA2      750
#define      CA3      500
#define      CA4      250
#define      EA1      500
#define      EA2      200
#define      EA3      100
#define      EA4       0

main()
{
    int      level, jobnumber;
    float    gross,
            basic,
            house_rent,
            perks,
            net,
            incometax;

    input:
    printf("\nEnter level, job number, and basic pay\n");
    printf("Enter 0 (zero) for level to END\n\n");
    scanf("%d", &level);
    if (level == 0) goto stop;
    scanf("%d %f", &jobnumber, &basic);
    switch (level)
    {
        case 1:
            perks = CA1 + EA1;
            break;
        case 2:
            perks = CA2 + EA2;
            break;
        case 3:
            perks = CA3 + EA3;
            break;
        case 4:
            perks = CA4 + EA4;
            break;
        default:
            printf("Error in level code\n");
            goto stop;
    }
    house_rent = 0.25 * basic;
    gross = basic + house_rent + perks;
    if (gross <= 2000)
        incometax = 0;
    else if (gross <= 4000)
        incometax = 0.03 * gross;
```

```

        else if (gross <= 5000)
            incometax = 0.05 * gross;
        else
            incometax = 0.08 * gross;
    net = gross - incometax;
    printf("%d %d %.2f\n", level, jobnumber, net);
    goto input;
stop: printf("\n\nEND OF THE PROGRAM");
}

```

Output

```

Enter level, job number, and basic pay
Enter 0 (zero) for level to END

```

```

1 1111 4000
1 1111 5980.00

```

```

Enter level, job number, and basic pay
Enter 0 (zero) for level to END

```

```

2 2222 3000
2 2222 4465.00

```

```

Enter level, job number, and basic pay
Enter 0 (zero) for level to END

```

```

3 3333 2000
3 3333 3007.00

```

```

Enter level, job number, and basic pay
Enter 0 (zero) for level to END

```

```

4 4444 1000
4 4444 1500.00

```

```

Enter level, job number, and basic pay
Enter 0 (zero) for level to END

```

```

0
END OF THE PROGRAM

```

Fig.5.15 Pay-bill calculations

Example 5.1

The program in Fig.5.3 reads four values a, b, c, and d from the terminal and evaluates the ratio of (a+b) to (c-d) and prints the result, if c-d is not equal to zero.

The program given in Fig.5.3 has been run for two sets of data to see that the paths function properly. The result of the first run is printed as

Ratio = -3.181818

ILLUSTRATION OF **if** STATEMENT

Program

```
main()
{
    int a, b, c, d;
    float ratio;

    printf("Enter four integer values\n");
    scanf("%d %d %d %d", &a, &b, &c, &d);

    if (c-d != 0) /* Execute statement block */
    {
        ratio = (float) (a+b) / (float) (c-d);
        printf("Ratio = %f\n", ratio);
    }
}
```

Output

```
Enter four integer values
12 23 34 45
Ratio = -3.181818

Enter four integer values
12 23 34 34
```

Fig. 5.3 Illustration of simple **if** statement

Example 5.2

The program in Fig.5.4 counts the number of boys whose weight is less than 50 kgs and height is greater than 170 cm.

The program has to test two conditions, one for weight and another for height. This is done using the compound relation

```
if (weight < 50 && height > 170)
```

This would have been equivalently done using two **if** statements as follows:

```
if (weight < 50)
    if (height > 170)
        count = count + 1;
```

If the value of **weight** is less than 50, then the following statement is executed, which in turn is another **if** statement. This **if** statement tests **height** and if the **height** is greater than 170, then the **count** is incremented by 1.

COUNTING WITH **if**

Program

```
main()
{
    int count, i;
    float weight, height;

    count = 0;
    printf("Enter weight and height for 10 boys\n");

    for (i = 1; i <= 10; i++)
    {
        scanf("%f %f", &weight, &height);
        if (weight < 50 && height > 170)
            count = count + 1;
    }

    printf("Number of boys with weight < 50 kgs\n");
    printf("and height > 170 cm = %d\n", count);
}
```

Output

```
Enter weight and height for 10 boys
45  176.5
55  174.2
47  168.0
49  170.7
54  169.0
53  170.5
49  167.0
48  175.0
47  167
51  170

Number of boys with weight < 50 kgs
and height > 170 cm = 3
```

Fig. 5.4 Use of *if* for counting

Example 5.3

A program to evaluate the power series

$$e^x = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots + \frac{x^n}{n!}, \quad 0 < x < 1$$

is given in Fig. 5.6. It uses **if.....else** to test the accuracy.

The power series contains the recurrence relationship of the type

$$T_n = T_{n-1} \left(\frac{x}{n} \right) \text{ for } n > 1$$

$$T_1 = x \quad \text{for } n = 1$$

$$T_0 = 1$$

If T_{n-1} (usually known as *previous term*) is known, then T_n (known as *present term*) can be easily found by multiplying the previous term by x/n . Then

$$e^x = T_0 + T_1 + T_2 + \dots + T_n = \text{sum}$$

Program

```
#define ACCURACY 0.0001

main()
{
    int n, count;
    float x, term, sum;

    printf("Enter value of x:");
    scanf("%f", &x);

    n = term = sum = count = 1;

    while (n <= 100)
    {
        term = term * x/n;
        sum = sum + term;
        count = count + 1;
        if (term < ACCURACY)
            n = 999;
        else
            n = n + 1;
    }

    printf("Terms = %d Sum = %f\n", count, sum);
}
```

Output

```
Enter value of x:0
Terms = 2 Sum = 1.000000

Enter value of x:0.1
Terms = 5 Sum = 1.105171

Enter value of x:0.5
Terms = 7 Sum = 1.648720

Enter value of x:0.75
Terms = 8 Sum = 2.116997

Enter value of x:0.99
Terms = 9 Sum = 2.691232

Enter value of x:1
Terms = 9 Sum = 2.718279
```

Fig 5.6 Illustration of *if...else* statement

Example 5.4

The program in Fig. 5.8 selects and prints the largest of the three numbers using nested *if...else* statements.

SELECTING THE LARGEST OF THREE VALUES

Program

```
main()
{
    float A, B, C;

    printf("Enter three values\n");
    scanf("%f %f %f", &A, &B, &C);

    printf("\nLargest value is  ");

    if (A>B)
    {
        if (A>C)
            printf("%f\n", A);
        else
            printf("%f\n", C);
    }
    else
    {
        if (C>B)
            printf("%f\n", C);
        else
            printf("%f\n", B);
    }
}
```

Output

```
Enter three values
23445  67379  88843

Largest value is  88843.000000
```

Fig 5.8 Selecting the largest of three numbers

Example 5.5

An electric power distribution company charges its domestic consumers as follows:

<i>Consumption Units</i>	<i>Rate of Charge</i>
0 - 200	Rs. 0.50 per unit
201 - 400	Rs. 100 plus Rs.0.65 per unit excess of 200
401 - 600	Rs. 230 plus Rs.0.80 per unit excess of 400
601 and above	Rs. 390 plus Rs.1.00 per unit excess of 600

The program in Fig.5.10 reads the customer number and power consumed and prints the amount to be paid by the customer.

USE OF **else if** LADDER

Program

```
main()
{
    int  units, custnum;
    float charges;

    printf("Enter CUSTOMER NO. and UNITS consumed\n");
    scanf("%d %d", &custnum, &units);

    if (units <= 200)
        charges = 0.5 * units;
    else if (units <= 400)
        charges = 100 + 0.65 * (units - 200);
    else if (units <= 600)
        charges = 230 + 0.8 * (units - 400);
    else
        charges = 390 + (units - 600);

    printf("\n\nCustomer No: %d: Charges = %.2f\n",
           custnum, charges);
}
```

Output

```
Enter CUSTOMER NO. and UNITS consumed 101  150
Customer No:101 Charges = 75.00

Enter CUSTOMER NO. and UNITS consumed 202  225
Customer No:202 Charges = 116.25

Enter CUSTOMER NO. and UNITS consumed 303  375
Customer No:303 Charges = 213.75

Enter CUSTOMER NO. and UNITS consumed 404  520
Customer No:404 Charges = 326.00

Enter CUSTOMER NO. and UNITS consumed 505  625
Customer No:505 Charges = 415.00
```

Fig. 5.10 Illustration of *else..if* ladder

Example 5.6

An employee can apply for a loan at the beginning of every six months, but he will be sanctioned the amount according to the following company rules:

Rule 1 : An employee cannot enjoy more than two loans at any point of time.

Rule 2 : Maximum permissible total loan is limited and depends upon the category of the employee.

A program to process loan applications and to sanction loans is given in Fig. 5.12.

CONDITIONAL OPERATOR

Program

```
#define    MAXLOAN    50000

main()
{
    long int loan1, loan2, loan3, sancloan, sum23;

    printf("Enter the values of previous two loans:\n");
    scanf(" %ld %ld", &loan1, &loan2);

    printf("\nEnter the value of new loan:\n");
    scanf(" %ld", &loan3);

    sum23 = loan2 + loan3;
    sancloan = (loan1>0)? 0 : ((sum23>MAXLOAN)?
                             MAXLOAN - loan2 : loan3);

    printf("\n\n");
    printf("Previous loans pending:\n%ld %ld\n", loan1, loan2);
    printf("Loan requested = %ld\n", loan3);
    printf("Loan sanctioned = %ld\n", sancloan);

}
```

Output

```
Enter the values of previous two loans:
0      20000

Enter the value of new loan:
45000
```

```

Previous loans pending:
0    20000
Loan requested  = 45000
Loan sanctioned = 30000

Enter the values of previous two loans:
1000    15000

Enter the value of new loan:
25000

Previous loans pending:
1000    15000
Loan requested  = 25000
Loan sanctioned = 0

```

Fig 5.12 *Illustration of the conditional operator*

Example 5.7

Program presented in Fig.5.13 illustrates the use of the **goto** statement.

The program evaluates the square root for five numbers. The variable count keeps the count of numbers read. When count is less than or equal to 5, **goto read**; directs the control to the label **read**; otherwise, the program prints a message and stops.

*USE OF **goto** STATEMENT*

Program

```

#include <math.h>
main()
{
    double x, y;
    int count;

    count = 1;

    printf("Enter FIVE real values in a LINE \n");
read:
    scanf("%lf", &x);
    printf("\n");
    if (x < 0)
        printf("Value - %d is negative\n",count);
    else
    {

```

```
        y = sqrt(x);
        printf("%lf\t %lf\n", x, y);
    }
    count = count + 1;

    if (count <= 5)
goto read;
    printf("\nEnd of computation");
}
```

Output

```
Enter FIVE real values in a LINE
50.70  40  -36  75  11.25
50.750000          7.123903
40.000000          6.324555

Value -3 is negative
75.000000          8.660254
11.250000          3.354102
End of computation
```

Fig.5.13 Use of the goto statement

CASE STUDIES

1. Table of Binomial Coefficients

Problem: Binomial coefficients are used in the study of binomial distributions and reliability of multicomponent redundant systems. It is given by

$$B(m,x) = \binom{m}{x} = \frac{m!}{x! (m-x)!}, \quad m \geq x$$

A table of binomial coefficients is required to determine the binomial coefficient for any set of m and x .

Problem Analysis: The binomial coefficient can be recursively calculated as follows:

$$B(m,0) = 1$$

$$B(m,x) = B(m,x-1) \left[\frac{m-x+1}{x} \right], \quad x = 1,2,3,\dots,m$$

Further,

$$B(0,0) = 1$$

That is, the binomial coefficient is one when either x is zero or m is zero. The program in Fig.6.12 prints the table of binomial coefficients for $m = 10$. The program employs one **do** loop and one **while** loop.

Program

```
#define      MAX      10
main()
{
    int  m, x, binom;
    printf(" m x");
    for (m = 0; m <= 10 ; ++m)
        printf("%4d", m);
    printf("\n-----\n");
    m = 0;
    do
    {
        printf("%2d  ", m);
        x = 0; binom = 1;
        while (x <= m)
        {
            if(m == 0 || x == 0)
                printf("%4d", binom);
            else
            {
                binom = binom * (m - x + 1)/x;
                printf("%4d", binom);
            }
            x = x + 1;
        }
        printf("\n");
        m = m + 1;
    }
    while (m <= MAX);
    printf("-----\n");
}
```

Output

m x	0	1	2	3	4	5	6	7	8	9	10
0	1										
1	1	1									
2	1	2	1								
3	1	3	3	1							
4	1	4	6	4	1						
5	1	5	10	10	5	1					
6	1	6	15	20	15	6	1				
7	1	7	21	35	35	21	7	1			
8	1	8	28	56	70	56	28	8	1		
9	1	9	36	84	126	126	84	36	9	1	
10	1	10	45	120	210	252	210	120	45	10	1

Fig.6.12 Program to print **binomial coefficient** table

2. Histogram

Problem: In an organization, the employees are grouped according to their basic pay for the purpose of certain perks. The pay-range and the number of employees in each group are as follows:

Group	Pay-Range	Number of Employees
1	750 - 1500	12
2	1501 - 3000	23
3	3001 - 4500	35
4	4501 - 6000	20
5	above 6000	11

Draw a histogram to highlight the group sizes.

Problem Analysis: Given the size of groups, it is required to draw bars representing the sizes of various groups. For each bar, its group number and size are to be written.

Program in Fig.6.13 reads the number of employees belonging to each group and draws a histogram. The program uses four **for** loops and two **if....else** statements.

PROGRAM TO DRAW HISTOGRAM

Program:

```
#define      N      5

main()
{
    int value[N];
    int i, j, n, x;

    for (n=0; n < N; ++n)
    {
        printf("Enter employees in Group - %d : ",n+1);
        scanf("%d", &x);
        value[n] = x;
        printf("%d\n", value[n]);
    }
    printf("\n");

    printf("          |\n");
    for (n = 0 ; n < N ; ++n)
    {
        for (i = 1 ; i <= 3 ; i++)
        {
            if ( i == 2)
                printf("Group-%1d    |",n+1);
            else
                printf("          |");
        }
    }
}
```

```

        for (j = 1 ; j <= value[n]; ++j)
            printf("*");
        if (i == 2)
            printf("(%d)\n", value[n]);
        else
            printf("\n");
    }
    printf("          |\n");
}
}

```

Output

```

Enter employees in Group - 1 : 12
12
Enter employees in Group - 2 : 23
23
Enter employees in Group - 3 : 35
35
Enter employees in Group - 4 : 20
20
Enter Employees in Group - 5 : 11
11

```

```

Group-1      |
              | *****
              | ***** (12)
              | *****
              |
Group-2      | *****
              | ***** (23)
              | *****
              |
Group-3      | *****
              | ***** (35)
              | *****
              |
Group-4      | *****
              | ***** (20)
              | *****
              |
Group-5      | *****
              | ***** (11)
              | *****
              |

```

Fig.6.13 Program to draw a *histogram*

3. Minimum Cost

Problem: The cost of operation of a unit consists of two components C1 and C2 which can

be expressed as functions of a parameter p as follows:

$$\begin{aligned}C_1 &= 30 - 8p \\C_2 &= 10 + p^2\end{aligned}$$

The parameter p ranges from 0 to 10. Determine the value of p with an accuracy of ± 0.1 where the cost of operation would be minimum.

Problem Analysis:

$$\text{Total cost} = C_1 + C_2 = 40 - 8p + p^2$$

The cost is 40 when $p = 0$, and 33 when $p = 1$ and 60 when $p = 10$. The cost, therefore, decreases first and then increases. The program in Fig.6.14 evaluates the cost at successive intervals of p (in steps of 0.1) and stops when the cost begins to increase. The program employs **break** and **continue** statements to exit the loop.

PROBLEM OF **MINIMUM COST**

Program:

```
main()
{
    float p, cost, p1, cost1;

    for (p = 0; p <= 10; p = p + 0.1)
    {
        cost = 40 - 8 * p + p * p;
        if(p == 0)
        {
            cost1 = cost;
            continue;
        }
        if (cost >= cost1)
            break;
        cost1 = cost;
        p1 = p;
    }
    p = (p + p1)/2.0;
    cost = 40 - 8 * p + p * p;
    printf("\nMINIMUM COST = %.2f   AT   p = %.1f\n",
           cost, p);
}
```

Output

MINIMUM COST = 24.00 AT p = 4.0

Fig.6.14 Program of minimum cost problem

4. Plotting of Two Functions

Problem: We have two functions of the type

$$\begin{aligned}y_1 &= \exp(-ax) \\y_2 &= \exp(-ax^2/2)\end{aligned}$$

Plot the graphs of these functions for x varying from 0 to 5.0.

Problem Analysis: Initially when $x = 0$, $y_1 = y_2 = 1$ and the graphs start from the same point. The curves cross when they are again equal at $x = 2.0$. The program should have appropriate branch statements to print the graph points at the following three conditions:

1. $y_1 > y_2$
2. $y_1 < y_2$
3. $y_1 = y_2$

The functions y_1 and y_2 are normalized and converted to integers as follows:

$$y_1 = 50 \exp(-ax) + 0.5$$

$$y_2 = 50 \exp(-ax^2/2) + 0.5$$

The program in Fig.6.15 plots these two functions simultaneously. (0 for y_1 , * for y_2 , and # for the common point).

PLOTTING OF TWO FUNCTIONS

Program

```
#include    <math.h>

main()
{
    int  i;
    float  a, x, y1, y2;

    a = 0.4;
    printf("                                Y -----> \n");
    printf(" 0 -----> \n");

    for ( x = 0; x < 5; x = x+0.25)
    { /* BEGINNING OF FOR LOOP */

        /*.....Evaluation of functions .....*/
        y1 = (int) ( 50 * exp( -a * x ) + 0.5 );
        y2 = (int) ( 50 * exp( -a * x * x/2 ) + 0.5 );

        /*.....Plotting when y1 = y2.....*/
        if ( y1 == y2)
        {
            if ( x == 2.5)
                printf("  X |");
            else
                printf("    |");

            for ( i = 1; i <= y1 - 1; ++i)
                printf(" ");

            printf("#\n");
            continue;
        }

        /*..... Plotting when y1 > y2 .....*/
        if ( y1 > y2)
```

```

    {
        if ( x == 2.5 )
            printf("  X |");
        else
            printf("    |");

        for ( i = 1; i <= y2 -1 ; ++i)
            printf(" ");

        printf("*");

        for ( i = 1; i <= (y1 - y2 - 1); ++i)
            printf("-");

        printf("0\n");
        continue;
    }

/*..... Plotting when y2 > y1.....*/
    if ( x == 2.5)
        printf("  X |");
    else
        printf("    |");

    for ( i = 1 ; i <= (y1 - 1); ++i )
        printf(" ");

    printf("0");
    for ( i = 1; i <= ( y2 - y1 - 1 ); ++i)
        printf("-");

    printf("*\n");

} /*.....END OF FOR LOOP.....*/
printf("    |\n");
}

```

Output




Fig.6.15 Plotting of two functions

Example 6.1

A program to evaluate the equation

$$y = x^n$$

when n is a non-negative integer, is given in Fig.6.2

The variable **y** is initialized to 1 and then multiplied by **x**, n times using the **while** loop. The loop control variable, **count** is initialized outside the loop and incremented inside the loop. When the value of **count** becomes greater than n , the control exists the loop.

EXAMPLE OF **while** STATEMENT

Program

```
main()
{
    int count, n;
    float x, y;

    printf("Enter the values of x and n : ");
    scanf("%f %d", &x, &n);
    y = 1.0;
    count = 1;                      /* Initialisation */

    /* LOOP BEGINS */

    while ( count <= n)             /* Testing */
    {
        y = y*x;
        count++;                   /* Incrementing */
    }
    /* END OF LOOP */
    printf("\nx = %f; n = %d; x to power n = %f\n",x,n,y);
}
```

Output

```
Enter the values of x and n : 2.5 4
x = 2.500000; n = 4; x to power n = 39.062500

Enter the values of x and n : 0.5 4
x = 0.500000; n = 4; x to power n = 0.062500
```

Fig.6.2 Program to compute x to the power n using **while** loop

Example 6.2

A program to print the multiplication table from 1 x 1 to 12 x 10 as shown below is given in Fig. 6.3.

1	2	3	4	10
2	4	6	8	20
3	6	9	12	30
4				40
-					-
-					-
-					-
12	120

This program contains two **do.... while** loops in nested form. The outer loop is controlled by the variable **row** and executed 12 times. The inner loop is controlled by the variable **column** and is executed 10 times, each time the outer loop is executed. That is, the inner loop is executed a total of 120 times, each time printing a value in the table.

PRINTING OF MULTIPLICATION TABLE

Program:

```
#define COLMAX 10
#define ROWMAX 12

main()
{
    int row,column, y;

    row = 1;
    printf("          MULTIPLICATION TABLE          \n");
    printf("-----\n");
    do    /*.....OUTER LOOP BEGINS.....*/
    {
        column = 1;

        do    /*.....INNER LOOP BEGINS.....*/
        {
            y = row * column;
            printf("%4d", y);
            column = column + 1;
        }
        while (column <= COLMAX); /*... INNER LOOP ENDS ...*/

        printf("\n");
        row = row + 1;
    }
}
```

```

        while (row <= ROWMAX); /*.....    OUTER LOOP ENDS    .....*/

        printf("-----\n");
    }

```

Output

MULTIPLICATION TABLE									
1	2	3	4	5	6	7	8	9	10
2	4	6	8	10	12	14	16	18	20
3	6	9	12	15	18	21	24	27	30
4	8	12	16	20	24	28	32	36	40
5	10	15	20	25	30	35	40	45	50
6	12	18	24	30	36	42	48	54	60
7	14	21	28	35	42	49	56	63	70
8	16	24	32	40	48	56	64	72	80
9	18	27	36	45	54	63	72	81	90
10	20	30	40	50	60	70	80	90	100
11	22	33	44	55	66	77	88	99	110
12	24	36	48	60	72	84	96	108	120

Fig.6.3 Printing of a multiplication table using **do...while** loop

Example 6.3

The program in Fig.6.4 uses a **for** loop to print the "Powers of 2" table for the power 0 to 20, both positive and negative.

The program evaluates the value

$$p = 2^n$$

successively by multiplying 2 by itself n times.

$$q = 2^{-n} = \frac{1}{p}$$

Note that we have declared **p** as a **long int** and **q** as a **double**.

Additional Features of for Loop

The **for** loop in C has several capabilities that are not found in other loop constructs. For example, more than one variable can be initialized at a time in the **for** statement. The statements

```

p = 1;
for (n=0; n<17; ++n)

```

can be rewritten as

```

for (p=1, n=0; n<17; ++n)

```

Program:

```
main()
{
    long int p;
    int      n;
    double   q;
    printf("-----\n");
    printf(" 2 to power n      n      2 to power -n\n");
    printf("-----\n");
    p = 1;
    for (n = 0; n < 21 ; ++n)      /* LOOP BEGINS */
    {
        if (n == 0)
            p = 1;
        else
            p = p * 2;
        q = 1.0/(double)p ;
        printf("%10ld %10d %20.12lf\n", p, n, q);
    }
    /* LOOP ENDS */
    printf("-----\n");
}
```

Output

2 to power n	n	2 to power -n
1	0	1.000000000000
2	1	0.500000000000
4	2	0.250000000000
8	3	0.125000000000
16	4	0.062500000000
32	5	0.031250000000
64	6	0.015625000000
128	7	0.007812500000
256	8	0.003906250000
512	9	0.001953125000
1024	10	0.000976562500
2048	11	0.000488281250
4096	12	0.000244140625
8192	13	0.000122070313
16384	14	0.000061035156
32768	15	0.000030517578
65536	16	0.000015258789
131072	17	0.000007629395
262144	18	0.000003814697
524288	19	0.000001907349
1048576	20	0.000000953674

Fig.6.4 Program to print 'Power of 2' table using for loop

Example 6.4

A class of **n** students take an annual examination in **m** subjects. A program to read the marks obtained by each student in various subjects and to compute and print the total marks obtained by each of them is given in Fig.6.5.

The program uses two **for** loops, one for controlling the number of students and the other for controlling the number of subjects. Since both the number of students and the number of subjects are requested by the program, the program may be used for a class of any size and any number of subjects.

The outer loop includes three parts:

- (1) reading of roll-numbers of students, one after another,
- (2) inner loop, where the marks are read and totaled for each student, and
- (3) printing of total marks and declaration of grades.

ILLUSTRATION OF **NESTED** LOOPS

Program

```
#define FIRST    360
#define SECOND   240
main()
{
    int n, m, i, j,
        roll_number, marks, total;

    printf("Enter number of students and subjects\n");
    scanf("%d %d", &n, &m);
    printf("\n");

    for (i = 1; i <= n ; ++i)
    {
        printf("Enter roll_number : ");
        scanf("%d", &roll_number);
        total = 0 ;

        printf("\nEnter marks of %d subjects for ROLL NO %d\n",
            m, roll_number);
        for (j = 1; j <= m; j++)
        {
            scanf("%d", &marks);
            total = total + marks;
```

```

    }
    printf("TOTAL MARKS = %d ", total);
    if (total >= FIRST)
        printf("( First Division )\n\n");
    else if (total >= SECOND)
        printf("( Second Division )\n\n");
    else
        printf("( *** F A I L *** )\n\n");
}
}

```

Output

```

Enter number of students and subjects
3      6
Enter roll_number : 8701
Enter marks of 6 subjects for ROLL NO 8701
81  75  83  45  61  59
TOTAL MARKS = 404 ( First Division )

Enter roll_number : 8702
Enter marks of 6 subjects for ROLL NO 8702
51  49  55  47  65  41
TOTAL MARKS = 308 ( Second Division )

Enter roll_number : 8704
Enter marks of 6 subjects for ROLL NO 8704
40  19  31  47  39  25
TOTAL MARKS = 201 ( *** F A I L *** )

```

Fig.6.5 Illustration of nested for loops

Example 6.5

The program in Fig.6.8 illustrates the use of the break statement in a C program.

The program reads a list of positive values and calculates their average. The **for** loop is written to read 1000 values. However, if we want the program to calculate the average of any set of values less than 1000, then we must enter a 'negative' number after the last value in the list, to mark the end of input.

USE OF **break** IN A PROGRAM

Program

```
main()
{
    int m;
    float x, sum, average;

    printf("This program computes the average of a
           set of numbers\n");
    printf("Enter values one after another\n");
    printf("Enter a NEGATIVE number at the end.\n\n");
    sum = 0;
    for (m = 1 ; m <= 1000 ; ++m)
    {
        scanf("%f", &x);
        if (x < 0)
            break;
        sum += x ;
    }

    average = sum/(float) (m-1);
    printf("\n");
    printf("Number of values = %d\n", m-1);
    printf("Sum                = %f\n", sum);
    printf("Average           = %f\n", average);
}
```

Output

```
This program computes the average of a set of numbers
Enter values one after another
Enter a NEGATIVE number at the end.

21  23  24  22  26  22  -1

Number of values = 6
Sum              = 138.000000
Average          = 23.000000
```

Fig.6.8 Use of **break** in a program

Example 6.6

A program to evaluate the series

$$\frac{1}{1-x} = 1 + x + x^2 + x^3 + \dots + x^n$$

for $-1 < x < 1$ with 0.01 per cent accuracy is given in Fig.6.9. The **goto** statement is used to exit the loop on achieving the desired accuracy.

We have used the **for** statement to perform the repeated addition of each of the terms in the series. Since it is an infinite series, the evaluation of the function is terminated when the term x^n reaches the desired accuracy. The value of n that decides the number of loop operations is not known and therefore we have decided arbitrarily a value of 100, which may or may not result in the desired level of accuracy.

EXAMPLE OF **exit** WITH **goto** STATEMENT

Program

```
#define    LOOP        100
#define    ACCURACY    0.0001
main()
{
    int n;
    float x, term, sum;

    printf("Input value of x : ");
    scanf("%f", &x);
    sum = 0 ;
    for (term = 1, n = 1 ; n <= LOOP ; ++n)
    {
        sum += term ;
        if (term <= ACCURACY)
            goto output; /* EXIT FROM THE LOOP */
        term *= x ;
    }
    printf("\nFINAL VALUE OF N IS NOT SUFFICIENT\n");
    printf("TO ACHIEVE DESIRED ACCURACY\n");
    goto end;
output:
    printf("\nEXIT FROM LOOP\n");
    printf("Sum = %f;  No.of terms = %d\n", sum, n);
end:
    ;          /* Null Statement */
}
```

Output

```
Input value of x : .21
EXIT FROM LOOP
Sum = 1.265800;  No.of terms = 7

Input value of x : .75
EXIT FROM LOOP
Sum = 3.999774;  No.of terms = 34

Input value of x : .99
FINAL VALUE OF N IS NOT SUFFICIENT
TO ACHIEVE DESIRED ACCURACY
```

Fig.6.9 Use of **goto** to exit from a loop

Example 6.7

The program in Fig.6.11 illustrates the use of **continue** statement.

The program evaluates the square root of a series of numbers and prints the results. The process stops when the number 9999 is typed in.

In case, the series contains any negative numbers, the process of evaluation of square root should be bypassed for such numbers because the square root of a negative number is not defined. The **continue** statement is used to achieve this. The program also prints a message saying that the number is negative and keeps an account of negative numbers.

The final output includes the number of positive values evaluated and the number of negative items encountered.

USE OF **continue** STATEMENT

Program:

```
#include <math.h>

main()
{
    int count, negative;
    double number, sqroot;

    printf("Enter 9999 to STOP\n");
    count = 0 ;
    negative = 0 ;

    while (count <= 100)
    {
        printf("Enter a number : ");
        scanf("%lf", &number);
```

```

        if (number == 9999)
            break;          /* EXIT FROM THE LOOP */
        if (number < 0)
        {
            printf("Number is negative\n\n");
            negative++;
            continue;    /* SKIP REST OF THE LOOP */
        }
        sqroot = sqrt(number);
        printf("Number          = %lf\n Square root = %lf\n\n",
               number, sqroot);

        count++;
    }
    printf("Number of items done = %d\n", count);
    printf("\n\nNegative items      = %d\n", negative);
    printf("END OF DATA\n");
}

```

Output

```

Enter 9999 to STOP
Enter a number : 25.0
Number          = 25.000000
Square root = 5.000000

```

```

Enter a number : 40.5
Number          = 40.500000
Square root = 6.363961

```

```

Enter a number : -9
Number is negative

```

```

Enter a number : 16
Number          = 16.000000
Square root = 4.000000

```

```

Enter a number : -14.75
Number is negative

```

```

Enter a number : 80
Number          = 80.000000
Square root = 8.944272

```

```
Enter a number : 9999  
Number of items done = 4  
Negative items      = 2  
END OF DATA
```

Fig.6.11 Use of `continue` statement

CASE STUDIES

7.1. Median of a List of Numbers

When all the items in a list are arranged in order, the middle value which divides the items into two parts with equal number of items on either side is called the median. Odd number of items have just one middle value while even number of items have two middle values. The median for even number of items is therefore designated as the average of the two middle values.


The major steps for finding the median are as follows:


1. Read the items into an array while keeping a count of the items.
2. Sort the items in increasing order.
3. Compute median.

The program and sample output are shown in Fig.7.7. The sorting algorithm used is as follows:

1. Compare the first two elements in the list, say $a[1]$, and $a[2]$. If $a[2]$ is smaller than $a[1]$, then interchange their values.
2. Compare $a[2]$ and $a[3]$; interchange them if $a[3]$ is smaller than $a[2]$.
3. Continue this process till the last two elements are compared and interchanged.
4. Repeat the above steps $n-1$ times.

In repeated trips through the array, the smallest elements 'bubble up' to the top. Because of this bubbling up effect, this algorithm is called bubble sorting. The bubbling effect is illustrated below for four items.





During the first trip, three pairs of items are compared and interchanged whenever needed. It should be noted that the number 80, the largest among the items, has been moved to the bottom at the end of the first trip. This means that the element 80 (the last item in the new list) need not be considered any further. Therefore, trip-2 requires only two pairs to be compared. This time, the number 65 (the second largest value) has been moved down the list. Notice that each trip brings the smallest value 10 up by one level.

The number of steps required in a trip is reduced by one for each trip made. The entire process will be over when a trip contains only one step. If the list contains n elements, then the number of comparisons involved would be $n(n-1)/2$.

PROGRAM TO SORT A LIST AND FIND ITS MEDIAN

Program

```
#define N 10

main( )
{
    int i,j,n;
    float median,a[N],t;

    printf("Enter the number of items\n");
    scanf("%d", &n);

    /* Reading items into array a */

    printf("Input %d values \n",n);
    for (i = 1; i <= n ; i++)
        scanf("%f", &a[i]);

    /* Sorting begins */
    for (i = 1 ; i <= n-1 ; i++)
    {
        /* Trip-i begins */
```

```

        for (j = 1 ; j <= n-i ; j++)
        {
            if (a[j] <= a[j+1])
            { /* Interchanging values */
                t = a[j];
                a[j] = a[j+1];
                a[j+1] = t;
            }
            else
                continue ;
        }
    } /* sorting ends */

    /* calculation of median */

    if ( n % 2 == 0)
        median = (a[n/2] + a[n/2+1])/2.0 ;
    else
        median = a[n/2 + 1];

    /* Printing */

    for (i = 1 ; i <= n ; i++)
        printf("%f ", a[i]);
    printf("\n\nMedian is %f\n", median);
}

```

Output

```

Enter the number of items
5
Input 5 values
1.111  2.222  3.333  4.444  5.555
5.555000  4.444000  3.333000  2.222000  1.111000

Median is 3.333000

Enter the number of items
6
Input 6 values
3  5  8  9  4  6
9.000000  8.000000  6.000000  5.000000  4.000000  3.000000

Median is 5.500000

```

Fig.7.7 Program to sort a list of numbers and to determine median

2. Calculation of Standard Deviation

In statistics, standard deviation is used to measure deviation of data from its mean. The formula for calculating standard deviation of n items is

$$s = \sqrt{\text{variance}}$$

where

$$\text{variance} = \frac{1}{n} \sum_{i=1}^n (x_i - m)^2$$

and

$$m = \text{mean} = \frac{1}{n} \sum_{i=1}^n x_i$$

The algorithm for calculating the standard deviation is as follows:

1. Read n items.
2. Calculate sum and mean of the items.
3. Calculate variance.
4. Calculate standard deviation.

Complete program with sample output is shown in Fig.7.8.

PROGRAM TO CALCULATE STANDARD DEVIATION

Program

```
#include <math.h>
#define MAXSIZE 100

main( )
{
    int i,n;
    float value [MAXSIZE], deviation,
          sum,sumsqr,mean,variance,stddeviation;

    sum = sumsqr = n = 0 ;

    printf("Input values: input -1 to end \n");
    for (i=1; i< MAXSIZE ; i++)
    {
        scanf("%f", &value[i]);
        if (value[i] == -1)
            break;
        sum += value[i];
        n += 1;
    }
    mean = sum/(float)n;

    for (i = 1 ; i<= n; i++)
```

```

    {
        deviation = value[i] - mean;
        sumsqr += deviation * deviation;
    }
    variance = sumsqr/(float)n ;
    stddeviation = sqrt(variance) ;

    printf("\nNumber of items : %d\n",n);
    printf("Mean : %f\n", mean);
    printf("Standard deviation : %f\n", stddeviation);
}

```

Output

```

Input values: input -1 to end
65 9 27 78 12 20 33 49 -1

Number of items : 8
Mean : 36.625000
Standard deviation : 23.510303

```

Fig 7.8 Program to calculate standard deviation

3. Evaluating a Test

A test consisting of 25 multiple-choice items is administered to a batch of 3 students. Correct answers and student responses are tabulated as shown below:

		Items																										
		1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5		
Correct	answers																											
Student 1																												
Student 2																												
Student 3																												

The algorithm for evaluating the answers of students is as follows:

1. Read correct answers into an array.
2. Read the responses of a student and count the correct ones.
3. Repeat step-2 for each student.
4. Print the results.

A program to implement this algorithm is given in Fig.7.9. The program uses the following arrays:

```

key[i]      - To store correct answers of items
response[i] - To store responses of students
correct[i]  - To identify items that are answered correctly.

```

PROGRAM TO EVALUATE A MULTIPLE-CHOICE TEST

Program

```
#define      STUDENTS      3
#define      ITEMS        25
main( )
{
    char  key[ITEMS+1],response[ITEMS+1];
    int   count, i, student,n,
          correct[ITEMS+1];

    /*  Reading of Correct answers */
    printf("Input key to the items\n");

    for(i=0; i < ITEMS; i++)
        scanf("%c",&key[i]);

    scanf("%c",&key[i]);
    key[i] = '\0';

    /*  Evaluation begins  */

    for(student = 1; student <= STUDENTS ; student++)
    {
        /*Reading student responses and counting correct ones*/
        count = 0;
        printf("\n");
        printf("Input responses of student-%d\n",student);

        for(i=0; i < ITEMS ; i++)
            scanf("%c",&response[i]);
        scanf("%c",&response[i]);
        response[i] = '\0';

        for(i=0; i < ITEMS; i++)
            correct[i] = 0;

        for(i=0; i < ITEMS ; i++)
            if(response[i] == key[i])
            {
                count = count +1 ;
                correct[i] = 1 ;
            }

        /* printing of results */

        printf("\n");
        printf("Student-%d\n", student);
        printf("Score is %d out of %d\n",count, ITEMS);
        printf("Response to the items below are wrong\n");

        n = 0;
        for(i=0; i < ITEMS ; i++)
```

```

        if(correct[i] == 0)
        {
            printf("%d ",i+1);
            n = n+1;
        }
        if(n == 0)
            printf("NIL\n");
        printf("\n");

    } /* Go to next student */

/* Evaluation and printing ends */
}

```

Output

Input key to the items
abcdabcdabcdabcdabcd

Input responses of student-1
abcdabcdabcdabcdabcd

Student-1
Score is 25 out of 25
Response to the following items are wrong
NIL

Input responses of student-2
abcdcdcaabcdabcd

Student-2
Score is 14 out of 25
Response to the following items are wrong
5 6 7 8 17 18 19 21 22 23 25

Input responses of student-3
aaaaaaaaaaaaaaaaaaaa

Student-3
Score is 7 out of 25
Response to the following items are wrong
2 3 4 6 7 8 10 11 12 14 15 16 18 19 20 22 23 24

Fig 7.9 Program to evaluate responses to a multiple-choice test

4. Production and Sales Analysis

A company manufactures five categories of products and the number of items manufactured and sold are recorded product-wise every week in a month. The company reviews its production schedule at every month-end. The review may require one or more of the following information:

- (a) Value of weekly production and sales.
- (b) Total value of all the products manufactured.
- (c) Total value of all the products sold.
- (d) Total value of each product, manufactured and sold.

Let us represent the products manufactured and sold by two two-dimensional arrays M and S respectively. Then,

M11	M12	M13	M14	M15
M21	M22	M23	M24	M25
M31	M32	M33	M34	M35
M41	M42	M43	M44	M45

M =

S11	S12	S13	S14	S15
S21	S22	S23	S24	S25
S31	S32	S33	S34	S35
S41	S42	S43	S44	S45

S =

where M_{ij} represents the number of j th type product manufactured in i th week and S_{ij} the number of j th product sold in i th week. We may also represent the cost of each product by a single dimensional array C as follows:

C1	C2	C3	C4	C5
----	----	----	----	----

C =

where C_j is the cost of j^{th} type product.

We shall represent the value of products manufactured and sold by two value arrays, namely, **Mvalue** and **Svalue**. Then,

$$\begin{aligned} \text{Mvalue}[i][j] &= M_{ij} \times C_j \\ \text{Svalue}[i][j] &= S_{ij} \times C_j \end{aligned}$$

A program to generate the required outputs for the review meeting is shown in Fig.7.10. The following additional variables are used:

$\text{Mweek}[i]$ = Value of all the products manufactured in week i .

$$= \sum_{j=1}^5 \text{Mvalue}[i][j]$$

$\text{Sweek}[i]$ = Value of all the products sold in week i

$$= \sum_{j=1}^5 \text{Svalue}[i][j]$$

$\text{Mproduct}[j]$ = Value of j th type product manufactured during the month

$$= \sum_{i=1}^4 \text{Mvalue}[i][j]$$

$\text{Sproduct}[j]$ = Value of j th type product sold during the month

$$= \sum_{i=1}^4 \text{Svalue}[i][j]$$

Mtotal = Total value of all the products sold during the month

$$= \sum_{i=1}^4 \text{Mweek}[i] = \sum_{j=1}^5 \text{Mproduct}[j]$$

Stotal = Total value of all the products sold during the month

$$= \sum_{i=1}^4 \text{Sweek}[i] = \sum_{j=1}^5 \text{Sproduct}[j]$$

Program

```

main( )
{
    int M[5][6],S[5][6],C[6],
        Mvalue[5][6],Svalue[5][6],
        Mweek[5], Sweek[5],
        Mproduct[6], Sproduct[6],
        Mtotal, Stotal, i,j,number;

    /*      Input data      */

    printf (" Enter products manufactured week_wise \n");
    printf (" M11,M12,----,  M21,M22,----  etc\n");

    for(i=1; i<=4; i++)
        for(j=1;j<=5; j++)
            scanf("%d",&M[i][j]);

    printf (" Enter products sold week_wise\n");
    printf (" S11,S12,----,  S21,S22,----  etc\n");

    for(i=1; i<=4; i++)
        for(j=1; j<=5; j++)
            scanf("%d", &S[i][j]);

    printf(" Enter cost of each product\n");
    for(j=1; j <=5; j++)
        scanf("%d",&C[j]);

    /* Value matrices of production and sales */
    for(i=1; i<=4; i++)
        for(j=1; j<=5; j++)
        {
            Mvalue[i][j] = M[i][j] * C[j];
            Svalue[i][j] = S[i][j] * C[j];
        }

    /* Total value of weekly production and sales */
    for(i=1; i<=4; i++)
    {
        Mweek[i] = 0 ;
        Sweek[i] = 0 ;
        for(j=1; j<=5; j++)
        {
            Mweek[i] += Mvalue[i][j];
            Sweek[i] += Svalue[i][j];
        }
    }
}

```

```

/* Monthly value of product_wise production and sales */
for(j=1; j<=5; j++)
{
    Mproduct[j] = 0 ;
    Sproduct[j] = 0 ;
    for(i=1; i<=4; i++)
    {
        Mproduct[j] += Mvalue[i][j];
        Sproduct[j] += Svalue[i][j];
    }
}

/* Grand total of production and sales values */

Mtotal = Stotal = 0;
for(i=1; i<=4; i++)
{
    Mtotal += Mweek[i];
    Stotal += Sweek[i];
}

/*****
Selection and printing of information required
*****/
printf("\n\n");
printf(" Following is the list of things you can\n");
printf(" request for. Enter appropriate item number\n");
printf(" and press RETURN Key\n\n");

printf(" 1.Value matrices of production & sales\n");

printf(" 2.Total value of weekly production & sales\n");

printf(" 3.Product_wise monthly value of production &");
printf(" sales\n");

printf(" 4.Grand total value of production & sales\n");

printf(" 5.Exit\n");

number = 0;
while(1)
{
    /* Beginning of while loop */
    printf("\n\n ENTER YOUR CHOICE:");
    scanf("%d",&number);
    printf("\n");
}

```

```

if(number == 5)
{
    printf(" G O O D   B Y E\n\n");
    break;
}

switch(number)
{ /* Beginning of switch */

```

```

/*      V A L U E      M A T R I C E S      */

```

```

case 1:
    printf(" VALUE MATRIX OF PRODUCTION\n\n");
    for(i=1; i<=4; i++)
    {
        printf(" Week(%d)\t",i);
        for(j=1; j <=5; j++)
            printf("%7d", Mvalue[i][j]);
        printf("\n");
    }
    printf("\n VALUE MATRIX OF SALES\n\n");
    for(i=1; i <=4; i++)
    {
        printf(" Week(%d)\t",i);
        for(j=1; j <=5; j++)
            printf("%7d", Svalue[i][j]);
        printf("\n");
    }
    break;

```

```

/*      W E E K L Y      A N A L Y S I S      */

```

```

case 2:
    printf(" TOTAL WEEKLY PRODUCTION & SALES\n\n");
    printf("                PRODUCTION    SALES\n");
    printf("                -----    ----- \n");
    for(i=1; i <=4; i++)
    {
        printf(" Week(%d)\t", i);
        printf("%7d\t%7d\n", Mweek[i], Sweek[i]);
    }
    break;

```

```

/*      P R O D U C T W I S E      A N A L Y S I S      */

    case 3:
        printf(" PRODUCT_WISE TOTAL PRODUCTION &");
        printf(" SALES\n\n");
        printf("          PRODUCTION    SALES\n");
        printf("          -----    -----");
        for(j=1; j <=5; j++)
        {
            printf(" Product(%d)\t", j);
            printf("%7d\t%7d\n",Mproduct[j],Sproduct[j]);
        }
        break;

/*      G R A N D      T O T A L S      */

    case 4:
        printf(" GRAND TOTAL OF PRODUCTION & SALES\n");
        printf("\n Total production = %d\n", Mtotal);
        printf(" Total sales      = %d\n", Stotal);
        break;

/*      D E F A U L T      */

    default :
        printf(" Wrong choice, select again\n\n");
        break;

    } /* End of switch */

} /* End of while loop */

printf(" Exit from the program\n\n");

} /* End of main */

```

Output

```
Enter products manufactured week_wise
M11,M12,----, M21,M22,---- etc
11 15 12 14 13
13 13 14 15 12
12 16 10 15 14
14 11 15 13 12
```

```
Enter products sold week_wise
S11,S12,----, S21,S22,---- etc
10 13 9 12 11
12 10 12 14 10
11 14 10 14 12
12 10 13 11 10
Enter cost of each product
10 20 30 15 25
```

Following is the list of things you can request for. Enter appropriate item number and press RETURN key

- 1.Value matrices of production & sales
- 2.Total value of weekly production & sales
- 3.Product_wise monthly value of production & sales
- 4.Grand total value of production & sales
- 5.Exit

ENTER YOUR CHOICE:1

VALUE MATRIX OF PRODUCTION

Week(1)	110	300	360	210	325
Week(2)	130	260	420	225	300
Week(3)	120	320	300	225	350
Week(4)	140	220	450	185	300

VALUE MATRIX OF SALES

Week(1)	100	260	270	180	275
Week(2)	120	200	360	210	250
Week(3)	110	280	300	210	300
Week(4)	120	200	390	165	250

ENTER YOUR CHOICE:2

TOTAL WEEKLY PRODUCTION & SALES

	PRODUCTION	SALES
	-----	-----
Week(1)	1305	1085
Week(2)	1335	1140
Week(3)	1315	1200
Week(4)	1305	1125

ENTER YOUR CHOICE:3

PRODUCT_WISE TOTAL PRODUCTION & SALES

	PRODUCTION	SALES
	-----	-----
Product (1)	500	450
Product (2)	1100	940
Product (3)	1530	1320
Product (4)	855	765
Product (5)	1275	1075

ENTER YOUR CHOICE:4

GRAND TOTAL OF PRODUCTION & SALES

Total production = 5260

Total sales = 4550

ENTER YOUR CHOICE:5

G O O D B Y E

Exit from the program

Fig.7.10 Program for production and sales analysis

Example 7.1

Write a program using a single-subscripted variable to evaluate the following expressions:

$$\text{Total} = \sum_{i=1}^{10} x_i^2$$

The values of x1,x2,...are read from the terminal.

Program in Fig.7.1 uses a one-dimensional array **x** to read the values and compute the sum of their squares.

PROGRAM SHOWING ONE-DIMENSIONAL ARRAY

Program :

```
main()
{
    int    i ;
    float  x[10], value, total ;

    /* . . . . .READING VALUES INTO ARRAY . . . . . */

    printf("ENTER 10 REAL NUMBERS\n") ;

    for( i = 0 ; i < 10 ; i++ )
    {
        scanf("%f", &value) ;
        x[i] = value ;
    }

    /* . . . . . .COMPUTATION OF TOTAL . . . . . */

    total = 0.0 ;
    for( i = 0 ; i < 10 ; i++ )
        total = total + x[i] * x[i] ;

    /*. . . . PRINTING OF x[i] VALUES AND TOTAL . . . */

    printf("\n");
    for( i = 0 ; i < 10 ; i++ )
        printf("x[%2d] = %5.2f\n", i+1, x[i]) ;

    printf("\ntotal = %.2f\n", total) ;
}
```

Output

```
ENTER 10 REAL NUMBERS
1.1  2.2  3.3  4.4  5.5  6.6  7.7  8.8  9.9  10.10
```

```

x[ 1] = 1.10
x[ 2] = 2.20
x[ 3] = 3.30
x[ 4] = 4.40
x[ 5] = 5.50
x[ 6] = 6.60
x[ 7] = 7.70
x[ 8] = 8.80
x[ 9] = 9.90
x[10] = 10.10

```

```
Total = 446.86
```

Fig.7.1 Program to illustrate **one-dimensional array**

Example 7.2

Given below is the list of marks obtained by a class of 50 students in an annual examination.

```

43 65 51 27 79 11 56 61 82 09 25 36 07 49 55 63 74 81 49 37
40 49 16 75 87 91 33 24 58 78 65 56 76 67 45 54 36 63 12 21
73 49 51 19 39 49 68 93 85 59

```

Write a program to count the number of students belonging to each of following groups of marks: 0-9, 10-19, 20-29,.....,100.

The program coded in Fig.7.2 uses the array **group** containing 11 elements, one for each range of marks. Each element counts those values falling within the range of values it represents.

For any value, we can determine the correct group element by dividing the value by 10. For example, consider the value 59. The integer division of 59 by 10 yields 5. This is the element into which 59 is counted.

PROGRAM FOR **FREQUENCY COUNTING**

Program

```

#define    MAXVAL    50
#define    COUNTER    11

main()
{
    float    value[MAXVAL];
    int      i, low, high;
    int      group[COUNTER] = {0,0,0,0,0,0,0,0,0,0,0,0};

    /* . . . . .READING AND COUNTING . . . . . */
    for( i = 0 ; i < MAXVAL ; i++ )
    {
        /*. . . . .READING OF VALUES . . . . . */
        scanf("%f", &value[i]) ;

        /*. . . . .COUNTING FREQUENCY OF GROUPS. . . . . */

```



```

        ++ group[ (int) ( value[i] + 0.5 ) / 10] ;
    }

    /* . . . .PRINTING OF FREQUENCY TABLE . . . . . */
    printf("\n");
    printf(" GROUP      RANGE      FREQUENCY\n\n") ;
    for( i = 0 ; i < COUNTER ; i++ )
    {
        low  = i * 10 ;
        if(i == 10)
            high = 100 ;
        else
            high = low + 9 ;
        printf("   %2d      %3d to %3d          %d\n",
               i+1, low, high, group[i] ) ;
    }
}

```

Output

```

43 65 51 27 79 11 56 61 82 09 25 36 07 49 55 63 74
81 49 37 40 49 16 75 87 91 33 24 58 78 65 56 76 67
45 54 36 63 12 21 73 49 51 19 39 49 68 93 85 59

```

(Input data)

GROUP	RANGE			FREQUENCY
1	0	to	9	2
2	10	to	19	4
3	20	to	29	4
4	30	to	39	5
5	40	to	49	8
6	50	to	59	8
7	60	to	69	7
8	70	to	79	6
9	80	to	89	4
10	90	to	99	2
11	100	to	100	0

Fig.7.2 Program for frequency counting

Example 7.3

Write a program using a two-dimensional array to compute and print the following information from the table of data discussed above:

- Total value of sales by each girl.
- Total value of each item sold.
- Grand total of sales of all items by all girls.

The program and its output are shown in Fig.7.4. The program uses the variable **value** in two-dimensions with the index *i* representing girls and *j* representing items. The following equations are used in computing the results:

$$\begin{aligned}
 \text{(a) Total sales by } m^{\text{th}} \text{ girl} &= \sum_{j=0}^2 \text{value}[m][j] \\
 &\text{(girl_total}[m]) \\
 \text{(b) Total value of } n^{\text{th}} \text{ item} &= \sum_{i=0}^3 \text{value}[i][n] \\
 &\text{(item_total}[n]) \\
 \text{(c) Grand total} &= \sum_{i=0}^3 \sum_{j=0}^2 \text{value}[i][j] \\
 &= \sum_{i=0}^3 \text{girl_total}[i] \\
 &= \sum_{j=0}^2 \text{item_total}[j]
 \end{aligned}$$

PROGRAM SHOWING TWO-DIMENSIONAL ARRAYS

Program:

```

#define      MAXGIRLS      4
#define      MAXITEMS      3

main()
{
    int    value[MAXGIRLS][MAXITEMS];
    int    girl_total[MAXGIRLS] , item_total[MAXITEMS];
    int    i, j, grand_total;

    /*.....READING OF VALUES AND COMPUTING girl_total ...*/

    printf("Input data\n");
    printf("Enter values, one at a time, row-wise\n\n");

    for( i = 0 ; i < MAXGIRLS ; i++ )
    {
        girl_total[i] = 0;
        for( j = 0 ; j < MAXITEMS ; j++ )
        {
            scanf("%d", &value[i][j]);
            girl_total[i] = girl_total[i] + value[i][j];
        }
    }

    /*.....COMPUTING item_total.....*/

    for( j = 0 ; j < MAXITEMS ; j++ )

```

```

    {
        item_total[j] = 0;
        for( i =0 ; i < MAXGIRLS ; i++ )
            item_total[j] = item_total[j] + value[i][j];
    }

/*.....COMPUTING grand_total.....*/

    grand_total = 0;
    for( i =0 ; i < MAXGIRLS ; i++ )
        grand_total = grand_total + girl_total[i];

/* .....PRINTING OF RESULTS.....*/

    printf("\n GIRLS TOTALS\n\n");
    for( i = 0 ; i < MAXGIRLS ; i++ )
        printf("Salesgirl[%d] = %d\n", i+1, girl_total[i] );
    printf("\n ITEM  TOTALS\n\n");
    for( j = 0 ; j < MAXITEMS ; j++ )
        printf("Item[%d] = %d\n", j+1 , item_total[j] );
    printf("\nGrand Total = %d\n", grand_total);
}

```

Output

Input data
Enter values, one at a time, row_wise

```

310  257  365
210  190  325
405  235  240
260  300  380

```

GIRLS TOTALS

```

Salesgirl[1] = 950
Salesgirl[2] = 725
Salesgirl[3] = 880
Salesgirl[4] = 940

```

ITEM TOTALS

```

Item[1] = 1185
Item[2] = 1000
Item[3] = 1310

```

Grand Total = 3495

Fig.7.4 Illustration of two-dimensional arrays.

Example 7.4

Write a program to compute and print a multiplication table for numbers 1 to 5 as shown below:

	1	2	3	4	5
1	1	2	3	4	5
2	2	4	6	8	10
3	3	6	.	.	.
4	4	8	.	.	.
5	5	10	.	.	25

The program shown in Fig.7.5 uses a two-dimensional array to store the table values. Each value is calculated using the control variables of the nested for loops as follows:

product(i,j) = row * column

where i denotes rows and j denotes columns of the product table. Since the indices i and j ranges from 0 to 4, we have introduced the following transformation:

row = i+1
column = j+1

PROGRAM TO PRINT MULTIPLICATION TABLE

Program:

```
#define    ROWS      5
#define    COLUMNS  5

main()
{
    int    row, column, product[ROWS][COLUMNS] ;
    int    i, j ;

    printf("    MULTIPLICATION TABLE\n\n") ;
    printf("    ") ;

    for( j = 1 ; j <= COLUMNS ; j++ )
        printf("%4d" , j ) ;
    printf("\n") ;
    printf("-----\n");
    for( i = 0 ; i < ROWS ; i++ )
    {
        row = i + 1 ;
        printf("%2d |", row) ;
        for( j = 1 ; j <= COLUMNS ; j++ )
        {
            column = j ;
            product[i][j] = row * column ;
            printf("%4d", product[i][j] ) ;
        }
        printf("\n") ;
    }
}
```

Output

MULTIPLICATION TABLE					
	1	2	3	4	5
1	1	2	3	4	5
2	2	4	6	8	10
3	3	6	9	12	15
4	4	8	12	16	20
5	5	10	15	20	25

Fig.7.5 Program to print multiplication table using two-dimensional array

Example 7.5

A survey to know the popularity of four cars (Ambassador, Fiat, Dolphin and Maruti) was conducted in four cities (Bombay, Calcutta, Delhi and Madras). Each person surveyed was asked to give his city and the type of car he was using. The results, in coded form, are tabulated as follows:

M	1	C	2	B	1	D	3	M	2	B	4	
C		1	D	3	M	4	B	2	D	1	C	3
D		4	D	4	M	1	M	1	B	3	B	3
C		1	C	1	C	2	M	4	M	4	C	2
D		1	C	2	B	3	M	1	B	1	C	2
D		3	M	4	C	1	D	2	M	3	B	4

Codes represent the following information:

M - Madras	1 - Ambassador
D - Delhi	2 - Fiat
C - Calcutta	3 - Dolphin
B - Bombay	4 - Maruti

Write a program to produce a table showing popularity of various cars in four cities.

A two-dimensional array **frequency** is used as an accumulator to store the number of cars used, under various categories in each city. For example, the element **frequency** [i][j] denotes the number of cars of type j used in city i. The **frequency** is declared as an array of size 5x5 and all the elements are initialized to zero.

The program shown in fig.7.6 reads the city code and the car code, one set after another, from the terminal. Tabulation ends when the letter X is read in place of a city code.

PROGRAM TO TABULATE SURVEY DATA

Program

```
main()
{
    int i, j, car;
    int frequency[5][5] = { {0},{0},{0},{0},{0} };
```

```

char city;

printf("For each person, enter the city code \n");
printf("followed by the car code.\n");
printf("Enter the letter X to indicate end.\n");

/* . . . . . TABULATION BEGINS . . . . . */

for( i = 1 ; i < 100 ; i++ )
{
    scanf("%c", &city );
    if( city == 'X' )
        break;

    scanf("%d", &car );

    switch(city)
    {

        case 'B' : frequency[1][car]++;
                    break;
        case 'C' : frequency[2][car]++;
                    break;
        case 'D' : frequency[3][car]++;
                    break;
        case 'M' : frequency[4][car]++;
                    break;

    }
}

/* . . . . .TABULATION COMPLETED AND PRINTING BEGINS. . . .*/

printf("\n\n");
printf("                POPULARITY  TABLE\n\n");
printf("-----\n");
printf("City      Ambassador  Fiat  Dolphin  Maruti \n");
printf("-----\n");
for( i = 1 ; i <= 4 ; i++ )
{

```

```

switch(i)
{
    case 1 : printf("Bombay    ") ;
              break ;
    case 2 : printf("Calcutta  ") ;
              break ;
    case 3 : printf("Delhi     ") ;
              break ;
    case 4 : printf("Madras    ") ;
              break ;
}
for( j = 1 ; j <= 4 ; j++ )
    printf("%7d", frequency[i][j] ) ;
printf("\n") ;
}
printf("-----\n");
/* . . . . . PRINTING ENDS. . . . . */
}

```

Output

For each person, enter the city code
followed by the car code.
Enter the letter X to indicate end.

```

M 1 C 2 B 1 D 3 M 2 B 4
C 1 D 3 M 4 B 2 D 1 C 3
D 4 D 4 M 1 M 1 B 3 B 3
C 1 C 1 C 2 M 4 M 4 C 2
D 1 C 2 B 3 M 1 B 1 C 2
D 3 M 4 C 1 D 2 M 3 B 4  X

```

POPULARITY TABLE				
City	Ambassador	Fiat	Dolphin	Maruti
Bombay	2	1	3	2
Calcutta	4	5	1	0
Delhi	2	1	3	2
Madras	4	1	1	4

Fig.7.6 Program to tabulate a survey data

CASE STUDIES

1. Counting Words in a Text

One of the practical applications of string manipulations is counting the words in a text. We assume that a word is a sequence of any characters, except escape characters and blanks, and that two words are separated by one blank character. The algorithm for counting words is as follows:

1. Read a line of text.
2. Beginning from the first character in the line, look for a blank. If a blank is found, increment words by 1.
3. Continue steps 1 and 2 until the last line is completed.

The implementation of this algorithm is shown in Fig.8.11. The first **while** loop will be executed once for each line of text. The end of text is indicated by pressing the 'Return' key an extra time after the entire text has been entered. The extra 'Return' key causes a newline character as input to the last line and as a result, the last line contains only the null character.

The program checks for this special line using the test

```
if ( line[0] == '\0')
```

and if the first (and only the first) character in the line is a null character, then counting is terminated. Note the difference between a null character and a blank character.

COUNTING CHARACTERS, WORDS AND LINES IN A TEXT

Program

```
#include    <stdio.h>

main()
{
    char line[81], ctr;
    int  i,c,
        end = 0,
        characters = 0,
        words = 0,
        lines = 0;

    printf("KEY IN THE TEXT.\n");
    printf("GIVE ONE SPACE AFTER EACH WORD.\n");
    printf("WHEN COMPLETED, PRESS 'RETURN'.\n\n");

    while( end == 0)
    {
        /* Reading a line of text */

        c = 0;
        while((ctr=getchar()) != '\n')
```



```

        line[c++] = ctr;
    line[c] = '\0';

    /* counting the words in a line */

    if(line[0] == '\0')
        break ;
    else
    {
        words++;
        for(i=0; line[i] != '\0';i++)
            if(line[i] == ' ' || line[i] == '\t')
                words++;
    }

    /* counting lines and characters */

    lines = lines +1;
    characters = characters + strlen(line);
}
printf ("\n");
printf("Number of lines = %d\n", lines);
printf("Number of words = %d\n", words);
printf("Number of characters = %d\n", characters);
}

```

Output

```

KEY IN THE TEXT.
GIVE ONE SPACE AFTER EACH WORD.
WHEN COMPLETED, PRESS 'RETURN'.

```

```

Admiration is a very short-lived passion.
Admiration involves a glorious obliquity of vision.
Always we like those who admire us but we do not
like those whom we admire.
Fools admire, but men of sense approve.

```

```

Number of lines = 5
Number of words = 36
Number of characters = 205

```

Fig.8.11 Counting of characters, words and lines in a text

The program also counts the number of lines read and the total number of characters in the text. Remember, the last line containing the null string is not counted.

After the first **while** loop is exited, the program prints the results of counting.

2. Processing of a Customer List

Telephone numbers of important customers are recorded as follows:

Full name	Telephone number
Joseph Louis Lagrange	869245
Jean Robert Argand	900823
Carl Freidrich Gauss	806788
----	---
----	---

It is desired to prepare a revised alphabetical list with surname (last name) first, followed by a comma and the initials of the first and middle names. For example,

Argand,J.R

We create a table of strings, each row representing the details of one person, such as first_name, middle_name, last_name, and telephone_number. The columns are interchanged as required and the list is sorted on the last_name. Fig.8.12 shows a program to achieve this.

PROCESSING OF CUSTOMER LIST

Program

```
#define CUSTOMERS 10

main( )
{
    char first_name[20][10], second_name[20][10],
        surname[20][10], name[20][20],
        telephone[20][10], dummy[20];

    int i,j;

    printf("Input names and telephone numbers \n");
    printf("?");
    for(i=0; i < CUSTOMERS ; i++)
    {
        scanf("%s %s %s %s", first_name[i],
            second_name[i], surname[i], telephone[i]);

        /* converting full name to surname with initials */

        strcpy(name[i], surname[i] );
        strcat(name[i], ",");
        dummy[0] = first_name[i][0];
        dummy[1] = '\0';
    }
}
```

```

        strcat(name[i], dummy);
        strcat(name[i], ".");
        dummy[0] = second_name[i][0];
        dummy[1] = '\0';
        strcat(name[i], dummy);
    }
    /* Alphabetical ordering of surnames */

    for(i=1; i <= CUSTOMERS-1; i++)
        for(j=1; j <= CUSTOMERS-i; j++)
            if(strcmp (name[j-1], name[j]) > 0)
            {
                /* Swaping names */
                strcpy(dummy, name[j-1]);
                strcpy(name[j-1], name[j]);
                strcpy(name[j], dummy);

                /* Swaping telephone numbers */
                strcpy(dummy, telephone[j-1]);
                strcpy(telephone[j-1], telephone[j]);
                strcpy(telephone[j], dummy);
            }

    /* printing alphabetical list */
    printf("\nCUSTOMERS LIST IN ALPHABETICAL ORDER \n\n");
    for(i=0; i < CUSTOMERS ; i++)
        printf("    %-20s\t %-10s\n", name[i], telephone[i]);
}

```

Output

```

Input names and telephone numbers
?Gottfried Wilhelm Leibniz 711518
Joseph Louis Lagrange 869245
Jean Robert Argand 900823
Carl Freidrich Gauss 806788
Simon Denis Poisson 853240
Friedrich Wilhelm Bessel 719731
Charles Francois Sturm 222031
George Gabriel Stokes 545454
Mohandas Karamchand Gandhi 362718

```

Josian Willard Gibbs 123145

CUSTOMERS LIST IN ALPHABETICAL ORDER

Argand, J.R	900823
Bessel, F.W	719731
Gandhi, M.K	362718
Gauss, C.F	806788
Gibbs, J.W	123145
Lagrange, J.L	869245
Leibniz, G.W	711518
Poisson, S.D	853240
Stokes, G.G	545454
Sturm, C.F	222031

Fig.8.12 Program to alphabetize a customer list

Example 8.1

Write a program to read a series of words from a terminal using **scanf** function

The program shown in Fig.8.1 reads four words and displays them on the screen. Note that the string 'Oxford Road' is treated as *two words* while the string 'Oxford-Road' as *one word*.

READING A SERIES OF WORDS USING **scanf** FUNCTION

Program

```
main( )
{
    char word1[40], word2[40], word3[40], word4[40];
    printf("Enter text : \n");
    scanf("%s %s", word1, word2);
    scanf("%s", word3);
    scanf("%s", word4);

    printf("\n");
    printf("word1 = %s\nword2 = %s\n", word1, word2);
    printf("word3 = %s\nword4 = %s\n", word3, word4);
}
```

Output

```
Enter text :
Oxford Road, London M17ED

word1 = Oxford
word2 = Road,
word3 = London
word4 = M17ED

Enter text :
Oxford-Road, London-M17ED United Kingdom
word1 = Oxford-Road
word2 = London-M17ED
word3 = United
word4 = Kingdom
```

*Fig.8.1 Reading a series of words using **scanf***

Example 8.2

Write a program to read a line of text containing a series of words from the terminal.

The program shown in Fig.8.2 can read a line of text (upto a maximum of 80 characters) into the string **line** using **getchar** function. Every time a character is read, it is assigned to its location in the string **line** and then tested for *newline* character. When the *newline* character is read (signalling the end of line), the reading loop is terminated and the *newline* character is replaced by the null character to indicate the end of character string.

When the loop is exited, the value of the index **c** is one number higher than the last character position in the string (since it has been incremented after assigning the new character to the

string). Therefore the index value **c-1** gives the position where the *null* character is to be stored.

PROGRAM TO **READ A LINE OF TEXT** FROM TERMINAL

Program

```
#include <stdio.h>

main( )
{
    char line[81], character;
    int c;

    c = 0;

    printf("Enter text. Press <Return> at end\n");
    do
    {
        character = getchar();
        line[c] = character;
        c++;
    }
    while(character != '\n');

    c = c - 1;
    line[c] = '\0';
    printf("\n%s\n", line);
}
```

Output

```
Enter text. Press <Return> at end
Programming in C is interesting.
Programming in C is interesting.

Enter text. Press <Return> at end
National Centre for Expert Systems, Hyderabad.
National Centre for Expert Systems, Hyderabad.
```

Fig.8.2 Program to read a line of text from terminal

Example 8.3

Write a program to copy one string into another and count the number of characters copied.

The program is shown in Fig.8.3. We use a **for** loop to copy the characters contained inside **string2** into the **string1**. The loop is terminated when the *null* character is reached. Note that we are again assigning a null character to the **string1**.

COPYING ONE STRING INTO ANOTHER

Program

```
main( )
{
    char string1[80], string2[80];
```

```

    int    i;

    printf("Enter a string \n");
    printf("?");

    scanf("%s", string2);

    for( i=0 ; string2[i] != '\0'; i++)
        string1[i] = string2[i];

    string1[i] = '\0';

    printf("\n");
    printf("%s\n", string1);
    printf("Number of characters = %d\n", i );
}

```

Output

```

Enter a string
?Manchester

Manchester
Number of characters = 10

Enter a string
?Westminster

Westminster
Number of characters = 11

```

Fig.8.3 Copying one string into another

Example 8.4

Write a program to store the string "United Kingdom" in the array **country** and display the string under various format specifications.

The program and its output are shown in Fig.8.4. The output illustrates the following features of the **%s** specifications.

1. When the field width is less than the length of the string, the entire string is printed.
2. The integer value on the right side of the decimal point specifies the number of characters to be printed.
3. When the number of characters to be printed is specified as zero, nothing is printed.
4. The minus sign in the specification causes the string to be printed left-justified.
5. The specification **% .ns** prints the first n characters of the string

Program

```
main()
{
    char  country[15] = "United Kingdom";

    printf("\n\n");
    printf("*123456789012345*\n");
    printf(" ----- \n");

    printf("%15s\n", country);
    printf("%5s\n", country);
    printf("%15.6s\n", country);
    printf("%-15.6s\n", country);
    printf("%15.0s\n", country);
    printf("%.3s\n", country);
    printf("%s\n", country);
    printf("----- \n");
}
```

Output

```
*123456789012345*
-----
    United Kingdom
United Kingdom
        United
United

Uni
United Kingdom
-----
```

Fig.8.4 Writing strings using %s format

Example 8.5

Write a program using **for loop** to print the following output.

C
CP
CPr
CPro
.....
.....
CProgramming
CProgramming
.....
.....
CPro
CPr
CP
C

The outputs of the program in Fig.8.5, for variable specifications **%12.*s**, **%.*s**, and **%.1s** are shown in Fig.8.6, which further illustrates the variable field width and the precision specifications.

PRINTING SEQUENCES OF CHARACTERS

Program

```
main()
{
    int  c, d;
    char string[] = "CProgramming";

    printf("\n\n");
    printf("-----\n");
    for( c = 0 ; c <= 11 ; c++ )
    {
        d = c + 1;
        printf("|%-12.*s|\n", d, string);
    }
    printf("|-----|\n");
    for( c = 11 ; c >= 0 ; c-- )
    {
        d = c + 1;
        printf("|%-12.*s|\n", d, string);
    }
    printf("-----\n");
}
```

Output	C CP CPr CPro CProg CProgr CProgra CProgram CProgramm CProgrammi CProgrammin CProgramming
	CProgramming CProgrammin CProgrammi CProgramm CProgram CProgra CProgr CProg CPro CPr CP C

Fig.8.5 Illustration of variable field specifications

Example 8.6

Write a program which would print the alphabet set a to z and A to Z in decimal and character form.

The program is shown in Fig.8.7. In ASCII character set, the decimal numbers 65 to 90 represent uppercase alphabets and 97 to 122 represent lowercase alphabets. The values from 91 to 96 are excluded using an **if** statement in the **for** loop.

PRINTING ALPHABET SET IN DECIMAL AND CHARACTER FORM

Program

```
main()
{
    char  c;
    printf("\n\n");
    for( c = 65 ; c <= 122 ; c = c + 1 )
    {
        if( c > 90  &&  c < 97 )
            continue;
    }
}
```

```

        printf("|%4d - %c ", c, c);
    }
    printf("\n");
}

```

Output

	65	-	A		66	-	B		67	-	C		68	-	D		69	-	E		70	-	F	
	71	-	G		72	-	H		73	-	I		74	-	J		75	-	K		76	-	L	
	77	-	M		78	-	N		79	-	O		80	-	P		81	-	Q		82	-	R	
	83	-	S		84	-	T		85	-	U		86	-	V		87	-	W		88	-	X	
	89	-	Y		90	-	Z		97	-	a		98	-	b		99	-	c		100	-	d	
	101	-	e		102	-	f		103	-	g		104	-	h		105	-	i		106	-	j	
	107	-	k		108	-	l		109	-	m		110	-	n		111	-	o		112	-	p	
	113	-	q		114	-	r		115	-	s		116	-	t		117	-	u		118	-	v	
	119	-	w		120	-	x		121	-	y		122	-	z									

Fig.8.7 Printing of the alphabet set in decimal and character form

Example 8.7

The names of employees of an organization are stored in three arrays, namely **first_name**, **second_name**, and **last_name**. Write a program to concatenate the three parts into one string to be called **name**.

The program is given in Fig.8.8. Three **for** loops are used to copy the three strings. In the first loop, the characters contained in the **first_name** are copied into the variable **name** until the *null* character is reached. The *null* character is not copied; instead it is replaced by a *space* by the assignment statement

```
name[i] = ' ';
```

Similarly, the **second_name** is copied into **name**, starting from the column just after the space created by the above statement. This is achieved by the assignment statement

```
name[i+j+1] = second_name[j];
```

If **first_name** contains 4 characters, then the value of *i* at this point will be 4 and therefore the first character from **second_name** will be placed in the *fifth cell* of **name**. Note that we have stored a space in the *fourth cell*.

In the same way, the statement

```
name[i+j+k+2] = last_name[k];
```

is used to copy the characters from **last_name** into the proper locations of **name**.

At the end, we place a null character to terminate the concatenated string **name**. In this example, it is important to note the use of the expressions **i+j+1** and **i+j+k+2**.

Program

```
main()
{
    int  i, j, k ;
    char  first_name[10] = {"VISWANATH"} ;
    char  second_name[10] = {"PRATAP"} ;
    char  last_name[10] = {"SINGH"} ;
    char  name[30] ;

    /* Copy first_name into name */
    for( i = 0 ; first_name[i] != '\0' ; i++ )
        name[i] = first_name[i] ;

    /* End first_name with a space */
    name[i] = ' ' ;

    /* Copy second_name into name */
    for( j = 0 ; second_name[j] != '\0' ; j++ )
        name[i+j+1] = second_name[j] ;

    /* End second_name with a space */
    name[i+j+1] = ' ' ;

    /* Copy last_name into name */
    for( k = 0 ; last_name[k] != '\0'; k++ )
        name[i+j+k+2] = last_name[k] ;

    /* End name with a null character */
    name[i+j+k+2] = '\0' ;

    printf("\n\n") ;
    printf("%s\n", name) ;
}
```

Output

VISWANATH PRATAP SINGH

Fig.8.8 Concatenation of strings

Example 8.8

s1, **s2**, and **s3** are three string variables. Write a program to read two string constants into **s1** and **s2** and compare whether they are equal or not. If they are not, join them together. Then copy the contents of **s1** to the variable **s3**. At the end, the program should print the contents of all the three variables and their lengths.

The program is shown in Fig.8.9. During the first run, the input strings are "New" and "York". These strings are compared by the statement

```
x = strcmp(s1, s2);
```

Since they are not equal, they are joined together and copied into **s3** using the statement

```
strcpy(s3, s1);
```

The program outputs all the three strings with their lengths.

During the second run, the two strings **s1** and **s2** are equal, and therefore, they are not joined together. In this case all the three strings contain the same string constant "London".

Program

```
#include    <string.h>

main()
{
    char    s1[20], s2[20], s3[20];
    int     x, l1, l2, l3;

    printf("\n\nEnter two string constants \n");
    printf("?");
    scanf("%s %s", s1, s2);

    /* comparing s1 and s2 */
    x = strcmp(s1, s2);
    if(x != 0)
    {
        printf("\n\nStrings are not equal \n");
        strcat(s1, s2);    /* joining s1 and s2 */
    }
    else
        printf("\n\nStrings are equal \n");

    /* copying s1 to s3
        strcpy(s3, s1);

    /* Finding length of strings */
    l1 = strlen(s1);
    l2 = strlen(s2);
    l3 = strlen(s3);

    /* output */
    printf("\ns1 = %s\t length = %d characters\n", s1, l1);
    printf("s2 = %s\t length = %d characters\n", s2, l2);
    printf("s3 = %s\t length = %d characters\n", s3, l3);

}
```

Output

```
Enter two string constants
? New York

Strings are not equal

s1 = NewYork      length = 7 characters
s2 = York         length = 4 characters
s3 = NewYork      length = 7 characters

Enter two string constants
? London  London

Strings are equal

s1 = London       length = 6 characters
s2 = London       length = 6 characters
s3 = London       length = 6 characters
```

Fig.7.9 Illustration of string handling functions

Example 8.9

Write a program that would sort a list of names in alphabetical order.

A program to sort the list of strings in alphabetical order is given in Fig.8.10. It employs the method of bubble sorting described in Case Study 1 in the previous chapter.

SORTING OF STRINGS IN ALPHABETICAL ORDER

Program

```
#define ITEMS 5
#define MAXCHAR 20

main( )
{
    char string[ITEMS][MAXCHAR], dummy[MAXCHAR];
    int i = 0, j = 0;

    /* Reading the list */
    printf ("Enter names of %d items \n ",ITEMS);
    while (i < ITEMS)
        scanf ("%s", string[i++]);

    /* Sorting begins */
    for (i=1; i < ITEMS; i++) /* Outer loop begins */
    {
        for (j=1; j <= ITEMS-i ; j++) /*Inner loop begins*/
        {
```

```

        if (strcmp (string[j-1], string[j]) > 0)
        {   /* Exchange of contents */
            strcpy (dummy, string[j-1]);
            strcpy (string[j-1], string[j]);
            strcpy (string[j], dummy );
        }

    } /* Inner loop ends */

} /* Outer loop ends */

/* Sorting completed */
printf ("\nAlphabetical list \n\n");
for (i=0; i < ITEMS ; i++)
    printf ("%s", string[i]);
}

```

Output

```

Enter names of 5 items
London Manchester Delhi Paris Moscow
Alphabetical list

Delhi
London
Manchester
Moscow
Paris

```

Fig.8.10 *Sorting of strings.*

Case Study

Calculation of Area Under a Curve

One of the applications of computers in numerical analysis is computing the area under a curve. One simple method of calculating the area under a curve is to divide the area into a number of trapezoids of same width and summing up the area of individual trapezoids. The area of a trapezoid is given by

$$\text{Area} = 0.5 * (h1 + h2) * b$$

Where h1 and h2 are the heights of two sides and b is the width as shown in Fig 9.18.




Fig. 9.18 Area under a curve

The program in Fig 9.20 calculates the area for a curve of the function

$$f(x) = x^2 + 1$$

between any two given limits, say, A and B.

Input

Lower limit (A)

Upper limit (B)

Number of trapezoids

Output

Total area under the curve between the given limits.

Algorithm

1. Input the lower and upper limits and the number of trapezoids.

2. Calculate the width of trapezoids.
3. Initialize the total area.
4. Calculate the area of trapezoid and add to the total area.
5. Repeat step-4 until all the trapezoids are completed.
6. Print total area.

The algorithm is implemented in top-down modular form as in Fig. 9.19.




Fig 9.19 Modular Chart

The evaluation of $f(x)$ has been done using a separate function so that it can be easily modified to allow other functions to be evaluated.

The output for two runs shows that better accuracy is achieved with larger number of trapezoids. The actual area for the limits 0 and 3 is 12 units (by analytical method)

AREA UNDER A CURVE

Program

```
#include <stdio.h>

float start_point,          /* GLOBAL VARIABLES */
      end_point,
      total_area;
int   numtraps;

main( )
{
    void    input(void);
    float   find_area(float a,float b,int n); /* prototype */

    print("AREA UNDER A CURVE");
    input( );
    total_area = find_area(start_point, end_point, numtraps);
    printf("TOTAL AREA = %f", total_area);
}

void input(void)
{
    printf("\n Enter lower limit:");
    scanf("%f", &start_point);
    printf("Enter upper limit:");
    scanf("%f", &end_point);
    printf("Enter number of trapezoids:");
    scanf("%d", &numtraps);
}

float find_area(float a, float b, int n)
{
    float base, lower, h1, h2; /* LOCAL VARIABLES */
    float function_x(float x); /* prototype */
    float trap_area(float h1,float h2,float base);/*prototype*/

    base = (b-a)/n;
    lower = a;

    for(lower = a; lower <= b-base; lower = lower + base)
    {
        h1 = function_x(lower);
        h2 = function_x(lower + base);
        total_area += trap_area(h1, h2, base);
    }

    return(total_area);

    float trap_area(float height_1,float height_2,float base)
    {
        float area;    /* LOCAL VARIABLE */
        area = 0.5 * (height_1 + height_2) * base;
        return(area);
    }

    float function_x(float x)
    {
        /* F(X) = X * X + 1 */

        return(x*x + 1);
    }
}
```

Output

```
AREA UNDER A CURVE
Enter lower limit: 0
Enter upper limit: 3
Enter number of trapezoids: 30
TOTAL AREA  = 12.005000

AREA UNDER A CURVE
Enter lower limit: 0
Enter upper limit: 3
Enter number of trapezoids: 100
TOTAL AREA = 12.000438
```

Fig. 9.20 Computing area under a curve

Example 9.1

Write a program with multiple functions that do not communicate any data between them.

A program with three user-defined functions is given in Fig.9.4. **main** is the calling function that calls **prntline** and **value** functions. Since both the called functions contain no arguments, there are no argument declarations. The **prntline** function, when encountered, prints a line with a length of 35 characters as prescribed in the function. The **value** function calculates the value of principal amount after a certain period of years and prints the results. The following equation is evaluated repeatedly:

$$\text{value} = \text{principal}(1 + \text{interest-rate})$$

Program

```
/* Function declaration */
void printline (void);
void value (void);

main()
{
    printline();
    value();
    printline();
}

/*      Function1: printline( )      */

void printline(void) /* contains no arguments */
{
    int i ;

    for(i=1; i <= 35; i++)
        printf("%c", '-');
    printf("\n");
}

/*      Function2: value( )      */

void value(void) /* contains no arguments */
{
    int    year, period;
    float  inrate, sum, principal;

    printf("Principal amount?");
    scanf("%f", &principal);
    printf("Interest rate?   ");
    scanf("%f", &inrate);
    printf("Period?         ");
    scanf("%d", &period);

    sum = principal;
    year = 1;
    while(year <= period)
    {
        sum = sum *(1+inrate);
        year = year +1;
    }
    printf("\n%8.2f %5.2f %5d %12.2f\n",
        principal,inrate,period,sum);
}
```

Output

```
-----  
Principal amount? 5000  
Interest rate?    0.12  
Period?           5  
  
5000.00  0.12      5      8811.71  
-----
```

Fig.9.4 Functions with no arguments and no return values

Example 9.2

Modify the program of Example 9.1 to include the arguments in the function calls.

The modified program with function arguments is presented in Fig.9.7. Most of the program is identical to the program in Fig.9.4. The input prompt and **scanf** assignment statement have been moved from **value** function to **main**. The variables **principal**, **inrate**, and **period** are declared in **main** because they are used in main to receive data. The function call

```
value(principal, inrate, period);
```

passes information it contains to the function **value**.

The function header of **value** has three formal arguments **p**, **r**, and **n** which correspond to the actual arguments in the function call, namely, **principal**, **inrate**, and **period**. On execution of the function call, the values of the actual arguments are assigned to the corresponding formal arguments. In fact, the following assignments are accomplished across the function boundaries:

```
p = principal;  
r = inrate;  
n = period;
```

FUNCTIONS WITH ARGUMENTS BUT NO RETURN VALUES

Program

```
/* prototypes */  
void printline (char c);  
void value (float, float, int);  
  
main( )  
{  
    float principal, inrate;  
    int period;  
  
    printf("Enter principal amount, interest");  
    printf(" rate, and period \n");  
    scanf("%f %f %d",&principal, &inrate, &period);  
    printline('Z');  
    value(principal,inrate,period);  
    printline('C');  
}
```

Output

Fig.9.7 Functions with arguments but no return values

In the program presented in Fig. 9.7 modify the function **value**, to return the final amount calculated to the **main**, which will display the required output at the terminal. Also extend the versatility of the function **printline** by having it to take the length of the line as an argument.

The modified program with the proposed changes is presented in Fig. 9.9. One major change is the movement of the **printf** statement from **value** to **main**.

FUNCTIONS WITH ARGUMENTS AND RETURN VALUES

Program

```
void printline (char ch, int len);
```



```

value (float, float, int);

main( )
{
    float principal, inrate, amount;
    int period;
    printf("Enter principal amount, interest");
    printf("rate, and period\n");
    scanf("%f %f %d", &principal, &inrate, &period);
    printline ('*' , 52);
    amount = value (principal, inrate, period);
    printf("\n%f\t%f\t%d\t%f\n\n",principal,
           inrate,period,amount);
    printline ('=' , 52);
}

void printline(char ch, int len)
{
    int i;
    for (i=1;i<=len;i++) printf("%c",ch);
    printf("\n");
}

value(float p, float r, int n) /* default return type */
{
    int year;
    float sum;
    sum = p; year = 1;
    while(year <=n)
    {
        sum = sum * (1+r);
        year = year +1;
    }
    return(sum);          /* returns int part of sum */
}

```

Output

```

Enter principal amount, interest rate, and period
5000 0.12      5
*****
5000.000000      0.1200000  5      8811.000000
= = = = =

```

Fig.9.9 Functions with arguments and return values

Example 9.4

Write a function **power** that computes x raised to the power y for integers x and y and returns double-type value.

Fig 9.10 shows a **power** function that returns a **double**. The prototype declaration

double power(int, int);

appears in **main**, before **power** is called.

POWER FUNCTIONS

Program

```
main( )
{
    int x,y;                /*input data */
    double power(int, int);  /* prototype declaration*/
    printf("Enter x,y:");
    scanf("%d %d" , &x,&y);
    printf("%d to power %d is %f\n", x,y,power (x,y));
}

double power (int x, int y);
{
    double p;
    p = 1.0 ;               /* x to power zero */

    if(y >=0)
        while(y-->0) /* computes positive powers */
            p *= x;
    else
        while (y--<0) /* computes negative powers */
            p /= x;
    return(p);
}
```

Output

```
Enter x,y:16 2
16 to power 2 is 256.000000

Enter x,y:16 -2
16 to power -2 is 0.003906
```

Fig 9.10 Illustration of return of float values

Example 9.5

Write a program to calculate the standard deviation of an array of values. The array elements are read from the terminal. Use functions to calculate standard deviation and mean.

Standard deviation of a set of n values is given by

$$S.D = \sqrt{\frac{\sum_{i=1}^n (x_i - \bar{x})^2}{n}}$$

Where \bar{x} is the mean of the values.

FUNCTIONS WITH ARRAYS

Program

```
#include <math.h>
#define SIZE 5
float std_dev(float a[], int n);
float mean (float a[], int n);

main( )
{
    float value[SIZE];
    int i;

    printf("Enter %d float values\n", SIZE);
    for (i=0 ; i < SIZE ; i++)
        scanf("%f", &value[i]);
    printf("Std.deviation is %f\n", std_dev(value,SIZE));
}

float std_dev(float a[], int n)
{
    int i;
    float x, sum = 0.0;
    x = mean (a,n);
    for(i=0; i < n; i++)
        sum += (x-a[i])*(x-a[i]);
    return(sqrt(sum/(float)n));
}

float mean(float a[],int n)
{
    int i ;
    float sum = 0.0;
    for(i=0 ; i < n ; i++)
        sum = sum + a[i];
    return(sum/(float)n);
}
```

```
}
```

Output

```
Enter 5 float values
35.0 67.0 79.5 14.20 55.75

Std.deviation is 23.231582
```

Fig.9.11 *Passing of arrays to a function*

Example 9.6

Write a program that uses a function to sort an array of integers.

A program to sort an array of integers using the function **sort()** is given in Fig.9.12. Its output clearly shows that a function can change the values in an array passed as an argument.

SORTING OF ARRAY ELEMENTS

Program

```
void sort(int m, int x[ ]);
main()
{
    int i;
    int marks[5] = {40, 90, 73, 81, 35};

    printf("Marks before sorting\n");
    for(i = 0; i < 5; i++)
        printf("%d ", marks[i]);
    printf("\n\n");

    sort (5, marks);

    printf("Marks after sorting\n");
    for(i = 0; i < 5; i++)
        printf("%4d", marks[i]);
    printf("\n");
}

void sort(int m, int x[ ])
{
    int i, j, t;
```

```

for(i = 1; i <= m-1; i++)
    for(j = 1; j <= m-i; j++)
        if(x[j-1] >= x[j])
        {
            t = x[j-1];
            x[j-1] = x[j];
            x[j] = t;
        }
}

```

Output

```

Marks before sorting
40 90 73 81 35

Marks after sorting
35 40 73 81 90

```

Fig.9.12 *Sorting of array elements using a function*

Example 9.7

Write a multifunction to illustrate how automatic variables work.

A program with two subprograms **function1** and **function2** is shown in Fig.9.13. **m** is an automatic variable and it is declared at the beginning of each function. **m** is initialized to 10, 100, and 1000 in function1, function2, and **main** respectively.

When executed, **main** calls **function2** which in turn calls **function1**. When **main** is active, **m** = 1000; but when **function2** is called, the **main**'s **m** is temporarily put on the shelf and the new local **m** = 100 becomes active. Similarly, when **function1** is called, both the previous values of **m** are put on the shelf and the latest value of **m** (=10) becomes active. As soon as **function1** (**m**=10) is finished, **function2** (**m**=100) takes over again. As soon it is done, **main** (**m**=1000) takes over. The output clearly shows that the value assigned to **m** in one function does not affect its value in the other functions; and the local value of **m** is destroyed when it leaves a function.

ILLUSTRATION OF WORKING OF **auto** VARIABLES

Program

```

void function1(void);
void function2(void);

```

```

main( )
{
    int m = 1000;
    function2();

    printf("%d\n",m); /* Third output */
}
void function1(void)
{
    int m = 10;

    printf("%d\n",m); /* First output */
}

void function2(void)
{
    int m = 100;
    function1();
    printf("%d\n",m); /* Second output */
}

```

Output

```

10
100
1000

```

Fig.9.13 Working of automatic variables

Example 9.8

Write a multifunction program to illustrate the properties of global variables.

A program to illustrate the properties of global variables is presented in Fig.9.14. Note that variable **x** is used in all functions but none except **fun2**, has a definition for **x**. Because **x** has been declared 'above' all the functions, it is available to each function without having to pass **x** as a function argument. Further, since the value of **x** is directly available, we need not use **return(x)** statements in **fun1** and **fun3**. However, since **fun2** has a definition of **x**, it returns its local value of **x** and therefore uses a **return** statement. In **fun2**, the global **x** is not visible. The local **x** hides its visibility here.

ILLUSTRATION OF PROPERTIES OF GLOBAL VARIABLES

Program

```

int fun1(void);
int fun2(void);
int fun3(void);
int x ;           /* global */

```

```

main( )
{
    x = 10 ;      /* global x */
    printf("x = %d\n", x);
    printf("x = %d\n", fun1());
    printf("x = %d\n", fun2());
    printf("x = %d\n", fun3());
}
fun1(void)
{
    x = x + 10 ;
}
int fun2(void)
{
    int x ;      /* local */
    x = 1 ;
    return (x);
}
fun3(void)
{
    x = x + 10 ; /* global x */
}

```

Output	x = 10
	x = 20
	x = 1
	x = 30

Fig.9.14 Illustration of global variables

Example 9.9

Write a program to illustrate the properties of a static variable.

The program in Fig.9.15 explains the behaviour of a static variable.

ILLUSTRATION OF STATIC VARIABLE

Program

```

void stat(void);
main ( )
{
    int i;
    for(i=1; i<=3; i++)
        stat( );
}
void stat(void)

```

```
{  
    static int x = 0;  
  
    x = x+1;  
    printf("x = %d\n", x);  
}
```

Output

```
x = 1  
x = 2  
x = 3
```

Fig.9.15 Illustration of static variable

CASE STUDY

Book Shop Inventory

A book shop uses a personal computer to maintain the inventory of books that are being sold at the shop. The list includes details such as author, title, price, publisher, stock position, etc. Whenever a customer wants a book, the shopkeeper inputs the title and author of the book and the system replies whether it is in the list or not. If it is not, an appropriate message is displayed. If book is in the list, then the system displays the book details and asks for number of copies. If the requested copies are available, the total cost of the books is displayed; otherwise the message "Required copies not in stock" is displayed.

A program to accomplish this is shown in Fig.10.8. The program uses a template to define the structure of the book. Note that the date of publication, a member of **record** structure, is also defined as a structure.

When the title and author of a book are specified, the program searches for the book in the list using the function

look_up(table, s1, s2, m)

The parameter **table** which receives the structure variable **book** is declared as type **struct record**. The parameters **s1** and **s2** receive the string values of **title** and **author** while **m** receives the total number of books in the list. Total number of books is given by the expression

sizeof(book)/sizeof(struct record)

The search ends when the book is found in the list and the function returns the serial number of the book. The function returns -1 when the book is not found. Remember that the serial number of the first book in the list is zero. The program terminates when we respond "NO" to the question

Do you want any other book?

Note that we use the function

get(string)

to get title, author, etc. from the terminal. This enables us to input strings with spaces such as "C Language". We cannot use **scanf** to read this string since it contains two words.

Since we are reading the quantity as a string using the **get(string)** function, we have to convert it to an integer before using it in any expressions. This is done using the **atoi()** function.

BOOK SHOP INVENTORY

Programs

```
#include <stdio.h>
#include <string.h>

struct record
{
    char    author[20];
    char    title[30];
    float   price;

    struct
    {
        char    month[10];
```

```

        int    year;
    }
    date;
    char    publisher[10];
    int    quantity;
};

int look_up(struct record table[],char s1[],char s2[],int m);
void get (char string [ ] );

main()
{
    char title[30], author[20];
    int  index, no_of_records;
    char response[10], quantity[10];
    struct record book[] = {
        {"Ritche","C Language",45.00,"May",1977,"PHI",10},
        {"Kochan","Programming in C",75.50,"July",1983,"Hayden",5},
        {"Balagurusamy","BASIC",30.00,"January",1984,"TMH",0},
        {"Balagurusamy","COBOL",60.00,"December",1988,"Macmillan",25}
    };

    no_of_records = sizeof(book)/ sizeof(struct record);
    do
    {
        printf("Enter title and author name as per the list\n");
        printf("\nTitle:    ");
        get(title);

        printf("Author:    ");
        get(author);

        index = look_up(book, title, author, no_of_records);
        if(index != -1)      /* Book found */
        {
            printf("\n%s %s %.2f %s %d %s\n\n",
                book[index].author,
                book[index].title,
                book[index].price,
                book[index].date.month,
                book[index].date.year,
                book[index].publisher);

            printf("Enter number of copies:");
            get(quantity);
            if(atoi(quantity) < book[index].quantity)

                printf("Cost of %d copies = %.2f\n",atoi(quantity),
                    book[index].price * atoi(quantity));
            else
                printf("\nRequired copies not in stock\n\n");
        }
    }
    else

```

```

        printf("\nBook not in list\n\n");

        printf("\nDo you want any other book? (YES / NO):");
        get(response);
    }
    while(response[0] == 'Y' || response[0] == 'y');
    printf("\n\nThank you.  Good bye!\n");
}

void get(char string [])
{
    char  c;
    int   i = 0;
    do
    {
        c = getchar();
        string[i++] = c;
    }
    while(c != '\n');
    string[i-1] = '\0';
}

int look_up(struct record table[],char s1[],char s2[],int m)
{
    int i;
    for(i = 0; i < m; i++)
        if(strcmp(s1, table[i].title) == 0  &&
            strcmp(s2, table[i].author) == 0)
            return(i);          /* book found      */
    return(-1);                 /* book not found */
}

```

Output

Enter title and author name as per the list

Title: BASIC

Author: Balagurusamy

Balagurusamy BASIC 30.00 January 1984 TMH

Enter number of copies:5

Required copies not in stock

Do you want any other book? (YES / NO):y

Enter title and author name as per the list

Title: COBOL

Author: Balagurusamy

Balagurusamy COBOL 60.00 December 1988 Macmillan

Enter number of copies:7

Cost of 7 copies = 420.00

Do you want any other book? (YES / NO):y
Enter title and author name as per the list

Title: C Programming
Author: Ritche

Book not in list

Do you want any other book? (YES / NO):n

Thank you. Good bye!

Fig.10.8 Program of bookshop inventory

Example 10.1

Define a structure type, **struct personal** that would contain person name, date of joining and salary. Using this structure, write a program to read this information for one person from the keyboard and print the same on the screen.

Structure definition along with the program is shown in Fig.10.1. The **scanf** and **printf** functions illustrate how the member operator **`.`** is used to link the structure members to the structure variables. The variable name with a period and the member name is used like an ordinary variable.

DEFINING AND ASSIGNING VALUES TO STRUCTURE MEMBERS

Program

```
struct personal
{
    char  name[20];
    int   day;
    char  month[10];
    int   year;
    float salary;
};
main()
{
    struct personal person;
    printf("Input Values\n");
    scanf("%s %d %s %d %f",
          person.name,
          &person.day,
          person.month,
          &person.year,
          &person.salary);
    printf("%s %d %s %d %f\n",
          person.name,
          person.day,
          person.month,
          person.year,
          person.salary);
}
```

Output

Input Values

M.L.Goel 10 January 1945 4500

M.L.Goel 10 January 1945 4500.00

Fig.10.1 *Defining and accessing structure members*

Example 10.2

Write a program to illustrate the comparison of structure variables.

The program shown in Fig.10.2 illustrates how a structure variable can be copied into another of the same type. It also performs member-wise comparison to decide whether two structure variables are identical.

COMPARISON OF STRUCTURE VARIABLES

Program

```
struct class
{
    int    number;
    char name[20];
    float marks;
};

main()
{
    int    x;
    struct class student1 = {111,"Rao",72.50};
    struct class student2 = {222,"Reddy", 67.00};
    struct class student3;

    student3 = student2;

    x = ((student3.number ==  student2.number) &&
        (student3.marks  ==  student2.marks)) ? 1 : 0;

    if(x == 1)
    {
        printf("\nstudent2 and student3 are same\n\n");
        printf("%d %s %f\n", student3.number,
                    student3.name,
                    student3.marks);
    }
    else
        printf("\nstudent2 and student3 are different\n\n");
}
```

Output

student2 and student3 are same

222 Reddy 67.000000

Fig.10.2 Comparing and copying structure variables

Example 10.3

For the **student** array discussed above, write a program to calculate the subject-wise and student-wise totals and store them as a part of the structure.

The program is shown in Fig.10.4. We have declared a four-member structure, the fourth one for keeping the student-totals. We have also declared an **array** total to keep the subject-totals and the grand-total. The grand-total is given by **total.total**. Note that a member name can be any valid C name and can be the same as an existing structure variable name. The linked name **total.total** represents the **total** member of the structure variable total.

ARRAYS OF STRUCTURES

Program

```
struct marks
{
    int    sub1;
    int    sub2;
    int    sub3;
    int    total;
};
main()
{
    int    i;
    struct marks student[3] = {{45,67,81,0},
                                {75,53,69,0},
                                {57,36,71,0}};

    struct marks total;
    for(i = 0; i <= 2; i++)
    {
        student[i].total = student[i].sub1 +
                            student[i].sub2 +
                            student[i].sub3;
        total.sub1 = total.sub1 + student[i].sub1;
        total.sub2 = total.sub2 + student[i].sub2;
        total.sub3 = total.sub3 + student[i].sub3;
        total.total = total.total + student[i].total;
    }
    printf(" STUDENT          TOTAL\n\n");
    for(i = 0; i <= 2; i++)
        printf("Student[%d]      %d\n", i+1, student[i].total);
}
```

```

printf("\n SUBJECT          TOTAL\n\n");
printf("%s          %d\n%s          %d\n%s          %d\n",
       "Subject 1", total.sub1,
       "Subject 2", total.sub2,
       "Subject 3", total.sub3);

printf("\nGrand Total = %d\n", total.total);
}

```

Output

```

STUDENT          TOTAL
Student[1]       193
Student[2]       197
Student[3]       164

SUBJECT          TOTAL
Subject 1        177
Subject 2        156
Subject 3        221

Grand Total    = 554

```

Fig.10.4 Illustration of subscripted structure variables

Example 10.4

Rewrite the program of Example 10.3 using an array member to represent the three subjects.

The modified program is shown in Fig.10.5. You may notice that the use of array name for subjects has simplified in code.

ARRAYS WITHIN A STRUCTURE

Program

```

main()
{
    struct marks
    {
        int  sub[3];
        int  total;
    };
    struct marks student[3] =
    {45,67,81,0,75,53,69,0,57,36,71,0};

    struct marks total;
    int  i,j;
}

```



```

for(i = 0; i <= 2; i++)
{
    for(j = 0; j <= 2; j++)
    {
        student[i].total += student[i].sub[j];
        total.sub[j] += student[i].sub[j];
    }
    total.total += student[i].total;
}
printf("STUDENT          TOTAL\n\n");
for(i = 0; i <= 2; i++)
    printf("Student[%d]          %d\n", i+1, student[i].total);

printf("\nSUBJECT          TOTAL\n\n");
for(j = 0; j <= 2; j++)
    printf("Subject-%d          %d\n", j+1, total.sub[j]);

printf("\nGrand Total   =   %d\n", total.total);

}

```

Output

```

STUDENT          TOTAL
Student[1]       193
Student[2]       197
Student[3]       164

SUBJECT          TOTAL
Subject-1        177
Subject-2        156
Subject-3        221

Grand Total   =   554

```

Fig.10.5 Use of subscripted members in structures

Example 10.5

Write a simple program to illustrate the method of sending an entire structure as a parameter to a function.

A program to update an item is shown in Fig.10.6. The function **update** receives a copy of the structure variable **item** as one of its parameters. Note that both the function **update** and the formal parameter **product** are declared as type **struct stores**. It is done so because the function uses the parameter **product** to receive the structure variable **item** and also to return the updated values of **item**.

The function **mul** is of type **float** because it returns the product of **price** and **quantity**. However, the parameter **stock**, which receives the structure variable **item** is declared as type **struct stores**.

The entire structure returned by **update** can be copied into a structure of identical type. The statement

```
item = update(item,p_increment,q_increment);
```

replaces the old values of **item** by the new ones.

STRUCTURES AS FUNCTION PARAMETERS

Program

```
/*          Passing a copy of the entire structure          */
struct stores
{
    char  name[20];
    float price;
    int   quantity;
};
struct stores update (struct stores product, float p, int q);
float mul (struct stores stock);
main()
{
    float    p_increment, value;
    int      q_increment;

    struct stores item = {"XYZ", 25.75, 12};

    printf("\nInput increment values:");
    printf("    price increment and quantity increment\n");
    scanf("%f %d", &p_increment, &q_increment);

    /* - - - - - */
    item = update(item, p_increment, q_increment);
    /* - - - - - */
    printf("Updated values of item\n\n");
    printf("Name      : %s\n",item.name);
    printf("Price       : %f\n",item.price);
    printf("Quantity    : %d\n",item.quantity);

    /* - - - - - */
    value = mul(item);
    /* - - - - - */
    printf("\nValue of the item = %f\n", value);
}

struct stores update(struct stores product, float p, int q)
{
    product.price += p;
    product.quantity += q;
    return(product);
}
```

```
float mul(struct stores stock)
{
    return(stock.price * stock.quantity);
}
```

Output

Input increment values: price increment and quantity increment
10 12

Updated values of item

Name : XYZ

Price : 35.750000

Quantity : 24

Value of the item = 858.000000

Fig.10.6 Using structure as a function parameter

CASE STUDIES

1. Processing of Examination Marks

Marks obtained by a batch of students in the Annual Examination are tabulated as follows:

Student name	Marks obtained
S.Laxmi	45 67 38 55
V.S.Rao	77 89 56 69
--	- - - -

It is required to compute the total marks obtained by each student and print the rank list based on the total marks.

The program in Fig.11.14 stores the student names in the array **name** and the marks in the array **marks**. After computing the total marks obtained by all the students, the program prepares and prints the rank list. The declaration

```
int marks[STUDENTS][SUBJECTS+1];
```

defines **marks** as a pointer to the array's first row. We use **rowptr** as the pointer to the row of **marks**. The **rowptr** is initialized as follows:

```
int (*rowptr)[SUBJECTS+1] = array;
```

Note that **array** is the formal argument whose values are replaced by the values of the actual argument **marks**. The parentheses around ***rowptr** makes the **rowptr** as a pointer to an array of **SUBJECTS+1** integers. Remember, the statement

```
int *rowptr[SUBJECTS+1];
```

would declare **rowptr** as an array of **SUBJECTS+1** elements.

When we increment the **rowptr** (by **rowptr+1**), the incrementing is done in units of the size of each row of **array**, making **rowptr** point to the next row. Since **rowptr** points to a particular row, **(*rowptr)[x]** points to the xth element in the row.

POINTERS AND TWO-DIMENSIONAL ARRAYS

Program

```
#define STUDENTS 5
#define SUBJECTS 4
#include <string.h>
```

```

main()
{
    char name[STUDENTS][20];
    int marks[STUDENTS][SUBJECTS+1];

    printf("Input students names & their marks in four subjects\n");
    get_list(name, marks, STUDENTS, SUBJECTS);
    get_sum(marks, STUDENTS, SUBJECTS+1);
    printf("\n");
    print_list(name, marks, STUDENTS, SUBJECTS+1);
    get_rank_list(name, marks, STUDENTS, SUBJECTS+1);
    printf("\nRanked List\n\n");
    print_list(name, marks, STUDENTS, SUBJECTS+1);
}

/*    Input student name and marks        */
get_list(char *string[ ],
          int array [ ] [SUBJECTS +1], int m, int n)
{
    int i, j, (*rowptr)[SUBJECTS+1] = array;
    for(i = 0; i < m; i++)
    {
        scanf("%s", string[i]);
        for(j = 0; j < SUBJECTS; j++)
            scanf("%d", &(*(rowptr + i))[j]);
    }
}

/*    Compute total marks obtained by each student    */
get_sum(int array [ ] [SUBJECTS +1], int m, int n)
{
    int i, j, (*rowptr)[SUBJECTS+1] = array;
    for(i = 0; i < m; i++)
    {
        (*(rowptr + i))[n-1] = 0;
        for(j = 0; j < n-1; j++)
            (*(rowptr + i))[n-1] += (*(rowptr + i))[j];
    }
}

/*    Prepare rank list based on total marks        */
get_rank_list(char *string [ ],
               int array [ ] [SUBJECTS + 1]
               int m,
               int n)
{

```

```

int i, j, k, (*rowptr)[SUBJECTS+1] = array;
char *temp;

for(i = 1; i <= m-1; i++)
    for(j = 1; j <= m-i; j++)
        if( (*rowptr + j-1)[n-1] < (*rowptr + j)[n-1])
        {
            swap_string(string[j-1], string[j]);

            for(k = 0; k < n; k++)
                swap_int(&(*rowptr + j-1)[k], &(*rowptr + j)[k]);
        }
}

/*      Print out the ranked list      */
print_list(char *string[ ],
            int array [][SUBJECTS + 1],
            int m,
            int n)
{
    int i, j, (*rowptr)[SUBJECTS+1] = array;
    for(i = 0; i < m; i++)
    {
        printf("%-20s", string[i]);
        for(j = 0; j < n; j++)
            printf("%5d", (*rowptr + i)[j]);
        printf("\n");
    }
}

/*      Exchange of integer values      */
swap_int(int *p, int *q)
{
    int temp;

    temp = *p;
    *p = *q;
    *q = temp;
}

/*      Exchange of strings      */
swap_string(char s1[ ], char s2[ ])
{
    char swaparea[256];
    int i;

    for(i = 0; i < 256; i++)
        swaparea[i] = '\0';
    i = 0;

```

```

while(s1[i] != '\0' && i < 256)
{
    swaparea[i] = s1[i];
    i++;
}
i = 0;
while(s2[i] != '\0' && i < 256)
{
    s1[i] = s2[i];
    s1[++i] = '\0';
}
i = 0;
while(swaparea[i] != '\0')
{
    s2[i] = swaparea[i];
    s2[++i] = '\0';
}
}

```

Output

Input students names & their marks in four subjects

```

S.Laxmi 45 67 38 55
V.S.Rao 77 89 56 69
A.Gupta 66 78 98 45
S.Mani 86 72 0 25
R.Daniel 44 55 66 77

```

S.Laxmi	45	67	38	55	205
V.S.Rao	77	89	56	69	291
A.Gupta	66	78	98	45	287
S.Mani	86	72	0	25	183
R.Daniel	44	55	66	77	242

Ranked List

V.S.Rao	77	89	56	69	291
A.Gupta	66	78	98	45	287
R.Daniel	44	55	66	77	242
S.Laxmi	45	67	38	55	205
S.Mani	86	72	0	25	183

Fig.11.14 Preparation of the rank list of a class of students.

2. Inventory Updating

The price and quantity of items stocked in a store changes every day. They may either increase or decrease. The program in Fig.11.15 reads the incremental values of price and quantity and computes the total value of the items in stock.

The program illustrates the use of structure pointers as function parameters. **&item**, the address of the structure **item**, is passed to the functions **update()** and **mul()**. The formal arguments

product and **stock**, which receive the value of **&item**, are declared as pointers of type **struct stores**.

STRUCTURES AS FUNCTION PARAMETERS

Using structure pointers

Program

```
struct stores
{
    char  name[20];
    float price;
    int   quantity;
};
main()
{
    void update(struct stores *, float, int);
    float      p_increment, value;
    int        q_increment;

    struct stores item = {"XYZ", 25.75, 12};
    struct stores *ptr = &item;

    printf("\nInput increment values:");
    printf(" price increment and quantity increment\n");
    scanf("%f %d", &p_increment, &q_increment);

    /* - - - - - */
    update(&item, p_increment, q_increment);
    /* - - - - - */
    printf("Updated values of item\n\n");
    printf("Name      : %s\n", ptr->name);
    printf("Price       : %f\n", ptr->price);
    printf("Quantity    : %d\n", ptr->quantity);

    /* - - - - - */
    value = mul(&item);
    /* - - - - - */
    printf("\nValue of the item = %f\n", value);
}

void update(struct stores *product, float p, int q)
{
    product->price += p;
    product->quantity += q;
}

float mul(struct stores *stock)
{
    return(stock->price * stock->quantity);
}
```

Output

```
Input increment values: price increment and quantity increment  
10 12
```

```
Updated values of item
```

```
Name      : XYZ  
Price     : 35.750000  
Quantity  : 24
```

```
Value of the item = 858.000000
```

Fig.11.15 Use of structure pointers as function parameters.

Example 11.1

Write a program to print the address of a variable along with its value.

The program shown in Fig.11.4, declares and initializes four variables and then prints out these values with their respective storage locations. Notice that we have used %u format for printing address values. Memory addresses are unsigned integers.

ACCESSING ADDRESSES OF VARIABLES

Program

```
main()
{
    char    a;
    int     x;
    float   p, q;

    a  = 'A';
    x  = 125;
    p  = 10.25, q = 18.76;

    printf("%c is stored at addr %u.\n", a, &a);
    printf("%d is stored at addr %u.\n", x, &x);
    printf("%f is stored at addr %u.\n", p, &p);
    printf("%f is stored at addr %u.\n", q, &q);

}
```

Output

```
A is stored at addr 4436.
125 is stored at addr 4434.
10.250000 is stored at addr 4442.
18.760000 is stored at addr 4438.
```

Fig.11.4 Accessing the address of a variable

Example 11.2

Write a program to illustrate the use of indirection operator '*' to access the value pointed to by a pointer.

The program and output are shown in Fig.11.5. The program clearly shows how we can access the value of a variable using a pointer. You may notice that the value of the pointer **ptr** is 4104 and the value it points to is 10. Further, you may also note the following equivalences:

```
x = *(&x) = *ptr = y
&x = &*ptr
```

ACCESSING VARIABLES USING POINTERS

Program

```
main()
{
    int    x, y;
    int    *ptr;
    x = 10;
    ptr = &x;
    y = *ptr;

    printf("Value of x is %d\n\n",x);
    printf("%d is stored at addr %u\n", x, &x);
    printf("%d is stored at addr %u\n", *&x, &x);
    printf("%d is stored at addr %u\n", *ptr, ptr);
    printf("%d is stored at addr %u\n", y, &*ptr);
    printf("%d is stored at addr %u\n", ptr, &ptr);
    printf("%d is stored at addr %u\n", y, &y);

    *ptr = 25;
    printf("\nNow x = %d\n",x);
}
```

Output

```
Value of x is 10
10    is stored at addr 4104
10    is stored at addr 4104
10    is stored at addr 4104
10    is stored at addr 4104
4104  is stored at addr 4106
10    is stored at addr 4108

Now x = 25
```

Fig.11.5 Accessing a variable through its pointer

Example 11.3

Write a program to illustrate the use of pointers in arithmetic operations.

The program in Fig.11.7 shows how the pointer variables can be directly used in expressions. It also illustrates the order of evaluation of expressions. For example, the expression

$$4 * - *p2 / *p1 + 10$$

is evaluated as follows:

$$((4 * (-(*p2))) / (*p1)) + 10$$

When $*p1 = 12$ and $*p2 = 4$, this expression evaluates to 9. Remember, since all the variables are of type int, the entire evaluation is carried out using the integer arithmetic.

ILLUSTRATION OF POINTER EXPRESSIONS

Program

```
main()
{
    int  a, b, *p1, *p2, x, y, z;

    a  = 12;
    b  = 4;
    p1 = &a;
    p2 = &b;

    x  = *p1 * *p2 - 6;
    y  = 4*  - *p2 / *p1 + 10;

    printf("Address of a = %u\n", p1);
    printf("Address of b = %u\n", p2);
    printf("\n");
    printf("a = %d, b = %d\n", a, b);
    printf("x = %d, y = %d\n", x, y);

    *p2 = *p2 + 3;
    *p1 = *p2 - 5;
    z   = *p1 * *p2 - 6;

    printf("\na = %d, b = %d,", a, b);
    printf(" z = %d\n", z);
}
```

Output

```
Address of a = 4020
Address of b = 4016

a = 12, b = 4
x = 42, y = 9
a = 2, b = 7, z = 8
```

Fig.11.7 Evaluation of pointer expressions

Example 11.4

Write a program using pointers to compute the sum of all elements stored in an array.

The program shown in Fig.11.8 illustrates how a pointer can be used to traverse an array element. Since incrementing an array pointer causes it to point to the next element, we need only to add one to **p** each time we go through the loop.

Program

```
main()
{
    int *p, sum, i;
    int x[5] = {5,9,6,3,7};

    i = 0;
    p = x;          /* initializing with base address of x */

    printf("Element   Value   Address\n\n");
    while(i < 5)
    {
        printf(" x[%d] %d %u\n", i, *p, p);
        sum = sum + *p;    /* accessing array element */
        i++, p++;          /* incrementing pointer */
    }

    printf("\n Sum      = %d\n", sum);
    printf("\n  &x[0]    = %u\n", &x[0]);
    printf("\n  p       = %u\n", p);
}
```

Output

Element	Value	Address
x[0]	5	166
x[1]	9	168
x[2]	6	170
x[3]	3	172
x[4]	7	174
Sum	= 55	
&x[0]	= 166	
p	= 176	

Fig.11.8 Accessing array elements using the pointer

Example 11.5

Write a program using pointers to determine the length of a character string.

A program to count the length of a string is shown in Fig.11.10. The statement

```
char *cptr = name;
```

declares **cptr** as a pointer to a character and assigns the address of the first character of **name** as the initial value. Since a string is always terminated by the null character, the statement


```
while(*cptr != '\0')
```

is true until the end of the string is reached.

When the **while** loop is terminated, the pointer **cptr** holds the address of the null character. Therefore, the statement

```
length = cptr - name;
```

gives the length of the string **name**.



The output also shows the address location of each character. Note that each character occupies one memory cell (byte).

POINTERS AND CHARACTER STRINGS

Program

```
main()
{
    char *name;
    int length;
    char *cptr = name;
    name = "DELHI";
    printf ("%s\n", name);

    while(*cptr != '\0')
    {
        printf("%c is stored at address %u\n", *cptr, cptr);
        cptr++;
    }
    length = cptr - name;
    printf("\nLength of the string = %d\n", length);
}
```

Output

```
DELHI
D is stored at address 54
E is stored at address 55
L is stored at address 56
H is stored at address 57
I is stored at address 58

Length of the string = 5
```

Fig.11.10 String handling by pointers

Example 11.6

Write a function using pointers to exchange the values stored in two locations in the memory.

The program in Fig.11.11 shows how the contents of two locations can be exchanged using their address locations. The function **exchange()** receives the addresses of the variables **x** and **y** and exchanges their contents.

Program

```
void exchange (int *, int *);      /* prototype */
main()
{
    int  x, y;
    x = 100;
    y = 200;
    printf("Before exchange   : x = %d   y = %d\n\n", x, y);
    exchange(&x, &y);              /* call */
    printf("After exchange    : x = %d   y = %d\n\n", x, y);
}
exchange (int *a, int *b)
{
    int t;

    t = *a;      /* Assign the value at address a to t */
    *a = *b;      /* put b into a */
    *b = t;      /* put t into b */
}
```

Output

```
Before exchange   : x = 100   y = 200
After exchange    : x = 200   y = 100
```

Fig.11.11 Passing of pointers as function parameters

Example 11.7

Write a program that uses a function pointer as a function argument.

A program to print the function values over a given range of values is shown in Fig.11.12. The printing is done by the function **table** by evaluating the function passed to it by the **main**.

With **table**, we declare the parameter **f** as a pointer to a function as follows:

double (*f)();

The value returned by the function is of type **double**. When **table** is called in the statement

table (y, 0.0, 2, 0.5);

we pass a pointer to the function **y** as the first parameter of **table**. Note that **y** is not followed by a parameter list.

During the execution of **table**, the statement

value = (*f)(a);

calls the function **y** which is pointed to by **f**, passing it the parameter **a**. Thus the function **y** is evaluated over the range 0.0 to 2.0 at the intervals of 0.5.

Similarly, the call

table (cos, 0.0, PI, 0.5);

passes a pointer to **cos** as its first parameter and therefore, the function **table** evaluates the value of **cos** over the range 0.0 to PI at the intervals of 0.5.

ILLUSTRATION OF POINTERS TO FUNCTIONS

Program

```
#include <math.h>
#define PI 3.1415926
double y(double);
double cos(double);
double table (double(*f)(), double, double, double);

main()
{
    printf("Table of y(x) = 2*x*x-x+1\n\n");
    table(y, 0.0, 2.0, 0.5);

    printf("\nTable of cos(x)\n\n");
    table(cos, 0.0, PI, 0.5);
}

double table(double(*f)(), double min, double max, double step)
{
    double a, value;
    for(a = min; a <= max; a += step)
    {
        value = (*f)(a);
        printf("%5.2f %10.4f\n", a, value);
    }
}

double y(double x)
{
    return(2*x*x-x+1);
}
```

Output

```
Table of y(x) = 2*x*x-x+1
    0.00    1.0000
    0.50    1.0000
    1.00    2.0000
    1.50    4.0000
    2.00    7.0000

Table of cos(x)
    0.00    1.0000
    0.50    0.8776
    1.00    0.5403
```

1.50	0.0707
2.00	-0.4161
2.50	-0.8011
3.00	-0.9900

Fig.11.12 Use of pointers to functions

Example 11.8

Write a program to illustrate the use of structure pointers.

A program to illustrate the use of a structure pointer to manipulate the elements of an array of structures is shown in Fig.11.13. The program highlights all the features discussed above. Note that the pointer **ptr** (of type **struct invent**) is also used as the loop control index in **for** loops.

POINTERS TO STRUCTURE VARIABLES

Program

```
struct invent
{
    char   *name[20];
    int    number;
    float  price;
};
main()
{
    struct invent product[3], *ptr;
    printf("INPUT\n\n");
    for(ptr = product; ptr < product+3; ptr++)
        scanf("%s %d %f", ptr->name, &ptr->number, &ptr->price);
    printf("\nOUTPUT\n\n");
    ptr = product;
    while(ptr < product + 3)
    {
        printf("%-20s %5d %10.2f\n",
               ptr->name,
               ptr->number,
               ptr->price);
        ptr++;
    }
}
```

Output

```
INPUT
Washing_machine   5      7500
Electric_iron     12      350
Two_in_one        7     1250

OUTPUT
```

Washing machine	5	7500.00
Electric_iron	12	350.00
Two_in_one	7	1250.00

Fig.11.13 Pointer to structure variables

Example 12.1

Write a program to read data from the keyboard, write it to a file called **INPUT**, again read the same data from the **INPUT** file, and display it on the screen.

A program and the related input and output data are shown in Fig.12.1. We enter the input data via the keyboard and the program writes it, character by character, to the file **INPUT**. The end of the data is indicated by entering an **EOF** character, which is *control-Z* in the reference system. (This may be control-D in other systems). The file INPUT is closed at this signal.

Program

```
#include <stdio.h>

main()
{
    FILE *f1;
    char c;

    printf("Data Input\n\n");
    /* Open the file INPUT */
    f1 = fopen("INPUT", "w");

    /* Get a character from keyboard */
    while((c=getchar()) != EOF)

        /* Write a character to INPUT */
        putc(c,f1);

    /* Close the file INPUT */
    fclose(f1);

    printf("\nData Output\n\n");
    /* Reopen the file INPUT */
    f1 = fopen("INPUT", "r");

    /* Read a character from INPUT*/
    while((c=getc(f1)) != EOF)

        /* Display a character on screen */
        printf("%c",c);

    /* Close the file INPUT */
    fclose(f1);
}
```

Output

Data Input

This is a program to test the file handling
features on this system^Z

Data Output

This is a program to test the file handling
features on this system

Fig.12.1 Character oriented read/write operations on a file

Example 12.2

A file named **DATA** contains a series of integer numbers. Code a program to read these numbers and then write all 'odd' numbers to a file to be called **ODD** and all 'even' numbers to a file to be called **EVEN**.

The program is shown in Fig.12.2. It uses three files simultaneously and therefore we need to define three-file pointers **f1**, **f2** and **f3**.

First, the file **DATA** containing integer values is created. The integer values are read from the terminal and are written to the file **DATA** with the help of the statement

```
putw(number, f1);
```

Notice that when we type -1, the reading is terminated and the file is closed. The next step is to open all the three files, **DATA** for reading, **ODD** and **EVEN** for writing. The contents of **DATA** file are read, integer by integer, by the function **getw(f1)** and written to **ODD** or **EVEN** file after an appropriate test. Note that the statement

```
(number = getw(f1)) != EOF
```

reads a value, assigns the same to **number**, and then tests for the end-of-file mark.

Finally, the program displays the contents of **ODD** and **EVEN** files. It is important to note that the files **ODD** and **EVEN** opened for writing are closed before they are reopened for reading.

HANDLING OF INTEGER DATA FILES

Program

```
#include <stdio.h>
main()
{
    FILE *f1, *f2, *f3;
    int number, i;

    printf("Contents of DATA file\n\n");
    f1 = fopen("DATA", "w");          /* Create DATA file */
    for(i = 1; i <= 30; i++)
    {
        scanf("%d", &number);
        if(number == -1) break;
        putw(number, f1);
    }
    fclose(f1);

    f1 = fopen("DATA", "r");
    f2 = fopen("ODD", "w");
    f3 = fopen("EVEN", "w");

    /* Read from DATA file */
    while((number = getw(f1)) != EOF)
    {
```

```

        if(number %2 == 0)
            putw(number, f3);    /* Write to EVEN file */
        else
            putw(number, f2);    /* Write to ODD file */
    }
    fclose(f1);
    fclose(f2);
    fclose(f3);

    f2 = fopen("ODD","r");
    f3 = fopen("EVEN", "r");
    printf("\n\nContents of ODD file\n\n");

    while((number = getw(f2)) != EOF)
        printf("%4d", number);
    printf("\n\nContents of EVEN file\n\n");

    while((number = getw(f3)) != EOF)
        printf("%4d", number);

    fclose(f2);
    fclose(f3);

}

```

Output

```

Contents of DATA file
111 222 333 444 555 666 777 888 999 000 121 232 343 454 565 -1

Contents of ODD file
111 333 555 777 999 121 343 565

Contents of EVEN file
222 444 666 888    0 232 454

```

Fig.12.2 Operations on integer data

Example 12.3

Write a program to open a file named INVENTORY and store in it the following data:

Item name	Number	Price	Quantity
AAA-1	111	17.50	115
BBB-2	125	36.00	75
C-3	247	31.75	104

Extend the program to read this data from the file INVENTORY and display the inventory table with the value of each item.

The program is given in Fig.12.3. The filename INVENTORY is supplied through the keyboard. Data is read using the function **fscanf** from the file **stdin**, which refers to the terminal and it is then written to the file that is being pointed to by the file pointer **fp**. Remember that the file pointer **fp** points to the file INVENTORY.

After closing the file INVENTORY, it is again reopened for reading. The data from the file, along with the item values are written to the file **stdout**, which refers to the screen. While reading from a file, care should be taken to use the same format specifications with which the contents have been written to the file....é

HANDLING OF FILES WITH MIXED DATA TYPES
(**fscanf** and **fprintf**)

Program

```
#include <stdio.h>

main()
{
    FILE *fp;
    int    number, quantity, i;
    float  price, value;
    char   item[10], filename[10];

    printf("Input file name\n");
    scanf("%s", filename);

    fp = fopen(filename, "w");

    printf("Input inventory data\n\n");
    printf("Item name  Number  Price  Quantity\n");
    for(i = 1; i <= 3; i++)
    {
        fscanf(stdin, "%s %d %f %d",
                item, &number, &price, &quantity);
        fprintf(fp, "%s %d %.2f %d",
                item, number, price, quantity);
    }
    fclose(fp);
    fprintf(stdout, "\n\n");

    fp = fopen(filename, "r");

    printf("Item name  Number  Price  Quantity  Value\n");
    for(i = 1; i <= 3; i++)
    {
        fscanf(fp, "%s %d %f %d", item, &number, &price, &quantity);
        value = price * quantity;
        fprintf(stdout, "%-8s %7d %8.2f %8d %11.2f\n",
                item, number, price, quantity, value);
    }
    fclose(fp);
}
```

Output

Input file name

INVENTORY

Input inventory data

Item name	Number	Price	Quantity
AAA-1	111	17.50	115
BBB-2	125	36.00	75
C-3	247	31.75	104

Item name	Number	Price	Quantity	Value
AAA-1	111	17.50	115	2012.50
BBB-2	125	36.00	75	2700.00
C-3	247	31.75	104	3302.00

Fig.12.3 Operations on mixed data types

Example 12.4

Write a program to illustrate error handling in file operations.

The program shown in Fig.12.4 illustrates the use of the **NULL** pointer test and **feof** function. When we input filename as TETS, the function call

```
fopen("TETS", "r");
```

returns a **NULL** pointer because the file TETS does not exist and therefore the message "Cannot open the file" is printed out.

Similarly, the call **feof(fp2)** returns a non-zero integer when the entire data has been read, and hence the program prints the message "Ran out of data" and terminates further reading.

ERROR HANDLING IN FILE OPERATIONS

Program

```
#include <stdio.h>

main()
{
    char *filename;
    FILE *fp1, *fp2;
    int i, number;
```

```

        fp1 = fopen("TEST", "w");
        for(i = 10; i <= 100; i += 10)
            putw(i, fp1);

        fclose(fp1);

        printf("\nInput filename\n");

open_file:
    scanf("%s", filename);

    if((fp2 = fopen(filename, "r")) == NULL)
    {
        printf("Cannot open the file.\n");
        printf("Type filename again.\n\n");
        goto open_file;
    }

    else

        for(i = 1; i <= 20; i++)
        {
            number = getw(fp2);
            if(feof(fp2))
            {
                printf("\nRan out of data.\n");
                break;
            }
            else
                printf("%d\n", number);
        }

        fclose(fp2);
}

```

Output

```

Input filename
TETS
Cannot open the file.
Type filename again.

TEST
10
20
30
40

```

50
60
70
80
90
100

Ran out of data.

Fig.12.4 Illustration of error handling

Example 12.5

Write a program that uses the functions **ftell** and **fseek**.

A program employing **ftell** and **fseek** functions is shown in Fig.12.5. We have created a file **RANDOM** with the following contents:

Position ----> 0 1 2 25
Character
stored ----> A B C Z

We are reading the file twice. First, we are reading the content of every fifth position and printing its value along with its position on the screen. The second time, we are reading the contents of the file from the end and printing the same on the screen.

During the first reading, the file pointer crosses the end-of-file mark when the parameter **n** of **fseek(fp,n,0)** becomes 30. Therefore, after printing the content of position 30, the loop is terminated.

For reading the file from the end, we use the statement

fseek(fp,-1L,2);

to position the file pointer to the last character. Since every read causes the position to move forward by one position, we have to move it back by two positions to read the next character. This is achieved by the function

fseek(fp, -2L, 1);

in the while statement. This statement also tests whether the file pointer has crossed the file boundary or not. The loop is terminated as soon as it crosses it.

ILLUSTRATION OF **fseek** & **ftell** FUNCTIONS

Program

```
#include <stdio.h>
main()
{
    FILE *fp;
    long n;
    char c;
```

```

fp = fopen("RANDOM", "w");
while((c = getchar()) != EOF)
    putc(c, fp);

printf("No. of characters entered = %ld\n", ftell(fp));
fclose(fp);
fp = fopen("RANDOM", "r");
n = 0L;

while(feof(fp) == 0)
{
    fseek(fp, n, 0); /* Position to (n+1)th character */
    printf("Position of %c is %ld\n", getc(fp), ftell(fp));
    n = n+5L;
}
putchar('\n');

fseek(fp, -1L, 2); /* Position to the last character */
do
{
    putchar(getc(fp));
}
while(!fseek(fp, -2L, 1));
fclose(fp);
}

```

Output

```

ABCDEFGHIJKLMNOPQRSTUVWXYZ^Z
No. of characters entered = 26
Position of A is 0
Position of F is 5
Position of K is 10
Position of P is 15
Position of U is 20
Position of Z is 25
Position of   is 30

ZYXWVUTSRQPONMLKJIHGFEDCBA

```

Fig.12.5 Illustration of *fseek* and *ftell* functions

Example 12.6

Write a program to append additional items to the file INVENTORY and print the total contents of the file.

The program is shown in Fig.12.6. It uses a structure definition to describe each item and a function **append()** to add an item to the file.

On execution, the program requests for the filename to which data is to be appended. After appending the items, the position of the last character in the file is assigned to **n** and then the file is closed.

The file is reopened for reading and its contents are displayed. Note that reading and displaying are done under the control of a **while** loop. The loop tests the current file position against **n** and is terminated when they become equal.

APPENDING ITEMS TO AN EXISTING FILE

Program

```
#include <stdio.h>

struct invent_record
{
    char    name[10];
    int     number;
    float   price;
    int     quantity;
};

main()
{
    struct invent_record item;
    char    filename[10];
    int     response;
    FILE    *fp;
    long    n;

    void append (struct invent_record 8x, file *y);

    printf("Type filename:");
    scanf("%s", filename);

    fp = fopen(filename, "a+");
    do
    {
        append(&item, fp);
        printf("\nItem %s appended.\n", item.name);
        printf("\nDo you want to add another item\
        (1 for YES /0 for NO)?");
        scanf("%d", &response);
    } while (response == 1);

    n = ftell(fp);          /* Position of last character */
    fclose(fp);

    fp = fopen(filename, "r");
```

```

        while(ftell(fp) < n)
        {
            fscanf(fp,"%s %d %f %d",
                item.name, &item.number, &item.price, &item.quantity);
            fprintf(stdout,"%-8s %7d %8.2f %8d\n",
                item.name, item.number, item.price, item.quantity);
        }
        fclose(fp);
    }
}

void append(struct invent_record *product, File *ptr)
{
    printf("Item name:");
    scanf("%s", product->name);

    printf("Item number:");
    scanf("%d", &product->number);

    printf("Item price:");
    scanf("%f", &product->price);

    printf("Quantity:");
    scanf("%d", &product->quantity);

    fprintf(ptr, "%s %d %.2f %d",
        product->name,
        product->number,
        product->price,
        product->quantity);
}

```

Output

```

Type filename:INVENTORY
Item name:XXX
Item number:444
Item price:40.50
Quantity:34

Item XXX appended.
Do you want to add another item(1 for YES /0 for NO)?1
Item name:YYY
Item number:555
Item price:50.50
Quantity:45

Item YYY appended.
Do you want to add another item(1 for YES /0 for NO)?0
AAA-1      111      17.50      115
BBB-2      125      36.00       75
C-3        247      31.75     104
XXX         444      40.50       34
YYY         555      50.50       45

```

Fig.12.6 Adding items to an existing file

Example 12.7

Write a program that will receive a filename and a line of text as command line arguments and write the text to the file.

Figure 12.7 shows the use of command line arguments. The command line is

```
F12_7 TEXT AAAAAA BBBB BB CCCCC DDDDD EEEEE FFFFF GGGGG
```

Each word in the command line is an argument to the **main** and therefore the total number of arguments is 9.

The argument vector **argv[1]** points to the string TEXT and therefore the statement

```
fp = fopen(argv[1], "w");
```

opens a file with the name TEXT. The **for** loop that follows immediately writes the remaining 7 arguments to the file TEXT.

COMMAND LINE ARGUMENTS

Program

```
#include <stdio.h>

main(argc, argv)
int  argc;                /*  argument count          */
char *argv[];             /*  list of arguments       */
{
    FILE  *fp;
    int   i;
    char word[15];

    fp = fopen(argv[1], "w"); /* open file with name argv[1] */
    printf("\nNo. of arguments in Command line = %d\n\n", argc);
    for(i = 2; i < argc; i++)
        fprintf(fp, "%s ", argv[i]); /* write to file argv[1] */
    fclose(fp);

    /* Writing content of the file to screen */

    printf("Contents of %s file\n\n", argv[1]);
    fp = fopen(argv[1], "r");
    for(i = 2; i < argc; i++)
    {
        fscanf(fp, "%s", word);
        printf("%s ", word);
    }
}
```

```
    }

    fclose(fp);
    printf("\n\n");

    /* Writing the arguments from memory */

    for(i = 0; i < argc; i++)
        printf("%*s \n", i*5,argv[i]);
}
```

Output

C>F12_7 TEXT AAAAAA BBBBBB CCCCCC DDDDDD EEEEE EFFFFFF GGGGG

No. of arguments in Command line = 9

Contents of TEXT file

AAAAAA BBBBBB CCCCCC DDDDDD EEEEE EFFFFFF GGGGG

C:\C\F12_7.EXE

TEXT

AAAAAA

BBBBBB

CCCCC

DDDDD

EEEE E

FFFFFF

GGGGG

Fig.12.7 Use of command line arguments

CASE STUDIES

1. Insertion in a Sorted List

The task of inserting a value into the current location in a sorted linked list involves two operations:

1. Finding the node before which the new node has to be inserted. We call this node as 'Key node'.
2. Creating a new node with the value to be inserted and inserting the new node by manipulating pointers appropriately.

In order to illustrate the process of insertion, we use a sorted linked list created by the create function discussed in Example 13.3. Figure 13.11 shows a complete program that creates a list (using sorted input data) and then inserts a given value into the correct place using function insert.

INSERTING A NUMBER IN A SORTED LIST

Program

```
#include <stdio.h>
#include<stdio.h>
#define NULL 0

struct linked_list
{
    int number;
    struct linked-list *next;
};
typedef struct linked_lit node;

main()
{
    int n;
    node *head;
    void create(node *p);
    node *insert(node *p, int n);
    void print(node *p);

    head = (node *)malloc(sizeof(node));

    create(head);
    printf("\n");
    printf("Original list: ");
    print(head);
    printf("\n\n");
    printf("Input number to be inserted: ");
    scanf("%d", &n);

    head = inert(head,n);
    printf("\n");
    printf("New list: ");
```

```

    print(head);
}
void create(node *list)
{
    printf("Input a number \n");
    printf("(type -999 at end): ");
    scanf("%d", &list->number);

    if(list->number == -999)
    {
        list->next = NULL;
    }
    else /* create next node */
    {
        list->next = (node *)malloc(sizeof(node));
        create(list->next);
    }
    return:
}

void print(node *list)
{
    if(list->next != NULL)
    {
        printf("%d -->", list->number);

        if(list->next->next == NULL)
            printf("%d", list->next->number);

        print(list->next);
    }
    return:
}

node *insert(node *head, int x)
{
    node *p1, *p2, *p;
    p1 = NULL;
    p2 = head; /* p2 points to first node */

    for( ; p2->number < x; p2 = p2->next)
    {
        p1 = p2;

        if(p2->next->next == NULL)
        {
            p2 = p2->next; /* insertion at end */
            break;
        }
    }

    /*key node found and insert new node */

```

```

    p = (node )malloc(sizeof(node)); / space for new node */
    p->number = x; /* place value in the new node */
    p->next = p2; /*link new node to key node */
    if (p1 == NULL)
        head = p; /* new node becomes the first node */
    else
        p1->next = p; /* new node inserted in middle */
    return (head);
}

```

Output

```

Input a number
(type -999 at end ); 10

Input a number
(type -999 at end ); 20

Input a number
(type -999 at end ); 30

Input a number
(type -999 at end ); 40

Input a number
(type -999 at end ); -999

Original list:      10 -->20-->30-->40-->-999

Input number to be inserted: 25
New list: 10-->20-->25-->30-->40-->-999


```

Fig.13.11 Inserting a number in a sorted linked list


The function takes two arguments, one the value to be inserted and the other a pointer to the linked list. The function uses two pointers, **p1** and **p2** to search the list. Both the pointers are moved down the list with **p1** trailing **p2** by one node while the value **p2** points to is compared with the value to be inserted. The 'key node' is found when the number **p2** points to is greater (or equal) to the number to be inserted.

Once the key node is found, a new node containing the number is created and inserted between the nodes pointed to by **p1** and **p2**. The figures below illustrate the entire process.


key node




At the start of the search



When key node is found



When new node is created



When new node is inserted

2. Building a Sorted List

The program in fig. 13.11 can be used to create a sorted list. This is possible by creating 'one item' list using the create function and then inserting the remaining items one after another using insert function.

A new program that would build a sorted list from a given list of numbers is shown in Fig. 13.12. The **main** function creates a 'base node' using the first number in the list and then calls the function **insert_sort** repeatedly to build the entire sorted list. It uses the same sorting algorithm discussed above but does not use any dummy node. Note that the last item points to NULL.

CREATION OF SORTED LIST FROM A GIVEN LIST OF NUMBERS

Program

```
#include <stdio.h>
#include <stdlib.h>
#define NULL 0

struct linked_list
{
    int number;
    struct linked_list *next;
};
typedef struct linked_list node;

main ()
{
    int n;
    node *head = NULL;
    void print(node *p);
    node *insert_Sort(node *p, int n);

    printf("Input the list of numbers.\n");
    printf("At end, type -999.\n");
    scanf("%d",&n);

    while(n != -999)
    {
        if(head == NULL)          /* create 'base' node */
        {
            head = (node *)malloc(sizeof(node));
            head->number = n;
            head->next = NULL;

        }

        else                      /* insert next item */
        {
            head = insert_sort(head,n);
        }
        scanf("%d", &n);
    }
    printf("\n");
    print(head);
    print("\n");
}

node *insert_sort(node *list, int x)
{
    node *p1, *p2, *p;
    p1 = NULL;
```

```

p2 = list; /* p2 points to first node */

for( ; p2->number < x ; p2 = p2->next)
{
    p1 = p2;

    if(p2->next == NULL)
    {
        p2 = p2->next;          /* p2 set to NULL */
        break;                  /* insert new node at end */
    }
}

/* key node found */
p = (node *)malloc(sizeof(node)); /* space for new node */
p->number = x;                    /* place value in the new node */
p->next = p2;                     /* link new node to key node */

if (p1 == NULL)
    list = p; /* new node becomes the first node */
else
    p1->next = p; /* new node inserted after 1st node */
return (list);
}

void print(node *list)
{
    if (list == NULL)
        printf("NULL");
    else
    {
        printf("%d-->", list->number);
        print(list->next);
    }
    return;
}

```

Output

```

Input the list of number.
At end, type - 999.
80 70 50 40 60 -999

40-->50-->60-->70-->80 -->NULL

Input the list of number.
At end, type -999.
40 70 50 60 80 -999

40-->50-->60-->70-->80-->NULL

```

Fig.13.12 Creation of sorted list from a given list of numbers

Example 13.1

Write a program that uses a table of integers whose size will be specified interactively at run time.

The program is given in Fig.13.2. It tests for availability of memory space of required size. If it is available, then the required space is allocated and the address of the first byte of the space allocated is displayed. The program also illustrates the use of pointer variable for storing and accessing the table values.

Program

```
#include <stdio.h>
#include <stdlib.h>
#define NULL 0

main()
{
    int *p, *table;
    int size;

    printf("\nWhat is the size of table?");
    scanf("%d",&size);

    printf("\n")

        /*-----Memory allocation -----*/
    if((table = (int*)malloc(size *sizeof(int))) == NULL)
    {
        printf("No space available \n");
        exit(1);
    }
    printf("\n Address of the first byte is  %u\n", table);
    /* Reading table values*/
    printf("\nInput table values\n");

    for (p=table; p<table + size; p++)
        scanf("%d",p);

    /* Printing table values in reverse order*/
    for (p = table + size -1; p >= table; p --)
        printf("%d is stored at address %u \n",*p,p);

}
```

Output

```
What is the size of the table? 5
Address of the first byte is 2262

Input table values
11 12 13 14 15

15 is stored at address 2270
14 is stored at address 2268
13 is stored at address 2266
12 is stored at address 2264
11 is stored at address 2262
```

Fig.13.2 Memory allocation with **malloc**

Example 13.2

Write a program to store a character string in a block of memory space created by **malloc** and then modify the same to store a larger string.

The program is shown in Fig. 13.3. The output illustrates that the original buffer size obtained is modified to contain a larger string. Note that the original contents of the buffer remains same even after modification of the original size.

USE OF realloc AND free FUNCTIONS

Program

```
#include <stdio.h>
#include<stdlib.h>
#define NULL 0

main()
{
    char *buffer;

    /* Allocating memory */
    if((buffer = (char *)malloc(10)) == NULL)
    {
        printf("malloc failed.\n");
        exit(1);
    }

    printf("Buffer of size %d created \n",_msize(buffer));
    strcpy(buffer, "HYDERABAD");
    printf("\nBuffer contains: %s \n ", buffer);

    /* Reallocation */
    if((buffer = (char *)realloc(buffer, 15)) == NULL)
    {
        printf("Reallocation failed. \n");
        exit(1);
    }
    printf("\nBuffer size modified. \n");
    printf("\nBuffer still contains: %s \n",buffer);

    strcpy(buffer, "SECUNDERBAD");
    printf("\nBuffer now contains: %s \n",buffer);

    /* Freeing memory */
    free(buffer);
}
```

Output

```
Buffer of size 10 created
Buffer contains: HYDERABAD
Buffer size modified
Buffer still contains: HYDERABAD
Buffer now contains: SECUNDERABAD
```

Fig . 13.3 Reallocation and release of memory space

Example 13.3

Write a program to create a linear linked list interactively and print out the list and the total number of items in the list.

The program shown in Fig.13.7 first allocates a block of memory dynamically for the first node using the statement

head = (node *)malloc(sizeof(node));

which returns a pointer to a structure of type **node** that has been type defined earlier. The linked list is then created by the function **create**. The function requests for the number to be placed in the current node that has been created. If the value assigned to the current node is -999, then null is assigned to the pointer variable **next** and the list ends. Otherwise, memory space is allocated to the next node using again the **malloc** function and the next value is placed into it. Not that the function **create** calls itself recursively and the process will continue until we enter the number -999.

The items stored in the linked list are printed using the function **print** which accept a pointer to the current node as an argument. It is a recursive function and stops when it receives a NULL pointer. Printing algorithm is as follows;

1. Start with the first node.
2. While there are valid nodes left to print
 - a) print the current item and
 - b) advance to next node

Similarly, the function **count** counts the number of items in the list recursively and return the total number of items to the **main** function. Note that the counting does not include the item -999 (contained in the dummy node).

CREATING A LINEAR LINKED LIST

Program

```
#include<stdio.h>
#include<stdlib.h>
#define NULL 0

struct linked_list
{
    int number;
    struct linked_list *next;
};
typedef struct linked_list node; /* node type defined */

main()
```

```

{
    node *head;
    void create(node *p);
    int count(node *p);
    void print(node *p);
    head = (node *)malloc(sizeof(node));
    create(head);
    printf("\n");
    printf(head);
    printf("\n");
    printf("\nNumber of items = %d \n", count(head));
}
void create(node *list)
{
    printf("Input a number\n");
    printf("(type -999 at end): ");
    scanf("%d", &list->number); /* create current node */

    if(list->number == -999)
    {
        list->next = NULL;
    }
    else /*create next node */
    {
        list->next = (node *)malloc(sizeof(node));
        create(list->next);
    }
    return;
}
void print(node *list)
{
    if(list->next != NULL)
    {
        printf("%d-->", list->number); /* print current item */

        if(list->next->next == NULL)
            printf("%d", list->next->number);

        printf(list->next); /* move to next item */
    }
    return;
}

int count(node *list)
{
    if(list->next == NULL)
        return (0);
    else
        return(1+ count(list->next));
}

```

Output

```
Input a number
(type -999 to end); 60

Input a number
(type -999 to end); 20

Input a number
(type -999 to end); 10

Input a number
(type -999 to end); 40

Input a number
(type -999 to end); 30

Input a number
(type -999 to end); 50

Input a number
(type -999 to end); -999

60 -->20 -->10 -->40 -->30 -->50 --> -999

Number of items = 6
```

Fig. 13.7 *Creating a linear linked list*

Example 13.4

Write a function to insert a given item *before* a specified node known as key node.

The function **insert** shown in Fig.13.8 requests for the item to be inserted as well as the 'key node'. If the insertion happens to be at the beginning, then memory space is created for the new node, the value of new item is assigned to it and the pointer **head** is assigned to the next member. The pointer **new** which indicates the beginning of the new node is assigned to **head**. Note the following statements:

```
new->number = x;
new->next = head;
head = new;
```

FUNCTION INSERT

```
node *insert(node *head)
{
    node *find(node *p, int a);
    node *new;           /* pointer to new node */
    node *n1;           /* pointer to node preceding key node */
    int key;
```

```

int x;                /* new item (number) to be inserted */

printf("Value of new item?");
scanf("%d", &x);
printf("Value of key item ? (type -999 if last) ");
scanf("%d", &key);

if(head->number == key)    /* new node is first */
{
    new = (node *)malloc(size of(node));
    new ->number = x;
    new->next = head;
    head = new;
}
else    /* find key node and insert new node */
{
    /* before the key node */
    n1 = find(head, key);    /* find key node */

    if(n1 == NULL)
        printf("\n key is not found \n");
    else    /* insert new node */
    {
        new = (node *)malloc(sizeof(node));
        new->number = x;
        new->next = n1->next;
        n1->next = new;
    }
}
return(head);
}
node *find(node *lists, int key)
{
    if(list->next->number == key)    /* key found */
        return(list);
    else

        if(list->next->next == NULL)    /* end */
            return(NULL);
    else
        find(list->next, key);
}

```

Fig. 13.8 A function for inserting an item into a linked list


Example 13.5

Write a function to delete a specified node.

A function to delete a specified node is given in Fig.13.9. The function first checks whether the specified item belongs to the first node. If yes, then the pointer to the second node is temporarily assigned the pointer variable **p**, the memory space occupied by the first node is freed and the


location of the second node is assigned to **head**. Thus, the previous second node becomes the first node of the new list.

If the item to be deleted is not the first one, then we use the **find** function to locate the position of 'key node' containing the item to be deleted. The pointers are interchanged with the help of a temporary pointer variable making the pointer in the preceding node to point to the node following the key node. The memory space of key node that has been deleted is freed. The figure below shows the relative position of the key node.



The execution of the following code deletes the key node.

```
p = n1->next->next;
free (n1->next);
n1->next = p;
```



FUNCTION DELETE

```
node *delete(node *head)
{
    node *find(node *p, int a);
    int key;      /* item to be deleted */
    node *n1;     /* pointer to node preceding key node */
    node *p;      /* temporary pointer */

    printf("\n What is the item (number) to be deleted?");
    scanf("%d", &key);

    if(head->number == key) /* first node to be deleted) */
    {
        p = head->next;      /* pointer to 2nd node in list */
        free(head);          /* release space of key node */
        head = p;            /* make head to point to 1st node */
    }
    else
    {
        n1 = find(head, key);
        if(n1 == NULL)
            printf("\n key not found \n");
        else
            /* delete key node */
            {
                p = n1->next->next;      /* pointer to the node
                                         following the keynode */
            }
    }
}
```

```

        free(n1->next);          /* free key node */
        n1->next = p;           /* establish link */
    }
}
return(head);
}

/* USE FUNCTION find() HERE */

```

Fig.13.9 *A function for deleting an item from linked list*

Inventory-project 2

/*****

Application: Invenry Management System
Compiled on: Borland Turbo C++ 3.0
Programmer: Geetika Mukhi

*****/

```
#include <conio.h>
#include <stdio.h>
#include <stdlib.h>
#include <dos.h>
#include <graphics.h>
#include <string.h>

#define TRUE 1
#define FALSE 0

/* List of Global variables used in the application*/
int mboxbrdrclr,mboxbgclr,mboxfgclr; /* To set colors for all message
boxes in the application*/
int menutxtbgclr,menutxtfgclr,appframeclr; /* To set the frame and color's
for menu items's*/
int section1_symb,section1_bgclr,section1_fgclr; /* To set color of section 1, the
region around the menu options*/
int section2_symb,section2_bgclr,section2_fgclr; /* To set color of section 2, the
section on the right of the menu options*/
int fEdit;
int animcounter;

static struct struct_stock /* Main database structure*/
{
    char itemcode[8];
    char itemname[50];
    float itemrate;
    float itemqty;
    int minqty; /*Used for Reorder level, which
is the minimum no of stock*/
}inv_stock;

struct struct_bill
{
    char itemcode[8];
    char itemname[50];
    float itemrate;
    float itemqty;
    float itemtot;
}item_bill[100];

char password[8];

const long int stocksize=sizeof(inv_stock); /*stocksize stores the size of the
struct_stock*/
float tot_investment;
int numItems; /*To count the no of items in the
stock*/
int button,column,row; /*To allow mouse operations in the
application*/

FILE *dbfp; /*To perform database file operations
on "inv_stock.dat"*/

int main(void)
```

Inventory-project 2

```

{
    float issued_qty;
    char userchoice,code[8];
    int flag,i,itemsold;
    float getInvestmentInfo(void);
    FILE *ft;
    int result;
    getConfiguration();

    /* Opens & set 'dbfp' globally so that it is accessible from anywhere in the
application*/
    dbfp=fopen("d:\invstoc.dat","r+");
    if(dbfp==NULL)
    {
        clrscr();
        printf("\nDatabase does not exists.\nPress Enter key to create it. To exit,
press any other key.\n ");
        fflush(stdin);
        if(getch()==13)
        {
            dbfp=fopen("d:\invstoc.dat","w+");
            printf("\nThe database for the application has been created.\nYou must restart
the application.\nPress any key to continue.\n");
            fflush(stdin);
            getch();
            exit(0);
        }
        else
        {
            exit(0);
        }
    }
    /* Application control will reach here only if the database file has been opened
successfully*/
    if(initmouse()==0)
        messagebox(10,33,"Mouse could not be loaded.,"Error ","'
',mboxbrdrclr,mboxbgclr,mboxfgclr,0);
    showmouseptr();
    _setcursortype(_NOCURS);

    while(1)
    {
        clrscr();
        fEdit=FALSE;
        ShowMenu();
        numItems=0;
        rewind(dbfp);

        /* To calculate the number of records in the database*/
        while(fread(&inv_stock,stocksize,1,dbfp)==1)
            ++numItems;
        textcolor(menuxtfgclr);
        textbackground(menuxtbgclr);
        gotopos(23,1);
        cprintf("Total Items in Stock: %d",numItems);
        textcolor(BLUE);
        textbackground(BROWN);
        fflush(stdin);

        /*The application will wait for user response */
        userchoice=getUserResponse();
        switch(userchoice)
        {

```

Inventory-project 2

```

/* To Close the application*/
case '0':
    BackupDatabase(); /*Backup the Database file to secure data*/
    fflush();
    fclose(dbfp);
    fcloseall();
    print2screen(12,40,"Thanks for Using the application.",BROWN,BLUE,0);
    sleep(1);
    setdefaultmode();
    exit(0);

/* To Add an item*/
case '1':
    if(getdata()==1)
    {
        fseek(dbfp,0,SEEK_END);
        /*write the item information into the database*/
        fwrite(&inv_stock,stocksize,1,dbfp);
        print2screen(13,33,"The item has been successfully added. ",BROWN,BLUE,0);
        getch();
    }
    break;

/* To edit the item information*/
case '2':
    print2screen(2,33,"Enter Item
Code>",BROWN,BLUE,0);gotopos(2,54);fflush(stdin);
    scanf("%s",&code);
    fEdit=TRUE;
    if(CheckId(code)==0)
    {
        if(messagebox(0,33,"Press Enter key to edit the item.,"Confirm",'
',mboxbrdrclr,mboxbgclr,mboxfgclr,0)!=13)
        {
            messagebox(10,33,"The item information could not be modified. Please
try again.,"Edit",' ',mboxbrdrclr,mboxbgclr,mboxfgclr,0);
            fEdit=FALSE;
            break;
        }
        fEdit=TRUE;
        getdata();
        fflush(stdin);
        fseek(dbfp,-stocksize,SEEK_CUR);
        fwrite(&inv_stock,stocksize,1,dbfp);
    }
    else
        messagebox(10,33,"The item is not available in the database.,"No records
found",' ',mboxbrdrclr,mboxbgclr,mboxfgclr,0);
        fEdit=FALSE;
        break;

/* To show information about an an Item*/
case '3':
    print2screen(2,33,"Enter Item Code:
",BROWN,BLUE,0);gotopos(2,55);fflush(stdin);
    scanf("%s",&code);
    flag=0;
    rewind(dbfp);
    while(fread(&inv_stock,stocksize,1,dbfp)==1)
    {
        if(strcmp(inv_stock.itemcode,code)==0)
        {
            DisplayItemInfo();

```

Inventory-project 2

```

        flag=1;
    }
}
if(flag==0)
    messagebox(10,33,"The item is not available.", "No records found ", '
',mboxbrdrclr,mboxbgclr,mboxfgclr,0);
    break;

/* To show information about all items in the database*/
case '4':
    if(numItems==0)
        messagebox(10,33,"No items are available. ", "Error ", '
',mboxbrdrclr,mboxbgclr,mboxfgclr,0);
        textcolor(BLUE);
        textbackground(BROWN);
        gotopos(3,33);
        printf("Number of Items Available in Stock:  %d",numItems);
        gotopos(4,33);
        getInvestmentInfo();
        printf("Total Investment :Rs.%.2f",tot_investment);
        gotopos(5,33);
        printf("Press Enter To View. Otherwise Press Any Key...");fflush(stdin);
        if(getch()==13)
        {
            rewind(dbfp);
            while(fread(&inv_stock,stocksize,1,dbfp)==1); /*List All records*/
                DisplayItemRecord(inv_stock.itemcode);
        }
        textcolor(BLUE);
        break;

/* To issue Items*/
case '5':
    itemsold=0;
    i=0;
    top:
    print2screen(3,33,"Enter Item Code:
",BROWN,BLUE,0);fflush(stdin);gotopos(3,55);
    scanf("%s",&code);
    if(CheckId(code)==1)
        if(messagebox(10,33,"The item is not available.", "No records found ", '
',mboxbrdrclr,mboxbgclr,mboxfgclr,0)==13)
            goto top;
        else
            goto bottom;
    rewind(dbfp);
    while(fread(&inv_stock,stocksize,1,dbfp)==1)
    {
        if(strcmp(inv_stock.itemcode,code)==0) /*To check if the item code is
available in the database*/
        {
            issued_qty=IssueItem();
            if(issued_qty > 0)
            {
                itemsold+=1;
                strcpy(item_bill[i].itemcode,inv_stock.itemcode);
                strcpy(item_bill[i].itemname,inv_stock.itemname);
                item_bill[i].itemqty=issued_qty;
                item_bill[i].itemrate=inv_stock.itemrate;
                item_bill[i].itemtot=inv_stock.itemrate*issued_qty;
                i+=1;
            }
        }
        print2screen(19,33,"would you like to issue another

```

```

Inventory-project 2
item(Y/N)?" ,BROWN,BLUE,0);fflush(stdin);gotopos(19,45);
    if(toupper(getch())=='Y')
        goto top;
    bottom:
    break;
}
}
break;

/* Items to order*/
case '6':
    if(numItems<=0)
    {
        messagebox(10,33,"No items are available. ","Items Not Found ",'
',mboxbrdrclr,mboxbgclr,mboxfgclr,0);
        break;
    }
    print2screen(3,33,"Stock of these items is on the minimum
level:",BROWN,RED,0);fflush(stdin);
    flag=0;
    fflush(stdin);
    rewind(dbfp);
    while(fread(&inv_stock,stocksize,1,dbfp)==1)
    {
        if(inv_stock.itemqty <= inv_stock.minqty)
        {
            DisplayItemInfo();
            flag=1;
        }
    }
    if(flag==0)
        messagebox(10,33,"No item is currently at reorder level. ","Reorder
Items", ' ',mboxbrdrclr,mboxbgclr,mboxfgclr,0);
    break;

    default:
        messagebox(10,33,"The option you have entered is not available. ","Invalid
Option ", ' ',mboxbrdrclr,mboxbgclr,mboxfgclr,0);
        break;
}
}
}

/*Display Menu & Skins that the user will see*/
ShowMenu()
{
    if(section1_bgclr != BROWN || section1_symb != ' ')
        fillcolor(2,1,23,39,section1_symb,section1_bgclr,section1_fgclr,0);
    if(section2_bgclr != BROWN || section2_symb != ' ')
        fillcolor(2,40,23,79,section2_symb,section2_bgclr,section2_fgclr,0);
    print2screen(2,2,"1: Add an Item",menutxtbgclr,menutxtfgclr,0);
    print2screen(4,2,"2: Edit Item Information",menutxtbgclr,menutxtfgclr,0);
    print2screen(6,2,"3: Show Item Information",menutxtbgclr,menutxtfgclr,0);
    print2screen(8,2,"4: View Stock Report",menutxtbgclr,menutxtfgclr,0);
    print2screen(10,2,"5: Issue Items from Stock",menutxtbgclr,menutxtfgclr,0);
    print2screen(12,2,"6: View Items to be Ordered ",menutxtbgclr,menutxtfgclr,0);
    print2screen(14,2,"0: Close the application",menutxtbgclr,menutxtfgclr,0);

    htskin(0,0,' ',80,appframeclr,LIGHTGREEN,0);
    htskin(1,0,' ',80,appframeclr,LIGHTGREEN,0);
    vtskin(0,0,' ',24,appframeclr,LIGHTGREEN,0);
    vtskin(0,79,' ',24,appframeclr,LIGHTGREEN,0);
    htskin(24,0,' ',80,appframeclr,LIGHTGREEN,0);

```

```

                                Inventory-project 2
    vtskin(0,31,' ',24,appframeclr,LIGHTGREEN,0);
    return;
}

/*Wait for response from the user & returns choice*/
getUserResponse()
{
    int ch,i;
    animcounter=0;

    while(!kbhit())
    {
        getmousepos(&button,&row,&column);

        /*To show Animation*/
        BlinkText(0,27,"Inventory Management System",1,YELLOW,RED,LIGHTGRAY,0,50);
        animcounter+=1;

        i++;
        if(button==1 && row==144 && column>=16 && column<=72) /*Close*/
            return('0');
        if(button==1 && row==16 && column>=16 && column<=136) /*Add New Item*/
            return('1');
        if(button==1 && row==32 && column>=16 && column<=144) /*Edit Item*/
            return('2');
        if(button==1 && row==48 && column>=16 && column<=160) /*Show an Item*/
            return('3');
        if(button==1 && row==64 && column>=16 && column<=104) /*Stock Report*/
            return('4');
        if(button==1 && row==80 && column>=16 && column<=144) /*Issue an Item*/
            return('5');
        if(button==1 && row==96 && column>=16 && column<=152) /*Items to order*/
            return('6');
    }
    ch=getch();
    return ch;
}

/*Reads a valid id and its information,returns 0 if id already exists*/
getdata()
{
    char tmp[8];
    float tst;
    _setcursortype(_NORMALCURSOR);
    print2screen(3,33,"Enter Item Code: ",BROWN,BLUE,0);fflush(stdin);gotopos(3,53);
    scanf("%s",&tmp);
    if(CheckId(tmp)==0 && fEdit == FALSE)
    {
        messagebox(10,33,"The id already exists. ","Error ','
',mboxbrdrclr,mboxbgclr,mboxfgclr,0);
        return 0;
    }
    strcpy(inv_stock.itemcode,tmp); /*Means got a correct item code*/
    print2screen(4,33,"Name of the Item: ",BROWN,BLUE,0);fflush(stdin);gotopos(4,53);
    gets(inv_stock.itemname);
    print2screen(5,33,"Price of Each Unit:
",BROWN,BLUE,0);fflush(stdin);gotopos(5,53);
    scanf("%f",&inv_stock.itemrate);
    print2screen(6,33,"Quantity: ",BROWN,BLUE,0);fflush(stdin);gotopos(6,53);
    scanf("%f",&inv_stock.itemqty);
    print2screen(7,33,"Reorder Level: ",BROWN,BLUE,0);fflush(stdin);gotopos(7,53);
    scanf("%d",&inv_stock.minqty);
    _setcursortype(_NOCURSOR);

```

Inventory-project 2

```

    return 1;
}

/*Returns 0 if the id already exists in the database, else returns 1*/
int CheckId(char item[8])
{
    rewind(dbfp);
    while(fread(&inv_stock,stocksize,1,dbfp)==1)
        if(strcmp(inv_stock.itemcode,item)==0)
            return(0);
    return(1);
}

/*Displays an Item*/
DisplayItemRecord(char idno[8])
{
    rewind(dbfp);
    while(fread(&inv_stock,stocksize,1,dbfp)==1)
        if(strcmp(idno,inv_stock.itemcode)==0)
            DisplayItemInfo();
    return;
}

/*Displays an Item information*/
DisplayItemInfo()
{
    int r=7;
    textcolor(menuxtfgclr);
    textbackground(menuxtbgclr);
    gotopos(r,33);
    printf("Item Code: %s",inv_stock.itemcode);
    gotopos(r,33);
    printf("Item Code: %s",inv_stock.itemcode);
    gotopos(r+1,33);
    printf("Name of the Item: %s",inv_stock.itemname);
    gotopos(r+1,33);
    printf("Name of the Item: %s",inv_stock.itemname);
    gotopos(r+2,33);
    printf("Price of each unit: %.2f",inv_stock.itemrate);
    gotopos(r+2,33);
    printf("Price of each unit: %.2f",inv_stock.itemrate);
    gotopos(r+3,33);
    printf("Quantity in Stock: %.4f",inv_stock.itemqty);
    gotopos(r+3,33);
    printf("Quantity in Stock: %.4f",inv_stock.itemqty);
    gotopos(r+4,33);
    printf("Reorder Level: %d",inv_stock.minqty);
    gotopos(r+4,33);
    printf("Reorder Level: %d",inv_stock.minqty);
    gotopos(r+5,33);
    printf("\nPress Any Key...");fflush(stdin);getch();
    textbackground(BROWN);
    textcolor(BLUE);
    return;
}

/*This function will return 0 if an item cannot issued, else issues the item*/
IssueItem()
{
    float issueqty;
    DisplayItemInfo();
    print2screen(15,33,"Enter Quantity: ",BROWN,BLUE,0);fflush(stdin);gotopos(15,49);
    scanf("%f",&issueqty);
}

```

Inventory-project 2

```

/*If the stock of the item is greater than minimum stock*/
if((inv_stock.itemqty - issueqty) >= inv_stock.minqty)
{
    textcolor(BLUE);
    textbackground(BROWN);
    gotopos(18,33);
    cprintf("%.4f Item(s) issued.",issueqty);
    gotopos(19,33);
    cprintf("You should pay RS. %.2f",issueqty*inv_stock.itemrate);getch();
    textcolor(BLUE);
    inv_stock.itemqty-=issueqty;          /*Updating quantity for the item in
stock*/
    fseek(dbfp,-stocksize,SEEK_CUR);
    fwrite(&inv_stock,stocksize,1,dbfp);
    return issueqty;
}
/* If the stock of the item is less than minimum stock.ie Reorder level*/
else
{
    messagebox(10,33,"Insufficient quantity in stock.,"Insufficient Stock",'
',mboxbrdrclr,mboxbgclr,mboxfgclr,0);
    gotopos(17,33);
    textcolor(BLUE);
    textbackground(BROWN);
    cprintf("ONLY %.4f pieces of the Item can be
issued.",inv_stock.itemqty-inv_stock.minqty);
    gotopos(18,33);
    cprintf("Press Any Key...");getch();
    textcolor(BLUE);
    textbackground(BROWN);
    return 0;
}
}

/* Calculates the total investment amount for the stock available*/
float getInvestmentInfo(void)
{
    tot_investment=0;
    rewind(dbfp);
    while(fread(&inv_stock,stocksize,1,dbfp)==1)
        tot_investment+=(inv_stock.itemrate*inv_stock.itemqty);
    return tot_investment;
}

/* Creates a backup file "Bakckup" of "inv_stock.dat"*/
BackupDatabase(void)
{
    FILE *fback;
    fback=fopen("d:/Backup.dat","w");
    rewind(dbfp);
    while(fread(&inv_stock,stocksize,1,dbfp)==1)
        fwrite(&inv_stock,stocksize,1,fback);
    fclose(fback);
    return;
}

/*This structure is used color settings for the application*/
struct colors
{
    char cfg_name[10];

    int mboxbrdrclr;

```


Inventory-project 2

```

int mboxbgclr;
int mboxfgclr;

int menutxtbgclr;
int menutxtfgclr;
int appframeclr;

int section1_symb;
int section1_bgclr;
int section1_fgclr;

int section2_symb;
int section2_bgclr;
int section2_fgclr;
}clr;
const long int clrsize=sizeof(clr);

/* Gets the display configuration for the application*/
getConfiguration()
{
    FILE *flast;
    flast=fopen("lastcfg","r+");
    if(flast==NULL)
    {
        SetDefaultColor();
        return 0;
    }
    rewind(flast);

    /*Reads the first record.*/
    fread(&clr,clrsize,1,flast);
#ifdef OKAY
    if(strcmp(clr.cfg_name,"lastclr")!=0)
    {
        SetDefaultColor();
        fclose(flast);
        return 0;
    }
#endif
    mboxbrdrclr=clr.mboxbrdrclr;mboxbgclr=clr.mboxbgclr;mboxfgclr=clr.mboxfgclr;

    menutxtbgclr=clr.menutxtbgclr;menutxtfgclr=clr.menutxtfgclr;appframeclr=clr.appframe
    clr;

    section1_symb=clr.section1_symb;section1_bgclr=clr.section1_bgclr;section1_fgclr=clr
    .section1_fgclr;

    section2_symb=clr.section2_symb;section2_bgclr=clr.section2_bgclr;section2_fgclr=clr
    .section2_fgclr;
    fclose(flast);
    return 1;
}

/* Sets the default color settings for the application*/
SetDefaultColor()
{
    mboxbrdrclr=BLUE,mboxbgclr=GREEN,mboxfgclr=WHITE;
    menutxtbgclr=BROWN,menutxtfgclr=BLUE,appframeclr=CYAN;
    section1_symb=' ',section1_bgclr=BROWN,section1_fgclr=BLUE;
    section2_symb=' ',section2_bgclr=BROWN,section2_fgclr=BLUE;
    return 1;
}

```

Inventory-project 2

```

/* Adds animation to a text */
BlinkText(const int r,const int c,char txt[],int bgclr,int fgclr,int BGCLR2,int
FGCLR2,int blink,const int dly)
{
    int len=strlen(txt);

    BGCLR2=bgclr;FGCLR2=BLUE;
    htskin(r,c,' ',len,bgclr,bgclr,0);
    print2screen(r,c,txt,bgclr,fgclr,blink);

    write2screen(r,c+animcounter+1,txt[animcounter],BGCLR2,FGCLR2,0);
    write2screen(r,c+animcounter+2,txt[animcounter+1],BGCLR2,FGCLR2,0);
    write2screen(r,c+animcounter+3,txt[animcounter+2],BGCLR2,FGCLR2,0);
    write2screen(r,c+animcounter+4,txt[animcounter+3],BGCLR2,FGCLR2,0);
    write2screen(r,c+animcounter+5,txt[animcounter+4],BGCLR2,FGCLR2,0);
    write2screen(r,c+animcounter+6,txt[animcounter+5],BGCLR2,FGCLR2,0);
    delay(dly*2);
    write2screen(r,c+animcounter+1,txt[animcounter],bgclr,fgclr,0);
    write2screen(r,c+animcounter+2,txt[animcounter+1],bgclr,fgclr,0);
    write2screen(r,c+animcounter+3,txt[animcounter+2],bgclr,fgclr,0);
    write2screen(r,c+animcounter+4,txt[animcounter+3],bgclr,fgclr,0);
    write2screen(r,c+animcounter+5,txt[animcounter+4],bgclr,fgclr,0);
    write2screen(r,c+animcounter+6,txt[animcounter+5],bgclr,fgclr,0);

    animcounter+=1;
    if(animcounter+5 >= len) animcounter=0;

    return;
}

/* Displays a single charector with its attrribute*/
write2screen(int row,int col,char ch,int bg_color,int fg_color,int blink)
{
    int attr;
    char far *v;
    char far *ptr=(char far*)0xB8000000;
    if(blink!=0)
        blink=128;

    attr=bg_color+blink;

    attr=attr<<4;
    attr+=fg_color;
    attr=attr|blink;
    v=ptr+row*160+col*2; /*Calculates the video memory address corresponding to row &
column*/
    *v=ch;
    v++;
    *v=attr;
    return 0;
}

/* Prints text with color attribute direct to the screen*/
print2screen(int row,int col,char string[],int bg_color,int fg_color,int blink)
{
    int i=row,j=col,strno=0,len;
    len=strlen(string);
    while(j<80)
    {
        j++;
        if(j==79)

```

Inventory-project 2

```

    {
        j=0;
        i+=1;
    }
    write2screen(i,j,string[strno],bg_color,fg_color,blink); /*See below
function*/
    strno+=1;
    if(strno > len-1)
        break;
}
return;
}

/* Prints text horizontdally*/
htskin(int row,int column,char symb,int no,int bg_color,int fg_color,int blink)
{
    int i;
    for(i=0;i<no;i++)
        write2screen(row,column++,symb,bg_color,fg_color,blink);    /*Print one
symbol*/
    return;
}

/*Print text vertically*/
vtskin(int row,int column,char symb,int no,int bg_color,int fg_color,int blink)
{
    int i;
    for(i=0;i<no;i++)
        write2screen(row++,column,symb,bg_color,fg_color,blink);    /*Print one symbol*/
    return;
}

/* Shows a message box*/
messagebox(int row,int column,char message[50],char heading[10],char symb,int
borderclr,int bg_color,int fg_color,int blink)
{
    int len;
    char key,image[1000];
    len=strlen(message);
    capture_image(row,column,row+3,column+len+7,&image);

draw_mbox(row,column,row+3,column+len+7,symb,symb,borderclr,YELLOW,blink,borderclr,Y
ELLOW,blink);
    fillcolor(row+1,column+1,row+2,column+len+6,' ',bg_color,bg_color,0);
    print2screen(row+1,column+2,message,bg_color,fg_color,blink);
    print2screen(row+2,column+2,"Press Any Key... ",bg_color,fg_color,blink);
    print2screen(row,column+1,heading,borderclr,fg_color,blink);
    sound(400);
    delay(200);
    nosound();
    fflush(stdin);
    key=getch();
    put_image(row,column,row+3,column+len+7,&image);
    return key;
}

/* Fills color in a region*/
fillcolor(int top_row,int left_column,int bottom_row,int right_column,char symb,int
bg_color,int fg_color,int blink)
{
    int i,j;
    for(i=top_row;i<=bottom_row;i++)
        htskin(i,left_column,symb,right_column-left_column+1,bg_color,fg_color,blink);

```

Inventory-project 2

```

    return;
}

/* Prints a message box with an appropriate message*/
draw_mbox(int trow,int tcolumn,int brow,int bcolumn,char hsymb,char vsymb,int
hbg_color,int hfg_color,int hblink,int vbg_color,int vfg_color,int vblink)
{
    htskin(trow,tcolumn,hsymb,bcolumn-tcolumn,hbg_color,hfg_color,hblink);
    htskin(brow,tcolumn,hsymb,bcolumn-tcolumn,hbg_color,hfg_color,hblink);
    vtskin(trow,tcolumn,vsymb,brow-trow+1,vbg_color,vfg_color,vblink);
    vtskin(trow,bcolumn,vsymb,brow-trow+1,vbg_color,vfg_color,vblink);
    return;
}

/* Copies the txt mode image below the messagebox*/
capture_image(int toprow,int leftcolumn,int bottomrow,int rightcolumn,int *image)
{
    char far *vidmem;
    int i,j,count;
    count=0;
    for(i=toprow;i<=bottomrow;i++)
        for(j=leftcolumn;j<=rightcolumn;j++)
        {
            vidmem=(char far*)0xB8000000+(i*160)+(j*2); /*Calculates the video memory
address corresponding to row & column*/
            image[count]=*vidmem;
            image[count+1]=*(vidmem+1);
            count+=2;
        }
    return;
}

/* Places an image on the screen*/
put_image(int toprow,int leftcolumn,int bottomrow,int rightcolumn,int image[])
{
    char far *ptr=(char far*)0xB8000000;
    char far *vid;
    int i,j,count;
    count=0;
    for(i=toprow;i<=bottomrow;i++)
        for(j=leftcolumn;j<=rightcolumn;j++)
        {
            vid=ptr+(i*160)+(j*2); /*Calculates the video memory address corresponding to
row & column*/
            *vid=image[count];
            *(vid+1)=image[count+1];
            count+=2;
        }
    return;
}

/* To move the curser position to derired position*/
gotopos(int r,int c)
{
    union REGS i,o;
    i.h.ah=2;
    i.h.bh=0;
    i.h.dh=r;
    i.h.dl=c;
    int86(16,&i,&o);
    return 0;
}

```

```

union REGS i,o;

/* Initialize the mouse*/
initmouse()
{
    i.x.ax=0;
    int86(0x33,&i,&o);
    return(o.x.ax);
}

/* Shows the mouse pointer*/
showmouseptr()
{
    i.x.ax=1;
    int86(0x33,&i,&o);
    return;
}

/* Get the mouse position*/
getmousepos(int *button,int *x,int *y)
{
    i.x.ax=3;
    int86(0x33,&i,&o);
    *button=o.x.bx;
    *x=o.x.dx;
    *y=o.x.cx;
    return 0;
}

/* Restores the default text mode*/
setdefaultmode()
{
    set25x80();
    setdefaultcolor();
    return;
}

/* Sets the default color and cursor of screen*/
setdefaultcolor()
{
    int i;
    char far *vidmem=(char far*)0xB8000000;
    window(1,1,80,25);
    clrscr();
    for (i=1;i<4000;i+=2)
        *(vidmem+i)=7;
    _setcursortype(_NORMALCURSOR);
    return;
}

/* Sets 25x80 Text mode*/
set25x80()
{
    asm mov ax,0x0003;
    asm int 0x10;
    return;
}

```

LinkedListExample

/*****

Application: Linked List Example
Compiled on: Borland Turbo C++ 3.0
Programmer: Geetika Mukhi

*****/

```
#include <stdio.h>
#include <conio.h>
```

```
/* Structure for nodes of linked list*/
struct listnode {
int value;
struct listnode * next;
};
typedef struct listnode node;
```

```
node * first,*save,*current;
node * getnode();
```

```
void InsertAtStart(int x);
void InsertAtEnd(int x);
void InsertInMid(int n_no,int x);
int DeleteNode(int kv);
node * FindNode(int kv);
void ReverseList();
void SortList();
void ClearList();
void ShowList();
int CountNodes();
```

```
void main()
{
int choice,nodeValue,insertPos;
first = NULL;
do
{
clrscr();
```

```
printf("\n1. Insert a Value at the Start");
printf("\n2. Show the Linked List");
printf("\n3. Insert a Value at the End");
printf("\n4. Clear Linked List");
printf("\n5. Show the Number of Nodes in the Linked List");
printf("\n6. Insert the Value After Mentioned Node");
printf("\n7. Delete a Node of Linked List");
printf("\n8. Search a Node of Linked List");
printf("\n9. Sort the Linked List");
printf("\n10. Reverse the Linked List");
printf("\n0. Close the application");
```

```
printf("\n\nPlease Enter Your Choice\n");
```

```
scanf("%d",&choice);
```

```
switch (choice)
{
```

```
    case 1:
        printf("\nEnter The Node value To Be Inserted At The Start: \n");
        scanf("%d",&nodeValue);
        InsertAtStart(nodeValue);
        break;
```

LinkListExample

```
case 2:
    ShowList();
    break;

case 3:
    printf("\nEnter The Node Value To Be Inserted At The End: \n");
    scanf("%d",&nodeValue);
    InsertAtEnd(nodeValue);
    break;

case 4:
    ClearList();
    break;

case 5:
    printf("\n%d Nodes are available in the Linked List",CountNodes());
    getch();
    break;

case 6:
    printf("\nEnter The Position after which you"
           " want to Insert the new value: \n");
    scanf("%d",&insertPos);
    if ( insertPos > CountNodes())
    {
        printf(" Node at position %d cannot be inserted. There are only"
               " %d node(s) in the list",insertPos,CountNodes());
        getch();
    }
    else
    {
        printf("\nEnter The Value To Be Inserted after %d node(s):
\n",insertPos);
        scanf("%d",&nodeValue);
        InsertInMid(insertPos,nodeValue);
    }
    break;

case 7:
    printf("\nEnter The Node Value To Be Deleted: \n");
    scanf("%d",&nodeValue);
    DeleteNode(nodeValue);
    break;

case 8:
    printf("\nEnter The Node Value To Be Searched: \n");
    scanf("%d",&nodeValue);
    FindNode(nodeValue);
    break;

case 9:
    SortList();
    break;

case 10:
    ReverseList();
    break;

}
}
while (choice!=0);
```

LinkedListExample

```
}

/* This function reverses the sequences of nodes in the linked list*/
void ReverseList()
{
    node *temp;
    current = save = first;
    if (first == NULL)
    {
        printf("\a\nThere are no nodes in the Linked List.\n");
        getch();
    }
    else
    {
        save = NULL;
        while (current != NULL)
        {
            temp = save;
            save = current;
            current = current->next;
            save->next = temp;
        }
        first = save;
        printf("\n\nThe Linked List Has Been Reversed.\n");
        getch();
    }
}

/* This function will sort the linked list*/
void SortList()
{
    int temp;
    current = save = first;
    if (first==NULL)
    {
        printf("\a\nThere are no nodes in the Linked List.\n");
        getch();
    }
    else
    {
        for (current=first;(current != NULL);current=current->next)
        {
            for (save=current->next;(save != NULL);save=save->next)
            {
                if ( current->value < save->value )
                {
                    temp = save->value;
                    save->value = current->value;
                    current->value = temp;
                }
            }
        }

        printf("\n\nThe Linked List Has Been Sorted.\n");
        getch();
    }
}

/* This function searches for a particular node value in the linked list*/
node * FindNode(int nvalue)
{
    current = first;
    if (first == NULL)
```



```

                                LinkedListExample
{
    printf("\a\nThere are no nodes in the Linked List.");
    getch();
}
else
{
    while ( (current != NULL) && (current->value != nValue) )
        current = current->next;
    if (current->value == nValue)
    {
        printf("\nThe Node is available in the Linked List.\n");
        getch();
        return(current);
    }
    else
        printf("\nThe Node is not available in the Linked List. Please try again.\n");
    getch();
}
}

/* This function deletes a node from the linked list*/
int DeleteNode(int nValue)
{
    int undel;
    current = first;
    if (first == NULL)
    {
        printf("\a\nThere are no nodes in the Linked List.");
        getch();
    }
    else
    {
        while ( (current != NULL) && (current->value != nValue) )
        {
            save = current;
            current = current->next;
        }
        if (current->value == nValue)
        {
            if (current == first)
            {
                undel = current->value;
                current = current->next;
                free(first);
                first = current;
            }
            else
            {
                undel = current->value;
                save->next = current->next;
                free(current);
            }

            printf("Node with value %d has been Deleted.",nValue);
            getch();
            return(undel);
        }
        else
            printf("Node with value %d is not available in the Linked List. Please try again.",nValue);
        getch();
    }
}

```

LinkedListExample

```
    }  
}  
  
/* This function inserts a node in the middle of the linked list*/  
void InsertInMid(int nPos,int nValue)  
{  
    int count=0;  
    node *temp;  
    temp = getnode();  
    temp->value = nValue;  
    temp->next = NULL;  
    current = first;  
    while (count < nPos )  
    {  
        save = current;  
        current = current->next;  
        count++;  
    }  
  
    if (first == NULL) first = temp;  
    else if (current == first)  
    {  
        temp->next = current;  
        first = temp;  
    }  
    else  
    {  
        temp->next = save->next;  
        save->next = temp;  
    }  
}  
  
/* This function returns the node*/  
node * getnode()  
{  
    node * temp;  
    temp = (node *) malloc(sizeof(node));  
    if (temp == NULL)  
    {  
        printf("\nProblem in allocating memory to the node.!\n");  
        exit(1);  
    }  
    else  
        return(temp);  
}  
  
/* This function calculates the number of nodes contained in the linked list*/  
int CountNodes()  
{  
    int count=0;  
    current = first;  
    while (current != NULL)  
    {  
        count++;  
        current = current->next;  
    }  
    return(count);  
}  
  
/* This function inserts a node at the start of the linked list*/  
void InsertAtStart(int nValue)  
{
```

LinkedListExample

```
node *temp;
temp = getnode();
temp->value = nValue;
temp->next = NULL;
if (first == NULL)
    first = temp;
else
{
    temp->next = first;
    first = temp;
}

/* This function inserts a node at the end of the linked list*/
void InsertAtEnd(int nValue)
{
    node *temp;
    temp = getnode();
    temp->value = nValue;
    temp->next = NULL;
    if (first == NULL)
        first = temp;
    else
    {
        current = first;
        while (current != NULL)
        {
            save = current;
            current = current->next;
        }
        save->next = temp;
    }
}

/* This function shows all the data contained in the linked list*/
void ShowList()
{
    clrscr();
    current = first;
    if (current == NULL)
        printf("\aThere are no nodes in the Linked List.\n");
    while (current != NULL)
    {
        printf("\n%d", current->value);
        current = current->next;
    }
    getch();
}

/* This function clears all data from the linked list*/
void ClearList()
{
    current = first;
    while (current != NULL)
    {
        current = current->next;
        free(first);
        first = current;
    }
    printf("\nLinked List has been cleared.\n");
    getch();
}
```

```

matrixmulti
/*****

Application: Matrix Multiplication
Compiled on: Borland Turbo C++ 3.0
Programmer : Geetika Mukhi

*****/

#include <stdio.h>
#include <stdlib.h>
#define MAXSIZE 20

void
RecordData( int mt[ ][ MAXSIZE ], int n ),
Multiply( int mt1[ ][ MAXSIZE ], int mt2[ ][ MAXSIZE ],
          int mt3[ ][ MAXSIZE ], int size ),
ShowResult( int mt[ ][ MAXSIZE ], int size );

void main()
{
    int size;
    int mt1[ MAXSIZE ][ MAXSIZE ],
        mt2[ MAXSIZE ][ MAXSIZE ],
        mt3[ MAXSIZE ][ MAXSIZE ];
    char checkAnotherOperation;

    checkAnotherOperation='y';

    while(checkAnotherOperation=='y')
    {
        clrscr();
        /* Reads data of Matrix mt1 and mt2 and multiply the two matrices*/
        printf( "MATRIX MULTIPLICATION\n\n" );
        printf( "Please Enter the Matrix Size: " );
        scanf( "%d", &size );
        printf( "\nEnter the First Matrix:\n" );
        RecordData( mt1, size );
        printf( "\nMatrix mt1:\n" );
        ShowResult( mt1, size );
        printf( "\nEnter the Second Matrix:\n" );
        RecordData( mt2, size );
        printf( "\nMatrix mt2:\n" );
        ShowResult( mt2, size );

        Multiply( mt1, mt2, mt3, size );

        /* Show the resultant matrix */
        printf( "\nResultant Matrix mt3 After Multiplication of mt1 and mt2:\n" );
        ShowResult( mt3, size );
        printf( "\nWould like to perform another matrix multiplication? (y/n):");
        fflush(stdin);
        checkAnotherOperation=getche();
    }
}

/* This function multiplies the two matrices and stores the result in a third
matrix*/
void Multiply( int mt1[ ][ MAXSIZE ],
              int mt2[ ][ MAXSIZE ],
              int mt3[ ][ MAXSIZE ],
              int size )
{

```

```

                                matrixmulti

int l, m, n;

for ( l = 0; l < size; l++ )
    for ( m = 0; m < size; m++ ) {
        mt3[ l ][ m ] = 0;
        for ( n = 0; n < size; n++ )
            mt3[ l ][ m ] += mt1[ l ][ m ] * mt2[ n ][ m ];
    }
}

/* This function records the data of a matrix*/
void RecordData( int mt[ ][ MAXSIZE ], int size )
{
    int row, col;

    for ( row = 0; row < size; row++ )
        for ( col = 0; col < size; col++ )
            scanf( "%d", &mt[ row ][ col ] );
}

/* This function prints the contents of a matrix*/
void ShowResult( int mt[ ][ MAXSIZE ], int size )
{
    int row, col;

    for ( row = 0; row < size; row++ ) {
        for ( col = 0; col < size; col++ )
            printf( "%d ", mt[ row ][ col ] );
        putchar( '\n' );
    }
}

```

Record Entry-project 1

/*****

Application: Record Entry System
Compiled on: Borland Turbo C++ 3.0
Programmer: Geetika Mukhi

*****/

```
#include <stdio.h>
#include <conio.h>
#include <string.h>
#include <dos.h>
#include <ctype.h>

void dataentry(void);
void selectAdminOption(void);
void getData(int option);
int showAdminMenu;

void main()
{
    int cancelOption,timeOption,entryOption,exitOption;
    char choice[1];
    char selectOption[1];

    textcolor(YELLOW);
    cancelOption=0;

    /* Shows the main menu for the application*/
    while (cancelOption==0)
    {
        clrscr();
        gotoxy(30,7);
        printf("Please Select an Action-->");
        gotoxy(30,10);
        printf("Daily Time Record [1] ");
        gotoxy(30,11);
        printf("Data Entry          [2] ");
        gotoxy(30,12);
        printf("Close                [3] ");
        gotoxy(30,15);
        printf("Please Enter Your Choice (1/2/3): ");
        scanf("%s",&choice);
        timeOption=strcmp(choice,"1");
        entryOption=strcmp(choice,"2");
        exitOption=strcmp(choice,"3");

        if (timeOption==0)
        {
            clrscr();
            gotoxy(23,6);
            printf("DAILY EMPLOYEE TIME RECORDING SYSTEM");
            gotoxy(16,24);
            printf("Input Any Other key to Return to Previous Screen.");
            gotoxy(31,9);
            printf("[1] Employee Log In ");
            gotoxy(31,10);
            printf("[2] Employee Log Out");
            gotoxy(28,12);
            printf("Please Enter Your Option: ");
            scanf("%s",&selectOption);
            if (strcmp(selectOption,"1")==0)
                Page 1
```



```

        Record Entry-project 1
        if (returnOption==0)
        {
            goto stream;
        }
        if (!(UserName==0 || returnOption==0))
        {

            gotoxy(32,11);
            printf("Administrator Name is Invalid.");
            getch();
            validUserNameOption=0;
        }
        else
            validUserNameOption=1;
    }

    gotoxy(30,11);
    printf("Enter Password: ");
    inc=0;
    while (inc<5)
    {
        passwd[inc]=getch();
        inc=inc+1;
        printf("* ");
    }
    inc=0;
    while (inc<5)
    {
        tempo[inc]=passwd[inc];
        inc=inc+1;
    }
    while(getch()!=13);
    if (!strcmp(tempo, "admin12"))
    {
        gotoxy(28,13);
        printf("You have Entered a Wrong Password. Please Try Again.");

        getch();
        validUserPwdOption=0;
        validUserNameOption=0;
    }
    else
    {
        clrscr();
        gotoxy(24,11);
        textcolor(YELLOW+BLINK);
        cprintf("You Have Successfully Logged In.");
        gotoxy(24,17);
        textcolor(YELLOW);
        printf("Press Any Key to Continue.");
        validUserPwdOption=1;
        validUserNameOption=1;
        getch();
        showAdminMenu=0;

        while (showAdminMenu==0)
        {
            clrscr();
            gotoxy(24,4);
            printf("ADMIN OPTIONS");
            gotoxy(26,9);
            printf("Add New Employee      [1]");
        }
    }
}

```



```

                                Record Entry-project 1
                                gotoxy(26,11);
                                printf("Show Daily Entries      [2]");
                                gotoxy(26,13);
                                printf("Search Employee Record [3]");
                                gotoxy(26,15);
                                printf("Remove Employee        [4]");
                                gotoxy(26,17);
                                printf("Close                  [5]");
                                gotoxy(24,21);
                                printf("Please enter your choice: ");
                                selectAdminOption();
                            }
                        }
                    }
stream: {}
}

/* This function provides the administrator level functionalities, such as Adding or
deleting an employee.*/
void selectAdminOption(void)
{
    char chc[1];
    int chooseNew,chooseShow,chooseSearch,chooseRemove,chooseClose;

    gets(chc);

    chooseNew=strcmp(chc,"1");
    chooseShow=strcmp(chc,"2");
    chooseSearch=strcmp(chc,"3");
    chooseRemove=strcmp(chc,"4");
    chooseClose=strcmp(chc,"5");

    if (!(chooseNew==0 || chooseShow==0 || chooseSearch==0 || chooseRemove==0 ||
chooseClose==0))
    {
        gotoxy(19,21);
        textcolor(RED+BLINK);
        cprintf("Invalid Input!");
        gotoxy(34,21);
        textcolor(YELLOW);
        cprintf("Press any key to continue.");
    }

    if (chooseNew==0)
    {
        clrscr();
        gotoxy(25,5);
        getData(1);
    }
    else if(chooseShow==0)
    {
        getData(2);
    }
    else if(chooseSearch==0)
    {
        clrscr();
        getData(3);
    }
    else if(chooseRemove==0)
    {
        getData(4);
    }
}

```

Record Entry-project 1

```

else if (chooseClose==0)
{
    showAdminMenu=1;
}
}

```

/* This function retrieves data from the database as well as do data processing according to user requests.

The function provides functionality for menu options provided to both employee as well as administrator user*/

```
void getData(int option)
```

```
{
    FILE *db,*tempdb;
    char anotherEmp;
    int choice;
    int showMenu,posx,posy;
    char checkSave,checkAddNew;
    int i;

```

```
struct employee
```

```
{
    char firstname[30];
    char lastname[30];
    char password[30];
    int empid;
    char loginhour;
    char loginmin;
    char loginsec;
    char logouthour;
    char logoutmin;
    char logoutsec;
    int yr;
    char mon;
    char day;
};

```

```
struct employee empData;
```

```
char confirmPassword[30];
long int size;
char lastNameTemp[30],firstNameTemp[30],password[30];
int searchId;
char pass[30];
char findEmployee;
char confirmDelete;

```

```
struct date today;
struct time now;

```

```
clrscr();

```

```
/* Opens the Employee Database*/
```

```
db=fopen("d:/empbase.dat","rb+");
```

```
if(db==NULL)
```

```
{
    db=fopen("d:/empbase.DAT","wb+");
    if(db==NULL)
    {
        printf("The File could not be opened.\n");
        exit();
    }
}

```

```
printf("Application Database \n");
```

Record Entry-project 1

```

size=sizeof(empData);
showMenu=0;
while(showMenu==0)
{
    fflush(stdin);
    choice=option;

    /* Based on the choice selected by admin/employee, this switch statement
    processes the request*/
    switch(choice)
    {

        /* To add a new employee to the database*/
        case 1:
            fseek(db,0,SEEK_END);
            anotherEmp='y';

            while(anotherEmp=='y')
            {
                checkAddNew=0;
                while(checkAddNew==0)
                {
                    clrscr();
                    gotoxy(25,3);
                    printf("ADD A NEW EMPLOYEE");
                    gotoxy(13,22);
                    printf("Warning: Password Must Contain Six(6) AlphaNumeric
Digits.");
                    gotoxy(5,8);
                    printf("Enter First Name: ");
                    scanf("%s",&firstNameTemp);
                    gotoxy(5,10);
                    printf("Enter Last Name: ");
                    scanf("%s",&lastNameTemp);
                    gotoxy(43,8);
                    printf("Enter Password: ");
                    for (i=0;i<6;i++)
                    {
                        password[i]=getch();
                        printf("* ");
                    }
                    password[6]='\0';

                    while(getch()!=13);

                    gotoxy(43,10);
                    printf("Confirm Password: ");
                    for (i=0;i<6;i++)
                    {
                        confirmPassword[i]=getch();
                        printf("* ");
                    }
                    confirmPassword[6]='\0';

                    while(getch()!=13);
                    if (strcmp(password,confirmPassword))
                    {
                        gotoxy(24,12);
                        printf("Passwords do not match.");
                        gotoxy(23,13);
                        printf("Press any key to continue.");
                        getch();
                    }
                }
            }
        }
    }
}

```

Record Entry-project 1

```

else
{
checkAddNew=1;
rewind(db);
empData.empid=0;
while(fread(&empData,size,1,db)==1);
if (empData.empid<2000)
empData.empid=20400;

empData.empid=empData.empid+1;
gotoxy(29,16);
printf("Save Employee Information? (y/n): ");
checkSave=getche();
if (checkSave=='y')
{
strcpy(empData.firstname,firstNameTemp);
strcpy(empData.lastname,lastNameTemp);
strcpy(empData.password,password);
empData.loginhour='t';
empData.logouthour='t';
empData.day='j';
fwrite(&empData,size,1,db);
}
gotoxy(28,16);
printf("                                ");
gotoxy(28,16);
printf("Would like to add another employee? (y/n):");
fflush(stdin);
anotherEmp=getche();
printf("\n");
}
}
break;

/* To view time records for all employees*/
case 2:

clrscr();
gotoxy(21,2);
printf("VIEW EMPLOYEE INFORMATION");
gotoxy(1,5);
printf("Employee ID   Employee Name       Time Logged In       Time Logged Out\n\n");
rewind(db);
posx=3;
posy=7;
while(fread(&empData,size,1,db)==1)
{
empData.firstname[0]=toupper(empData.firstname[0]);
empData.lastname[0]=toupper(empData.lastname[0]);
gotoxy(posx,posy);
printf("%d",empData.empid);
gotoxy(posx+10,posy);
printf("| %s, %s",empData.lastname,empData.firstname);
gotoxy(posx+30,posy);
if (empData.loginhour=='t')
{
printf("| Not Logged In");
}
else
printf("|
%d:%d:%d",empData.loginhour,empData.loginmin,empData.loginsec);

```

Record Entry-project 1

```

gotoxy(posx+49, posy);
if (empData.logouthour=='t')
{
printf("| Not Logged Out");
}
else
printf("|
%d:%d:%d", empData.logouthour, empData.logoutmin, empData.logoutsec);
if (empData.day=='j')
{
gotoxy(posx+69, posy);
printf("| No Date");
}
else
{
gotoxy(posx+73, posy);
printf("| %d/%d/%d", empData.mon, empData.day, empData.yr);
}

posy=posy+1;
}
getch();

printf("\n");
break;

```

/* To search a particular employee and view their time records*/
case 3:

```

clrscr();
gotoxy(27, 5);
printf("SEARCH EMPLOYEE INFORMATION");
gotoxy(25, 9);
printf("Enter Employee Id to Search: ");
scanf("%d", &searchId);
findEmployee='f';
rewind(db);
while(fread(&empData, size, 1, db)==1)
{
if (empData.empid==searchId)
{
gotoxy(33, 11);
textcolor(YELLOW+BLINK);
cprintf("Employee Information is Available.");
textcolor(YELLOW);
gotoxy(25, 13);
printf("Employee name is: %s
%s", empData.lastname, empData.firstname);
if(empData.loginhour=='t')
{
gotoxy(25, 14);
printf("Log In Time: Not Logged In");
}
else
{
gotoxy(25, 14);
printf("Log In Time is:
%d:%d:%d", empData.loginhour, empData.loginmin, empData.loginsec);
}
if(empData.logouthour=='t')
{
gotoxy(25, 15);

```

```

                                Record Entry-project 1
        printf("Log Out Time: Not Logged Out");
    }
    else
    {
        gotoxy(25,15);
        printf("Log Out Time is:
%d:%d:%d",empData.logouthour,empData.logoutmin,empData.logoutsec);
    }
    findEmployee='t';
    getch();
}
if (findEmployee!='t')
{
    gotoxy(30,11);
    textcolor(YELLOW+BLINK);
    cprintf("Employee Information not available. Please modify the search.");
    textcolor(YELLOW);
    getch();
}
break;

/* To remove entry of an employee from the database*/
case 4:
    clrscr();
    gotoxy(25,5);
    printf("REMOVE AN EMPLOYEE");
    gotoxy(25,9);
    printf("Enter Employee Id to Delete: ");
    scanf("%d", &searchId);
    findEmployee='f';
    rewind(db);
    while(fread(&empData,size,1,db)==1)
    {
        if (empData.empid==searchId)
        {
            gotoxy(33,11);
            textcolor(YELLOW+BLINK);
            cprintf("Employee Information is Available.");
            textcolor(YELLOW);
            gotoxy(25,13);
            printf("Employee name is: %s
%s",empData.lastname,empData.firstname);
            findEmployee='t';
        }
    }
    if (findEmployee!='t')
    {
        gotoxy(30,11);
        textcolor(YELLOW+BLINK);
        cprintf("Employee Information not available. Please modify the search.");
        textcolor(YELLOW);
        getch();
    }
    if (findEmployee=='t')
    {
        gotoxy(29,15);
        printf("Do you want to Delete the Employee? (y/n)");
        confirmDelete=getche();
        if (confirmDelete=='y' || confirmDelete=='Y')
        {

```

```

                                Record Entry-project 1
tempdb=fopen("d:/tempo.dat","wb+");
rewind(db);
while(fread(&empData,size,1,db)==1)
{
    if (empData.empid!=searchId)
    {
        fseek(tempdb,0,SEEK_END);
        fwrite(&empData,size,1,tempdb);
    }
}
fclose(tempdb);
fclose(db);
remove("d:/empbase.dat");
rename("d:/tempo.dat","d:/empbase.dat");
db=fopen("d:/empbase.dat","rb+");
}
break;

/* To login an employee into the system and record the login date and time*/
case 5:
    clrscr();
    gotoxy(20,4);
    printf("DAILY EMPLOYEE TIME RECORDING SYSTEM");
    gotoxy(20,23);
    printf("Warning: Please Enter Numeric Values Only.");
    gotoxy(23,7);
    printf("Enter Your Id to Login: ");
    scanf("%d", &searchId);
    gotoxy(20,23);
    printf("                                ");
    findEmployee='f';
    rewind(db);
    while(fread(&empData,size,1,db)==1)
    {
        if (empData.empid==searchId)
        {
            gotoxy(23,8);
            printf("Enter Your Password: ");

            for (i=0;i<6;i++)
            {
                pass[i]=getch();
                printf("* ");
            }
            pass[6]='\0';
            while(getch()!=13);

            if (strcmp(empData.password,pass))
            {
                gotoxy(23,11);
                textcolor(YELLOW+BLINK);
                cprintf("You Have Supplied a wrong Password.");
                textcolor(YELLOW);
                findEmployee='t';
                getch();
                break;
            }
            gotoxy(23,11);
            textcolor(YELLOW+BLINK);
            cprintf("You have successfully Logged In the System.");
            textcolor(YELLOW);
            gotoxy(23,13);

```

```

                                Record Entry-project 1
printf("Employee name: %s %s",empData.lastname,empData.firstname);
gettime(&now);
getdate(&today);
gotoxy(23,14);
printf("Your LogIn Time:
%2d:%2d:%2d",now.ti_min,now.ti_hour,now.ti_sec);
gotoxy(23,15);
printf("Your Log In Date:
%d/%d/%d",today.da_mon,today.da_day,today.da_year);
empData.day=today.da_day;
empData.mon=today.da_mon;
empData.yr=today.da_year;
fseek(db,-size,SEEK_CUR);
empData.loginhour=now.ti_min;
empData.loginmin=now.ti_hour;
empData.loginsec=now.ti_sec;
fwrite(&empData,size,1,db);
findEmployee='t';
getch();

    }
}
if (findEmployee!='t')
{
gotoxy(30,11);
textcolor(YELLOW+BLINK);
cprintf("Employee Information is not available.");
textcolor(YELLOW);
getch();
}

break;

/* To logout an employee and record the logout date and time*/
case 6:

```

```

clrscr();
gotoxy(20,4);
printf("DAILY EMPLOYEE TIME RECORDING SYSTEM");
gotoxy(20,23);
printf("Warning: Please Enter Numeric Values Only.");
gotoxy(23,7);
printf("Enter Your Id to Logout: ");
scanf("%d", &searchId);
gotoxy(20,23);
printf("                                ");
findEmployee='f';
rewind(db);
while(fread(&empData,size,1,db)==1)
{
    if (empData.empid==searchId)
    {
        gotoxy(23,8);
        printf("Enter Password: ");

        for (i=0;i<6;i++)
        {
            pass[i]=getch();
            printf("* ");
        }
        pass[6]='\0';
        while(getch()!=13);
    }
}

```



```

                                Record Entry-project 1
if (strcmp(empData.password,pass))
{
    gotoxy(30,11);
    textcolor(YELLOW+BLINK);
    cprintf("You Have Supplied a Wrong Password.");
    textcolor(YELLOW);
    findEmployee='t';
    getch();
    break;
}
gotoxy(23,11);
textcolor(YELLOW+BLINK);
cprintf("You have successfully Logged Out of the system.");
textcolor(YELLOW);
gotoxy(23,13);
printf("Employee name is: %s
%s",empData.lastname,empData.firstname);
gettime(&now);
getdate(&today);
gotoxy(23,14);
printf("Your Log Out Time:
%2d:%2d:%2d",now.ti_min,now.ti_hour,now.ti_sec);
gotoxy(23,15);
printf("Your Log Out Date:
%d/%d/%d",today.da_mon,today.da_day,today.da_year);
fseek(db,-size,SEEK_CUR);
empData.logouthour=now.ti_min;
empData.logoutmin=now.ti_hour;
empData.logoutsec=now.ti_sec;
fwrite(&empData,size,1,db);
findEmployee='t';
getch();

}
}
if (findEmployee!='t')
{
    gotoxy(23,11);
    textcolor(YELLOW+BLINK);
    cprintf("Employee Information is not available.");
    textcolor(YELLOW);
    getch();
}

break;

/* Show previous menu*/
case 9:
    printf("\n");
    exit();
}
fclose(db);
showMenu=1;
}
}

```