

Introduction

- The wrapper class in Java provides the mechanism to convert primitive into object and object into primitive.
- Since J2SE 5.0, autoboxing and unboxing feature convert primitives into objects and objects into primitives automatically.
- The automatic conversion of primitive into an object is known as autoboxing and vice-versa unboxing.

Eight Wrapper Classes

Primitive Type	Wrapper Class
boolean	Boolean
char	Character
short	Short
int	Integer
long	Long
float	Float
double	Double

Autoboxing

The automatic conversion of primitive data type into its corresponding wrapper class is known as autoboxing



```
//Autoboxing example of int to Integer
public class Autoboxing{
    public static void main(String args[]){
        //Converting int into Integer
        int a=20;
        //converting int into Integer explicitly
        Integer i=Integer.valueOf(a);
        //autoboxing, now compiler will write Integer.valueOf(a) internally
        Integer j=a;
        System.out.println(a+" "+i+" "+j);
    }
}
//output:
//20 20 20
```

Unboxing

The automatic conversion of wrapper type into its corresponding primitive type is known as unboxing.



```
//Unboxing example of Integer to int
public class Unboxing{
    public static void main(String args[]){
        //Converting Integer to int
        Integer a=new Integer(3);
        //converting Integer to int explicitly
        int i=a.intValue();
        //unboxing, now compiler will write a.intValue() internally
        int j=a;
        System.out.println(a+" "+i+" "+j);
    }
}
//output:
//3 3 3
```