

Package ‘CalibInc’

February 9, 2018

Title Prediction of incidence using calibration model and proxy of incidence

Version 0.1

Author Edouard Chatignoux [aut,cre], Zoe Uhry [aut, ctb], Laurent Remonet [aut, ctb], Marc Colonna [aut, ctb]

Maintainer Edouard Chatignoux <edouard.chatignoux@santepubliquefrance.fr>

Description

The package provides fonctions to predict incidence from proxy data using a calibration approach

Depends R (>= 3.3.3)

License GPL-3

Encoding UTF-8

LazyData true

Imports tidyverse,
scales,
splines,
RColorBrewer,
Matrix,
maptools,
methods

Suggests lme4,
MASS,
splines,
mgcv

RoxygenNote 6.0.1

R topics documented:

| | |
|-------------------------|----------|
| CalibInc | 2 |
| ggMap | 3 |
| LogNormPI | 4 |
| lopm.alldist | 5 |
| lopm.CalibSet | 5 |
| nhlw.alldist | 6 |
| nhlw.CalibSet | 7 |
| poly2ggplot | 7 |
| ShapDep | 8 |
| Index | 9 |

Description

CalibInc functions takes a calibration model and a table with proxy data as arguments and returns a table with predictions and standard errors

Usage

```
CalibInc(mod, pred = NULL, weight = 1, aggregate = NULL,
         keep.Vp = FALSE)
```

Arguments

| | |
|-----------|--|
| mod | Calibration model (type H/I ratio), fitted with glmer, glmmPQL, gam or gamm |
| pred | Data frame containing proxy data to be calibrated. If NULL, try to use the data.frame used for model evaluation (searched in .GlobalEnv). |
| weight | Weight vector (size 1 for an uniform weight, same size as nrow(pred) otherwise). weight can be given as the name of a column in pred. |
| aggregate | Aggregate the predictions according to a combination of variables given as a formula (see examples). If NULL aggregation is done according to the combinations of all co-variables specified in the model formula. |
| keep.Vp | Set to TRUE to keep variances covariance matrix of the predictions |

Value

A data frame containing predictions values (column pred) and se (column se) at the levels defined in aggregate. If keep.Vp=TRUE, the variances covariance matrix of the predictions is also returned as an attribute.

Author(s)

Edouard Chatignoux

Examples

```
library(lme4)
library(splines)
library(tidyverse)
data(lopmm.CalibSet)
data(lopmm.alldist)
## Run the calibration model for lop cancer incidence
## and hospitalisation data in men, 2007-2011
k<-Hmisc::wtd.quantile(lopmm.CalibSet$age,weights=lopmm.CalibSet$C,p=0.5)%>%as.numeric
form.calib<-substitute(H~offset(log(C))+
                      ns(age,knots=k, Boundary.knots = range(age)+c(5,-5))+
                      (1|dist),
                      list(k=k))%>%as.formula
mod.calib<-glmer(form.calib,data=lopmm.CalibSet%>%filter(C>0),family="poisson", nAGQ =20)
## Predict the total number of incident cases by district
CalibInc(mod.calib,pred=lopmm.alldist,aggregate=~dist)
```

```
## Predict the total number of incident cases by age and district
CalibInc(mod.calib,pred=lop.m.alldist,aggregate=~dist+age)
```

ggMap

Plot variables values on a map

Description

ggMap create a map from a data frame with observations on spatial units. It allows to represent values in continuous (with possible lower and upper bounds) or categorical scale, and to hatch non significant areas.

Usage

```
ggMap(var, data = NULL, map = NULL, limits = NULL, breaks = NULL,
      legend = list(breaks = NULL, density = F, title = NULL, pretty = T,
                    placement = NULL), color = "Greys", rev = FALSE, na.action = na.pass,
      ns = NULL, path = TRUE)
```

Arguments

| | |
|-----------|---|
| var | Variable name from the data data to map, or vector sorted in the order of the map spatial units |
| data | Data with column to plot. Must contain an id variable that identifies the district (jointure variable with map data) |
| map | Map shape ("polygg" type, set to ShapDep if NULL) |
| limits | Set limits if a continuous map is chosen |
| breaks | Values to cut var into classes |
| legend | List of legend parameters breaks Breaks in the legend density Set to TRUE to represent the legend as the density distribution of the observed values title Legend title (variable name otherwise) pretty If var is cut in classe with cut function, convert classes names to pretty labels placement Legend placement (x0,x1,y0,y1) coordinates, in proportion of the plot zone |
| color | Name of the brewer palette brewer.pal |
| rev | Reverse color palette order (TRUE, FALSE) |
| na.action | What to do with missing values |
| ns | Variable name in the data set that identifies non significant areas (TRUE when non significant). In that case, the corresponding geographical areas are hatched. |
| path | Draw geographical boundaries (default to TRUE) |

Value

A ggplot2 graph

Author(s)

Edouard Chatignoux

Examples

```
## Represent crude hospitalisation rate in France by district for LP cancer in men, 2007-2011
library(tidyverse)
data(lopmm.alldist)
crude.rate<-lopmm.alldist%>%group_by(dist)%>%summarise(rate=100000*sum(H)/sum(py))%>%mutate(id=dist)
ggMap(var=rate,data=crude.rate,color= "YlOrRd",legend=list(title="Hosp. rate\nfor 100 000"))+
ggtitle("Crude hospitalisation rate for LOP, men, 2007-2011")
```

LogNormPI

Confidence interval for log-normal distributed observations

Description

LogNormPI calculates confidence interval for log-normal distributed observations

Usage

```
LogNormPI(data, pred = pred, se = se, level = 0.95)
```

Arguments

| | |
|-------|---|
| data | A data frame with log-normal observations |
| pred | Log-normal observation |
| se | Standard error of pred |
| level | Confidence interval level |

Author(s)

Edouard Chatignoux

Examples

```
dt<-data_frame(m=2,sd=1)
LogNormPI(data=dt,m,sd)
```

| | |
|----------------|--|
| lopmm.allldist | <i>LOP cancer in men for French districts.</i> |
|----------------|--|

Description

Data on hospitalisation for LOP cancer in men over the 2007-2011 period for the 96 French administrative districts.

Usage

```
data( lopmm.allldist )
```

Format

A data frame with 1728 rows and 5 variables

- dist District
- age Central age of the age class
- H Number of hospitalizations
- py Number of person-years
- WSP World Standard Population (Segi 1960 standard)

Details

The number of hospitalizations and person-years are tabulated by 5 years age groups (from 0-5 to 90+, variable 'age' corresponds to the central age of the class) and district (variable 'dist').

References

<http://seer.cancer.gov/stdpopulations/>

| | |
|----------------|--|
| lopmm.CalibSet | <i>LOP cancer in men for districts covered by a cancer registry.</i> |
|----------------|--|

Description

Data on LOP cancer in men over the 2007-2011 period for the 14 districts covered by a cancer registry.

Usage

```
data( lopmm.CalibSet )
```

Format

A data frame with 182 rows and 5 variables

- dist District
- age Central age of the age class
- C Number of cancer incident cases
- H Number of hospitalizations
- py Number of person-years

Details

The number of cancer incident cases were provided by the network of French cancer registries FRANCIM. The number of cancer incident cases, corresponding numbers of hospitalizations and person-years are tabulated by 5 years age groups (from 0-5 to 90+, variable 'age' corresponds to the central age of the class) and district (variable 'dist'). In order to diminish the number of age classes with no cancer, the number of incident cases in lower ages classes were aggregated.

nhlw.alldist

NHL cancer in women for French districts.

Description

Data on hospitalisation for NHL cancer in women over the 2007-2011 period for the 96 French administrative districts.

Usage

```
data( nhlw.alldist )
```

Format

A data frame with 1728 rows and 5 variables

- dist District
- age Central age of the age class
- H Number of hospitalizations
- py Number of person-years
- WSP World Standard Population (Segi 1960 standard)

Details

The number of hospitalizations and person-years are tabulated by 5 years age groups (from 0-5 to 90+, variable 'age' corresponds to the central age of the class) and district (variable 'dist').

References

<http://seer.cancer.gov/stdpopulations/>

| | |
|---------------|--|
| nhlw.CalibSet | <i>NHL cancer in women for districts covered by a cancer registry.</i> |
|---------------|--|

Description

Data on NHL cancer in women over the 2007-2011 period for the 16 districts covered by a cancer registry.

Usage

```
data( nhlw.CalibSet )
```

Format

A data frame with 256 rows and 5 variables

- dist District
- age Central age of the age class
- C Number of cancer incident cases
- H Number of hospitalizations
- py Number of person-years

Details

The number of cancer incident cases were provided by the network of French cancer registries FRANCIM. The number of cancer incident cases, corresponding numbers of hospitalizations and person-years are tabulated by 5 years age groups (from 0-5 to 90+, variable 'age' corresponds to the central age of the class) and district (variable 'dist'). In order to diminish the number of age classes with no cancer, the number of incident cases in lower ages classes were aggregated.

| | |
|-------------|---|
| poly2ggplot | <i>Convert a spatialpolygon to a data frame for a ggplot2 use</i> |
|-------------|---|

Description

Convert a spatialpolygon to a data frame for a ggplot2 use

Usage

```
poly2ggplot(file = NULL, poly = NULL, id = NULL)
```

Arguments

| | |
|------|--|
| file | : File path to shape file |
| poly | : names of a SpatialPolygon if NULL file |
| id | : id variable for polygons |

Value

A "polygg" object, to be used with ggplot2 (ggMap for example)

Author(s)

Edouard Chatignoux

ShapDep

French administrative districts limits (Departement borders), simplified to be used with ggMap (polygg type)

Usage

```
data( ShapDep )
```

Format

A data frame with 2404 rows and 8 variables

Details

- long numeric (123255.6089–1242403.8507)
- lat numeric (6049568.1597–7110958.5478)
- order numeric (1–38)
- hole logical (0–0)
- piece factor avec 1 niveaux (1–1)
- id dept number : character (01–95)
- group factor avec 96 niveaux (01.1–95.1)
- INSEE_DEP character (01–95)

Index

*Topic **datasets**

- lopnm.alldist, [5](#)
- lopnm.CalibSet, [5](#)
- nhlw.alldist, [6](#)
- nhlw.CalibSet, [7](#)
- ShapDep, [8](#)

brewer.pal, [3](#)

CalibInc, [2](#)

ggMap, [3](#)

LogNormPI, [4](#)

lopnm.alldist, [5](#)

lopnm.CalibSet, [5](#)

nhlw.alldist, [6](#)

nhlw.CalibSet, [7](#)

poly2ggplot, [7](#)

ShapDep, [8](#)