



Cetyltrimethoxysilane

CAS: 16415-12-6

Product Information

Chemical Name: Cetyltrimethoxysilane

Product Code: LT-9116

Molecular Formula: $C_{19}H_{42}O_3Si$

Molecular Weight: 346

CAS No.: 16415-12-6

Properties and Reactivity

Colorless to light yellow transparent liquid, solid at low temperature, easily soluble in hydrocarbons, ethers, ketones and other general polar or non-polar organic solvents. Easily hydrolyzed and condensed to form polysiloxane.

Technical Data

Typical Characteristics	Value
Appearance	Colorless to light yellow transparent liquid
Purity	$\geq 95.0\%$
Density at 20°C	0.8770-0.8970g/ml
Boiling point at	160~162°C/0.4KPa
Flash point	165°C
Refractive index 25°C	1.4250-1.4450

Note: the above data is for reference only, cannot be as a technical specification

Application

The introduction of long chain alkyl modified groups into silicone molecules can give silicone products new characteristics. As a new type of organosilane coupling agent, long chain alkyl trimethoxysilane can be used to treat inorganic materials (such as glass, SiO_2 , Al_2O_3 , kaolin, mica, SiC, talc, etc.) to improve the compatibility of inorganic materials and organic materials (such as plastics, rubber, oil, adhesives) and enhance the mechanical properties of products. It is used as a glass anti-fogging agent,

which can protect blank glass and film treatment glass (optical anti-reflection film, vacuum anti-reflection film, reflection film), and protect optical parts and precision instruments with scales and metal frames; It can be used as a cultural relic protection agent to prevent the destruction of cultural relics by acid corrosion and freeze-thaw weathering. Used as fabric finishing agent, it can make cotton, linen, wool and blended fabrics full (with thickening effect), smooth, wool feeling strong, and can effectively enhance the hydrophobicity of fabrics; It can also be used for modification of engineering plastics, waterproof and anticorrosion of buildings, and demoulding of rubber plastics.

It can also be used for surface modification of ultrafine powders, such as stationary phase surface treatment of chromatographic columns or separated materials.

Product safety, handing and storage

Before using the product, you should carefully read the latest product safety technical information and toxicity data of the product as well as the correct storage and use information of the product.

The container should be sealed after opening to prevent water vapor from entering and producing hydrolysis.

The expiry time of the product is indicated on the label. Beyond this time, it does not mean that the product is no longer usable, and it can still be used after the performance test confirms that it is qualified.

Packaging

The size of the available packages can be checked with International Sales Department of Anhui Moon Technology Co.,Ltd.

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants

within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.