



Anhui Moon Technology Co., Ltd


Room 449, Building 3, Industrial Park, 1151 Yanan South Road, Bengbu City, Anhui Province, China

TEL, FAX: +86-552-2079969 POST CODE: 233000

MOON N-Octyl triethoxysilane

Product description

Structural formula:



Molecular formula: C₁₄H₃₂O₃Si

Molecular weigh: 276.49

CAS No.: 2943-75-1

Chemical name:

N-Octyl triethoxysilane

Characteristic

It is an octyl functional group silane with a colorless or slightly yellow transparent liquid. It is soluble in most organic solvents such as acetone, benzene, ether and carbon tetrachloride.

Physical and chemical data

Item	Data
Appearance	Colorless transparent liquid
Purity	≥98.0%
Density 20°Cg/ml	0.8740-0.8840
Refractive Index 25°C	1.4090-1.4190

Note: The above data is for reference only and cannot be formulated as a technical specification

Applications

After diluted with an appropriate solvent, MOON-6341 can be used to formulate waterproof products. The formulated product will penetrate and provide hydrophobicity through chemical reaction with the cement substrate. The treated substrate is hydrophobic and retains its original appearance.

MOON-6341 can be used as a surface treatment agent for inorganic fillers or pigments such as titanium dioxide to improve the affinity and wettability with basic resins such as paints, adhesives and sealants.

It is widely used as a waterproofing agent in commercial buildings, parking/garages, highways, bridge structures, and as a filler surface treatment. Specific performance is: as a building waterproof agent, protective agent, can form



Anhui Moon Technology Co., Ltd

Room 449, Building 3, Industrial Park, 1151 Yanan South Road, Bengbu City, Anhui Province, China

TEL, FAX: +86-552-2079969 POST CODE: 233000

in the substrate surface hydrophobic layer, effectively prevent water seepage, sun, acid and alkali erosion, extend the service life of the building;Used as surface treatment agent for inorganic fillers to improve the dispersibility and compatibility of fillers in plastics, rubber and resins;As a dispersant for pigments, the treated pigments have better dispersibility.

Product safety, handling and storage

After the container is opened, it should be sealed to prevent water vapor from entering to produce hydrolysis.

Stored in the original unopened container at room temperature, this product has a shelf life of one year from the date of production, and expired products are tested

After passing, the buyer decides whether to continue to use it.

Remarks: The company is only responsible for the sales specifications of the products at the time of shipment, and is not responsible for any indirect or incidental damages.

Package

5L,10L,25L,200L,1000L

