



Anhui Moon Technology Co., Ltd.

Room 449, Building 3, Industrial Park, 1151 Yanan South Road, Bengshan District, Anhui China
POST CODE: 233030 Email: echo@ahmoontech.com TEL, FAX: +86-552-2079969

MOON Potassium methyl silicate TDS

Potassium methyl silicate

I. Chemical names

Potassium Methylsiliconate

II. Structural formula

CH₃K₃O₃Si CAS:31795-24-1

III. Technical indicators

ITEM	Indicators	
Appearance	Colorless to light yellow liquid	
Solid content	42±2%	52±2%
Silsesquioxane	20% or higher	25% or higher
Density (25 °C, g/cm ³)	1.3 ~ 1.4	
PH	13	
Flammability	incombustible	
Dilutive	Dilute in any proportion with water	

IV. Performance and application

Potassium methyl silicate can react with carbon dioxide or other acidic compounds in the air to form insoluble network waterproof breathable film inside and on the surface of the substrate, with excellent waterproof, impermeable, moisture-proof, anti-aging and anti-pollution advantages. This product is simple in construction, low in price, durable in effect, and wear-resistant, brush-resistant, high and low temperature (-50 ~ 150°C). Can be used as: stone, brick, ceramic, cement mortar, perlite, gypsum and fiber gypsum board and other porous materials such as hydrophobic treatment, can be treated in the material internal and surface waterproof effect, reduce water absorption, while can maintain the original color, ventilation and appearance of the material characteristics.

V. Packaging, storage and transportation

The product is packed in 25L and 200L plastic drums, rigid plastic composite medium bulk containers (IBC) TC10 00S and stored in a cool and dry place. This product belongs to non-dangerous goods, which can be transported according to ordinary cargo conditions.