




Vinyl Silicone oil

PRODUCT NAME

Moon- Vinyl Silicone oil

DESCRIPTION

This is a kind of vinyl modified polydimethyl siloxane, the structural formula as follows:



Molecular weight is between 20 and 100,000 (manufacture according to the needs of the customers)

Except smooth, soft, shining and so on, which is easy to react with hydrogen silicone oil, also attend others several reaction.

SPECIFICATION

ITEMS	SPECIFICATIONS	
Appearance	Colorless	transparent liquid
Viscosity(25°C mpa.s)	20-100000	
Vinyl content (%)	0-20	
Volatitle(150°C 3h)	≤3%	
Heavy metal ion content	≤10ppm	

USE

1. The filler of silicone rubber, to increase the hardness and intensity.
2. The main material of LSR, thermal forming silicone rubber and LED pouring sealant.
3. React with polyurethane, acrylic acid and other organic material, will be made out more outstanding new material.(e.g coating)

USAGE AND DOSAGE

As additive agent: 5%-10%

As basic material : 50%-100%

Attention

This is a kind of active material, which is easy to react with other products, so pay attention do mix with other products in the transport.





Common viscosity

产品型号 Product model	外观 Appearance	粘度 Viscosity 25℃ mm ² %	挥发份 Volatile matter	乙烯基 Vinyl silicone content (mol%)
Viscosity 100	Colorless tasteless transparent oily liquid	90-110	≤1.5	2.80-3.10
Viscosity 1000	Colorless tasteless transparent oily liquid	900-1100	≤1.0	0.80-0.90
Viscosity 2000	Colorless tasteless transparent oily liquid	1800-2000	≤1.0	0.60-0.70
Viscosity 10000	Colorless tasteless transparent oily liquid	9000-11000	≤1.0	0.30-0.40
Viscosity 20000	Colorless tasteless transparent oily liquid	18000-22000	≤1.0	0.28-0.38
Viscosity 100000	Colorless tasteless transparent oily liquid	80000-100000	≤1.0	0.08-0.15

