



Anhui MOON Technology Co., Ltd.

Room 449, Building 3, 1151 Yanan South Road, Bengbu City, Anhui Province, China
TEL, FAX: +86-552-2079969 POST CODE: 233000

D-10

Anhui MOON Technology Co., Ltd.

Version: 3.0

Chemical Safety Technical Specification - prepared in accordance with GB/T 16483 (2008), GB/T 17519 (2013)

2. HAZARDS IDENTIFICATION

1. 1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Name of substance/preparation

Commercial product name: D-10

Chemical name: Methyl tri acetoxysilane

1.2 Use of substance/preparation

Industrial, crosslinker for silicone sealant

1.3 Company information

Manufacturer/distributor: ANHUI MOON TECHNOLOGY CO.,LTD

ADD:Room 449, Building 3, Industrial Park, 1151 Yanan South Road, Bengbu City, Anhui Province, China

Postal code:233000

Tel/Fax: +86-552-2079969

1.4 Revision Date

2020.07.01

2.1 GHS Classification

Physical hazard

Flammable liquids

Category 4

Health hazards

Skin corrosion/irritation

Category 1B

Severe eye damage/eye irritation

Category 1

Environmental hazards

Unclassified

2.2 GHS Label Elements



Pictogram

Signal word

Danger

Hazard statement(s)

H227

Combustible liquid

H314

Causes severe skin burns and eye damage.

Precautionary statement(s)

P280

Wear protective gloves/ eye protection/ face protection.



Anhui MOON Technology Co., Ltd.

Room 449, Building 3, 1151 Yanan South Road, Bengbu City, Anhui Province, China
TEL, FAX: +86-552-2079969 POST CODE: 233000

P264	Clean the skin thoroughly after operation.
P362	Remove the contaminated clothes and clean them before they can be reused.
P321	Specific treatment (see first aid guidance provided on this label).
P271	Use outdoors or in well ventilated areas.
P260	Do not breathing dust/ fume/ gas/ mist/ vapours/ spray.

Reaction statement(s)

P305 + P351 + P338	If entering the eyes: Wash carefully with water for a few minutes. Such as wearing contact lenses and easy to remove, remove contact lenses then continue flushing.
P304 + P340	If inhaled move the patient to a fresh air to rest and maintain a comfortable breathing position.
P312	If you feel unwell, call a detox center or doctor.
P337+P332+P313	If you still feel eye irritation or skin irritation: seek medical attention/consultation.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

Storage statement(s)

P233 +P271	Keep containers closed and can only be used outdoors or in well ventilated areas.
Waste disposal P501	Dispose of contents/container in accordance with local regulation

2.2 Other effects

None known

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Chemical characterization (substance)

Ingredients Name	CAS No.
Methyltriacetoxysilane	4253-34-3

3.2 Hazardous ingredients

Chemical name	CAS No.	Concentration
Methyltriacetoxysilane	4253-34-3	≥90.0%
Acetic acid	64-19-7	≤5%
Dimer		≤5%

4. FIRST AID MEASURES

4.1 General information

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of



Anhui MOON Technology Co., Ltd.

Room 449, Building 3, 1151 Yanan South Road, Bengbu City, Anhui Province, China
TEL, FAX: +86-552-2079969 POST CODE: 233000

dangerous area.

4.2 After inhalation

Move the victim to fresh air, keep breathing clear and rest. If breathing stops, carry out artificial respiration as soon as possible. If you have difficult breathing, you need to provide oxygen immediately.

Keep the patient warm, in serious cases or not immediately fully recover edi-ass.

4.3 After contact with the skin

Remove/remove all contaminated clothing immediately.

Gently wash with plenty of soap and water for 15 minutes to remove the dirt.

If large areas of skin hand damage or continuous irritation, please seek medical attention.

Wash your clothes before you use them.

4.4 After contact with the eyes

Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.5 After swallowing

Don't vomiting is allowed.

Never feed anything from your mouth to a person who is severely unconscious.

If the patient is conscious, rinse your mouth with water and apply 24 full cups of milk or warm water.

Seek medical attention as soon as you feel unwell.

4.6 Advice for the physician

Rescuers are required to wear personal protective clothing, such as rubber gloves and airtight goggles.

5. FIRE FIGHTING MEASURES

5.1 Flash point

Flash point is about 69.5°C (Test method: closed cup).

5.2 Suitable extinguishing media

Alcohol resistant foam, carbon dioxide, dry chemical.

5.3 Specific hazards during fire fighting

Vapors are heavier than air and may travel to a source of ignition and flash back. Static electricity will accumulate and may ignite vapors. Prevent a possible fire hazard by bonding and grounding or inert gas purge.

5.4 Special protective equipment for fire fighting

Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

5.5 Additional advice

Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions

Wear personal protection equipment. Keep unprotected persons away. Ensure adequate ventilation. Remove all sources of ignition. Do not swallow. Avoid breathing vapors, mist or gas. Avoid contact with skin, eyes and clothing. If material is released indicate risk of slipping.



Anhui MOON Technology Co., Ltd.

Room 449, Building 3, 1151 Yanan South Road, Bengbu City, Anhui Province, China
TEL, FAX: +86-552-2079969 POST CODE: 233000

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Discharge into the environment must be avoided.
Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Do not allow run-off from fire fighting to enter drains or water courses.

6.3 Methods and materials for containment and removal of spillage.

Absorbed with inert adsorbent and treated as hazardous waste
Stored in a suitable enclosed processing container

7. HANDLING AND STORAGE

7.1 Handling

Precautions for safe handling

Use with adequate ventilation.

Use air supply or self-contained breathing apparatus to provide ventilation, When the product is used.

Avoid contact with eyes.

Avoid contact with skin.

Avoid breathing steam, mist, dust or smoke.

Keep container tightly closed.

Don't swallow.

Develop good industrial hygiene habits. Wash before eating, drinking or smoking.

Precautions against fire

Take measures for fire protection.

7.2 Storage

Store in a cool, dry, airy fireproof area away from substances that cannot coexist.

Keep container tightly closed.

Open containers must be carefully resealed and placed in a vertical position to prevent leakage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure limits

Component	CAS No.	Exposure Limits
Methyltriacetoxysilane	4253-34-3	Reference acetic acid comments.
Acetic acid	64-19-7	China: TWA 10 mg/m ³ . STEL 20 mg/m ³ . OSHA PEL (final rule): TWA 10 ppm and ACGIH TLV: TWA 10 ppm, STEL 15 ppm.

8.2 Exposure in the work place limited and controlled

8.2.1 Personal protection

Respiratory Protection: Wearing a filtered gas mask (half mask) when the concentration in the air exceeds the standard.

Air-carrying respirators should be worn when emergency rescue or evacuation.

Hand protection: Chemical protective gloves should be worn.

Eye Protection: Wearing chemical lys to protect your eyes.



Anhui MOON Technology Co., Ltd.

Room 449, Building 3, 1151 Yanan South Road, Bengbu City, Anhui Province, China
TEL, FAX: +86-552-2079969 POST CODE: 233000

Skin protection: Protective clothing should be worn. Wearing protective boots if necessary.

8.2.2 Environmental protection

Local Ventilation: Recommended

General Ventilation: Recommended

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state/form.....: Liquid
Color.....: Clear to light yellow
pH.....: 4.4(25°C)
Boiling point.....: 110~112°C (17mmHg)
Melting point.....: 40.5°C
Flash point.....: 69.5°C(tag closed cup)
Molecular Weight.....: 220.3g/mol
Refractive index n_D^{25}: 1.4045~1.4055
Ignition temperature.....: No data available
Oxidizing properties.....: No
Upper explosion limit.....: No data available
Lower explosion limit.....: No data available
Vapor pressure.....: No data available
Vapor density.....: No data available
Density/relative density.....: 1.16~1.17g/cm³
Solubility.....: React with water
Heat of combustion.....: No data available
Viscosity(dynamic).....: No data available

10. STABILITY AND REACTIVITY

10.1 General information

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

10.2 Chemical stability: Humidity sensitive

10.3 Reactive

Conditions to avoid: Water (Including a small amount of moisture in the air), Oxidants, metal.Incompatible materials, ignition sources, excess heat

Decomposition products: The amount of carbon dioxide and for the incomplete combustion of carbon, silicon dioxide, acetic acid

Hazardous polymerization: Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

11.1 Route of Exposure: Inhalation, skin contact and accidental ingestion.

11.2 Signs and Symptoms of Overexposure:



Anhui MOON Technology Co., Ltd.

Room 449, Building 3, 1151 Yanan South Road, Bengbu City, Anhui Province, China
TEL, FAX: +86-552-2079969 POST CODE: 233000

Harmful if swallowed. Causes severe skin burns and eye damage.

11.3 Acute Toxicity:

Chemical Name	CAS No.	LD50 (Oral)	LD50 (Dermal)	LC50 (Inhalation)
Methyltriacetoxysilane	4253-34-3	2060mg/kg (Rat)		

Eyes: May cause irreversible damage and burns to the eyes. Vapor may cause eye irritation.

Skin: Corrosive. Burns skin upon short periods of contact.

Ingestion: Harmful if swallowed. Corrosive. May cause severe and permanent damage to the mouth, throat and stomach.

Inhalation: Vapor irritating to the respiratory tract.

11.4 Chronic Toxicity

Skin: No known applicable information.

Ingestion: Repeated ingestion or swallowing large amounts may injure internally.

Inhalation: Prolonged or repeated exposure by inhalation may injure internally.

12. ECOLOGICAL INFORMATION

12.1 Aquatic and Terrestrial Ecotoxicity

Ecotoxicity Effects:

Toxicity to daphnia and	No data available
Toxicity to fish	No data available
Toxicity to Bacterial	No data available
Toxicity to algae	No data available

12.2 Residual / degradability:

This product is hydrolyzed in water or moist air, releasing acetic acid and silicone compounds

12.3 Bioaccumulative Potential Bioaccumulation: No bioaccumulation potential.

12.4 Mobility in Soil: No data available.

12.5 Additional Environmental Information:

Toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Product disposal:	Dispose of in accordance with local regulations.
Packaging disposal:	Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

14.1 Land transport regulations

Valuation..... : hazardous product
Class.....:8
Packing group.....:III
UN-Number.....: 3265
Proper Shipping Name.....: Corrosive liquid, acidic,organic,n.o.s.
Technical name.....: Methyltriacetoxysilane
EMS.....: F-A; S-B



Anhui MOON Technology Co., Ltd.

Room 449, Building 3, 1151 Yanan South Road, Bengbu City, Anhui Province, China
TEL, FAX: +86-552-2079969 POST CODE: 233000

15. REGULATORY INFORMATION

15.1 National regulations

Provisions of the Regulations for the Safe Handling of Chemicals in the Workplace [(1996) Ministry of Labour issued 423], particularly those relating to the safe use, production, storage and transportation of dangerous chemicals.

15.2 Chemical inventories:

AICS: All ingredients listed or exempt.

IECSC: All ingredients listed or exempt.

KECL: All ingredients listed or exempt.

EINECS: All ingredients listed or exempt.

TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

MITI: Not determined.

DSL: All chemical substances in this material are included on or exempted from the DSL.

16. OTHER INFORMATION

Prepared by Anhui Moon Tech Co.,Ltd.

(R) indicates Registered Trademark

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific materials designated herein and may not be valid for such materials used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.

-End of MSDS -