



Technical Data Sheet

Methyl triacetoxysilane CAS: 4253-34-3

Product Information

D-10 (methyltriacetoxysilane)

Molecular formula: C₇H₁₂O₆Si

Molecular weight: 220.25

CAS No. : 4253-34-3

Product Features

A pungent smell, white or light yellow crystal at room temperature, when the temperature is greater than 40°C is colorless to light yellow transparent low viscosity liquid.

Physicochemical data

Properties	Numerical value
Appearance (40 ° C)	Colorless/light yellow clear liquid
purity	90.0% or higher
Density (40 ° C)	1.15-1.18g /ml
Boiling point 17mmHg	110~ 112°C
Closed cup flash point	87 °C
Refractive index (40 ° C)	1.4000~ 1.4300

Note: The above data is for reference only and cannot be formulated as technical specifications

Reaction properties

D-10 has strong hydrolytic activity and can react with water without catalyst at room temperature. The hydrolytic activity is between alkoxysilane and chlorosilane.

D-10 is acidic and reacts violently with alkaline substances.

D-10 has three hydrolysable groups that cross-link with water or hydroxyl groups.

Product Applications

Deacetic acid type single component room temperature vulcanized silicone rubber crosslinking agent. D-10 is the main crosslinking agent of the deacetic type RTV-1, which can be used either alone or with other acyl Oxy-silane is used in combination to achieve the desired properties and curing speed. The recommended addition of D-10 is 3-5% of the total quality of the glue produced.

Precautions

The theoretical crystallization point of this product is 40°C, in the actual storage (seal is not opened) process, when the ambient temperature is lower than 40°C, there may be crystallization, check whether there is crystallization before use. If crystallization has occurred, it should not be used directly. It is recommended to use it after drying (no more than 80°C). The color of the product will become darker after multiple baking. Please try to use it once after baking and melting. The acid RTV1 produced as a crosslinking agent may crystallize below 10°C.

Please adjust the formula according to the sales region or season.

The product will release acetic acid from the moisture in the air over a long period of time during storage. After a long period of storage, the content may decrease

Do the corresponding detection and evaluation before use, and make the corresponding adjustment according to the detection situation.

Products that have been opened but not used up are more likely to deteriorate during storage. In this case, please use them after assessment and confirmation.

There will be acetic acid produced during the use of the product, and personal protective measures should be taken during use. When opening the lid of the barrel, it is necessary to do a good job of personal protection and slowly open the barrel to avoid punching material injury due to inconsistency of internal and external air pressure after long-term storage. The product will react violently when it encounters water, please take evasive measures. If the reaction involves the reaction with water, please do a good job of process control to avoid over-reaction All adverse effects caused by the intensity.

The product is acidic and will react with alkaline substances. Please avoid it when storing or using the product. When the product meets the moisture in the air, flake or granular crystals will be formed. The part of the conveying pipeline that is in contact with the air often produces crystals. Please react before using the product Filter equipment is installed before the kettle to avoid crystals entering the reaction system affecting product quality. The product is easy to crystallize in low temperature environment, please take insulation measures for the pipeline according to the actual local situation, to avoid crystallization in the pipeline, blocking the pipeline and causing products

Quality safety accident.

The color of the product may become dark after a long time. Please store in a cool place. For discolored products, please evaluate before use.

The product is very corrosive, can not directly contact the body, such as accidental contact, please rinse with plenty of water, if not relieved, please seek medical attention in time.

The product is acidic, please avoid contact with materials that are easy to be corroded by acetic acid, to avoid the introduction of other impurities or other adverse effects due to corrosion.

If the product is exposed for a long time, it may become cloudy or crystalline. Please avoid the product being exposed for a long time. If the exposure time is too long, please evaluate before use. Avoid affecting the quality of the product.

Keep away from fire, heat sources, and no smoking in the workplace.

If canning is required, the flow rate should be controlled, and there is a grounding device to prevent static electricity accumulation. When handling, light loading and unloading should be done to prevent damage to packaging and containers.

The empty containers may contain harmful substances. Please take protective measures and handle them according to laws and regulations. Wash your hands after use. Do not eat or drink in the workplace. It should be stored separately from oxidants and edible chemicals, and should not be mixed.

Product safety, handling and storage

Before using the product, you should carefully read the latest product safety technical information and toxicity data of the product as well as the correct storage and use information of the product.

The container should be sealed after opening to prevent water vapor from entering and hydrolyzing. The effective time of the product is indicated on the label. Beyond this time, it does not mean that the product is no longer usable. After the performance test confirms that it is qualified, Can still be used.

Packaging

The size of the available containers can be checked with Anhui Moon Technology Co., Ltd.'s suppliers.

This product information, as well as all technical advice, is based on our current level of experience and knowledge. We accept no liability whatsoever, including for known third party intellectual property rights. In particular, we do not make any guarantee or warranty in a legal sense as to the nature of the Products. We reserve the right to make any changes to the product information due to technological progress or further development. The customer carefully tests and inspects the product itself. This description of the nature of the product should also be verified by the Customer through professional testing. References to grades used by other companies are neither recommendations nor exclusions from the availability of similar products.

Anhui Moon Technology Co., Ltd.'s sole warranty is that the products meet the Anhui Moon Technology Co., Ltd. sales specifications at the time of shipment.

Your only remedy for breach of Warranty by Anhui Moon Technology Co., Ltd. to a refund of the purchase price or replacement of any product that does not comply with the WARRANTY.

