



Anhui Moon Technology Co., Ltd.

Room 449, Building 3, Industrial Park, 1151 Yanan South Road, Bengshan District, Anhui China

POST CODE:233030 Email:echo@ahmoontech.com TEL,FAX: +86-552-2079969

Dibutyltin diacetate CAS: 1067-33-0

Product Information

D-70 (dibutyltin diacetate)

Molecular formula: C₁₂H₂₄O₄Sn

Molecular weight: 351.03

CAS No. : 1067-33-0

Product Features

D-70 is a light yellow clear liquid. Soluble in benzene, toluene, ethanol, acetone, ethyl acetate, chloroform, carbon tetrachloride, benzene, ethanol, petroleum ether and most other common solvents and various industrial plasticizers, insoluble in water. Promote fast gel and surface cure.

Physicochemical data

Properties	Numerical value
appearance	Light yellow clear liquid
Tin content	30 to 33%
Density 25 ° C	1.32 g/ml
Boiling point 10mmHg	142~ 145 ° C
Closed cup flash point	> 110 ° C
Refractive index 20 ° C	1.470

Note: The above data is for reference only and cannot be formulated as technical specifications

Reaction properties

D-70 is stable in aqueous solution, but hydrolyzes at room temperature in alkaline solution.

Product Applications

Mainly used as room temperature vulcanized silicone rubber catalyst. Especially suitable for deacetic acid type silicone products. Its characteristic is that the catalytic speed is faster than dibutyltin silicate. In order to reduce its acetic acid odor, dibutyltin dibutyltin diacetate can be used in combination with dibutyltin dibutyltin diacetate; Dibutyltin dibutylsilicate is 1:9 or 2:8.

Product security, handling and storage

Before using the product, carefully read the latest product safety technical information and toxicity data of the product to ensure the correct storage, transportation and use of the product.

The container should be sealed after opening to prevent water vapor from entering and hydrolyzing. The effective time of the product is indicated on the label. Beyond this time, it does not mean that the product is no longer usable, and can still be used after the performance test confirms that it is qualified.

Packaging

The size of the available containers can be checked with Moon Tech.

This product information, as well as all technical advice, is based on our current level of experience and knowledge. We accept no liability whatsoever, including for known third party intellectual property rights. In particular, we do not make any guarantee or warranty in a legal sense as to the nature of the Products. We reserve the right to make any changes to the product information due to technological progress or further development. The customer carefully tests and inspects the product itself. This description of the nature of the product should also be verified by the Customer through professional testing. References to grades used by other companies are neither recommendations nor exclusions from the availability of similar products.

Moon Tech sole warranty is that the products meet the Moon Tech sales specifications at the time of shipment.

Your only remedy for breach of Warranty by Moon Tech to a refund of the purchase price or replacement of any product that does not comply with the WARRANTY.