

mysql 基础sql语句

```
select * from t\G;
\G : 将查询结果按列打印
create table t
(a int unsigned,
b int unsigned
)
engine=INNODB;
insert into t select 1, 2;
select a - b from t;
set sql_mode='NO_UNSIGNED_SUBTRACTION';
select a - b from t;
select a between c and d; (检查a是否在c,d区间内)
mysql> alter table t change column a a int(4) unsigned zerofill;
Query OK, 0 rows affected (0.77 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql>
mysql> select a, b from t\G;
***** 1. row *****
a: 0001
b: 2
1 row in set (0.01 sec)
```

```
ERROR:
No query specified
```

```
mysql> select * from t;
+-----+-----+
| a     | b     |
+-----+-----+
| 0001  | 2     |
+-----+-----+
1 row in set (0.00 sec)
```

```
mysql>
mysql> select a, HEX(a) from t;
+-----+-----+
| a     | HEX(a) |
+-----+-----+
| 0001  | 1      |
+-----+-----+
1 row in set (0.03 sec)
```

```
mysql>
mysql> select @@global.sql_mode;
+-----+
| @@global.sql_mode |
+-----+
|                    |
+-----+
1 row in set (0.00 sec)
```

```
mysql> select @@global.sql_mode\G;
***** 1. row *****
```

```
@@global.sql_mode:
1 row in set (0.00 sec)
```

```
ERROR:
No query specified
```

```
mysql> select @@session.sql_mode\G
***** 1. row *****
@@session.sql_mode: NO_UNSIGNED_SUBTRACTION
1 row in set (0.00 sec)
```

```
mysql> set global sql_mode='strict_trans_tables';
Query OK, 0 rows affected (0.00 sec)
```

```
mysql> select @@global.sql_mode\G;
***** 1. row *****
@@global.sql_mode: STRICT_TRANS_TABLES
1 row in set (0.00 sec)
```

```
ERROR:
No query specified
```

```
mysql> create table z (a varchar(10)) engine=innodb;
Query OK, 0 rows affected (0.01 sec)
```

```
mysql>
mysql> insert into z select "aaa";
Query OK, 1 row affected (0.00 sec)
Records: 1 Duplicates: 0 Warnings: 0
```

```
mysql> select * from z;
+-----+
| a      |
+-----+
| aaa    |
+-----+
1 row in set (0.00 sec)
```

```
mysql>
mysql> set sql_mode='ANSI_QUOTES';
Query OK, 0 rows affected (0.00 sec)
```

```
mysql> insert into z select "aaa";
ERROR 1054 (42S22): Unknown column 'aaa' in 'field list'
mysql>
```

```
mysql> select * from z;
+-----+
| a      |
+-----+
| aaa    |
+-----+
1 row in set (0.00 sec)
```

```
mysql>
mysql> select 0 between -1 and 1\G;
***** 1. row *****
0 between -1 and 1: 1
1 row in set (0.00 sec)
```

ERROR:

No query specified

```
mysql> select 0 between -1 and 1;
```

```
+-----+
| 0 between -1 and 1 |
+-----+
|                  1 |
+-----+
```

1 row in set (0.00 sec)

```
mysql> select @@sql_mode;
```

```
+-----+
| @@sql_mode |
+-----+
| ANSI_QUOTES |
+-----+
```

1 row in set (0.00 sec)

```
mysql> select between -1 and 1;
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'between -1 and 1' at line 1

```
mysql>
```

```
mysql> select 1 between -1 and 1;
```

```
+-----+
| 1 between -1 and 1 |
+-----+
|                  1 |
+-----+
```

1 row in set (0.00 sec)

```
mysql> select 10 between -1 and 1;
```

```
+-----+
| 10 between -1 and 1 |
+-----+
|                  0 |
+-----+
```

1 row in set (0.00 sec)

```
mysql> select 10 between 9 and 10;
```

```
+-----+
| 10 between 9 and 10 |
+-----+
|                  1 |
+-----+
```

1 row in set (0.01 sec)

```
mysql> select 9 between 9 and 10;
```

```
+-----+
| 9 between 9 and 10 |
+-----+
|                  1 |
+-----+
```

1 row in set (0.00 sec)

```
mysql> select 8 between 9 and 10;
```

```
+-----+
```

| 8 between 9 and 10 |

+-----+

| 0 |

+-----+

1 row in set (0.00 sec)