

YLBUF.ylbuf_to_cen_interface_v20

```
CREATE OR REPLACE PROCEDURE YLBUF.ylbuf_to_cen_interface_v20 IS
    v_cnt          INTEGER;
    v_exception_msg VARCHAR2(3000);
BEGIN
    --tb_dic_medicines
    BEGIN
        INSERT /*+ append nologging */
        INTO cen_interface_v20.tb_dic_medicines
            (yljgdm, yyzbdm, ybmlbm, sybz, tycm, ynzjzb, posid)
        SELECT DISTINCT yljgdm, substrb(yyzbdm, 1, 20), ybmlbm, sybz, tycm,
            ynzjzb, '319001'
        FROM    (SELECT /*+ parallel(a, 8) */
            yljgdm, xmbm AS yyzbdm, xmbmyb AS ybmlbm, '1' AS sybz,
            mxxmmc AS tycm, '0' AS ynzjzb
        FROM    ylbuf.tb_his_mz_fee_detail a
        WHERE   mxfylb IN ('12', '13', '14')
        AND     llbz = '1'
        UNION
        SELECT /*+ parallel(b, 8) */
            yljgdm, xmbm, ybmlbm, '1', mxxmmc, '0'
        FROM    ylbuf.tb_his_zy_fee_detail b
        WHERE   mxfylb IN ('12', '13', '14')) r;
        v_cnt := SQL%ROWCOUNT;

        INSERT INTO cenbuf.t_def_dataprocessing_log
            (id, processing_date, p_tablename, processing_info, process_count,
            log_type, info_class, notel)
        VALUES
            (cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_DIC_MEDICINES',
            '完成对TB_DIC_MEDICINES表的处理', v_cnt, '6', '1',
            'ylbuf->cen_interface_v20');
        COMMIT;
    EXCEPTION
        WHEN OTHERS THEN
            v_exception_msg := substr(SQLERRM, 1, 500);
            ROLLBACK;
            INSERT INTO cenbuf.t_def_dataprocessing_log
                (id, processing_date, p_tablename, processing_info, exception_msg,
                log_type, info_class, notel) --写日志记录异常信息
            VALUES
                (cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_DIC_MEDICINES',
                'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
                v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');

            COMMIT;
    END;
    -----

    --tb_dic_materials
    BEGIN
        INSERT /*+ append nologging */
        INTO cen_interface_v20.tb_dic_materials
            (yljgdm, yyzbdm, ybmlbm, xmwsdm, xmmc, sfdw, sfdj, sfxdlb, sybz,
```

```

        ynzjbz, posid)
SELECT DISTINCT yljgdm, substrb(yyzbdm, 1, 20), ybmlbm, xmwsdm, xmmc,
                sfdw, sfdj, sfxdlb, sybz, ynzjbz, '319001'
FROM    (SELECT /*+ parallel(a, 8) */
        yljgdm, xmbm AS yyzbdm, xmbmyb AS ybmlbm,
        substr(xmbmyb, 2, 10) AS xmwsdm, mxxmmc AS xmmc,
        mxxmdw AS sfdw, mxxmdj AS sfdj, '9' AS sfxdlb, '1' AS sybz,
        '0' AS ynzjbz
FROM      ylbuff.tb_his_mz_fee_detail a
WHERE     mxfylb NOT IN ('12', '13', '14')
AND       llbz = '1'
UNION
SELECT /*+ parallel(b, 8) */
        yljgdm, xmbm, ybmlbm, substr(ybmlbm, 2, 10), mxxmmc, mxxmdw,
        mxxmdj, '9', '1', '0'
FROM      ylbuff.tb_his_zy_fee_detail b
WHERE     mxfylb NOT IN ('12', '13', '14')) r;
v_cnt := SQL%ROWCOUNT;

INSERT INTO cenbuff.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, process_count,
 log_type, info_class, notel)
VALUES
(cenbuff.seq_dataprocessing_log.nextval, SYSDATE, 'TB_DIC_MATERIALS',
 '完成对TB_DIC_MATERIALS表的处理', v_cnt, '6', '1',
 'ylbuff->cen_interface_v20');
COMMIT;

EXCEPTION
WHEN OTHERS THEN
    v_exception_msg := substr(SQLERRM, 1, 500);
ROLLBACK;
INSERT INTO cenbuff.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, exception_msg,
 log_type, info_class, notel) --写日志记录异常信息
VALUES
(cenbuff.seq_dataprocessing_log.nextval, SYSDATE, 'TB_DIC_MATERIALS',
 'YLBUFF到CEN_INTERFACE_V20过程中出现异常,详细信息见v_exception_msg和scripts字段的内容.',
 v_exception_msg, '6', '3', 'ylbuff->cen_interface_v20');

COMMIT;
END;

-----

--tb_cis_dradvice_detail
BEGIN
UPDATE /*+ parallel(t, 8) */ ylbuff.tb_cis_dradvice_detail t
SET     llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbuff.tb_cis_dradvice_detail t
WHERE llbz = '1' and to_char(YZXDSJ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';

INSERT /*+ append nologging */
INTO cen_interface_v20.tb_cis_dradvice_detail
(yljgdm, yzid, jzlsh, cxbz, kh, klx, bq, xdkbmb, xdrgh, xdrxm, yzxdsj,
 zxksbm, zxrgh, zrxrm, yzzxsj, yzzzs, yzsm, yzzh, yzlb, yzmxbm,
 yzmxbmby, yzmxmc, yzlx, ypgg, ypyf, yypd, jl, dw, mcs1, mcdw, yf,

```

```

yyts, sfps, ypsl, ypdw, jydm, jcbw, bz, mj, ylyl1, ylyl2, posid)
SELECT /*+ parallel(t, 8) */
ylygdm, yzid, jzlsh, cxbz, kh, klx, bq, xdkbmb, xdrgh, xdrxm, yzxsj,
zxksbm, zxrgh, zrxrm, nvl(yzxsj, yzxsj), nvl(yzxsj, yzxsj), yzsm,
yzzh, yzlb, yzmxbm, yzbyb, yzmxmc, yzlx, ypgg, ypyf, yypd, jl,
substr(dw, 1, 64), mcs1, substr(mcdw, 1, 64), yf, yyts, sfps, ypsl,
substr(ypdw, 1, 64), jydm, jcbw, bz, mj, ylyl1, ylyl2, '319001'
FROM ylbud.tb_cis_drAdvice_detail t
WHERE llbz = '1';

```

```

DELETE /*+ parallel(t, 8) */
FROM ylbud.tb_cis_drAdvice_detail t
WHERE llbz = '1';
v_cnt := SQL%ROWCOUNT;

```

```

INSERT INTO cenbud.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, process_count,
log_type, info_class, note1)
VALUES
(cenbud.seq_dataprocessing_log.nextval, SYSDATE,
'TB_CIS_DRADVICE_DETAIL', '完成对TB_CIS_DRADVICE_DETAIL表的处理', v_cnt, '6',
'1', 'ylbud->cen_interface_v20');
COMMIT;

```

```

EXECUTE IMMEDIATE 'ALTER TABLE ylbud.tb_cis_drAdvice_detail SHRINK SPACE';

```

EXCEPTION

```

WHEN OTHERS THEN
v_exception_msg := substr(SQLERRM, 1, 500);
ROLLBACK;
INSERT INTO cenbud.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, exception_msg,
log_type, info_class, note1) --写日志记录异常信息
VALUES
(cenbud.seq_dataprocessing_log.nextval, SYSDATE,
'TB_CIS_DRADVICE_DETAIL',
'YLBUD到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
v_exception_msg, '6', '3', 'ylbud->cen_interface_v20');

```

```

COMMIT;

```

END;

BEGIN

```

UPDATE /*+ parallel(t, 8) */ ylbud.tb_cis_leavehospital_summary t
SET llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbud.tb_cis_leavehospital_summary t
WHERE llbz = '1' and to_char(CYSJ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';

```

```

INSERT /*+ append nologging */
INTO cen_interface_v20.tb_cis_leavehospital_summary
(ks, kh, klx, ch, xm, xb, nl, rysj, cysj, zyts, mzzd, ryzd, cyzd,
ryzztz, jchz, tsjc, zlge, hbz, cyqk, cyyz, zljg, zyzsgh, zyzsxm,
zyysgh, zyzsxm, yzbtbl, yzbtb2, wjlj, xgbz, mj, ylyl1, jzlsh, ylygdm,
posid)

```

```

SELECT /*+ parallel(t, 8) */
ks, kh, klx, ch, xm, decode(xb, '4', '3', '5', '3', xb), nl,
to_char(rysj, 'yyyymmdd'), to_char(cysj, 'yyyymmdd'), zyts, mzzd,
ryzd, cyzd, ryzztz, jchz, tsjc, zlgc, hbz, cyqk, cyyz, zljg, zyzsgh,
zzysxm, zyzsgh, zyysxm, yyztb1, yyztb2, wjlj,
decode(xgbz, '2', '1', '3', '2', xgbz), mj, ylyl1, jz1sh, yljgdm,
'319001'
FROM ylbuff.tb_cis_leavehospital_summary t
WHERE llbz = '1';

```

```

DELETE /*+ parallel(t, 8) */
FROM ylbuff.tb_cis_leavehospital_summary t
WHERE llbz = '1';
v_cnt := SQL%ROWCOUNT;

```

```

INSERT INTO cenbuff.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, process_count,
log_type, info_class, note1)
VALUES
(cenbuff.seq_dataprocessing_log.nextval, SYSDATE,
'TB_CIS_LEAVEHOSPITAL_SUMMARY', '完成对TB_CIS_LEAVEHOSPITAL_SUMMARY表的处理',
v_cnt, '6', '1', 'ylbuff->cen_interface_v20');
COMMIT;

```

```

EXECUTE IMMEDIATE 'ALTER TABLE ylbuff.tb_cis_leavehospital_summary SHRINK SPACE';

```

EXCEPTION

```

WHEN OTHERS THEN
v_exception_msg := substr(SQLERRM, 1, 500);
ROLLBACK;
INSERT INTO cenbuff.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, exception_msg,
log_type, info_class, note1) --写日志记录异常信息
VALUES
(cenbuff.seq_dataprocessing_log.nextval, SYSDATE,
'TB_CIS_LEAVEHOSPITAL_SUMMARY',
'YLBUFF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
v_exception_msg, '6', '3', 'ylbuff->cen_interface_v20');

```

COMMIT;

END;

BEGIN

```

UPDATE /*+ parallel(t, 8) */ ylbuff.tb_cis_prescription_detail t
SET llbz = '1';

```

```

DELETE /*+ parallel(t, 8) */
FROM ylbuff.tb_cis_prescription_detail t
WHERE llbz = '1' and to_char(KFRQ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';

```

```

INSERT /*+ append nologging */
INTO cen_interface_v20.tb_cis_prescription_detail
(cyh, cfmhx, yljgdm, jz1sh, cxbz, kh, klx, jzksdm, kfys, kfysxm, kfrq,
xmbm, xmbmyb, xmmc, cflx, jxdm, ypgg, ypsl, ypdw, cfts, yzzh, sypc,
jl, dw, mcs1, mcdw, yf, yyts, jydm, sfps, jcbw, bz, mj, ylyl1, ylyl2,

```

```

    posid)
SELECT /*+ parallel(t, 8) */
    cyh, cfmhx, yljgdm, jzls, '1', kh, klx, jzksdm, kfys, kfysxm, kfrq,
    xmbm, xmbmyb, xmmc, cflx, jxdm, ypgg, ypsl, ypdw, cfts, yzzh, sypc,
    jl, substr(dw, 1, 64), mcs1, substr(mcdw, 1, 64), yf, yyts, jydm,
    sfps, jcbw, bz, mj, ylyl1, ylyl2, '319001'
FROM    ylbuf.tb_cis_prescription_detail t
WHERE   llbz = '1';

```

```

DELETE /*+ parallel(t, 8) */
FROM ylbuf.tb_cis_prescription_detail t
WHERE llbz = '1';
v_cnt := SQL%ROWCOUNT;

```

```

INSERT INTO cenbuf.t_def_dataprocessing_log
    (id, processing_date, p_tablename, processing_info, process_count,
     log_type, info_class, note1)
VALUES
    (cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
     'TB_CIS_PRESCRIPTION_DETAIL', '完成对TB_CIS_PRESCRIPTION_DETAIL表的处理',
     v_cnt, '6', '1', 'ylbuf->cen_interface_v20');
COMMIT;

```

```

EXECUTE IMMEDIATE 'ALTER TABLE ylbuf.tb_cis_prescription_detail SHRINK SPACE';

```

```

EXCEPTION
    WHEN OTHERS THEN
        v_exception_msg := substr(SQLERRM, 1, 500);
        ROLLBACK;
        INSERT INTO cenbuf.t_def_dataprocessing_log
            (id, processing_date, p_tablename, processing_info, exception_msg,
             log_type, info_class, note1) --写日志记录异常信息
        VALUES
            (cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
             'TB_CIS_PRESCRIPTION_DETAIL',
             'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
             v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');

        COMMIT;

```

```

END;

```

```

BEGIN

```

```

UPDATE /*+ parallel(t, 8) */ ylbuf.tb_dic_department t SET llbz = '1';

```

```

INSERT /*+ append nologging */
INTO cen_interface_v20.tb_dic_department
    (yljgdm, yyksdm, yyksmc, ybdm, sm, wsjdm, posid)
SELECT /*+ parallel(t, 8) */
    yljgdm, yyksdm, yyksmc, ybdm, sm, '-', '319001'
FROM    ylbuf.tb_dic_department t
WHERE   llbz = '1';

```

```

DELETE /*+ parallel(t, 8) */
FROM ylbuf.tb_dic_department t
WHERE llbz = '1';

```

```
v_cnt := SQL%ROWCOUNT;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, process_count,  
log_type, info_class, notel)
```

```
VALUES
```

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_DIC_DEPARTMENT',  
'完成对TB_DIC_DEPARTMENT表的处理', v_cnt, '6', '1',  
'ylbuf->cen_interface_v20');
```

```
COMMIT;
```

```
EXCEPTION
```

```
WHEN OTHERS THEN
```

```
v_exception_msg := substr(SQLERRM, 1, 500);
```

```
ROLLBACK;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, exception_msg,  
log_type, info_class, notel) --写日志记录异常信息
```

```
VALUES
```

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,  
'TB_DIC_DEPARTMENT',  
'YLBUF到CEN_INTERFACE_V20过程中出现异常,详细信息见v_exception_msg和scripts字段的内容.',  
v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');
```

```
COMMIT;
```

```
END;
```

```
-----  
BEGIN
```

```
UPDATE /*+ parallel(t, 8) */ ylbuf.tb_dic_practitioner t
```

```
SET    llbz = '1';
```

```
INSERT /*+ append nologging */
```

```
INTO cen_interface_v20.tb_dic_practitioner
```

```
(gh, yljgdm, zcm, xm, sfzh, ssks, zwdm, zhiw, zcdm, zhic, csrq, lb,  
zhuany, posid)
```

```
SELECT /*+ parallel(t, 8) */
```

```
gh, yljgdm, MAX(zcm) zcm, MAX(xm) xm, MAX(sfzh) sfzh, MAX(ssks) ssks,  
MAX(zwdm) zwdm, MAX(zhiw) zhiw, MAX(zcdm) zcdm, MAX(zhic) zhic,  
MAX(csrq) csrq,  
MAX(decode(lb, '01', '11', '02', '21', '03', '41', '04', '80', '70')) lb,  
MAX(zhuany) zhuany, '319001'
```

```
FROM    ylbuf.tb_dic_practitioner t
```

```
WHERE    llbz = '1'
```

```
GROUP BY gh, yljgdm;
```

```
DELETE /*+ parallel(t, 8) */
```

```
FROM ylbuf.tb_dic_practitioner t
```

```
WHERE    llbz = '1';
```

```
v_cnt := SQL%ROWCOUNT;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, process_count,  
log_type, info_class, notel)
```

```
VALUES
```

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
```

```
'TB_DIC_PRACTITIONER', '完成对TB_DIC_PRACTITIONER表的处理', v_cnt, '6', '1',  
'ylbuf->cen_interface_v20');
```

```
COMMIT;
```

```
EXECUTE IMMEDIATE 'ALTER TABLE ylbuf.tb_dic_practitioner SHRINK SPACE';
```

```
EXCEPTION
```

```
WHEN OTHERS THEN
```

```
v_exception_msg := substr(SQLERRM, 1, 500);
```

```
ROLLBACK;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, exception_msg,
```

```
log_type, info_class, notel) --写日志记录异常信息
```

```
VALUES
```

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
```

```
'TB_DIC_PRACTITIONER',
```

```
'YLBUF到CEN_INTERFACE_V20过程中出现异常,详细信息见v_exception_msg和scripts字段的内容.',
```

```
v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');
```

```
COMMIT;
```

```
END;
```

```
BEGIN
```

```
UPDATE /*+ parallel(t, 8) */ ylbuf.tb_his_mz_fee_detail t
```

```
SET llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
```

```
FROM ylbuf.tb_his_mz_fee_detail t
```

```
WHERE llbz = '1' and to_char(STFSJ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';
```

```
INSERT /*+ append nologging */
```

```
INTO cen_interface_v20.tb_his_mz_fee_detail
```

```
(sfmxid, xgbz, yljgdm, jzlsh, kh, klx, cfidh, fph, mxfy1b, stfsj,
```

```
mxxmbm, mxxmbmyb, mxxmmc, mxxmdw, mxxmdj, mxxmsl, mxxmje, ylyl1,
```

```
ylyl2, posid)
```

```
SELECT /*+ parallel(t, 8) */
```

```
sfmxid, xgbz, yljgdm, jzlsh, kh, klx, cfidh, fph, mxfy1b, stfsj, xmbm,
```

```
xmbmyb, mxxmmc, mxxmdw, mxxmdj, mxxmsl, mxxmje, ylyl1, ylyl2,
```

```
'319001'
```

```
FROM ylbuf.tb_his_mz_fee_detail t
```

```
WHERE llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
```

```
FROM ylbuf.tb_his_mz_fee_detail t
```

```
WHERE llbz = '1';
```

```
v_cnt := SQL%ROWCOUNT;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, process_count,
```

```
log_type, info_class, notel)
```

```
VALUES
```

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
```

```
'TB_HIS_MZ_FEE_DETAIL', '完成对TB_HIS_MZ_FEE_DETAIL表的处理', v_cnt, '6',
```

```
'1', 'ylbuf->cen_interface_v20');
```

```
COMMIT;
```

```
EXECUTE IMMEDIATE 'ALTER TABLE ylbud.tb_his_mz_fee_detail SHRINK SPACE';
```

```
EXCEPTION
```

```
WHEN OTHERS THEN
```

```
    v_exception_msg := substr(SQLERRM, 1, 500);
```

```
    ROLLBACK;
```

```
    INSERT INTO cenbud.t_def_dataprocessing_log
```

```
        (id, processing_date, p_tablename, processing_info, exception_msg,
```

```
         log_type, info_class, notel) --写日志记录异常信息
```

```
VALUES
```

```
    (cenbud.seq_dataprocessing_log.nextval, SYSDATE,
```

```
     'TB_HIS_MZ_FEE_DETAIL',
```

```
     'YLBUD到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
```

```
     v_exception_msg, '6', '3', 'ylbud->cen_interface_v20');
```

```
COMMIT;
```

```
END;
```

```
BEGIN
```

```
UPDATE /*+ parallel(t, 8) */ ylbud.tb_his_zy_fee_detail t
```

```
SET    llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
```

```
FROM ylbud.tb_his_zy_fee_detail t
```

```
WHERE llbz = '1' and to_char(STFSJ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';
```

```
INSERT /*+ append nologging */
```

```
INTO cen_interface_v20.tb_his_zy_fee_detail
```

```
    (yljgdm, sfmxid, xgbz, jzlsj, kh, klx, yzid, fph, mxfylb, stfsj,
```

```
     mxmmbm, mxmmbmyb, mxmmmc, mxmmdw, mxmmdj, mxmxsl, mxxmje, ylyl1,
```

```
     ylyl2, posid)
```

```
SELECT /*+ parallel(t, 8) */
```

```
    yljgdm, sfmxid, xgbz, jzlsj, kh, klx, yzid, fph, mxfylb, stfsj, xmbm,
```

```
    ybmlbm, substr(mxxmmc, 1, 512), substr(mxxmdw, 1, 64), mxmmdj, mxmxsl,
```

```
    mxxmje, ylyl1, ylyl2, '319001'
```

```
FROM   ylbud.tb_his_zy_fee_detail t
```

```
WHERE  llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
```

```
FROM ylbud.tb_his_zy_fee_detail t
```

```
WHERE llbz = '1';
```

```
v_cnt := SQL%ROWCOUNT;
```

```
INSERT INTO cenbud.t_def_dataprocessing_log
```

```
    (id, processing_date, p_tablename, processing_info, process_count,
```

```
     log_type, info_class, notel)
```

```
VALUES
```

```
    (cenbud.seq_dataprocessing_log.nextval, SYSDATE,
```

```
     'TB_HIS_ZY_FEE_DETAIL', '完成对TB_HIS_ZY_FEE_DETAIL表的处理', v_cnt, '6',
```

```
     '1', 'ylbud->cen_interface_v20');
```

```
COMMIT;
```

```
EXECUTE IMMEDIATE 'ALTER TABLE ylbud.tb_his_zy_fee_detail SHRINK SPACE';
```


EXCEPTION

WHEN OTHERS THEN

v_exception_msg := substr(SQLERRM, 1, 500);

ROLLBACK;

INSERT INTO cenbuf.t_def_dataprocessing_log

(id, processing_date, p_tablename, processing_info, exception_msg,
log_type, info_class, notel) --写日志记录异常信息

VALUES

(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,

'TB_HIS_ZY_FEE_DETAIL',

'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',

v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');

COMMIT;

END;

BEGIN

UPDATE /*+ parallel(t, 8) */ ylbuff.tb_lis_allergy_result t

SET llbz = '1';

DELETE /*+ parallel(t, 8) */

FROM ylbuff.tb_lis_allergy_result t

WHERE llbz = '1' and TO_CHAR(BGRQ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';

INSERT /*+ append nologging */

INTO cen_interface_v20.tb_lis_allergy_result

(ymjglsh, yljgdm, bgdh, bgrq, xjdh, dyxh, ymdm, ymmc, jcjg, zphyl,
yind, yjhzj, xgbz, ylyl1, ylyl2, posid)

SELECT /*+ parallel(t, 8) */

ymjglsh, yljgdm, bgdh, bgrq, xjdh, dyxh, ymdm, ymmc, jcjg, zphyl,
yind, yjhzj, decode(xgbz, '2', '1', '3', '2', xgbz), ylyl1, ylyl2,
'319001'

FROM ylbuff.tb_lis_allergy_result t

WHERE llbz = '1';

DELETE /*+ parallel(t, 8) */

FROM ylbuff.tb_lis_allergy_result t

WHERE llbz = '1';

v_cnt := SQL%ROWCOUNT;

INSERT INTO cenbuf.t_def_dataprocessing_log

(id, processing_date, p_tablename, processing_info, process_count,
log_type, info_class, notel)

VALUES

(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,

'TB_LIS_ALLERGY_RESULT', '完成对TB_LIS_ALLERGY_RESULT表的处理', v_cnt, '6',

'1', 'ylbuf->cen_interface_v20');

COMMIT;

EXECUTE IMMEDIATE 'ALTER TABLE ylbuff.tb_lis_allergy_result SHRINK SPACE';

EXCEPTION

WHEN OTHERS THEN

v_exception_msg := substr(SQLERRM, 1, 500);

ROLLBACK;

```

INSERT INTO cenbuf.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, exception_msg,
log_type, info_class, notel) --写日志记录异常信息
VALUES
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
'TB_LIS_ALLERGY_RESULT',
'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');

COMMIT;

END;
-----

BEGIN

UPDATE /*+ parallel(t, 8) */ ylbuff.tb_lis_bacteria_result t
SET    llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbuff.tb_lis_bacteria_result t
WHERE  llbz = '1' and to_char(BGRQ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';

INSERT /*+ append nologging */
INTO cen_interface_v20.tb_lis_bacteria_result
(xjjglsh, yljgdm, bgdh, bgrq, xjdh, xjmc, jljs, byj, bysj, pytj, fxfs,
jcjg, jcjgwz, sbbm, yqbh, yqmc, xgbz, ylyl1, ylyl2, posid)
SELECT /*+ parallel(t, 8) */
xjjglsh, yljgdm, bgdh, bgrq, xjdh, xjmc, jljs, byj, bysj, pytj, fxfs,
jcjg, jcjgwz, sbbm, yqbh, yqmc,
decode(xgbz, '2', '1', '3', '2', xgbz), ylyl1, ylyl2, '319001'
FROM    ylbuff.tb_lis_bacteria_result t
WHERE   llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbuff.tb_lis_bacteria_result t
WHERE  llbz = '1';
v_cnt := SQL%ROWCOUNT;

INSERT INTO cenbuf.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, process_count,
log_type, info_class, notel)
VALUES
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
'TB_LIS_BACTERIA_RESULT', '完成对TB_LIS_BACTERIA_RESULT表的处理', v_cnt, '6',
'1', 'ylbuf->cen_interface_v20');
COMMIT;

EXECUTE IMMEDIATE 'ALTER TABLE ylbuff.tb_lis_bacteria_result SHRINK SPACE';

EXCEPTION
WHEN OTHERS THEN
v_exception_msg := substr(SQLERRM, 1, 500);
ROLLBACK;
INSERT INTO cenbuf.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, exception_msg,
log_type, info_class, notel) --写日志记录异常信息
VALUES

```

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
'TB_LIS_BACTERIA_RESULT',
'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');
```

```
COMMIT;
```

```
END;
```

```
BEGIN
```

```
UPDATE /*+ parallel(t, 8) */ ylbuff.tb_lis_indicators t SET llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
```

```
FROM ylbuff.tb_lis_indicators t
```

```
WHERE llbz = '1' and to_char(BGRQ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';
```

```
INSERT /*+ append nologging */
```

```
INTO cen_interface_v20.tb_lis_indicators
```

```
(jyzblsh, yljgdm, bgdh, bgrq, jcrgh, jcrxm, shrgh, shrxm, ybsfmd,
jczbmd, jcff, jczbmc, jczbjg, loinc, sbbm, yqbh, yqmc, ckz, jldw,
yets, yzid, dyxh, xgbz, ylyl1, ylyl2, posid)
```

```
SELECT /*+ parallel(t, 8) */
```

```
jyzblsh, yljgdm, bgdh, bgrq, jcrgh, jcrxm, shrgh, shrxm, ybsfmd,
jczbmd, jcff, jczbmc, jczbjg, loinc, sbbm, yqbh, yqmc, ckz, jldw,
yets, yzid, substr(dyxh, 1, 4),
```

```
decode(xgbz, '2', '1', '3', '2', xgbz), ylyl1, ylyl2, '319001'
```

```
FROM ylbuff.tb_lis_indicators t
```

```
WHERE llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
```

```
FROM ylbuff.tb_lis_indicators t
```

```
WHERE llbz = '1';
```

```
v_cnt := SQL%ROWCOUNT;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, process_count,
log_type, info_class, notel)
```

```
VALUES
```

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_LIS_INDICATORS',
'完成对TB_LIS_INDICATORS表的处理', v_cnt, '6', '1',
'ylbuf->cen_interface_v20');
```

```
COMMIT;
```

```
EXECUTE IMMEDIATE 'ALTER TABLE ylbuff.tb_lis_indicators SHRINK SPACE';
```

```
EXCEPTION
```

```
WHEN OTHERS THEN
```

```
v_exception_msg := substr(SQLERRM, 1, 500);
```

```
ROLLBACK;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, exception_msg,
log_type, info_class, notel) --写日志记录异常信息
```

```
VALUES
```

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
```

```
'TB_LIS_INDICATORS',
```

```
'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
```

```

        v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');

COMMIT;

END;
-----

BEGIN

UPDATE /*+ parallel(t, 8) */ ylbuf.tb_lis_report t SET llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbuf.tb_lis_report t
WHERE llbz = '1' and to_char(BGRQ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';

INSERT /*+ append nologging */
INTO cen_interface_v20.tb_lis_report
(wjlj, xgbz, ylyl1, ylyl2, yljgdm, bgdh, bgrq, jzls, mzzybz, kh, klx,
 brxm, brxb, brnl, sqrg, sqrxm, bgrgh, bgrxm, shrgh, shrxm, sqks, bq,
 ch, dyrq, sqrq, cjr, jyr, bgbz, bbdm, bbmc, bgdlbbm, bgdlb, mj,
 posid)
SELECT /*+ parallel(t, 8) */
wjlj, decode(xgbz, '2', '1', '3', '2', xgbz), ylyl1, ylyl2, yljgdm,
bgdh, bgrq, jzls, mzzybz, kh, klx, brxm,
decode(brxb, '4', '3', '5', '3', brxb), brnl, sqrg, sqrxm, bgrgh,
bgrxm, shrgh, shrxm, sqks, bq, ch, dyrq, sqrq, cjr, jyr, bgbz, bbdm,
bbmc, bgdlbbm, bgdlb, mj, '319001'
FROM ylbuf.tb_lis_report t
WHERE llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbuf.tb_lis_report t
WHERE llbz = '1';
v_cnt := SQL%ROWCOUNT;

INSERT INTO cenbuf.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, process_count,
 log_type, info_class, notel)
VALUES
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_LIS_REPORT',
 '完成对TB_LIS_REPORT表的处理', v_cnt, '6', '1', 'ylbuf->cen_interface_v20');
COMMIT;

EXECUTE IMMEDIATE 'ALTER TABLE ylbuf.tb_lis_report SHRINK SPACE';

EXCEPTION
WHEN OTHERS THEN
    v_exception_msg := substr(SQLERRM, 1, 500);
    ROLLBACK;
    INSERT INTO cenbuf.t_def_dataprocessing_log
    (id, processing_date, p_tablename, processing_info, exception_msg,
     log_type, info_class, notel) --写日志记录异常信息
    VALUES
    (cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_LIS_REPORT',
     'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
     v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');

COMMIT;

```

END;

BEGIN

```
UPDATE /*+ parallel(t, 8) */ ylbud.tb_operation_detail t
SET    llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbud.tb_operation_detail t
WHERE llbz = '1' and to_char(SSJSSJ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';

INSERT /*+ append nologging */
INTO cen_interface_v20.tb_operation_detail
(yljgdm, ssmxlsh, kh, klx, jzlsh, mzzybz, rjssbz, sslx, ssczbm,
 ssczmc, ssqzd, sshzd, sskssj, ssjssj, ssysgh, ssysxm, ssyszlgh,
 ssyszlxm, ssysz2gh, ssysz2xm, mzysgh, mzysxm, mzfs, qkyhdj, mj, xgbz,
 ylyll, posid)
SELECT /*+ parallel(t, 8) */
 yljgdm, ssmxlsh, kh, klx, jzlsh, mzzybz, rjssbz, sslx, ssczbm, ssczmc,
 ssqzd, sshzd, sskssj, ssjssj, ssysgh, ssysxm, ssyszlgh, ssyszlxm,
 ssysz2gh, ssysz2xm, mzysgh, mzysxm, mzfs, qkyhdj, mj,
 decode(xgbz, '2', '1', '3', '2', xgbz), ylyll, '319001'
FROM   ylbud.tb_operation_detail t
WHERE  llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbud.tb_operation_detail t
WHERE llbz = '1';
v_cnt := SQL%ROWCOUNT;

INSERT INTO cenbuf.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, process_count,
 log_type, info_class, note1)
VALUES
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
 'TB_OPERATION_DETAIL', '完成对TB_OPERATION_DETAIL表的处理', v_cnt, '6', '1',
 'ylbud->cen_interface_v20');
COMMIT;

EXECUTE IMMEDIATE 'ALTER TABLE ylbud.tb_operation_detail SHRINK SPACE';

EXCEPTION
WHEN OTHERS THEN
v_exception_msg := substr(SQLERRM, 1, 500);
ROLLBACK;
INSERT INTO cenbuf.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, exception_msg,
 log_type, info_class, note1) --写日志记录异常信息
VALUES
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
 'TB_OPERATION_DETAIL',
 'YLBUD到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
 v_exception_msg, '6', '3', 'ylbud->cen_interface_v20');

COMMIT;
```

END;

BEGIN

UPDATE /*+ parallel(t, 8) */ ylbuff.tb_ris_report t SET llbz = '1';

DELETE /*+ parallel(t, 8) */

FROM ylbuff.tb_ris_report t

WHERE llbz = '1' and to_char(JCSJ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';

INSERT /*+ append nologging */

INTO cen_interface_v20.tb_ris_report

(studyuid, yljgdm, jzlsj, mzzybz, kh, klx, brxm, brxb, patientid,
jcxmdm, sqdh, kdsj, jysj, examtype, sbbm, yqbm, sqks, sqgrh, sqrxm,
jcks, jcys, jcysgh, bgrq, bgsj, bgrgh, bgrxm, shrgh, shrxm, jcbw,
bwacr, jcmc, yys, bgldcd, yxbx, yxzd, bzhjy, sfyyy, xgbz, mj, ylyl1,
ylyl2, posid)

SELECT /*+ parallel(s, 8) */

s.studyuid, s.yljgdm, s.jzlsj, s.mzzybz, s.kh, s.klx, s.brxm,
decode(s.brxb, '4', '3', '5', '3', s.brxb), s.patientid, s.jcxmdm,
s.sqdh, s.kdsj, s.jcsj, s.examtype, s.sbbm, s.yqbm, s.sqks, s.sqgrh,
s.sqrxm, s.jcks, s.jcys, s.jcysgh, s.bgrq, s.bgsj, s.bgrgh, s.bgrxm,
s.shrgh, s.shrxm, s.jcbw, s.bwacr, s.jcmc, s.yys, s.bgldcd, s.yxbx,
s.yxzd, s.bzhjy, s.sfyyy, decode(xgbz, '2', '1', '3', '2', xgbz),
s.mj, s.ylyl1, s.ylyl2, '319001'

FROM (SELECT b.*

FROM (SELECT studyuid, yljgdm, MAX(instanceuid) instanceuid
FROM ylbuff.tb_ris_report
GROUP BY studyuid, yljgdm) a, ylbuff.tb_ris_report b
WHERE a.studyuid = b.studyuid
AND a.yljgdm = b.yljgdm
AND a.instanceuid = b.instanceuid) s

WHERE s.llbz = '1';

--INSTANCEUID字段大卫生中暂时无，医联3.1接口已上，之后升级请注意该字段

DELETE /*+ parallel(t, 8) */

FROM ylbuff.tb_ris_report t

WHERE llbz = '1';

v_cnt := SQL%ROWCOUNT;

INSERT INTO cenbuff.t_def_dataprocessing_log

(id, processing_date, p_tablename, processing_info, process_count,
log_type, info_class, notel)

VALUES

(cenbuff.seq_dataprocessing_log.nextval, SYSDATE, 'TB_RIS_REPORT',
'完成对TB_RIS_REPORT表的处理', v_cnt, '6', '1', 'ylbuff->cen_interface_v20');

COMMIT;

EXECUTE IMMEDIATE 'ALTER TABLE ylbuff.tb_ris_report SHRINK SPACE';

EXCEPTION

WHEN OTHERS THEN

v_exception_msg := substr(SQLERRM, 1, 500);

ROLLBACK;

INSERT INTO cenbuff.t_def_dataprocessing_log

(id, processing_date, p_tablename, processing_info, exception_msg,
log_type, info_class, notel) --写日志记录异常信息

VALUES

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_RIS_REPORT',  
'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',  
v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');
```

COMMIT;

END;

BEGIN

```
UPDATE /*+ parallel(t, 8) */ ylbuf.tb_ris_report2 t SET llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
```

```
FROM ylbuf.tb_ris_report2 t
```

```
WHERE llbz = '1' and to_char(JCSJ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';
```

```
INSERT /*+ append nologging */
```

```
INTO cen_interface_v20.tb_ris_report2
```

```
(studyuid, yljgdm, instanceuid, jzlsh, mzzybz, kh, klx, brxm, brxb,  
patientid, jcxmdm, sqdh, kdsj, jcsj, examtype, sbbm, yqbm, sqks,  
sqgrgh, sqrxm, jcks, jcys, jcysgh, bgrq, bgsj, bgrgh, bgrxm, shrgh,  
shrxm, jcbw, bwacr, jcmc, xgbz, mj, ylyl1, ylyl2, posid)
```

```
SELECT /*+ parallel(t, 8) */
```

```
studyuid, yljgdm, instanceuid, jzlsh, mzzybz, kh, klx, brxm,  
decode(brxb, '4', '3', '5', '3', brxb), patientid, jcxmdm, sqdh, kdsj,  
jcsj, examtype, sbbm, yqbm, sqks, sqgrgh, sqrxm, jcks, jcys, jcysgh,  
bgrq, bgsj, bgrgh, bgrxm, shrgh, shrxm, jcbw, bwacr, jcmc,  
decode(xgbz, '2', '1', '3', '2', xgbz), mj, ylyl1, ylyl2, '319001'  
FROM ylbuf.tb_ris_report2 t  
WHERE llbz = '1';
```

--INSTANCEUID字段大卫生中暂时无, 医联3.1接口已上, 之后升级请注意该字段

```
DELETE /*+ parallel(t, 8) */
```

```
FROM ylbuf.tb_ris_report2 t
```

```
WHERE llbz = '1';
```

```
v_cnt := SQL%ROWCOUNT;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, process_count,  
log_type, info_class, notel)
```

VALUES

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_RIS_REPORT2',  
'完成对TB_RIS_REPORT2表的处理', v_cnt, '6', '1', 'ylbuf->cen_interface_v20');
```

COMMIT;

```
EXECUTE IMMEDIATE 'ALTER TABLE ylbuf.tb_ris_report2 SHRINK SPACE';
```

EXCEPTION

WHEN OTHERS THEN

```
v_exception_msg := substr(SQLERRM, 1, 500);
```

```
ROLLBACK;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, exception_msg,  
log_type, info_class, notel) --写日志记录异常信息
```

VALUES

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_RIS_REPORT2',
```

```
'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',  
v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');
```

```
COMMIT;
```

```
END;
```

```
BEGIN
```

```
UPDATE /*+ parallel(t, 8) */ ylbuf.tb_ih_diagnosis_detail t  
SET    llbz = '1';  
  
DELETE /*+ parallel(t, 8) */  
FROM ylbuf.tb_ih_diagnosis_detail t  
WHERE llbz = '1' and to_char(ZDSJ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';
```

```
INSERT /*+ append nologging */  
INTO cen_interface_v20.tb_ih_diagnosis_detail  
(zyzdls, yljgdm, jzls, mzzybz, kh, klx, zdlxqf, zdlb, zdsj, zdbm,  
 bmlx, zdsm, cyzdbz, yzdbz, cyqkdm, mj, xgbz, ylyl1, ylyl2, posid)  
SELECT /*+ parallel(t, 8) */  
zyzdls, yljgdm, jzls, mzzybz, kh, klx, zdlxqf, zdlb, zdsj, zdbm,  
 bmlx, zdsm, cyzdbz, yzdbz, cyqkdm, mj,  
 decode(xgbz, '2', '1', '3', '2', xgbz), ylyl1, ylyl2, '319001'  
FROM ylbuf.tb_ih_diagnosis_detail t  
WHERE llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */  
FROM ylbuf.tb_ih_diagnosis_detail t  
WHERE llbz = '1';  
v_cnt := SQL%ROWCOUNT;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log  
(id, processing_date, p_tablename, processing_info, process_count,  
 log_type, info_class, notel)  
VALUES  
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,  
 'TB_IH_DIAGNOSIS_DETAIL', '完成对TB_IH_DIAGNOSIS_DETAIL表的处理', v_cnt, '6',  
 '1', 'ylbuf->cen_interface_v20');  
COMMIT;
```

```
EXECUTE IMMEDIATE 'ALTER TABLE ylbuf.tb_ih_diagnosis_detail SHRINK SPACE';
```

```
EXCEPTION
```

```
WHEN OTHERS THEN  
v_exception_msg := substr(SQLERRM, 1, 500);  
ROLLBACK;  
INSERT INTO cenbuf.t_def_dataprocessing_log  
(id, processing_date, p_tablename, processing_info, exception_msg,  
 log_type, info_class, notel) --写日志记录异常信息  
VALUES  
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,  
 'TB_IH_DIAGNOSIS_DETAIL',  
 'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',  
 v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');  
  
COMMIT;
```


END;

BEGIN

```
UPDATE /*+ parallel(t, 8) */ ylbuf.tb_yl_zy_medical_record t
SET    llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
FROM ylbuf.tb_yl_zy_medical_record t
WHERE llbz = '1' and to_char(CYSJ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01' and to_char(CYSJ, 'yyyymmdd') !=
'19000101';
```

```
INSERT /*+ append nologging */
INTO cen_interface_v20.tb_yl_zy_medical_record
(yljgdm, jzlsh, cisid, kh, klx, hzxm, jzlx, jzksbm, jzksc, cyksbm,
 cyksmc, rysj, cysj, xgbz, mj, ylyl1, ylyl2, posid)
SELECT /*+ parallel(t, 8) */
yljgdm, jzlsh, cisid, kh, klx, hzxm, jzlx, jzksbm, jzksc, cyksbm,
cyksmc, rysj, cysj, decode(xgbz, '2', '1', '3', '2', xgbz), mj, ylyl1,
ylyl2, '319001'
FROM   ylbuf.tb_yl_zy_medical_record t
WHERE  llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
FROM ylbuf.tb_yl_zy_medical_record t
WHERE llbz = '1';
v_cnt := SQL%ROWCOUNT;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, process_count,
 log_type, info_class, notel)
VALUES
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
'TB_YL_ZY_MEDICAL_RECORD', '完成对TB_YL_ZY_MEDICAL_RECORD表的处理', v_cnt,
'6', '1', 'ylbuf->cen_interface_v20');
COMMIT;
```

```
EXECUTE IMMEDIATE 'ALTER TABLE ylbuf.tb_yl_zy_medical_record SHRINK SPACE';
```

EXCEPTION

```
WHEN OTHERS THEN
v_exception_msg := substr(SQLERRM, 1, 500);
ROLLBACK;
INSERT INTO cenbuf.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, exception_msg,
 log_type, info_class, notel) --写日志记录异常信息
VALUES
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
'TB_YL_ZY_MEDICAL_RECORD',
'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');

COMMIT;
```

END;

BEGIN

```
UPDATE /*+ parallel(t, 8) */ ylbud.tb_yl_patient_information t
SET    llbz = '1';
```

```
INSERT /*+ append nologging */
INTO cen_interface_v20.tb_yl_patient_information
(yljgdm, kh, klx, fkdq, zjhm, zjlx, xb, xm, hzlx, hyzk, csrq, csd, mz,
 gj, dhbm, sjhm, gzdwyb, gzdwm, gzdwdz, jzdz, hkdz, hkdzyb, lxxm,
 lxxg, lxxdz, lxxrb, lxxdh, mj, xgbz, ywscsj, yydah, ylyl1, ylyl2,
 posid)
SELECT /*+ parallel(t, 8) */
 yljgdm, kh, klx, fkdq, zjhm,
 decode(zjlx, '1', '01', '2', '04', '3', '03', '6', '05', '7', '07',
        '99'), decode(xb, '4', '3', '5', '3', xb), xm,
 decode(hzlx, '0', '1', '1', '2', '2', '3', '5'), hyzk, csrq, csd, mz,
 gj, dhbm, sjhm, gzdwyb, gzdwm, gzdwdz, jzdz, hkdz, hkdzyb, lxxm,
 lxxg, lxxdz, lxxrb, lxxdh, mj,
 decode(xgbz, '2', '1', '3', '2', xgbz), ywscsj, yydah, ylyl1, ylyl2,
 '319001'
FROM    ylbud.tb_yl_patient_information t
WHERE   llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
FROM ylbud.tb_yl_patient_information t
WHERE llbz = '1';
v_cnt := SQL%ROWCOUNT;
```

```
INSERT INTO cenbud.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, process_count,
 log_type, info_class, notel)
VALUES
(cenbud.seq_dataprocessing_log.nextval, SYSDATE,
 'TB_YL_PATIENT_INFORMATION', '完成对TB_YL_PATIENT_INFORMATION表的处理',
 v_cnt, '6', '1', 'ylbud->cen_interface_v20');
COMMIT;
```

```
EXECUTE IMMEDIATE 'ALTER TABLE ylbud.tb_yl_patient_information SHRINK SPACE';
```

EXCEPTION

```
WHEN OTHERS THEN
 v_exception_msg := substr(SQLERRM, 1, 500);
ROLLBACK;
INSERT INTO cenbud.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, exception_msg,
 log_type, info_class, notel) --写日志记录异常信息
VALUES
(cenbud.seq_dataprocessing_log.nextval, SYSDATE,
 'TB_YL_PATIENT_INFORMATION',
 'YLBUD到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
 v_exception_msg, '6', '3', 'ylbud->cen_interface_v20');

COMMIT;
```

END;

BEGIN

```
UPDATE /*+ parallel(t, 8) */ ylbuff.tb_yl_mz_medical_record t
SET    llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbuff.tb_yl_mz_medical_record t
WHERE  llbz = '1' and to_char(JZKSRQ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';

INSERT /*+ append nologging */
INTO cen_interface_v20.tb_yl_mz_medical_record
    (yljgdm, jzlsh, kh, klx, hzxm, jzlx, jzksbm, jzksc, jzksrq, zzysgh,
     zzysxm, jzzdbm, bmlx, jzzdsm, zs, xgbz, mj, ylyl1, ylyl2, zzms, posid)
SELECT /*+ parallel(t, 8) */
    yljgdm, jzlsh, kh, klx, hzxm, decode(jzlx, '600', '999', jzlx),
    jzksbm, jzksc, jzksrq, zzysgh, zzysxm, jzzdbm, bmlx, jzzdsm, zs,
    decode(xgbz, '2', '1', '3', '2', xgbz), mj, ylyl1, ylyl2, zzms,
    '319001'
FROM    ylbuff.tb_yl_mz_medical_record t
WHERE   llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbuff.tb_yl_mz_medical_record t
WHERE  llbz = '1';
v_cnt := SQL%ROWCOUNT;

INSERT INTO cenbuff.t_def_dataprocessing_log
    (id, processing_date, p_tablename, processing_info, process_count,
     log_type, info_class, notel)
VALUES
    (cenbuff.seq_dataprocessing_log.nextval, SYSDATE,
     'TB_YL_MZ_MEDICAL_RECORD', '完成对TB_YL_MZ_MEDICAL_RECORD表的处理', v_cnt,
     '6', '1', 'ylbuff->cen_interface_v20');
COMMIT;

EXECUTE IMMEDIATE 'ALTER TABLE ylbuff.tb_yl_mz_medical_record SHRINK SPACE';
```

EXCEPTION

```
WHEN OTHERS THEN
    v_exception_msg := substr(SQLERRM, 1, 500);
    ROLLBACK;
    INSERT INTO cenbuff.t_def_dataprocessing_log
        (id, processing_date, p_tablename, processing_info, exception_msg,
         log_type, info_class, notel) --写日志记录异常信息
    VALUES
        (cenbuff.seq_dataprocessing_log.nextval, SYSDATE,
         'TB_YL_MZ_MEDICAL_RECORD',
         'YLBUFF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
         v_exception_msg, '6', '3', 'ylbuff->cen_interface_v20');

    COMMIT;
```

END;

----以下为2.0新增

BEGIN

```

UPDATE /*+ parallel(t, 8) */ ylbud.tb_his_mz_reg t SET llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbud.tb_his_mz_reg t
WHERE llbz = '1' and to_char(GHRQ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';

INSERT /*+ append nologging */
INTO cen_interface_v20.tb_his_mz_reg
(yljgdm, gthbz, ghbm, ghrq, stfbh, gthsj, gh1b, bxlx, ksbm, txbz,
 wdbz, zfzlf, zlf, qtf, kh, klx, yzssf, sfyy, posid)
SELECT /*+ parallel(t, 8) */
yljgdm, gthbz, ghbm, ghrq, stfbh, gthsj, gh1b,
decode(bxlx, '5', 'A', '6', '3', '8', 'B', bxlx), ksbm, txbz, wdbz,
zfzlf, zlf, qtf, kh, klx, yzssf, sfyy, '319001'
FROM ylbud.tb_his_mz_reg t
WHERE llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbud.tb_his_mz_reg t
WHERE llbz = '1';
v_cnt := SQL%ROWCOUNT;

INSERT INTO cenbud.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, process_count,
 log_type, info_class, notel)
VALUES
(cenbud.seq_dataprocessing_log.nextval, SYSDATE, 'TB_HIS_MZ_REG',
'完成对TB_HIS_MZ_REG表的处理', v_cnt, '6', '1', 'ylbud->cen_interface_v20');
COMMIT;

EXECUTE IMMEDIATE 'ALTER TABLE ylbud.tb_his_mz_reg SHRINK SPACE';

EXCEPTION
WHEN OTHERS THEN
v_exception_msg := substr(SQLERRM, 1, 500);
ROLLBACK;
INSERT INTO cenbud.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, exception_msg,
 log_type, info_class, notel) --写日志记录异常信息
VALUES
(cenbud.seq_dataprocessing_log.nextval, SYSDATE, 'TB_HIS_MZ_REG',
'YLBUD到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
v_exception_msg, '6', '3', 'ylbud->cen_interface_v20');

COMMIT;

END;

-----
BEGIN

UPDATE /*+ parallel(t, 8) */ ylbud.tb_his_zy_fee_detail_fs t
SET llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbud.tb_his_zy_fee_detail_fs t
WHERE llbz = '1' and to_char(FYFSSJ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';

INSERT /*+ append nologging */

```

```

INTO cen_interface_v20.tb_his_zy_fee_detail_fs
(yljgdm, mxfsid, xgbz, jzls, kh, klx, yzid, bxl, mxfylb, fyfssj,
 xmbm, ybmlb, mxmmc, mxmdw, mxmdj, mxmsl, mxmje, posid)
SELECT /*+ parallel(t, 8) */
 yljgdm, sfmxid, xgbz, jzls, kh, klx, yzid,
 decode(bxl, '5', 'A', '6', '3', '8', 'B', bxl), mxfylb, fyfssj,
 xmbm, ybmlb, substr(mxmmc, 1, 512), substr(mxmdw, 1, 64), mxmdj,
 mxmsl, mxmje, '319001'
FROM ylbuff.tb_his_zy_fee_detail_fs t
WHERE llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbuff.tb_his_zy_fee_detail_fs t
WHERE llbz = '1';
v_cnt := SQL%ROWCOUNT;

INSERT INTO cenbuff.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, process_count,
 log_type, info_class, notel)
VALUES
(cenbuff.seq_dataprocessing_log.nextval, SYSDATE,
 'TB_HIS_ZY_FEE_DETAIL_FS', '完成对TB_HIS_ZY_FEE_DETAIL_FS表的处理', v_cnt,
 '6', '1', 'ylbuff->cen_interface_v20');
COMMIT;

EXECUTE IMMEDIATE 'ALTER TABLE ylbuff.tb_his_zy_fee_detail_fs SHRINK SPACE';

```

```

EXCEPTION
WHEN OTHERS THEN
 v_exception_msg := substr(SQLERRM, 1, 500);
ROLLBACK;
INSERT INTO cenbuff.t_def_dataprocessing_log
(id, processing_date, p_tablename, processing_info, exception_msg,
 log_type, info_class, notel) --写日志记录异常信息
VALUES
(cenbuff.seq_dataprocessing_log.nextval, SYSDATE,
 'TB_HIS_ZY_FEE_DETAIL_FS',
 'YLBUFF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
 v_exception_msg, '6', '3', 'ylbuff->cen_interface_v20');

COMMIT;

```

END;

BEGIN

```

UPDATE /*+ parallel(t, 8) */ ylbuff.tb_his_mz_charge t SET llbz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbuff.tb_his_mz_charge t
WHERE llbz = '1' and to_char(STFRQ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';

INSERT /*+ append nologging */
INTO cen_interface_v20.tb_his_mz_charge
(yljgdm, stfbz, stfbh, stfrq, bxl, wdbz, stfsj, stfze, ybfwwzf,
 txfye, ghf, zlf, ssclf, jcf, hyf, tsf, spf, xyf, zcyf, zcaf, qtf,
 cfzs, kh, klx, yzssf, posid)
SELECT /*+ parallel(t, 8) */

```

```

        yljgdm, stfbz, stfbh, stfrq,
        decode(bx1x, '5', 'A', '6', '3', '8', 'B', bx1x), wdbz, stfsj, stfze,
        ybfwwzf, txfye, ghf, zlf, ssclf, jcf, hyf, tsf, spf, xyf, zcyf, zcaf,
        qtf, cfzs, kh, klx, yzssf, '319001'
FROM    ylbuf.tb_his_mz_charge t
WHERE   11bz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbuf.tb_his_mz_charge t
WHERE 11bz = '1';
v_cnt := SQL%ROWCOUNT;

INSERT INTO cenbuf.t_def_dataprocessing_log
        (id, processing_date, p_tablename, processing_info, process_count,
        log_type, info_class, notel)
VALUES
        (cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_HIS_MZ_CHARGE',
        '完成对TB_HIS_MZ_CHARGE表的处理', v_cnt, '6', '1',
        'ylbuf->cen_interface_v20');
COMMIT;

EXECUTE IMMEDIATE 'ALTER TABLE ylbuf.tb_his_mz_charge SHRINK SPACE';

EXCEPTION
WHEN OTHERS THEN
        v_exception_msg := substr(SQLERRM, 1, 500);
        ROLLBACK;
        INSERT INTO cenbuf.t_def_dataprocessing_log
                (id, processing_date, p_tablename, processing_info, exception_msg,
                log_type, info_class, notel) --写日志记录异常信息
        VALUES
                (cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_HIS_MZ_CHARGE',
                'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
                v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');

        COMMIT;

END;

-----
BEGIN

UPDATE /*+ parallel(t, 8) */ ylbuf.tb_his_zy_adm_reg t SET 11bz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbuf.tb_his_zy_adm_reg t
WHERE 11bz = '1' and TO_CHAR(RYSJ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';

INSERT /*+ append nologging */
INTO cen_interface_v20.tb_his_zy_adm_reg
        (yljgdm, zyid, ryks, rysj, lgbz, zfbz, posid)
SELECT /*+ parallel(t, 8) */
        yljgdm, zyid, ryks, rysj, lgbz, zfbz, '319001'
FROM    ylbuf.tb_his_zy_adm_reg t
WHERE   11bz = '1';

DELETE /*+ parallel(t, 8) */
FROM ylbuf.tb_his_zy_adm_reg t
WHERE 11bz = '1';

```

```
v_cnt := SQL%ROWCOUNT;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, process_count,  
log_type, info_class, note1)
```

```
VALUES
```

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_HIS_ZY_ADM_REG',  
'完成对TB_HIS_ZY_ADM_REG表的处理', v_cnt, '6', '1',  
'ylbuf->cen_interface_v20');
```

```
COMMIT;
```

```
EXECUTE IMMEDIATE 'ALTER TABLE ylbuf.tb_his_zy_adm_reg SHRINK SPACE';
```

```
EXCEPTION
```

```
WHEN OTHERS THEN
```

```
v_exception_msg := substr(SQLERRM, 1, 500);
```

```
ROLLBACK;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, exception_msg,  
log_type, info_class, note1) --写日志记录异常信息
```

```
VALUES
```

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE,  
'TB_HIS_ZY_ADM_REG',  
'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',  
v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');
```

```
COMMIT;
```

```
END;
```

```
-----  
BEGIN
```

```
UPDATE /*+ parallel(t, 8) */ ylbuf.tb_his_jz_charge t SET llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
```

```
FROM ylbuf.tb_his_jz_charge t
```

```
WHERE llbz = '1' and to_char(STFRQ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01';
```

```
INSERT /*+ append nologging */
```

```
INTO cen_interface_v20.tb_his_jz_charge
```

```
(yljgdm, stfbz, stfbh, stfrq, bxlx, zyid, stfsj, zfy, ybfwwzf, txfy,  
zyf, zlf, zhf, hlf, ssclf, jcf, hyf, tsf, spf, sxf, syf, xyf, zcyf,  
zcac, qtf, kh, klx, cybz, posid)
```

```
SELECT /*+ parallel(t, 8) */
```

```
yljgdm, stfbz, stfbh, stfrq,  
decode(bxlx, '5', 'A', '6', '3', '8', 'B', bxlx), zyid, stfsj, zfy,  
ybfwwzf, txfy, zyf, zlf, zhf, hlf, ssclf, jcf, hyf, tsf, spf, sxf,  
syf, xyf, zcyf, zcac, qtf, kh, klx, cybz, '319001'
```

```
FROM ylbuf.tb_his_jz_charge t
```

```
WHERE llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
```

```
FROM ylbuf.tb_his_jz_charge t
```

```
WHERE llbz = '1';
```

```
v_cnt := SQL%ROWCOUNT;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, process_count,  
log_type, info_class, notel)
```

```
VALUES
```

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_HIS_JZ_CHARGE',  
'完成对TB_HIS_JZ_CHARGE表的处理', v_cnt, '6', '1',  
'ylbuf->cen_interface_v20');
```

```
COMMIT;
```

```
EXECUTE IMMEDIATE 'ALTER TABLE ylbuf.tb_his_jz_charge SHRINK SPACE';
```

```
EXCEPTION
```

```
WHEN OTHERS THEN
```

```
v_exception_msg := substr(SQLERRM, 1, 500);
```

```
ROLLBACK;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, exception_msg,  
log_type, info_class, notel) --写日志记录异常信息
```

```
VALUES
```

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_HIS_JZ_CHARGE',  
'YLBUF到CEN_INTERFACE_V20过程中出现异常,详细信息见v_exception_msg和scripts字段的内容.',  
v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');
```

```
COMMIT;
```

```
END;
```

```
-----  
BEGIN
```

```
UPDATE /*+ parallel(t, 8) */ ylbuf.tb_his_zy_dis_reg t SET llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
```

```
FROM ylbuf.tb_his_zy_dis_reg t
```

```
WHERE llbz = '1' and to_char(CYSJ, 'YYYYMMDD') < to_char(sysdate - 17, 'YYYYMM') || '01' and to_char(CYSJ, 'yyyymmdd') !=  
'19000101';
```

```
INSERT /*+ append nologging */
```

```
INTO cen_interface_v20.tb_his_zy_dis_reg
```

```
(yljgdm, zyid, ryks, rysj, cyks, cysj, lgbz, bxlx, wdbz, txbz, kh,  
klx, zfbz, posid)
```

```
SELECT /*+ parallel(t, 8) */
```

```
yljgdm, zyid, ryks, rysj, cyks, cysj, lgbz,  
decode(bxlx, '5', 'A', '6', '3', '8', 'B', bxlx), wdbz, txbz, kh, klx,  
zfbz, '319001'
```

```
FROM ylbuf.tb_his_zy_dis_reg t
```

```
WHERE llbz = '1';
```

```
DELETE /*+ parallel(t, 8) */
```

```
FROM ylbuf.tb_his_zy_dis_reg t
```

```
WHERE llbz = '1';
```

```
v_cnt := SQL%ROWCOUNT;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
(id, processing_date, p_tablename, processing_info, process_count,  
log_type, info_class, notel)
```

```
VALUES
```

```
(cenbuf.seq_dataprocessing_log.nextval, SYSDATE, 'TB_HIS_ZY_DIS_REG',  
'完成对TB_HIS_ZY_DIS_REG表的处理', v_cnt, '6', '1',  
'ylbuf->cen_interface_v20');
```



```
COMMIT;
```

```
EXECUTE IMMEDIATE 'ALTER TABLE ylbuf.tb_his_zy_dis_reg SHRINK SPACE';
```

```
EXCEPTION
```

```
WHEN OTHERS THEN
```

```
    v_exception_msg := substr(SQLERRM, 1, 500);
```

```
ROLLBACK;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
    (id, processing_date, p_tablename, processing_info, exception_msg,
```

```
    log_type, info_class, note1) --写日志记录异常信息
```

```
VALUES
```

```
    (cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
```

```
    'TB_HIS_ZY_DIS_REG',
```

```
    'YLBUF到CEN_INTERFACE_V20过程中出现异常, 详细信息见v_exception_msg和scripts字段的内容.',
```

```
    v_exception_msg, '6', '3', 'ylbuf->cen_interface_v20');
```

```
COMMIT;
```

```
END;
```

```
INSERT INTO cenbuf.t_def_dataprocessing_log
```

```
    (id, processing_date, processing_info, log_type, info_class, note1)
```

```
VALUES
```

```
    (cenbuf.seq_dataprocessing_log.nextval, SYSDATE,
```

```
    '本次YLBUF->CEN_INTERFACE_V20的数据转移处理结束', '6', '1',
```

```
    'ylbuf->cen_interface_v20');
```

```
END ylbuf_to_cen_interface_v20;
```