

oracle 10g 研究ORACLE_HOME rdbms admin 下的脚本的功能 (18) awrrpt.sql

oracle 10g 研究ORACLE_HOME rdbms admin 下的脚本的功能 (18) awrrpt.sql

```
#This script defaults the dbid and instance number to that of the
Rem      current instance connected-to, then calls awrrpti.sql to produce
Rem      the Workload Repository report.
#

Rem $Header: awrrpt.sql 24-oct-2003.12:04:53 pbelknap Exp $
Rem
Rem awrrpt.sql
Rem
Rem Copyright (c) 1999, 2003, Oracle Corporation. All rights reserved.
Rem
Rem      NAME
Rem      awrrpt.sql
Rem
Rem      DESCRIPTION
Rem      This script defaults the dbid and instance number to that of the
Rem      current instance connected-to, then calls awrrpti.sql to produce
Rem      the Workload Repository report.
Rem
Rem      NOTES
Rem      Run as select_catalog privileges.
Rem      This report is based on the Statspack report.
Rem
Rem      If you want to use this script in an non-interactive fashion,
Rem      see the 'customer-customizable report settings' section in
Rem      awrrpti.sql
Rem
Rem      MODIFIED      (MM/DD/YY)
Rem      pbelknap      10/24/03 - swrfrpt to awrrpt
Rem      pbelknap      10/14/03 - moving params to rpti
Rem      pbelknap      10/02/03 - adding non-interactive mode cmnts
Rem      mlfeng         09/10/03 - heading on
Rem      aime           04/25/03 - aime_going_to_main
Rem      mlfeng         01/27/03 - mlfeng_swrf_reporting
Rem      mlfeng         01/13/03 - Update comments
Rem      mlfeng         07/08/02 - swrf flushing
Rem      mlfeng         06/12/02 - Created
Rem
--
-- Get the current database/instance information - this will be used
-- later in the report along with bid, eid to lookup snapshots

set echo off heading on underline on;
column inst_num heading "Inst Num" new_value inst_num format 99999;
column inst_name heading "Instance" new_value inst_name format a12;
column db_name heading "DB Name" new_value db_name format a12;
column dbid heading "DB Id" new_value dbid format 9999999999 just c;

prompt
prompt Current Instance
prompt ~~~~~
```

```
select d.dbid                dbid
       , d.name              db_name
       , i.instance_number  inst_num
       , i.instance_name    inst_name
from v$database d,
     v$instance i;
```

```
@@awrrpti
```

```
undefine num_days;
undefine report_type;
undefine report_name;
undefine begin_snap;
undefine end_snap;
--
-- End of file
```