

YJ29560 TECHdata - Modicon Modbus Plus

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Color Code Chart : No. 5 for Paired Cables (Western Electric Standard).pdf</p>
---	---

Description:

24 AWG stranded (7x32) tinned copper conductors, twisted pair, polyethylene insulated, overall 100% Beldfoil. shield plus a 90% tinned copper braid shield, 24 AWG tinned copper drain wire, chrome PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	24
Stranding	7x32
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PE - Polyethylene
---------------------	-------------------

PAIR:

Pair Lay Length :

Lay Length (in.)	Direction	Twists/ft (twist/ft)
2.5	Left Hand Lay	4.8

Pair Twists/ft.	4.8
Pair Color Code Chart	White/Blue and Blue/White

OUTER SHIELD:

Outer Shield Trade Name	Beldfoil®
Outer Shield Type	Tape/Braid

Outer Shield Material :

Layer Number	Material Trade Name	Type	Material	% Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	Tinned Copper Braid Shield	90

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	24
-----------------------------	----

YJ29560 TECHdata - Modicon Modbus Plus

Outer Shield Drain Wire Stranding	7x32
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:

Outer Jacket Material	PVC (Chrome)
-----------------------	--------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.265 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-30°C To +80°C
Temperature Rating	80°C
Bulk Cable Weight	40 lbs/1000 ft.
Max. Recommended Pulling Tension	72,000 lbs.
Min. Bend Radius (Install)	2.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM
CEC/C(UL) Specification	CM
AWM Specification	2919 (30 V)

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	N

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	123 Ohms
Nom. Capacitance Conductor to Conductor @ 1 KHz	11.3 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	25 pF/ft
Nominal Velocity of Propagation	66 %
Nominal Delay	1.6 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	24 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg. C	3.350 Ohms/1000 ft
Nom. Attenuation (dB/100 ft)	0.6 (@ 1 MHz) dB/100 ft.
Max. Operating Voltage - UL	300 V RMS
Other Maximum Continuous Currents	2.1 Amps per conductor @ 25°C

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
YJ29560	1 PR #24 PE SH PVC	1000	40	CHROME	C
YJ29560	1 PR #24 PE SH PVC	1500	60	CHROME	

YJ29560 TECHdata - Modicon Modbus Plus

--	--	--	--	--	--

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 2009-11-19

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.