New Generation Data Models and Dbmss Course - Assignment 1 - Crowdfunding Company

Carlo Falchi (Matr. 67340A)[1*]
and Francesco Palladini (Matr. 85652A)[1*]

[1]Department of Computer Science, University of Milan, Italy.

*Corresponding author(s). E-mail(s): carlo.falchi@studenti.unimi.it;
francesco.palladini@studenti.unimi.it;




Fig. 1: UML Diagram

1 Solution

The class Member has been chosen as a generalization of the classes Creator and Backer, because this simplifies the identification of a member, and it is also useful to implement feedback and contact information. To each member is associated zero or one Contact information. Both Creator and Backer classes are associated with the class Campaign. A campaign can be created by only a creator. A backer can promise pledges, modeled by the association Pledges, to a number of campaigns between 200 and 3000, with an average of 1000, as specified in the text. The attributes of Pledge are the amount, timestamp and transfer, a boolean attribute which determines if the promised amount is transferred. Pledge is connected to Transfer class, a class which represents the transfer of money, by the association transferredTo: more pledges can be transferred to a transfer, but each pledge can be associated only to a transfer. The class Category associated with campaign has the purpose of answering the second query, which otherwise would not be able to execute. A campaign can be associated to only one category, while a category can be associated with more campaigns. Finally, we have the class Feedback, which is a weak class identified by Member and Campaign. This class has a maximum of 2 billion instances, because we have annually 100.000 users and 2 millions of campaigns, so the multiplication of the number of users times the number of campaigns gives 2 billion total possible feedbacks per year. Of course 2 millions of feedbacks can be left by a user, while a user can be associated only with its feedbacks, and each campaign can receive 100.000 feedbacks, which is also the number of users, while a campaign is associated only with its feedbacks.

1.1 Assumption

1. First, we assume that the conceptual class diagram reports the annual amount of instances for classes and relations.
2. Since the number of categories is not given, we assume that they are 100, which can be a reasonable number of categories.
3. As the campaign period ends, and the system determines whether the campaign is successful, the attribute successful of the class Campaign is set to True
4. The attribute successful of Campaig has a default value of false
5. We assume the user will login to the platform using a email and a password, so we set email as key of the Member class

1.2 Constraints

The following constraints can be identified in the considered domain. Note that we report only the constraints that are not already included in the representation of the class diagram:

1. The password field of the Member class is an encrypted field
2. A campaign is succesfull if the total amount pledges meets or exceeds the funding goal
3. A pledge and its timestamp should be created only within the date range (start_date, end_date) of the campaign

4. The IBAN of the creator should have a length between 15 and 34 characters long and comply with the ISO 13616 standard
5. The SwiftCode should follow the ISO 9362 standard and being between 8 and 11 characters
6. When the campaign ends and is successful, the pledges funds are transferred from the backers to the creator
7. The date of the transfer should be after the end_date of the campaign
8. Creator and Backers can leave feedback only after the campaign ends successfully
9. Feedback consists of a numerical rating from 1 to 10
10. The end date of the campaign should be a date later than the start date
11. The attribute amount in Transfer is the sum of the amounts of the pledges involved in the transfer.

1.3 Workload

The workload is shown in Figure 2




Fig. 2: Representation Workload

1. To identify the top 5 most competitive campaigns, the entry point is the class Pledge, they are grouped by Campaign and ordered by the total number of pledges, then navigate to campaign to get title of the campaign. So the query path is (Pledge)→(Campaign)

2. The entry point is the Creator class, then we identify the category trough the campaign and get the highest average pledge amount in the Pledge class. Query path is (Creator) $\underset{creator}{\rightarrow}$ (Campaign)$\rightarrow$(Pledge) and Campaign $\underset{category}{\rightarrow}$ Category to identify the titles of categories
3. To identify the top 10 creators per month in the last year by number of successful campaigns, the entry point is the class Campaign. Campaigns are filtered by successful and end_date within the last year, and then grouped by the month of end_date and by their creator, navigating to the Creator class to order and select the top 10 creators for each month. So, the query path is (Campaign) $\underset{createdBy}{\rightarrow}$ (Creator).