



CSS

:is()
pseudo class.



USE CASES

For selecting

Different list types.



```
:is(ul, ol) li {  
  list-style: square;  
}
```

This is applied to list items inside both unordered and ordered lists

For selecting

Multiple states.

☆ PERSONAL FAVOURITE



```
button:is(:hover, :focus) {  
  background: hotpink;  
}
```

Background is changed during both focused and hovered states of the button

For selecting

Items inside a table row.



```
:is(thead, tfoot) tr :is(th, td) {  
  background: palegreen;  
}
```

Selects all **td** and **th** items inside table header and footer

For selecting

Multiple heading pseudo elements.



```
:is(h1, h2, h3)::before {  
  content: ">";  
}
```

Sets some content before all H1 - H3 headings

For selecting

Nested lists.



```
:is(ul, ol, menu) > :is(ul, ol, menu) {  
  font-size: 0.8rem;  
}
```

Selects the list containers that are already inside another list container

For selecting

First paragraph after any heading.



```
:is(h1, h2, h3, h4, h5, h6)+p {  
  color: blue;  
}
```



BABY WOLF CODES

Thanks for reading!

💬 SHARE YOUR THOUGHTS



If you find my content helpful,
consider donating by clicking on
this highlight in my profile



Support