

# AP Computer Science A

## Java Programming Essentials [Ver. 2.0]

### Unit 1: Elementary Programming

WEEK 2: CHAPTER 2 ELEMENTARY PROGRAMMING – DATA TYPES AND  
NUMBER SYSTEM

DR. ERIC CHOU

IEEE SENIOR MEMBER



# Objectives

---

## Variables

- Storage of Data – Type – ID and Value
- Identifier
- Variable Declaration and Initialization
- Naming Convention



# Objectives

---

## Data Types

- Primitive Data Versus Reference Data Type
- Constants
- Integer Number
- Real Number



# Objectives

---

## **Reference Data Types – Basic Class and Objects**

- Storage of Data – Type – ID and Value
- Identifier
- Variable Declaration and Initialization
- Naming Convention




# Variables

---

LECTURE 1

`int age = 20;` ← value

datatype      variable\_name



RAM



# Identifier


---

LECTURE 1



# Where will see a lot of identifiers

```
public class Example {  
    public static void main(String[] args){  
        // Variable Declaration  
        double radius = 5.0;  
        // Input part  
        Scanner input = new Scanner(System.in);  
        radius = input.nextDouble();  
        // Processing part  
        double area = Math.PI * radius * radius;  
        // Output Part  
        System.out.println(area);  
    }  
}
```







# Identifiers

---

- Identifiers are the name that identify the elements such as **variables, classes, methods** in a program.
- All identifiers in Java must obey the following rules:
  - An identifier is a sequence of characters that consists of **letters, digits underscores (\_), and dollar sign (\$)**. An identifier must start with **a letter, an underscore (\_), or a dollar sign (\$)**. It can not start with a digit (number).
  - An identifier cannot be a reserved word.
  - An identifier cannot be **true, false, or null**.
  - An identifier can be of any length.



# Variables

Variables are used to represent values that may be changed in the program.

---

- A variable must be declared before used.
- A variable declaration in syntax: `<data type> <variable name>;`
- Examples of variable declarations:
  - `int count;`
  - `double radius;`
  - `double interestRate;`



# Variables

Variables are used to represent values that may be changed in the program.

---

- Primitive data type:

`byte, short, int, long, float, double, char, boolean;`

- Reference data type: `<class name>`

- Multiple instance for variable declaration is allowed in Java:

`datatype variable1, variable2, ..., variablen;`

- Declaration and assignment in the same statement is also allowed:

`int count=1;`



# Identifiers for Methods

---

```
public static void main(String[] args){ ... }
```

```
public double abs(double a){ ... }
```



# Variable Declaration

---

LECTURE 1



# Declaring Variables

---

```
int x;           // Declare x to be an
                  // integer variable;

double radius; // Declare radius to
                // be a double variable;

char a;          // Declare a to be a
                  // character variable;
```



# Assignment Statements

---

`x = 1;            // Assign 1 to x;`

`radius = 1.0;   // Assign 1.0 to radius;`

`a = 'A';        // Assign 'A' to a;`



# Variables

---

```
// Compute the first area
```

```
radius = 1.0;
```

```
area = radius * radius * 3.14159;
```

```
System.out.println("The area is “ + area + ” for radius "+radius);
```

```
// Compute the second area
```

```
radius = 2.0;
```

```
area = radius * radius * 3.14159;
```

```
System.out.println("The area is “ + area + ” for radius "+radius);
```





# Assignment Statement and Assignment Expressions

An assignment statement designates a value for a variable. An assignment statement can be used as an expression in Java.

---

## Syntax (assignment statement):

`<variable> = <expression> ;`

- An expression represents a computation involving values, variables, and operators that taking them together, evaluates to a value.

```
int y=1;
```

```
double radius = 1.0;
```

```
int x = 5 * (3 / 2) ;
```

```
x = 1; // correct;
```

```
1 = x; // incorrect;
```



# Assignments

---

- Evaluate the + sign first, then the assignment.

`x = 1;`

`x = x + 1;`

- If a value is assigned to multiple variables, you can use this syntax:

`i = j = k = 1;`

- Which is equivalent to:

`k = 1;`

`j = k;`

`i = j;`



# Naming Convention

---

LECTURE 1



# Naming Conventions

(not part of syntax)

---

- Naming conventions can vary from team to team. Every programming team may have their own conventions.
- Right here, we are discussing the commonly used naming conventions, but it is not mandatory.



# Naming Conventions

(not part of syntax)

## Variable and Method names:

- Use lowercase for variables and methods. If a method is longer than one word, the first letter for each word, except the first word, may sometime in uppercase.

Example: `int aa;`

`double women_age;`

`int functionName();`

`int functionToComputeInterest();`

## Constant names:

- Capitalize every letter in a constant and use underscore between words – for example, the constant `PI` and `MAX_VALUE`;



# Naming Conventions (module and package)

---

## **Class names:**

- Capitalize the first letter of each word in the name.
- For example, the class name `ComputeArea`.

## **Package names:**

- The whole package name in lower case.

# Java Standard Naming Conventions

**Package Name** - A package should be named in lowercase characters.

**Class Name** - Class names should be nouns in UpperCamelCase.

**Interface Name** - Interface name should start with an uppercase letter and be an adjective.

**Method Name** - Methods should be verbs and in lowerCamelCase.

**Variable Name** - Variable name should in lowerCamelCase.

**Constant Variable** - Constant variable names should be written in upper characters separated by underscores.

**Abstract Class Name** - Abstract class name must start with Abstract or Base prefix.

**Exception Class Name** - Exception class name must end with Exception suffix




# Data Types


---

## LECTURE 1



# Primitive Data type








# Reference Data Type


---

- A **reference type** is a data type that's based on a class rather than on one of the primitive types that are built in to the Java language. The class can be a class that's provided as part of the Java API class library or a class that you write yourself.
- **Reference types** are any instantiable class as well as arrays
- String, Scanner, Random, Die, int[], String[], etc.
- **Reference variables** store addresses. (**Address Pointer** is the value of the reference variable.)



# Reference Data Type







# Constants

---

LECTURE 1

# Declaring constants

- Java does not directly support constants. However, a **final** variable is *effectively* a constant.
- The **final** modifier causes the variable to be unchangeable
- Java constants are normally declared in ALL CAPS

```
class Math
{
    public final double PI=3.14;

}
```



# Named Constants

A named constant is an identifier that represents a permanent value.

---

Syntax:

```
final <datatype> CONSTANTNAME = <value> ;
```

The word `final` is a Java reserved keyword for declaring a constant.

A constant in Java (or most of other language) is usually in all **UPPERCASE**.

## Benefits for using constants:

- (1) you don't have to repeatedly type the same value over over again if it is used multiple times;
- (2) if you have to change the constant value, you need to change it only in a single location in the source code; and
- (3) a descriptive name for a constant makes the program easier to read.





# Named Constants

---

```
final datatype CONSTANTNAME = VALUE;
```

```
final double PI = 3.14159;
```

```
final int SIZE = 3;
```




# Number System


---

LECTURE 1

# Place Value



	3 <sup>th</sup> Place	2 <sup>nd</sup> Place	1 <sup>st</sup> Place	Decimal Point	1 <sup>st</sup> Decimal Place	2 <sup>nd</sup> Decimal Place	3 <sup>rd</sup> Decimal Place	4 <sup>th</sup> Decimal Place
Value of place (words)	Hundred	Ten	One	●	Tenths	Hundredths	Thousandths	Ten Thousandths
Value of place (digits)	100	10	1	●	$\frac{1}{10}$	$\frac{1}{100}$	$\frac{1}{1\ 000}$	$\frac{1}{10\ 000}$



# quinary

A place value Base-5 number system.

Five digits are used: 0, 1, 2, 3, 4.

in the quinary system the base number is 5

$5^5$	$5^4$	$5^3$	$5^2$	$5^1$	$5^0$
3125's	625's	125's	25's	5's	1's



Used in the tally marks system of counting.




© Jenny Eather 2015


$1101001_2$

Digit	1	1	0	1	0	0	1
Place value	$2^6$	$2^5$	$2^4$	$2^3$	$2^2$	$2^1$	$2^0$

The place values of the binary number system are powers of 2.







# Number System Video

---



# Binary Numbers

---

LECTURE 1



# Decimal to Binary

Handwritten conversion of 156 to binary:

$$\begin{array}{r} 2 \overline{)156} \\ 2 \overline{)78} \\ 2 \overline{)39} \\ 2 \overline{)19} \\ 2 \overline{)9} \\ 2 \overline{)4} \\ 2 \overline{)2} \\ 2 \overline{)1} \end{array}$$

Remainder:

0  
0  
1  
1  
1  
0  
0  
1

**$156_{10} = 10011100_2$**

wikihow

Divider	Dividend	Remainder
2	202	0
2	101	1
2	50	0
2	25	1
2	12	0
2	6	0
2	3	1
		1




# Binary/Decimal Conversion

128	64	32	16	8	4	2	1
1	0	0	1	1	0	1	1
<hr/>							
128 + 0 + 0 + 16 + 8 + 0 + 2 + 1							
<b>= 155</b>							

wikihow

10011011



$$\begin{aligned}1 \times 2^0 &= 1 \\1 \times 2^1 &= 2 \\0 \times 2^2 &= 0 \\0 \times 2^3 &= 0 \\1 \times 2^4 &= 16 \\1 \times 2^5 &= 32 \\0 \times 2^6 &= 0 \\1 \times 2^7 &= 128\end{aligned}$$

**Result = 155**

Binary Value	Decimal Representation				Decimal Value
	8	4	2	1	
0 0 0 0	0 +	0 +	0 +	0	0
0 0 0 1	0 +	0 +	0 +	1	1
0 0 1 0	0 +	0 +	2 +	0	2
0 0 1 1	0 +	0 +	2 +	1	3
0 1 0 0	0 +	4 +	0 +	0	4
0 1 0 1	0 +	4 +	0 +	1	5
0 1 1 0	0 +	4 +	2 +	0	6
0 1 1 1	0 +	4 +	2 +	1	7
1 0 0 0	8 +	0 +	0 +	0	8
1 0 0 1	8 +	0 +	0 +	1	9
1 0 1 0	8 +	0 +	2 +	0	10

## Decimal, Binary, Octal, Hexidecimal Values

Decimal	Binary	Octal	Hexidecimal
0	0000	0	0
1	0001	1	1
2	0010	2	2
3	0011	3	3
4	0100	4	4
5	0101	5	5
6	0110	6	6
7	0111	7	7
8	1000	10	8
9	1001	11	9
10	1010	12	A
11	1011	13	B
12	1100	14	C
13	1101	15	D
14	1110	16	E
15	1111	17	F

$$\begin{array}{r}
 2 \overline{) 41} \textcircled{1} \cdot 0.6875 \\
 2 \overline{) 20} \textcircled{0} \quad \times \quad 2 \\
 2 \overline{) 10} \textcircled{0} \quad \textcircled{1} 3750 \\
 2 \overline{) 5} \textcircled{1} \quad \times \quad 2 \\
 2 \overline{) 2} \textcircled{0} \quad \textcircled{0} 750 \\
 \textcircled{1} \quad \times \quad 2 \\
 \textcircled{1} 50 \\
 \times 2 \\
 \textcircled{1} 0
 \end{array}$$

$$\begin{array}{r}
 8 \overline{) 41} \textcircled{1} \cdot 0.6875 \\
 \textcircled{5} \quad \times \quad 8 \\
 \textcircled{5} 5000 \\
 \times 8 \\
 \textcircled{4} 0
 \end{array}$$

$$\begin{array}{r}
 16 \overline{) 41} \textcircled{9} \quad 0.6875 \\
 \textcircled{2} \quad \times \quad 16 \\
 \hline
 4.1250 \\
 + 6.8750 \\
 \hline
 \textcircled{11} .0000
 \end{array}$$



# Integer Types

---

LECTURE 1




# Numeric Data Types and Operations



Java has six numeric types for integers and floating-point numbers with operators +, -, \*, . and %

Name	Data	Range	Default Value	Size
byte	signed integer	[-128, 127]	0	8 bits
short	signed integer	[-32768, 32767]	0	16 bits
int	signed integer	[-2147483648, 2147483647]	0	32 bits
long	signed integer	[-9223372036854775808, 9223372036854775807]	0	64 bits
float	floating-point	MIN: $\pm 1.4\text{E-}45$ MAX: $\pm 3.4028235\text{E}+38$	0.0	32 bits
double	floating-point	MIN: $\pm 4.9\text{E-}324$ MAX: $\pm 1.7976931348623157\text{E}+308$	0.0	64 bits
char	Unicode	['\u0000', '\uFFFF']	'\u0000'	16 bits
boolean	logical value	{false, true}	false	$\geq 1$ bit




Orders of Implicit Type-Casting for Primitives

Integer.MIN\_VALUE  
Integer.MAX\_VALUE



# Two's Complement



Negative number is represented as two's complement.

For byte number's (8 bits):

$$-X = (2^8 - 1) - X + 1;$$

$$X + (-X) = X + (2^8 - X) = 2^8 = 0;$$

eg.

A = 0100 -> A's One's Complement = 1011 ->

A's Two's Complement -> 1100

The number  $2^8$  is a overflow for the byte format, because unsigned byte number range


from 0 to  $2^8 - 1 = 11111111$ .

Therefore, this method can work for computer.

# One's Complement

Invert all bits. Each 1 becomes a 0, and each 0 becomes a 1.

Original Value		One's Complement	
0	→	1	
1		0	
1010	→	0101	
1111		0000	
11110000	→	00001111	
10100011		01011100	
11110000 10100101	→	00001111 01011010	



$$\begin{array}{r}
 5 = 00000101 \\
 \downarrow \downarrow \downarrow \downarrow \downarrow \downarrow \downarrow \downarrow \\
 11111010 \\
 \hline
 + 1 \\
 \hline
 -5 = 11111011
 \end{array}
 \begin{array}{l}
 \left. \begin{array}{l} \\ \\ \end{array} \right\} \text{Complement Digits} \\
 \left. \begin{array}{l} \\ \end{array} \right\} \text{Add 1}
 \end{array}$$

$$\begin{array}{r}
 -13 = 11110011 \\
 \downarrow \downarrow \downarrow \downarrow \downarrow \downarrow \downarrow \downarrow \\
 00001100 \\
 \hline
 + 1 \\
 \hline
 13 = 00001101
 \end{array}
 \begin{array}{l}
 \left. \begin{array}{l} \\ \\ \end{array} \right\} \text{Complement Digits} \\
 \left. \begin{array}{l} \\ \end{array} \right\} \text{Add 1}
 \end{array}$$



# Finding 2's Complement

	-128	64	32	16	8	4	2	1	
$X$	0	1	0	0	1	1	1	1	Number : 79 decimal
$(2^8-1) - X$	1	0	1	1	0	0	0	0	Flip the bits
	0	0	0	0	0	0	0	1	Add 1
$NegX = (2^8-1) - X + 1$	1	0	1	1	0	0	0	1	Number: -79 in 2's Complement format



# Integer Literals

---

LECTURE 1



# Java Integer literals

---

- Theoretically Literal means – Any number, text or other information that represents a **value**.
- Different values that can be assigned to an integer variable (Integer data type Literal)





# Literal Types

Literal Type	Assignment Statement	Explanation
Decimal	<code>int num = 20;</code>	Decimal 20 is assigned to the variable num
Octal	<code>int num = 020;</code>	“ <u>020</u> ” is octal number , so first octal number is converted into integer and then it is assigned to variable “ <u>num</u> ”
Hexadecimal	<code>int num = 0x20;</code>	“ <u>0x20</u> ” is hexadecimal number , It is first converted into Decimal then assigned to variable “ <u>num</u> ”
Binary	<code>int num = 0b1010;</code>	“ <u>0b1010</u> ” is binary number , assigned to the variable “ <u>num</u> ” after converting it into decimal number
Long	<code>long num = 563L;</code>	“ <u>563L</u> ” is long number , assigned to the variable “ <u>num</u> ”



# Java integer literal and Underscore

1. In JDK 7, we can embed one or more underscores in an integer literal.
2. It makes easier to read large integer literals.
3. When the literal is compiled, the underscores are discarded. `int num = 19_90;`
4. Java compiler will discard '\_' from the above number and will assign 1990 to variable "num". Thus it is as good as writing – `int num = 1990;`

Literal	Using Underscore	Actual Value
Integer Literal	45_89	4589
Octal Literal	045_23	Equivalent Octal : 04523
Hexadecimal Literal	0x56_23	Equivalent Hex : 0x5623
Binary Literal	0b1000_1001	Equivalent Binary : 10001001



# Java integer literal and Underscore

---

## **Note : Using Underscore in Integer**

1. Don't Use Underscore as first and last character.
2. It is used to read long number easily

## **Illegal ways of using underscore**

- Below are some places where we cannot put the underscore while using the Java integer literal –
  1. We cannot put underscore at the beginning or end of a number
  2. Underscore should not be placed adjacent to a decimal point in a floating point literal
  3. Use of underscore prior to an F or L suffix is illegal
  4. Underscore should not be used in positions where a string of digits is expected



# Characters

---

LECTURE 1




# Characters

---

- The data type **char** represents a single character in Java.
- Character values are written as a symbol: 'a', ')', 'A', etc.
- A **char** value in Java is really represented as an integer.
  - Each character has an associated integer value. The integer value is the ASCII value or Unicode value (UTF-16)

## ISO / IEC 8859-1 8-bit character set



ASCII Character Set



ASCII + Western European Characters

# ASCII

Dec	Hex	Char	Dec	Hex	Char	Dec	Hex	Char	Dec	Hex	Char
0	00	Null	32	20	Space	64	40	@	96	60	`
1	01	Start of heading	33	21	!	65	41	A	97	61	a
2	02	Start of text	34	22	"	66	42	B	98	62	b
3	03	End of text	35	23	#	67	43	C	99	63	c
4	04	End of transmit	36	24	\$	68	44	D	100	64	d
5	05	Enquiry	37	25	%	69	45	E	101	65	e
6	06	Acknowledge	38	26	&	70	46	F	102	66	f
7	07	Audible bell	39	27	'	71	47	G	103	67	g
8	08	Backspace	40	28	(	72	48	H	104	68	h
9	09	Horizontal tab	41	29	)	73	49	I	105	69	i
10	0A	Line feed	42	2A	*	74	4A	J	106	6A	j
11	0B	Vertical tab	43	2B	+	75	4B	K	107	6B	k
12	0C	Form feed	44	2C	,	76	4C	L	108	6C	l
13	0D	Carriage return	45	2D	-	77	4D	M	109	6D	m
14	0E	Shift out	46	2E	.	78	4E	N	110	6E	n
15	0F	Shift in	47	2F	/	79	4F	O	111	6F	o
16	10	Data link escape	48	30	0	80	50	P	112	70	p
17	11	Device control 1	49	31	1	81	51	Q	113	71	q
18	12	Device control 2	50	32	2	82	52	R	114	72	r
19	13	Device control 3	51	33	3	83	53	S	115	73	s
20	14	Device control 4	52	34	4	84	54	T	116	74	t
21	15	Neg. acknowledge	53	35	5	85	55	U	117	75	u
22	16	Synchronous idle	54	36	6	86	56	V	118	76	v
23	17	End trans. block	55	37	7	87	57	W	119	77	w
24	18	Cancel	56	38	8	88	58	X	120	78	x
25	19	End of medium	57	39	9	89	59	Y	121	79	y
26	1A	Substitution	58	3A	:	90	5A	Z	122	7A	z
27	1B	Escape	59	3B	;	91	5B	[	123	7B	{
28	1C	File separator	60	3C	<	92	5C	\	124	7C	
29	1D	Group separator	61	3D	=	93	5D	]	125	7D	}
30	1E	Record separator	62	3E	>	94	5E	^	126	7E	~
31	1F	Unit separator	63	3F	?	95	5F	_	127	7F	□



# Java-Supplementary Characters and UTF-16 Encoding

---

- The **char** data type are based on the original **Unicode** specification, which defined characters as fixed-width 16-bit entities. The Unicode standard has since been changed to allow for characters whose representation requires more than 16 bits.
- The range of legal code points is now **U+0000** to **U+10FFFF**, known as Unicode scalar value.





# Java-Supplementary Characters and UTF-16 Encoding

---

- The set of characters from **U+0000** to **U+FFFF** is sometimes referred to as the Basic Multilingual Plane (**BMP**). Characters whose code points are greater than **U+FFFF** are called supplementary characters.
- The Java 2 platform uses the UTF-16 representation in char arrays and in the **String** and **StringBuffer** classes. In this representation, supplementary characters are represented as a pair of char values, the first from the high-surrogates range, (\uD800-\uDBFF), the second from the low-surrogates range (\uDC00-\uDFFF).



# Bit-Level Integer Operations

---

LECTURE 1



# Binary Addition

## Binary Arithmetic Rules

Key:  
Carry Out  
Carry in

0	1	0	1
+ 0	+ 0	+ 1	+ <sup>1</sup> 1
<u>0</u>	<u>1</u>	<u>1</u>	<u>0</u>
0	1	0	1
+ 0 <sub>1</sub>	+ <sup>1</sup> 0 <sub>1</sub>	+ <sup>1</sup> 1 <sub>1</sub>	+ <sup>1</sup> 1 <sub>1</sub>
<u>1</u>	<u>0</u>	<u>0</u>	<u>1</u>



# Binary Addition

$C$		101111000
$X$	190	10111110
$Y$	<u>+ 141</u>	<u>+ 10001101</u>
$X + Y$	331	101001011

$C$		011111110
$X$	127	01111111
$Y$	<u>+ 63</u>	<u>+ 00111111</u>
$X + Y$	190	10111110

$C$		001011000
$X$	173	10101101
$Y$	<u>+ 44</u>	<u>+ 00101100</u>
$X + Y$	217	11011001

$C$		000000000
$X$	170	10101010
$Y$	<u>+ 85</u>	<u>+ 01010101</u>
$X + Y$	255	11111111




# Hardware Design for a One-bit adder

Row	Inputs			Outputs		Comment
	x	y	$c_{in}$	$c_{out}$	s	
0	0	0	0	0	0	$0 + 0 + 0 = 00_2$
1	0	0	1	0	1	$0 + 0 + 1 = 01_2$
2	0	1	0	0	1	$0 + 1 + 0 = 01_2$
3	0	1	1	1	0	$0 + 1 + 1 = 10_2$
4	1	0	0	0	1	$1 + 0 + 0 = 01_2$
5	1	0	1	1	0	$1 + 0 + 1 = 10_2$
6	1	1	0	1	0	$1 + 1 + 0 = 10_2$
7	1	1	1	1	1	$1 + 1 + 1 = 11_2$



# Hardware Design for a One-bit adder





# Subtraction $(A-B) = (A + -B)$

using Two's complement addition for subtraction

---

- $12_{\text{ten}} - 5_{\text{ten}}$  (using Java int data type example)


$$\begin{array}{r} 0000\ 0000\ 0000\ 0000\ 0000\ 0000\ 0000\ 1100\ (12_{\text{ten}}) \\ -\ 0000\ 0000\ 0000\ 0000\ 0000\ 0000\ 0000\ 0101\ (5_{\text{ten}}) \\ \hline = 0000\ 0000\ 0000\ 0000\ 0000\ 0000\ 0000\ 0111\ (7_{\text{ten}}) \end{array}$$

- $12_{\text{ten}} - 5_{\text{ten}} = 12_{\text{ten}} + (-5_{\text{ten}})$

$$\begin{array}{r} 0000\ 0000\ 0000\ 0000\ 0000\ 0000\ 0000\ 1100\ (12_{\text{ten}}) \\ +\ 1111\ 1111\ 1111\ 1111\ 1111\ 1111\ 1111\ 1011\ (-5_{\text{ten}}) \\ \hline = 0000\ 0000\ 0000\ 0000\ 0000\ 0000\ 0000\ 0111\ (7_{\text{ten}}) \end{array}$$



# Full 8-bit adder/subtractor design








# Floating Point Data Types

---

LECTURE 1





## Java's special number rules (different from other languages)

---

- **Java doesn't have unsigned number primitives.**
  - unsigned number is seldom used.
  - If you need to use unsigned number, use **char** data type instead. Because char does not follow the number operation rules while **char** can still operate the **bit-wise** operations.
- **Java's char is 16 bit.** (supporting Unicode: UTF-16)
- **IEEE 754 binary floating point representation.** (Java's Float Standard)



# Java's special number rules

---

## IEEE 754 Floating Point Standard



$$\text{number} = (-1)^s * (1.m) * 2^{e-127}$$



# Java's special number rules

---

**Single precision (32-bit) form: (Bias = 127)**

(1)sign (8) exponent (23) fraction

**Double precision (64-bit) form: (Bias = 1023)**

(1)sign (11) exponent (52) fraction



# Floating Point Literals


---

LECTURE 1



# Floating Point Literal : Primitive Data Type in Java Programming

1. Decimal values with a fractional component is called floating point.
2. They can be expressed in either standard or scientific notation.



## Standard Notation

1. Standard notation consists of a whole number component followed by a decimal point followed by a fractional component.
2. For example : 78.0, 3.14159 represent valid standard-notation floating-point numbers.



# Scientific Notation

Scientific notation uses a standard-notation, floating-point number plus a suffix that specifies a power of 10 by which the number is to be multiplied.

The exponent is indicated by an E or e followed by a decimal number, which can be positive or negative.

Valid Examples are :

- 6.02E21
- 314159E-05
- 2e+100.

**Floating-point literals in Java default to double precision. 0.333F 0.333D (Same double Format)**

Literal	Representation	Size	Default
Floating Point Number	F or f	32 bits	–
Double Number	D or d	64 bits	It is default type





# Live Example : Assigning Values to Floating Point Literal

```
public static void main(String args[])  
{  
    double d1 = 45.6;  
    float f1 = 32.5;  
}
```

## Short Notes :

1. Jdk 7 also provides us facility for writing hexadecimal literal but they are rarely used.
2. We can use Underscore inside Literals.

```
double num = 1_567_2_82.0;
```




# Named Constants

```
final datatype CONSTANTNAME = VALUE;
```

```
final double PI = 3.14159;
```

```
final int SIZE = 3;
```

## OVERVIEW OF JAVA LANGUAGE





# Constants are Immutable Data

## Literals are Data Representations

---

Constants are used to hide coding complexity. (One way of doing abstraction)

Constants for Scientific Calculation:

Math.PI (3.141592....), Math.E

Replacing Long URL or Long Text Message:

```
final String googleURL = "http://www.google.com"
```

Constants for Program Control: (declare at the head of program and update only once.)

```
final int STEPS = 100;
```

```
final int TRIALS = 1000000000;
```

```
final int MODE = 0; // 0: debug, 1: development, 2: analysis, 3: production
```




# Color Data Type

---

LECTURE 1



# Constants: Color



The class **java.awt.Color** provides 13 standard colors as named-constants. They are: **Color.RED, GREEN, BLUE, MAGENTA, CYAN, YELLOW, BLACK, WHITE, GRAY, DARK\_GRAY, LIGHT\_GRAY, ORANGE, and PINK.**

(In JDK 1.1, these constant names are in lowercase, e.g., red. This violates the Java naming convention for constants. In JDK 1.2, the uppercase names are added. The lowercase names were not removed for backward compatibility.)


You can use the `toString()` to print the RGB values of these color (e.g., `System.out.println(Color.RED)`):



# Font java.awt.Font;

```
Font myFont1 = new Font(Font.MONOSPACED, Font.PLAIN, 12);
Font myFont2 = new Font(Font.SERIF, Font.BOLD | Font.ITALIC, 16); // bold and italics
JButton btn = new JButton("RESET");
btn.setFont(myFont1);
JLabel lbl = new JLabel("Hello");
lbl.setFont(myFont2);
.....
g.drawString("In default Font", 10, 20); // in default font
Font myFont3 = new Font(Font.SANS_SERIF, Font.ITALIC, 12);
g.setFont(myFont3);
g.drawString("Using the font set", 10, 50); // in myFont3
```





# Basic Java Program Unit

---

LECTURE 1



# ComputeArea.java

---

```
public class ComputeArea {  
    public static void main(String[] args) {  
        double radius;    // Declare radius  
        double area;      // Declare area  
        // Assign a radius  
        radius = 20; // New value is radius  
        // Compute area  
        area = radius * radius * 3.14159;  
        // Display results  
        System.out.println("The area for the circle of radius " + radius + " is " + area);  
    }  
}
```



# Trace a Program Execution

```
public class ComputeArea {  
    /** Main method */  
    public static void main(String[] args) {  
        double radius;  
        double area;  
  
        // Assign a radius  
        radius = 20;  
  
        // Compute area  
        area = radius * radius * 3.14159;  
  
        // Display results  
        System.out.println("The area for the circle of radius " +  
            radius + " is " + area);  
    }  
}
```

allocate memory  
for radius

radius

no value

# Trace a Program Execution

```
public class ComputeArea {  
    /** Main method */  
    public static void main(String[] args) {  
        double radius;  
        double area;  
  
        // Assign a radius  
        radius = 20;  
  
        // Compute area  
        area = radius * radius * 3.14159;  
  
        // Display results  
        System.out.println("The area for the circle of radius " +  
            radius + " is " + area);  
    }  
}
```

memory

radius

no value

area

no value

allocate memory  
for area

# Trace a Program Execution

```
public class ComputeArea {  
    /** Main method */  
    public static void main(String[] args) {  
        double radius;  
        double area;  
  
        // Assign a radius  
        radius = 20;  
  
        // Compute area  
        area = radius * radius * 3.14159;  
  
        // Display results  
        System.out.println("The area for the circle of radius " +  
            radius + " is " + area);  
    }  
}
```

assign 20 to radius

radius


20

area

no value

# Trace a Program Execution

```
public class ComputeArea {  
    /** Main method */  
    public static void main(String[] args) {  
        double radius;  
        double area;  
  
        // Assign a radius  
        radius = 20;  
  
        // Compute area  
        area = radius * radius * 3.14159;  
  
        // Display results  
        System.out.println("The area for the circle of radius " +  
            radius + " is " + area);  
    }  
}
```



# Trace a Program Execution

```
public class ComputeArea {  
    /** Main method */  
    public static void main(String[] args) {  
        double radius;  
        double area;  
  
        // Assign a radius  
        radius = 20;  
  
        // Compute area  
        area = radius * radius * 3.14159;  
  
        // Display results  
        System.out.println("The area for the circle of radius " +  
            radius + " is " + area);  
    }  
}
```

memory


radius

20

area

1256.636

print a message to the  
console



# Input>process>output

Every system has:

## Input

(ingredients that are put into the system)



## Process


(what happens to make the system work)



## Output

(what the system creates)


For example...






# How to input from Console?

```
public class Example {  
    public static void main(String[] args){  
        // Variable Declaration  
        double radius = 5.0;  
        // Input part  
        Scanner input = new Scanner(System.in);  
        radius = input.nextDouble();  
        // Processing part  
        double area = Math.PI * radius * radius;  
        // Output Part  
        System.out.println(area);  
    }  
}
```



# Input-process-output model of team effectiveness







# Demonstration Program

---

COMPUTEAREA.JAVA



# Basic Class and Objects

---

LECTURE 1



# In-Class Demonstration Program

- Constant Pi
  - Constructor
  - Getter method
  - Setter method
  - getArea()
  - getPerimeter()
- 

CIRCLE.JAVA AND  
TESTCIRCLE.JAVA



# Scanner Class

---

LECTURE 1



# Reading Input from the Console

Demo Program: `ComputeAreaWithConsoleInputWithConstant.java`

---

## 1. Create a Scanner object

```
Scanner input = new Scanner(System.in);
```

2. Use the methods next(), nextByte(), nextShort(), nextInt(), nextLong(), nextFloat(), nextDouble(), or nextBoolean() to obtain to a string, byte, short, int, long, float, double, or boolean value. For example,

```
System.out.print("Enter a double value: ");  
Scanner input = new Scanner(System.in);  
double d = input.nextDouble();
```



# import

---


- The **Scanner** class is in the **java.util** package. It is imported on a program for input purpose. There are two types of import statements: ***specific import*** and ***wildcard import***.
- Specific import specifies a single class in the import statement. For example, the following statement imports Scanner from the package **java.util**.

```
import java.util.Scanner;
```

- The wildcard import imports all the classes in a package by using the asterisk as the wildcard. (Take much larger space. Push into the Operand Stack or Constant Pool) For example, the following statement imports all the classes from the package java.util.

```
import java.util.*;
```

0: getstatic





# System Input and Output

---

- **System** is a class in the `java.lang` package. `out` is a static member of the System class, and is an instance of `java.io.PrintStream`. `println` is a method of `java.io.PrintStream`. This method is overloaded to print message to output destination, which is typically a console or file.
- **System.in**: System Input Device
- **System.out**: System Output Device (character stream type)
- Scanner is a class from scan code to ASCII code and then, ASCII String is converted to data of certain data type (`nextDouble()`, `nextInt()`).
- `println` is a output method





# In-Class Demonstration Program

- HashCode
- Reference data type

---

`HASHCODE.JAVA`