<table>
<tr>
<td rowspan="2">Inputs</td>
<td>Types of Width
10, 13, 16, 19, 22, 25, 29, 32 (mm)

For this application, the length provided for the steel will always be 8 meters.

Example Order:
25mm 2.3m 200EA
25mm 2.1m 250EA
25mm 2.2m 200EA
25mm 1.4m 400EA

Controlled Variable:
Width of the steel

Processing the Order:
25mm 2.3m 200EA
25mm 2.1m 250EA
25mm 2.2m 200EA
25mm 1.4m 400EA

2.3 + 2.1 + 2.2 + 1.4 = 8m

In this case, in order to minimize loss, the optimization program will cut 200 EA of each which will leave 50EA of 2.1m and 200EA of 1.4m. The leftovers will be used as a different combination.</td>
</tr>
<tr>
<td>ORDER tab

_________ (mm) _______ m ________ EA
_________ (mm) _______ m ________ EA

(add rows)</td>
</tr>
<tr>
<td>Outputs</td>
<td>25mm 2.3m 200EA
25mm 2.1m 200EA
25mm 2.2m 200EA
25mm 1.4m 200EA

Leftovers
25mm 2.1m 50EA
25mm 1.4m 200EA</td>
</tr>
</table>

	Loss: __%

Conditions	There are thousands of orders coming on each day, so there should be no concerns about storing the remaining order. If there are remaining parts, such as 25mm, 1.4m, 200EA, this will be in the “remainder” box. The remainder box should prioritize the 10 orders from the remaining calculations in order to efficiently remove the orders accordingly. The given length of the steel will be set as the controlled variable. The calculations should be processed with the 8m steel. Furthermore, for each order (input), the width of the steel must be controlled.