

Portfolio Project: API Spec

Deployed Application / Login Landing URL: <https://final-eckermee.wl.r.appspot.com>

Erin Eckerman

CS 493: Cloud Application Development

Fall 2022

Oregon State University

Last Update: Nov 30, 2022

[Data Model](#)

[Relationship Between Fabrics and Patterns](#)

[Create a Fabric](#)

[List All Fabric](#)

[Get a Fabric](#)

[Delete a Fabric](#)

[Update a Fabric](#)

[Create a Pattern](#)

[List All Patterns](#)

[Get a Pattern](#)

[Delete a Pattern](#)

[Update a Pattern](#)

[Add Fabric to a Pattern](#)

[Remove Fabric from a Pattern](#)

[List All Users](#)

Data Model

The app stores three kinds of entities in Datastore, Users, Fabrics, and Patterns. There is no endpoint for user record creation - user records are created automatically at time of first login.

Users

| Property | Data Type | Notes | Required | Valid Values |
|-------------|------------------|--|----------|--|
| uid | Integer | Unique ID of user - is the sub of the user's OAuth JWT | Y | Any positive integer |
| given_name | String | First name | Y | Any string |
| family_name | String | Last name | Y | Any string |
| join_date | Datetime | Date and time user's record was created | Y | YYYY-MM-DD HH:MM:SS.MS+TZ e.g. "2022-11-28 12:26:33.523124+00:00" |
| patterns | List of Integers | IDs of Patterns assigned to the user | N | Any ids in Patterns |

Fabrics

| Property | Data Type | Notes | Required | Valid Values |
|-----------|------------------|---|----------|--|
| id | Integer | The id of the fabric - automatically generated by Datastore | Y | Any positive integer |
| substrate | String | Type of fabric | Y | Any string representing a substrate e.g. "cotton" |
| color | String | Color of fabric | Y | Any string representing a color e.g. "black" |
| yards | Integer | Number of yards available for fabric - must be > 0 | Y | Any integer > 0 |
| patterns | List of Integers | ID of pattern(s) to which fabric is assigned - can be null | N | Any id in Patterns |

Patterns

| Property | Data Type | Notes | Required | Valid Values |
|----------|-----------|--|----------|--|
| id | Integer | The id of the pattern - automatically generated by Datastore | Y | Any positive integer |
| name | String | Name of the pattern | Y | Any string representing a pattern name |

| | | | | |
|---------|--------|--|---|---|
| maker | String | ID of user to which pattern is assigned - can be null | N | Any id in Users |
| fabric | String | ID of fabric that is assigned to pattern - can be null | N | Any id in Fabrics |
| garment | String | Type of pattern | Y | Any string representing a type of garment e.g. "dress" |
| company | String | Name of company that produces the pattern | Y | Any string representing a pattern company e.g. "Closet Core" |

Relationship Between Fabrics and Patterns

There is a 1:Many relationship between Fabrics and Patterns - i.e. the same fabric record may be associated with multiple pattern records but patterns can only have a single fabric associated with it. It is possible for fabrics to not be associated with any patterns and for patterns to not have any fabrics assigned to it. Any updates to the "fabric" value of a Pattern record must supply the id of the fabric and any updates to the "pattern" value of a Fabric record must supply the id of the pattern. Any updates to the relationship between patterns and fabrics or deletions of either a Pattern or Fabric record will be cascaded to any associated records.

User Entity Modeling

The unique identifier for a User is the uid - this is generated at the time of User record creation and is derived from the "sub" within the user's JWT provided by Google OAuth. There is a 1:Many relationship between Users and Patterns - i.e. the same user record may be associated with multiple pattern records but patterns can only have a single user associated with it. If a Pattern record is going to be assigned to a user (a.k.a. "maker"), the uid must be provided as part of the update to the Pattern record - any endpoints that update the "maker" of a Pattern record will also update the "patterns" value on the corresponding User record and any deletions of either a Pattern or User record will be cascaded to associated User or Pattern records.

Create a Fabric

Allows you to create a new fabric.

POST /fabrics

Request

Path Parameters

None

Request Body

Required

Request Body Format

JSON

Request JSON Attributes

| Name | Description | Required? |
|-----------|-------------------------------|-----------|
| substrate | The type of fabric | Yes |
| color | The color of the fabric | Yes |
| yards | Number of yards of the fabric | Yes |

Request Body Example

```
{
  "substrate": "cotton",
  "color": "blue",
  "yards": 3
}
```

Response

Response Body Format

JSON

Response Statuses

| Outcome | Status Code | Notes |
|---------|-----------------|--|
| Success | 201 Created | |
| Failure | 400 Bad Request | If the request is missing any of the 3 required attributes |

Response Examples

- Datastore will automatically generate an ID and store it with the entity being created.

Success

```
Status: 201 Created

{
  "color": "blue",
  "id": "5925479739555840",
  "patterns": [],
  "self": "https://final-eckermee.wl.r.appspot.com/5925479739555840",
  "substrate": "cotton",
```

```
"yards": 3
}
```

Failure

```
Status: 400 Bad Request

{
  "Error": "The request object is missing at least one of the required attributes"
}
```

List All Fabric

Returns a paginated list of Fabric records - 5 records at a time using limit and offset variables within the url - and includes a "next" url in every response except at the end of the list of records.

| |
|--------------|
| GET /fabrics |
|--------------|

Request

Path Parameters

None

Request Body

None

Response

Response Body Format

JSON

Response Statuses

| Outcome | Status Code | Notes |
|---------|-------------|-------|
| Success | 200 OK | |

Response Examples

Success

```
Status: 200 OK
{
  "fabrics": [
    {
      "substrate": "silk",
      "yards": 3,
      "patterns": [
        null
      ],
      "color": "rainbow",
      "pattern": null,
      "self": "https://final-eckermoe.wl.r.appspot.com/fabrics/4626141671325696",
      "id": "4626141671325696"
    },
    {
      "yards": 1,
      "color": "white",
      "substrate": "bamboo",
      "self": "https://final-eckermoe.wl.r.appspot.com/fabrics/4670788124803072",
      "id": "4670788124803072",
      "patterns": []
    },
    {
      "yards": 2,
```

```
{
  "color": "blue",
  "substrate": "cotton",
  "self": "https://final-eckermee.wl.r.appspot.com/fabrics/4792952966610944",
  "id": "4792952966610944",
  "patterns": []
},
{
  "yards": 2,
  "color": "red",
  "substrate": "cotton",
  "self": "https://final-eckermee.wl.r.appspot.com/fabrics/4806027115495424",
  "id": "4806027115495424",
  "patterns": []
},
{
  "yards": 1,
  "color": "white",
  "substrate": "bamboo",
  "self": "https://final-eckermee.wl.r.appspot.com/fabrics/4818367227625472",
  "id": "4818367227625472",
  "patterns": []
}
],
"next": "https://final-eckermee.wl.r.appspot.com/fabrics?limit=5&offset=5",
"total_items": 45
}
```

Get a Fabric

Allows you to get an existing fabric.

| |
|-------------------------|
| GET /fabrics/:fabric_id |
|-------------------------|

Request

Path Parameters

| Name | Description |
|-----------|------------------|
| fabric_id | ID of the fabric |

Request Body

None

Response

Response Body Format

JSON

Response Statuses

| Outcome | Status Code | Notes |
|---------|---------------|--------------------------------------|
| Success | 200 OK | |
| Failure | 404 Not Found | No fabric with this fabric_id exists |

Response Examples

Success

```
Status: 200 OK
{
  "yards": 3,
  "color": "blue",
  "substrate": "cotton",
  "patterns": [],
  "id": "5351024105619456",
  "self": "https://final-eckermee.wl.r.appspot.com/fabrics/5351024105619456"
}
```

Failure

```
Status: 404 Not Found

{
  "Error": "No fabric with this fabric_id exists"
}
```


Delete a Fabric

Allows you to delete a fabric. Note that if the fabric is assigned to a pattern, the “fabric” of the pattern will be changed to None.

| |
|----------------------------|
| DELETE /fabrics/:fabric_id |
|----------------------------|

Request

Path Parameters

| Name | Description |
|-----------|------------------|
| fabric_id | ID of the fabric |

Request Body

None

Response

No body

Response Body Format

Success: No body

Failure: JSON

Response Statuses

| Outcome | Status Code | Notes |
|---------|----------------|--------------------------------------|
| Success | 204 No Content | |
| Failure | 404 Not Found | No fabric with this fabric_id exists |

Response Examples

Success

| |
|------------------------|
| Status: 204 No Content |
|------------------------|

Failure

| |
|---|
| Status: 404 Not Found <pre>{ "Error": "No fabric with this fabric_id exists" }</pre> |
|---|

Update a Fabric

Updates an existing fabric and only updates/overwrites attributes included in the request body.

PUT or PATCH /fabrics/:fabric_id

Request

Path Parameters

| Name | Description |
|-----------|------------------|
| fabric_id | ID of the fabric |

Request Body

Required

Request Body Format

JSON

Request JSON Attributes

| Name | Description | Required? |
|-----------|-------------------------------|-----------|
| substrate | The type of fabric | No |
| color | The color of the fabric | No |
| yards | Number of yards of the fabric | No |

Request Body Example

```
{
  "yards": 2
}
```

Response Statuses

| Outcome | Status Code | Notes |
|---------|---------------|--------------------------------------|
| Success | 200 OK | |
| Failure | 404 Not Found | No fabric with this fabric_id exists |

Response Examples

Success

```
Status: 200 OK
{
  "yards": 2,
  "color": "blue",
  "substrate": "cotton",
  "patterns": [],
  "id": "5351024105619456",
  "self": "https://final-eckermee.wl.r.appspot.com/fabrics/5351024105619456"
}
```

Failure

Status: 404 Not Found

```
{  
  "Error": "No fabric with this fabric_id exists"  
}
```

Create a Pattern

Allows you to create a new pattern. A bearer token in the Authorization header of the request is required. After the user's token is verified, that user's id will be assigned as the "maker" attribute of the pattern.

POST /pattern

Request

Path Parameters

None

Request Body

Required

Request Body Format

JSON

Request JSON Attributes

| Name | Description | Required? |
|---------|---------------------------------|-----------|
| name | The name of the pattern | Yes |
| garment | The type of garment | Yes |
| company | The name of the pattern company | Yes |

Request Body Example

```
{
  "name": "Agave",
  "garment": "skirt",
  "company": "Deer & Doe"
}
```

Response

Response Body Format

JSON

Response Statuses

| Outcome | Status Code | Notes |
|---------|------------------|--|
| Success | 201 Created | |
| Failure | 400 Bad Request | If the request is missing any of the 3 required attributes |
| Failure | 401 Unauthorized | |

Response Examples

- Datastore will automatically generate an ID and store it with the entity being created.

Success

```
Status: 201 Created

{
  "company": "Deer & Doe",
  "fabric": null,
```

```
"garment": "skirt",  
"id": "6335358803378176",  
"maker": "109740306570073680111",  
"name": "Agave",  
"self": "https://final-eckermoe.wl.r.appspot.com/patterns/6335358803378176"  
}
```

Failure

Status: 400 Bad Request

```
{  
"Error": "The request object is missing at least one of the required attributes"  
}
```

Status: 401 Unauthorized

List All Patterns

Returns a paginated list of pattern records belonging to logged in user - 5 records at a time using limit and offset variables within the url - and includes a "next" url in every response except at the end of the list of records.

| |
|---------------|
| GET /patterns |
|---------------|

Request

Path Parameters

None

Request Body

None

Response

Response Body Format

JSON

Response Statuses

| Outcome | Status Code | Notes |
|---------|------------------|-------|
| Success | 200 OK | |
| Failure | 401 Unauthorized | |

Response Examples

Success

```
Status: 200 OK
{
  "patterns": [
    {
      "company": "Closet Core",
      "garment": "dress",
      "fabric": null,
      "maker": "109740306570073680111",
      "name": "Jenny",
      "self": "https://final-eckermoe.wl.r.appspot.com/patterns/4532102422855680",
      "id": "4532102422855680"
    },
    {
      "company": "Pattern Emporium",
      "garment": "shirt",
      "maker": "109740306570073680111",
      "fabric": null,
      "name": "Long Goodbye",
      "self": "https://final-eckermoe.wl.r.appspot.com/patterns/4619637882880000",
      "id": "4619637882880000"
    },
  ],
}
```

```
"company": "Paper Theory Patterns",
"garment": "jumpsuit",
"maker": "109740306570073680111",
"name": "Zadie",
"self": "https://final-eckermoe.wl.r.appspot.com/patterns/4828657734385664",
"id": "4828657734385664",
"fabric": null
},
{
  "company": "Pattern Emporium",
  "garment": "shirt",
  "maker": "109740306570073680111",
  "name": "Hello Gorgeous",
  "self": "https://final-eckermoe.wl.r.appspot.com/patterns/4862202200719360",
  "id": "4862202200719360",
  "fabric": null
},
{
  "company": "Pattern Emporium",
  "garment": "shirt",
  "maker": "109740306570073680111",
  "name": "Hello Gorgeous",
  "self": "https://final-eckermoe.wl.r.appspot.com/patterns/4882541421002752",
  "id": "4882541421002752",
  "fabric": null
}
],
"next": "https://final-eckermoe.wl.r.appspot.com/patterns?limit=5&offset=5",
"total_items": 21
}
```

Failure

Status: 401 Unauthorized

Get a Pattern

Allows user to get an existing pattern if they are the “maker” listed on the pattern record.

| |
|---------------------------|
| GET /patterns/:pattern_id |
|---------------------------|

Request

Path Parameters

| Name | Description |
|------------|-------------------|
| pattern_id | ID of the pattern |

Request Body

None

Response

Response Body Format

JSON

Response Statuses

| Outcome | Status Code | Notes |
|---------|------------------|--|
| Success | 200 OK | |
| Failure | 401 Unauthorized | |
| Failure | 404 Not Found | No pattern with this pattern_id exists |
| Failure | 403 Forbidden | ID in “maker” field does not match user’s ID |

Response Examples

Success

| |
|---|
| Status: 200 OK { "company": "Closet Core", "garment": "overalls", "maker": "109740306570073680111", "name": "Jenny", "fabric": [], "id": "6551438742257664", "self": "https://final-eckermee.wl.r.appspot.com/patterns/6551438742257664" } |
|---|

Failure

| |
|--------------------------|
| Status: 401 Unauthorized |
|--------------------------|

| |
|--|
| Status: 404 Not Found { "Error": "No pattern with this pattern_id exists" } |
|--|

Status: 403 Forbidden

```
{  
  "Error": "You are not authorized to access this resource"  
}
```

Delete a Pattern

Allows user to delete an existing pattern if they are the “maker” listed on the pattern record. If there is a fabric listed within the pattern record, the pattern id will be removed from that fabric record’s patterns field.

DELETE /patterns/:pattern_id

Request

Path Parameters

| Name | Description |
|------------|-------------------|
| pattern_id | ID of the pattern |

Request Body

None

Response

No body

Response Body Format

Success: No body

Failure: JSON

Response Statuses

| Outcome | Status Code | Notes |
|---------|------------------|--------------------------------------|
| Success | 204 No Content | |
| Failure | 401 Unauthorized | |
| Failure | 403 Forbidden | |
| Failure | 404 Not Found | No fabric with this fabric_id exists |

Response Examples

Success

Status: 204 No Content

Failure

Status: 401 Unauthorized

Status: 403 Forbidden
{
"Error": "You are not authorized to access this resource"
}

Status: 404 Not Found
{
"Error": "No pattern with this pattern_id exists"
}

Update a Pattern

Allows user to update an existing pattern if they are the “maker” listed on the pattern record.

| |
|------------------------------------|
| PUT or PATCH /patterns/:pattern_id |
|------------------------------------|

Request

Path Parameters

| Name | Description |
|------------|-------------------|
| pattern_id | ID of the pattern |

Request Body

Required

Request Body Format

JSON

Request JSON Attributes

| Name | Description | Required? |
|---------|---------------------------------|-----------|
| name | The name of the pattern | Yes |
| garment | The type of garment | Yes |
| company | The name of the pattern company | Yes |

Request Body Example

```
{
  "garment": "dress"
}
```

Response Statuses

| Outcome | Status Code | Notes |
|---------|------------------|--|
| Success | 200 OK | |
| Failure | 401 Unauthorized | |
| Failure | 403 Forbidden | |
| Failure | 404 Not Found | No pattern with this pattern_id exists |

Response Examples

Success

```
Status: 200 OK
{
  "garment": "dress",
  "fabric": [],
  "company": "Closet Core",
  "maker": "109740306570073680111",
  "name": "Jenny",
  "id": 4677581555105792,
  "self": "https://final-eckermee.wl.r.appspot.com/patterns/4677581555105792"
```

```
}
```

Failure

Status: 401 Unauthorized

Status: 403 Forbidden

```
{  
  "Error": "You are not authorized to access this resource"  
}
```

Status: 404 Not Found

```
{  
  "Error": "No pattern with this pattern_id exists"  
}
```

Add Fabric to a Pattern

Allows user to add a fabric id to an existing pattern if they are the “maker” listed on the pattern record.

PUT or PATCH /patterns/:pattern_id/fabrics/:fabric_id

Request

Path Parameters

| Name | Description |
|------------|-------------------|
| pattern_id | ID of the pattern |
| fabric_id | ID of the fabric |

Request Body

None

Response Statuses

| Outcome | Status Code | Notes |
|---------|------------------|--|
| Success | 200 OK | |
| Failure | 401 Unauthorized | |
| Failure | 403 Forbidden | |
| Failure | 404 Not Found | No pattern with this pattern_id exists |

Response Examples

Success

```
Status: 200 OK
{
  "company": "Closet Core",
  "garment": "dress",
  "maker": "109740306570073680111",
  "name": "Jenny",
  "fabric": {
    "yards": 2,
    "color": "blue",
    "substrate": "cotton",
    "patterns": [
      "6289916304556032"
    ]
  },
  "self": "https://final-eckermee.wl.r.appspot.com/patterns/6289916304556032",
  "id": 6289916304556032
}
```

Failure

```
Status: 401 Unauthorized
```

Status: 403 Forbidden (does not belong to user)

```
{  
  "Error": "You are not authorized to access this resource"  
}
```

Status: 403 Forbidden (there is already a fabric assigned to the pattern)

```
{  
  "Error": "There is already a fabric assigned to this pattern"  
}
```

Status: 404 Not Found

```
{  
  "Error": "No pattern with this pattern_id exists or no fabric with this fabric_id  
exists"  
}
```

Remove Fabric from a Pattern

Allows user to remove a fabric id from an existing pattern if they are the “maker” listed on the pattern record.

```
DELETE /patterns/:pattern_id/fabrics/:fabric_id
```

Request

Path Parameters

| Name | Description |
|------------|-------------------|
| pattern_id | ID of the pattern |
| fabric_id | ID of the fabric |

Request Body

None

Response Statuses

| Outcome | Status Code | Notes |
|---------|------------------|--|
| Success | 200 OK | |
| Failure | 401 Unauthorized | |
| Failure | 403 Forbidden | |
| Failure | 404 Not Found | No pattern with this pattern_id exists |

Response Examples

Success

```
Status: 204 No Content
```

Failure

```
Status: 401 Unauthorized
```

```
Status: 403 Forbidden (does not belong to user)
{
  "Error": "You are not authorized to access this resource"
}
```

```
Status: 403 Forbidden (there is no fabric id in pattern record)
{
  "Error": "There is no fabric to remove from this pattern"
}
```

```
Status: 403 Forbidden (fabric id in pattern record does not match given fabric id)
{
  "Error": "This fabric_id is not associated with this pattern"
}
```

Status: 404 Not Found

```
{  
  "Error": "No pattern with this pattern_id exists or no fabric with this fabric_id  
exists"  
}
```


List All Users

Returns a list of users.

| |
|------------|
| GET /users |
|------------|

Request

Path Parameters

None

Request Body

None

Response

Response Body Format

JSON

Response Statuses

| Outcome | Status Code | Notes |
|---------|-------------|-------|
| Success | 200 OK | |

Response Examples

Success

```
Status: 200 OK
{
  [
    {
      "family_name": "Eckerman",
      "given_name": "Erin",
      "join_date": "2022-11-29 12:30:59.685072+00:00",
      "uid": "112619984909112801964"
    },
    {
      "family_name": "Gheorghe",
      "given_name": "Bogdan",
      "join_date": "2022-11-28 12:26:33.523000+00:00",
      "uid": "109740306570073680111"
    }
  ]
}
```