

Lecture Notes for **Machine Learning in Python**



Professor Eric Larson
Neural Network Optimization and Activation

Class Logistics and Agenda

- Logistics
 - grading update (and AWS, quizzes, etc.)
 - flipped module next time! Cross validation.
- Agenda:
 - More optimization techniques and programming examples
 - Momentum
 - Objective Functions
 - Initialization
 - More activations: Tanh, ReLU, SiLU
 - Adaptive learning: AdaGrad, AdaM, etc.

Class Overview, by topic

Table Data
Visualization

Numpy, Pandas, Seaborn
Overviews with some in-depth discussion

Dimension
Reduction and
Image Processing

Scikit-learn, Scikit Image,
Intuition only, Some mathematics

Linear and
Logistic
Regression

Numpy, Recreate API for Scikit-learn
Detailed mathematics for simple optimization
intuition for advanced optimization

Neural Networks
and Back Prop.

Numpy
Detailed mathematics for NN operations

Wide and Deep
Networks

Convolutional
Networks

Recurrent
Networks

Keras, Tensorflow
Intuition, Detailed implement.

Ethics in
Language Models

ConceptNet
Case studies

08a. Practical_NeuralNetsWithBias.ipynb


Quick Review:

Momentum


Learning Rate Adaptation



Objective Function



Changing the Objective Function



• Self Test:

True or False: If we change the cost function, $J(\mathbf{W})$, we only need to update the final layer sensitivity calculation, $\mathbf{V}^{(2)}$, of the back propagation steps. The remainder of the algorithm is unchanged.


- A. True
- B. False

Practical Implementation of Architectures

- Mean squared error:

$$J(\mathbf{W}) = \sum_k^M (\mathbf{y}^{(k)} - \mathbf{a}^{(L)})^2$$

least squares objective,
tends to slow training initially




Run

Practical Implementation of Architectures

- Mean squared error:

$$J(\mathbf{W}) = \sum_k^M (\mathbf{y}^{(k)} - \mathbf{a}^{(L)})^2$$

least squares objective,
tends to slow training initially




Run

Practical Implementation of Architectures

- Our old friend, **Binary Cross entropy**

$$J(\mathbf{W}) = - [\mathbf{y}^{(i)} \ln([\mathbf{a}^{(L+1)}]^{(i)}) + (1 - \mathbf{y}^{(i)}) \ln(1 - [\mathbf{a}^{(L+1)}]^{(i)})]$$


speeds up initial training



Practical Implementation of Architectures

- Negative of MLE: **Binary Cross entropy**

$$J(\mathbf{W}) = - \left[\mathbf{y}^{(i)} \ln([\mathbf{a}^{(L+1)}]^{(i)}) + (1 - \mathbf{y}^{(i)}) \ln(1 - [\mathbf{a}^{(L+1)}]^{(i)}) \right] \quad \text{speeds up initial training}$$



Practical Implementation of Architectures

$$J(\mathbf{W}) = - [\mathbf{y}^{(i)} \ln([\mathbf{a}^{(L+1)}]^{(i)}) + (1 - \mathbf{y}^{(i)}) \ln(1 - [\mathbf{a}^{(L+1)}]^{(i)})]$$

likely to speed up initial training

$$\begin{aligned} \left[\frac{\partial J(\mathbf{W})}{\partial \mathbf{z}^{(L)}} \right]^{(i)} &= - \frac{\partial}{\partial \mathbf{z}^{(L)}} [\mathbf{y}^{(i)} \ln([\mathbf{a}^{(L+1)}]^{(i)}) + (1 - \mathbf{y}^{(i)}) \ln(1 - [\mathbf{a}^{(L+1)}]^{(i)})] \quad \text{only } \mathbf{a} \text{ has dependence on } \mathbf{z} \\ &= - \left[\mathbf{y}^{(i)} \frac{\partial}{\partial \mathbf{z}^{(L)}} (\ln([\mathbf{a}^{(L+1)}]^{(i)})) + (1 - \mathbf{y}^{(i)}) \frac{\partial}{\partial \mathbf{z}^{(L)}} (\ln(1 - [\mathbf{a}^{(L+1)}]^{(i)})) \right] \\ &= - \left[\mathbf{y}^{(i)} \frac{1}{[\mathbf{a}^{(L+1)}]^{(i)}} \left(\frac{\partial}{\partial \mathbf{z}^{(L)}} [\mathbf{a}^{(L+1)}]^{(i)} \right) + \frac{(1 - \mathbf{y}^{(i)})}{1 - [\mathbf{a}^{(L+1)}]^{(i)}} \left(- \frac{\partial}{\partial \mathbf{z}^{(L)}} [\mathbf{a}^{(L+1)}]^{(i)} \right) \right] \\ &= - \left[\mathbf{y}^{(i)} \frac{1}{[\mathbf{a}^{(L+1)}]^{(i)}} ([\mathbf{a}^{(L+1)}]^{(i)} (1 - [\mathbf{a}^{(L+1)}]^{(i)})) - \frac{(1 - \mathbf{y}^{(i)})}{1 - [\mathbf{a}^{(L+1)}]^{(i)}} ([\mathbf{a}^{(L+1)}]^{(i)} (1 - [\mathbf{a}^{(L+1)}]^{(i)})) \right] \\ &= - [\mathbf{y}^{(i)} (1 - [\mathbf{a}^{(L+1)}]^{(i)}) - (1 - \mathbf{y}^{(i)}) ([\mathbf{a}^{(L+1)}]^{(i)})] \\ &= - [\mathbf{y}^{(i)} - \mathbf{y}^{(i)} [\mathbf{a}^{(L+1)}]^{(i)} - [\mathbf{a}^{(L+1)}]^{(i)} + [\mathbf{a}^{(L+1)}]^{(i)} \mathbf{y}^{(i)}] = [\mathbf{a}^{(L+1)}]^{(i)} - \mathbf{y}^{(i)} \end{aligned}$$

$$\mathbf{V}^{(2)} = -2(\mathbf{Y} - \mathbf{A}^{(3)}) \odot \mathbf{A}^{(3)} \odot (1 - \mathbf{A}^{(3)}) \text{ old update}$$

Practical Implementation of Architectures

- Back to our old friend: **Cross entropy**

$$J(\mathbf{W}) = - \left[\mathbf{y}^{(i)} \ln([\mathbf{a}^{(L+1)}]^{(i)}) + (1 - \mathbf{y}^{(i)}) \ln(1 - [\mathbf{a}^{(L+1)}]^{(i)}) \right] \quad \text{likely to speed up initial training}$$

$$\left[\frac{\partial J(\mathbf{W})}{\partial \mathbf{z}^{(L)}} \right]^{(i)} = [\mathbf{a}^{(L+1)}]^{(i)} - \mathbf{y}^{(i)}$$

$$\left[\frac{\partial J(\mathbf{W})}{\partial \mathbf{z}^{(2)}} \right]^{(i)} = [\mathbf{a}^{(3)}]^{(i)} - \mathbf{y}^{(i)}$$

two layer network

$$\mathbf{V}^{(2)} = \mathbf{A}^{(3)} - \mathbf{Y}$$

new update

```
# vectorized backpropagation
V2 = (A3 - Y_enc) # <- this is only line t
V1 = A2 * (1 - A2) * (W2.T @ V2)
```

$$\mathbf{V}^{(2)} = -2(\mathbf{Y} - \mathbf{A}^{(3)}) \odot \mathbf{A}^{(3)} \odot (1 - \mathbf{A}^{(3)}) \quad \text{old update}$$

bp-5

08a. Practical_NeuralNetsWithBias.ipynb

Momentum

~~Learning Rate Adaptation~~

Cross Entropy



Practical Initialization of Architectures

AWS down
Half of the internet:




Formative Self Test

- for adding Gaussian random variables, variances add together


$\mathbf{a}^{(L+1)} = \phi(\mathbf{W}^{(L)}\mathbf{a}^{(L)})$ assume each element of $\mathbf{a}^{(L)}$ is Gaussian

- If you initialized the weights, \mathbf{W} , with too large variance, you would expect the output of the neuron, $\mathbf{a}^{(L+1)}$, to be:
 - A. saturated to “1”
 - B. saturated to “0”
 - C. could either be saturated to “0” or “1”
 - D. would not be saturated



Formative Self Test

- What is the derivative of a saturated sigmoid neuron?
 - A. zero
 - B. one
 - C. $a \times (1 - a)$
 - D. it depends




Practical Implementation of Architectures

Weight initialization: try not to saturate your neurons right away!

$$\mathbf{z}^{(L)} = \mathbf{W}^{(L)} \mathbf{a}^{(L)} \qquad z_i^{(L)} = \sum_j^{n^{(L)}} w_{ij} a_j^{(L)}$$

each row is summed before sigmoid





- want each $-\epsilon < z_i^{(L)} < \epsilon$ for no saturation, where $\epsilon \approx 4$ $z_i^{(L)}$
- if the $\text{Std}[z_i^{(L)}] \approx 4$ then the $\text{Std}[a_i^{(L+1)}] \approx 1$, which we want
 - because $\sigma(z_i^{(L)}) = a_i^{(L+1)}$, so it will be well distributed from $[0,1]$
- since $z_i^{(L)} = \sum w_{ij} a_j^{(L)}$, we want to “squash” initial weight magnitudes
- how do we squash w_{ij} , such that $\text{Std}[z_i^{(L)}] \approx 4$?
- **One solution:** draw w_{ij} from a Normal Distribution, $w_{ij} \sim \mathcal{N}(0, \alpha)$
 - solve for a good α such that **Goal:** $\text{Std}[z_i^{(L)}] \approx 4$

Initialization, check for understanding

Goal: $\text{Std}[z_i^{(L)}] \approx 4$

$$w_{ij} \sim \mathcal{N}(0, \alpha)$$

$$\text{Std}[a_i^{(L+1)}] \approx 1$$



$$z_i^{(L)}$$

$$a_i^{(L+1)}$$

$$w_{ij}$$

are all zero mean to start with...

$$\mathbf{b}^{(L)}$$

starts as zeros


Glorot Weight Initialization

Xavier Glorot

JMLR 2010

Yoshua Bengio

DIRO, Université de Montréal, Montréal, Québec, Canada



try not to
saturate

$$z_i^{(L)} = \sum_j w_{ij} a_j^{(L)}$$

$$w_{ij} \sim \mathcal{N}(0, \alpha)$$

$$\text{Goal: Std}[z_i^{(L)}] \approx 4$$

Random variables add variances: $\text{Var}[z_i^{(L)}] = \sum_j \text{Var}[w_{ij} \cdot a_j^{(L)}]$

Variance of multiplication of random variables:

$$\text{Var}[z_i^{(L)}] = \sum_j E[w_{ij}]^2 \text{Var}[a_j^{(L)}] + \text{Var}[w_{ij}] E[a_j^{(L)}]^2 + \text{Var}[w_{ij}] \text{Var}[a_j^{(L)}] = \sum_j \text{Var}[w_{ij}] \text{Var}[a_j^{(L)}]$$

...both are zero mean... ↑
same var, $\forall j$

$$\text{Var}[z_i^{(L)}] = n^{(L)} \text{Var}[w_{ij}] \text{Var}[a_j^{(L)}] = n^{(L)} \text{Var}[w_{ij}]$$

↑
 ≈ 1 , from previous layer

$$\text{Std}[z_i^{(L)}] = \sqrt{n^{(L)}} \cdot \text{Std}[w_{ij}]$$

$$\text{Std}[z_i^{(L)}] = 4 = \sqrt{n^{(L)}} \cdot \text{Std}[w_{ij}]$$

$$\text{Std}[w_{ij}] = 4 \cdot \sqrt{\frac{1}{n^{(L)}}}$$

$$w_{ij}^{(L)} \sim \mathcal{N}\left(0, 4 \cdot \sqrt{\frac{1}{n^{(L)}}}\right) \quad \text{forward from sigmoid}$$

Understanding the difficulty of training deep feedforward neural networks

Glorot Weight Initialization

$$\text{Std}[z_i^{(L)}] = 4 = \sqrt{n^{(L)}} \cdot \text{Std}[w_{ij}]$$

$$w_{ij}^{(L)} \sim \mathcal{N}\left(0, 4 \cdot \sqrt{\frac{1}{n^{(L)}}}\right) \quad \text{forward from sigmoid}$$

$$\mathbf{v}^{(L)} = \mathbf{a}^{(L)}(1 - \mathbf{a}^{(L)})\mathbf{W}^{(L)} \cdot \mathbf{v}^{(L+1)}$$


want to keep variance of \mathbf{v} stable
magnitude \rightarrow stable gradient

Similar calculation for back prop.

$$\text{Var}[v_i^{(L)}] = n^{(L+1)}\text{Var}[w_{ij}]\text{Var}[v_j^{(L+1)} \cdot a_j^{(L)}(1 - a_j^{(L)})]$$

$$\text{Std}[v_i^{(L)}] = \sqrt{n^{(L+1)}} \cdot \text{Std}[w_{ij}] \cdot 0.25 \quad \text{want} = 1$$

$$w_{ij}^{(L)} \sim \mathcal{N}\left(0, 4 \cdot \sqrt{\frac{1}{n^{(L+1)}}}\right) \quad \text{backward from sensitivity}$$



$$w_{ij}^{(L)} \sim \mathcal{N}\left(0, 4 \cdot \sqrt{\frac{2}{n^{(L)} + n^{(L+1)}}}\right) \quad \text{compromise}$$

$$w_{ij}^{(L)} \sim U\left[\pm 4 \sqrt{\frac{6}{n^{(L)} + n^{(L+1)}}}\right] \quad \text{if drawn from uniform dist.}$$


Glorot Weight Initialization

Understanding the difficulty of training deep feedforward neural networks

Xavier Glorot

DIRO, Université de Montréal, Montréal, Québec, Canada

Yoshua Bengio



Starting gradient histograms
per layer
standard initialization

Figure 7: *Back-propagated gradients normalized histograms with hyperbolic tangent activation, with standard (top) vs normalized (bottom) initialization. Top: 0-peak decreases for higher layers.*

08a. Practical_NeuralNetsWithBias.ipynb

Momentum


~~Learning Rate Adaptation~~

~~Cross Entropy~~

Smarter Weight Initialization



Beyond Sigmoid: Other Activations




Can we do better than sigmoid?

- Perhaps! Sigmoid assumes $[0, 1]$ firing, but that doesn't need to be true, right?
- If we change the activation, we need to:
 - derive the gradient for back prop
 - define what “saturation” means
 - update initialization of w_{ij} to not “saturate” in feedforward
 - update initialization so that sensitivity variance is about “1”
- Other researchers have done this for you! But you need to use it properly...

New Activation: Hyperbolic Tangent

- Basically a sigmoid from -1 to 1



$$\phi(z) = \frac{\sinh(z)}{\cosh(z)} = \frac{e^z - e^{-z}}{e^z + e^{-z}}$$

$$\frac{\partial}{\partial z}\phi(z) = \text{sech}^2(z)$$


Back
Prop

$$w_{ij}^{(L)} \sim \sqrt{\frac{2}{n^{(L)} + n^{(L+1)}}}$$

Similar to
sigmoid,
no factor of 4

New Activation: ReLU

- A new nonlinearity: **rectified linear units**



$$\phi(z) = \begin{cases} z, & \text{if } z > 0 \\ 0, & \text{else} \end{cases}$$

it has the advantage of **large gradients** and **extremely simple** derivative

$$\frac{\partial}{\partial z} \phi(z) = \begin{cases} 1, & \text{if } z > 0 \\ 0, & \text{else} \end{cases}$$

$$w_{ij}^{(L)} \sim \sqrt{2} \sqrt{\frac{2}{n^{(L)} + n^{(L+1)}}}$$

New init

Other Activation Functions

- Sigmoid Weighted Linear Unit **SiLU** (also called Swish)
- Mixing of sigmoid, σ , and ReLU

$$\phi(z) = \sigma(z) \cdot z$$




Figure 1: The Swish activation function.

$$\frac{\partial \phi(z)}{\partial z} = \frac{\partial}{\partial z} \sigma(z) \cdot z$$

$$= z \cdot \left[\frac{\partial}{\partial z} \sigma(z) \right] + \sigma(z) \cdot \left[\frac{\partial}{\partial z} z \right]$$

$$= z \cdot \sigma(z)(1 - \sigma(z)) + \sigma(z)$$

$$= z \cdot \sigma(z) + \sigma(z) \cdot (1 - z \cdot \sigma(z))$$

$$= \phi(z) + \sigma(z) \cdot (1 - \phi(z))$$

Elfwing, Stefan, Eiji Uchibe, and Kenji Doya. "Sigmoid-weighted linear units for neural network function approximation in reinforcement learning." *Neural Networks* (2018).

Ramachandran P, Zoph B, Le QV. Swish: a Self-Gated Activation Function. *arXiv preprint arXiv:1710.05941*. 2017 Oct 16

Glorot and He Initialization





We have solved this assuming the activation output is in the range -4 to 4 (for a sigmoid) and assuming that we use Gaussian for sampling.

This range is different depending on the activation and assuming Gaussian or Uniform sampling.

	Uniform	Gaussian
Tanh	$w_{ij}^{(L)} \sim \sqrt{\frac{6}{n^{(L)} + n^{(L+1)}}}$	$w_{ij}^{(L)} \sim \sqrt{\frac{2}{n^{(L)} + n^{(L+1)}}}$
Sigmoid	$w_{ij}^{(L)} \sim 4\sqrt{\frac{6}{n^{(L)} + n^{(L+1)}}}$	$w_{ij}^{(L)} \sim 4\sqrt{\frac{2}{n^{(L)} + n^{(L+1)}}}$
ReLU SiLU	$w_{ij}^{(L)} \sim \sqrt{2}\sqrt{\frac{6}{n^{(L)} + n^{(L+1)}}}$	$w_{ij}^{(L)} \sim \sqrt{2}\sqrt{\frac{2}{n^{(L)} + n^{(L+1)}}}$

Summarized by Glorot and He

Activations Summary

	Definition	Derivative	Weight Init (Uniform Bounds)
 <p>Sigmoid</p>	$\phi(z) = \frac{1}{1 + e^{-z}}$	$\nabla \phi(z) = a(1 - a)$	$w_{ij}^{(L)} \sim \pm 4 \sqrt{\frac{6}{n^{(L)} + n^{(L+1)}}}$
 <p>Hyperbolic Tangent</p>	$\phi(z) = \frac{e^z - e^{-z}}{e^z + e^{-z}}$	$\nabla \phi(z) = \frac{4}{(e^z + e^{-z})^2}$	$w_{ij}^{(L)} \sim \pm \sqrt{\frac{6}{n^{(L)} + n^{(L+1)}}}$
 <p>ReLU</p>	$\phi(z) = \begin{cases} z, & \text{if } z > 0 \\ 0, & \text{else} \end{cases}$	$\nabla \phi(z) = \begin{cases} 1, & \text{if } z > 0 \\ 0, & \text{else} \end{cases}$	$w_{ij}^{(L)} \sim \pm \sqrt{2} \sqrt{\frac{6}{n^{(L)} + n^{(L+1)}}}$
 <p>SiLU</p>	$\phi(z) = \frac{z}{1 + e^{-z}}$	$\nabla \phi(z) = \phi(z) + \sigma(z) \cdot (1 - \phi(z))$	


Adaptive Optimization



Going beyond
changing the learning rate

Be adaptive based on Gradient Magnitude?

- Decelerate down regions that are steep
- Accelerate on plateaus



Momentum: be robust to **abrupt changes** in **steepness** (accumulate magnitudes)

Be adaptive based on Gradient Magnitude?


Inverse magnitude of gradient in multiple directions?

$$\mathbf{W}_{k+1} \leftarrow \mathbf{W}_k + \eta \frac{1}{\sqrt{\mathbf{G}_k + \epsilon}} \odot \nabla J(\mathbf{W}_k)$$


↑ ↙
new matrix for normalizing gradient

$$\mathbf{G}_k = \nabla J(\mathbf{W}_k) \odot \nabla J(\mathbf{W}_k)$$

same size as \mathbf{W}



```
G = gradW1 * gradW1  
W1 += eta*gradW1 / sqrt(G+eps)
```



Now we just need to add momentum to $\mathbf{G}_k^{(l)}$

Note: \mathbf{G} exists for every layer, but we will abuse layer notation

Common Adaptive Strategies $\mathbf{W}_{k+1} = \mathbf{W}_k - \eta \cdot \rho_k$

Adjust each element of gradient by the steepness

- AdaGrad

all operations are per element

$$\rho_k = \frac{1}{\sqrt{\mathbf{G}_k + \epsilon}} \odot \nabla J(\mathbf{W}_k)$$

where

$$\mathbf{G}_k = \gamma \cdot \mathbf{G}_{k-1} + \nabla J(\mathbf{W}_k) \odot \nabla J(\mathbf{W}_k)$$

- RMSProp

all operations are per element

$$\rho_k = \frac{1}{\sqrt{\mathbf{V}_k + \epsilon}} \odot \nabla J(\mathbf{W}_k)$$

$$\mathbf{G}_k = \nabla J(\mathbf{W}_k) \odot \nabla J(\mathbf{W}_k)$$

$$\mathbf{V}_k = \gamma \cdot \mathbf{V}_{k-1} + (1 - \gamma) \cdot \mathbf{G}_k$$

- AdaDelta

all operations are per element

$$\rho_k = \frac{\mathbf{M}_k}{\sqrt{\mathbf{V}_k + \epsilon}}$$

$$\mathbf{M}_{k+1} = \gamma \cdot \mathbf{M}_k + (1 - \gamma) \cdot \nabla J(\mathbf{W}_k)$$

- AdaM

\mathbf{G} updates with decaying momentum of J and J^2

- NAdaM

same as Adam, but with nesterov's acceleration

None of these are “**one-size-fits-all**” because the space of neural network **optimization varies** by problem, AdaM is **popular** but **not a panacea**

Adaptive Momentum

All operations are element wise:

$$\beta_1 = 0.9, \beta_2 = 0.999, \eta = 0.001, \epsilon = 10^{-8}$$

$$k = 0, \mathbf{M}_0 = \mathbf{0}, \mathbf{V}_0 = \mathbf{0}$$

Published as a conference paper at ICLR 2015

ADAM: A METHOD FOR STOCHASTIC OPTIMIZATION

Diederik P. Kingma*
University of Amsterdam, OpenAI

Jimmy Lei Ba*
University of Toronto

For each epoch:

update iteration $k \leftarrow k + 1$

get gradient $\nabla J(\mathbf{W}_k)$

accumulated gradient $\mathbf{M}_k \leftarrow \beta_1 \cdot \mathbf{M}_{k-1} + (1 - \beta_1) \cdot \nabla J(\mathbf{W}_k)$

accumulated squared gradient $\mathbf{V}_k \leftarrow \beta_2 \cdot \mathbf{V}_{k-1} + (1 - \beta_2) \cdot \nabla J(\mathbf{W}_k) \odot \nabla J(\mathbf{W}_k)$

boost moments magnitudes
(notice k in exponent) $\hat{\mathbf{M}}_k \leftarrow \frac{\mathbf{M}_k}{(1 - [\beta_1]^k)} \quad \hat{\mathbf{V}}_k \leftarrow \frac{\mathbf{V}_k}{(1 - [\beta_2]^k)}$

update gradient, normalized
by second moment
similar to AdaDelta $\mathbf{W}_k \leftarrow \mathbf{W}_{k-1} - \eta \cdot \frac{\hat{\mathbf{M}}_k}{\sqrt{\hat{\mathbf{V}}_k + \epsilon}}$


gradient with momentum
squared magnitude normalizer

Visualization of Optimization

<https://ruder.io/optimizing-gradient-descent/>

Takeaways:

1. **SGD** slows tremendously on plateau
2. **Momentum** and **Nesterov** drastically overshoot
3. Adaptive strategies are similar



08a. Practical_NeuralNetsWithBias.ipynb

Momentum

Learning Rate Adaptation

Cross Entropy


Smarter Weight Initialization

ReLU Nonlinearities

Adaptive training with AdaGrad



Review



$$\mathbf{W}_{k+1} = \mathbf{W}_k - \rho_k$$

- Cross entropy $\mathbf{A}^{(3)} - \mathbf{Y}$
new final layer update

- Momentum $\rho_k = \alpha \nabla J(\mathbf{W}_k) + \beta \nabla J(\mathbf{W}_{k-1})$

- Nesterov's Accelerated Gradient $\rho_k = \beta \nabla J(\underbrace{\mathbf{W}_k + \alpha \nabla J(\mathbf{W}_{k-1})}_{\text{step twice}}) + \alpha \nabla J(\mathbf{W}_{k-1})$

- Mini-batching

← all data →





	batch 1	batch 2	batch 3	batch 4	batch 5	batch 6	batch 7	batch 8	batch 9
Epoch 1									
Epoch 2									
Epoch 3									
Epoch 4									
...									

shuffle ordering each epoch and update W 's after each batch

- Learning rate adaptation (eta)

$$\eta_e = \eta_0 \cdot d^{\lfloor \frac{e}{e_d} \rfloor} \quad \eta_e = \eta_{min} + \frac{1}{2}(\eta_{max} - \eta_{min}) \left(1 + \cos \left(\frac{e}{e_{max}} \pi \right) \right)$$

Review: Activations Summary

	Definition	Derivative	Weight Init (Uniform Bounds)
 <p>Sigmoid</p>	$\phi(z) = \frac{1}{1 + e^{-z}}$	$\nabla \phi(z) = a(1 - a)$	$w_{ij}^{(L)} \sim \pm 4 \sqrt{\frac{6}{n^{(L)} + n^{(L+1)}}}$
 <p>Hyperbolic Tangent</p>	$\phi(z) = \frac{e^z - e^{-z}}{e^z + e^{-z}}$	$\nabla \phi(z) = \frac{4}{(e^z + e^{-z})^2}$	$w_{ij}^{(L)} \sim \pm \sqrt{\frac{6}{n^{(L)} + n^{(L+1)}}}$
 <p>ReLU</p>	$\phi(z) = \begin{cases} z, & \text{if } z > 0 \\ 0, & \text{else} \end{cases}$	$\nabla \phi(z) = \begin{cases} 1, & \text{if } z > 0 \\ 0, & \text{else} \end{cases}$	$w_{ij}^{(L)} \sim \pm \sqrt{2} \sqrt{\frac{6}{n^{(L)} + n^{(L+1)}}}$
 <p>SiLU</p>	$\phi(z) = \frac{z}{1 + e^{-z}}$	$\nabla \phi(z) = \phi(z) + \sigma(z) \cdot (1 - \phi(z))$	