


Lecture Notes for **Machine Learning in Python**



Professor Eric Larson
Wide and Deep Networks

Logistics and Agenda

- Logistics
 - Wide/Deep due soon!
 - Lecture video
 - A brief intro to career opportunities (Sonjia Stafford)
- Agenda
 - Wide/Deep Finish Demo
 - Town Hall
 - (if time) Basic CNN architectures

Class Overview, by topic

Table Data
Visualization

Numpy, Pandas, Seaborn
Overviews with some in-depth discussion

Dimension
Reduction and
Image Processing

Scikit-learn, Scikit Image,
Intuition only, Some mathematics

Linear and
Logistic
Regression

Numpy, Recreate API for Scikit-learn
Detailed mathematics for simple optimization
intuition for advanced optimization

Neural Networks
and Back Prop.

Numpy
Detailed mathematics for NN operations

Wide and Deep
Networks

Convolutional
Networks

Sequential
Networks

Keras, Tensorflow
Intuition, Detailed implement.

Ethics in
Language Models

ConceptNet
Case studies

Review: Feature Embeddings

Trainable Matrix, $\mathbf{W}^{(emb)}$, in Network


Reduced Dimensions

0.1	0.3	-0.01	0.15
0.2	1.2	-0.5	0.8

Num Categories

Eye Color

0	Blue	→ 0
1	Brown	→ 1
0	Green	→ 2
0	Hazel	→ 3




High Dimensional Categorical Data Space

Lower Dimensional Embedding Space

Embedding matrix

$$\mathbf{a} = \mathbf{W}^{(emb)} \cdot \mathbf{x}_{OHE}$$

Review: Embeddings with Feature Spaces



Self Test:

- `Keras FeatureSpaces` ...
 - A. ... provide operations in the tensorflow computation graph
 - B. ... can be used to create intermediate `tf.Dataset` representations.
 - C. ... require the call to `.adapt` to learn from an example dataset about aspects like vocabulary size and normalization values
 - D. All of the Above

Finish Demo

Adding Embedding Branches



10a. Keras Wide and Deep as TFData.ipynb

Wide and Deep Networks



Wide and Deep

Wide & Deep Learning for Recommender Systems

Heng-Tze Cheng, Levent Koc, Jeremiah Harmsen, Tal Shaked, Tushar Chandra, Hrishi Aradhye, Glen Anderson, Greg Corrado, Wei Chai, Mustafa Ispir, Rohan Anil, Zakaria Haque, Lichan Hong, Vihan Jain, Xiaobing Liu, Hemal Shah

Google Inc.*

ABSTRACT

Generalized linear models with nonlinear feature transfor-

have never or rarely occurred in the past. Recommendations based on memorization are usually more topical and





Figure 1: The spectrum of Wide & Deep models.

linear model with feature transformations for generic recommender systems with sparse inputs.

- The implementation and evaluation of the Wide & Deep recommender system productionized on Google



Why wide and deep?




Figure 1: The spectrum of Wide & Deep models.

But why memorize?


Obvious!

- Categorical values have combinations that repeat!
 - so memorizing these values is not necessarily a bad strategy
 - let's make memorizing easy on one network

Wide networks (Memorize?)

- Wide refers to the expansion of features set
- Crossed feature columns of categorical features

- Movie Rating
 - G
 - PG
 - PG-13
 - R
 - Else
- Movie Genre
 - Action
 - Drama
 - Comedy
 - Horror
 - Else




- Crossed feature “Rating-Genre”
 - G-Action, G-Drama, G-Comedy, G-Horror, G-else
 - PG-Action, PG-Drama, PG-Comedy, PG-Horror, G-else
 - and so on ... one hot encoded


Deep Features: What we have already done!

- Deep refers to increasingly narrow hidden layers
- **Essentially the same as what we already did!**


- Movie Actors
 - Armand Assante
 - Meryl Streep
 - Danny Trejo
 - Kevin Bacon
 - Audrey Hepburn
 - ...



Combining Memorization and Generalization



Crossed Embeddings in Keras




Adding Wide Branches





10a. Keras Wide and Deep as TFData.ipynb

Dropout: Helping prevent over fitting...



Dropout: Helping prevent over fitting...

Deep
ReLU
MLP




↓
Prediction

Shallow
MLP




↓
Prediction

- Do not update all weights for each batch.
- Randomly choose which weights to update
- Choose different set of weights for each batch (random percentage)
- **Caveat:** does extend required training time for convergence



Predictions





Additional tuning with Dropout
Using saved pre-processed outputs

10a. Keras Wide and Deep as TFData.ipynb

Town Hall, Wide and Deep Networks



WHEN VISITING A NEW HOUSE, IT'S GOOD TO CHECK WHETHER THEY HAVE AN ALWAYS-ON DEVICE TRANSMITTING YOUR CONVERSATIONS SOMEWHERE.



End of Session

- Next Time (or now if time):
 - Convolutional Neural Networks