

Lecture Notes for Neural Networks I



Logistic Regression I & II

Class Logistics and Agenda

- Last Time: Linear Regression
- Logistics
 - Grading
 - TA Office Hours Posted
 - Final Exam Dates
- Agenda
 - Logistic Regression
 - Solving and Programming

Class Overview, by topic

Table Data
Visualization

Numpy, Pandas, Seaborn
Overviews with some in-depth discussion

Linear and
Logistic
Regression

Numpy, Recreate API for Scikit-learn
Detailed mathematics for simple optimization
intuition for advanced optimization

Neural Networks
and Back Prop.

Numpy, Recreate API for DL Frameworks
Detailed mathematics for NN operations

Wide and Deep
Networks

Convolutional
Networks


Sequential
Networks

Large Language
Models (if time)


Hugging Face
Intuition only

Optimizing a function of multiple variables

- Given an Objective function: $L(\mathbf{w})$ or $l(\mathbf{w})$
- With parameters: θ or $\mathbf{w}$ or $\mathbf{b}$ or $\mathbf{W}$ (the variables)
- Choose random starting point $\mathbf{w}_0$
- Need to calculate a Direction to move parameters:
$$\nabla L(\mathbf{w}) \text{ or } \nabla l(\mathbf{w}) = \frac{\partial}{\partial \mathbf{w}} l(\mathbf{w}) \text{ (the gradient)}$$
- Use direction in an update rule: $\mathbf{w}_{k+1} \leftarrow \mathbf{w}_k + \eta \cdot \nabla l(\mathbf{w})$



Logistic Regression




@researchmark

Setting Up Binary Logistic Regression

- From flipped lecture:

This notation assumes that $\mathbf{x}^{(i)}$ is a *column* vector, not *row*...


$$p(y^{(i)} = 1 \mid \mathbf{x}^{(i)}, \mathbf{w}) = g(\mathbf{w}^T \cdot \mathbf{x}^{(i)}) = \frac{1}{1 + \exp(-\mathbf{w}^T \cdot \mathbf{x}^{(i)})}$$

$$p(y^{(i)} = 0 \mid \mathbf{x}^{(i)}, \mathbf{w}) = 1 - g(\mathbf{w}^T \cdot \mathbf{x}^{(i)}) = 1 - \frac{1}{1 + \exp(-\mathbf{w}^T \cdot \mathbf{x}^{(i)})}$$

$$L(\mathbf{w}) = \prod_i g(\mathbf{w}^T \mathbf{x}^{(i)})_{y^{(i)}=1} \cdot (1 - g(\mathbf{w}^T \mathbf{x}^{(i)}))_{y^{(i)}=0}$$

maximize!


where $g(\cdot)$ is a sigmoid
and probability that $y^{(i)} = 1$

Expanded Notation, Linear Algebra

$$p(y^{(i)} = 1 \mid \mathbf{x}^{(i)}, \mathbf{w}) = g(\mathbf{x}^{(i)} \cdot \mathbf{w}) = \frac{1}{1 + \exp(-\mathbf{x}^{(i)} \cdot \mathbf{w})}$$

$$\mathbf{X} = \begin{bmatrix} 1 & x_1^{(1)} & x_2^{(1)} & \dots & x_N^{(1)} \\ 1 & x_1^{(2)} & x_2^{(2)} & \dots & x_N^{(2)} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_1^{(M)} & x_2^{(M)} & \dots & x_N^{(M)} \end{bmatrix} = \begin{bmatrix} \leftarrow & \mathbf{x}^{(1)} & \rightarrow \\ \leftarrow & \mathbf{x}^{(2)} & \rightarrow \\ \vdots & \vdots & \vdots \\ \leftarrow & \mathbf{x}^{(M)} & \rightarrow \end{bmatrix} \quad \begin{array}{l} \text{table data with ones} \\ M \times (N + 1) \end{array}$$

map projection to probability
via sigmoid




$$\mathbf{X} \cdot \mathbf{w} = \begin{bmatrix} \leftarrow & \mathbf{x}^{(1)} & \rightarrow \\ \leftarrow & \mathbf{x}^{(2)} & \rightarrow \\ \vdots & \vdots & \vdots \\ \leftarrow & \mathbf{x}^{(M)} & \rightarrow \end{bmatrix} \cdot \begin{bmatrix} w_0 \\ w_1 \\ \vdots \\ w_N \end{bmatrix} = \begin{bmatrix} \mathbf{x}^{(1)} \cdot \mathbf{w} \\ \mathbf{x}^{(2)} \cdot \mathbf{w} \\ \vdots \\ \mathbf{x}^{(M)} \cdot \mathbf{w} \end{bmatrix} \quad \begin{array}{l} \text{projections onto } \mathbf{w} \end{array}$$

$$g(\mathbf{X} \cdot \mathbf{w}) = \begin{bmatrix} g(\mathbf{x}^{(1)} \cdot \mathbf{w}) \\ g(\mathbf{x}^{(2)} \cdot \mathbf{w}) \\ \vdots \\ g(\mathbf{x}^{(M)} \cdot \mathbf{w}) \end{bmatrix} = \begin{bmatrix} p(y^{(1)} = 1 \mid \mathbf{x}^{(1)}) \\ p(y^{(2)} = 1 \mid \mathbf{x}^{(2)}) \\ \vdots \\ p(y^{(M)} = 1 \mid \mathbf{x}^{(M)}) \end{bmatrix}$$

$\mathbf{w} = [w_0, w_1, w_2]$, Geometric Interpretation

$$\mathbf{x} \cdot \mathbf{w} = \text{dot}([1, x_1, x_2], [w_0, w_1, w_2]) \\ = \Theta + w_0$$



$$\text{LR: } g(\Theta + w_0)$$

$$\text{LR: } g(\mathbf{x} \cdot \mathbf{w}) > 0.5 ?$$

$$\Theta = \text{dot}([x_1, x_2], [w_1, w_2])$$

○ class 0
● class 1

$$\mathbf{x}_b = [x_1, x_2]$$

$$[w_1, w_2]$$

Changing $\mathbf{w}$ alters probability

Want to choose $\mathbf{w}$ such that this objective is maximized

$$L(\mathbf{w}) = \prod_i g(\mathbf{x}^{(i)} \cdot \mathbf{w})_{y^{(i)}=1} \cdot (1 - g(\mathbf{x}^{(i)} \cdot \mathbf{w}))_{y^{(i)}=0}$$

○ class 0
● class 1

$[w_0, w_1, w_2]$

Optimize iteratively

- **Objective Function:** likelihood, given below
- **Parameters:** changing $\mathbf{w}$
- **Update Direction:** need to calculate gradient to know how to update initial guess of $\mathbf{w}$

$$L(\mathbf{w}) = \prod_i g(\mathbf{x}^{(i)} \cdot \mathbf{w})_{y^{(i)}=1} \cdot (1 - g(\mathbf{x}^{(i)} \cdot \mathbf{w}))_{y^{(i)}=0}$$

- Simplify $L(\mathbf{w})$ with **logarithm**, $l(\mathbf{w})$

$$l(\mathbf{w}) = \sum_i y^{(i)} \ln(g(\mathbf{x}^{(i)} \cdot \mathbf{w})) + (1 - y^{(i)}) \ln(1 - g(\mathbf{x}^{(i)} \cdot \mathbf{w}))$$

Logistic Regression Optimization Procedure

Log
Likelihood

$$l(\mathbf{w}) = \sum_i y^{(i)} \ln (g(\mathbf{x}^{(i)} \cdot \mathbf{w})) + (1 - y^{(i)}) \ln (1 - g(\mathbf{x}^{(i)} \cdot \mathbf{w}))$$

- **Take** Gradient

$$\frac{\partial}{\partial w_j} l(\mathbf{w}) = \sum_i (y^{(i)} - g(\mathbf{x}^{(i)} \cdot \mathbf{w})) x_j^{(i)}$$

- **Use** gradient to **update** equation for $\mathbf{w}$

$$\mathbf{w}_{k+1} \leftarrow \mathbf{w}_k + \eta \cdot \nabla l(\mathbf{w})$$

- Video Supplement (also on canvas):

• <https://www.youtube.com/watch?v=FGnoHdjFrJ8>

Binary Solution for Update Equation

- Use gradient inside update equation for $\mathbf{w}$

$$\frac{\partial}{\partial w_j} l(\mathbf{w}) = \sum_i (y^{(i)} - g(\mathbf{x}^{(i)} \cdot \mathbf{w})) x_j^{(i)}$$

$$\mathbf{w}_{k+1} \leftarrow \mathbf{w}_k + \eta \cdot \nabla l(\mathbf{w})$$

$$\underbrace{w_j}_{\text{new value}} \leftarrow \underbrace{w_j}_{\text{old value}} + \underbrace{\frac{\eta}{M}}_{\text{step}} \underbrace{\sum_{i=1}^M (y^{(i)} - g(\mathbf{x}^{(i)} \cdot \mathbf{w})) x_j^{(i)}}_{\text{gradient } \nabla l(\mathbf{w})}$$

This updates each element of gradient, how to calculate for all elements of the gradient update?

$$\mathbf{w} \leftarrow \mathbf{w} + \frac{\eta}{M} \sum_{i=1}^M (y^{(i)} - g(\mathbf{x}^{(i)} \cdot \mathbf{w})) \cdot \mathbf{x}^{(i)}$$

Reinvent sklearn Logistic Regression **Demo**

03. Logistic Regression.ipynb

Programming

Vectorization

Regularization

Multi-class extension



```
>>> from sklearn.datasets import load_iris
>>> from sklearn.linear_model import LogisticRegression
>>> X, y = load_iris(return_X_y=True)
>>> clf = LogisticRegression(random_state=0).fit(X, y)
>>> clf.predict(X[:2, :])
array([0, 0])
>>> clf.predict_proba(X[:2, :])
array([[9.82e-01, 1.82e-02, 1.44e-08],
       [9.72e-01, 2.82e-02, 3.02e-08]])
>>> clf.score(X, y)
0.97
```

Jupyter notebook demo is available, but all code is truncated and included in these slides...


Dataset for Testing Binary Logistic Regression

```
from sklearn.datasets import load_iris
from sklearn.model_selection import train_test_split


ds = load_iris()
X = ds.data
y = (ds.target>1).astype(int) # make problem binary

X_train, X_test, y_train, y_test = train_test_split(X,y, train_size = 0.8, test_size=0.2)
```

Binary Class Distribution



Load iris dataset,
four features: width, length or petal/sepal
make two classes (0 or 1)



Base Code for Logistic Regression

```
class BinaryLogisticRegressionBase:
    def __init__(self, eta, iterations=20):
        self.eta = eta
        self.iters = iterations

    def __str__(self):
        return 'Base Binary Logistic Regression Object, Not Trainable'

    @staticmethod
    def _sigmoid(theta):
        return 1/(1+np.exp(-theta))

    @staticmethod
    def _add_intercept(X):
        return np.hstack((np.ones((X.shape[0],1)),X)) # add bias term

    @property
    def coef_(self):
        return self.w_[1:]

    @property
    def intercept_(self):
        return self.w_[0]

    def predict_proba(self, X, add_intercept=True):
        Xb = self._add_intercept(X) if add_intercept else X # add bias term if requested
        return self._sigmoid(Xb @ self.w_) # return the probability y=1

    def predict(self, X):
        return (self.predict_proba(X)>0.5) #return the actual prediction
```

Define same style interface as sklearn.

After “fit” we set various properties

Fitting Logistic Regression (slow version)

```
class BinaryLogisticRegression(BinaryLogisticRegressionBase):
    def __str__(self):
        if(hasattr(self,'w_')): return 'Binary Logistic Regression coefficients:\n'+ str(self.w_)
        else: return 'Untrained Binary Logistic Regression Object'

    def _get_gradient(self,X,y):
        gradient = np.zeros(self.w_.shape)
        for (xi,yi) in zip(X,y):
            gradi = (yi - self.predict_proba(xi,add_intercept=False))*xi
            gradient += gradi.reshape(self.w_.shape)
        return gradient/float(len(y))

    def fit(self, X, y):
        Xb = self._add_intercept(X) # add bias term
        num_samples, num_features = Xb.shape
        self.w_ = np.zeros((num_features,1)) # init weight vector to zeros

        for _ in range(self.iters):
            gradient = self._get_gradient(Xb,y)
            self.w_ += gradient*self.eta # multiply by learning rate
```

$$\nabla l(\mathbf{w}) = \frac{1}{M} \sum_{i=1}^M (y^{(i)} - g(\mathbf{x}^{(i)} \cdot \mathbf{w})) \cdot \mathbf{x}^{(i)}$$

$$\mathbf{w}_{init} = [0...0]$$

$$\mathbf{w} \leftarrow \mathbf{w} + \eta \cdot \nabla l(\mathbf{w})$$

```
%%time
# Now we can train the classifier
blr = BinaryLogisticRegression(eta=0.1,iterations=12)
blr.fit(X_train,y_train)
print(blr)
```

```
Binary Logistic Regression Object with coefficients:
[[-0.0722316 ]
 [-0.18542668]
 [-0.24636172]
 [ 0.31415213]
 [ 0.19209272]]
CPU times: user 17.5 ms, sys: 2.59 ms, total: 20.1 ms
Wall time: 19.9 ms
```

```
print("coef",blr.coef_)
print("intercept",blr.intercept_)
print("w",blr.w_)
```

```
coef [[-0.18542668]
 [-0.24636172]
 [ 0.31415213]
 [ 0.19209272]]
intercept [-0.0722316]
w [[-0.0722316 ]
 [-0.18542668]
 [-0.24636172]
 [ 0.31415213]
 [ 0.19209272]]
```

```
from sklearn.metrics import accuracy_score

yhat = blr.predict(X_test)
print('Accuracy of: ',accuracy_score(y_test,yhat))

Accuracy of:  0.9
```

Fitting Logistic Regression (fast version)

```
def _get_gradient(self, X, y):
    gradient = np.zeros(self.w_.shape)
    for (xi, yi) in zip(X, y):
        gradi = (yi - self.predict_proba(xi, ...)) * xi
        gradient += gradi.reshape(self.w_.shape)
    return gradient / float(len(y))
```

prev get_gradient

$$\nabla l(\mathbf{w}) = \frac{1}{M} \sum_{i=1}^M (y^{(i)} - g(\mathbf{x}^{(i)} \cdot \mathbf{w})) \cdot \mathbf{x}^{(i)}$$

$$\mathbf{y}_{diff} = \begin{bmatrix} y^{(1)} - g(\mathbf{x}^{(1)} \cdot \mathbf{w}) \\ y^{(2)} - g(\mathbf{x}^{(2)} \cdot \mathbf{w}) \\ \vdots \\ y^{(M)} - g(\mathbf{x}^{(M)} \cdot \mathbf{w}) \end{bmatrix} = \begin{bmatrix} y_{diff}^{(1)} \\ y_{diff}^{(2)} \\ \vdots \\ y_{diff}^{(M)} \end{bmatrix}$$

Binary Logistic Regression Object with coefficients:
 [[-0.1864301]
 [-0.45680892]
 [-0.55976024]
 [0.79216699]
 [0.52832691]]
 Accuracy of: 0.9
 CPU times: user 267 ms, sys: 3.45 ms, total: 271 ms
 Wall time: 270 ms

for loop: 270ms

$$\mathbf{y}_{diff} \odot \mathbf{X} = \begin{bmatrix} y_{diff}^{(1)} \\ y_{diff}^{(2)} \\ \vdots \\ y_{diff}^{(M)} \end{bmatrix} \cdot \begin{bmatrix} \leftarrow & \mathbf{x}^{(1)} & \rightarrow \\ \leftarrow & \mathbf{x}^{(2)} & \rightarrow \\ & \vdots & \\ \leftarrow & \mathbf{x}^{(M)} & \rightarrow \end{bmatrix} = \begin{bmatrix} (\leftarrow \mathbf{x}^{(1)} \rightarrow) \cdot y_{diff}^{(1)} \\ (\leftarrow \mathbf{x}^{(2)} \rightarrow) \cdot y_{diff}^{(2)} \\ \vdots \\ (\leftarrow \mathbf{x}^{(M)} \rightarrow) \cdot y_{diff}^{(M)} \end{bmatrix}$$

[[-0.1864301]
 [-0.45680892]
 [-0.55976024]
 [0.79216699]
 [0.52832691]]
 Accuracy of: 0.9
 CPU times: user 16.6 ms, sys: 2.31 ms, total: 19 ms
 Wall time: 17.6 ms

Vectorized: 17ms

$$\nabla l(\mathbf{w}) = \frac{1}{M} \sum_{i=1}^M y_{diff}^{(i)} \cdot \mathbf{x}^{(i)}$$

```
class VectorBinaryLogisticRegression( BinaryLogisticRegression ):
```

```
def _get_gradient(self, X, y):
    ydiff = y - self.predict_proba(X, add_intercept=False)
    gradient = np.mean(X * ydiff[:, np.newaxis], axis=0)
    return gradient
```

$$\nabla l(\mathbf{w}) = \text{mean}(\mathbf{y}_{diff} \odot \mathbf{X})_{\text{columns}}$$

new get_gradient

Self Test

- 1. What part of the equation is represented by


- `self.predict_proba(xi)`

$$\mathbf{w} \leftarrow \mathbf{w} + \eta \frac{1}{M} \sum_{i=1}^M (\underbrace{y^{(i)}}_{\mathbf{A}} - \underbrace{g(\mathbf{x}^{(i)} \cdot \mathbf{w})}_{\mathbf{B}}) \underbrace{\mathbf{x}^{(i)}}_{\mathbf{C}}$$

$\underbrace{\hspace{10em}}_{\mathbf{D}}$


- 2. If we had a class imbalance problem, with one type of class dominating the response, how could we manipulate `fit` to give more importance to a given class?
 - A. Add weights to the gradient calculation (for each instance of `ydiff`)
 - B. Repeat certain classes in the update of the gradient calculation
 - C. Update `get_gradient` function to only update the worst performing class

Multi-class Logistic Regression



One Versus Rest

Multi-class formulation



classes[   ]


model probabilities

test data (rows)	M1	M2	M3	M4		
	0.91	0.0	0.78	0.53	→	0 → 
	0.53	0.5	0.32	0.91	→	3 → 
	0.01	0.6	0.98	0.01	→	2 → 
	0.05	0.83	0.21	0.81	→	1 → 
	0.85	0.02	0.33	0.02	→	0 → 
	0.63	0.11	0.09	0.33	→	0 → 
	0.01	0.32	0.12	0.88	→	3 → 
	M1	M2	M3	M4		


arg max

hash


Binary formulations




Model 1



Model 2



Model 3



Model 4

Programming OVR Logistic Regression

```
class LogisticRegression:
    def __init__(self, eta, iterations=20): ...
    def __str__(self): ...
    @property def coef_(self): ...
    @property def intercept_(self): ...
```

Class setup, interface like sklearn



```
def fit(self, X, y):
    self.unique_ = np.unique(y) # list of unique class values
    num_unique_classes = len(self.unique_)
    self.classifiers_ = [] # fill array with binary classifiers

    for i, yval in enumerate(self.unique_): # for each unique value
        y_binary = (y==yval) # create a binary problem
        blr = VectorBinaryLogisticRegression(self.eta, self.iters)
        blr.fit(X, y_binary)
        self.classifiers_.append(blr)
```

```
def predict_proba(self, X):
    probs = []
    for blr in self.classifiers_:
        probs.append(blr.predict_proba(X)) # per classifier

    return np.hstack(probs) # make into single matrix

def predict(self, X):
    idx = np.argmax(self.predict_proba(X), axis=1)
    return self.unique_[idx]
```



Testing OVR Logistic Regression

```
%%time
ds = load_iris()
X = ds.data
y = ds.target # note problem is NOT binary anymore, there are three classes!

X_train, X_test, y_train, y_test = train_test_split(X,y, train_size = 0.8, test_size=0.2)

lr = LogisticRegression(0.1,500)
lr.fit(X_train,y_train)
print(lr)

yhat = lr.predict(X_test)
print('Accuracy of: ',accuracy_score(y_test,yhat))

MultiClass Logistic Regression Object with coefficients:
[[ 0.29773533  0.4533672  1.55246277 -2.41143016 -1.13092625]
 [ 0.38589636  0.31560559 -1.28306232  0.5421915  -0.97321777]
 [-0.81705268 -1.49226693 -1.41357874  2.20417964  2.04839556]]
Accuracy of: 0.9666666666666667
CPU times: user 35.5 ms, sys: 3.66 ms, total: 39.2 ms
Wall time: 37.6 ms
```

Ours

Sklearn has some efficiency that we do not yet implement:

- regularization (try not to overfit)
- better direction finding for the next step in updating $\mathbf{w}$

```
%%time
from sklearn.linear_model import LogisticRegression as SKLogisticRegression


lr_sk = SKLogisticRegression(solver='lbfgs') # all params default

lr_sk.fit(X_train,y_train)
print(np.hstack((lr_sk.intercept_[:],np.newaxis),lr_sk.coef_))
yhat = lr_sk.predict(X_test)
print('Accuracy of: ',accuracy_score(y_test,yhat))


[[ 9.56665511 -0.4149617  0.85665417 -2.38058111 -0.96355898]
 [ 2.11236587  0.49579807 -0.28883991 -0.19632485 -0.92836642]
 [-11.67902098 -0.08083637 -0.56781427  2.57690596  1.8919254 ]]
Accuracy of: 1.0
CPU times: user 17.5 ms, sys: 3.79 ms, total: 21.3 ms
Wall time: 19.5 ms
```

Sklearn

Regularization, Intuition



Regularization, Mathematics



Large values of $\mathbf{w}$ allow sigmoid to be steep

$$l(\mathbf{w})_{reg} = \underbrace{l(\mathbf{w})_{prev}}_{\text{old objective}} - \underbrace{C \cdot \sum_j w_j^2}_{\text{regularization}}$$

$$\underbrace{\left[\left(\sum_{i=1}^M (y^{(i)} - g(\mathbf{x}^{(i)} \cdot \mathbf{w})) x_j^{(i)} \right) - C \cdot 2w_j \right]}_{\text{new gradient}}$$

$$\mathbf{w} \leftarrow \mathbf{w} + \eta \left[\underbrace{\nabla l(\mathbf{w})_{prev}}_{\text{previous gradient}} - C \cdot 2\mathbf{w} \right]$$

```
class RegularizedBLR(VectorBLR):
    def __init__(self, C=0.0, **kwargs):
        self.C = C
        super().__init__(**kwargs) # call parent

    def _get_gradient(self, X, y):
        gradient = super()._get_gradient(X, y)
        gradient[1:] += -2 * self.C * self.w_[1:]
        return gradient
```

C is a hyperparameter controlling how much we want to optimize the previous objective function versus keep the weights small.

