

## **EclipseLink**

Java Persistence API (JPA) Extensions Reference  
for EclipseLink

Release 2.4

July 2012

**EclipseLink Java Persistence API (JPA) Extensions Reference for EclipseLink**

Copyright © 2012 by The Eclipse Foundation under the Eclipse Public License (EPL)

<http://www.eclipse.org/org/documents/epl-v10.php>

The initial contribution of this content was based on work copyrighted by Oracle and was submitted with permission.

Print date: October 1, 2012

---

---

# Contents

<b>Preface</b> .....	xi
Audience .....	xi
Conventions .....	xi
 <b>1 Introduction</b>	
About EclipseLink .....	1-1
About This Documentation .....	1-2
Other Resources .....	1-2
 <b>2 Annotation Extensions Reference</b>	
<b>Functional Listing of Annotation Extensions</b> .....	2-1
Mapping Annotations .....	2-1
Entity Annotations .....	2-2
Converter Annotations .....	2-2
Caching Annotations .....	2-2
Customization and Optimization Annotations .....	2-2
Copy Policy Annotations .....	2-3
Returning Policy Annotations .....	2-3
Stored Procedure and Function Annotations .....	2-3
Partitioning Annotations .....	2-3
Non-relational (NoSQL) Annotations .....	2-4
<b>Alphabetical Listing of Annotation Extensions</b> .....	2-4
@AdditionalCriteria .....	2-8
@Array .....	2-12
@BatchFetch .....	2-14
@Cache .....	2-16
@CacheIndex .....	2-20
@CacheIndexes .....	2-22
@CacheInterceptor .....	2-24
@CascadeOnDelete .....	2-26
@ChangeTracking .....	2-30
@ClassExtractor .....	2-32
@CloneCopyPolicy .....	2-34
@CompositeMember .....	2-36
@ConversionValue .....	2-38

<b>@Convert</b> .....	2-40
<b>@Converter</b> .....	2-42
<b>@Converters</b> .....	2-44
<b>@CopyPolicy</b> .....	2-46
<b>@Customizer</b> .....	2-48
<b>@DeleteAll</b> .....	2-50
<b>@DiscriminatorClass</b> .....	2-52
<b>@ExcludeDefaultMappings</b> .....	2-54
<b>@ExistenceChecking</b> .....	2-56
<b>@FetchAttribute</b> .....	2-58
<b>@FetchGroup</b> .....	2-60
<b>@FetchGroups</b> .....	2-62
<b>@Field</b> .....	2-64
<b>@HashPartitioning</b> .....	2-66
<b>@Index</b> .....	2-68
<b>@Indexes</b> .....	2-70
<b>@InstantiationCopyPolicy</b> .....	2-72
<b>@JoinFetch</b> .....	2-74
<b>@JoinField</b> .....	2-76
<b>@JoinFields</b> .....	2-78
<b>@MapKeyConvert</b> .....	2-80
<b>@Multitenant</b> .....	2-82
Single-Table Multitenancy .....	2-83
Examples .....	2-83
Table-Per-Tenat Multitenancy .....	2-84
Examples .....	2-84
VDP Multitenancy .....	2-86
Examples .....	2-86
<b>@Mutable</b> .....	2-88
<b>@NamedPLSQLStoredProcedureQuery</b> .....	2-90
<b>@NamedPLSQLStoredFunctionQueries</b> .....	2-92
<b>@NamedPLSQLStoredFunctionQuery</b> .....	2-94
<b>@NamedPLSQLStoredProcedureQueries</b> .....	2-96
<b>@NamedStoredFunctionQueries</b> .....	2-98
<b>@NamedStoredFunctionQuery</b> .....	2-100
<b>@NamedStoredProcedureQueries</b> .....	2-102
<b>@NamedStoredProcedureQuery</b> .....	2-104
<b>@Noncacheable</b> .....	2-106
<b>@NoSql</b> .....	2-108
<b>@ObjectTypeConverter</b> .....	2-112
<b>@ObjectTypeConverters</b> .....	2-114
<b>@OptimisticLocking</b> .....	2-116
<b>@OrderCorrection</b> .....	2-118
<b>@Partitioned</b> .....	2-120
<b>@Partitioning</b> .....	2-124
<b>@PinnedPartitioning</b> .....	2-128
<b>@PLSQLRecords</b> .....	2-130

@PLSQLParameter .....	2-132
@PLSQLRecord .....	2-134
@PrimaryKey .....	2-136
@PrivateOwned .....	2-138
@Properties .....	2-140
@Property .....	2-142
@QueryRedirectors .....	2-144
@RangePartition .....	2-146
@RangePartitioning .....	2-148
@ReadOnly .....	2-150
@ReadTransformer .....	2-152
@ReplicationPartitioning.....	2-154
@ReturnInsert.....	2-156
@ReturnUpdate .....	2-158
@RoundRobinPartitioning.....	2-160
@StoredProcedureParameter .....	2-162
@Struct .....	2-164
@StructConverter.....	2-166
@StructConverters .....	2-168
@Structure .....	2-170
@TenantDiscriminatorColumn .....	2-172
@TenantDiscriminatorColumns .....	2-178
@TenantTableDiscriminator.....	2-180
@TimeOfDay .....	2-182
@Transformation.....	2-184
@TypeConverter.....	2-186
@TypeConverters .....	2-188
@UuidGenerator .....	2-190
@UnionPartitioning .....	2-192
@ValuePartition .....	2-194
@ValuePartitioning .....	2-196
@VariableOneToOne.....	2-198
@VirtualAccessMethods.....	2-200
@WriteTransformer.....	2-202
@WriteTransformers.....	2-204

### 3 Java Persistence Query Language Extensions

Special Operators .....	3-1
EclipseLink Query Language.....	3-1
CAST.....	3-4
COLUMN.....	3-6
EXCEPT.....	3-8
EXTRACT.....	3-10
FUNCTION .....	3-12
INTERSECT.....	3-14
ON .....	3-16
OPERATOR .....	3-18

REGEXP.....	3-22
SQL.....	3-24
TABLE.....	3-26
TREAT .....	3-28
UNION .....	3-30

## 4 JPA Query Customization Extensions

batch.....	4-4
batch.size.....	4-6
batch.type.....	4-8
cache-usage .....	4-10
cache-usage.indirection-policy .....	4-12
cursor.....	4-14
cursor.initial-size .....	4-16
cursor.page-size.....	4-18
exclusive-connection.....	4-20
flush .....	4-22
history.as-of .....	4-24
history.as-of.scn .....	4-26
inheritance.outer-join .....	4-28
jdbc.bind-parameters.....	4-30
jdbc.cache-statement.....	4-32
jdbc.fetch-size .....	4-34
jdbc.first-result.....	4-36
jdbc.max-rows .....	4-38
jdbc.native-connection .....	4-40
jdbc.parameter-delimiter .....	4-42
jdbc.timeout.....	4-44
join-fetch .....	4-46
left-join-fetch.....	4-48
load-group.....	4-50
load-group.attribute.....	4-52
maintain-cache .....	4-54
pessimistic-lock .....	4-56
prepare .....	4-58
query-results-cache .....	4-60
query-results-cache.expiry .....	4-62
query-results-cache.expiry-time-of-day .....	4-64
query-results-cache.ignore-null.....	4-66
query-results-cache.randomize-expiry .....	4-68
query-results-cache.size .....	4-70
query-results-cache.type .....	4-72
query-type.....	4-74
read-only .....	4-76
refresh .....	4-78
refresh.cascade .....	4-80
result-collection-type .....	4-82

sql.hint.....	4-84
---------------	------

## 5 Persistence Property Extensions Reference

Functional Listing of Persistence Property Extensions.....	5-1
Exception Handling .....	5-1
Weaving .....	5-1
Customizers .....	5-1
Validation and Optimization .....	5-2
Logging .....	5-2
Caching .....	5-2
Mapping Annotations .....	5-2
JDBC Configuration Options .....	5-2
Alphabetical Listing of Persistence Property Extensions.....	5-2
application-location .....	5-6
cache.coordination.channel .....	5-8
cache.coordination.jms.factory .....	5-10
cache.coordination.jms.host .....	5-12
cache.coordination.jms.reuse-topic-publisher.....	5-14
cache.coordination.jms.topic.....	5-16
cache.coordination.jndi.initial-context-factory .....	5-18
cache.coordination.jndi.password .....	5-20
cache.coordination.jndi.user .....	5-22
cache.coordination.naming-service.....	5-24
cache.coordination.propagate-asynchronously .....	5-26
cache.coordination.protocol .....	5-28
cache.coordination.remove-connection-on-error .....	5-32
cache.coordination.rmi.announcement-delay.....	5-34
cache.coordination.rmi.multicast-group .....	5-36
cache.coordination.rmi.multicast-group.port .....	5-38
cache.coordination.rmi.packet-time-to-live .....	5-40
cache.coordination.rmi.url.....	5-42
cache.coordination.thread.pool.size .....	5-44
cache.database-event-listener .....	5-46
classloader.....	5-48
composite-unit .....	5-50
composite-unit.member .....	5-52
composite-unit.properties.....	5-54
connection-pool .....	5-56
connection-pool.read .....	5-58
connection-pool.sequence .....	5-60
create-ddl-jdbc-file-name .....	5-62
ddl.table-creation-suffix.....	5-64
ddl-generation.....	5-66
ddl-generation.output-mode .....	5-68
deploy-on-startup .....	5-70
descriptor.customizer.....	5-72
drop-ddl-jdbc-file-name .....	5-74

exception-handler.....	5-76
exclude-eclipselink-orm.....	5-78
flush-clear.cache.....	5-80
id-validation .....	5-82
jdbc.allow-native-sql-queries .....	5-84
jdbc.batch-writing .....	5-86
jdbc.batch-writing.size .....	5-88
jdbc.cache-statements .....	5-90
jdbc.cache-statements.size .....	5-92
jdbc.connector .....	5-94
jdbc.exclusive-connection.is-lazy.....	5-96
jdbc.exclusive-connection.mode .....	5-98
jdbc.native-sql.....	5-100
jdbc.property .....	5-102
jdbc.sql-cast .....	5-104
jdbc.uppercase-columns.....	5-106
jpa.uppercase-column-names .....	5-108
jpql.parser .....	5-110
jpql.validation.....	5-112
logging.connection.....	5-114
logging.exceptions.....	5-116
logging.file.....	5-118
logging.level .....	5-120
logging.logger .....	5-122
logging.parameters.....	5-124
logging.session.....	5-126
logging.thread .....	5-128
logging.timestamp.....	5-130
metadata-source .....	5-132
metadata-source.properties.file .....	5-134
metadata-source.send-refresh-command .....	5-136
metadata-source.xml.file .....	5-138
metadata-source.xml.url .....	5-140
multitenant.tenants-share-cache.....	5-142
multitenant.tenants-share-emf .....	5-144
nosql.connection-factory.....	5-146
nosql.connection-spec .....	5-148
nosql.property .....	5-150
orm.throw.exceptions.....	5-152
oracle.proxy-type .....	5-154
orm.validate.schema .....	5-156
partitioning.....	5-158
partitioning.callback.....	5-160
persistence-context.close-on-commit.....	5-162
persistence-context.commit-without-persist-rules .....	5-164
persistence-context.flush-mode .....	5-166
persistence-context.persist-on-commit.....	5-168



<b>persistence-context.reference-mode</b> .....	5-170
<b>persistenceunits</b> .....	5-172
<b>persistencexml</b> .....	5-174
<b>profiler</b> .....	5-176
<b>session.customizer</b> .....	5-178
<b>session.include.descriptor.queries</b> .....	5-180
<b>session-event-listener</b> .....	5-182
<b>session-name</b> .....	5-184
<b>sessions-xml</b> .....	5-186
<b>target-database</b> .....	5-188
<b>target-server</b> .....	5-190
<b>transaction.join-existing</b> .....	5-192
<b>validate-existence</b> .....	5-194
<b>validation-only</b> .....	5-196
<b>weaving</b> .....	5-198
<b>weaving.eager</b> .....	5-200
<b>weaving.internal</b> .....	5-202
<b>weaving.lazy</b> .....	5-204

## 6 eclipselink-orm.xml Schema Reference

<b>Overriding and Merging</b> .....	6-1
Rules for Overriding and Merging .....	6-2
Persistence Unit Metadata .....	6-2
Entity Mappings .....	6-2
Mapped Superclasses .....	6-3
Entity override and merging rules .....	6-5
Embeddable .....	6-7
Examples of Overriding and Merging .....	6-8



---

---

# Preface

EclipseLink provides specific annotations (*EclipseLink extensions*) in addition to supporting the standard Java Persistence Architecture (JPA) annotations. You can use these EclipseLink extensions to take advantage of EclipseLink's extended functionality and features within your JPA entities.

## Audience

This document is intended for application developers who want to develop applications using EclipseLink with Java Persistence Architecture (JPA). This document does not include details about related common tasks, but focuses on EclipseLink functionality.

Developers should be familiar with the concepts and programming practices of

- Java SE and Java EE.
- Java Persistence Architecture 2.0 specification (<http://jcp.org/en/jsr/detail?id=317>)
- Eclipse IDE (<http://www.eclipse.org>)

## Conventions

The following text conventions are used in this document:

Convention	Meaning
<b>boldface</b>	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.



---

# Introduction

EclipseLink is an advanced, object-persistence and object-transformation framework that provides development tools and run-time capabilities that reduce development and maintenance efforts, and increase enterprise application functionality. This chapter includes the following topics:

- [About EclipseLink](#)
- [About This Documentation](#)

## About EclipseLink

Using EclipseLink, you can integrate persistence and object-transformation into your application, while staying focused on your primary domain problem by taking advantage of an efficient, flexible, and field-proven solution.

EclipseLink is suitable for use with a wide range of Java Enterprise Edition (Java EE) and Java application architectures. Use EclipseLink to design, implement, deploy, and optimize an advanced object-persistence and object-transformation layer that supports a variety of data sources and formats, including the following:

- JPA – For object-relational persistence, supporting the JPA (Java Persistence API) specification and a native API
- NoSQL – For object persistence of non-relational NoSQL and EIS databases through JPA and a native API
- JAXB – For object-XNL transformation, supporting the JAXB (Java Architecture for XML Binding) specification and a native API
- JSON – For object-JSON (JavaScript Object Notation) transformation
- DBWS – For generation of web services from database tables and stored procedures

The EclipseLink native API includes:

- Relational – For transactional persistence of Java objects to a relational database accessed using Java Database Connectivity (JDBC) drivers.
- Object-Relational Data Type – For transactional persistence of Java objects to special-purpose structured data source representations optimized for storage in object-relational data type databases such as Oracle Database.
- Enterprise information system (EIS) – For transactional persistence of Java objects to a non-relational data source accessed using a Java EE Connector architecture

(JCA) adapter and any supported EIS record type, including indexed, mapped, or XML.

- XML – For non-transactional, non-prescription (in-memory) conversion between Java objects and XML Schema Document (XSD)-based XML documents using Java Architecture for XML Binding (JAXB).

EclipseLink includes support for EJB 3.0 and the Java Persistence API (JPA) in Java EE and Java SE environments including integration with a variety of application servers including:

- Oracle WebLogic Server
- Oracle Glassfish Server
- JBoss Web Server
- IBM WebSphere application server
- SAP NetWeaver
- Oracle Containers for Java EE (OC4J)
- Various other web containers, such as Apache Tomcat, Eclipse Gemini, IBM WebSphere CE, and SpringSource tcServer

EclipseLink lets you quickly capture and define object-to-data source and object-to-data representation mappings in a flexible, efficient metadata format.

The EclipseLink runtime lets your application exploit this mapping metadata with a simple session facade that provides in-depth support for standard APIs such as JPA, and JAXB as well as EclipseLink-specific extensions to those standards.

## About This Documentation

EclipseLink is the reference implementation of the Java Persistence Architecture (JPA) 2.0 specification. It also includes many enhancements and extensions.

This document explains the EclipseLink enhancements and extensions to JPA. Please refer to the JPA specification for full documentation of core JPA. Where appropriate, this documentation provides links to the pertinent section of the specification.

## Other Resources

For more information, see:

- Java Persistence specification for complete information about JPA  
<http://jcp.org/en/jsr/detail?id=317>
- EclipseLink User Guide for more information about EclipseLink support of JPA.  
<http://www.eclipse.org/eclipselink/documentation/>
- The EclipseLink API reference documentation (Javadoc) for complete information on core JPA plus the EclipseLink enhancements  
<http://www.eclipse.org/eclipselink/api/>
  - The schema for the JPA persistence configuration file  
[http://java.sun.com/xml/ns/persistence/persistence\\_2\\_0.xsd](http://java.sun.com/xml/ns/persistence/persistence_2_0.xsd)
  - The schema for the persistence object/relational mapping file  
[http://java.sun.com/xml/ns/persistence/orm\\_2\\_0.xsd](http://java.sun.com/xml/ns/persistence/orm_2_0.xsd)
  - The schema for the native EclipseLink mapping file  
[http://www.eclipse.org/eclipselink/xsds/eclipselink\\_orm\\_2\\_0.xsd](http://www.eclipse.org/eclipselink/xsds/eclipselink_orm_2_0.xsd)

- Examples that display the use of a number of EclipseLink JPA features  
<http://wiki.eclipse.org/EclipseLink/Examples/>
- JavaEE and JPA tutorial. Although this tutorial does not include EclipseLink-specific information, it does contain useful information to help you implement JPA 2.0 applications.  
<http://download.oracle.com/javaee/5/tutorial/doc/bnbpy.html>
- Java Persistence, a wiki-based "open book" about JPA 2.0  
[http://en.wikibooks.org/wiki/Java\\_Persistence](http://en.wikibooks.org/wiki/Java_Persistence)





---

## Annotation Extensions Reference

EclipseLink supports the Java Persistence API (JPA) 2.0 specification. It also includes many enhancements and extensions. This chapter includes information on the EclipseLink extensions to the JPA annotations.

This chapter contains the following sections:

- [Functional Listing of Annotation Extensions](#)
- [Alphabetical Listing of Annotation Extensions](#)

### Functional Listing of Annotation Extensions

The following lists the EclipseLink annotation extensions, categorized by function:

- [Mapping Annotations](#)
- [Entity Annotations](#)
- [Converter Annotations](#)
- [Caching Annotations](#)
- [Customization and Optimization Annotations](#)
- [Copy Policy Annotations](#)
- [Returning Policy Annotations](#)
- [Stored Procedure and Function Annotations](#)
- [Partitioning Annotations](#)
- [Non-relational \(NoSQL\) Annotations](#)

### Mapping Annotations

EclipseLink includes the following annotation extensions for mappings:

- [@PrivateOwned](#)
- [@JoinFetch](#)
- [@Mutable](#)
- [@Property](#)
- [@Transformation](#)
- [@ReadTransformer](#)
- [@WriteTransformer](#)

- [@WriteTransformers](#)

## Entity Annotations

EclipseLink includes the following annotation extensions for entities:

- [@AdditionalCriteria](#)
- [@ExcludeDefaultMappings](#)
- [@Multitenant](#)
- [@ReadOnly](#)
- [@OptimisticLocking](#)
- [@TenantDiscriminatorColumns](#)
- [@TenantDiscriminatorColumn](#)
- [@TenantTableDiscriminator](#)
- [@Struct](#)

## Converter Annotations

EclipseLink includes the following annotation extensions for converting data:

- [@Convert](#)
- [@Converter](#)
- [@Converters](#)
- [@TypeConverter](#)
- [@TypeConverters](#)
- [@ObjectTypeConverter](#)
- [@ObjectTypeConverters](#)
- [@StructConverter](#)
- [@StructConverters](#)

## Caching Annotations

EclipseLink includes the following annotation extensions for caching:

- [@Cache](#)
- [@CacheIndex](#)
- [@CacheIndexes](#)
- [@CacheInterceptor](#)
- [@TimeOfDay](#)
- [@ExistenceChecking](#)

## Customization and Optimization Annotations

EclipseLink includes the following annotation extensions for customization and optimization.

- [@Customizer](#)

- [@ChangeTracking](#)

## Copy Policy Annotations

EclipseLink includes the following annotation extensions for copy policies:

- [@CloneCopyPolicy](#)
- [@CopyPolicy](#)
- [@InstantiationCopyPolicy](#)

## Returning Policy Annotations

EclipseLink includes the following annotation extensions for returning policies:

- [@ReturnInsert](#)
- [@ReturnUpdate](#)

## Stored Procedure and Function Annotations

EclipseLink includes the following annotation extensions for stored procedures and stored functions:

- [@NamedPLSQLStoredFunctionQueries](#)
- [@NamedPLSQLStoredFunctionQuery](#)
- [@NamedPLSQLStoredProcedureQueries](#)
- [@NamedPLSQLStoredProcedureQuery](#)
- [@NamedStoredFunctionQueries](#)
- [@NamedStoredFunctionQuery](#)
- [@NamedStoredProcedureQueries](#)
- [@NamedStoredProcedureQuery](#)
- [@PLSQLParameter](#)
- [@PLSQLRecord](#)
- [@PLSQLRecords](#)
- [@StoredProcedureParameter](#)

## Partitioning Annotations

EclipseLink includes the following annotation extensions for using partitions:

- [@HashPartitioning](#)
- [@Partitioned](#)
- [@Partitioning](#)
- [@PinnedPartitioning](#)
- [@RangePartition](#)
- [@RangePartitioning](#)
- [@ReplicationPartitioning](#)
- [@RoundRobinPartitioning](#)

- [@UnionPartitioning](#)
- [@ValuePartitioning](#)

## Non-relational (NoSQL) Annotations

EclipseLink includes the following annotation extensions for non-relational datasources:

- [@Field](#)
- [@JoinField](#)
- [@JoinFields](#)
- [@NoSql](#)

## Alphabetical Listing of Annotation Extensions

The following lists the EclipseLink annotation extensions:

- [@AdditionalCriteria](#)
- [@Array](#)
- [@BatchFetch](#)
- [@Cache](#)
- [@CacheIndex](#)
- [@CacheIndexes](#)
- [@CacheInterceptor](#)
- [@CascadeOnDelete](#)
- [@ChangeTracking](#)
- [@ClassExtractor](#)
- [@CloneCopyPolicy](#)
- [@CompositeMember](#)
- [@ConversionValue](#)
- [@Convert](#)
- [@Converter](#)
- [@Converters](#)
- [@CopyPolicy](#)
- [@Customizer](#)
- [@DeleteAll](#)
- [@DiscriminatorClass](#)
- [@ExcludeDefaultMappings](#)
- [@ExistenceChecking](#)
- [@FetchAttribute](#)
- [@FetchGroup](#)
- [@FetchGroups](#)

- [@Field](#)
- [@HashPartitioning](#)
- [@Index](#)
- [@Indexes](#)
- [@InstantiationCopyPolicy](#)
- [@JoinFetch](#)
- [@JoinField](#)
- [@JoinFields](#)
- [@MapKeyConvert](#)
- [@Multitenant](#)
- [@Mutable](#)
- [@NamedPLSQLStoredFunctionQuery](#)
- [@NamedPLSQLStoredProcedureQuery](#)
- [@NamedStoredFunctionQueries](#)
- [@NamedStoredFunctionQuery](#)
- [@NamedStoredProcedureQueries](#)
- [@NamedStoredProcedureQuery](#)
- [@Noncacheable](#)
- [@NoSql](#)
- [@ObjectTypeConverter](#)
- [@ObjectTypeConverters](#)
- [@OptimisticLocking](#)
- [@OrderCorrection](#)
- [@Partitioned](#)
- [@Partitioning](#)
- [@PinnedPartitioning](#)
- [@PLSQLParameter](#)
- [@PLSQLRecord](#)
- [@PLSQLRecords](#)
- [@PrimaryKey](#)
- [@PrivateOwned](#)
- [@Properties](#)
- [@Property](#)
- [@QueryRedirectors](#)
- [@RangePartition](#)
- [@RangePartitioning](#)
- [@ReadOnly](#)

- [@ReadTransformer](#)
- [@ReplicationPartitioning](#)
- [@ReturnInsert](#)
- [@ReturnUpdate](#)
- [@RoundRobinPartitioning](#)
- [@StoredProcedureParameter](#)
- [@Struct](#)
- [@StructConverter](#)
- [@StructConverters](#)
- [@Structure](#)
- [@TenantDiscriminatorColumns](#)
- [@TenantDiscriminatorColumn](#)
- [@TenantTableDiscriminator](#)
- [@TimeOfDay](#)
- [@Transformation](#)
- [@TypeConverter](#)
- [@TypeConverters](#)
- [@ValuePartition](#)
- [@UuidGenerator](#)
- [@UnionPartitioning](#)
- [@ValuePartitioning](#)
- [@VariableOneToOne](#)
- [@VirtualAccessMethods](#)
- [@WriteTransformer](#)
- [@WriteTransformers](#)



## @AdditionalCriteria

Use @AdditionalCriteria to define parameterized views on data.

You can define additional criteria on entities or mapped superclass. When specified at the mapped superclass level, the additional criteria definition applies to all inheriting entities, unless those entities define their own additional criteria, in which case those defined for the mapped superclass are ignored.

### Annotation Elements

[Table 2–1](#) describes this annotation's elements.

**Table 2–1** @AdditionalCriteria Annotation Elements

Attribute	Description	Default
value	(Required) The JPQL fragment to use as the additional criteria.	

### Usage

Additional criteria can provide an additional filtering mechanism for queries. This filtering option, for example, allows you to use an existing additional JOIN expression defined for the entity or mapped superclass and allows you to pass parameters to it.

Set additional criteria parameters through properties on the entity manager factory or on the entity manager. Properties set on the entity manager override identically named properties set on the entity manager factory. Properties must be set on an entity manager before executing a query. Do not change the properties for the lifespan of the entity manager.

---

---

**Note:** Additional criteria are not supported with native SQL queries.

---

---

### Examples

Specify additional criteria using the @AdditionalCriteria annotation or the <additional-criteria> element. The additional criteria definition supports any valid JPQL string and must use this as an alias to form the additional criteria. For example:

```
@AdditionalCriteria("this.address.city IS NOT NULL")
```

[Example 2–1](#) shows additional criteria defined for the entity `Employee` and then shows the parameters for the additional criteria set on the entity manager.

#### **Example 2–1** Using @AdditionalCriteria Annotation

Define additional criteria on `Employee`, as follows:

```
package model;

@AdditionalCriteria("this.company=:COMPANY")
public class Employee {

    ...
}
```



Set the property on the `EntityManager`. This example returns all employees of `MyCompany`.

```
entityManager.setProperty("COMPANY", "MyCompany");
```

[Example 2-2](#) illustrates the same example as before, but uses the `<additional-criteria>` element in the `eclipselink-orm.xml` mapping file.

#### **Example 2-2 Using `<additional-criteria>` XML**

```
<additional-criteria>
  <criteria>this.address.city IS NOT NULL</criteria>
</additional-criteria>
```

### **Uses for Additional Criteria**

Uses for additional criteria include:

- [Multitenancy](#)
- [Soft Delete](#)
- [Data History](#)
- [Temporal Filtering](#)
- [Shared Table](#)

### **Multitenancy**

In a multitenancy environment, tenants (users, clients, organizations, applications) can share database tables, but the views on the data are restricted so that tenants have access only to their own data. You can use additional criteria to configure such restrictions.

---

---

**Note:** In most cases, you use the `@Multitenant` annotation in multitenancy environments instead, as shown on page -82.

---

---

#### **Example 2-3 Multitenancy Example 1**

The following example restricts the data for a **Billing** client, such as a billing application or billing organization:

```
@AdditionalCriteria("this.tenant = 'Billing'")
```

#### **Example 2-4 Multitenancy Example 2**

The following example could be used in an application used by multiple tenants at the same time. The additional criteria is defined as:

```
@AdditionalCriteria("this.tenant = :tenant")
```

When the tenant acquires its `EntityManagerFactory` or `EntityManager`, the persistence/entity manager property `tenant` is set to the name of the tenant acquiring it. For example,

```
Map properties = new HashMap();
properties.put("tenant", "ACME");
EntityManagerFactory emf = Persistence.createEntityManagerFactory(properties);
```

Or

```
Map properties = new HashMap();
properties.put("tenant", "ACME");
EntityManager em = factory.createEntityManager(properties);
```

## Soft Delete

The following example filters data that is marked as deleted (but which still exists in the table) from a query:

```
@AdditionalCriteria("this.isDeleted = false")
```

## Data History

The following example returns the current data from a query, thus filtering out any out-of-date data, for example data stored in a history table.

```
@AdditionalCriteria("this.endDate is null")
```

---

---

**Note:** EclipseLink also provides specific history support, via `HistoryPolicy`. See [Tracking Changes Using History Policy](http://wiki.eclipse.org/EclipseLink/Examples/JPA/History) at <http://wiki.eclipse.org/EclipseLink/Examples/JPA/History>.

---

---

## Temporal Filtering

The following example filters on a specific date:

```
@AdditionalCriteria("this.startDate <= :viewDate and this.endDate >= :viewDate")
```

## Shared Table

For a shared table, there may be inheritance in the table but not in the object model. For example, a `SavingsAccount` class may be mapped to an `ACCOUNT` table, but the `ACCOUNT` table contains both savings account data (`SAVINGS`) and checking account (`CHECKING`) data. You can use additional criteria to filter out the checking account data.

## See Also

For more information, see:

- ["COLUMN"](#) on page -6
- ["@Multitenant"](#) on page -82



## @Array

Use @Array to define object-relational data types supported by specific databases, such as Oracle VARRAY types or PostgreSQL JDBC Array types.

### Annotation Elements

[Table 2–2](#) describes this annotation's elements.

**Table 2–2 @Array Annotation Elements**

Annotation Element	Description	Default
databaseType	(Required) The name of the database array structure type.	
targetClass	(Optional only if the collection field or property is defined using Java generics; otherwise Required) The class (basic or embeddable) that is the element type of the collection.	Parameterized type of the collection.

### Usage

Use @Array on a collection attribute that is persisted to an Array type. The collection can be of basic types or embeddable class mapped using a Struct.

### Examples

[Example 2–5](#) shows how to use this annotation with an Oracle VARRAY type.

**Example 2–5 Using @Array with Oracle VARRAY**

```
VARRAY DDL:  
CREATE TYPE TASKS_TYPE AS VARRAY(10) OF VARCHAR(100)
```

```
@Struct  
@Entity  
public class Employee {  
    @Id  
    private long id;  
    @Array(databaseType="TASKS_TYPE")  
    private List<String> tasks;  
}
```

[Example 2–6](#) shows how to use this annotation with an Postgress Struct type.

**Example 2–6 Using @Array with Postgress Struct**

```
DDL:  
CREATE TABLE EMPLOYEE (ID BIGINT, TASKS TEXT[])
```

```
@Struct  
@Entity  
public class Employee {  
    @Id  
    private long id;  
    @Array(databaseType="TEXT[]")  
    private List<String> tasks;  
}
```

}

## See Also

For more information, see the following:

- ["@Struct"](#) on page -164

## @BatchFetch

Use @BatchFetch to read objects related to a relationship mapping (such as one-to-one, one-to-many, many-to-one, many-to-many, and element collection) to be read in a single query.

### Annotation Elements

Table 2–3 describes this annotation's elements.

**Table 2–3 @BatchFetch Annotation Elements**

Annotation Element	Description	Default
size	Default size of the batch fetch, used only when BatchFetchType=IN to define the number of keys in each IN clause	256 or the query's pageSize (for cursor queries)
BatchFetchType	(optional) The type of batch fetch to use: <ul style="list-style-type: none"><li>■ JOIN – The original query's selection criteria is joined with the batch query</li><li>■ EXISTS – Uses an SQL EXISTS clause and a sub-select in the batch query instead of a JOIN</li><li>■ IN – Uses an SQL IN clause in the batch query, passing in the source object IDs.</li></ul>	JOIN

### Usage

Batch fetching allows for the optimal loading of a tree. Setting the @BatchFetch annotation on a *child* relationship of a tree structure causes EclipseLink to use a *single* SQL statement for each level.

Using BatchFetchType=EXISTS does not require an SQL DISTINCT statement (which may cause issues with LOBs) and may be more efficient for some types of queries or on specific databases.

When using BatchFetchType=IN, EclipseLink selects only objects not already in the cache. This method may work better with cursors or pagination, or in situations in which you cannot use a JOIN. On some databases, this may only work for singleton IDs.

### Examples

The following examples show how to use this annotation (and XML) with different batch fetch types.

**Example 2–7 Using JOIN BatchFetch Type**

```
@OneToOne
@BatchFetch(BatchFetchType.JOIN)
private Address address;

<element-collection name="stringMap">
  <batch-fetch type="JOIN">
</element-collection>
```

**Example 2–8 Using EXISTS BatchFetch Type**

```
@BatchFetch(BatchFetchType.EXISTS)
@OneToOne
public Map<String, String> getStringMap() {
    return stringMap;
}
```

```
<element-collection name="stringMap">
  <batch-fetch type="EXISTS">
</element-collection>
```

**Example 2–9 Using IN BatchFetch Type**

```
@BatchFetch(BatchFetchType.IN, size=50)
@OneToOne
public Map<String, String> getStringMap() {
    return stringMap;
}
```

```
<element-collection name="StringMap">
  <batch-fetch type="IN" size="50">
</element-collection>
```

**See Also**

For more information, see:

- ["@JoinFetch"](#) on page -74

## @Cache

Use @Cache (in place of the JPA @Cacheable annotation) to configure the EclipseLink object cache. By default, EclipseLink uses a shared object cache to cache all objects. You can configure the caching type and options on a per class basis to allow optimal caching.

### Annotation Elements

Table 2–4 describes this annotation's elements.

**Table 2–4 @Cache Annotation Elements**

Annotation Element	Description	Default
type	<p>(Optional) Set this attribute to the type (org.eclipse.persistence.annotations.CacheType enumerated type) of the cache that you will be using:</p> <ul style="list-style-type: none"> <li>■ FULL</li> <li>■ WEAK</li> <li>■ SOFT</li> <li>■ SOFT_WEAK</li> <li>■ HARD_WEAK</li> <li>■ CACHE (not recommended)</li> <li>■ NONE (not recommended, use isolation=ISOLATED instead)</li> </ul> <p>You can override this attribute with these persistence unit properties:</p> <ul style="list-style-type: none"> <li>■ eclipselink.cache.type.&lt;ENTITY&gt;</li> <li>■ eclipselink.cache.type.default</li> </ul>	CacheType.SOFT_WEAK
size	(Optional) Set this attribute to an int value to define the size of cache to use (number of objects).	100
isolation	<p>(Optional) The caching level of the Entity:</p> <ul style="list-style-type: none"> <li>■ shared – Entity instances will be cached within the EntityManagerFactory/ServerSession level.</li> <li>■ isolated – The Entity and its data is not stored in the shared cache, but is isolated to the Persistence Context/UnitOfWork or IsolatedClientSession.</li> <li>■ protected – Entity state information will be cached in the shared cache, but Entity instances will not be shared.</li> </ul>	shared
expiry	(Optional) The int value to enable the expiration of the cached instance after a fixed period of time (milliseconds). Queries executed against the cache after this will be forced back to the database for a refreshed copy.	no expiry
expiryTimeOfDay	(Optional) Specific time of day (org.eclipse.persistence.annotations.TimeOfDay) when the cached instance will expire. Queries executed against the cache after this will be forced back to the database for a refreshed copy.	no expiry



**Table 2–4 (Cont.) @Cache Annotation Elements**

Annotation Element	Description	Default
<code>alwaysRefresh</code>	(Optional) Set to a boolean value of <code>true</code> to force all queries that go to the database to always refresh the cache	<code>false</code>
<code>refreshOnlyIfNewer</code>	(Optional) Set to a boolean value of <code>true</code> to force all queries that go to the database to refresh the cache only if the data received from the database by a query is newer than the data in the cache (as determined by the optimistic locking field). <b>Note:</b> <ul style="list-style-type: none"> <li>■ This option only applies if one of the other refreshing options, such as <code>alwaysRefresh</code>, is already enabled.</li> <li>■ A version field is necessary to apply this feature.</li> </ul>	<code>false</code>
<code>disableHits</code>	(Optional) Set to a boolean value of <code>true</code> to force all queries to bypass the cache for hits, but still resolve against the cache for identity. This forces all queries to hit the database.	<code>false</code>
<code>coordinationType</code>	(Optional) Set this attribute to the cache coordination mode ( <code>org.eclipse.persistence.annotations.CacheCoordinationType</code> enumerated type). You must also configure cache coordination in your persistence unit properties. See " <a href="#">Caching</a> " on page 5-2.	<code>SEND_OBJECT_CHANGES</code>
<code>databaseChangeNotificationType</code>	(Optional) The database change notification mode: <ul style="list-style-type: none"> <li>■ Invalidate – Invalidates the EclipseLink cache when a database change event is received for an object.</li> <li>■ None – No database change events will be processed. The database event listener must also be configured for the persistence unit/session.</li> </ul>	<code>INVALIDATE</code>

## Usage

Use the `@Cache` annotation instead of the JPA `@Cacheable` annotation to provide additional caching configuration.

You can define the `@Cache` annotation on the following:

- `@Entity`
- `@MappedSuperclass`
- the root of the inheritance hierarchy (if applicable)

If you define the `@Cache` annotation on an inheritance subclass, the annotation will be ignored. If you define the `@Cache` annotation on `@Embeddable` EclipseLink will throw an exception.

### Caching in EclipseLink

The EclipseLink cache is an in-memory repository that stores recently read or written objects based on class and primary key values. EclipseLink uses the cache to do the following:

- Improve performance by holding recently read or written objects and accessing them in-memory to minimize database access.

- Manage locking and isolation level.
- Manage object identity.

For more information about the EclipseLink cache and its default behavior, see:

- "Caching Overview"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Caching\\_Overview](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Caching_Overview)
- [http://wiki.eclipse.org/Introduction\\_to\\_Cache\\_%28ELUG%29](http://wiki.eclipse.org/Introduction_to_Cache_%28ELUG%29)

EclipseLink defines the following entity caching annotations:

- @Cache
- @TimeOfDay
- @ExistenceChecking

EclipseLink also provides a number of persistence unit properties that you can specify to configure the EclipseLink cache. These properties may compliment or provide an alternative to the usage of annotations.

For more information, see the following:

- How to Use the Persistence Unit Properties for Caching  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_%28ELUG%29#How\\_to\\_Use\\_the\\_Persistence\\_Unit\\_Properties\\_for\\_Caching](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#How_to_Use_the_Persistence_Unit_Properties_for_Caching)
- What You May Need to Know About Overriding Annotations in JPA  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_%28ELUG%29#What\\_You\\_May\\_Need\\_to\\_Know\\_About\\_Overriding\\_Annotations\\_in\\_JPA](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#What_You_May_Need_to_Know_About_Overriding_Annotations_in_JPA)
- What You May Need to Know About Using EclipseLink JPA Persistence Unit Properties  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_%28ELUG%29#What\\_You\\_May\\_Need\\_to\\_Know\\_About\\_Using\\_EclipseLink\\_JPA\\_Persistence\\_Unit\\_Properties](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#What_You_May_Need_to_Know_About_Using_EclipseLink_JPA_Persistence_Unit_Properties)

## Examples

[Example 2–10](#) illustrates an @Cache annotation.

### **Example 2–10 Using @Cache Annotation**

```
...
@Entity
@Cache(
    type=CacheType.SOFT, // Cache everything until the JVM decides memory is low.
    size=64000 // Use 64,000 as the initial cache size.
    expiry=36000000, // 10 minutes
    coordinationType=CacheCoordinationType.INVALIDATE_CHANGED_OBJECTS // if cache
    coordination is used, only send invalidation messages.
)
public class Employee {
    ...
}
```

[Example 2–11](#) shows how to use this annotation in the eclipselink-orm.xml file.

**Example 2-11 Using <cache> XML**

```

<entity-mappings
  xmlns="http://www.eclipse.org/eclipselink/xsds/persistence/orm"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.eclipse.org/eclipselink/xsds/persistence/orm
http://www.eclipse.org/eclipselink/xsds/eclipselink_orm_2_4.xsd"
  version="2.4">
  <entity name="Employee" class="org.acme.Employee" access="FIELD">
    <cache type="SOFT" size="64000" expiry="36000000"
coordination-type="INVALIDATE_CHANGED_OBJECTS" />
  </entity>
</entity-mappings>

```

You can also specify caching properties at the persistence unit level (in the persistence.xml file) as shown here:

**Example 2-12 Specifying Caching in persistence.xml**

```

<persistence xmlns="http://java.sun.com/xml/ns/persistence"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://java.sun.com/xml/ns/persistence persistence_2_0.xsd"
  version="2.0">
  <persistence-unit name="acme" transaction-type="RESOURCE_LOCAL">
    <provider>org.eclipse.persistence.jpa.PersistenceProvider</provider>
    <exclude-unlisted-classes>false</exclude-unlisted-classes>
    <properties>
      <property name="eclipselink.cache.shared.default" value="false"/>
      <property name="eclipselink.cache.shared.Employee" value="true"/>
      <property name="eclipselink.cache.type.Employee" value="SOFT"/>
      <property name="eclipselink.cache.size.Employee" value="64000"/>
    </properties>
  </persistence-unit>
</persistence>

```

**See Also**

For more information, see:

- ["@ExistenceChecking"](#) on page -56
- ["@TimeOfDay"](#) on page -182
- ["@CacheInterceptor"](#) on page -24
- ["Configuring Caching"](#)  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Cache\\_Annotation](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Cache_Annotation)

## @CacheIndex

Use @CacheIndex to define a cached index. Cache indexes are used only when caching is enabled.

### Annotation Elements

[Table 2–5](#) describes this annotation's elements.

**Table 2–5 @CacheIndex Annotation Elements**

Annotation Element	Description	Default
columnNames	(Optional) The set of columns on which to define the index. Not required when annotated on a field/method.	
updateable	(Optional) Specify if the indexed field is updateable. If true, the object will be re-indexed on each update or refresh.	true

### Usage

A cache index allows `singleResult` queries to obtain a cache hit when querying on the indexed fields. A `resultList` query cannot obtain cache hits, as it is unknown if all of the objects are in memory, (unless the cache usage query hint is used).

The index should be unique. If it is not, the first indexed object will be returned.

You can use @CacheIndex on an Entity class or on an attribute. The column is defaulted when defined on a attribute.

### Examples

[Example 2–13](#) shows an example of using the @CacheIndex annotation.

#### **Example 2–13 Using @CacheIndex Annotation**

```
@Entity
@CacheIndex(columnNames={"F_NAME", "L_NAME"}, updateable=true)
public class Employee {
    @Id
    private long id;
    @CacheIndex
    private String ssn;
    @Column(name="F_NAME")
    private String firstName;
    @Column(name="L_NAME")
    private String lastName;
}
```

[Example 2–14](#) shows an example of using the <cache-index> XML element in the eclipselink-orm.xml file.

#### **Example 2–14 Using <cache-index> XML**

```
<?xml version="1.0"?>
<entity-mappings
    xmlns="http://www.eclipse.org/eclipselink/xsds/persistence/orm"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```

xsi:schemaLocation="http://www.eclipse.org/eclipselink/xsds/persistence/orm
http://www.eclipse.org/eclipselink/xsds/eclipselink_orm_2_4.xsd"
version="2.4">
  <entity name="Employee" class="org.acme.Employee" access="FIELD">
    <cache-index updateable="true">
      <column-name>F_NAME</column-name>
      <column-name>L_NAME</column-name>
    </cache-index>
    <attributes>
      <id name="id"/>
      <basic name="ssn">
        <cache-index/>
      </basic>
      <basic name="firstName">
        <column name="F_NAME"/>
      </basic>
      <basic name="lastName">
        <column name="L_NAME"/>
      </basic>
    </attributes>
  </entity>
</entity-mappings>

```

[Example 2–15](#) shows an example query using a cache index.

#### **Example 2–15 Caching an Index Query**

```

Query query = em.createQuery("Select e from Employee e where e.firstName =
:firstName and e.lastName = :lastName");
query.setParameter("firstName", "Bob");
query.setParameter("lastName", "Smith");
Employee employee = (Employee)query.getSingleResult();

```

## See Also

For more information, see:

- ["@Cache"](#) on page -16
- "Cache Indexes"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Indexes](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Indexes)

---

## @CacheIndexes

Use @CacheIndexes to define a set of @CacheIndex on an entity.

### Annotation Elements

[Table 2–6](#) describes this annotation's elements.

**Table 2–6   @CacheIndexes Annotation Elements**

Annotation Element	Description	Default
CacheIndex[]	An array of cache indexes	

### Examples

See "[@CacheIndex](#)" on page -20 for examples of using the @CacheIndexes annotation.

### See Also

For more information, see:

- "[@CacheIndex](#)" on page -20



## @CacheInterceptor

Use `@CacheInterceptor` on an entity to intercept all EclipseLink cache access to the entity instead of responding to cache operations through an event.

### Annotation Elements

[Table 2–7](#) describes this annotation's elements.

**Table 2–7    @CacheInterceptor Annotation Elements**

Annotation Element	Description	Default
value	The class to be used to intercept EclipseLink's cache access.	

### Usage

Once set, the specified class will receive all caching calls. Existing EclipseLink cache settings will continue to be used, any calls allowed to continue to the EclipseLink cache will execute against the configured cache.

When using with an entity in inheritance, you should define the `@CacheInterceptor` on the *root* of the inheritance hierarchy.

### Examples

[Example 2–16](#) shows how to integrate an external cache with EclipseLink.

#### **Example 2–16    Using @CacheInterceptor Annotation**

In this example, the `Employee` class intercepts all EclipseLink calls to the internal EclipseLink cache and redirects them to the Oracle Coherence Grid cache (`CoherenceInterceptor`).

```
import oracle.eclipselink.coherence.integrated.cache.CoherenceInterceptor;
import org.eclipse.persistence.annotations.Customizer;

@Entity
@CacheInterceptor(value = CoherenceInterceptor.class)
public class Employee {
    ...
}
```

[Example 2–17](#) shows an example of using the `<cache-interceptor>` XML element in the `eclipselink-orm.xml` file.

#### **Example 2–17    Using <cache-interceptor> XML**

```
<entity class="Employee">
  <cache-interceptor class="CoherenceInterceptor"/>
  ...
</entity>
```

### See Also

For more information, see:

- ["@Cache"](#) on page -16





## @CascadeOnDelete

Use the `@CascadeOnDelete` annotation to specify that a delete operation performed on a database object is cascaded on secondary or related tables.

`ON DELETE CASCADE` is a database foreign key constraint option that automatically removes the dependent rows.

### Annotation Elements

There are no elements for this annotation.

### Usage

You can place `@CascadeOnDelete` on any relationship in which the target is defined as foreign key to the source Entity.

Add the annotation on the source relationship: `@OneToOne`, `@OneToMany`, `@ManyToMany`, and `@ElementCollection`. You can also add `@CascadeOnDelete` to an Entity with a `@SecondaryTable` or `JOINED` inheritance. [Table 2–8](#) describes the affect of placing `@CascadeDelete` on these different elements

**Table 2–8 Using @Cascade on Different Elements**

Element	Effect of @CascadeOnDelete
Entity	Defines that secondary or joined inheritance tables should cascade the delete on the database
OneToOne mapping	The deletion of the related object is cascaded on the database. This is only allowed for mappedBy/target-foreign key OneToOne mappings (because of constraint direction).
OneToMany mapping	For a OneToMany using a mappedBy or JoinColumn, the deletion of the related objects is cascaded on the database. For a OneToMany using a JoinTable, the deletion of the join table is cascaded on the database (target objects cannot be cascaded even if private because of constraint direction).
ManyToMany mapping	The deletion of the join table is cascaded on the database (target objects cannot be cascaded even if private because of constraint direction).
ElementCollection mapping	The deletion of the collection table is cascaded on the database.

`@CascadeOnDelete` has the following behavior:

- DDL generation: If DDL generation is used, the generated constraint will include the cascade deletion option.
- Entity: Remove will not execute SQL for deletion from secondary or joined inheritance tables (as constraint will handle deletion).
- OneToOne: If the mapping uses cascading or orphanRemoval, SQL will not be executed to delete target object.
- OneToMany: If the mapping uses cascading or orphanRemoval, SQL will not be executed to delete target objects.
- ManyToMany: SQL will not be executed to delete from the join table.

- ElementCollection: SQL will not be executed to delete from the collection table.
- Cache: Cascaded objects will still be removed from the cache and persistence context.
- Version locking: Version will not be verified on deletion of cascaded object.
- Events: Deletion events may not be executed on the cascaded objects if the objects are not loaded.
- Cascading: The remove operation should still be configured to cascade in the mapping if using CascadeOnDelete.

## Examples

[Example 2-18](#) shows the cascading deletion of the Employee secondary table and all of its owned relationships.

### **Example 2-18 Using @CascadeOnDelete Annotation**

```
@Entity
@SecondaryTable(name="EMP_SALARY")
@CascadeOnDelete
public class Employee{
    @Id
    private long id;
    private String firstName;
    private String lastName;
    @Column(table="EMP_SALARY")
    private String salary;
    @OneToOne(mappedBy="owner", orphanRemoval=true, cascade={CascadeType.ALL})
    @CascadeOnDelete
    private Address address;
    @OneToMany(mappedBy="owner", orphanRemoval=true, cascade={CascadeType.ALL})
    @CascadeOnDelete
    private List<Phone> phones;
    @ManyToMany
    @JoinTable(name="EMP_PROJ")
    @CascadeOnDelete
    private List<Project> projects;
    ...
}
```

In the eclipselink-orm.xml descriptor file, specify cascade on delete as shown in [Example 2-19](#)

### **Example 2-19 Using <cascade-on-delete> XML**

```
...
<cascade-on-delete>true</cascade-on-delete>
...
```

## See Also

For more information, see:

- EclipseLink example:  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/DeleteCascade>

- "@CascadeOnDelete"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Schema\\_Generation/CascadeOnDelete](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Schema_Generation/CascadeOnDelete)



## @ChangeTracking

Use @ChangeTracking to specify the `org.eclipse.persistence.descriptors.changetracking.ObjectChangePolicy`. This policy computes change sets for the EclipseLink commit process and optimizes the transaction by including objects in the change set calculation that have at least one changed attribute.

### Annotation Elements

[Table 2–9](#) describes this annotation's elements.

**Table 2–9 @ChangeTracking Annotation Elements**

Annotation Element	Description	Default
ChangeTrackingType	(Optional) The change tracking policy to use: <ul style="list-style-type: none"><li>■ <b>ATTRIBUTE</b> – The object's <code>set</code> method is weaved to raise change events to collect changes as they are made. Requires usage of weaving, and LAZY collection relationships, or eager weaving.</li><li>■ <b>OBJECT</b> – The object's <code>set</code> method is weaved to mark the object as <i>dirty</i>. Any dirty objects are compared against a copy of their original state for changes on commit or flush operations. Requires usage of weaving, and LAZY collection relationships, or eager weaving.</li><li>■ <b>DEFERRED</b> – All managed objects are compared against a copy of their original state for changes on commit or flush. Does not require weaving.</li><li>■ <b>AUTO</b> – Does not set any change tracking policy; change tracking will be determined at runtime.</li></ul>	AUTO

### Usage

Use this annotation to configure an alternative change policy, if the automatic policy is having issues with your application. Using @ChangeTracking may improve commit performance for objects with few attributes or objects with many changed attributes.

---

**Note:** When using change tracking with **ATTRIBUTE** or **OBJECT**, if you modify an object's field through reflection, EclipseLink *will not* detect the change. However, if you use **DEFERRED**, EclipseLink *will* detect the change.

---

### Examples

[Example 2–20](#) shows how to use @ChangeTracking to set the unit of work's change policy.

**Example 2–20 Using @ChangeTracking Annotation**

```
@ChangeTracking(DEFERRED)
@Entity
public class Employee {
    ...
}
```

[Example 2-21](#) shows how to use the `<change-tracking>` element in the `eclipselink-orm.xml` file.

**Example 2-21 Using `<change-tracking>` XML**

```
<entity class="Employee"
  <change-tracking type="DEFERRED"/>
...
</entity>
```

[Example 2-22](#) shows how to configure change tracking in the persistence unit `persistence.xml` file or by importing a property map.

**Example 2-22 Specifying Change Tracking in `persistence.xml`**

Using `persistence.xml` file:

```
<property name="eclipselink.weaving.changetracking" value="false"/>
```

Using property map:

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.WEAVING_CHANGE_TRACKING, "false");
```

## See Also

For more information, see:

- How to Use the `@ChangeTracking` Annotation  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_%28ELUG%29#Using\\_EclipseLink\\_JPA\\_Extensions\\_for\\_Tracking\\_Changes](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#Using_EclipseLink_JPA_Extensions_for_Tracking_Changes)

## @ClassExtractor

Use `@ClassExtractor` to define a custom class indicator in place of providing a discriminator column.

### Annotation Elements

[Table 2–10](#) describes this annotation's elements.

**Table 2–10** *@ClassExtractor Annotation Elements*

Annotation Element	Description	Default
<code>java.lang.Class</code>	(Required) The name of the class extractor to apply to the entity's descriptor	

### Usage

If you are mapping to an existing database, and the tables do not have a discriminator column you can still define inheritance using the `@ClassExtractor` annotation or `<class-extractor>` element. The class extractor takes a class that implements the `ClassExtractor` interface. An instance of this class is used to determine the class type to use for a database row. The class extractor must define a `extractClassFromRow` method that takes the database `Record` and `Session`.

If a class extractor is used with `SINGLE_TABLE` inheritance, the rows of the class type must be able to be filtered in queries. This can be accomplished by setting an `onlyInstancesExpression` or `withAllSubclassesExpression` for branch classes. These can be set to `Expression` objects using a `DescriptorCustomizer`.

### Examples

[Example 2–23](#) shows an example of using `ClassExtractor` to define inheritance.

#### **Example 2–23** *Using @ClassExtractor Annotation*

```
@Entity
@Table(name="MILES_ACCOUNT")
@Inheritance(strategy=InheritanceType.SINGLE_TABLE)
@ClassExtractor(AirMilesClassExtractor.class)
@Customizer(AirMilesCustomizer.class)
public class AirMilesAccount implements Serializable {
    @Id
    private Long id;
    @Basic
    private String totalMiles;
    @Basic
    private String milesBalance;
    ...
}

@Entity
@Customizer(PreferredCustomizer.class)
public class PreferredAccount extends AirMilesAccount {
    ...
}

public class AirMilesClassExtractor implements ClassExtractor {
    public void extractClassFromRow(Record row, Session session) {
```



```

        if (row.get("TOTALMILES").lessThan(100000)) {
            return AirMilesAccount.class;
        } else {
            return PreferredAccount.class;
        }
    }
}

public class AirMilesCustomizer implements DescriptorCustomizer {
    public void customize(ClassDescriptor descriptor) {
        ExpressionBuilder account = new ExpressionBuilder();
        Expression expression = account.getField("TOTALMILES").lessThan(100000);
        descriptor.getInheritancePolicy().setOnlyInstancesExpression(expression);
    }
}

public class PreferredCustomizer implements DescriptorCustomizer {
    public void customize(ClassDescriptor descriptor) {
        ExpressionBuilder account = new ExpressionBuilder();
        Expression expression =
account.getField("TOTALMILES").greaterThanEqual(100000);
        descriptor.getInheritancePolicy().setOnlyInstancesExpression(expression);
    }
}

```

[Example 2-24](#) shows how to use the `<class-extractor>` element in the `eclipselink-orm.xml` file.

**Example 2-24 Using `<class-extractor>` XML**

```

<entity class="AirMilesAccount">
    <table name="MILES_ACCOUNT"/>
    <inheritance strategy="SINGLE_TABLE"/>
    <class-extractor class="AirMilesClassExtractor"/>
    ...
</entity>

<entity class="PreferredAccount">
    <customizer class="PreferredCustomizer"/>
    ...
</entity>

```

## See Also

For more information, see:

- ["@Customizer"](#) on page -48

## @CloneCopyPolicy

Use @CloneCopyPolicy to specify an `org.eclipse.persistence.descriptors.copying.CloneCopyPolicy` on an Entity.

### Annotation Elements

[Table 2–11](#) describes this annotation's elements.

**Table 2–11** @CloneCopyPolicy Annotation Elements

Annotation Element	Description	Default
method	(Optional) The method that will be used to create a clone for comparison with EclipseLink's <code>DeferredChangeDetectionPolicy</code> .	
workingCopyMethod	(Optional) The <code>workingCopyMethod</code> that will be used to create a clone that will be used when registering an object in an EclipseLink <code>UnitOfWork</code> .	

---

---

**Note:** You must specify either a `method` or `workingCopyMethod`.

---

---

### Usage

The `clone` method should perform a shallow clone of the object. This can be used to clone non-persistent fields from a instance in the shared cache.

You can specify @CloneCopyPolicy on an Entity, MappedSuperclass, or Embeddable class.

### Examples

[Example 2–25](#) and [Example 2–26](#) show several examples of the @CloneCopyPolicy annotation and `<clone-copy-policy>` XML element, respectively.

#### Example 2–25 Using @CloneCopyPolicy Annotation

```
@CloneCopyPolicy(method="myClone")
```

```
@CloneCopyPolicy(method="myClone", workingCopyMethod="myWorkingCopyClone")
```

```
@CloneCopyPolicy(workingCopyMethod="myWorkingCopyClone")
```

#### Example 2–26 Using <clone-copy-policy> XML

```
<clone-copy-policy type="copy" method="myClone"
workingCopyMethod="myWorkingCopyClone" />
```

```
<clone-copy-policy type="copy" workingCopyMethod="myWorkingCopyClone" />
```

```
<clone-copy-policy type="copy" method="myClone" />
```

## See Also

For more information, see:

- How to Use the @CloneCopyPolicy Annotation  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_%28ELUG%29#How\\_to\\_Use\\_the\\_.40CloneCopyPolicy\\_Annotation](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#How_to_Use_the_.40CloneCopyPolicy_Annotation)

## @CompositeMember

Use @CompositeMember to indicate that a class belongs to a composite persistence unit.

It should be used if target type is a primitive type and @CollectionTable designates the table that belongs to composite member persistence unit other than the source composite member persistence unit. This allows the source and target to be mapped to different databases.

### Annotation Elements

Table 2–12 describes this annotation's elements.

**Table 2–12 @CompositeMember Annotation Elements**

Annotation Element	Description	Default
value	The name of a target composite member persistence unit to which element table belongs (if differs from source composite member persistence unit).	

### Usage

The @CompositeMember annotation is ignored unless it is in a composite member persistence unit. It may be used in conjunction with @ElementCollection and @CollectionTable annotations.

### Examples

You can configure the CompositeMember using annotations or the eclipselink-orm.xml file, as shown in these examples.

#### **Example 2–27 Using @CompositeMember Annotation**

```
@ElementCollection()
@CollectionTable(name = "MBR1_RESPONS", joinColumns=@JoinColumn(name="EMP_ID"))
@CompositeMember("branch-database")
@Column(name = "DESCRIPTION")
public Collection<String> getResponsibilities() {
    return responsibilities;
}
```

#### **Example 2–28 Using <composite-member> XML**

```
<element-collection name="responsibilities" composite-member="branch-database">
  <column name="DESCRIPTION"/>
  <collection-table name="XML_MBR3_RESPONS">
    <join-column name="EMP_ID"/>
  </collection-table>
</element-collection>
```

### See Also

For more information, see:

- ["composite-unit" on page -50](#)
- ["composite-unit.member" on page -52](#)

- "Composite Persistence Units"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Composite\\_Persistence\\_Units](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Composite_Persistence_Units)

## @ConversionValue

Use `@ConversionValue` to specify the database and object values for an `ObjectTypeConverter`.

### Annotation Elements

[Table 2–13](#) describes this annotation's elements.

**Table 2–13 @ConversionValue Annotation Elements**

Annotation Element	Description	Default
<code>dataValue</code>	(Required) The database value.	
<code>objectValue</code>	(Required) The object value	

### Usage

The JPA specification allows you to map an `Enum` to database columns using the `@Enumerated` annotation, when the database value is either the name of the `Enum` or its ordinal value. With EclipseLink, you can also map an `Enum` to a coded value, using a converter.

### Examples

In [Example 2–29](#), the enum `Gender` (`MALE`, `FEMALE`) is mapped to a single character in the database where `M=MALE` and `F=FEMALE`.

#### Example 2–29 Using @ConversionValue Annotation

```
@ObjectTypeConverter(name = "gender", objectType = Gender.class, dataType =
String.class, conversionValues = {
    @ConversionValue(objectValue = "Male", dataValue = "M"),
    @ConversionValue(objectValue = "Female", dataValue = "F") })

...

@Basic
@Convert("gender")
private Gender gender = Gender.Male;
```

[Example 2–30](#) illustrates the same function using XML.

#### Example 2–30 Using <conversion-value> XML

```
<object-type-converter name="gender" object-type="model.Gender
"data-type="java.lang.String">
  <conversion-value object-value="Male" data-value="M" />
  <conversion-value object-value="Female" data-value="F" />
</object-type-converter>

...

<basic name="gender">
  <column name="GENDER" />
  <convert>gender</convert>
</basic>
```

## See Also

For more information, see:

- ["@ObjectTypeConverter"](#) on page -112

## @Convert

Use `@Convert` to specify that a named converter should be used with the corresponding mapped attribute.

### Annotation Elements

[Table 2–14](#) describes this annotation's elements.

**Table 2–14** *@Convert Annotation Elements*

Annotation Element	Description	Default
value	(Optional) The String name for your converter	none

### Usage

The `@Convert` has the following reserved names:

- **serialized** – Places the `org.eclipse.persistence.mappings.converters.SerializedObjectConverter` on the associated mapping.
- **class-instance** – Uses an `ClassInstanceConverter` on the associated mapping. When using a `ClassInstanceConverter`, the database representation is a `String` representing the Class name and the object-model representation is an instance of that class built with a no-args constructor
- **none** – Does not place a converter on the associated mapping.

### Examples

[Example 2–31](#) shows how to use the `@Convert` annotation to define the gender field.

**Example 2–31** *Using the @Convert Annotation*

```
@Entity
@Table(name="EMPLOYEE")
@Converter(
    name="genderConverter",
    converterClass=org.myorg.converters.GenderConverter.class
)
public class Employee implements Serializable{
    ...
    @Basic
    @Convert("genderConverter")
    public String getGender() {
        return gender;
    }
    ...
}
```

### See Also

For more information, see:

- ["@Converter"](#) on page -42



- ["@ObjectTypeConverter"](#) on page -112
- ["@TypeConverter"](#) on page -186

## @Converter

Use the `@Converter` annotation to specify a custom converter for modification of the data value(s) during the reading and writing of a mapped attribute.

### Annotation Elements

[Table 2–15](#) describes this annotation's elements.

**Table 2–15** @Converter Annotation Elements

Annotation Element	Description	Default
name	The String name for your converter, must be unique across the persistence unit	none
converterClass	The class of your converter. This class must implement the <code>org.eclipse.persistence.mappings.converters.Converter</code> interface.	none

### Usage

Use `@Converter` to define a named converter that can be used with mappings. A converter can be defined on an entity class, method, or field. Specify a converter with the [@Convert](#) annotation on a Basic or ElementCollection mapping.

#### Using non-JPA Converter Annotations

EclipseLink provides a set of non-JPA converter annotations (in addition to the JPA default type mappings):

- `@Converter`
- [@TypeConverter](#)
- [@ObjectTypeConverter](#)
- [@StructConverter](#)
- [@Convert](#)

The persistence provider searches the converter annotations in the following order:

1. `@Convert`
2. `@Enumerated`
3. `@Lob`
4. `@Temporal`
5. Serialized (automatic)

Specify the converters on the following classes:

- `@Entity`
- `@MappedSuperclass`
- `@Embeddable`

Use the converters with the following mappings:

- `@Basic`
- `@Id`

- @Version
- @ElementCollection

An exception is thrown if a converter is specified with any other type of mapping annotation.

## Examples

[Example 2-32](#) shows how to use the @Converter annotation to specify a converter class for the gender field.

### **Example 2-32 Using the @Converter Annotation**

```
@Entity
public class Employee implements Serializable{
    ...
    @Basic
    @Converter (
        name="genderConverter",
        converterClass=org.myorg.converters.GenderConverter.class
    )
    @Convert("genderConverter")
    public String getGender() {
        return gender;
    }
    ...
}
```

[Example 2-33](#) shows how to use the <converter> element in the eclipselink-orm.xml file.

### **Example 2-33 Using <converter> XML**

```
<entity class="Employee">
    ...
    <attributes>
        ...
        <basic name="gender">
            <convert>genderConverter</convert>
            <converter name="genderConverter"
class="org.myorg.converters.GenderConverter"/>
        </basic>
        ...
    </attributes>
</entity>
```

## See Also

For more information, see:

- ["@Converters"](#) on page -44
- ["@Convert"](#) on page -40
- ["@MapKeyConvert"](#) on page -80

---

## @Converters

Use `@Converters` annotation to define multiple `@Converter` elements.

### Annotation Elements

[Table 2–16](#) describes this annotation's elements.

**Table 2–16** *@Converters Annotation Elements*

Annotation Element	Description	Default
<code>Converter[]</code>	(Required) An array of converters	

### Examples

See "[@Converter](#)" on page -42 for an example of this annotation.

### See Also

For more information, see:

- "[@Converter](#)" on page -42



## @CopyPolicy

Use @CopyPolicy to set an `org.eclipse.persistence.descriptors.copying.CopyPolicy` on an entity to produce a copy of the persistent element.

### Annotation Elements

[Table 2–17](#) describes this annotation's elements.

**Table 2–17 @CopyPolicy Annotation Elements**

Annotation Element	Description	Default
<code>java.lang.Class</code>	(Required) The class of the copy policy. The class must implement <code>org.eclipse.persistence.descriptors.copying.CopyPolicy</code> .	

### Usage

You can specify @CopyPolicy on an Entity, MappedSuperclass, or Embeddable class.

### Examples

[Example 2–34](#) shows how to use this annotation.

**Example 2–34 Using @CopyPolicy Annotation**

```
@Entity
@Table(name="EMPLOYEE")
@CopyPolicy(mypackage.MyCopyPolicy.class)
public class Employee implements Serializable {
    ...
}
```

[Example 2–35](#) shows how to use the <copy-policy> element in the eclipselink-orm.xml file.

**Example 2–35 Using <copy-policy> XML**

```
<entity class="Employee">
  <table name="EMPLOYEE"/>
  <copy-policy class="mypackage.MyCopyPolicy"/>
  ...
</entity>
```

### See Also

For more information, see:

- ["@CloneCopyPolicy"](#) on page -34
- ["@InstantiationCopyPolicy"](#) on page -72



## @Customizer

Use `@Customizer` to specify a class that implements `org.eclipse.persistence.config.DescriptorCustomizer` and is to run against an entity's class descriptor after all metadata processing has been completed.

### Annotation Elements

[Table 2–18](#) describes this annotation's elements.

**Table 2–18** *@Customizer Annotation Elements*

Annotation Element	Description	Default
<code>java.lang.Class</code>	(Required) The name of the descriptor customizer to apply to the entity's descriptor.	

### Usage

Use this annotation to customize or extend the mapping metadata through the EclipseLink native API. With `@Customizer`, you can access additional EclipseLink functionality and configurations.

You can specify `@Customizer` on an Entity, MappedSuperclass, or Embeddable class.

---

---

**Note:** A `@Customizer` is not inherited from its parent classes.

---

---

### Examples

[Example 2–36](#) show how to use this annotation.

#### **Example 2–36** *Using @Customizer Annotation*

```
@Entity
@Table(name="EMPLOYEE")
@Customizer(mypackage.MyCustomizer.class)
public class Employee implements Serializable {
    ...
}
```

[Example 2–37](#) show how to use the `<customizer>` element in the `eclipselink-orm.xml` file.

#### **Example 2–37** *Using <customizer> XML*

```
<entity class="Employee">
  <table name="EMPLOYEE"/>
  <customizer class="mypackage.MyCustomizer"/>
  ...
</entity>
```

### See Also

For more information, see:



- "How to Use the @Customizer Class"  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_%28ELUG%29#How\\_to\\_Use\\_the\\_.40Customizer\\_Annotation](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#How_to_Use_the_.40Customizer_Annotation)
- EclipseLink Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/MappingSelectionCriteria>
- "Customizers"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Customizers](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Customizers)

---

## @DeleteAll

Use `@DeleteAll` to indicate that when an relationship is deleted, EclipseLink should use a delete all query. This typically happens if the relationship is `PrivateOwned` and its owner is deleted. In that case, the members of the relationship will be deleted without reading them in.

### Annotation Elements

There are no elements for this annotation.

### Usage

---

---

**WARNING:** Use this annotation with caution. EclipseLink will not validate whether the target entity is mapped in such a way as to allow the delete all to work.

---

---

### Examples

[Example 2-38](#) shows how to use `@DeleteAll` on a relationship mapping.

#### *Example 2-38 Using @DeleteAll Annotation*

```
@Entity
public class Department {
    ...
    @OneToMany(mappedBy = "department")
    @PrivateOwned
    @DeleteAll
    public List<Equipment> getEquipment() {
        return equipment;
    }
    ...
}
```

[Example 2-38](#) shows how to use the `<delete-all>` element in the `eclipselink-orm.xml` file.

#### *Example 2-39 Using <delete-all> XML*

```
<entity class="Department">
    ...
    <attributes>
        <one-to-many name="equipment" target-entity="Equipment"
mapped-by="department">
            <private-owned/>
            <delete-all/>
        </one-to-many>
    ...
</attributes>
```

</entity>

## See Also

For more information, see:

- ["@PrivateOwned"](#) on page -138

---

## @DiscriminatorClass

Use @DiscriminatorClass with a @VariableOneToOne annotation to determine which entities will be added to the list of types for the mapping.

### Annotation Elements

[Table 2–19](#) describes this annotation's elements.

**Table 2–19** @DiscriminatorClass Annotation Elements

Annotation Element	Description	Default
discriminator	(Required) The discriminator to be stored in the database.	
value	(Required) The class to be instantiated with the discriminator.	

### Usage

The @DiscriminatorClass annotation can be specified only within a [@VariableOneToOne](#) mapping.

### Examples

See "[@VariableOneToOne](#)" on page -198 for an example of a variable one-to-one mapping with @DiscriminatorClass.

### See Also

For more information, see:

- "[@VariableOneToOne](#)" on page -198



---

## @ExcludeDefaultMappings

Use @ExcludeDefaultMappings to specify that no default mapping should be added to a specific class. Instead, EclipseLink will use only mappings that are explicitly defined by annotations or the XML mapping file.

### Annotation Elements

There are no elements for this annotation.

### Usage

You can specify @ExcludeDefaultMappings on an Entity, MappedSuperclass, or Embeddable class.

### Examples

[Example 2–40](#) shows how to use the @ExcludeDefaultMapping annotation.

#### ***Example 2–40 Using the @ExcludeDefaultMappings Annotation***

```
@ExcludeDefaultMappings
@Entity
public class Dealer {
    @Id
    private long id;
    @Basic
    private String name;
    // These would be ignored
    private List<Card> deck;
    private List<Card> hand;
    ...
}
```

### See Also

For more information, see:



## @ExistenceChecking

Use `@ExistenceChecking` to specify how EclipseLink should check to determine if an entity is new or exists.

On `merge()` operations, use `@ExistenceChecking` to specify if EclipseLink uses only the cache to determine if an object exists, or if the object should be read (from the database or cache). By default the object will be read from the database.

### Annotation Elements

[Table 2–20](#) describes this annotation's elements.

**Table 2–20** *@ExistenceChecking Annotation Elements*

Annotation Element	Description	Default
ExistenceType	(Optional) Set the existence checking type: <ul style="list-style-type: none"><li>■ ASSUME_EXISTENCE</li><li>■ ASSUME_NON_EXISTENCE</li><li>■ CHECK_CACHE</li><li>■ CHECK_DATABASE</li></ul>	CHECK_CACHE

### Usage

You can specify `@ExistenceChecking` on an Entity or MappedSuperclass.

EclipseLink supports the following existence checking types:

- ASSUME\_EXISTENCE – If the object's primary key does not include null then it must exist. You may use this option if the application guarantees or does not care about the existence check.
- ASSUME\_NON\_EXISTENCE – Assume that the object does not exist. You may use this option if the application guarantees or does not care about the existence check. This will always force an INSERT operation.
- CHECK\_CACHE – If the object's primary key does not include null and it is in the cache, then it must exist.
- CHECK\_DATABASE – Perform a SELECT on the database.

### Examples

[Example 2–41](#) shows how to use this annotation.

**Example 2–41** *Using @ExistenceChecking Annotation*

```
@Entity
@Cache(type=CacheType.HARD_WEAK, expiryTimeOfDay=@TimeOfDay(hour=1))
@ExistenceChecking(ExistenceType.CHECK_DATABASE)
public class Employee implements Serializable {
    ...
}
```



## See Also

For more information, see:

- ["@Cache"](#) on page -16

## @FetchAttribute

Use `@FetchAttribute` to improve performance within a fetch group; it allows on-demand loading of a group of an object's attributes. As a result, the data for an attribute might not be loaded from the datasource until an explicit access call occurs.

This avoids loading all the data of an object's attributes if the user requires only some of the attributes.

### Annotation Elements

[Table 2–21](#) describes this annotation's elements.

**Table 2–21** *@FetchAttribute Annotation Elements*

Annotation Element	Description	Default
name	(Required) Name of the fetch attribute.	

### Usage

EclipseLink provides two types of fetch groups:

- Pre-defined fetch groups at the Entity or MappedSuperclass level
- Dynamic (use case) fetch groups at the query level

You should extensively review your use cases when using fetch groups. In many cases, additional round-trips will offset any gains from deferred loading.

### Examples

[Example 2–42](#) shows how to use `@FetchAttribute` within a `@FetchGroup` annotation.

**Example 2–42** *Using @FetchAttribute Annotation*

```
@Entity
@FetchGroup(name="basic-fetch-group", attributes={
    @FetchAttribute(name="id"),
    @FetchAttribute(name="name"),
    @FetchAttribute(name="address")})
public class Person {

    @Id
    private int id;

    private String name;

    @OneToOne(fetch=LAZY)
    private Address address;

    @ManyToOne(fetch=EAGER)
    private ContactInfo contactInfo;
```

**Example 2–43** *Using <fetch-group> XML*

```
<fetch-group name="basic-fetch-group">
  <attribute name="id"/>
```

```
<attribute name="name"/>
<attribute name="address"/>
</fetch-group>
```

## See Also

For more information, see:

- ["@FetchGroup"](#) on page -60

## @FetchGroup

Use `@FetchGroup` to load a group of attributes on demand, as needed.

This avoids wasteful practice of loading all data of the object's attributes, if which the user is interested in only partial of them. However, it also means that the data for an attribute might not loaded from the underlying data source until an explicit access call for the attribute first occurs.

### Annotation Elements

[Table 2–22](#) describes this annotation's elements.

**Table 2–22 @FetchGroup Annotation Elements**

Annotation Element	Description	Default
<code>FetchAttribute[] attributes</code>	(Required) The list of attributes to fetch.	none
<code>java.lang.String name</code>	(Required) The fetch group name.	none
<code>boolean load</code>	(Optional) Indicates whether all relationship attributes specified in the fetch group should be loaded.	false

### Usage

You should perform a careful use case analysis when using `@FetchGroup`; any gains realized from the deferred loading could be offset by the extra round-trip.

EclipseLink supports fetch groups at two levels:

- Pre-defined fetch groups at the Entity or MappedSuperclass level
- Dynamic (use case) fetch groups at the query level

You can use fetch groups only when using weaving or when individual classes that define them explicitly implement the

`org.eclipse.persistence.queries.FetchGroupTracker` interface.

When using a fetch group, you can define a subset of an object's attributes and associate the fetch group with a query. When you execute the query, EclipseLink retrieves only the attributes in the fetch group. EclipseLink automatically executes a query to fetch all the attributes excluded from this subset when and if you call a get method on any one of the excluded attributes.

You can define more than one fetch group for a class. You can optionally designate at most one such fetch group as the default fetch group. If you execute a query without specifying a fetch group, EclipseLink will use the default fetch group, unless you configure the query otherwise.

Before using fetch groups, we recommend that you perform a careful analysis of system use. In many cases, the extra queries required to load attributes not in the fetch group could well offset the gain from the partial attribute loading.

### Examples

[Example 2–44](#) show how to use this annotation.

#### **Example 2–44 Using @FetchGroup Annotation**

```
@FetchGroup(name="names", attributes={
    @FetchAttribute(name="firstName"),
```

```
@FetchAttribute(name="lastName"))
```

[Example 2-44](#) show how to use this feature in the eclipselink-orm.xml file.

**Example 2-45 Using <fetch-group> XML**

```
<entity class="model.Employee">
  <secondary-table name="SALARY" />
  <fetch-group name="names">
    <attribute name="firstName" />
    <attribute name="lastName" />
  </fetch-group>
...

```

You can also use a named fetch group with a query, as shown in [Example 2-46](#).

**Example 2-46 Using a Named Fetch Group on a Query**

```
TypedQuery query = em.createQuery("SELECT e FROM Employee e", Employee.class);

query.setHint(QueryHints.FETCH_GROUP_NAME, "names");
```

## See Also

For more information, see:

- ["@FetchAttribute"](#) on page -58
- ["@FetchGroups"](#) on page -62

## @FetchGroups

Use @FetchGroups to define a group of @FetchGroup.

### Annotation Elements

[Table 2–23](#) describes this annotation's elements.

**Table 2–23** @FetchGroups Annotation Elements

Annotation Element	Description	Default
FetchGroup	(Required) An array of fetch groups (@FetchGroup)	

### Usage

You can specify @FetchGroups on an Entity or MappedSuperclass.

You can also enable or disable fetch groups through weaving for the persistence unit.

### Examples

See "[@FetchGroup](#)" on page -60 for an example of using fetch groups.

[Example 2–47](#) shows how to configure fetch groups in the persistence unit persistence.xml file or by importing a property map.

#### **Example 2–47** Specifying Fetch Groups in persistence.xml

Using persistence.xml file:

```
<property name="eclipselink.weaving.fetchgroups" value="false"/>
```

Using property map:

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.WEAVING_FETCHGROUPS, "false");
```

### See Also

For more information, see:

- "[@FetchGroup](#)" on page -60
- "[@FetchAttribute](#)" on page -58
- "Using EclipseLink JPA Weaving"  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_%28ELUG%29#Using\\_EclipseLink\\_JPA\\_Weaving](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#Using_EclipseLink_JPA_Weaving)



---

## @Field

Use `@Field` to define a structured data type's field name for an object mapped to NoSql data.

### Annotation Elements

[Table 2–24](#) describes this annotation's elements.

**Table 2–24** *@Field Annotation Elements*

Annotation Element	Description	Default
name	(Optional) The data type's name of the field.	

### Usage

The `@Field` annotation is a generic form of the `@Column` annotation, which is not specific to relational databases. You can use `@Field` to map EIS and NoSQL data.

### Examples

See "[@NoSql](#)" on page -108 for an example of the `@Field` annotation.

### See Also

For more information, see:

- "[@NoSql](#)" on page -108





## @HashPartitioning

Use @HashPartitioning to partition access to a database cluster by the hash of a field value from the object (such as the object's location or tenant). The hash indexes into the list of connection pools.

### Annotation Elements

Table 2–25 describes this annotation's elements.

**Table 2–25 @HashPartitioning Annotation Elements**

Annotation Element	Description	Default
name	(Required) The name of the partition policy. The name must be unique within the persistence unit.	
partitionColumn	(Required) The database column or query parameter by which to partition queries.	
connectionPools	(Optional) List of connection pool names across which to partition.	All defined pools in the ServerSession
unionUnpartitionableQueries	(Optional) Specify if queries that <i>do not</i> contain the partition hash should be sent to every database and union the result.	False

### Usage

All write or read requests for objects with the hash value are sent to the server. Queries that do not include the field as a parameter will be:

- Sent to all servers and unioned
- or
- Handled based on the session's default behavior.

You can enable partitioning on an Entity, relationship, query, or session/persistence unit. Partition policies are globally named (to allow reuse) and must set using the @Partitioned annotation.

The persistence unit properties support adding named connection pools in addition to the existing configuration for read/write/sequence. A named connection pool must be defined for each node in the database cluster.

If a transaction modifies data from multiple partitions, you should use JTA to ensure proper two-phase commit of the data. You can also configure an exclusive connection in the EntityManager to ensure that only a single node is used for a single transaction.

### Examples

See "[@Partitioned](#)" on page -120 for an example of partitioning with EclipseLink.

### See Also

For more information, see:

- "Data Partitioning"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Data\\_Partitioning](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Data_Partitioning)

- ["@Partitioned"](#) on page -120

## @Index

An index is a database structure defined for a table, to improve query and look-up performance for a set of columns. Use the `@Index` annotation in code or the `<index>` element in the `eclipselink-orm.xml` descriptor to create an index on a table.

An index can be defined on an entity or on an attribute. For the entity it must define a set of columns to index.

Index creation is database specific. Some databases may not support indexes. Most databases auto-index primary key and foreign key columns. Some databases support advanced index DDL options. To create more advanced index DDL, a DDL script or native query can be used.

### Annotation Elements

Table 2–26 describes this annotation's elements.

**Table 2–26 @Index Annotation Elements**

Annotation Element	Description	Default
<code>java.lang.String catalog</code>	(Optional) The catalog of the INDEX.	Default catalog
<code>java.lang.String[] columnNames</code>	(Not required when annotated on a field or method) Specify the set of columns to define the index on.	For an Entity, none. For an attribute, the attribute's column.
<code>java.lang.String name</code>	(Optional) The name of the INDEX.	<code>&lt;table&gt;_&lt;column&gt;_INDEX</code> (but a name should be provided)
<code>java.lang.String schema</code>	(Optional) The schema of the INDEX.	Default schema
<code>java.lang.String table</code>	(Optional) The table to define the index on; defaults to entities primary table.	The entity's primary table.
<code>boolean unique</code>	(Optional) Specify whether the index is unique or non-unique.	false

### Usage

Use `@Index` annotation to index any attributes or columns that will commonly be used in queries.

### Examples

This example defines three indexes, one on **first name**, one on **last name**, and a multiple column index on **first name** and **last name**.

**Example 2–48 Using @Index Annotation**

```
@Entity
@Index(name="EMP_NAME_INDEX", columns={"F_NAME", "L_NAME"})
public class Employee{
    @Id
    private long id;
    @Index
    @Column(name="F_NAME")
    private String firstName;
    @Index
    @Column(name="L_NAME")
```

```
        private String lastName;  
        ...  
    }
```

You can also create an index in the `eclipselink-orm.xml` descriptor using `<index>`, as shown in the following example. Define columns using the `<column>` subelement. All the attributes supported in the `@Index` annotation are also supported in the `<index>` element.

**Example 2-49 Using `<index>` XML**

```
<index name="EMP_NAME_INDEX" table="EMPLOYEE" unique="true">  
    <column>F_NAME</column>  
    <column>L_NAME</column>  
</index>
```

## See Also

For more information see:

- ["@Indexes"](#) on page -70

---

## @Indexes

Use `@Indexes` to define a set of database indexes for an Entity.

### Annotation Elements

[Table 2–27](#) describes this annotation's elements.

**Table 2–27** *@Indexes Annotation Elements*

Annotation Element	Description	Default
<code>Index[]</code>	An array of database indexes	

### Examples

See "[@Index](#)" on page -68 for an example of using the `@Index` annotation.

### See Also

For more information see:

- "[@CopyPolicy](#)" on page -46
- "[@CloneCopyPolicy](#)" on page -34
- "[@Index](#)" on page -68



---

## @InstantiationCopyPolicy

Use @InstantiationCopyPolicy to set an `org.eclipse.persistence.descriptors.copyping.InstantiationCopyPolicy` on an Entity.

Because `InstantiationCopyPolicy` is the default EclipseLink copy policy, this annotation needed only to override other types of copy policies.

### Annotation Elements

[Table 2–28](#) describes this annotation's elements.

**Table 2–28** @InstantiationCopyPolicy Annotation Elements

Annotation Element	Description	Default

### Usage

You can specify @InstantiationCopyPolicy on an Entity, MappedSuperclass, or Embeddable entity.

Instantiation is the default copy policy in EclipseLink.

### Examples

**Example 2–50** Using @InstantiationCopyPolicy Annotation

**Example 2–51** Using <instantiation-copy-policy> XML

### See Also

For more information, see:

- ["@CopyPolicy"](#) on page -46
- ["@CloneCopyPolicy"](#) on page -34
- "How to Use the @InstantiationCopyPolicy Annotation"  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_  
%28ELUG%29#How\\_to\\_Use\\_the\\_.40InstantiationCopyPolicy\\_Annotation](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#How_to_Use_the_.40InstantiationCopyPolicy_Annotation)





## @JoinFetch

Use the `@JoinFetch` annotation to enable the joining and reading of the related objects in the same query as the source object.

---

**Note:** You should set join fetching at the query level, as not all queries require joining.

---

### Annotation Elements

[Table 2–29](#) describes this annotation's elements.

**Table 2–29** *@JoinFetch Annotation Elements*

Annotation Element	Description	Default
value	<p>(Optional) Set this attribute to the <code>org.eclipse.persistence.annotations.JoinFetchType</code> enumerated type of the fetch that you will be using.</p> <p>The following are the valid values for the <code>JoinFetchType</code>:</p> <ul style="list-style-type: none"><li>■ <code>INNER</code>—This option provides the inner join fetching of the related object.</li></ul> <p><b>Note:</b> Inner joining does not allow for null or empty values.</p> <ul style="list-style-type: none"><li>■ <code>OUTER</code>—This option provides the outer join fetching of the related object.</li></ul> <p><b>Note:</b> Outer joining allows for null or empty values.</p>	<code>JoinFetchType.INNER</code>

### Usage

You can specify the `@JoinFetch` annotation for the following mappings:

- `@OneToOne`
- `@OneToMany`
- `@ManyToOne`
- `@ManyToMany`
- `@BasicCollection` (deprecated)
- `@BasicMap` (deprecated)

Alternatively, you can use batch reading, especially for collection relationships.

### Examples

The following example shows how to use the `@JoinFetch` annotation to specify Employee field `managedEmployees`.

**Example 2–52** *Using @JoinFetch Annotation*

```
@Entity
public class Employee implements Serializable {
    ...
    @OneToMany(cascade=ALL, mappedBy="owner")
    @JoinFetch(value=OUTER)
    public Collection<Employee> getManagedEmployees() {
```

```
        return managedEmployees;  
    }  
    ...  
}
```

## See Also

For more information, see:

- ["@BatchFetch"](#) on page -14

---

## @JoinField

Use `@JoinField` to define a structured data type's foreign key field for an object mapped to NoSql data.

### Annotation Elements

[Table 2–30](#) describes this annotation's elements.

**Table 2–30** *@JoinField Annotation Elements*

Annotation Element	Description	Default
<code>name</code>	(Optional) The name of the foreign key /ID reference field in the source record.	
<code>referencedFieldName</code>	(Optional) The name of the ID field in the target record.	

### Usage

The `@JoinField` annotation is a generic form of the `@JoinColumn` annotation, which is not specific to relational databases. You can use `@JoinField` to map EIS and NoSQL data.

### Examples

### See Also

For more information, see:

- "Mappings"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/NoSQL/Mappings](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/NoSQL/Mappings)
- "[@JoinFields](#)" on page -78



---

## @JoinFields

Use `@JoinFields` to define a set of `@JoinField` annotations on a relationship.

### Annotation Elements

[Table 2–31](#) describes this annotation's elements.

**Table 2–31** *@JoinFields Annotation Elements*

Annotation Element	Description	Default
<code>JoinField[]</code>	An array of join fields	

### Examples

See "[@JoinField](#)" on page -76 for an example of using the `@Index` annotation.

### See Also

For more information, see:

- "[@JoinField](#)" on page -76



## @MapKeyConvert

Use `@MapKeyConvert` to specify a named converter to be used with the corresponding mapped attribute key column.

### Annotation Elements

[Table 2–32](#) describes this annotation's elements.

**Table 2–32** *@MapKeyConvert Annotation Elements*

Annotation Element	Description	Default
value	(Optional) Name of the converter to use: <ul style="list-style-type: none"><li>■ <code>serialized</code></li><li>■ <code>class-instance</code></li><li>■ <code>none</code></li><li>■ <code>custom converter</code></li></ul>	<code>none</code>

### Usage

The `@MapKeyConvert` annotation has the following reserved names:

- `serialized`: Will use a `SerializedObjectConverter` on the associated mapping. When using a `SerializedObjectConverter` the database representation is a binary field holding a serialized version of the object and the object-model representation is the actual object
- `class-instance`: Will use an `ClassInstanceConverter` on the associated mapping. When using a `ClassInstanceConverter` the database representation is a `String` representing the Class name and the object-model representation is an instance of that class built with a no-args constructor
- `none` - Will place no converter on the associated mapping. This can be used to override a situation where either another converter is defaulted or another converter is set.

If you do not use one of these reserved names, you must define a custom converter, using the `@Converter` annotation.

### Examples

[Example 2–53](#) shows using a `@MapKeyConvert` annotation to apply a converter to a map's key.

#### **Example 2–53** *Using @MapKeyConvert Annotation*

```
@Entity
public class Entity
...
    @ElementCollection
    @MapKeyColumn(name="BANK")
    @Column(name="ACCOUNT")
    @Convert("Long2String")
    @MapKeyConvert("CreditLine")
    public Map getCreditLines() {
        return creditLines;
    }
```



[Example 2-54](#) shows how to use the `<map-key-convert>` element in the `eclipselink-orm.xml` file.

**Example 2-54 Using `<map-key-convert>` XML**

```
<element-collection name="creditLines">
  <map-key-convert>CreditLine</map-key-convert>
  <map-key-column name="BANK"/>
  <column name="ACCOUNT"/>
  <convert>Long2String</convert>
  <object-type-converter name="CreditLine">
    <conversion-value data-value="RBC" object-value="RoyalBank"/>
    <conversion-value data-value="CIBC" object-value="CanadianImperial"/>
    <conversion-value data-value="SB" object-value="Scotiabank"/>
    <conversion-value data-value="TD" object-value="TorontoDominion"/>
  </object-type-converter>
  <type-converter name="Long2String" data-type="String" object-type="Long"/>
  <collection-table name="EMP_CREDITLINES">
    <join-column name="EMP_ID"/>
  </collection-table>
</element-collection>
```

## See Also

For more information, see:

- ["@Converter"](#) on page -42
- ["@Convert"](#) on page -40

---

## @Multitenant

The `@Multitenant` annotation specifies that a given entity is shared among multiple tenants of an application. The multitenant type specifies how the data for these entities are to be stored on the database for each tenant. Multitenancy can be specified at the entity or mapped superclass level.

### Annotation Elements

[Table 2–33](#) describes this annotation’s elements.

**Table 2–33** *@Multitenant Annotation Elements*

Annotation Element	Description	Default
boolean <code>IncludeCriteria</code>	Indicates if the database requires the tenant criteria to be added to the <code>SELECT</code> , <code>UPDATE</code> , and <code>DELETE</code> queries.	<code>true</code>
<code>MultitenantType</code> value	Specifies the multitenant strategy to use: <code>SINGLE_TABLE</code> , <code>TABLE_PER_TENANT</code> , or <code>VDP</code> .	<code>SINGLE_TABLE</code>

### Usage

To use the `@Multitenant` annotation, include the annotation with an `@Entity` or `@MappedSuperclass` annotation. For example:

```
@Entity
@Multitenant
...
public class Employee() {
    ...
}
```

Three types of multitenancy are available:

- [Single-Table Multitenancy](#)
- [Table-Per-Tenanat Multitenancy](#)
- [VDP Multitenancy](#)

## Single-Table Multitenancy

The `SINGLE_TABLE` multitenant type specifies that any table to which an entity or mapped superclass maps can include rows for multiple tenants. Access to tenant-specific rows is restricted to the tenant.

Tenant-specific rows are associated with the tenant by using tenant discriminator columns. The discriminator columns are used with application context values to limit what a persistence context can access.

The results of queries on the mapped tables are limited to the tenant discriminator value(s) provided as property values. This applies to all insert, update, and delete operations on the table. When multitenant metadata is applied at the mapped superclass level, it is applied to all subentities unless they specify their own multitenant metadata.

---

**Note:** In the context of single-table multitenancy, “single-table” means multiple tenants can share a single table, and each tenant’s data is distinguished from other tenants’ data via the discriminator column(s). It is possible to use multiple tables with single-table multitenancy; but in that case, an entity’s persisted data is stored in multiple tables (Table and SecondaryTable), and multiple tenants can share all the tables.

---

For more information how to use tenant discriminator columns to configure single-table multitenancy, see “[@TenantDiscriminatorColumn](#)” on page 172.

## Examples

The following example uses `@Multitenant`, `@TenantDiscriminatorColumn`, and a context property to define single-table multitenancy on an entity:

### **Example 2-55 Example Using @Multitenant**

```
@Entity
@Table(name="EMP")
@Multitenant(SINGLE_TABLE)
@TenantDiscriminatorColumn(name = "TENANT_ID",
    contextProperty = "employee-tenant.id")
```

The following example uses the `<multitenant>` element to specify a minimal single-table multitenancy. `SINGLE_TABLE` is the default value and therefore does not have to be specified.

### **Example 2-56 Example Using <multitenant>**

```
<entity class="model.Employee">
  <multitenant/>
  <table name="EMP"/>
  ...
</entity>
```

## Table-Per-Tenant Multitenancy

The `TABLE_PER_TENANT` multitenant type specifies that the table(s) (Table and SecondaryTable) for an entity are tenant-specific tables based on the tenant context.. Access to these tables is restricted to the specified tenant. Relationships within an entity that use a join or collection table are also assumed to exist within that context.

As with other multitenant types, table-per-tenant multitenancy can be specified at the entity or mapped superclass level. At the entity level, a tenant context property must be provided on each entity manager after a transaction has started.

Table-per-tenant entities can be mixed with other multitenant-type entities within the same persistence unit.

All read, insert, update, and delete operations for the tenant apply only to the tenant's table(s).

Tenants share the same server session by default. The table-per-tenant identifier must be set or updated for each entity manager. ID generation is assumed to be unique across all the tenants in a table-per-tenant strategy.

To configure table-per-tenant multitenancy, you must specify:

- A table-per-tenant property to identify the user. This can be set per entity manager, or it can be set at the entity manager factory to isolate table-per-tenant per persistence unit.)
- A tenant table discriminator to identify and isolate the tenant's tables from other tenants' tables. The discriminator types are `SCHEMA`, `SUFFIX`, and `PREFIX`. For more information about tenant discriminator types, see "[@TenantTableDiscriminator](#)" on page -180

.

## Examples

The following example shows the `@Multitenant` annotation used to define table-per-tenant multitenancy on an entity. `@TenantTableDiscriminator(SCHEMA)` specifies that the discriminator table is identified by schema.

### **Example 2-57 Example Using @Multitenant with @TenantTableDiscriminator**

```
@Entity
@Table(name="EMP")
@Multitenant(TABLE_PER_TENANT)
@TenantTableDiscriminator(SCHEMA)
public class Employee {
    ...
}
```

The following example shows the `<multitenant>` element and the `<tenant-table-discriminator>` elements used to define a minimal table-per-tenant multitenancy.

### **Example 2-58 Example Using <multitenant> with <tenant-table-discriminator>**

```
<entity class="Employee">
  <multitenant type="TABLE_PER_TENANT">
    <tenant-table-discriminator type="SCHEMA"/>
  </multitenant>
  <table name="EMP">
```

...  
</entity>

## VDP Multitenancy

The VPD (Virtual Private Database) multitenancy type specifies that the database handles the tenant filtering on all SELECT, UPDATE and DELETE queries. To use this type, the platform used with the persistence unit must support VPD.

To use EclipseLink VPD multitenancy, you must first configure VPD in the database and then specify multitenancy on the entity or mapped superclass, using `@Multitenant` and `@TenantDiscriminatorColumn`:

### Examples

[Example 2-59](#) shows VPD multitenancy defined on an entity. As noted above, VPD in the database must also be configured to enable VPD multitenancy. In this case, the VPD database was configured to use the `USER_ID` column to restrict access to specified rows by specified clients. Therefore, `USER_ID` is also specified as the tenant discriminator column for the EclipseLink multitenant operations.

#### **Example 2-59 Example Using @Multitenancy**

The following example shows

```
@Entity
@Multitenant(VPD)
@TenantDiscriminatorColumn(name = "USER_ID", contextProperty = "tenant.id")
@Cacheable(false)

public class Task implements Serializable {
    ...
    ...
}
```

The following example shows...

#### **Example 2-60 Example Using <multitenant>**

```
<entity class="model.Employee">
  <multitenant type="VPD">
    <tenant-discriminator-column name="USER_ID" context-property="tenant.id"/>
  </multitenant>
  <table name="EMPLOYEE"/>
  ...
</entity>
```

### See Also

- ["@TenantDiscriminatorColumn"](#) on page 172
- ["@TenantDiscriminatorColumns"](#) on page 178
- 
- Multitenant Examples at <http://wiki.eclipse.org/EclipseLink/Examples/JPA/Multitenant>



## @Mutable

Use `@Mutable` on a `@Basic` mapping to specify if the value of a complex field type can be *changed* (or not changed) instead of being *replaced*. Mutable mappings may affect the performance of change tracking; attribute change tracking can only be weaved with non-mutable mappings.

### Annotation Elements

[Table 2–34](#) describes this annotation's elements.

**Table 2–34** *@Mutable Annotation Elements*

Annotation Element	Description	Default
boolean value	(Optional) Specify if the mapping is mutable.	true

### Usage

Most basic types (such as `int`, `long`, `float`, `double`, `String`, and `BigDecimal`) are not mutable.

By default, `Date` and `Calendar` types are assumed to be not mutable. To make these types mutable, use the `@Mutable` annotation. You can also use the global persistence property `eclipselink.temporal.mutable` to set the mappings as mutable.

By default, serialized types are assumed to be mutable. You can set the `@Mutable` annotation to `false` to make these types not mutable.

You can also configure mutable mappings for `Date` and `Calendar` fields in the persistence unit in the `persistence.xml` file.

### Examples

[Example 2–61](#) shows how to use the `@Mutable` annotation to specify `Employee` field `hireDate`.

#### **Example 2–61** Using @Mutable Annotation

```
@Entity
public class Employee implements Serializable {

    ...

    @Temporal(DATE)
    @Mutable
    public Calendar getHireDate() {
        return hireDate;
    }

    ..
}
```

[Example 2–62](#) shows how to configure mutable mappings in the persistence unit `persistence.xml` file or by importing a property map.



**Example 2-62 Specifying Mutable Mappings in persistence.xml**

Using persistence.xml file:

```
<property name="eclipselink.temporal.mutable" value="true"/>
```

Using property map:

```
import org.eclipse.persistence.config.PersistenceUnitProperties;  
propertiesMap.put(PersistenceUnitProperties.TEMPORAL_MUTABLE, "false");
```

**See Also**

For more information, see:

- ["Mapping Annotations"](#) on page 2-1

## @NamedPLSQLStoredProcedureQuery

Use @NamedPLSQLStoredProcedureQuery to define queries that call Oracle PLSQL stored procedures as named queries

### Annotation Elements

Table 2–35 describes this annotation's elements.

**Table 2–35** @NamedPLSQLStoredProcedureQuery Annotation Elements

Annotation Element	Description	Default
procedureName	(Required) The name of the stored procedure.	
name	(Required) The unique name that references this stored procedure query.	
resultClass	(Optional) The class of the result.	
hints	(Optional) Query hints	
parameters	(Optional) The parameters for the stored procedure.	
resultSetMapping	(Optional) The name of the SQLResultSetMapping.	

### Usage

This annotation adds support for complex PLSQL types such as RECORD and TABLE, that are not accessible from JDBC.

You can specify @NamedPLSQLStoredProcedureQuery on an Entity or MappedSuperclass.

### Examples

Example 2–63 shows how to use this annotation.

#### **Example 2–63** Using @NamedPLSQLStoredProcedureQuery Annotation

### See Also

For more information, see:

- Oracle PL/SQL  
<http://www.oracle.com/technetwork/database/features/plsql/index.html>
- PLSQL Stored Procedure Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/PLSQLStoredFunction>



---

## @NamedPLSQLStoredFunctionQueries

Use @NamedPLSQLStoredFunctionQueries annotation to define multiple NamedPLSQLStoredFunctionQuery items.

### Annotation Elements

[Table 2–36](#) describes this annotation's elements.

**Table 2–36** @NamedPLSQLStoredFunctionQueries Annotation Elements

Annotation Element	Description	Default
NamedStoredFunctionQuery[]	(Required) An array of named stored procedure query.	

### Examples

[Example 2–64](#) shows how to use this annotation.

**Example 2–64** Using @NamedPLSQLStoredFunctionQueries Annotation

### See Also

For more information, see:

- ["@NamedPLSQLStoredFunctionQuery"](#) on page -94



## @NamedPLSQLStoredFunctionQuery

Use `@NamedPLSQLStoredFunctionQuery` to define queries that call Oracle PLSQL stored functions as named queries

### Annotation Elements

[Table 2–37](#) describes this annotation's elements.

**Table 2–37** *@NamedPLSQLStoredFunctionQuery Annotation Elements*

Annotation Element	Description	Default
<code>functionName</code>	(Required) The name of the stored function.	
<code>name</code>	(Required) The unique name that references this stored function query.	
<code>returnParamter</code>	(Required) The return value of the stored function.	
<code>hints</code>	(Optional) Query hints	
<code>parameters</code>	(Optional) The parameters for the stored function.	
<code>resultSetMapping</code>	(Optional) The name of the <code>SQLResultSetMapping</code> .	

### Usage

This annotation adds support for complex PLSQL types such as `RECORD` and `TABLE`, that are not accessible from JDBC.

You can specify `@NamedPLSQLStoredFunctionQuery` on an Entity or `MappedSuperclass`.

### Examples

[Example 2–65](#) shows how to use this annotation.

**Example 2–65** *Using @NamedPLSQLStoredFunctionQuery Annotation*

```
@NamedPLSQLStoredFunctionQuery(  
    name="getEmployee",  
    functionName="EMP_PKG.GET_EMP",  
    returnParameter=@PLSQLParameter(  
        name="RESULT",  
        databaseType="EMP_PKG.EMP_REC"  
    )  
)  
@Embeddable  
@Struct(name="EMP_TYPE", fields={"F_NAME", "L_NAME", "SALARY"})  
@PLSQLRecord(  
    name="EMP_PKG.EMP_REC",  
    compatibleType="EMP_TYPE",  
    javaType=Employee.class,  
    fields={  
        @PLSQLParameter(name="F_NAME"),  
        @PLSQLParameter(name="L_NAME"),  
        @PLSQLParameter(  
            name="SALARY",  
            databaseType="NUMERIC_TYPE"  
        )  
    }  
)  
}
```

```
public class Employee {  
    ...  
}
```

## See Also

For more information, see:

- Oracle PL/SQL  
<http://www.oracle.com/technetwork/database/features/plsql/index.html>

---

## @NamedPLSQLStoredProcedureQueries

Use @NamedPLSQLStoredProcedureQueries annotation to define multiple NamedPLSQLStoredProcedureQuery items.

### Annotation Elements

[Table 2–38](#) describes this annotation's elements.

**Table 2–38** @NamedPLSQLStoredProcedureQueries Annotation Elements

Annotation Element	Description	Default
value	(Required) An array of named stored procedure query.	

### Examples

[Example 2–66](#) shows how to use this annotation.

**Example 2–66** Using @NamedPLSQLStoredProcedureQueries Annotation

### See Also

For more information, see:

- "[@NamedPLSQLStoredProcedureQuery](#)" on page -90
- Oracle PL/SQL  
<http://www.oracle.com/technetwork/database/features/plsql/index.html>
- PLSQL Stored Procedure Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/PLSQLStoredFunction>





## @NamedStoredFunctionQueries

Use @NamedStoredFunctionQueries annotation to define multiple NamedStoredFunctionQuery items.

### Annotation Elements

[Table 2–39](#) describes this annotation's elements.

**Table 2–39** @NamedStoredFunctionQueries Annotation Elements

Annotation Element	Description	Default
NamedStoredFunctionQuery[]	(Required) An array of named stored procedure query.	

### Examples

[Example 2–67](#) shows how to use this annotation.

#### **Example 2–67 Using @NamedStoredFunctionQueries Annotation**

XML is just a list multiple named-stored-function-query elements in a row

```
@NamedStoredFunctionQueries{(  
    @NamedStoredFunctionQuery(  
        name="StoredFunction_In",  
        functionName="StoredFunction_In",  
        parameters={  
            @StoredProcedureParameter(direction=IN, name="P_IN", queryParameter="P_  
IN", type=Long.class)  
        },  
        returnParameter=@StoredProcedureParameter(queryParameter="RETURN",  
type=Long.class))  
    )}
```

To define multiple named stored procedures in the eclipselink-orm.xml file, simply create a list of multiple <named-stored-function\_query> elements.

### See Also

For more information, see:

- ["@NamedStoredFunctionQuery"](#) on page -100



## @NamedStoredFunctionQuery

Use `@NamedStoredFunctionQuery` to define queries that call stored functions as named queries.

### Annotation Elements

[Table 2–40](#) describes this annotation's elements.

**Table 2–40** *@NamedStoredFunctionQuery Annotation Elements*

Annotation Element	Description	Default
<code>functionName</code>	(Required) The name of the stored function.	
<code>name</code>	(Required) The unique name that references this stored function query.	
<code>returnParamter</code>	(Required) The return value of the stored function.	
<code>callByIndex</code>	(Optional) Specifies if the stored function should be called by <b>index</b> or by <b>name</b> . <ul style="list-style-type: none"><li>■ If by index, the parameters must be defined in the same order as the procedure on the database.</li><li>■ If by name, you must use the database platform support naming procedure parameters</li></ul>	false
<code>hints</code>	(Optional) Query hints	
<code>parameters</code>	(Optional) The parameters for the stored function.	
<code>resultSetMapping</code>	(Optional) The name of the <code>SQLResultSetMapping</code> .	

### Usage

You can specify `@NamedStoredFunctionQuery` on an Entity or `MappedSuperclass`.

### Examples

[Example 2–68](#) shows how to use this annotation.

**Example 2–68** *Using @NamedStoredFunctionQuery Annotation*

```
@Entity
@Table(name="CMP3_ADDRESS")

@NamedStoredFunctionQuery(
    name="StoredFunction_In",
    functionName="StoredFunction_In",
    parameters={
        @StoredProcedureParameter(direction=IN, name="P_IN", queryParameter="P_IN",
        type=Long.class)
    },
    returnParameter=@StoredProcedureParameter(queryParameter="RETURN",
    type=Long.class)
)
public class Address implements Serializable {
    ...
}
```

[Example 2–69](#) shows how to use the `<named-stored-function-query>` element in the `eclipselink-orm.xml` file.

**Example 2-69 Using <named-stored-function-query> XML**

```
<named-stored-function-query name="StoredFunction_In"
  procedure-name="StoredFunction_In">
  <parameter direction="IN" name="P_IN" query-parameter="P_IN" type="Long"/>
</named-stored-function-query>
```

**See Also**

For more information, see:

- ["@NamedStoredFunctionQueries"](#) on page -98

## @NamedStoredProcedureQueries

Use @NamedStoredProcedureQueries annotation to define multiple NamedStoredProcedureQuery items.

### Annotation Elements

[Table 2–41](#) describes this annotation's elements.

**Table 2–41** @NamedStoredProcedureQueries Annotation Elements

Annotation Element	Description	Default
value	(Required) An array of named stored procedure query.	

### Examples

[Example 2–70](#) shows how to use this annotation.

#### **Example 2–70** Using @NamedStoredProcedureQueries Annotation

```
@Entity
@Table(name="EMPLOYEE")
@NamedStoredProcedureQueries({
    @NamedStoredProcedureQuery(
        name="ReadEmployeeInOut",

resultClass=org.eclipse.persistence.testing.models.jpa.customfeatures.Employee.class,
        procedureName="Read_Employee_InOut",
        parameters={
            @StoredProcedureParameter(direction=IN_OUT, name="employee_id_v",
queryParameter="ID", type=Integer.class),
            @StoredProcedureParameter(direction=OUT, name="nchar_v",
queryParameter="NCHARTYPE", type=Character.class)}
    ),
    @NamedStoredProcedureQuery(
        name="ReadEmployeeCursor",

resultClass=org.eclipse.persistence.testing.models.jpa.customfeatures.Employee.class,
        procedureName="Read_Employee_Cursor",
        parameters={
            @StoredProcedureParameter(direction=IN, name="employee_id_v",
queryParameter="ID", type=Integer.class),
            @StoredProcedureParameter(direction=OUT_CURSOR, queryParameter="RESULT_
CURSOR")})
    })
})
public class Employee implements Serializable {
```

To define multiple named stored procedure queries in the eclipselink-orm.xml file, simply create a list of multiple <named-stored-procedure\_query> elements.

### See Also

For more information, see:

- ["@NamedStoredProcedureQuery"](#) on page -104

## @NamedStoredProcedureQuery

Use `@NamedStoredProcedureQuery` to define queries that call stored procedures as named queries.

### Annotation Elements

[Table 2–42](#) describes this annotation's elements.

**Table 2–42** *@NamedStoredProcedureQuery Annotation Elements*

Annotation Element	Description	Default
name	(Required) Unique name that references this stored procedure query.	
procedureName	(Required) Name of the stored procedure	
callByIndex	(Optional) Specifies if the stored procedure should be called by name. <ul style="list-style-type: none"><li>■ If <b>true</b>, the <code>StoredProcedureParameters</code> must be defined in the same order as the procedure on the database</li><li>■ If <b>false</b>, the database platform must support naming procedure parameters</li></ul>	false
hints	(Optional) An array of query hints.	
multipleResultSets	(Optional) Specifies if the stored procedure returns multiple result sets.  This applies only for databases that support multiple result sets from stored procedures.	false
parameters	(Optional) An array of parameters for the stored procedure	
resultClass	(Optional) The class of the result	<code>void.class</code>
resultSetMapping	(Optional) Name of the <code>SQLResultMapping</code>	
returnsResultSet	(Optional) Specifies if the stored procedure retains a result set  This applies only for databases that support result sets from stored procedures.	false

### Usage

You can specify `@NamedStoredProcedureQuery` on an Entity or `MappedSuperclass`.

### Examples

[Example 2–71](#) shows how to use `@NamedStoredProcedureQuery` to define a stored procedure.

#### **Example 2–71** *Using @NamedStoredProcedureQuery Annotation*

```
@NamedStoredProcedureQuery(name="findAllEmployees", procedureName="EMP_READ_ALL",
resultClass=Employee.class, parameters={
    @StoredProcedureParameter(queryParameter="result", name="RESULT_CURSOR",
direction=Direction.OUT_CURSOR)})
@Entity
public class Employee {
    ...
}
```



[Example 2-72](#) shows how to use the `<named-stored-procedure-query>` element in the `eclipselink-orm.xml` file.

**Example 2-72 Using `<named-stored-procedure-query>` XML**

```
<named-stored-procedure-query name="SProcXMLInOut" result-class="Address"
  procedure-name="SProc_Read_XMLInOut">
  <parameter direction="IN_OUT" name="address_id_v" query-parameter="ADDRESS_ID"
    type="Long"/>
  <parameter direction="OUT" name="street_v" query-parameter="STREET"
    type="String"/>
</named-stored-procedure-query>
```

## See Also

For more information, see:

- ["@NamedStoredProcedureQueries"](#) on page -102
- "Stored Procedures Examples"  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/StoredProcedures>

## @Noncacheable

Use @Noncacheable to configure caching behavior for relationships. If used on a relationship, that relationship *will not* be cached, even though the parent Entity may be cached.

### Annotation Elements

There are no elements for this annotation.

### Usage

Each time EclipseLink retrieves the Entity, the relationship will be reloaded from the datasource. This may be useful for situations where caching of relationships is not desired or when using different EclipseLink IdentityMap types and having cached references extends the cache lifetime of related Entities using a different caching scheme. For instance Entity A references Entity B, Entity A is FullIdentityMap and Entity B is WeakIdentityMap. Without removing the caching of the relationship the Entity B's cache effectively become a FullIdentityMap.

### Examples

[Example 2-73](#) shows how to use @Noncacheable to create a protected cache.

#### **Example 2-73 Using @Noncacheable Annotation**

```
@Entity
@Cache(
    isolation=CacheIsolationType.PROTECTED
)
public class Employee {
    @Id
    private long id;
    ...
    @OneToMany(mappedBy="manager")
    @Noncacheable
    private List<Employee> managedEmployees;
    ...
}
```

[Example 2-74](#) shows using the <noncacheable> XML element in the eclipselink-orm.xml file.

#### **Example 2-74 Using <noncacheable> XML**

```
<?xml version="1.0"?>
<entity-mappings
    xmlns="http://www.eclipse.org/eclipselink/xsds/persistence/orm"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://www.eclipse.org/eclipselink/xsds/persistence/orm
http://www.eclipse.org/eclipselink/xsds/eclipselink_orm_2_4.xsd"
    version="2.4">
    <entity name="Employee" class="org.acme.Employee" access="FIELD">
        <cache isolation="PROTECTED"/>
        <attributes>
            <id name="id"/>
        </attributes>
    </entity>
</entity-mappings>
```

```
        <one-to-many name="managedEmployees" mapped-by="manager">
            <noncacheable/>
        </one-to-many>
    </attributes>
</entity>
</entity-mappings>
```

## See Also

For more information, see:

- "Caching"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching)

## @NoSql

Use `@NoSql` to specify a non-relational (that is, no SQL) data source. EclipseLink can map non-relational data to objects and access that data through JPA.

### Annotation Elements

[Table 2–43](#) describes this annotation's elements.

**Table 2–43** *@NoSql Annotation Elements*

Annotation Element	Description	Default
<code>dataType</code>	The name of the entities structure. The purpose of the <code>dataType</code> depends on the NoSQL platform used: <ul style="list-style-type: none"><li>■ For MongoDB, it is the collection name that the JSON documents are stored to.</li><li>■ For Oracle NoSQL, it is the first part of the major key value.</li><li>■ For XML files, it is the file name. and XML messaging, use <code>XML</code>.</li></ul>	
<code>dataFormat</code>	(Optional) The type structure (data format) in which the data is stored within the database: <ul style="list-style-type: none"><li>■ <code>INDEXED</code> – Maps a class to an array of values.</li><li>■ <code>MAPPED</code> – Maps a class to a set of nested key / value pairs, a value can be an embedded map or list. Use to map to key / value stores, JSON databases, and other structured data systems.</li><li>■ <code>XML</code> – Maps a class to an XML document. Use with XML data-stores, XML files, XML messaging systems, and other XML systems.</li></ul>	<code>XML</code>

### Usage

The `dataFormat` depends on the NoSQL platform used:

- For MongoDB, use `MAPPED`.
- For Oracle NoSQL, use `MAPPED` (for key / value data) or `XML` (for a single XML document).
- For XML files and XML messaging, use `XML`.

#### Supported Datasources

EclipseLink supports several NoSQL and EIS platforms, as well as generic NoSQL and EIS datasources through the JavaEE Connector Architecture CCI (Common Client Interface) API. You can also define your own `EISPlatform` subclass and JCA adapter

EclipseLink supports the following datasources:

- MongoDB
- Oracle NoSQL
- XML Files
- JMS
- Oracle AQ

## Examples

[Example 2-75](#) shows using @NoSql with an XML data source.

### **Example 2-75 Using @NoSql Annotation with XML**

```
@Entity
@NoSQL(dataType="order")
public class Order {
    @Id
    @GeneratedValue
    @Field(name="@id")
    private long id;
    @Basic
    @Field(name="@description")
    private String description;
    @Embedded
    @Field(name="delivery-address")
    private Address deliveryAddress
    @ElementCollection
    @Field(name="orderLines/order-line")
    private List<OrderLine> orderLines;
    @ManyToOne
    @JoinField(name="customer-id")
    private Customer customer;
}

@Embeddable
@NoSQL
public class OrderLine {
    @Field(name="@line-number")
    private int lineNumber;
    @Field(name="@item-name")
    private String itemName;
    @Field(name="@quantity")
    private int quantity;
}
```

This would produce the following XML data:

```
<order id="4F99702B271B1948027FAF06" description="widget order">
  <deliveryAddress street="1712 Hasting Street" city="Ottawa" province="ON"
postalCode="L5J1H5"/>
  <order-lines>
    <order-line lineNumber="1" itemName="widget A" quantity="5"/>
    <order-line lineNumber="2" itemName="widget B" quantity="1"/>
    <order-line lineNumber="3" itemName="widget C" quantity="2"/>
  </order-lines>
  <customer-id>4F99702B271B1948027FAF08</customer-id>
</order>
```

[Example 2-76](#) shows using @NoSql with a JSON data source.

### **Example 2-76 Using @NoSql Annotation with JSON**

```
@Entity
@NoSQL(dataType="orders", dataFormat=DataFormatType.MAPPED)
public class Order {
    @Id
    @GeneratedValue
    @Field(name="_id")
```

```
private long id;
@Basic
@Field(name="description")
private String description;
@Embedded
@Field(name="deliveryAddress")
private Address deliveryAddress
@ElementCollection
@Field(name="orderLines")
private List<OrderLine> orderLines;
@ManyToOne
@JoinField(name="customerId")
private Customer customer;
}

@Embeddable
@NoSQL(dataFormat=DataFormatType.MAPPED)
public class OrderLine {
    @Field(name="lineNumber")
    private int lineNumber;
    @Field(name="itemName")
    private String itemName;
    @Field(name="quantity")
    private int quantity;
}
```

This would produce the following JSON document:

```
{
  "_id": "4F99702B271B1948027FAF06",
  "description": "widget order",
  "deliveryAddress": {
    "street": "1712 Hasting Street",
    "city": "Ottawa",
    "province": "ON",
    "postalCode": "L5J1H5",
  },
  "orderLines": [
    {"lineNumber": "1", "itemName": "widget A", "quantity": "5"},
    {"lineNumber": "2", "itemName": "widget B", "quantity": "1"},
    {"lineNumber": "3", "itemName": "widget C", "quantity": "2"}
  ],
  "customerId": "4F99702B271B1948027FAF08",
}
```

## See Also

For more information, see:

- @NoSQL  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/NoSQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/NoSQL)
- NoSQL Persistence Units  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/NoSQL/Persistence\\_Units](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/NoSQL/Persistence_Units)

- Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/NoSQL>
- "nosql.property" on page -150
- EclipseLink Platform Incubator  
<http://wiki.eclipse.org/EclipseLink/Development/Incubator/Platform>
- Supported NoSQL and EIS Datasources  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/NoSQL/Supported\\_Data-sources](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/NoSQL/Supported_Data-sources)

## @ObjectTypeConverter

The `@ObjectTypeConverter` annotation specifies an `org.eclipse.persistence.mappings.converters.ObjectTypeConverter` that converts a fixed number of database data value(s) to Java object value(s) during the reading and writing of a mapped attribute.

### Annotation Elements

[Table 2–44](#) describes this annotation's elements.

**Table 2–44** *@ObjectTypeConverter Annotation Elements*

Annotation Element	Description	Default
name	Set this attribute to the <code>String</code> name for your converter. Ensure that this name is unique across the persistence unit	none
dataType	(Optional) Set this attribute to the type stored in the database.	<code>void.class</code> <sup>1</sup>
objectType	(Optional) Set the value of this attribute to the type stored on the entity.	<code>void.class</code> <sup>1</sup>
conversionValues	Set the value of this attribute to the array of conversion values (instances of <code>ConversionValue</code> : <code>String</code> <code>objectValue</code> and <code>String</code> <code>dataValue</code> ).	none
defaultObjectValue	Set the value of this attribute to the default object value. Note that this argument is for dealing with legacy data if the data value is missing.	Empty <code>String</code>

<sup>1</sup> The default is inferred from the type of the persistence field or property.

### Usage

EclipseLink also includes `@TypeConverter` and `@StructConverter` converters.

### Examples

[Example 2–77](#) shows how to use the `@ObjectTypeConverter` annotation to specify object converters for the gender field.

**Example 2–77** *Using the @ObjectTypeConverter Annotation*

```
public class Employee implements Serializable{
    ...
    @ObjectTypeConverter (
        name="genderConverter",
        dataType=java.lang.String.class,
        objectType=java.lang.String.class,
        conversionValues={
            @ConversionValue(dataValue="F", objectValue="Female"),
            @ConversionValue(dataValue="M", objectValue="Male")}
    )
    @Convert("genderConverter")
    public String getGender() {
        return gender;
    }
    ...
}
```



You can use the `<object-type-converter>` element in the deployment descriptor as an alternative to using the `@ObjectTypeConverter` annotation in the source code, as shown in [Example 2-78](#).

**Example 2-78 Using `<object-type-converter>` XML**

```
<object-type-converter name="gender-converter" object-type="model.Gender"
  data-type="java.lang.String">
  <conversion-value object-value="Male" data-value="M" />
  <conversion-value object-value="Female" data-value="F" />
</object-type-converter>
```

## See Also

For more information, see:

- ["@TypeConverter"](#) on page -186
- ["@StructConverter"](#) on page -166
- ["@ConversionValue"](#) on page -38

## @ObjectTypeConverters

Use @ObjectTypeConverters to define multiple ObjectTypeConverter items.

### Annotation Elements

[Table 2–45](#) describes this annotation's elements.

**Table 2–45 @ObjectTypeConverters Annotation Elements**

Annotation Element	Description	Default
ObjectTypeConverter	(Required) An array of @ObjectTypeConverter	

### Examples

[Example 2–79](#) shows how to use this annotation.

#### **Example 2–79 Using @ObjectTypeConverters Annotation**

```
@Entity(name="Employee")
@Table(name="CMP3_FA_EMPLOYEE")
@ObjectTypeConverters({
    @ObjectTypeConverter(
        name="sex",
        dataType=String.class,

        objectType=org.eclipse.persistence.testing.models.jpa.fieldaccess.advanced.Employee.Gender.class,
        conversionValues={
            @ConversionValue(dataValue="F", objectValue="Female"),
            @ConversionValue(dataValue="M", objectValue="Male")
        }
    )
})
```

To define multiple object type converts in the eclipselink-orm.xml file, simply create a list of multiple <object-type-converter> elements.

### See Also

For more information, see:

- ["@ObjectTypeConverter"](#) on page -112



## @OptimisticLocking

Use `@OptimisticLocking` to specify the type of optimistic locking EclipseLink should use when updating or deleting entities.

### Annotation Elements

[Table 2–46](#) describes this annotation's elements.

**Table 2–46 @OptimisticLocking Annotation Elements**

Annotation Element	Description	Default
<code>cascade</code>	(Optional) Specify where the optimistic locking policy should cascade lock.  Currently only supported with <code>VERSION_COLUMN</code> locking.	<code>false</code>
<code>SelectedColumns</code>	(Optional) Specify a list of columns that will be optimistically locked.  This element is required when <code>type=SELECTED_COLUMNS</code> .	
<code>type</code>	(Optional) The type of optimistic locking policy to use: <ul style="list-style-type: none"> <li>■ <code>ALL_COLUMNS</code> – EclipseLink compares every field in the table with the <code>WHERE</code> clause, when performing an update or delete operation.</li> <li>■ <code>CHANGED_COLUMNS</code> – EclipseLink compares only the changed fields in the <code>WHERE</code> clause when performing an update.</li> <li>■ <code>SELECTED_COLUMNS</code> – EclipseLink compares the selected field in the <code>WHERE</code> clause when performing an update or delete operation on the <code>SelectedColumns</code>.</li> <li>■ <code>VERSION_COLUMN</code> – EclipseLink compares a single version number in the <code>WHERE</code> clause when performing an update.</li> </ul>	<code>VERSION_COLUMN</code>

### Usage

You can specify `@OptimisticLocking` on an Entity or `MappedSuperclass`.

### Examples

[Example 2–80](#) shows how to use the `@OptimisticLocking` annotation for all columns

#### Example 2–80 Using @OptimisticLocking Annotation

```
@Table(name = "EMPLOYEES")
@OptimisticLocking(type=OptimisticLockingType.ALL_COLUMNS)
public class Employee implements Serializable {
    ...
}
```

[Example 2–80](#) shows how to use the `<optimistic-locking>` element in the `eclipselink-orm.xml` file for a single column.

#### Example 2–81 Using <optimistic-locking> XML

```
<entity name="Employee" class="my.Employee" access="PROPERTY"
change-tracking="DEFERRED">
    ...
    <optimistic-locking type="SELECTED_COLUMNS" cascade="false">
```

```
        <selected-column name="id"/>
        <selected-column name="firstName"/>
    </optimistic-locking>
    ...
</entity>
```

**See Also**

For more information, see:

## @OrderCorrection

Use `@OrderCorrection` to specify a strategy to use if the order list read from the database is invalid (for example, it has nulls, duplicates, negative values, or values greater than or equal to the list size).

To be valid, an order list of  $n$  elements must be  $\{0, 1, \dots, n-1\}$

### Annotation Elements

Table 2–47 describes this annotation's elements.

**Table 2–47 @OrderCorrection Annotation Elements**

Annotation Element	Description	Default
<code>OrderCorrectionType</code>	(Optional) Specify a strategy to use if the order list read from the database is invalid: <ul style="list-style-type: none"> <li>▪ <code>EXCEPTION</code></li> <li>▪ <code>READ</code></li> <li>▪ <code>READ_WRITE</code></li> </ul>	<code>READ_WRITE</code>

### Usage

When using `@OrderCorrection`, you can specify how EclipseLink should handle invalid list orders:

- **EXCEPTION** – When `OrderCorrectionType=EXCEPTION`, EclipseLink will not correct the list. Instead, EclipseLink will throw a `QueryException` with error code `QueryException.LIST_ORDER_FIELD_WRONG_VALUE`

For example, given the following list of three objects in the database:

```
{null, objectA}; {2, objectB}, {5, ObjectC};
```

When read into the application, EclipseLink will throw an exception.

- **READ** – When `OrderCorrectionType=READ`, EclipseLink corrects the list read into application, but does not retain any information about the invalid list order that remains in the database. Although this is not an issue in read-only uses of the list, if the list is modified and then saved into the database, the order will most likely differ from the cache and be invalid.

The `READ` mode is used as the default when the mapped attribute is neither a `List` nor `Vector` (that is, it is not assignable from the EclipseLink internal class `IndirectList`).

For example, given the following list of three objects in the database:

```
{null, objectA}; {2, objectB}, {5, ObjectC}
```

- When read as a list: `{objectA, objectB, objectC}`
- When adding a new element to the list: `{objectA, objectB, objectC, objectD}`
- When saving the updated list to the database: `{null, objectA}, {2, objectB}, {5, objectC}, {3, objectD}`
- When reading the list again: `{objectA, objectB, objectD, objectC}`

- **READ\_WRITE** – When `OrderCorrectionType=READ_WRITE`, EclipseLink corrects the order of the list read into application *and* remembers the invalid list order left in the database. If the list is updated and saved to the database, the order indexes are saved ensuring that the list order in the data base will be exactly the same as in cache (and therefore valid).

The `READ_WRITE` mode is used as the default when the mapped attribute is either a `List` or `Vector` (that is, it is assignable from the EclipseLink internal class `IndirectList`). In JPA, if the mode is not specified, `READ_WRITE` is used by default.

For example, given the following list of three objects in the database:

```
{null, objectA}; {2, objectB}, {5, ObjectC}
```

- When read as a list: {objectA, objectB, objectC}
- When adding a new element to the list: {objectA, objectB, objectC, objectD}
- When saving the updated list to the database: {0, objectA}, {1, objectB}, {2, objectC}, {3, objectD}
- When reading the list again: {objectA, objectB, objectC, objectD}

## Examples

[Example 2-82](#) shows how to use this annotation.

### **Example 2-82 Using @OrderCorrection Annotation**

```
@OrderColumn(name="ORDER_COLUMN")
@OrderCorrection(EXCEPTION)
List<String> designations;
```

## See Also

For more information see:

- ["Entity Annotations"](#) on page 2-2

## @Partitioned

Use @Partitioned to specify a partitioning policy to use for an Entity or relationship.

### Annotation Elements

Table 2–48 describes this annotation's elements.

**Table 2–48 @Partitioned Annotation Elements**

Annotation Element	Description	Default
value	(Required) Name of the partitioning policy: <ul style="list-style-type: none"> <li>▪ @HashPartitioning</li> <li>▪ @PinnedPartitioning</li> <li>▪ @RangePartition</li> <li>▪ @ReplicationPartitioning</li> <li>▪ @RoundRobinPartitioning</li> <li>▪ @UnionPartitioning</li> <li>▪ @ValuePartitioning</li> </ul>	

### Usage

Use partitioning to partition the data for a class across multiple databases or a database cluster (such as Oracle RAC). Partitioning can provide improved scalability by allowing multiple database machines to service requests.

You can specify @Partitioned on an Entity, relationship, query, or session/persistence unit.

### Examples

Example 2–83 shows the partition of Employee data by location. The two primary sites, Ottawa and Toronto, are stored on separate databases. All other locations are stored on the default database.

The example project is range partitioned by its ID. Each range of ID values are stored on a different database. The employee/project relationship is an example of a cross partition relationship.

To allow the employees and projects to be stored on different databases, EclipseLink uses a union policy; the join table is replicated to each database.

#### **Example 2–83 Using Partitioning**

```

@Entity
@IdClass(EmployeePK.class)
@UnionPartitioning(
    name="UnionPartitioningAllNodes",
    replicateWrites=true)
@ValuePartitioning(
    name="ValuePartitioningByLOCATION",
    partitionColumn=@Column(name="LOCATION"),
    unionUnpartitionableQueries=true,
    defaultConnectionPool="default",
    partitions={
        @ValuePartition(connectionPool="node2", value="Ottawa"),
    }

```



```

        @ValuePartition(connectionPool="node3", value="Toronto")
    })
    @Partitioned("ValuePartitioningByLOCATION")
    public class Employee {
        @Id
        @Column(name = "EMP_ID")
        private Integer id;

        @Id
        private String location;
        ...

        @ManyToMany(cascade = { PERSIST, MERGE })
        @Partitioned("UnionPartitioningAllNodes")
        private Collection<Project> projects;
        ...
    }

    @Entity
    @RangePartitioning(
        name="RangePartitioningByPROJ_ID",
        partitionColumn=@Column(name="PROJ_ID"),
        partitionValueType=Integer.class,
        unionUnpartitionableQueries=true,
        partitions={
            @RangePartition(connectionPool="default", startValue="0",
endValue="1000"),
            @RangePartition(connectionPool="node2", startValue="1000",
endValue="2000"),
            @RangePartition(connectionPool="node3", startValue="2000")
        })
    @Partitioned("RangePartitioningByPROJ_ID")
    public class Project {
        @Id
        @Column(name="PROJ_ID")
        private Integer id;
        ...
    }

```

## See Also

For more information, see:

- ["@Partitioning"](#)
- ["@HashPartitioning"](#) on page -66
- ["@PinnedPartitioning"](#) on page -128
- ["@RangePartition"](#) on page -146
- ["@ReplicationPartitioning"](#) on page -154
- ["@RoundRobinPartitioning"](#) on page -160
- ["@UnionPartitioning"](#) on page -192
- ["@ValuePartitioning"](#) on page -196

- "Data Partitioning"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Data\\_Partitioning](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Data_Partitioning)
- Partitioning Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Partitioning>



## @Partitioning

Use `@Partitioning` to configure a custom `PartitioningPolicy`.

### Annotation Elements

[Table 2–49](#) describes this annotation's elements.

**Table 2–49** *@Partitioning Annotation Elements*

Annotation Element	Description	Default
name	Name of the partition policy. Names must be unique for the persistence unit.	
PartitioningClass	(Required) Full <code>package.class</code> name of a subclass of <code>PartitioningPolicy</code> .	

### Usage

Data partitioning allows for an application to scale its data across more than a single database machine. EclipseLink supports data partitioning at the Entity level to allow a different set of entity instances for the same class to be stored in a different physical database or different node within a database cluster. Both regular databases and clustered databases are supported. Data can be partitioned both horizontally and vertically.

Partitioning can be enabled on an entity, a relationship, a query, or a persistence unit.

#### Partitioning Policies

To configure data partitioning, use the `@Partitioned` annotation and one or more partitioning policy annotations. The annotations for defining the different kinds of policies are:

- [@HashPartitioning](#): Partitions access to a database cluster by the hash of a field value from the object, such as the object's ID, location, or tenant. The hash indexes into the list of connection pools/nodes. All write or read request for objects with that hash value are sent to the same server. If a query does not include the hash field as a parameter, it can be sent to all servers and unioned, or it can be left to the session's default behavior.
- [@PinnedPartitioning](#): Pins requests to a single connection pool/node. This allows for vertical partitioning.
- [@RangePartitioning](#): Partitions access to a database cluster by a field value from the object, such as the object's ID, location, or tenant. Each server is assigned a range of values. All write or read requests for objects with that value are sent to the same server. If a query does not include the field as a parameter, then it can either be sent to all server's and unioned, or left to the session's default behavior.
- [@ReplicationPartitioning](#): Sends requests to a set of connection pools/nodes. This policy is for replicating data across a cluster of database machines. Only modification queries are replicated.
- [@RoundRobinPartitioning](#): Sends requests in a round-robin fashion to the set of connection pools/nodes. It is for load balancing read queries across a cluster of database machines. It requires that the full database be replicated on each machine, so it does not support partitioning. The data should either be read-only, or writes should be replicated.

- [@UnionPartitioning](#): Sends queries to all connection pools and unions the results. This is for queries or relationships that span partitions when partitioning is used, such as on a ManyToMany cross partition relationship.
- [@ValuePartitioning](#): Partitions access to a database cluster by a field value from the object, such as the object's location or tenant. Each value is assigned a specific server. All write or read requests for objects with that value are sent to the same server. If a query does not include the field as a parameter, then it can be sent to all servers and unioned, or it can be left to the session's default behavior.
- [@Partitioning](#): Partitions access to a database cluster by a custom partitioning policy. A PartitioningPolicy class must be provided and implemented.

Partitioning policies are globally-named objects in a persistence unit and are reusable across multiple descriptors or queries. This improves the usability of the configuration, specifically with JPA annotations and XML.

The persistence unit properties support adding named connection pools in addition to the existing configuration for read/write/sequence. A named connection pool must be defined for each node in the database cluster.

If a transaction modifies data from multiple partitions, JTA should be used to ensure 2-phase commit of the data. An exclusive connection can also be configured in the EntityManager to ensure only a single node is used for a single transaction.

### Clustered Databases and Oracle RAC

Some databases support clustering the database across multiple machines. Oracle RAC allows for a single database to span multiple different server nodes. Oracle RAC also supports table and node partitioning of data. A database cluster allows for any of the data to be accessed from any node in the cluster. However, it is generally more efficient to partition the data access to specific nodes, to reduce cross node communication.

EclipseLink partitioning can be used in conjunction with a clustered database to reduce cross node communication, and improve scalability.

To use partitioning with a database cluster the following is required:

- Partition policy should not enable replication, as database cluster makes data available to all nodes.
- Partition policy should not use unions, as database cluster returns the complete query result from any node.
- A data source and EclipseLink connection pool should be defined for each node in the cluster.
- The application's data access and data partitioning should be designed to have each transaction only require access to a single node.
- Usage of an exclusive connection for an EntityManager is recommended to avoid having multiple nodes in a single transaction and avoid 2-phase commit.

## Examples

[Example 2-84](#) shows how to partition Employee data by location. The two primary sites, **Ottawa** and **Toronto** are each stored on a separate database. All other locations are stored on the default database. Project is range partitioned by its ID, as shown in [Example 2-85](#). Each range of ID values are stored on a different database. The employee/project relationship is an example of a cross partition relationship. To allow

the employees and projects to be stored on different databases a union policy is used and the join table is replicated to each database.

#### **Example 2-84 Using Partitioning**

```
@Entity
@IdClass(EmployeePK.class)
@UnionPartitioning(
    name="UnionPartitioningAllNodes",
    replicateWrites=true)
@ValuePartitioning(
    name="ValuePartitioningByLOCATION",
    partitionColumn=@Column(name="LOCATION"),
    unionUnpartitionableQueries=true,
    defaultConnectionPool="default",
    partitions={
        @ValuePartition(connectionPool="node2", value="Ottawa"),
        @ValuePartition(connectionPool="node3", value="Toronto")
    })
@Partitioned("ValuePartitioningByLOCATION")
public class Employee {
    @Id
    @Column(name = "EMP_ID")
    private Integer id;

    @Id
    private String location;
    ...

    @ManyToMany(cascade = { PERSIST, MERGE })
    @Partitioned("UnionPartitioningAllNodes")
    private Collection<Project> projects;
    ...
}
```

#### **Example 2-85 Using @RangePartitioning**

```
@Entity
@RangePartitioning(
    name="RangePartitioningByPROJ_ID",
    partitionColumn=@Column(name="PROJ_ID"),
    partitionValueType=Integer.class,
    unionUnpartitionableQueries=true,
    partitions={
        @RangePartition(connectionPool="default", startValue="0",
            endValue="1000"),
        @RangePartition(connectionPool="node2", startValue="1000",
            endValue="2000"),
        @RangePartition(connectionPool="node3", startValue="2000")
    })
@Partitioned("RangePartitioningByPROJ_ID")
public class Project {
    @Id
    @Column(name="PROJ_ID")
    private Integer id;
    ...
}
```

## See Also

For more information, see:

- ["@Partitioned"](#) on page -120
- ["@HashPartitioning"](#) on page -66
- ["@PinnedPartitioning"](#) on page -128
- ["@RangePartitioning"](#) on page -148
- ["@ReplicationPartitioning"](#) on page -154
- ["@RoundRobinPartitioning"](#) on page -160
- ["@UnionPartitioning"](#) on page -192
- ["@ValuePartitioning"](#) on page -196
- ["partitioning"](#) on page -158
- "Data Partitioning"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Data\\_Partitioning](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Data_Partitioning)
- EclipseLink Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Partitioning>

---

## @PinnedPartitioning

Use `@PinnedPartitionPolicy` to pin requests to a single connection pool.

### Annotation Elements

[Table 2–50](#) describes this annotation's elements.

**Table 2–50** @PinnedPartitioning Annotation Elements

Annotation Element	Description	Default
connectionPool	Connection pool name to which to pin queries.	
name	Name of the partition policy. Names must be unique for the persistence unit.	

### Usage

Partition policies are globally named, to allow reuse. You must also set the partitioning policy with the `@Partitioned` annotation.

You can specify `@PinnedPartitioning` on an Entity, relationship, query, or session/persistence unit.

The persistence unit properties support adding named connection pools in addition to the existing configuration for read/write/sequence. A named connection pool must be defined for each node in the database cluster.

If a transaction modifies data from multiple partitions, you should use JTA ensure proper two-phase commit of the data. You can also configure an exclusive connection in the `EntityManager` to ensure that only a single node is used for a single transaction.

### Examples

See [Example 2–83](#) on page -120 for an example of partitioning with EclipseLink.

### See Also

For more information, see:

- "Data Partitioning"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Data\\_Partitioning](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Data_Partitioning)
- "[@Partitioned](#)" on page -120





---

## @PLSQLRecords

Use @PLSQLRecords to define multiple PLSQLRecord.

### Annotation Elements

[Table 2–51](#) describes this annotation's elements.

**Table 2–51 @PLSQLRecord Annotation Elements**

Annotation Element	Description	Default
value	(Required) An array of named PLSQL records.	

### Examples

[Example 2–86](#) shows how to use this annotation.

**Example 2–86 Using @PLSQLRecords Annotation**

### See Also

For more information, see:

- ["@NamedPLSQLStoredProcedureQuery"](#) on page -90
- ["@PLSQLRecord"](#) on page -134
- Oracle PL/SQL  
<http://www.oracle.com/technetwork/database/features/plsql/index.html>
- PLSQL Stored Procedure Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/PLSQLStoredFunction>



## @PLSQLParameter

Use `@PLSQLParameter` within a `NamedPLSQLStoredProcedureQuery` or `PLSQLRecord` annotation.

### Annotation Elements

[Table 2–52](#) describes this annotation's elements.

**Table 2–52** *@PLSQLParameter Annotation Elements*

Annotation Element	Description	Default
name	(Required) The query parameter name	
direction	(Optional) The direction of the stored procedure parameter: <ul style="list-style-type: none"><li>■ IN – Input parameter</li><li>■ IN_OUT – Input and output parameters</li><li>■ OUT – Output parameter</li><li>■ OUT_CURSOR – Output cursor</li></ul>	IN
databaseType	(Optional) Database data type for the parameter. This either one of the type constants defined in <code>OraclePLSQLTypes</code> , or <code>JDBCTypes</code> , or a custom record or table type name.	
length	(Optional) Maximum length of the field value.	
name	(Optional) Stored procedure parameter name	
optional	(Optional) Specify if the parameter is required, or optional and defaulted by the procedure.	false
scale	(Optional) Maximum precision value.	
precision	(Optional) Maximum precision value.	

### Usage

EclipseLink will throw an exception if you set more than one parameter to the `OUT_CURSOR` type.

### Examples

See "[@NamedPLSQLStoredProcedureQuery](#)" on page -90 for an example using the `@PLSQLParameter` annotation.

### See Also

For more information:

- "[@NamedPLSQLStoredProcedureQuery](#)" on page -90
- "[@PLSQLRecord](#)" on page -134
- PLSQL Stored Procedure Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/PLSQLStoredFunction>



---

## @PLSQLRecord

Use `@PLSQLRecord` to define a database PLSQL RECORD type for use within PLSQL procedures.

### Annotation Elements

[Table 2–53](#) describes this annotation's elements.

**Table 2–53** *@PLSQLRecord Annotation Elements*

Annotation Element	Description	Default
name	(Required) The name of the record type in the database.	
compatibleType	(Required) Name of the database OBJECTTYPE that mirror's the record's structure.	
fields	(Required) The fields in the record type.	
javaType	(Optional) The class to which to the object type. You must map this class with the <a href="#">@Struct</a> annotation.	

### Examples

[Example 2–87](#) shows how to use this annotation.

**Example 2–87** *Using @PLSQLRecord Annotation*

### See Also

For more information, see:

- ["@NamedPLSQLStoredProcedureQuery"](#) on page -90
- ["@PLSQLRecords"](#) on page -130
- Oracle PL/SQL  
<http://www.oracle.com/technetwork/database/features/plsql/index.html>
- PLSQL Stored Procedure Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/PLSQLStoredFunction>



## @PrimaryKey

Use @PrimaryKey to allow advanced configuration of the ID.

A validation policy can be given that allows specifying if zero is a valid ID value. The set of primary key columns can also be specified precisely.

### Annotation Elements

[Table 2–54](#) describes this annotation's elements.

**Table 2–54 @PrimaryKey Annotation Elements**

Annotation Element	Description	Default
cacheKeyType	(Optional) Configures the cache key type to store the object in the cache.	AUTO
columns	(Optional) Directly specify the primary key columns. This can be used instead of @Id if the primary key includes a non basic field, such as a foreign key, or a inheritance discriminator, embedded, or transformation mapped field.	
validation	(Optional) Configures what ID validation is done: <ul style="list-style-type: none"><li>■ NULL – EclipseLink interprets zero values as zero. This permits primary keys to use a value of zero.</li><li>■ ZERO (default) – EclipseLink interprets zero as null.</li><li>■ NEGATIVE – EclipseLink interprets negative values as null.</li><li>■ NONE – EclipseLink does not validate the id value.</li></ul> By default 0 is not a valid ID value, this can be used to allow 0 id values.	ZERO

### Usage

By default, EclipseLink interprets zero as null for primitive types that cannot be null (such as int and long), causing zero to be an invalid value for primary keys. You can modify this setting by using the @PrimaryKey annotation to configure an IdValidation for an entity class.

### Examples

[Example 2–88](#) shows how to use this annotation.

**Example 2–88 Using @PrimaryKey Annotation**

```
@PrimaryKey(validation=IdValidation.ZERO)
public class Employee implements Serializable, Cloneable {
    ...
}
```

[Example 2–89](#) shows how to use the <primary-key> element in your eclipselink-orm.xml file.

**Example 2–89 Using @<primary-key> XML**

```
<entity name="Employee" class="foo.Employee" access="PROPERTY">
    <primary-key validation="ZERO"/>
    ...
</entity>
```



## See Also

For more information, see:

- "@Id"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Entities/Ids/Id](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Entities/Ids/Id)
- "Entity Annotations" on page 2-2

---

## @PrivateOwned

Use @PrivateOwned to specify that a relationship is privately owned; target object is a dependent part of the source object and is not referenced by any other object and cannot exist on its own.

### Annotation Elements

The @PrivateOwned annotation does not have attributes.

### Usage

Using @PrivateOwned causes many operations to be cascaded across the relationship including delete, insert, refresh, and lock (when cascaded). It also ensures that private objects removed from collections are deleted and that objects added are inserted.

You can specify @PrivateOwned on with @OneToOne, @OneToMany and @VariableOneToOne annotations. Private ownership is implied with the @BasicCollection and @BasicMap annotations.

When the referenced object is privately owned, the referenced child object cannot exist without the parent object.

### Additional Information

When indicating that a relationship is privately owned, you are specifying the following:

- If the source of a privately owned relationship is deleted, then EclipseLink will delete the target. This is equivalent of setting [@CascadeOnDelete](#).
- If you remove the reference to a target from a source, then EclipseLink will delete the target.

Normally, do not configure privately owned relationships on objects that might be shared. An object should not be the target in more than one relationship if it is the target in a privately owned relationship.

---

**Note:** Referencing a privately owned object may produce undesired effects, as it is the application's responsibility to "clean up" references to the privately owned object.

If the object becomes de-referenced and is deleted, other objects in the cache that continue to reference the deleted object may cause constraint violations, they may resurrect the object (if using cascade persist), or they may simply not reflect what is in the database.

---

### Examples

[Example 2-90](#) shows using @PrivateOwned to specify Employee field phoneNumbers. .

#### **Example 2-90 Using @PrivateOwned Annotation**

```
@Entity
public class Employee implements Serializable {
    ...
    @OneToMany(cascade=ALL, mappedBy="employee")
    @PrivateOwned
```

```
public Collection<PhoneNumber> getPhoneNumbers() {  
    return phoneNumbers;  
}  
...  
}
```

When you create a mapping using Java, use its `privateOwnedRelationship` method to tell EclipseLink that the referenced object is privately owned: that is, the referenced child object cannot exist without the parent object.

## See Also

For more information, see:

- ["@CascadeOnDelete"](#) on page -26

---

## @Properties

Use `@Property` to specify a single user-defined property on a mapped attribute or its `get/set` method. Use the `@Properties` annotation to wrap multiple properties.

### Annotation Elements

[Table 2–55](#) describes this annotation's elements.

**Table 2–55** *@Properties Annotation Elements*

Annotation Element	Description	Default
Property	Array of <code>Property</code> elements.	

### Usage

You can specify `@Property` on a mapped attribute (or its `get/set` method) within an `Entity`, `MappedSuperclass`, or `Embeddable` class. You can also specify this annotation on an `Entity`, `MappedSuperclass`, or `Embeddable` class.

Properties defined in `MappedSuperclass` are passed to all inheriting `Entities` and `MappedSuperclasses`. In case of a conflict, property values defined directly on a class always override values inherited from a class's parent.

When using an `orm.xml` mapping file, EclipseLink ignores `@Property` and `@Properties` annotations on mapped attributes; annotations on classes are merged with those specified in the `orm.xml` file, with the latter taking precedence in case of conflicts.

### Examples

[Example 2–111](#) on page -184 shows how to use the `@Properties` annotation within a `@Transformation` mapping. [Example 2–112](#) shows how to use the `<properties>` XML element within the `orm.xml` file.

### See Also

For more information, see:

- ["@Property"](#) on page -142



---

## @Property

Use `@Property` to specify a single user-defined property on a mapped attribute or its `get/set` method. Use the `@Properties` annotation to wrap multiple properties.

### Annotation Elements

[Table 2–56](#) describes this annotation's elements.

**Table 2–56** *@Property Annotation Elements*

Annotation Element	Description	Default
name	(Required) Name of the property	
value	(Required) String representation of the property value, converted to an instance of <code>valueType</code> .	
valueType	(Optional) Property value type, converted to <code>valueType</code> by <code>ConversionManager</code> . This must be a simple type that can be handled by the <code>ConversionManager</code> .	String

### Usage

You can specify `@Property` on a mapped attribute (or its `get/set` method) within an Entity, `MappedSuperclass`, or `Embeddable` class. You can also specify this annotation on an Entity, `MappedSuperclass`, or `Embeddable` class.

Properties defined in `MappedSuperclass` are passed to all inheriting Entities and `MappedSuperclasses`. In case of a conflict, property values defined directly on a class always override values inherited from a class's parent.

When using an `orm.xml` mapping file, EclipseLink ignores `@Property` and `@Properties` annotations on mapped attributes; annotations on classes are merged with those specified in the `orm.xml` file, with the latter taking precedence in case of conflicts.

### Examples

[Example 2–111](#) on page -184 shows how to use the `@Property` annotation within a `@Transformation` mapping. [Example 2–112](#) shows how to use the `<property>` XML element within the `orm.xml` file.

### See Also

For more information, see:

- ["@Properties"](#) on page -140



## @QueryRedirectors

Use `@QueryRedirectors` to intercept EclipseLink queries for pre- and post-processing, redirection, or performing some side effect such as auditing.

### Annotation Elements

[Table 2–57](#) describes this annotation's elements.

**Table 2–57 @QueryRedirectors Annotation Elements**

Annotation Element	Description	Default
<code>allQueries</code>	This <code>AllQueries</code> Query Redirector will be applied to any executing object query that does not have a more precise redirector (like the <code>ReadObjectQuery</code> Redirector) or a redirector set directly on the query.	<code>void.class</code>
<code>delete</code>	A Default <code>Delete</code> Object Query Redirector will be applied to any executing <code>DeleteObjectQuery</code> or <code>DeleteAllQuery</code> that does not have a redirector set directly on the query.	<code>void.class</code>
<code>insert</code>	A Default <code>Insert</code> Query Redirector will be applied to any executing <code>InsertObjectQuery</code> that does not have a redirector set directly on the query.	<code>void.class</code>
<code>readAll</code>	A Default <code>ReadAll</code> Query Redirector will be applied to any executing <code>ReadAllQuery</code> that does not have a redirector set directly on the query.  For users executing a JPA Query through the <code>getResultList()</code> , API this is the redirector that will be invoked	<code>void.class</code>
<code>readObject</code>	A Default <code>ReadObject</code> Query Redirector will be applied to any executing <code>ReadObjectQuery</code> that does not have a redirector set directly on the query.  For users executing a JPA Query through the <code>getSingleResult()</code> API or <code>EntityManager.find()</code> , this is the redirector that will be invoked	<code>void.class</code>
<code>report</code>	A Default <code>ReportQuery</code> Redirector will be applied to any executing <code>ReportQuery</code> that does not have a redirector set directly on the query.  For users executing a JPA Query that contains aggregate functions or selects multiple entities this is the redirector that will be invoked	<code>void.class</code>
<code>update</code>	A Default <code>Update</code> Query Redirector will be applied to any executing <code>UpdateObjectQuery</code> or <code>UpdateAllQuery</code> that does not have a redirector set directly on the query. In EclipseLink an <code>UpdateObjectQuery</code> is executed whenever flushing changes to the datasource.	<code>void.class</code>

### Usage

Use `@QueryRedirectors` to extend the standard EclipseLink query functionality.

You can set a `QueryRedirector` through the `Query Hint` `eclipselink.query.redirector` or set as a default Redirector on an Entity.

### Examples

[Example 2–91](#) shows how to use this annotation.



**Example 2–91 Using @QueryRedirectors Annotation**

```
@QueryRedirectors(  
    allQueries=org.queryredirectors.AllQueriesForEntity.class)  
@Entity  
public class  
...
```

**See Also**

For more information, see:

---

## @RangePartition

Use `@RangePartition` to create a specific range partition for a connection pool. Values within the range will be routed to the specified connection pool.

### Annotation Elements

[Table 2–58](#) describes this annotation's elements.

**Table 2–58** *@RangePartition Annotation Elements*

Annotation Element	Description	Default
<code>connectionPool</code>	The connection pool to which to route queries for the specified range.	
<code>startValue</code>	The String representation of the range start value.	
<code>endValue</code>	The String representation of the range end value.	

### Examples

See [Example 2–83](#) on page -120 for an example of partitioning with EclipseLink.

### See Also

For more information, see:

- "Data Partitioning"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Data\\_Partitioning](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Data_Partitioning)
- "[@Partitioned](#)" on page -120



## @RangePartitioning

Use `@RangePartitioning` to partitions access to a database cluster by a field value from the object (such as the object's ID, location, or tenant).

EclipseLink assigns each server a range of values. All write or read request for objects with a server's value are sent to that specific server. If a query does not include the field as a parameter, then it can either be sent to all server's and unioned, or left to the session's default behavior.

### Annotation Elements

[Table 2–59](#) describes this annotation's elements.

**Table 2–59 @RangePartitioning Annotation Elements**

Annotation Element	Description	Default
name	(Required) The name of the partition policy; must be unique for the persistence unit.	
partitionColumn	(Required) The database column or query parameter to partition queries by. This is the <i>table column name</i> , not the class attribute name. The column value must be included in the query and should normally be part of the object's ID.  This can also be the name of a query parameter. If a query does not contain the field the query will not be partitioned.	
partitions	(Required) List of connection pool names to load balance across.	
partitionValueType	The type of the start and end values.	String
unionunpartitionableQueries	Defines if queries that do not contain the partition field should be sent to every database and have the result unioned.	false

### Usage

Partitioning can be enabled on an Entity, relationship, query, or session/persistence unit.

Partition policies are globally named to allow reuse, the partitioning policy must also be set using the `@Partitioned` annotation to be used.

The persistence unit properties support adding named connection pools in addition to the existing configuration for read/write/sequence. A named connection pool must be defined for each node in the database cluster.

If a transaction modifies data from multiple partitions, you should use JTA ensure proper two-phase commit of the data. You can also configure an exclusive connection in the `EntityManager` to ensure that only a single node is used for a single transaction.

### Examples

[Example 2–92](#) shows how to use the `@RangePartitioning` annotation

**Example 2–92 Using @RangePartitioning Annotation**

```
@Entity
@Table(name="PART_PROJECT")
@RangePartitioning(
```

```

name="RangePartitioningByPROJ_ID",
partitionColumn=@Column(name="PROJ_ID"),
partitionValueType=Integer.class,
unionUnpartitionableQueries=true,
partitions={
    @RangePartition(connectionPool="default", startValue="0", endValue="1000"),
    @RangePartition(connectionPool="node2", startValue="1000", endValue="2000"),
    @RangePartition(connectionPool="node3", startValue="2000")
})
@Partitioned("RangePartitioningByPROJ_ID")
public class Project implements Serializable {
    ...
}

```

[Example 2-92](#) shows how to use the `<range-partitioning>` element in the `eclipselink-orm.xml` file.

### **Example 2-93 Using `<range-partitioning>` XML**

```

<entity name="Project" class="Project" access="FIELD">
    <table name="PART_PROJECT"/>
    <range-partitioning name="RangePartitioningByPROJ_ID"
partition-value-type="java.lang.Integer" union-unpartitionable-queries="true">
        <partition-column name="PROJ_ID"/>
        <partition connection-pool="default" start-value="0" end-value="1000"/>
        <partition connection-pool="node2" start-value="1000" end-value="2000"/>
        <partition connection-pool="node3" start-value="2000"/>
    </range-partitioning>
    <partitioned>RangePartitioningByPROJ_ID</partitioned>
</entity>

```

## **See Also**

For more information, see:

- ["@RangePartition"](#) on page -146
- ["@Partitioned"](#) on page -120

---

## @ReadOnly

Use @ReadOnly to specify that a class is read-only.

### Annotation Elements

This annotation contains no elements.

### Usage

It may be defined on an Entity or MappedSuperclass.

In the case of inheritance, a @ReadOnly annotation can only be defined on the root of the inheritance hierarchy .

You can also use @ReadOnly to bypass EclipseLink's persistence context to save heap space (such as if you need to load a large dataset).

### Examples

[Example 2-94](#) shows how to use this annotation.

#### **Example 2-94 Using @ReadOnly Annotation**

```
@ReadOnly
@Entity
@Table(name = "TMP_READONLY")
public class ReadOnlyEntity {
    ...
}
```

[Example 2-95](#) shows how to use the <read-only> element in the eclipselink-orm.xml file.

#### **Example 2-95 Using <read-only> XML**

```
<entity name="XMLReadOnlyClass" class="ReadOnlyClass" access="PROPERTY"
read-only="true">
```

### See Also

For more information, see:

- ["Entity Annotations"](#) on page 2-2



## @ReadTransformer

Use `@ReadTransformer` with Transformation mappings to define the transformation of the database column values into attribute values (unless the mapping is write-only).

### Annotation Elements

Table 2–60 describes this annotation's elements.

**Table 2–60** *@ReadTransformer Annotation Elements*

Annotation Element	Description	Default
method	The mapped class must have a method with this name which returns a value to be assigned to the attribute (not assigns the value to the attribute).	
transformerClass	User-defined class that implements the <code>org.eclipse.persistence.mappings.transformers.AttributeTransformer</code> interface.  The class will be instantiated, its <code>buildAttributeValue</code> will be used to create the value to be assigned to the attribute.	<code>void.class</code>

---

---

**Note:** You must specify **either** a method or `transformerClass`, but not both.

---

---

### Usage

Also unless it's a read-only mapping, either `@WriteTransformer` annotation or `@WriteTransformers` annotation should be specified. Each `WriteTransformer` defines transformation of the attribute value to a single database column value (column is specified in the `WriteTransformer`).

### Examples

See "[Using @Transformation Annotation](#)" on page -184 for an example of how to use the `@WriteTransformer` annotation with a Transformation mapping.

### See Also

For more information, see:

- "How to Use the `@ReadTransformer` Annotation"  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_%28ELUG%29#How\\_to\\_Use\\_the\\_.40ReadTransformer\\_Annotation](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#How_to_Use_the_.40ReadTransformer_Annotation)
- "[@Transformation](#)" on page -184.





## @ReplicationPartitioning

Use @ReplicationPartitioning to send requests to a set of connection pools. It is for replicating data across a cluster of database machines. Only modification queries are replicated.

### Annotation Elements

[Table 2–61](#) describes this annotation's elements.

**Table 2–61** @ReplicationPartitioning Annotation Elements

Annotation Element	Description	Default
name	The name of the partition policy; must be unique for the persistence unit.	
connectionPools	List of connection pool names to load balance across.	All defined pools in the ServerSession

### Usage

Partitioning can be enabled on an Entity, relationship, query, or session/persistence unit.

Partition policies are globally named to allow reuse, the partitioning policy must also be set using the @Partitioned annotation to be used.

The persistence unit properties support adding named connection pools in addition to the existing configuration for read/write/sequence. A named connection pool must be defined for each node in the database cluster.

If a transaction modifies data from multiple partitions, you should use JTA ensure proper two-phase commit of the data. You can also configure an exclusive connection in the EntityManager to ensure that only a single node is used for a single transaction.

### Examples

See [Example 2–83](#) on page -120 for an example of partitioning with EclipseLink.

### See Also

For more information, see:

- "Data Partitioning"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Data\\_Partitioning](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Data_Partitioning)
- "@Partitioned" on page -120



## @ReturnInsert

Use `@ReturnInsert` to cause `INSERT` operations to return values back into the object being written. This allows for table default values, trigger or stored procedures computed values to be set back into the object.

### Annotation Elements

[Table 2–62](#) describes this annotation's elements.

**Table 2–62** *@ReturnInsert Annotation Elements*

Annotation Element	Description	Default
<code>returnOnly</code>	(Optional) If specified ( <code>true</code> ), the mapping field will be excluded from the <code>INSERT</code> clause during SQL generation.	<code>false</code>

### Usage

A `@ReturnInsert` annotation can only be specified on a `Basic` mapping.

### Examples

[Example 2–96](#) shows how to use the `@ReturnInsert` annotation. If you do not use an argument, `EclipseLink` accepts the default value, `false`.

#### **Example 2–96** *Using @ReturnInsert Annotation*

```
@ReturnInsert(returnOnly=true)
public String getFirstName() {
    return firstName;
}
```

[Example 2–97](#) shows how to use the `<return-insert>` element in the `eclipselink-orm.xml` file.

#### **Example 2–97** *Using <return-insert> XML*

```
<basic name="firstName">
    <column name="FIRST_NAME"/>
    <return-insert read-only="true"/>
</basic>
```

### See Also

For more information, see:

- "How to Use the `@ReturnInsert` Annotation"  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_  
%28ELUG%29#How\\_to\\_Use\\_the\\_.40ReturnInsert\\_Annotation](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#How_to_Use_the_.40ReturnInsert_Annotation)



## @ReturnUpdate

Use @ReturnUpdate to cause UPDATE operations to return values back into the object being written. This allows for table default values, trigger or stored procedures computed values to be set back into the object.

### Annotation Elements

This annotation contains no elements.

### Usage

A @ReturnUpdate annotation can only be specified on a Basic mapping.

### Examples

[Example 2-98](#) shows how to use the @ReturnUpdate annotation. The annotation does not accept any arguments.

#### **Example 2-98 Using @ReturnUpdate Annotation**

```
@ReturnUpdate
public String getFirstName() {
    return firstName;
}
```

[Example 2-99](#) illustrates the same example as before, but uses the <return-update> element in the eclipselink-orm.xml mapping file.

#### **Example 2-99 Using <return-update> XML**

```
<basic name="firstName">
  <column name="F_NAME"/>
  <return-update/>
</basic>
```

### See Also

For more information, see:

- "How to Use the @ReturnInsert Annotation"  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_%28ELUG%29#How\\_to\\_Use\\_the\\_.40ReturnInsert\\_Annotation](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#How_to_Use_the_.40ReturnInsert_Annotation)
- "@ReturnInsert" on page -156



## @RoundRobinPartitioning

Use @RoundRobinPartitioning to send requests in a "round robin" fashion to the set of connection pools.

### Annotation Elements

Table 2–63 describes this annotation's elements.

**Table 2–63** @RoundRobinPartitioning Annotation Elements

Annotation Element	Description	Default
name	(Required) Name of the partition policy. Names must be unique for the persistence unit.	
connectionPools	(Optional) List of connection pool names to load balance across.	All defined pools in the ServerSession
replicateWrite	(Optional) This allows for a set of database to be written to and kept in sync, and have reads load-balanced across the databases.	false

### Usage

Use the @RoundRobinPartitioning annotation for load-balancing read queries across a cluster of database machines. Using @RoundRobinPartitioning requires that the full database be replicated on each machine.

The data should either be read-only, or writes should be replicated on the database.

The persistence unit properties support adding named connection pools in addition to the existing configuration for read/write/sequence. A named connection pool must be defined for each node in the database cluster.

If a transaction modifies data from multiple partitions, you should use JTA ensure proper two-phase commit of the data. You can also configure an exclusive connection in the EntityManager to ensure that only a single node is used for a single transaction.

### Examples

See "[@Partitioned](#)" on page -120 for an example of partitioning with EclipseLink.

### See Also

For more information, see:

- "Data Partitioning"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Data\\_Partitioning](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Data_Partitioning)
- "[@Partitioned](#)" on page -120





---

## @StoredProcedureParameter

---

Use `@StoredProcedureParameter` within a `NamedStoredProcedureQuery` annotation..

### Annotation Elements

[Table 2–64](#) describes this annotation's elements.

**Table 2–64** *@StoredProcedureParameter Annotation Elements*

Annotation Element	Description	Default
<code>queryParameter</code>	(Required) The query parameter name	
<code>direction</code>	(Optional) The direction of the stored procedure parameter: <ul style="list-style-type: none"><li>■ <code>IN</code> – Input parameter</li><li>■ <code>IN_OUT</code> – Input and output parameters</li><li>■ <code>OUT</code> – Output parameter</li><li>■ <code>OUT_CURSOR</code> – Output cursor</li></ul>	<code>IN</code>
<code>jdbcType</code>	(Optional) JDBC type code. This depends on the type returned from the procedure.	<code>-1</code>
<code>jdbcTypeName</code>	(Optional) JDBC type name. This may be required for <code>ARRAY</code> or <code>STRUCT</code> types.	
<code>name</code>	(Optional) Stored procedure parameter name	
<code>optional</code>	(Optional) Specify if the parameter is required, or optional and defaulted by the procedure.	<code>false</code>
<code>type</code>	(Optional) Type of Java class desired back from the procedure. This depends on the type returned from the procedure.	<code>void.class</code>

### Usage

EclipseLink will throw an exception if you set more than one parameter to the `OUT_CURSOR` type.

### Examples

See "[@NamedStoredProcedureQuery](#)" on page -104 for an example using the `@StoredProcedureParameter` annotation.

### See Also

For more information:

- "[@NamedStoredProcedureQuery](#)" on page -104
- Stored Procedure Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/StoredProcedures>



## @Struct

Use @Struct to define a class to map to a database Struct type. The class should normally be an Embeddable, but could also be an Entity if stored in a object table.

### Annotation Elements

[Table 2–65](#) describes this annotation's elements.

**Table 2–65** @Struct Annotation Elements

Annotation Element	Description	Default
name	(Required) The database name of the database structure type.	
fields	(Optional) Defines the order of the fields contained in the database structure type.	

### Usage

Struct types are extended object-relational data-types supported by some databases. Struct types are user define types in the database such as OBJECT types on Oracle. Structs can normally contains Arrays (VARRAY) or other Struct types, and can be stored in a column or a table.

### Examples

[Example 2–100](#) shows using the @Struct annotation to define a Java class to map to an OBJECT type.

#### **Example 2–100** Using @Struct Annotation

```
@Embeddable
@Struct(name="EMP_TYPE", fields={"F_NAME", "L_NAME", "SALARY"})
public class Employee {
    @Column(name="F_NAME")
    private String firstName;
    @Column(name="L_NAME")
    private String lastName;
    @Column(name="SALARY")
    private BigDecimal salary;
    ...
}
```

[Example 2–101](#) shows how to use the <struct> element in the eclipselink-orm.xml file.

#### **Example 2–101** Using <struct> XML

```
<embeddable class="Address" access="FIELD">
  <struct name="PLSQL_P_PLSQL_ADDRESS_REC">
    <field>ADDRESS_ID</field>
    <field>STREET_NUM</field>
    <field>STREET</field>
    <field>CITY</field>
    <field>STATE</field>
  </struct>
  <attributes>
```

```
<basic name="id">
  <column name="ADDRESS_ID" />
</basic>
<basic name="number">
  <column name="STREET_NUM" />
</basic>
</attributes>
</embeddable>
```

## See Also

For more information, see:

- ["@Structure"](#) on page -170

## @StructConverter

The `@StructConverter` annotation is added to an `org.eclipse.persistence.platform.database.DatabasePlatform` using its `addStructConverter` method to enable custom processing of `java.sql.Struct` types.

### Annotation Elements

[Table 2–66](#) describes this annotation's elements.

**Table 2–66** @StructConverter Annotation Elements

Annotation Element	Description	Default
name	The <code>String</code> name for your converter. Ensure that this name is unique across the persistence unit.	none
converter	The converter class as a <code>String</code> . This class must implement the <code>org.eclipse.persistence.mappings.converters.Converter</code> interface.	none

### Usage

A `DatabasePlatform` object holds a structure converter. An `org.eclipse.persistence.database.platform.converters.StructConverter` affects all objects of a particular type read into the `Session` that has that `DatabasePlatform`. This prevents you from configuring the `StructConverter` on a mapping-by-mapping basis. To configure mappings that use the `StructConverter`, you call their `setFieldType(java.sql.Types.STRUCT)` method. You must call this method on all mappings that the `StructConverter` will affect – if you do not call it, errors might occur.

The JPA specification requires all `@Basic` mappings that map to a non-primitive or a non-primitive-wrapper type have a serialized converter added to them. This enables certain `STRUCT` types to map to a field without serialization.

You can use the existing `@Convert` annotation with its value attribute set to the `StructConverter` name – in this case, the appropriate settings are applied to the mapping. This setting is required on all mappings that use a type for which a `StructConverter` has been defined. Failing to configure the mapping with the `@Convert` will cause an error.

EclipseLink also includes [@ObjectTypeConverter](#) and [@TypeConverter](#) converters.

### Examples

[Example 2–102](#) shows how to define the `@StructConverter` annotation.

#### **Example 2–102** Using @StructConverter Annotation

```
@StructConverter(name="MyType",
    converter="myproject.converters.MyStructConverter")
```

You can specify the `@StructConverter` annotation anywhere in an `Entity` with the scope being the whole session. An exception is thrown if you add more than one `StructConverter` annotation that affects the same Java type. An `@StructConverter` annotation exists in the same namespaces as `@Converter`. A validation exception is

thrown if you add an `@Converter` and an `@StructConverter` of the same name. You can also configure structure converters in a `sessions.xml` file.

## See Also

For more information, see:

- ["@StructConverters"](#) on page -168
- "Default Conversions and Converters"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Mapping/Basic\\_Mappings/Default\\_Conversions\\_and\\_Converters/StructConverter](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Mapping/Basic_Mappings/Default_Conversions_and_Converters/StructConverter)

---

## @StructConverters

Use @StructConverters to define multiple @StructConverter annotations.

### Annotation Elements

[Table 2–67](#) describes this annotation's elements.

**Table 2–67** @StructConverters Annotation Elements

Annotation Element	Description	Default
StructConverter[]	(Required) An array of struct converter	

### Examples

[Example 2–103](#) shows how to use the @StructConverters annotation to define multiple @StructConverter elements.

**Example 2–103 Using @StructConverters Annotation**

```
@StructConverters({  
    @StructConverter(name="StructConverter1", converter="foo.StructConverter1"),  
    @StructConverter(name="StructConverter2", converter="foo.StructConverter2")  
})
```

[Example 2–104](#) shows how to use the <struct-converters> element in the eclipselink-orm.xml file.

**Example 2–104 Using <struct-converters> XML**

```
<struct-converters>  
    <struct-converter name="StructConverter1" converter="foo.StructConverter1"/>  
    <struct-converter name="StructConverter2" converter="foo.StructConverter2"/>  
</struct-converters>
```

### See Also

For more information, see:

- ["@StructConverter"](#) on page -166





---

## @Structure

Use @Structure on a field/method to define an `StructureMapping` to an embedded `Struct` type. The target `Embeddable` must be mapped using the `Struct` annotation.

### Annotation Elements

This annotation contains no elements.

### Usage

Struct types are extended object-relational data-types supported by some databases. Struct types are user define types in the database such as `OBJECT` types on Oracle. Structs can normally contains Arrays (`VARRAY`) or other Struct types, and can be stored in a column or a table.

### Examples

[Example 2-105](#) shows how to use the @Structure annotation. See [Example 2-100](#) on page -170 to an example of using @Struct to map the target.

#### **Example 2-105 Using @Structure Annotation**

```
@Structure
protected Address address;
```

You can also define structure mappings in the `eclipselink-orm.xml` file by using the `<structure>` element.

#### **Example 2-106 Using <structure> XML**

```
<structure name="address" />
```

### See Also

For more information, see:

- ["@Struct"](#) on page -164



## @TenantDiscriminatorColumn

The `@TenantDiscriminator` annotation is used with the `@Multitenant` annotation and the `SINGLE-TABLE` multitenant type to limit what a persistence context can access in single-table multitenancy.

### Annotation Elements

[Table 2–68](#) describes this annotation's elements.

**Table 2–68** *@TenantDiscriminatorColumn Properties*

Annotation Element	Description	Default
<code>java.lang.String columnDefinition</code>	(Optional) The SQL fragment that is used when generating the DDL for the discriminator column.	The provider-generated SQL to create a column of the specified discriminator type.
<code>java.lang.String contextProperty</code>	(Optional) The name of the context property to apply to the tenant discriminator column.	<code>eclipselink.tenant-id</code>
<code>DiscriminatorType discriminatorType</code>	(Optional) The type of object/column to use as a class discriminator.	<code>javax.persistence.DiscriminatorType.STRING</code>
<code>int length</code>	(Optional) The column length for String-based discriminator types.	The column length for String-based discriminator types. Ignored for other discriminator types.
<code>java.lang.String name</code>	(Optional) The name of column to be used for the tenant discriminator.	<code>TENANT_ID</code>
<code>boolean primaryKey</code>	Specifies that the tenant discriminator column is part of the primary key of the tables.	<code>false</code>
<code>java.lang.String table</code>	(Optional) The name of the table that contains the column.	The name of the table that contains the column. If absent the column is assumed to be in the primary table. This attribute must be specified if the column is on a secondary table.

### Usage

To configure single-table multi-tenancy, you must specify both of the following:

- Annotate the entity or mapped superclass to use single-table multi-tenancy, using the `@Multitenant` annotation, for example:

```
@Entity
@Table(name="EMP")
@Multitenant(SINGLE_TABLE)
```

`SINGLE_TABLE` states that the table or tables (`Table` and `SecondaryTable`) associated with the given entity can be shared among tenants.

---

**Note:** The `@Table` annotation is not required, because the discriminator column is assumed to be on the primary table. However, if the discriminator column is defined on a secondary table, you must identify that table using `@SecondaryTable`.

---

- Specify the column or columns to be used as the discriminator column, using the `@TenantDiscriminatorColumn` annotation, for example:

```
@Entity
@Table(name="EMP")
@Multitenant(SINGLE_TABLE)
@TenantDiscriminatorColumn(name = "TENANT_ID")
```

You can specify multiple discriminator columns by using the `@TenantDiscriminatorColumns` annotation, for example:

```
@Entity
@Table(name = "EMPLOYEE")
@Multitenant(SINGLE_TABLE)
@TenantDiscriminatorColumns({
    @TenantDiscriminatorColumn(name = "TENANT_ID")
    @TenantDiscriminatorColumn(name = "TENANT_CODE") })
```

## Using Discriminator Columns

The following characteristics apply to discriminator columns:

- On persist, the values of tenant discriminator columns are populated from their associated context properties.
- Tenant discriminator columns are application definable. That is, the discriminator column is not tied to a specific column for each shared entity table. You can use `TENANT_ID`, `T_ID`, etc.
- There is no limit on how many tenant discriminator columns an application can define.
- Any name can be used for a discriminator column.
- Tenant discriminator column(s) must always be used with `@Multitenant(SINGLE_TABLE)`. You cannot specify the tenant discriminator column(s) only.
- Generated schemas can include specified tenant discriminator columns.
- Tenant discriminator columns can be mapped or unmapped:
  - When a tenant discriminator column is mapped, its associated mapping attribute must be marked as read only. With this restriction in place, a tenant discriminator column cannot be part of the entity identifier; it can only be part of the primary key specification on the database.
- Both mapped and unmapped properties are used to form the additional criteria when issuing a `SELECT` query.

## Using Single-Table Multi-Tenancy in an Inheritance Hierarchy

Inheritance strategies are configured by specifying the inheritance type (see `@javax.persistence.Inheritance`). Single-table multi-tenancy can be used in an inheritance hierarchy, as follows:

- Multi-tenant metadata can be applied only at the root level of the inheritance hierarchy when using a `SINGLE_TABLE` or `JOINED` inheritance strategy.
- You can also specify multi-tenant metadata within a `TABLE_PER_CLASS` inheritance hierarchy. In this case, every entity has its own table, with all its mapping data (which is not the case with `SINGLE_TABLE` or `JOINED` strategies). Consequently, in the `TABLE_PER_CLASS` strategy, some entities of the hierarchy may be multi-tenant, while others may not be. The other inheritance strategies can only specify

multi-tenancy at the root level, because you cannot isolate an entity to a single table to build only its type.

## Examples

Table 2–107 shows a number of uses of tenant discriminator columns.

### **Example 2–107 Using @TenantDiscriminatorColumn Annotation**

```
/** Single tenant discriminator column */

@Entity
@Table(name = "CUSTOMER")
@Multitenant
@TenantDiscriminatorColumn(name = "TENANT", contextProperty = "multi-tenant.id")
public Customer() {
    ...
}

/** Multiple tenant discriminator columns using multiple tables */

@Entity
@Table(name = "EMPLOYEE")
@SecondaryTable(name = "RESPONSIBILITIES")
@Multitenant(SINGLE_TABLE)
@TenantDiscriminatorColumns({
    @TenantDiscriminatorColumn(name = "TENANT_ID", contextProperty =
"employee-tenant.id", length = 20)
    @TenantDiscriminatorColumn(name = "TENANT_CODE", contextProperty =
"employee-tenant.code", discriminatorType = STRING, table = "RESPONSIBILITIES")
})
public Employee() {
    ...
}

/** Tenant discriminator column mapped as part of the primary key on the database
**/

@Entity
@Table(name = "ADDRESS")
@Multitenant
@TenantDiscriminatorColumn(name = "TENANT", contextProperty = "tenant.id",
primaryKey = true)
public Address() {
    ...
}

/** Mapped tenant discriminator column */

@Entity
@Table(name = "Player")
@Multitenant
@TenantDiscriminatorColumn(name = "AGE", contextProperty = "tenant.age")
public Player() {
    ...
}
```

```

@Basic
@Column(name="AGE", insertable="false", updatable="false")
public int age;
}

```

[Example 2-108](#) shows the same mappings, using the `<tenant-discriminator-column>` XML element in the `eclipselink-orm.xml` file.

**Example 2-108 Using `<tenant-discriminator-column>` XML**

```

<!-- Single tenant discriminator column -->

<entity class="model.Customer">
  <multitenant>
    <tenant-discriminator-column name="TENANT"
context-property="multi-tenant.id" />
  </multitenant>
  <table name="CUSTOMER" />
  ...
</entity>

<!-- Multiple tenant discriminator columns using multiple tables -->

<entity class="model.Employee">
  <multitenant type="SINGLE_TABLE">
    <tenant-discriminator-column name="TENANT_ID"
context-property="employee-tenant.id" length="20" />
    <tenant-discriminator-column name="TENANT_CODE"
context-property="employee-tenant.id" discriminator-type="STRING"
table="RESPONSIBILITIES" />
  </multitenant>
  <table name="EMPLOYEE" />
  <secondary-table name="RESPONSIBILITIES" />
  ...
</entity>

<!-- Tenant discriminator column mapped as part of the primary key on the database
-->

<entity class="model.Address">
  <multitenant>
    <tenant-discriminator-column name="TENANT" context-property="multi-tenant.id"
primary-key="true" />
  </multitenant>
  <table name="ADDRESS" />
  ...
</entity>

<!-- Mapped tenant discriminator column -->

<entity class="model.Player">
  <multi-tenant>
    <tenant-discriminator-column name="AGE" context-property="tenant.age" />
  </multi-tenant>

```

```
<table name="PLAYER"/>
...
<attributes>
  <basic name="age" insertable="false" updatable="false">
    <column name="AGE"/>
  </basic>
  ...
</attributes>
...
</entity>
```

## See Also

- ["@Multitenant"](#) on page 82
- ["@TenantDiscriminatorColumns"](#) on page 178
- ["@TenantTableDiscriminator"](#) on page 180
- 
- Multitenant Examples at <http://wiki.eclipse.org/EclipseLink/Examples/JPA/Multitenant>





## @TenantDiscriminatorColumns

Specify multiple discriminator columns for single-table multitenancy by using the `@TenantDiscriminatorColumns` annotation to contain multiple `@TenantDiscriminatorColumn` annotations.

### Annotation Elements

[Table 2–69](#) describes this annotation's elements.

**Table 2–69** @TenantDiscriminatorColumns Annotation Elements

Annotation Element	Description	Default
<code>TenantDiscriminatorColumn</code> value	(Optional) One or more <code>TenantDiscriminatorColumn</code> annotations.	none

### Usage

You must use the `@TenantDiscriminatorColumns` annotation to contain multiple `@TenantDiscriminatorColumn` annotations. The `@TenantDiscriminatorColumns` annotation cannot be used alone, and multiple the `@TenantDiscriminatorColumn` annotations cannot be used alone, without `@TenantDiscriminatorColumns`.

### Examples

```
@Entity
@Table(name = "EMPLOYEE")
@Multitenant(SINGLE_TABLE)
@TenantDiscriminatorColumns({
    @TenantDiscriminatorColumn(name = "TENANT_ID", contextProperty = "tenant-id")
    @TenantDiscriminatorColumn(name = "TENANT_CODE", contextProperty =
"tenant-code")})
```

See "[@TenantDiscriminatorColumn](#)" on page -172 for more examples of `@TenantDiscriminatorColumns`.

### See Also

- "[@Multitenant](#)" on page -82
- "[@TenantDiscriminatorColumn](#)" on page -172
- "[@TenantTableDiscriminator](#)" on page -180



## @TenantTableDiscriminator

Table-per-tenant multitenancy allows multiple tenants of an application to isolate their data in one or more tenant-specific tables. The tenant table discriminator specifies how to discriminate the tenant's tables from the other tenants' tables in a table-per-tenant multitenancy strategy.

### Annotation Elements

Table 2–70 describes this annotation's elements.

**Table 2–70** @TenantTableDiscriminator Annotation Elements

Annotation Element	Description	Default
java.lang.String ContextProperty	(Optional) Name of the context property to apply to as tenant table discriminator	eclipselink-tenant.id
TenantTableDiscriminat or type	(Optional) Type of tenant table discriminator to use with the tables of the persistence unit. <ul style="list-style-type: none"> <li>■ SCHEMA</li> <li>■ SUFFIX</li> <li>■ PREFIX</li> </ul>	org.eclipse.persistence.an notations.TenantTableDiscr iminatorsType.SUFFIX

### Usage

In table-per-tenant multitenancy, tenants' tables can be in the same schema, using a prefix or suffix naming pattern to distinguish them; or they can be in separate schemas. The tenant table discriminator identifies whether to use the prefix or suffix naming pattern or to use a separate schema to identify and isolate the tenant's tables from other tenants' tables. The types are:

- **Schema:** Applies the tenant table discriminator as a schema to all multitenant tables. This strategy requires appropriate database provisioning.
- **Suffix:** Applies the tenant table discriminator as a suffix to all multitenant tables. This is the default strategy.
- **Prefix:** Applies the tenant table discriminator as a prefix to all multitenant tables.

Tenant table discriminator can be specified at the entity or mapped superclass level and must always be used with `Multitenant(TABLE_PER_TENANT)`. It is not sufficient to specify only a tenant table discriminator.

For more information about using @TenantTableDiscriminator and table-per-tenant multitenancy, see "[@Multitenant](#)" on page -82.

### Examples

The following example shows a SCHEMA-type table discriminator.

**Example 2–109** Using @TenantTableDiscriminator Annotation

```
@Entity
@Table(name="EMP")
@Multitenant(TABLE_PER_TENANT)
@TenantTableDiscriminator(type=SCHEMA, contextProperty="eclipselink-tenant.id")
public class Employee {
    ...
}
```

```
}
```

**Example 2–110 Using <tenant-table-discriminator> XML**

```
<entity class="Employee">
  <multitenant type="TABLE_PER_TENANT">
    <tenant-table-discriminator type="SCHEMA"
context-property="eclipselink-tenant.id"/>
  </multitenant>
  <table name="EMP">
    ...
  </table>
</entity>
```

**See Also**

- ["@Multitenant"](#) on page 82
- ["@TenantDiscriminatorColumn"](#) on page 172
- ["@TenantDiscriminatorColumns"](#) on page 178
- 
- Multitenant Examples at <http://wiki.eclipse.org/EclipseLink/Examples/JPA/Multitenant>

---

## @TimeOfDay

Use @TimeOfDay to specify a specific time of day using a Calendar instance which is to be used within an @OptimisticLocking annotation.

### Annotation Elements

Table 2–71 describes this annotation's elements.

**Table 2–71** @TimeOfDay Annotation Elements

Annotation Element	Description	Default
hour	(Optional) Hour of the day	0
millisecond	(Optional) Millisecond of the day	0
minute	(Optional) Minute of the day	0
second	(Optional) Second of the day	0
specified	For internal use – do not modify	true

### Examples

See "[@Cache](#)" on page -16 for examples of using @TimeOfDay.

### See Also

For more information, see:

- "[@ExistenceChecking](#)" on page -56
- "[@Cache](#)" on page -16
- "How to Use the @TimeOfDay Annotation"  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_%28ELUG%29#How\\_to\\_Use\\_the\\_.40TimeOfDay\\_Annotation](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#How_to_Use_the_.40TimeOfDay_Annotation)
- "Cache Expiration and Invalidation"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Expiration](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Expiration)



## @Transformation

Use `@Transformation` with a Transformation mapping to define the transformation of database columns into attribute values (unless the Transformation mapping is write-only, in which case it should have a `@ReadTransformer` annotation).

### Annotation Elements

[Table 2–72](#) describes this annotation's elements.

**Table 2–72 @Transformation Annotation Elements**

Annotation Element	Description	Default
fetch	(Optional) Defines whether the value of the field or property should be lazily loaded or must be eagerly fetched. <ul style="list-style-type: none"> <li>The <code>EAGER</code> strategy is a requirement on the persistence provider runtime that the value must be eagerly fetched.</li> <li>The <code>LAZY</code> strategy is a hint to the persistence provider runtime.</li> </ul>	EAGER
optional	(Optional) A hint as to whether the value of the field or property may be null. It is disregarded for primitive types, which are considered non-optional.	true

### Usage

Unless it's a read-only mapping, either `WriteTransformer` annotation or `WriteTransformers` annotation should be specified. Each `WriteTransformer` defines transformation of the attribute value to a single database column value (column is specified in the `WriteTransformer`).

### Examples

[Example 2–111](#) shows how to use the `@Transformation` annotation.

#### Example 2–111 Using @Transformation Annotation

```
@Transformation(fetch=FetchType.LAZY, optional="true")
@ReadTransformer(class=package.MyNormalHoursTransformer.class)
@WriteTransformers({
    @WriteTransformer(column=@Column(name="START_TIME"),
        method="getStartDate"),
    @WriteTransformer(column=@Column(name="END_TIME"),
        class=package.MyTimeTransformer.class)
})
@Mutable
@ReturnUpdate
@Access(AccessType.PROPERTY)
@AccessMethods(get="getNormalHours", set="setNormalHours")
@Properties({
    @Property(name="x", value="y")
})
```

[Example 2–112](#) shows the same mapping, using the `<transformation>` XML element in the `eclipselink-orm.xml` file.

#### Example 2–112 Using <transformation> XML

```
<transformation name="normalHours" fetch="LAZY" optional="true">
  <read-transformer method="buildNormalHours"/>
```



```
<write-transformer method="getStartTime">
    <column name="START_TIME" />
</write-transformer>
<write-transformer class="package.MyTimeTransformer">
    <column name="END_TIME" />
</write-transformer>
<mutable/>
<return-update/>
<access type="PROPERTY"/>
<access-methods get="getNormalHours" set="setNormalHours"/>
<properties>
    <property name="x" value="y"/>
</properties>
</transformation>
```

## See Also

For more information, see:

- ["@WriteTransformer"](#) on page -202
- ["@ReadTransformer"](#) on page -152
- ["How to Use the @Transformation Annotation"](#)  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_  
%28ELUG%29#How\\_to\\_Use\\_the\\_.40Transformation\\_Annotation](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#How_to_Use_the_.40Transformation_Annotation)

## @TypeConverter

Use `@TypeConverter` to modify data values during the reading and writing of a mapped attribute.

### Annotation Elements

[Table 2–73](#) describes this annotation's elements.

**Table 2–73** @TypeConverter Annotation Elements

Annotation Element	Description	Default
name	(Required) The <code>String</code> name for your converter. This name must be unique across the persistence unit.	none
dataType	(Optional) The type stored in the database.	<code>void.class</code> <sup>1</sup>
objectType	(Optional) The type stored on the entity.	<code>void.class</code> <sup>1</sup>

<sup>1</sup> The default is inferred from the type of the persistence field or property.

### Usage

Each `TypeConverter` must be uniquely named and can be defined at the class, field and property level and can be specified within an `Entity`, `MappedSuperclass` and `Embeddable` class. A `TypeConverter` is always specified by using an `@Convert` annotation.

You can place a `@TypeConverter` on a `Basic`, `BasicMap` or `BasicCollection` mapping. EclipseLink also includes `@ObjectConverter` and `@StructConverter` converters.

### Examples

[Example 2–113](#) shows how to use the `@TypeConverter` annotation to convert the `Double` value stored in the database to a `Float` value stored in the entity.

#### **Example 2–113** Using the @TypeConverter Annotation

```
@Entity
public class Employee implements Serializable{

    ...

    @TypeConverter (
        name="doubleToFloat",
        dataType=Double.class,
        objectType=Float.class,
    )
    @Convert("doubleToFloat")
    public Number getGradePointAverage() {
        return gradePointAverage;
    }

    ...
}
```

## See Also

For more information, see:

- ["@Convert"](#) on page -40
- ["@TypeConverters"](#) on page -188
- [@TypeConverter](#)  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Mapping/Basic\\_Mappings/Default\\_Conversions\\_and\\_Converters/TypeConverter](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Mapping/Basic_Mappings/Default_Conversions_and_Converters/TypeConverter)
- ["How to Use the @TypeConverter Annotation"](#)  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_%28ELUG%29#How\\_to\\_Use\\_the\\_.40TypeConverter\\_Annotation](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#How_to_Use_the_.40TypeConverter_Annotation)
- ["Default Conversions and Converters"](#)  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Mapping/Basic\\_Mappings/Default\\_Conversions\\_and\\_Converters](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Mapping/Basic_Mappings/Default_Conversions_and_Converters)

## @TypeConverters

Use @TypeConverters to define multiple TypeConverter elements.

### Annotation Elements

Table 2–74 describes this annotation's elements.

**Table 2–74** @TypeConverters Annotation Elements

Annotation Element	Description	Default
TypeConverter[]	(Required) An array of type converter.	

### Examples

Example 2–114 shows how to use this annotation.

#### **Example 2–114** Using @TypeConverters Annotation

```
@Entity
@TypeConverters({

    @TypeConverter(name="BigIntegerToString",dataType=String.class,objectType=BigInteg
er.class)
})
public class Parameters implements Serializable {
    private static final long serialVersionUID = -1979843739878183696L;
    @Column(name="maxValue", nullable=false, length=512)
    @Convert("BigIntegerToString")
    private BigInteger maxValue;
    ...
}
```

Example 2–114 shows how to use the <type-converters> element in the eclipselink-orm.xml file.

#### **Example 2–115** Using <type-converters> XML

```
<type-converters>
    <type-converter name="Long2String" data-type="String" object-type="Long"/>
    <type-converter name="String2String" data-type="String" object-type="String"/>
</type-converters>
<entity class="Employee">
    ...
</entity>
```

### See Also

For more information, see:

- "[@TypeConverter](#)" on page -186
- "How to Use the @TypeConverter Annotation"  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_  
%28ELUG%29#How\\_to\\_Use\\_the\\_.40TypeConverter\\_Annotation](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#How_to_Use_the_.40TypeConverter_Annotation)



## @UuidGenerator

Use `@UuidGenerator` to defines a primary key generator that may be referenced by name when a generator element is specified for the `@GeneratedValue` annotation. A UUID (universally unique identifier) generator may be specified on the entity class or on the primary key field or property.

The generator name is global to the persistence unit (that is, across all generator types).

### Annotation Elements

[Table 2–75](#) describes this annotation's elements.

**Table 2–75 @UuidGenerator Annotation Elements**

Annotation Element	Description	Default
name	Name of the UUID generator, must be unique for the persistence unit	

### Examples

[Example 2–116](#) shows how to use this annotation.

**Example 2–116 Using @UuidGenerator Annotation**

```
@Entity
@UuidGenerator(name="EMP_ID_GEN")
public class Employee {
    @Id
    @GeneratedValue(generator="EMP_ID_GEN")
    private String id;
}
```

You can also specify the `SessionCustomizer` and configure the named sequence in your `eclipselink-orm.xml` file, as shown in [Example 2–117](#).

**Example 2–117 Using <generated-value> XML**

```
<id name="id">
    <column name="PROJ_ID" />
    <generated-value generator="system-uuid"/>
</id>
```

You can also specify the named sequence at the persistence unit level (in the `persistence.xml` file) as shown in [Example 2–118](#).

**Example 2–118 Specifying Generator in persistence.xml**

```
<property name="eclipselink.session.customizer"
value="eclipselink.example.UUIDSequence"/>
```

### See Also

For more information, see:

- @Generated Value  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Entities/Ids/GeneratedValue](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Entities/Ids/GeneratedValue)
- "Entity Annotations" on page 2-2

## @UnionPartitioning

Use `@UnionPartitioning` to send queries to all connection pools and then union the results. This can be used for queries or relationships that span partitions when partitioning is used, such as on a ManyToMany cross partition relationship.

### Annotation Elements

[Table 2–76](#) describes this annotation's elements.

**Table 2–76** *@UnionPartitioning Annotation Elements*

Annotation Element	Description	Default
name	Name of the partition policy. Names must be unique for the persistence unit.	
connectionPools	List of connection pool names to load balance across	Defaults to all defined pools in the <code>ServerSession</code>
replicateWrite	Defines if write queries should be replicated.  Writes are normally not replicated when unioning, but can be for ManyToMany relationships, when the join table needs to be replicated.	false

### Usage

Partitioning can be enabled on an Entity, relationship, query, or session/persistence unit. Partition policies are globally named to allow reuse, the partitioning policy must also be set using the `@Partitioned` annotation to be used.

The persistence unit properties support adding named connection pools in addition to the existing configuration for read/write/sequence. A named connection pool must be defined for each node in the database cluster.

If a transaction modifies data from multiple partitions, you should use JTA ensure proper two-phase commit of the data. You can also configure an exclusive connection in the `EntityManager` to ensure that only a single node is used for a single transaction.

### Examples

See [Example 2–83](#) on page -120 for an example of partitioning with EclipseLink.

### See Also

For more information, see:

- "Data Partitioning"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Data\\_Partitioning](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Data_Partitioning)
- "[@Partitioned](#)" on page -120





## @ValuePartition

Use @ValuePartition to represent a specific value partition that will be routed to a specific connection pool.

### Annotation Elements

[Table 2–77](#) describes this annotation's elements.

**Table 2–77** @ValuePartition Annotation Elements

Annotation Element	Description	Default
connectionPool	The connection pool to which to route queries to for the value	
value	The String representation of the value	

### Examples

[Example 2–119](#) shows how to use the @ValuePartition and @ValuePartitioning annotations.

#### **Example 2–119 Using @ValuePartition Annotation**

```
@Entity
@Table(name = "PART_EMPLOYEE")
@IdClass(EmployeePK.class)
@ValuePartitioning(
    name="ValuePartitioningByLOCATION",
    partitionColumn=@Column(name="LOCATION"),
    unionUnpartitionableQueries=true,
    defaultConnectionPool="default",
    partitions={
        @ValuePartition(connectionPool="node2", value="Ottawa"),
        @ValuePartition(connectionPool="node3", value="Toronto")
    })
@Partitioned("ValuePartitioningByLOCATION")
public class Employee implements Serializable, Cloneable {
    ...
}
```

[Example 2–120](#) shows how to use the <partition> element in the eclipselink-orm.xml file.

#### **Example 2–120 Using <partition> XML**

```
<entity name="Employee" class="Employee" access="FIELD">
  <table name="PART_EMPLOYEE"/>
  <id-class class="EmployeePK"/>
  <value-partitioning name="ValuePartitioningByLOCATION"
    union-unpartitionable-queries="true" default-connection-pool="default">
    <partition-column name="LOCATION"/>
    <partition connection-pool="node2" value="Ottawa"/>
    <partition connection-pool="node3" value="Toronto"/>
  </value-partitioning>
</partitioned>ValuePartitioningByLOCATION</partitioned>
```

## See Also

For more information, see:

- ["@Partitioned"](#) on page -120
- ["@ValuePartitioning"](#) on page -196

## @ValuePartitioning

Use `@ValuePartitioning` to partition access to a database cluster by a field value from the object (such as the object's location or tenant). Each value is assigned a specific server. All write or read request for object's with that value are sent to the server. If a query does not include the field as a parameter, then it can either be sent to all server's and unioned, or left to the session's default behavior.

### Annotation Elements

[Table 2–78](#) describes this annotation's elements.

**Table 2–78 @ValuePartitioning Annotation Elements**

Annotation Element	Description	Default
name	(Required) Name of the partition policy. Names must be unique for the persistence unit.	
partitionColumn	(Required) The database column or query parameter to partition queries by  This is the table column name, not the class attribute name. The column value must be included in the query and should normally be part of the object's ID. This can also be the name of a query parameter.  If a query does not contain the field the query will not be partitioned.	
partitions	(Required) Store the value partitions. Each partition maps a value to a <code>connectionPool</code> .	
defaultConnectionPool	(Optional) The default connection pool is used for any unmapped values	
partitionValueType	(Optional) The type of the start and end values	String
unionUnpartitionableQueries	(Optional) Defines if queries that do not contain the partition field should be sent to every database and have the result unioned.	false

### Usage

Partitioning can be enabled on an Entity, relationship, query, or session/persistence unit. Partition policies are globally named to allow reuse, the partitioning policy must also be set using the `@Partitioned` annotation to be used.

The persistence unit properties support adding named connection pools in addition to the existing configuration for read/write/sequence. A named connection pool must be defined for each node in the database cluster.

If a transaction modifies data from multiple partitions, you should use JTA ensure proper two-phase commit of the data. You can also configure an exclusive connection in the `EntityManager` to ensure that only a single node is used for a single transaction.

### Examples

See [Example 2–83](#) on page -120 for an example of partitioning with EclipseLink.

### See Also

For more information, see:

- "Data Partitioning"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Data\\_Partitioning](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Data_Partitioning)
- "@Partitioned" on page -120

## @VariableOneToOne

Use `@VariableOneToOne` to represent a pointer references between a java object and an implementer of an interface. This mapping is usually represented by a single pointer (stored in an instance variable) between the source and target objects. In the relational database tables, these mappings are normally implemented using a foreign key and a type code.

### Annotation Elements

[Table 2–79](#) describes this annotation's elements.

**Table 2–79** @VariableOneToOne Annotation Elements

Annotation Element	Description	Default
CascadeType	(Optional) Array of operations that must be cascaded to the target of the association.	
DiscriminatorClasses	(Optional) Array of discriminator types that can be used with this mapping.	If none are specified, EclipseLink adds entities within the persistence unit that implement the target interface.  If DiscriminatorColumn is <code>STRING</code> , EclipseLink uses <code>Entity.name()</code> .  If DiscriminatorColumn is <code>CHAR</code> , EclipseLink uses the first letter of the entity class.  If DiscriminatorColumn is <code>INTEGER</code> , EclipseLink uses the next integer after the highest integer explicitly stated.
DiscriminatorColumn	(Optional) The discriminator column that contains the type identifiers.	<code>DTYPE</code>
FetchType	(Optional) Specify how the value of the field or property should be loaded: <ul style="list-style-type: none"><li>▪ <b>Eager:</b> Requires that the persistence provider runtime must eagerly fetch the value</li><li>▪ <b>Lazy:</b> Hints that the persistence provider should lazily load the value</li></ul>	<code>Eager</code>
Optional	(Optional) Specify if the association is optional.	
OrphanRemoval	(Optional) Specify if interface class that is the target of this mapping.	
TargetInterface	(Optional) The interface class that is the target of this mapping.	If none is specified, EclipseLink will infer the interface class based on the type of object being referenced.

### Usage

You can specify `@VariableOneToOne` on an Entity, MappedSuperclass, or Embeddable class.

### Examples

[Example 2–121](#) shows how to use the `@VariableOneToOne` annotation.

**Example 2-121 Using @VariableOneToOne Annotation**

```

@VariableOneToOne(
    cascade={ALL},
    fetch=LAZY,
    discriminatorColumn=@DiscriminatorColumn(name="CONTACT_TYPE"),
    discriminatorClasses={
        @DiscriminatorClass(discriminator="E", value="Email.class"),
        @DiscriminatorClass(discriminator="P", value="Phone.class")
    }
)
@JoinColumn(name="CONTACT_ID", referencedColumnName="C_ID")
@PrivateOwned
@JoinFetch(INNER)
public Contact getContact() {
    return contact;
}

```

Example 2-122 shows the same mapping using the <variable-one-to-one> XML element in the eclipselink-orm.xml file.

**Example 2-122 Using <variable-one-to-one> XML**

```

<variable-one-to-one name="contact" fetch="LAZY">
    <cascade>
        <cascade-all/>
    </cascade>
    <discriminator-column name="CONTACT_TYPE"/>
    <discriminator-class discriminator="E" value="Email.class"/>
    <discriminator-class discriminator="P" value="Phone.class"/>
    <join-column name="CONTACT_ID" referenced-column-name="C_ID"/>
    <private-owned/>
    <join-fetch>INNER</join-fetch>
</variable-one-to-one>

```

**See Also**

For more information, see:

- "[@DiscriminatorClass](#)" on page -52
- "How to Use the @VariableOneToOne Annotation"  
[http://wiki.eclipse.org/Using\\_EclipseLink\\_JPA\\_Extensions\\_%28ELUG%29#How\\_to\\_Use\\_the\\_.40VariableOneToOne\\_Annotation](http://wiki.eclipse.org/Using_EclipseLink_JPA_Extensions_%28ELUG%29#How_to_Use_the_.40VariableOneToOne_Annotation)
- "Variable One-To-One Mapping"  
[http://wiki.eclipse.org/Introduction\\_to\\_Relational\\_Mappings\\_%28ELUG%29#Variable\\_One-to-One\\_Mapping](http://wiki.eclipse.org/Introduction_to_Relational_Mappings_%28ELUG%29#Variable_One-to-One_Mapping)

## @VirtualAccessMethods

Use @VirtualAccessMethods to specify that a specific class contains virtual methods.

### Annotation Elements

[Table 2–80](#) describes this annotation's elements.

**Table 2–80** @VirtualAccessMethods Annotation Elements

Annotation Element	Description	Default
get	(Optional) Name of the <code>getter</code> method to use for the virtual property. This method must take a single <code>java.lang.String</code> parameter and return a <code>java.lang.Object</code> .  If <code>get</code> is specified, you must also specify <code>set</code> .	get
set	(Optional) Name of the <code>setter</code> method to use for the virtual property. This method must take a <code>java.lang.String</code> parameter and a <code>java.lang.Object</code> parameter.  If <code>set</code> is specified, you must also specify <code>get</code> .	set

### Usage

Use the @VirtualAccessMethods annotation to define access methods for mappings with in which `accessType=VIRTUAL`.

### Examples

[Table 2–80](#) shows an entity using property access.

**Example 2–123** Using @VirtualAccessMethods Annotation

```
@Entity
@VirtualAccessMethods
public class Customer{

    @Id
    private int id;
    ...

    @Transient
    private Map<String, Object> extensions;

    public <T> T get(String name) {
        return (T) extensions.get(name);
    }

    public Object set(String name, Object value) {
        return extensions.put(name, value);
    }
}
```

In addition to using the @VirtualAccessMethods annotation, you can use the `<access>` and `<access-method>` elements in your `eclipselink-orm.xml` file, as shown in [Example 2–124](#).

**Example 2–124** Using <access> and <access-methods> XML

```
<access>VIRTUAL</access>
```



```
<access-methods get-method="get" set-method="set"/>@Entity
```

## See Also

For more information, see:

- "Extensible Entities"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Extensible\\_Entities](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Extensible_Entities)

## @WriteTransformer

Use `@WriteTransformer` on a `TransformationMapping` to transform a single attribute value to a single database column value. Use the `@WriteTransformers` annotation to wrap multiple transformations.

### Annotation Elements

[Table 2–81](#) describes this annotation's elements.

**Table 2–81** @WriteTransformer Annotation Elements

Annotation Element	Description	Default
column	(Optional) The column into which the value should be written.  If a single <code>WriteTransformer</code> annotates an attribute, the attribute's name will be used as the column name.	<code>@javax.persistence.Column</code>
method	(Optional) The <code>String</code> method name that the mapped class must have. This method returns the value to be written into the database column.  <b>Note:</b> To support DDL generation and returning policy, the method should be defined to return a particular type, not just an <code>Object</code> . For example: <code>public Time getStartTime()</code>  The method may require <code>@Transient</code> to avoid being mapped as a <code>Basic</code> by default.	
transformerClass	(Optional) User-defined class that implements the <code>FieldTransformer</code> interface. This will instantiate the class and use its <code>buildFieldValue</code> method to create the value to be written into the database column.  <b>Note:</b> To support DDL generation and returning policy, the method <code>buildFieldValue</code> in the class should be defined to return the relevant Java type, not just <code>Object</code> as defined in the interface. For example: <code>public Time buildFieldValue(Object instance, String fieldName, Session session).</code>	<code>void.class</code>

---

---

**Note:** You must specify either `transformerClass` or `method`, but not both.

---

---

### Usage

You cannot define a `@WriteTransformer` for a read-only mapping.

Unless the `TransformationMapping` is write-only, it should include a `ReadTransformer` that defines the transformation of the database column values into attribute values.

### Configuring Field Transformer Associations

Using a `FieldTransformer` is non-intrusive; your domain object does not need to implement an `EclipseLink` interface or provide a special transformation method.

You can configure a method-based field transformer using `AbstractTransformationMapping` method `addFieldTransformation`, passing in the name of the database field and the name of the domain object method to use.

You can configure a class-based field transformer using `AbstractTransformationMapping` method `addFieldTransformer`, passing in the name of the database field and an instance of `org.eclipse.persistence.mappings.Transformers.FieldTransformer`.

A convenient way to create a `FieldTransformer` is to extend `FieldTransformerAdapter`.

## Examples

See "[Using @Transformation Annotation](#)" on page -184 for an example of how to use the `@WriteTransformer` annotation with a Transformation mapping.

## See Also

For more information, see:

- "[@WriteTransformers](#)" on page -204
- "[@Transformation](#)" on page -184.
- [http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Print\\_Version#How\\_to\\_Use\\_the\\_.40Transformation\\_Annotation](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Print_Version#How_to_Use_the_.40Transformation_Annotation)

---

## @WriteTransformers

Use `@WriteTransformer` on a `TransformationMapping` to transform a single attribute value to a single database column value. Use the `@WriteTransformers` annotation to wrap multiple transformations.

### Annotation Elements

[Table 2–82](#) describes this annotation's elements.

**Table 2–82** @WriteTransformers Annotation Elements

Annotation Element	Description	Default
<code>WriteTransformer</code>	An array of <code>WriteTransformer</code>	

### Usage

You cannot use `@WriteTransformers` for a read-only mapping.

### Examples

See "[Using @Transformation Annotation](#)" on page -184 for an example of how to use the `@WriteTransformer` annotation with a Transformation mapping.

### See Also

For more information, see:

- "[@WriteTransformer](#)" on page -202.
- "[@Transformation](#)" on page -184.
- [http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Print\\_Version#How\\_to\\_Use\\_the\\_40Transformation\\_Annotation](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Print_Version#How_to_Use_the_40Transformation_Annotation)

---

## Java Persistence Query Language Extensions

EclipseLink provides many extensions to the standard JPA Java Persistence Query Language (JPQL). These extensions, referred to as the EclipseLink Query Language (EQL), provide access to additional database features many of which are part of standard SQL, provide access to native database features and functions, and provide access to EclipseLink specific features.

This chapter contains the following sections:

- [Special Operators](#)
- [EclipseLink Query Language](#)

For more information on JQPL, see:

- "Query Language" in the JPA Specification (<http://jcp.org/en/jsr/detail?id=317>)
- "The Java Persistence Query Language" in *The Java EE 6 Tutorial* (<http://docs.oracle.com/javaee/6/tutorial/doc/bnbtg.html>)

### Special Operators

EclipseLink defines the following operators to perform database operations that would not be possible in standard JPQL:

- [COLUMN](#)
- [FUNCTION](#)
- [OPERATOR](#)
- [SQL](#)

### EclipseLink Query Language

The following lists the EQL extensions to JPQL:

- [CAST](#)
- [EXCEPT](#)
- [EXTRACT](#)
- [INTERSECT](#)
- [ON](#)

- [REGEXP](#)
- [TABLE](#)
- [TREAT](#)
- [UNION](#)



---

## CAST

Use CAST to convert a value to a specific database type.

### Usage

The CAST function is database independent, but requires database support.

### Examples

[Example 3-1](#) shows how to use this JPQL extension.

***Example 3-1 Using CAST EQL***

```
CAST(e.salary NUMERIC(10,2))
```

### See Also

For more information, see:

- "JPQL"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/JPQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/JPQL)
-





## COLUMN

---

Use `COLUMN` to access to unmapped columns in an object's table.

### Usage

You can use `COLUMN` to access foreign key columns, inheritance discriminators, or primitive columns (such as `ROWID`). You can also use `COLUMN` in JPQL fragments inside the `@AdditionalCriteria` annotation.

### Examples

[Example 3–2](#) shows how to use the `COLUMN` EQL.

**Example 3–2 Using `COLUMN` EQL**

```
SELECT e FROM Employee e WHERE COLUMN('MANAGER_ID', e) = :id
```

In [Example 3–3](#), uses `COLUMN` EQL access a primitive column (`ROWID`).

**Example 3–3 Using `COLUMN` with a Primitive Column**

```
SELECT e FROM Employee e WHERE COLUMN('ROWID', e) = :id
```

### See Also

For more information, see:

- ["@AdditionalCriteria"](#) on page -8
- ["JPQL"](#)  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/JPQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/JPQL)



---

## EXCEPT

When performing multiple queries, use `EXCEPT` to remove the results of a second query from the results of a first query.

### Usage

The `EXCEPT` function is database independent, but requires database support.

### Examples

[Example 3–4](#) shows how to use this JPQL extension.

***Example 3–4 Using EXCEPT EQL***

```
SELECT e FROM Employee e
EXCEPT SELECT e FROM Employee e WHERE e.salary > e.manager.salary
```

### See Also

For more information, see:

- ["UNION"](#) on page -30
- ["INTERSECT"](#) on page -14
- ["JPQL"](#)  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/JPQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/JPQL)



---

## EXTRACT

Use `EXTRACT` to retrieve the date portion of a date/time value.

### Usage

The `EXTRACT` function is database independent, but requires database support

### Examples

[Example 3–5](#) shows how to use this JPQL extension.

***Example 3–5 Using EXTRACT EQL***

```
EXTRACT(YEAR, e.startDate)
```

### See Also

For more information, see:

- "JPQL"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/JPQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/JPQL)
-



---

## FUNCTION

Use `FUNCTION` (formerly `FUNC`) to call database specific functions from JPQL

### Usage

You can use `FUNCTION` to call database functions that are not supported directly in JPQL and to call user or library specific functions.

---

---

**Note:** `FUNCTION` is database specific – it does not translate the function call in any way to support different databases as other JPQL functions do.

---

---

Use `FUNCTION` to call functions with normal syntax. Functions that require special syntax cannot be called with `FUNCTION`. Instead, use [OPERATOR](#)

### Examples

[Example 3–6](#) shows how to use this JPQL extension.

**Example 3–6 Using `FUNCTION` EQL**

```
SELECT p FROM Phone p WHERE FUNCTION('TO_NUMBER', e.areaCode) > 613

SELECT FUNCTION('YEAR', e.startDate) AS year, COUNT(e) FROM Employee e GROUP BY
year
```

[Example 3–7](#) shows how to use `FUNCTION` with Oracle Spatial queries

**Example 3–7 Using `FUNCTION` EQL Oracle Spatial examples**

```
SELECT a FROM Asset a, Geography geo WHERE geo.id = :id AND a.id IN :id_list AND
FUNCTION('ST_INTERSECTS', a.geometry, geo.geometry) = 'TRUE'
```

```
SELECT s FROM SimpleSpatial s WHERE FUNCTION('MDSYS.SDO_RELATE', s.jGeometry,
:otherGeometry, :params) = 'TRUE' ORDER BY s.id ASC
```

### See Also

For more information, see:

- ["OPERATOR"](#) on page -18
- ["JPQL"](#)  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/JPQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/JPQL)





---

## INTERSECT

When performing multiple queries, use `INTERSECT` to return only results that are found in both queries.

### Examples

[Example 3–8](#) shows how to use this JPQL extension.

**Example 3–8 Using `INTERSECT` EQL**

```
SELECT e FROM Employee e JOIN e.phones p WHERE p.areaCode = :areaCode1
INTERSECT SELECT e FROM Employee e JOIN e.phones p WHERE p.areaCode = :areaCode2
```

### See Also

For more information, see:

- ["UNION"](#) on page -30
- ["EXCEPT"](#) on page -8
- ["JPQL"](#)  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/JPQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/JPQL)



## ON

---

Use the ON clause to append additional conditions to a JOIN condition, such as for outer joins.

### Usage

EclipseLink supports using the ON clause between two root level objects.

### Examples

[Example 3–9](#) shows how to use this JPQL extension.

***Example 3–9 Using ON Clause EQ***

```
SELECT e FROM Employee e LEFT JOIN e.address ON a.city = :city
```

```
SELECT e FROM Employee e LEFT JOIN MailingAddress a ON e.address = a.address
```

### See Also

For more information, see:

- "JPQL"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/JPQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/JPQL)
-



## OPERATOR

---

Use `OPERATION` to call any EclipseLink operator.

### Usage

EclipseLink supports many database functions using standard operator names that are translated to different databases. EclipseLink operators are supported on any database that has an equivalent function (or set of functions). Use the EclipseLink `ExpressionOperator` class to define a custom operator or allow `DatabasePlatform` to override an operator..

`OPERATOR` is similar to [FUNCTION](#), but allows the function to be database independent, and you can call functions that require special syntax.

The supported EclipseLink operators include:

- `Abs`
- `ToUpperCase`
- `ToLowerCase`
- `Chr`
- `Concat`
- `Coalesce`
- `Case`
- `HexToRaw`
- `Initcap`
- `Instring`
- `Soundex`
- `LeftPad`
- `LeftTrim`
- `RightPad`
- `RightTrim`
- `Substring`
- `Translate`
- `Ascii`
- `Length`
- `CharIndex`
- `Cast`
- `Extract`
- `CharLength`
- `Difference`
- `Reverse`
- `Replicate`

- Right
- Locate
- ToNumber
- ToChar
- AddMonths
- DateToString
- MonthsBetween
- NextDay
- RoundDate
- AddDate
- DateName
- DatePart
- DateDifference
- TruncateDate
- NewTime
- Nvl
- NewTime
- Ceil
- Cos
- Cosh
- Acos
- Asin
- Atan
- Exp
- Sqrt
- Floor
- Ln
- Log
- Mod
- Power
- Round
- Sign
- Sin
- Sinh
- Tan
- Tanh
- Trunc

- Greatest
- Least
- Add
- Subtract
- Divide
- Multiply
- Atan2
- Cot
- Deref
- Ref
- RefToHex
- Value
- ExtractXml
- ExtractValue
- ExistsNode
- GetStringVal
- GetNumberVal
- IsFragment
- SDO\_WITHIN\_DISTANCE
- SDO\_RELATE
- SDO\_FILTER
- SDO\_NN
- NullIf

## Examples

[Example 3-10](#) shows how to use this JPQL extension.

### ***Example 3-10 Using OPERATOR EQL***

```
SELECT e FROM Employee e WHERE OPERATOR('ExtractXml', e.resume,
'@years-experience') > 10
```

## See Also

For more information, see:

- ["FUNCTION"](#) on page -12
- ["JPQL"](#)  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/JPQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/JPQL)





## REGEXP

---

Use `REGEXP` to determine if a string matches a regular expression.

### Usage

To use the `REGEXP` function, your database must support regular expressions.

### Examples

[Example 3–11](#) shows how to use this JPQL extension.

**Example 3–11 Using *REGEXP* EQL**

```
e.lastName REGEXP '^Dr\.'
```

### See Also

For more information, see:

- "JPQL"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/JPQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/JPQL)
-



## SQL

Use `SQL` to integrate SQL within a JPQL statement. This provides an alternative to using native SQL queries simply because the query may require a function not supported in JPQL.

### Usage

The `SQL` function includes both the SQL string (to inline into the JPQL statement) and the arguments to translate into the SQL string. Use a question mark character ( `?` ) to define parameters within the SQL that are translated from the SQL function arguments.

You can use `SQL` to call database functions with non standard syntax, embed SQL literals, and perform any other SQL operations within JPQL. With `SQL`, you can still use JPQL for the query.

### Examples

[Example 3–12](#) shows how to use this JPQL extension.

#### **Example 3–12 Using SQL EQ**

```
SELECT p FROM Phone p WHERE SQL('CAST(? AS CHAR(3))', e.areaCode) = '613'
```

```
SELECT SQL('EXTRACT(YEAR FROM ?)', e.startDate) AS year, COUNT(e) FROM Employee e  
GROUP BY year
```

```
SELECT e FROM Employee e ORDER BY SQL('? NULLS FIRST', e.startDate)
```

```
SELECT e FROM Employee e WHERE e.startDate = SQL('(SELECT SYSDATE FROM DUAL)')
```

### See Also

For more information, see:

- "JPQL"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/JPQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/JPQL)
-



---

## TABLE

Use `TABLE` to access unmapped tables.

### Usage

With the `TABLE` function, you use join, collection, history, auditing, or system tables in a JPQL query.

### Examples

[Example 3–13](#) shows how to use an **audit** table (unmapped) within a `SELECT` statement.

***Example 3–13 Using TABLE EQL***

```
SELECT e, a.LAST_UPDATE_USER FROM Employee e, TABLE('AUDIT') a WHERE a.TABLE =  
'EMPLOYEE' AND a.ROWID = COLUMN('ROWID', e)
```

### See Also

For more information, see:

- "JPQL"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/JPQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/JPQL)
-



---

## TREAT

Use `TREAT` to cast an object as its subclass value (that is, downcast related entities with inheritance).

### Examples

[Example 3–14](#) shows how to use this JPQL extension.

**Example 3–14 Using *TREAT* EQL**

```
SELECT e FROM Employee JOIN TREAT(e.projects AS LargeProject) p WHERE p.budget > 1000000
```

### See Also

For more information, see:

- "JPQL"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/JPQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/JPQL)
-





## UNION

Use `UNION` to combine the results of two queries into a single query.

### Usage

With `UNION`, the unique results from both queries will be returned. If you include the `ALL` option, the results found in both queries will be duplicated.

### Examples

[Example 3–15](#) shows how to use this JPQL extension.

***Example 3–15 Using UNION EQL***

```
SELECT MAX(e.salary) FROM Employee e WHERE e.address.city = :city1
UNION SELECT MAX(e.salary) FROM Employee e WHERE e.address.city = :city2
```

### See Also

For more information, see:

- ["EXCEPT" on page -8](#)
- ["INTERSECT" on page -14](#)
- ["JPQL"](#)  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/JPQL](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/JPQL)

---

## JPA Query Customization Extensions

You can specify EclipseLink query hints (JPA query extensions) by:

- Using the `@QueryHint` annotation
- Including the hints in the `orm.xml` or `eclipselink-orm.xml` file
- Using the `setHint()` method when executing a named or dynamic query (JPQL or Criteria)

EclipseLink supplies the following query hints:

- `batch`
- `batch.size`
- `batch.type`
- `cache-usage`
- `cache-usage.indirection-policy`
- `composite-unit.member`
- `cursor`
- `cursor.initial-size`
- `cursor.page-size`
- `exclusive-connection`
- `fetch-group`
- `fetch-group.attribute`
- `fetch-group.default`
- `fetch-group.load`
- `fetch-group.name`
- `flush`
- `history.as-of`
- `history.as-of.scn`
- `inheritance.outer-join`
- `jdbc.allow-native-sql-queries`
- `jdbc.bind-parameters`
- `jdbc.cache-statement`

- 
- `jdbc.fetch-size`
  - `jdbc.first-result`
  - `jdbc.max-rows`
  - `jdbc.native-connection`
  - `jdbc.parameter-delimiter`
  - `jdbc.timeout`
  - `join-fetch`
  - `left-join-fetch`
  - `load-group`
  - `load-group.attribute`
  - `maintain-cache`
  - `partitioning`
  - `pessimistic-lock`
  - `prepare`
  - `query-results-cache`
  - `query-results-cache.expiry`
  - `query-results-cache.expiry-time-of-day`
  - `query-results-cache.ignore-null`
  - `query-results-cache.randomize-expiry`
  - `query-results-cache.size`
  - `query-results-cache.type`
  - `query-type`
  - `query.redirection`
  - `read-only`
  - `refresh`
  - `refresh.cascade`
  - `result-collection-type`
  - `sql.hint`

All EclipseLink query hints are defined in the `QueryHints` class in the `org.eclipse.persistence.config` package. When you set a hint, you can set the value using the public static final field in the appropriate configuration class in `org.eclipse.persistence.config` package, including the following:

- `HintValues`
- `CacheUsage`
- `PessimisticLock`
- `QueryType`

For more information, see Section 10.3.1 "NamedQuery Annotation" in the JPA Specification (<http://jcp.org/en/jsr/detail?id=317>).



## batch

Use `eclipselink.batch` to supply EclipseLink with batching information so subsequent queries of related objects can be optimized in batches, instead of being retrieved one-by-one or in one large joined read.

### Values

This query hint accepts a single-valued, relationship path expression.

### Usage

Using the `eclipselink.batch` hint is more efficient than joining, because EclipseLink avoids reading duplicate data.

You can only batch queries that have a single object in the select clause.

Valid values: a single-valued relationship path expression.

---

---

**Note:** Use *dot notation* to access nested attributes. For example, to batch-read an employee's manager's address, use `e.manager.address`.

---

---

### Examples

[Example 4-1](#) shows how to use this hint in a JPA query.

#### **Example 4-1 Using batch in a JPA Query**

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.QueryHints;
query.setHint("eclipselink.batch", "e.address");
```

[Example 4-2](#) shows how to use this hint with the `@QueryHint` annotation.

#### **Example 4-2 Using batch in a @QueryHint Annotation**

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.QueryHints;
@QueryHint(name=QueryHints.BATCH, value="e.address");
```

### See Also

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
- "[join-fetch](#)" on page -46



## batch.size

Use `eclipselink.batch.size` to configure the batch size when using `batch.type` set to `IN`.

### Values

[Table 4–1](#) describes this persistence property's values.

**Table 4–1** Valid Values for

Value	Description
Size	The number of keys in each <code>IN</code> clause Default: 256 or the query's <code>pageSize</code> (for cursor queries)

### Examples

**Example 4–3** Using `batch.size` in a JPA Query

**Example 4–4** Using `batch.size` in a `@QueryHint` Annotation

### See Also

For more information, see:

- ["batch"](#) on page -4





## batch.type

Use `eclipselink.batch.type` to specify the type of batch fetching the query should use for any batch-fetched relationships.

### Values

[Table 4–2](#) describes this query hint's values.

**Table 4–2** Valid Values for *batch.type*

Value	Description
JOIN	(Default) The original query's selection criteria is joined with the batch query.
EXISTS	Uses an SQL <code>EXISTS</code> and a sub-select in the batch query instead of a join.
IN	Uses an SQL <code>IN</code> clause in the batch query passing in the source object IDs.

### Examples

**Example 4–5** Using *batch.type* in a JPA Query

**Example 4–6** Using *batch.type* in a `@QueryHint` Annotation

### See Also

For more information, see:

- ["batch"](#) on page -4
- ["@BatchFetch"](#) on page -14



## cache-usage

Use `eclipselink.cache-usage` to specify how the query should interact with the EclipseLink cache.

### Values

[Table 4–3](#) describes this query hint's valid values.

**Table 4–3** Valid Values for `org.eclipse.persistence.config.CacheUsage`

Value	Description
<code>DoNotCheckCache</code>	Always go to the database.
<code>CheckCacheByExactPrimaryKey</code>	If a read-object query contains an expression where the primary key is the only comparison, you can obtain a cache hit if you process the expression against the object in memory
<code>CheckCacheByPrimaryKey</code>	If a read-object query contains an expression that compares at least the primary key, you can obtain a cache hit if you process the expression against the objects in memory.
<code>CheckCacheThenDatabase</code>	You can configure any read-object query to check the cache completely before you resort to accessing the database.
<code>CheckCacheOnly</code>	You can configure any read-all query to check only the parent session cache (shared cache) and return the result from it without accessing the database.
<code>ConformResultsInUnitOfWork</code>	You can configure any read-object or read-all query within the context of a unit of work to conform the results with the changes to the object made within that unit of work. This includes new objects, deleted objects and changed objects.
<code>UseEntityDefault</code>	<p>(Default) Use the cache configuration as specified by the EclipseLink descriptor API for this entity.</p> <p><b>Note:</b> The entity default value is to not check the cache (<code>DoNotCheckCache</code>). The query will access the database and synchronize with the cache. Unless refresh has been set on the query, the cached objects will be returned without being refreshed from the database. EclipseLink does not support the cache usage for native queries or queries that have complex result sets such as returning data or multiple objects.</p>

### Usage

EclipseLink JPA uses a shared cache assessed across the entire persistence unit. After completing an operation in a particular persistence context, EclipseLink merges the results into the shared cache, so that other persistence contexts can use the results *regardless of whether the entity manager and persistence context are created in Java SE or Java EE*.

Any entity persisted or removed using the entity manager will always consistently maintained with the cache.

### Examples

[Example 4–7](#) shows how to use this hint in a JPA query.

**Example 4–7** Using *cache-usage* in a JPA Query

```
import org.eclipse.persistence.config.CacheUsage;
import org.eclipse.persistence.config.QueryHints;
query.setHint(QueryHints.CACHE_USAGE, CacheUsage.CheckCacheOnly);
```

[Example 4-8](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4-8 Using cache-usage in a @QueryHint Annotation**

```
import org.eclipse.persistence.config.CacheUsage;
import org.eclipse.persistence.config.TargetDatabase;
@QueryHint(name=QueryHints.CACHE_USAGE, value=CacheUsage.CheckCacheOnly);
```

## See Also

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
- "[cache-usage.indirection-policy](#)" on page -12

## cache-usage.indirection-policy

Use `eclipselink.cache-usage.indirection-policy` (with [cache-usage](#)) to configure in-memory querying and conforming's treatment of uninstantiated indirection/lazy relationships.

### Values

[Table 4–4](#) describes this query hint's values.

**Table 4–4** Valid Values for `cache-usage.indirection-policy`

Value	Description
Conform	If conforming encounters an uninstantiated indirection/lazy object, it is assumed to conform.
Exception	(Default) If conforming encounters an uninstantiated indirection/lazy object an exception is thrown.
NotConform	If conforming encounters an uninstantiated indirection/lazy object it is assumed to not conform.
Trigger	If conforming encounters an uninstantiated indirection/lazy object it is triggered.

### Usage

This hint applies only when the query traverses a join across a lazy relationship.

### Examples

**Example 4–9** Using `cache-usage.indirection-policy` in a JPA Query

```
query.setHint(QueryHints.INDIRECTION_POLICY, CacheUsageIndirectionPolicy.Trigger);
```

**Example 4–10** Using `cache-usage.indirection-policy` in a `@QueryHint` Annotation

```
@QueryHint(name=QueryHints.INDIRECTION_POLICY,  
value=CacheUsageIndirectionPolicy.Trigger)
```

### See Also

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
- ["cache-usage"](#) on page -10



## cursor

Use `eclipselink.cursor` to configure the query to return a `CursoredStream`.

### Values

[Table 4–5](#) describes this persistence property's values.

**Table 4–5** Valid Values for *cursor*

Value	Description
true	
false	(Default)

### Usage

A *Cursor* is a stream of the JDBC `ResultSet`. Cursors are useful for large results sets, or when you only need the few results of a query.

A cursor implements `Enumeration`, when the `each next()` will fetch the next from the JDBC `ResultSet`, and builds the resulting Object or value. A Cursor requires, and will keep, a live JDBC connection. You must use `close()` to free the Cursor's resources.

You can access a Cursor from a JPA Query through `getSingleResult()`, or from `JpaQuery` using `getResultCursor()`.

**Tip:** You can use `MAX_ROWS` and `FIRST_RESULT` instead of a Cursor to obtain a page of results.

### Examples

**Example 4–11** Using cursor in a JPA Query

**Example 4–12** Using cursor in a `@QueryHint` Annotation

### See Also

For more information, see:

- ["cursor.initial-size"](#) on page -16
- ["cursor.page-size"](#) on page -18





## cursor.initial-size

Use `eclipselink.cursor.initial-size` to configure the query to return a `CursoredStream` with the specified initial size.

### Values

[Table 4–6](#) describes this query hint's values.

**Table 4–6** Valid Values for *cursor.initial-size*

Value	Description
Integer or Strings that can be parsed to <code>int</code> values	The initial number of objects that are prebuilt for the stream before a <code>next()</code> is called

### Examples

**Example 4–13** Using *cursor.initial-size* in a JPA Query

**Example 4–14** Using *cursor.initial-size* in a `@QueryHint` Annotation

### See Also

For more information, see:

- ["cursor"](#) on page -14



## cursor.page-size

Use `eclipselink.cursor.page-size` to configure the query to return a `CursoredStream` with the specified page size.

### Values

[Table 4–7](#) describes this query hint's values.

**Table 4–7** Valid Values for *cursor.page-size*

Value	Description
Integer or Strings that can be parsed to <code>int</code> values	The number of objects that are fetched from the stream on a <code>next()</code> call, if the buffer of objects is empty

### Examples

**Example 4–15** Using *cursor.page-size* in a JPA Query

**Example 4–16** Using *cursor.page-size* in a `@QueryHint` Annotation

### See Also

For more information, see:

- ["cursor"](#) on page -14



## exclusive-connection

Use `eclipselink.exclusive-connection` to specify if the query should use the exclusive (transactional/write) connection.

### Values

[Table 4–8](#) describes this query hint's values.

**Table 4–8** Valid Values for *exclusive-connection*

Value	Description
true	
false	

### Usage

This is valid only when an `EXCLUSIVE_CONNECTION_MODE` property has been set for the persistence unit (such as VPD). If a `jdbc.exclusive-connection.mode` has been configured, use this query hint to ensure that the query is executed through the exclusive connection.

This may be required in certain cases, such as when database security prevents a query joining to a secure table from returning the correct results, when executed through the shared connection.

### Examples

**Example 4–17** Using *exclusive-connection* in a JPA Query

**Example 4–18** Using *exclusive-connection* in a `@QueryHint` Annotation

### See Also

For more information, see:

- ["jdbc.exclusive-connection.mode"](#) on page -98



## flush

Use `eclipselink.flush` to specify if the query should flush the persistence context before executing.

### Values

[Table 4–9](#) describes this query hint's values.

**Table 4–9** Valid Values for *flush*

Value	Description
true	
false	(Default)

### Usage

If the query may access objects that have been changed in the persistence context, you must trigger a flush in order for the query to see the changes. If the query does not require seeing the changes, you should avoid the flush in order to improve performance.

You can also configure the flush-mode as a persistence unit property. See ["flush-clear.cache"](#) on page -80 for more information.

You can also use conforming to query changes without requiring a flush. See ["cache-usage"](#) on page -10 for more information.

### Examples

#### **Example 4–19** Using *flush* in a JPA Query

#### **Example 4–20** Using *flush* in a `@QueryHint` Annotation

### See Also

For more information, see:

- ["persistence-context.flush-mode"](#) on page -166
- ["flush-clear.cache"](#) on page -80
- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
- ["cache-usage.indirection-policy"](#) on page -12
- ["cache-usage"](#) on page -10





---

## history.as-of

Configures the query to query the state of the object as-of a point in time.

### Values

[Table 4–10](#) describes this query hint's values.

**Table 4–10** Valid Values for *history.as-of*

Value	Description
Timestamp	Timestamp, in the form: YYYY/MM/DD HH:MM:SS.n

### Usage

Both the query execution and result will conform to the database as it existed in the past.

---

---

**Note:** This query hint requires a class with historical support or when using Oracle Flashback.

---

---

### Examples

**Example 4–21** Using *history.as-of* in a JPA Query

**Example 4–22** Using *history.as-of* in *@QueryHint* Annotation

### See Also

For more information, see:

- ["history.as-of.scn"](#) on page -26



## history.as-of.scn

Use `eclipselink.history.as-of.scn` to configure the query to query the state of the object as-of a database SCN (System Change Number).

### Values

[Table 4–11](#) describes this query hint's values.

**Table 4–11** Valid Values for *history.as-of.scn*

Value	Description
value	Integer SCN value

### Usage

---

---

**Note:** This query hint requires Oracle Flashback support.

---

---

### Examples

**Example 4–23** Using *history.as-of.scn* in a JPA Query

**Example 4–24** Using *history.as-of.scn* in *@QueryHint* Annotation

### See Also

For more information, see:

- ["history.as-of"](#) on page -24



## inheritance.outer-join

Use `eclipselink.inheritance.outer-join` to configure the query to use an outer-join for all subclasses.

### Values

[Table 4–12](#) describes this query hint's values.

**Table 4–12** *Valid Values for inheritance.outer-join*

Value	Description
true	Use outer-join.
false	(Default) Do not use outer-join; execute a separate query for each subclass.

### Usage

This query hint can be used queries to root or branch inherited classes.

You can also configure this behavior by using a `DescriptorCustomizer` (see ["descriptor.customizer"](#) on page -72).

---

---

**Note:** This is required for correct ordering, `firstResult`, `maxResult`, and cursors.

---

---

### Examples

**Example 4–25** *Using inheritance.outer-join in a JPA Query*

### See Also

For more information, see:

-



## jdbc.bind-parameters

Use `eclipselink.jdbc.bind-parameters` to specify if the query uses parameter binding (parameterized SQL).

### Values

[Table 4–13](#) describes this query hint's valid values.

**Table 4–13** Valid Values for `org.eclipse.persistence.config.HintValues`

Value	Description
TRUE	Bind all parameters.
FALSE	Do not bind all parameters.
PERSISTENCE_UNIT_DEFAULT	(Default) Use the parameter binding setting made in your EclipseLink session's database login, which is true by default.

### Usage

By default, EclipseLink enables parameter binding and statement caching. This causes EclipseLink to use a prepared statement, binding all SQL parameters and caching the prepared statement. When you re-execute this query, you avoid the SQL preparation, which improves performance.

You can also configure parameter binding for the persistence unit in the `persistence.xml` file (when used in a Java SE environment).

### Examples

[Example 4–26](#) shows how to use this hint in a JPA query.

**Example 4–26 Using bind-parameters in a JPA Query**

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.QueryHints;
query.setHint(QueryHints.BIND_PARAMETERS, HintValues.TRUE);
```

[Example 4–27](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4–27 Using bind-parameters in a @QueryHint Annotation**

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.TargetDatabase;
@QueryHint(name=QueryHints.BIND_PARAMETERS, value=HintValues.TRUE);
```

[Example 4–28](#) shows how to configure parameter binding in the persistence unit `persistence.xml` file.

**Example 4–28 Specifying Parameter Binding Persistence Unit Property**

```
<property name="eclipselink.jdbc.bind-parameters" value="false"/>
```

Or by importing a property map:

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.NATIVE_SQL, "true");
```



## See Also

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
- "How to Use Parameterized SQL and Statement Caching in a DatabaseQuery"  
[http://wiki.eclipse.org/Using\\_Basic\\_Query\\_API\\_%28ELUG%29#How\\_to\\_Use\\_Parameterized\\_SQL\\_and\\_Statement\\_Caching\\_in\\_a\\_DatabaseQuery](http://wiki.eclipse.org/Using_Basic_Query_API_%28ELUG%29#How_to_Use_Parameterized_SQL_and_Statement_Caching_in_a_DatabaseQuery)
- "How to Use Parameterized SQL (Parameter Binding) and Prepared Statement Caching for Optimization"  
[http://wiki.eclipse.org/Optimizing\\_the\\_EclipseLink\\_Application\\_%28ELUG%29#How\\_to\\_Use\\_Parameterized\\_SQL\\_.28Parameter\\_Binding.29\\_and\\_Prepared\\_Statement\\_Caching\\_for\\_Optimization](http://wiki.eclipse.org/Optimizing_the_EclipseLink_Application_%28ELUG%29#How_to_Use_Parameterized_SQL_.28Parameter_Binding.29_and_Prepared_Statement_Caching_for_Optimization)

## jdbc.cache-statement

Specify if the query caches its JDBC statement.

### Values

[Table 4–14](#) describes this query hint's values.

**Table 4–14** Valid Values for *jdbc.cache-statement*

Value	Description
true	
false	

### Usage

This allows queries to use parameterized SQL with statement caching. It also allows a specific query to not cache its statement, if statement caching is enable for the persistence unit.

**Tip:** Normally, you should set statement caching for the entire persistence unit (see "[jdbc.cache-statements](#)" on page -90) instead of each query.

When using a `DataSource`, you must set statement caching in the `DataSource` configuration.

### Examples

**Example 4–29** Using *jdbc.cache-statement* in a JPA Query

**Example 4–30** Using *jdbc.cache-statement* in a `@QueryHint` Annotation

### See Also

For more information, see:

-



## jdbc.fetch-size

Use `eclipselink.jdbc.fetch-size` to specify the number of rows to be fetched from the database when additional rows are needed.

---

---

**Note:** This property requires JDBC driver support.

---

---

### Values

[Table 4–15](#) describes this query hint's valid values.

**Table 4–15** Valid Values for `eclipselink.jdbc.fetch-size`

Value	Description
from 0 to <code>Integer.MAX_VALUE</code>	(Default = 0) As a String, depending on your JDBC driver. If 0, the JDBC driver default will be used.

### Usage

For queries that return a large number of objects, you can configure the row fetch size used in the query to improve performance by reducing the number database hits required to satisfy the selection criteria.

By default, most JDBC drivers use a fetch size of 10. , so if you are reading 1000 objects, increasing the fetch size to 256 can significantly reduce the time required to fetch the query's results. The optimal fetch size is not always obvious. Usually, a fetch size of one half or one quarter of the total expected result size is optimal.

If you are unsure of the result set size, incorrectly setting a fetch size too large or too small can decrease performance.

### Examples

[Example 4–31](#) shows how to use this hint in a JPA query.

**Example 4–31** Using `jdbc.fetch-size` in a JPA Query

[Example 4–32](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4–32** Using `jdbc.fetch-size` in a `@QueryHint` Annotation

### See Also

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
- "How to Use JDBC Fetch Size for Optimization"  
[http://wiki.eclipse.org/Optimizing\\_the\\_EclipseLink\\_Application\\_%28ELUG%29#How\\_to\\_Use\\_JDBC\\_Fetch\\_Size\\_for\\_Optimization](http://wiki.eclipse.org/Optimizing_the_EclipseLink_Application_%28ELUG%29#How_to_Use_JDBC_Fetch_Size_for_Optimization)

## jdbc.first-result

Use `eclipselink.jdbc.first-result` to specify if the query should skip the specified number of rows in the result.

### Values

[Table 4–16](#) describes this query hint's values.

**Table 4–16** *Valid Values for jdbc.first-result*

Value	Description
Integer	Integer or String value that can be parsed to an int value. The position of the first result to retrieve.

### Usage

This query hint is similar to JPA Query `setFirstResults()`, but can be set in metadata for `NamedQuery`s.

### Examples

**Example 4–33** *Using jdbc.first-result in a JPA Query*

### See Also

For more information, see:

-



## jdbc.max-rows

Use `eclipselink.jdbc.max-rows` to specify the maximum number of rows to be returned. If the query returns more rows than specified, the trailing rows will not be returned.

### Values

[Table 4–17](#) describes this query hint's valid values.

**Table 4–17** Valid Values for `eclipselink.jdbc.max-rows`

Value	Description
Int or String (that can be parsed to Int values)	Configures the JDBC maximum number of rows.

### Usage

This hint is similar to JPQL `setMaxResults()`, but can be specified within the metadata for `NamedQueries`.

### Examples

[Example 4–34](#) shows how to use this hint in a JPA query.

**Example 4–34** Using `jdbc.max-rows` in a JPA Query

[Example 4–35](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4–35** Using `jdbc.max-rows` in a `@QueryHint` Annotation

### See Also

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
-





## jdbc.native-connection

Use `eclipselink.jdbc.native-connection` to specify if the query requires a native JDBC connection.

### Values

[Table 4–18](#) describes this persistence property's values.

**Table 4–18** Valid Values for *jdbc.native-connection*

Value	Description
true	Require native connection.
false	(Default) Do not require native connection.

### Usage

This may be required for some queries on some server platforms that have `DataSource` implementations that wrap the JDBC connection in their own proxy. If the query requires custom JDBC access, it may require a native connection.

A `ServerPlatform` is required to be set as a persistence property to be able to use a native connection. For features that EclipseLink already knows require a native connection, `eclipselink.jdbc.native-connection` will default to `true`.

### Examples

**Example 4–36** Using *jdbc.native-connection* in a JPA Query

### See Also

For more information, see:



## jdbc.parameter-delimiter

Use `eclipselink.jdbc.parameter-delimiter` to specify a custom parameter binding character (instead of the default hash # character).

### Values

[Table 4–19](#) describes this query hint's values.

**Table 4–19** Valid Values for

Value	Description
Character	Any valid, single character. Do not use "".

### Examples

*Example 4–37 Using `jdbc.parameter-delimiter` in a JPA Query*

### See Also

For more information, see:

- ["jdbc.bind-parameters"](#) on page -30



## jdbc.timeout

Use `eclipselink.jdbc.timeout` to specify number of seconds EclipseLink will wait (time out) for a query result, before throwing a `DatabaseException`.

---

---

**Note:** This property requires JDBC driver support.

---

---

### Values

[Table 4–20](#) describes this query hint's valid values.

**Table 4–20** Valid Values for `eclipselink.jdbc.timeout`

Value	Description
from 0 to <code>Integer.MAX_VALUE</code>	(Default = 0) As a String, depending on your JDBC driver. If 0, EclipseLink will never time out waiting for a query.

### Usage

### Examples

[Example 4–38](#) shows how to use this hint in a JPA query.

**Example 4–38** Using cache-usage in a JPA Query

```
import org.eclipse.persistence.config.CacheUsage;
import org.eclipse.persistence.config.QueryHints;
query.setHint(QueryHints.CACHE_USAGE, CacheUsage.CheckCacheOnly);
```

[Example 4–39](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4–39** Using cache-usage in a `@QueryHint` Annotation

```
import org.eclipse.persistence.config.CacheUsage;
import org.eclipse.persistence.config.TargetDatabase;
@QueryHint(name=QueryHints.CACHE_USAGE, value=CacheUsage.CheckCacheOnly);
```

### See Also

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
-



## join-fetch

Use `eclipselink.join-fetch` hint to join attributes in a query.

---

**Note:** Use *dot notation* to access nested attributes. For example, to batch-read an employee's manager's address, use `e.manager.address`.

---

### Values

[Table 4–21](#) describes this query hint's valid values.

**Table 4–21** Valid Values for `eclipselink.join-fetch` hint

Value
A relationship path expression

### Usage

This hint is similar to `eclipselink.batch`. Subsequent queries of related objects can be optimized in batches instead of being retrieved in one large joined read

The `eclipselink.join-fetch` hint differs from JPQL joining in that it allows multilevel fetch joins.

### Examples

[Example 4–40](#) shows how to use this hint in a JPA query.

**Example 4–40** Using `join-fetch` in a JPA Query

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.QueryHints;
query.setHint("eclipselink.join-fetch", "e.address");
```

[Example 4–41](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4–41** Using `join-fetch` in a `@QueryHint` Annotation

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.QueryHints;
@QueryHint(name=QueryHints.FETCH, value="e.address");
```

### See Also

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
- EclipseLink Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/QueryOptimization>



- "Optimizing Queries"  
[http://wiki.eclipse.org/Optimizing\\_the\\_EclipseLink\\_Application\\_%28ELUG%29#Optimizing\\_Queries](http://wiki.eclipse.org/Optimizing_the_EclipseLink_Application_%28ELUG%29#Optimizing_Queries)
- "Fetch Joins" in the JPA Specification (<http://jcp.org/en/jsr/detail?id=317>)
- "batch" on page -4
- "left-join-fetch" on page -48

## left-join-fetch

Use `eclipselink.left-join-fetch` to optimize the query: related objects will be joined into the query instead of being queries separately.

### Values

[Table 4–22](#) describes this query hint's values.

**Table 4–22** *Valid Values for left-join-fetch*

Value	Description
String	JPQL-style navigations to a relationship

### Usage

You can use this query hint to create nested join fetches, which is not supported by JPQL. You can also use `eclipselink.left-join-fetch` to create join fetches with native queries.

---

---

**Note:** This uses an OUTER join to allow null or empty values.

---

---

### Examples

**Example 4–42** *Using left-join-fetch in persistence.xml*

### See Also

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
- EclipseLink Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/QueryOptimization>
- "Optimizing Queries"  
[http://wiki.eclipse.org/Optimizing\\_the\\_EclipseLink\\_Application\\_%28ELUG%29#Optimizing\\_Queries](http://wiki.eclipse.org/Optimizing_the_EclipseLink_Application_%28ELUG%29#Optimizing_Queries)
- "Fetch Joins" in the JPA Specification (<http://jcp.org/en/jsr/detail?id=317>)
- "batch" on page -4
- "join-fetch" on page -46



---

## load-group

Use `eclipselink.load-group` to configures a query to use the load group object.

### Values

[Table 4–23](#) describes this persistence property’s values.

**Table 4–23**    *Valid Values for load-group*

Value	Description
	An instance of <code>LoadGroup</code>

### Usage

With load groups, EclipseLink ensures that all relational attributes for a group are loaded. LoadGroups are only supported for queries returning objects (only a single alias can be the select clause).

### Examples

**Example 4–43**    *Using load-group in persistence.xml*

### See Also

For more information, see:

- ["load-group.attribute"](#) on page -52



## load-group.attribute

---

Use `eclipselink.load-group.attribute` to specify if the query uses a [load-group](#) that includes a list of attributes.

### Values

[Table 4–24](#) describes this query hint's values.

**Table 4–24** Valid Values for `load-group.attribute`

Value	Description

### Usage

You must define each attribute using a separate hint. The query loads all relational attributes defined in the load group.

LoadGroups are only supported for queries returning objects (only a single alias can be the select clause). Both local and nested attributes are supported.

### Examples

**Example 4–44** Using `load-group.attribute` in a JPA Query

### See Also

For more information, see:

- ["load-group"](#) on page -50



## **maintain-cache**

Use `eclipselink.maintain-cache` to controls whether or not query results are cached in the session cache

### **Values**

[Table 4–25](#) describes this query hint's valid values.

**Table 4–25** Valid Values for `org.eclipselink.maintain-cache`

Value	Description
TRUE	Maintain cache.
FALSE	(Default) Do not maintain cache.

### **Usage**

The `eclipselink.maintain-cache` hint provides a way to query the current database contents *without affecting the current persistence context*. It configures the query to return un-managed instances so any updates to entities queried using this hint would have to be merged into the persistence context.

### **Examples**

[Example 4–45](#) shows how to use this hint in a JPA query.

**Example 4–45 Using maintain-cache in a JPA Query**

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.QueryHints;
query.setHint(QueryHints.MAINTAIN_CACHE, HintValues.FALSE);
```

[Example 4–46](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4–46 Using maintain-cache in a @QueryHint Annotation**

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.QueryHints;
@QueryHint(name=QueryHints.MAINTAIN_CACHE, value=HintValues.FALSE);
```

### **See Also**

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)





## pessimistic-lock

Use `eclipselink.pessimistic-lock` to specify if EclipseLink uses pessimistic locking.

### Values

[Table 4–26](#) describes this query hint's valid values.

**Table 4–26** Valid Values for `org.eclipse.persistence.config.PessimisticLock`

Value	Description
NoLock	(Default) Do not use pessimistic locking.
Lock	EclipseLink issues <code>SELECT . . . . FOR UPDATE</code> statements.
LockNoWait	EclipseLink issues <code>SELECT . . . . FOR UPDATE NO WAIT</code> statements.

### Usage

The primary advantage of using pessimistic locking is that you are assured, once the lock is obtained, of a successful edit. This is desirable in highly concurrent applications in which optimistic locking may cause too many optimistic locking errors.

One drawback of pessimistic locking is that it requires additional database resources, requiring the database transaction and connection to be maintained for the duration of the edit. Pessimistic locking may also cause deadlocks and lead to concurrency issues.

### Examples

[Example 4–47](#) shows how to use this hint in a JPA query.

**Example 4–47** Using pessimistic-lock in a JPA Query

```
import org.eclipse.persistence.config.PessimisticLock;
import org.eclipse.persistence.config.QueryHints;
query.setHint(QueryHints.PESSIMISTIC_LOCK, PessimisticLock.LockNoWait);
```

[Example 4–48](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4–48** Using pessimistic-lock in a `@QueryHint` Annotation

```
import org.eclipse.persistence.config.PessimisticLock;
import org.eclipse.persistence.config.QueryHints;
@QueryHint(name=QueryHints.PESSIMISTIC_LOCK, value=PessimisticLock.LockNoWait);
```

### See Also

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
- EclipseLink Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/PessimisticLocking>

- "Locking"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Mapping/Locking](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Mapping/Locking)

---

## prepare

Use `eclipselink.prepare` to specify if a query prepares (that is, generates) its SQL for each execution.

### Values

[Table 4–27](#) describes this query hint’s values.

**Table 4–27**    *Valid Values for prepare*

Value	Description
true	Generate the SQL <i>each time</i> EclipseLink executes the query.
false	(Default) Generate the SQL only the <i>first time</i> EclipseLink executes the query.

### Usage

By default, EclipseLink does not re-generate the SQL for each execution. This may improve performance.

For queries that require dynamic SQL (for example, to handle null parameters) set `eclipselink.prepare` to **false**.

### Examples

**Example 4–49**    *Using prepare in a JPA Query*

**Example 4–50**    *Using prepare in a @QueryHint Annotation*

### See Also

For more information, see:

- 
-



# query-results-cache

Use `eclipselink.query-results-cache` to specify that the query should use a results cache.

## Values

Table 4–28 describes this persistence property’s values.

Table 4–28 Valid Values for query-results-cache

Value	Description
Persistence_Unit_Default	(Default)
True	Query results are cache.
False	Query results are not cached.

## Usage

By default, the query will cache 100 query results (see [query-results-cache.size](#)); if the same named query with the same arguments is re-executed EclipseLink will skip the database and return the cached results.

**Note:** The *query* cache is different and independent from the *object* cache.

## Examples

**Example 4–51** Using query-results-cache in a JPA Query

**Example 4–52** Using query-results-cache in a @QueryHint Annotation

**Example 4–53** Using query-results-cache in orm.xml File

```
<?xml version="1.0"?>
<entity-mappings
  xmlns="http://www.eclipse.org/eclipselink/xsds/persistence/orm"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.eclipse.org/eclipselink/xsds/persistence/orm
http://www.eclipse.org/eclipselink/xsds/eclipselink_orm_2_4.xsd"
  version="2.4">
  <entity name="Employee" class="org.acme.Employee" access="FIELD">
    <named-query name="findAllEmployeesInCity" query="Select e from Employee e
where e.address.city = :city">
      <hint name="eclipselink.query-results-cache" value="true"/>
    </named-query>
  </entity>
</entity-mappings>
```

```
        <hint name="eclipselink.query-results-cache.size" value="500"/>
    </named-query>
    ...
</entity>
</entity-mappings>
```

## See Also

For more information, see:

- "Query Results Cache"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Query\\_Cache](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Query_Cache)
-

## query-results-cache.expiry

Use `eclipselink.query-results-cache.expiry` to set the time-to-live (that is, expiration time) of the query's results cache.

### Values

[Table 4–29](#) describes this query hint's values.

**Table 4–29** Valid Values for *query-results-cache.expiry*

Value	Description
Value	Number of milliseconds, as Integer or Strings that can be parsed to int values.

### Usage

By default the query results cache will not expiry results.

### Examples

**Example 4–54** Using *query-results-cache.expiry* in a JPA Query

Para

**Example 4–55** Using *query-results-cache.expiry* in a *@QueryHint* Annotation

### See Also

For more information, see:

- "Query Results Cache"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Query\\_Cache](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Query_Cache)
- "[query-results-cache](#)" on page -60





## query-results-cache.expiry-time-of-day

Use `eclipselink.query-results-cache.expiry-time-of-day` to set the time of day of the query's results cache expiration.

### Values

[Table 4–30](#) describes this persistence property's values.

**Table 4–30** Valid Values for `query-results-cache.expiry-time-of-day`

Value	Description
Value	Time, in HH:MM:SS format, as a <code>String</code>

### Usage

By default the query results cache will not expiry results.

### Examples

**Example 4–56** Using `query-results-cache.expiry-time-of-day` in a JPA Query

**Example 4–57** Using `query-results-cache.expiry-time-of-day` in a `@QueryHint` Annotation

### See Also

For more information, see:

- "Query Results Cache"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Query\\_Cache](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Query_Cache)
- "[query-results-cache](#)" on page -60



---

## query-results-cache.ignore-null

Use `eclipselink.query-results-cache.ignore-null` to specify if EclipseLink caches `null` query results

### Values

[Table 4–31](#) describes this query hint's values.

**Table 4–31** Valid Values for `query-results-cache.ignore-null`

Value	Description
<code>true</code>	Ignore null results (that is, <i>do not</i> cache results)
<code>false</code>	(Default) Do not ignore null results (that is, <i>do</i> cache results)

### Usage

You can use this query hint to use query cache as a secondary key index, and allow inserts of new objects.

### Examples

**Example 4–58** Using `query-results-cache.ignore-null` in a JPA Query

**Example 4–59** Using `query-results-cache.ignore-null` in a `@QueryHint` Annotation

### See Also

For more information, see:

- "Query Results Cache"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Query\\_Cache](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Query_Cache)
- "`query-results-cache`" on page -60



## query-results-cache.randomize-expiry

Use `eclipselink.query-results-cache.randomize-expiry` to specify the expiry time (`query-results-cache.expiry`) should be randomized by 10% of its set value.

### Values

Table 4–32 describes this query hint's values.

**Table 4–32** Valid Values for `query-results-cache.randomize-expiry`

Value	Description
true	Randomize the expiration time by 10%.
false	(Default) Do not randomize the expiration time.

### Usage

Use this query hint to avoid bottlenecks from multiple cached values expiring at a fixed time.

### Examples

**Example 4–60** Using `query-results-cache.randomize-expiry` in a JPA Query

Para

**Example 4–61** Using `query-results-cache.randomize-expiry` in a `@QueryHint` Annotation

### See Also

For more information, see:

- "Query Results Cache"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Query\\_Cache](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Query_Cache)
- "query-results-cache" on page -60
- "query-results-cache.expiry" on page -62



## query-results-cache.size

Use `eclipselink.query-results-cache.size` to set the fixed size of the query's results cache.

### Values

[Table 4–33](#) describes this query hint's values.

**Table 4–33** Valid Values for `query-results-cache.size`

Value	Description
Size	Integer or Strings that can be parsed to int values (Default: 100)

### Usage

When using [query-results-cache](#), if the same named query with the same arguments is re-executed EclipseLink will skip the database and return the cached results.

---

---

**Note:** If a query has no arguments, use a size of 1 (as there is only a single result).

---

---

### Examples

**Example 4–62** Using `query-results-cache.size` in a JPA Query

**Example 4–63** Using `query-results-cache.size` in a `@QueryHint` Annotation

### See Also

For more information, see:

- "Query Results Cache"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Query\\_Cache](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Query_Cache)
- "[query-results-cache](#)" on page -60





## query-results-cache.type

Use `eclipselink.query-results-cache.type` to set the cache type used for the query's results cache.

### Values

[Table 4–34](#) describes this query hint's values.

**Table 4–34** Valid Values for **query-results-cache.type**

Value	Description
Cache	(Default) Fixed size LRU cache ( <code>CacheIdentityMap</code> )
Full	
Hard_Weak	
None	
Soft	
Soft_Weak	
Weak	

### Usage

### Examples

[Example 4–64](#) shows how to use this hint in a JPA query.

**Example 4–64** Using `query-results-cache.type` in a JPA Query

[Example 4–65](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4–65** Using `query-results-cache.type` in a `@QueryHint` Annotation

### See Also

For more information, see:

- ["@Cache"](#) on page -16
- "Caching Overview"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Caching\\_Overview](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Caching_Overview)
- [http://wiki.eclipse.org/Introduction\\_to\\_Cache\\_%28ELUG%29](http://wiki.eclipse.org/Introduction_to_Cache_%28ELUG%29)
-



## query-type

Use `eclipselink.query-type` to specify which EclipseLink query type to use for the query.

### Values

[Table 4–35](#) describes this query hint's valid values.

**Table 4–35** Valid Values for `org.eclipse.persistence.config.QueryType`

Value	Description
Auto	(Default = 0) EclipseLink chooses the type of query.
ReadAll	Use a <code>ReadAllQuery</code> .
ReadObject	Use a <code>ReadObjectQuery</code> .
Report	Use a <code>ReportQuery</code> .

### Usage

By default, EclipseLink uses `org.eclipse.persistence.queries.ReportQuery` or `org.eclipse.persistence.queries.ReadAllQuery` for most JPQL queries. Use the `eclipselink.query-type` hint lets to specify another query type, such as `org.eclipse.persistence.queries.ReadObjectQuery` for queries that will return a single object.

### Examples

[Example 4–66](#) shows how to use this hint in a JPA query.

**Example 4–66** Using query-type in a JPA Query

```
import org.eclipse.persistence.config.QueryType;
import org.eclipse.persistence.config.QueryHints;
query.setHint(QueryHints.QUERY_TYPE, QueryType.ReadObject);
```

[Example 4–67](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4–67** Using query-type in a `@QueryHint` Annotation

```
import org.eclipse.persistence.config.QueryType;
import org.eclipse.persistence.config.TargetDatabase;
@QueryHint(name=QueryHints.QUERY_TYPE, value=QueryType.ReadObject);
```

### See Also

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)



## read-only

Use `eclipselink.read-only` to retrieve read-only results back from a query.

### Values

[Table 4–36](#) describes this query hint's valid values.

**Table 4–36** *Valid Values for read-only*

Value	Description
TRUE	Retrieve read-only results from the query.
FALSE	(Default) Do not retrieve read-only results from the query.

### Usage

For non-transactional read operations, if the requested entity types are stored in the shared cache you can request that the shared instance be returned instead of a detached copy.

---

**Note:** You should never modify objects returned from the shared cache.

---

### Examples

[Example 4–68](#) shows how to use this hint in a JPA query.

**Example 4–68** *Using read-only in a JPA Query*

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.QueryHints;
query.setHint(QueryHints.READ_ONLY, HintValues.TRUE);
```

[Example 4–69](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4–69** *Using read-only in a @QueryHint Annotation*

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.QueryHints;
@QueryHint(name=QueryHints.READ_ONLY, value=HintValues.TRUE);
```

### See Also

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
- "Using Read-Only Queries"  
[http://wiki.eclipse.org/Using\\_Advanced\\_Query\\_API\\_%28ELUG%29#Using\\_Read-Only\\_Queries](http://wiki.eclipse.org/Using_Advanced_Query_API_%28ELUG%29#Using_Read-Only_Queries)



## refresh

Use `eclipselink.refresh` to specify whether or not to update the EclipseLink session cache with objects returned by the query.

### Values

[Table 4–37](#) describes this query hint's valid values.

**Table 4–37** Valid Values for `eclipselink.refresh`

Value	Description
FALSE	Refresh the cache.
FALSE	(Default) Do not refresh the cache.

### Usage

### Examples

[Example 4–70](#) shows how to use this hint in a JPA query.

**Example 4–70 Using refresh in a JPA Query**

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.QueryHints;
query.setHint(QueryHints.REFRESH, HintValues.TRUE);
```

[Example 4–71](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4–71 Using refresh in a @QueryHint Annotation**

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.QueryHints;
@QueryHint(name=QueryHints.REFRESH, value=HintValues.TRUE);
```

### See Also

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
- "[refresh.cascade](#)" on page -80





## refresh.cascade

Use `eclipselink.refresh.cascade` to specify if a refresh query should cascade the refresh to relationships.

### Values

[Table 4–38](#) describes this query hint's valid values.

**Table 4–38** Valid Values for `eclipselink.refresh.cascade`

Value	Description
<code>CascadeAllParts</code>	Cascade to all associations.
<code>CascadeByMapping</code>	Cascade by mapping metadata.
<code>CascadePrivateParts</code>	Cascade to privately-owned relationships.
<code>NoCascade</code>	Do not cascade.

### Usage

You should also use a [refresh](#) hint in order to cause the refresh.

### Examples

[Example 4–72](#) shows how to use this hint in a JPA query.

**Example 4–72** Using `refresh.cascade` in a JPA Query

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.QueryHints;
query.setHint(QueryHints.REFRESH_CASCADE, CascadePolicy.CascadeAllParts);
```

[Example 4–73](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4–73** Using `refresh.cascade` in a `@QueryHint` Annotation

```
import org.eclipse.persistence.config.HintValues;
import org.eclipse.persistence.config.QueryHints;
@QueryHint(name=QueryHints.REFRESH_CASCADE, value=CascadePolicy.CascadeAllParts);
```

### See Also

For more information, see:

- "EclipseLink" JPA Query Hints  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Querying/Query\\_Hints](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Querying/Query_Hints)
- "[refresh](#)" on page -78



## result-collection-type

Use `eclipselink.result-collection-type` to configure the collection class implementation for the query's results.

### Values

[Table 4–39](#) describes this query hint's values.

**Table 4–39** Valid Values for *result-collection-type*

Value	Description
true	Fully qualified class name, without <code>.class</code> , representing a collection type.
false	(Default) Do not ignore null results (that is, <i>do</i> cache results)

### Usage

If you use a Collection type that *is not* a List, you must use `getResultCollection()` or `getSingleResult()` instead of `getResultList()`.

### Examples

### See Also

For more information, see:

- 
-



## sql.hint

Use `eclipselink.sql.hint` to include an SQL hint in the SQL for a query.

### Values

[Table 4–40](#) describes this query hint's values.

**Table 4–40** Valid Values for *sql.hint*

Value	Description
value	The full hint string, including the comment \ delimiters

### Usage

A SQL hint can be used on certain database platforms to define how the query uses indexes and other such low level usages. The SQL hint will be included in the SQL, after the `SELECT/INSERT/UPDATE/DELETE` command.

### Examples

[Example 4–74](#) shows how to use this hint in a JPA query.

**Example 4–74** Using *sql.hint* in a JPA Query

[Example 4–75](#) shows how to use this hint with the `@QueryHint` annotation.

**Example 4–75** Using *sql.hint* in a `@QueryHint` Annotation

### See Also

For more information, see:

- Section 10.3.1 "NamedQuery Annotation" in the JPA Specification (<http://jcp.org/en/jsr/detail?id=317>).

---

## Persistence Property Extensions Reference

---

You configure persistence units in the JPA persistence descriptor file: `persistence.xml`. EclipseLink includes many persistence property enhancements and extensions that can be configured in the `persistence.xml` file.

This chapter contains the following sections:

- [Functional Listing of Persistence Property Extensions](#)
- [Alphabetical Listing of Persistence Property Extensions](#)

### Functional Listing of Persistence Property Extensions

The following lists the EclipseLink persistence property (`persistence.xml` file) extensions, categorized by function:

- [Exception Handling](#)
- [Weaving](#)
- [Customizers](#)
- [Validation and Optimization](#)
- [Caching](#)
- [Mapping Annotations](#)
- [JDBC Configuration Options](#)

#### Exception Handling

EclipseLink includes the following persistence property extensions for handling exceptions:

- 

#### Weaving

EclipseLink includes the following persistence property extensions for weaving:

- 

#### Customizers

EclipseLink includes the following persistence property extensions for customizing descriptors and sessions:

-

## Validation and Optimization

EclipseLink includes the following persistence property extensions for validation.

- 

## Logging

EclipseLink includes the following persistence property extensions for logging.

- 

## Caching

EclipseLink includes the following persistence property extensions for caching:

- 

## Mapping Annotations

EclipseLink includes the following persistence property extensions for mappings:

- 

## JDBC Configuration Options

EclipseLink includes the following persistence property extensions for configuring JDBC connections and connection pooling:

- 

## Alphabetical Listing of Persistence Property Extensions

The following lists the EclipseLink persistence property (`persistence.xml` file) extensions, in alphabetical order:

- `application-location`
- `cache.coordination.channel`
- `cache.coordination.jms.factory`
- `cache.coordination.jms.host`
- `cache.coordination.jms.reuse-topic-publisher`
- `cache.coordination.jms.topic`
- `cache.coordination.jndi.initial-context-factory`
- `cache.coordination.jndi.password`
- `cache.coordination.jndi.user`
- `cache.coordination.naming-service`
- `cache.coordination.propagate-asynchronously`
- `cache.coordination.protocol`
- `cache.coordination.remove-connection-on-error`
- `cache.coordination.rmi.announcement-delay`
- `cache.coordination.rmi.multicast-group`



- `cache.coordination.rmi.multicast-group.port`
- `cache.coordination.rmi.packet-time-to-live`
- `cache.coordination.rmi.url`
- `cache.coordination.thread.pool.size`
- `cache.database-event-listener`
- `cache.shared`
- `cache.size`
- `cache.type`
- `classloader`
- `composite-unit`
- `composite-unit.member`
- `composite-unit.properties`
- `connection-pool`
- `connection-pool.read`
- `connection-pool.sequence`
- `create-ddl-jdbc-file-name`
- `ddl.table-creation-suffix`
- `ddl-generation`
- `ddl-generation.output-mode`
- `deploy-on-startup`
- `descriptor.customizer`
- `drop-ddl-jdbc-file-name`
- `exception-handler`
- `exclude-eclipselink-orm`
- `flush-clear.cache`
- `id-validation`
- `jdbc.allow-native-sql-queries`
- `jdbc.batch-writing`
- `jdbc.batch-writing.size`
- `jdbc.bind-parameters`
- `jdbc.cache-statements`
- `jdbc.cache-statements.size`
- `jdbc.connector`
- `jdbc.exclusive-connection.is-lazy`
- `jdbc.exclusive-connection.mode`
- `jdbc.native-sql`
- `jdbc.property`

- `jdbc.sql-cast`
- `jdbc.uppercase-columns`
- `jpa.uppercase-column-names`
- `jpql.parser`
- `jpql.validation`
- `logging.connection`
- `logging.exceptions`
- `logging.file`
- `logging.level`
- `logging.session`
- `logging.thread`
- `logging.timestamp`
- `metadata-source`
- `metadata-source.properties.file`
- `metadata-source.send-refresh-command`
- `metadata-source.xml.url`
- `nosql.connection-factory`
- `nosql.connection-spec`
- `nosql.property`
- `oracle.proxy-type`
- `orm.throw.exceptions`
- `orm.validate.schema`
- `partitioning`
- `partitioning.callback`
- `persistence-context.close-on-commit`
- `persistence-context.commit-without-persist-rules`
- `persistence-context.flush-mode`
- `persistence-context.persist-on-commit`
- `persistence-context.reference-mode`
- `persistenceunits`
- `persistencexml`
- `profiler`
- `session.customizer`
- `session.include.descriptor.queries`
- `session-event-listener`
- `session-name`
- `sessions-xml`

- [target-database](#)
- [target-server](#)
- `temporal.mutable`
- `tenant-id`
- [transaction.join-existing](#)
- [validate-existence](#)
- [validation-only](#)
- [weaving](#)
- `weaving.changetracking`
- [weaving.eager](#)
- `weaving.fetchgroups`
- [weaving.internal](#)
- [weaving.lazy](#)

## application-location

Use `eclipselink.application-location` to specify the file system directory in which EclipseLink writes (outputs) DDL files.

### Values

[Table 5–1](#) describes this persistence property's values.

**Table 5–1** Valid Values for application-location

Value	Description
value	

### Usage

You may set this option only if `eclipselink.ddl-generation.output-mode` is `sql-script` or `both`.

### Examples

[Example 5–1](#) shows how to use this persistence property extension in the `persistence.xml` file.

**Example 5–1** Using application-location in persistence.xml

```
<property name="eclipselink.application-location" value="c:/YOURDIRECTORY"/>
```

### See Also

For more information, see:

- ["ddl-generation.output-mode"](#) on page -68



# [[[cache.coordination.channel]

[Use [eclipselink.cache.coordination.channel] to configure cache coordination for a clustered environment.]

## [[Values]

[[Table 5–2] describes this persistence property’s values. ]

**Table 5–2** [ ]Valid Values for cache.coordination.channel

[Value]	[Description]
[channel name]	[The channel used for cache coordination. All persistence units using the same channel will be coordinated. ] [Default: [EclipseLinkCommandChannel]]

## [[Usage]

[]]

## [[Examples]

[[Example 5–2] shows how to use this persistence property extension in the [persistence.xml] file.]

**Example 5–2** [[Using application-location in persistence.xml]

```
[<property name="eclipselink.cache.coordination.channel" value="EmployeeChannel "
/>]
[[]]
```

## [[See Also]

- [For more information, see:]
- [["@Cache" on page -16]]
  - [{"Clustering and Cache Coordination" [\[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Coordination\]](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Coordination)]]
  - [{"Cache Coordination Example" [\[http://wiki.eclipse.org/EclipseLink/Examples/JPA/CacheCoordination\]](http://wiki.eclipse.org/EclipseLink/Examples/JPA/CacheCoordination)]]]
- [[]]]



## cache.coordination.jms.factory

Use `eclipselink.cache.coordination.jms.factory` to configure the JMS topic connection factory name, when using JMS coordination for a clustered environment.

### Values

[Table 5–3](#) describes this persistence property's values.

**Table 5–3** Valid Values for *cache.coordination.jms.factory*

Value	Description
	The JMS topic connection factory name. Default: <code>jms/EclipseLinkTopicConnectionFactory</code>

### Usage

Use this property for JMS coordination (when `eclipselink.cache.coordination.protocol = jms`).

### Examples

See [Example 5–6](#) for an example of using this property.

### See Also

For more information, see:

- ["cache.coordination.protocol"](#) on page -28





## cache.coordination.jms.host

Use `eclipselink.cache.coordination.jms.host` to configure the URL of the JMS server that hosts the topic, when using JMS coordination for a clustered environment.

### Values

[Table 5–4](#) describes this persistence property's values.

**Table 5–4** Valid Values for *cache.coordination.jms.host*

Value	Description
	The URL for the JMS server.
	This is not required if the topic is distributed across the cluster (that is, it can be looked up in local JNDI)

### Usage

Use this property for JMS coordination (when `eclipselink.cache.coordination.protocol = jms`).

### Examples

See [Example 5–6](#) for an example of using this property.

### See Also

For more information, see:

- ["cache.coordination.protocol"](#) on page -28



## cache.coordination.jms.reuse-topic-publisher

Use `eclipselink.cache.coordination.jms.reuse-topic-publisher` to specify if the JSM transport manager should cache a `TopicPublisher` and reuse it for all cache coordination publishing.

### Values

[Table 5–5](#) describes this persistence property's values.

**Table 5–5** Valid Values for `cache.coordination.jms.reuse-topic-publisher`

Value	Description
true	
false (Default)	

### Usage

Use this property for JMS coordination (when `eclipselink.cache.coordination.protocol = jms`).

### Examples

See [Example 5–6](#) for an example of using this property.

### See Also

For more information, see:

- ["cache.coordination.protocol"](#) on page -28



## cache.coordination.jms.topic

Use `eclipselink.cache.coordination.jms.topic` to set the JMS topic name, when using JMS coordination for a clustered environment.

### Values

[Table 5–6](#) describes this persistence property's values.

**Table 5–6** Valid Values for `cache.coordination.jms.topic`

Value	Description
name	Set the JMS topic name. Default: <code>jms/EclipseLinkTopic</code>

### Usage

Use this property for JMS coordination (when `eclipselink.cache.coordination.protocol = jms`).

### Examples

See [Example 5–6](#) for an example of using this property.

### See Also

For more information, see:

- ["cache.coordination.protocol"](#) on page -28



## cache.coordination.jndi.initial-context-factory

Use `eclipselink.cache.coordination.jndi.initial-context-factory` to set the JNDI `InitialContext` factory, when using cache coordination for a clustered environment.

### Values

[Table 5–7](#) describes this persistence property's values.

**Table 5–7** Valid Values for `cache.coordination.jndi.initial-context-factory`

Value	Description
name	Name of the JNDI <code>InitialContext</code> factory.

### Usage

Normally, you will not need this property when connecting to the local server.

### Examples

### See Also

For more information, see:

- ["cache.coordination.protocol"](#) on page -28





## cache.coordination.jndi.password

---

Use `eclipselink.cache.coordination.jndi.password` to set the password for the `cache.coordination.jndi.user`, when using cache coordination for a clustered environment.

### Values

[Table 5–8](#) describes this persistence property's values.

**Table 5–8** Valid Values for `cache.coordination.jndi.password`

Value	Description
value	

### Usage

Normally, you will not need this property when connecting to the local server.

### Examples

[Example 5–3](#) shows how to use this property in the `persistence.xml` file.

**Example 5–3** Using `cache.coordination.jndi.password` in `persistence.xml`

```
<property name="eclipselink.cache.coordination.jndi.user" value="USERNAME"/>
<property name="eclipselink.cache.coordination.jndi.password" value="PASSWORD"/>
```

### See Also

For more information, see:

- ["cache.coordination.jndi.user"](#) on page -22
- ["cache.coordination.protocol"](#) on page -28



## cache.coordination.jndi.user

---

Use `eclipselink.cache.coordination.jndi.user` to set JNDI naming service user, when using cache coordination for a clustered environment.

### Values

[Table 5–9](#) describes this persistence property's values.

**Table 5–9** *Valid Values for `cache.coordination.jndi.user`*

Value	Description

### Usage

Normally, you will not need this property when connecting to the local server.

### Examples

See [Example 5–6](#) for an example of how to use this property.

### See Also

For more information, see:

- ["cache.coordination.jndi.password"](#) on page -20
- ["cache.coordination.protocol"](#) on page -28



## cache.coordination.naming-service

Use `eclipselink.cache.coordination.naming-service` to specify the naming service to use, when using cache coordination for a clustered environment.

### Values

[Table 5–10](#) describes this persistence property's values.

**Table 5–10** Valid Values for `cache.coordination.naming-service`

Value	Description
jndi	
rmi	

### Usage

### Examples

[Example 5–4](#) shows how to use this property in the `persistence.xml` file.

**Example 5–4** Using `cache.coordination.naming-service` in `persistence.xml`

```
<property name="eclipselink.cache.coordination" value="true" />
<property name="eclipselink.cache.coordination.naming-service" value="jndi" />
```

### See Also

For more information, see:

- ["cache.coordination.protocol"](#) on page -28



# cache.coordination.propagate-asynchronously

Use `eclipselink.cache.coordination.propagate-asynchronously` to specify if the coordination broadcast should occur asynchronously with the committing thread property configures cache coordination for a clustered environment. Set if the coordination broadcast should occur asynchronously with the committing thread. This means the coordination will be complete before the thread returns from the commit of the transaction.

## Values

[Table 5–11](#) describes this persistence property’s values.

**Table 5–11** Valid Values for `cache.coordination.propagate-asynchronously`

Value	Description
true	(Default) EclipseLink will broadcast asynchronously. The coordination will be complete before the thread returns from the committing the transaction.
false	EclipseLink will broadcast synchronously.

## Usage

JMS cache coordination is always asynchronous, regardless of this setting.

By default, RMI cache coordination is asynchronous. Use synchronous (`eclipselink.cache.coordination.propagate-asynchronously = false`) to ensure that all servers are updated before the request returns.

## Examples

[Example 5–5](#) shows how to use this property in the `persistence.xml` file.

**Example 5–5** Using `cache.coordination.propagate-asynchronously` in `persistence.xml`

```
<property name="eclipselink.cache.coordination.propagate-asynchronously" value="false" />
```

## See Also

- For more information, see:
- ["cache.coordination.protocol"](#) on page -28





## cache.coordination.protocol

Use `eclipselink.cache.coordination.protocol` to specify the cache coordination protocol to use. Depending on the cache configuration for each descriptor, this will broadcast cache updates or inserts to the cluster to update or invalidate each session's cache.

### Values

[Table 5–12](#) describes this persistence property's values.

**Table 5–12** Valid Values for `cache.coordination.protocol`

Value	Description
jms	
jms-publishing	
rmi	
rmi-iiop	

### Usage

You must specify the `cache.coordination.protocol` for every persistence unit and session in the cluster.

### Examples

[Example 5–6](#) shows how to configure JMS cache coordination in the `persistence.xml` file.

**Example 5–6** Configuring JMS Cache Coordination in `persistence.xml`

```
<property name="eclipselink.cache.coordination.protocol" value="jms" />
<property name="eclipselink.cache.coordination.jms.topic"
value="jms/EmployeeTopic" />
<property name="eclipselink.cache.coordination.jms.factory"
value="jms/EmployeeTopicConnectionFactory" />
```

If your application *is not* running in a cluster, you must provide the URL:

```
<property name="eclipselink.cache.coordination.jms.host"
value="t3://myserver:7001/" />
```

You can also include a username and password, if required, to access the server (for example, if on a separate domain):

```
<property name="eclipselink.cache.coordination.jndi.user" value="weblogic" />
<property name="eclipselink.cache.coordination.jndi.password" value="welcome1" />
```

**Example 5–7** Configuring RMI Cache Coordination in `persistence.xml`

```
<property name="eclipselink.cache.coordination.protocol" value="rmi" />
```

If your application *is not* running in a cluster, you must provide the URL:

```
<property name="eclipselink.cache.coordination.rmi.url"
value="t3://myserver:7001/" />
```

You can also include a username and password, if required, to access the server (for example, if on a separate domain):

```
<property name="eclipselink.cache.coordination.jndi.user" value="weblogic" />
<property name="eclipselink.cache.coordination.jndi.password" value="welcome1" />
```

By default, RMI cache coordination broadcasts are asynchronous. You can override this, if needed:

```
<property name="eclipselink.cache.coordination.propagate-asynchronously"
value="false" />
```

If you have multiple applications on the same server or network, you can specify a separate cache coordination channel for each application:

```
<property name="eclipselink.cache.coordination.channel" value="EmployeeChannel" />
```

RMI cache coordination uses a multicast socket to allow servers to find each other. You can configure the multicast settings, if needed:

```
<property name="eclipselink.cache.coordination.rmi.announcement-delay"
value="1000" />
<property name="eclipselink.cache.coordination.rmi.multicast-group"
value="239.192.0.0" />
<property name="eclipselink.cache.coordination.rmi.multicast-group.port"
value="3121" />
<property name="eclipselink.cache.coordination.packet-time-to-live" value="2" />
```

## See Also

For more information, see:

- ["cache.coordination.channel"](#) on page -8
- ["cache.coordination.jms.factory"](#) on page -10
- ["cache.coordination.jms.host"](#) on page -12
- ["cache.coordination.jms.reuse-topic-publisher"](#) on page -14
- ["cache.coordination.jms.topic"](#) on page -16
- ["cache.coordination.jndi.initial-context-factory"](#) on page -18
- ["cache.coordination.jndi.password"](#) on page -20
- ["cache.coordination.jndi.user"](#) on page -22
- ["cache.coordination.naming-service"](#) on page -24
- ["cache.coordination.propagate-asynchronously"](#) on page -26
- ["cache.coordination.remove-connection-on-error"](#) on page -32
- ["cache.coordination.rmi.announcement-delay"](#) on page -34
- ["cache.coordination.rmi.multicast-group"](#) on page -36
- ["cache.coordination.rmi.multicast-group.port"](#) on page -38

- "cache.coordination.rmi.packet-time-to-live" on page -40
- "cache.coordination.rmi.url" on page -42
- "cache.coordination.thread.pool.size" on page -44
- Cache Coordination Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/CacheCoordination>
- "Clustering and Cache Coordination"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Coordination](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Coordination)



## cache.coordination.remove-connection-on-error

Use `eclipselink.cache.coordination.remove-connection-on-error` to specify if the connection should be removed if EclipseLink encounters a communication error when coordinating the cache.

### Values

[Table 5–13](#) describes this persistence property's values.

**Table 5–13** Valid Values for `cache.coordination.remove-connection-on-error`

Value	Description
true	Remove the connection if a communication error occurs. EclipseLink will reconnect when the server becomes available.
false	

### Usage

Normally, this is used for RMI connections in the event that a server goes down.

### Examples

[Example 5–8](#) shows how to use this property in the `persistence.xml` file.

**Example 5–8** Using `cache.coordination.remove-connection-on-error` in `persistence.xml`

```
<property name="eclipselink.cache.coordination.remove-connection-on-error"
value="true"/>
```

### See Also

For more information, see:

- ["cache.coordination.protocol"](#) on page -28



## cache.coordination.rmi.announcement-delay

Use `eclipselink.cache.coordination.rmi.announcement-delay` to set the time (in milliseconds) to wait for announcements from other cluster members on startup.

### Values

[Table 5–14](#) describes this persistence property's values.

**Table 5–14** Valid Values for `cache.coordination.rmi.announcement-delay`

Value	Description
Numeric	Time (in milliseconds) to wait for announcements, on startup. Default: 1000

### Usage

Use this property for RMI coordination (when `eclipselink.cache.coordination.protocol = rmi`).

### Examples

See [Example 5–7](#) to learn how to use this property in the `persistence.xml` file.

### See Also

For more information, see:

- ["cache.coordination.protocol"](#) on page -28





## cache.coordination.rmi.multicast-group

Use `eclipselink.cache.coordination.rmi.multicast-group` to set the multicast socket group address (used to find other members of the cluster), when using cache coordination for a clustered environment.

### Values

[Table 5–15](#) describes this persistence property's values.

**Table 5–15** Valid Values for `cache.coordination.rmi.multicast-group`

Value	Description
Numeric	Set the multicast socket group address Default: 239.192.0.0

### Usage

Use this property for RMI coordination (when `eclipselink.cache.coordination.protocol = rmi`).

### Examples

See [Example 5–7](#) to learn how to use this property in the `persistence.xml` file.

### See Also

For more information, see:

- ["cache.coordination.protocol"](#) on page -28



## cache.coordination.rmi.multicast-group.port

Use `eclipselink.cache.coordination.rmi.multicast-group.port` to set the multicast socket group port (used to find other members of the cluster), when using cache coordination for a clustered environment.

### Values

[Table 5–16](#) describes this persistence property's values.

**Table 5–16** Valid Values for `cache.coordination.rmi.multicast-group.port`

Value	Description
Numeric	Set the multicast socket group port Default: 3121

### Usage

Use this property for RMI coordination (when `eclipselink.cache.coordination.protocol = rmi`).

### Examples

See [Example 5–7](#) to learn how to use this property in the `persistence.xml` file.

### See Also

For more information, see:

- ["cache.coordination.protocol"](#) on page -28



## cache.coordination.rmi.packet-time-to-live

Use `eclipselink.cache.coordination.rmi.packet-time-to-live` to set the number of hops the session announcement data packets will take before expiring. The multicast group is used to find other members of the cluster.

### Values

[Table 5–17](#) describes this persistence property's values.

**Table 5–17** Valid Values for `cache.coordination.rmi.packet-time-to-live`

Value	Description
Numeric	Number of hops the session announcement data packets will take before expiring. Default: 2

### Usage

If sessions are hosted on different LANs that are part of WAN, the announcement sent by one session may not reach other sessions. In this case, consult your network administrator for the correct time-to-live value or test your network by increasing the value until each session receives announcement sent by others.

Use this property for RMI coordination (when `eclipselink.cache.coordination.protocol = rmi`).

### Examples

See [Example 5–7](#) to learn how to use this property in the `persistence.xml` file.

### See Also

For more information, see:

- ["cache.coordination.protocol"](#) on page -28



## cache.coordination.rmi.url

Use `eclipselink.cache.coordination.rmi.url` to set the URL of the host server. This is the URL that other cluster member use to connect to this host.

### Values

[Table 5–18](#) describes this persistence property's values.

**Table 5–18** Valid Values for `cache.coordination.rmi.url`

Value	Description
	URL of the host server
	Default: <code>local</code>

### Usage

Use this property for RMI coordination (when `eclipselink.cache.coordination.protocol = rmi`).

This may not be required in a clustered environment where JNDI is replicated. You can also set the location as a System property or using a `SessionCustomizer` to avoid requiring a separate `persistence.xml` file per server.

### Examples

See [Example 5–7](#) to learn how to use this property in the `persistence.xml` file.

### See Also

For more information, see:

- ["cache.coordination.protocol"](#) on page -28





## cache.coordination.thread.pool.size

---

Use `eclipselink.cache.coordination.thread.pool.size` to configure the size of the thread pool, for cache coordination threads.

### Values

[Table 5–19](#) describes this persistence property's values.

**Table 5–19** Valid Values for `cache.coordination.thrad.pool.size`

Value	Description
Numeric	Size of the thread pool. If 0, EclipseLink does not use a thread pool; instead threads are spawned when required. Default: 32

### Usage

For RMI cache coordination, EclipseLink spawns one thread per node to send change notifications and one thread to listen for new node notifications.

For JMS cache coordination, EclipseLink spawns one thread to *receive* JMS change notification messages (unless MDB is used) and one thread to *process* the change notification (unless MDB is used).

### Examples

### See Also

For more information, see:

- ["cache.coordination.protocol"](#) on page -28



# cache.database-event-listener

Use `eclipselink.cache.database-event-listener` to integrate EclipseLink with a database event notification service, such as Oracle QCN/DCN (Query Change Notification/Database Change Notification).

## Values

Table 5–20 describes this persistence property’s values.

Table 5–20 Valid Values for `cache.database-event-listener`

Value	Description
Class	The name of a class that implements <code>DatabaseEventListener</code> , such as the <code>OracleChangeNotificationListener</code> ( <code>org.eclipse.persistence.platform.database.oracle.dcn.OracleChangeNotificationListener</code> )  You can also use <b>DCN</b> and <b>QCN</b> for Oracle.

## Usage

You can use this property to allow the EclipseLink cache to be invalidated by database change events, triggers, or other services.

## Examples

Example 5–9 shows how to use this property with Oracle DCN.

Example 5–9 Using `cache.database-event-listener` in `persistence.xml`

```
<?xml version="1.0" encoding="UTF-8"?>
<persistence xmlns="http://java.sun.com/xml/ns/persistence"
             xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
             xsi:schemaLocation="http://java.sun.com/xml/ns/persistence
persistence_2_0.xsd"
             version="2.0">
  <persistence-unit name="acme" transaction-type="RESOURCE_LOCAL">
    <provider>org.eclipse.persistence.jpa.PersistenceProvider</provider>
    <exclude-unlisted-classes>false</exclude-unlisted-classes>
    <properties>
      <property name="eclipselink.cache.database-event-listener"
value="org.eclipse.persistence.platform.database.oracle.dcn.OracleChangeNotificati
onListener"/>
    </properties>
  </persistence-unit>
</persistence>
```

## See Also

- For more information, see:
- ["@Cache"](#) on page -16
  - "Database Change Notification" in *Oracle Fusion Middleware Configuring and Managing JDBC Data Sources for Oracle WebLogic Server*

- "Clustering and Cache Coordination"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Coordination](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Coordination)
- Cache Coordination Example  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/CacheCoordination>

---

## classloader

Use `eclipselink.classloader` to create an `EntityManagerFactory` in the property map to be passed to `Persistence.createEntityManagerFactory`.

### Values

[Table 5–21](#) describes this persistence property's values.

**Table 5–21**    *Valid Values for classloader*

Value	Description

### Usage

This is a dynamic property that must be set at runtime, in the property map. You cannot configure this property in the `persistence.xml` file.

### Examples

[Example 5–10](#) shows how to use this extension in a property map

**Example 5–10**    *Using classloader in a Property Map*

```
properties.put("eclipselink.classloader", this.getClass().getClassLoader());
```

### See Also

For more information, see:

-



## composite-unit

Use `eclipselink.composite-unit` to specify if the persistence unit is a *composite* persistence unit.

### Values

[Table 5–22](#) describes this persistence property's values.

**Table 5–22** Valid Values for *composite-unit*

Value	Description
true	Persistence unit <i>is</i> a composite persistence unit.
false	(Default) Persistence unit <i>is not</i> a composite persistence unit.

### Usage

The property must be specified in `persistence.xml` of a composite persistence unit. The composite persistence unit must contain all persistence units found in JAR files specified by the `persistence.xml` file.

---

---

**Note:** If this property is passed to the `createEntityManagerFactory` method or if it is set in system properties, it is ignored.)

---

---

### Examples

[Example 5–11](#) shows how to use this persistence property extension in the `persistence.xml` file.

**Example 5–11** Using *composite-unit* in *persistence.xml*

```
<persistence xmlns="http://java.sun.com/xml/ns/persistence"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://java.sun.com/xml/ns/persistence persistence_1_0.xsd"
version="1.0">
  <persistence-unit name="compositePu" transaction-type="JTA">
    <provider>
      org.eclipse.persistence.jpa.PersistenceProvider
    </provider>

    <jar-file>member1.jar</jar-file>
    <jar-file>member2.jar</jar-file>

    <properties>
      <property name="eclipselink.composite-unit" value="true"/>
      <property name="eclipselink.target-server" value="WebLogic_10"/>
    </properties>
  </persistence-unit>
</persistence>
```



## See Also

For more information, see:

- ["composite-unit.member"](#) on page -52
- ["composite-unit.properties"](#) on page -54
- "Composite Persistence Units"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Composite\\_Persistence\\_Units](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Composite_Persistence_Units)
-

# composite-unit.member

Use `eclipselink.composite-unit.member` to specify if the persistence unit is a *member* composite persistence unit.

## Values

Table 5–23 describes this persistence property’s values.

Table 5–23 Valid Values for *composite-unit.member*

Value	Description
true	The persistence unit must be a member of a composite persistence unit and cannot be used as an independent persistence unit.
false	The persistence unit does not have to be a member of a composite persistence unit.

## Usage

Setting this property to `true` indicates that the persistence unit has dependencies on other persistence units.

**Note:** If this property is passed to the `createEntityManagerFactory` method or if it is set in system properties, it is ignored.)

If this property is `true`, you may still create `EntityManagerFactory`, but it cannot be connected. Any attempt to create an entity manger will cause an exception.

### Query Hint

When executing a native query on a composite persistence unit, use `composite-unit.member` to specify the name of the composite member persistence unit on which to execute the query.

## Examples

Example 5–12 shows how to use this persistence property extension in the `persistence.xml` file.

### Example 5–12 Using *composite-unit.member* in *persistence.xml*

Composite member persistence unit **memberPu2** is defined in the **member2.jar** file. It has dependency on a class defined in **member1.jar** and cannot be used independently.

```
<persistence xmlns="http://java.sun.com/xml/ns/persistence"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://java.sun.com/xml/ns/persistence persistence_1_0.xsd"
version="1.0">
  <persistence-unit name="memberPu2">
    <provider>
      org.eclipse.persistence.jpa.PersistenceProvider
    </provider>
    <mapping-file>META-INF/advanced-entity-mappings2.xml</mapping-file>
    <jta-data-source>jdbc/MySqlJtaDS</jta-data-source>
    <exclude-unlisted-classes>>false</exclude-unlisted-classes>
```

```
<properties>
  <property name="eclipselink.composite-unit.member" value="true"/>
  <property name="eclipselink.target-database"
value="org.eclipse.persistence.platform.database.MySQLPlatform"/>
</properties>
</persistence-unit>
</persistence>
```

## See Also

For more information, see:

- ["@CompositeMember"](#) on page -36
- ["composite-unit"](#) on page -50

# composite-unit.properties

Use `eclipselink.composite-unit.properties` to configure the properties for persistence unit members.

## Values

[Table 5–24](#) describes this persistence property’s values.

**Table 5–24** Valid Values for *composite-unit.properties*

Value	Description
Map of properties	Properties to be passed to the persistence unit. Use the persistence unit’s name as the key.

## Usage

Pass this property to `createEntityManager` method of a composite persistence unit to pass properties to its member persistence units.

## Examples

[Example 5–13](#) shows how to use this extension in a property map

**Example 5–13** Using *composite-unit.properties* in a Property Map

```
Map props1 = new HashMap();

    props1.put("javax.persistence.jdbc.user", "user1");
    props1.put("javax.persistence.jdbc.password", "password1");
    props1.put("javax.persistence.jdbc.driver", "oracle.jdbc.OracleDriver");
    props1.put("javax.persistence.jdbc.url", "jdbc:oracle:thin:@oracle_db_
url:1521:db");

Map props2 = new HashMap();

    props2.put("javax.persistence.jdbc.user", "user2");
    props2.put("javax.persistence.jdbc.password", "password2");
    props2.put("javax.persistence.jdbc.driver", "com.mysql.jdbc.Driver");
    props2.put("javax.persistence.jdbc.url", " jdbc:mysql://my_sql_db_
url:3306/user2");

Map memberProps = new HashMap();
    memberProps.put("memberPu1", props1);
    memberProps.put("memberPu2", props2);

Map props = new HashMap();
    props.put("eclipselink.logging.level", "FINEST");
    props.put("eclipselink.composite-unit.properties", memberProps);

EntityManagerFactory emf = Persistence.createEntityManagerFactory("compositePu",
props);
```

## See Also

For more information, see:

- ["composite-unit"](#) on page -50



## connection-pool

Use `eclipselink.connection-pool` to configure the various connection pool properties.

### Values

[Table 5–25](#) describes this persistence property's values.

**Table 5–25** Valid Values for *connection-pool*

Value	Description
<code>initial</code>	Starting (initial) number of connections
<code>min</code>	Minimum number of connections
<code>max</code>	Maximum number of connections.
<code>wait</code>	Amount of time (in milliseconds) to wait for a connection from the pool.
<code>url</code>	URL of the JDBC for the connection
<code>shared</code>	For read connection pools, indicates that read connections are shared across threads.
<code>jtaDataSource</code>	JTA DataSource name to use for the connection, if different than the default
<code>nonJtaDataSource</code>	Non-JTA DataSource name to use for the connection, if different than the default
<code>user</code>	Username to use for this connection (if different than the default).
<code>password</code>	Password of the user for this connection (if different than the default)

### Usage

Append the name of the connection pool and property to be configured. If connection pool is specified, EclipseLink configures the default (write) pool.

### Examples

[Example 5–14](#) shows how to use this property in the `persistence.xml` file.

**Example 5–14** Using *connection-pool* in *persistence.xml*

```
<property name="eclipselink.connection-pool.default.initial" value="1" />
<property name="eclipselink.connection-pool.node2.min" value="16" />
<property name="eclipselink.connection-pool.node2.max" value="16" />
<property name="eclipselink.connection-pool.node2.url"
value="jdbc:oracle:thin:@node2:1521:orcl" />
```

### See Also

For more information, see:

- Partitioning Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Partitioning>
- "Data Partitioning"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Data\\_Partitioning](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Data_Partitioning)
- "[jdbc.cache-statements](#)" on page -90

- ["connection-pool.read"](#) on page -58
- ["connection-pool.sequence"](#) on page -60

## connection-pool.read

---

Use `eclipselink.connection-pool.read` to configure a read connection pool for non-transaction read queries.

### Values

[Table 5–26](#) describes this persistence property's values.

**Table 5–26** *Valid Values for connection-pool.read*

Value	Description

### Usage

By default, EclipseLink *does not* use a separate read connection pool; the default pool is used for read queries.

### Examples

[Example 5–15](#) shows how to use this property in the `persistence.xml` file.

**Example 5–15** *Using connection-pool.read in persistence.xml*

### See Also

For more information, see:

- ["connection-pool"](#) on page -56





## connection-pool.sequence

Use `eclipselink.connection-pool.sequence` to have the connection pool allocate generated IDs.

### Values

[Table 5–27](#) describes this persistence property's values.

**Table 5–27** *Valid Values for connection-pool.sequence*

Value	Description

### Usage

This is only required for `TABLE` sequencing. By default, EclipseLink *does not* use a separate sequence connection pool; the default pool is used for sequencing.

### Examples

[Example 5–16](#) shows how to use this property in the `persistence.xml` file.

**Example 5–16** *Using connection-pool.sequence in persistence.xml*

### See Also

For more information, see:

- ["connection-pool"](#) on page -56



## create-ddl-jdbc-file-name

Use `eclipselink.create-ddl-jdbc-file-name` to specify the name of the DDL file generated by EclipseLink that contains the SQL statements to create tables for JPA entities.

### Values

[Table 5–28](#) describes this persistence property's values.

**Table 5–28** Valid Values for *create-ddl-jdbc-file-name*

Value	Description
File name	A file name valid for your operating system.  You can prefix the file name with a file path if a concatenation of <code>eclipselink.application-location</code> + <code>eclipselink.create-ddl-jdbc-file-name</code> is valid for your operating system.

### Usage

If `eclipselink.ddl-generation` is set to `create-tables` or `drop-and-create-tables`, EclipseLink writes this file to the location specified by `eclipselink.application-location`.

### Examples

See [Example 5–17](#) for information on how to use this property in the `persistence.xml` file.

### See Also

For more information, see:

- ["application-location"](#) on page -6
- ["ddl-generation"](#) on page -66



## ddl.table-creation-suffix

Use `eclipselink.ddl.table-creation-suffix` to append a string to the end of generated `CREATE Table` statements. EclipseLink adds this suffix to all generated DDL `CREATE` statements.

### Values

[Table 5–29](#) describes this persistence property's values.

**Table 5–29**    *Valid Values for `ddl-generation.table-creation-suffix`*

Value	Description

### Usage

### Examples

### See Also

For more information, see:

- ["ddl-generation"](#) on page -66



## ddl-generation

Use `eclipselink.ddl-generation` to specify how EclipseLink generates DDL (Data Definition Language) for the database schema (tables and constraints) on deployment

### Values

[Table 5–30](#) describes this persistence property's values.

**Table 5–30** Valid Values for `ddl-generation`

Value	Description
<code>create-tables</code>	EclipseLink will attempt to execute a <code>CREATE TABLE</code> SQL for each table.  If the table already exists, EclipseLink will follow the default behavior of your specific database and JDBC driver combination (when a <code>CREATE TABLE</code> SQL is issued for an already existing table). In most cases an exception is thrown and the table is not created; the existing table will be used. EclipseLink will then continue with the next statement.
<code>create-or-extend</code>	EclipseLink will attempt to create tables. If the table exists, EclipseLink will add any missing columns.
<code>drop-and-create</code>	EclipseLink will attempt to <code>DROP</code> all tables, then <code>CREATE</code> all tables. If any issues are encountered, EclipseLink will follow the default behavior of your specific database and JDBC driver combination, then continue with the next statement  This is useful in development if the schema frequently changes or during testing when the existing data needs to be cleared.  <b>Note:</b> Using <code>drop-and-create</code> will remove all of the data in the tables when they are dropped. You should never use option on a production schema that has valuable data in the database. If the schema changed dramatically, there could be old constraints in the database that prevent the dropping of the old tables. This may require the old schema to be dropped through another mechanism
<code>none</code>	(Default) No DDL generated; no schema generated.

### Usage

You can use `create-and-extend` only when `eclipselink.ddl-generation.output-mode = database`.

If you are using persistence in a Java SE environment and would like to create the DDL files without creating tables, additionally define a Java system property `INTERACT_WITH_DB` and set its value to `false`.

### Examples

[Example 5–17](#) shows how to use this property in the `persistence.xml` file.

**Example 5–17** Using `ddl-generation` in `persistence.xml`

```
<property name="eclipselink.ddl-generation" value="drop-and-create-tables"/>
<property name="eclipselink.create-ddl-jdbc-file-name" value="createDDL_
ddlGeneration.jdbc"/>
<property name="eclipselink.drop-ddl-jdbc-file-name" value="dropDDL_
ddlGeneration.jdbc"/>
<property name="eclipselink.ddl-generation.output-mode" value="both"/>
```

[Example 5–18](#) shows how to use this property in a property map.



**Example 5–18 Using ddl-generation in a Property Map**

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.DDL_GENERATION,
PersistenceUnitProperties.DROP_AND_CREATE);
propertiesMap.put(PersistenceUnitProperties.DDL_GENERATION_MODE,
PersistenceUnitProperties.BOTH);
propertiesMap.put(PersistenceUnitProperties.CREATE_JDBC_DDL_FILE, "create.sql");
```

**See Also**

For more information, see:

- ["create-ddl-jdbc-file-name"](#) on page -62
- ["drop-ddl-jdbc-file-name"](#) on page -74
- ["ddl-generation.output-mode"](#) on page -68
- Example  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/DDL>

## ddl-generation.output-mode

Use `eclipselink.ddl-generation.output-mode` to specify where EclipseLink generates and writes the DDL.

### Values

[Table 5–31](#) describes this persistence property's values.

**Table 5–31** Valid Values for `ddl-generation.output-mode`

Value	Description
both	<p>DDL will be generated and written to both the database and a file.</p> <ul style="list-style-type: none"> <li>■ If <code>eclipselink.ddl-generation</code> is set to <code>create-tables</code>, then <code>eclipselink.create-ddl-jdbc-file-name</code> is written to <code>eclipselink.application-location</code> and executed on the database.</li> <li>■ If <code>eclipselink.ddl-generation</code> is set to <code>drop-and-create-tables</code>, then both <code>eclipselink.create-ddl-jdbc-file-name</code> and <code>eclipselink.drop-ddl-jdbc-file-name</code> are written to <code>eclipselink.application-location</code>, and both SQL files are executed on the database.</li> </ul>
database	(Default) DDL will be generated and written to the database only.
sql-script	<p>DDL will be generated and written to a file only.</p> <ul style="list-style-type: none"> <li>■ If <code>eclipselink.ddl-generation</code> is set to <code>create-tables</code>, then <code>eclipselink.create-ddl-jdbc-file-name</code> is written to <code>eclipselink.application-location</code>. It is <i>not</i> executed on the database.</li> <li>■ If <code>eclipselink.ddl-generation</code> is set to <code>drop-and-create-tables</code>, then both <code>eclipselink.create-ddl-jdbc-file-name</code> and <code>eclipselink.drop-ddl-jdbc-file-name</code> are written to <code>eclipselink.application-location</code>. Neither are executed on the database.</li> </ul>

### Usage

### Examples

See [Example 5–17](#) for information on how to use this persistence property.

### See Also

For more information, see:

- ["application-location"](#) on page -6
- ["ddl-generation"](#) on page -66
- ["create-ddl-jdbc-file-name"](#) on page -62



## deploy-on-startup

Use `eclipselink.deploy-on-startup` to configure deployment on startup (at the creation of the `EntityManagerFactory`) instead of occurring the first time an `EntityManager` is created.

### Values

[Table 5–32](#) describes this persistence property's values.

**Table 5–32** Valid Values for

Value	Description
true	
false	(Default)

### Usage

Using `true` may increase startup time of a JavaEE server, but will avoid the first request from hanging as the persistence unit is deployed.

### Examples

[Example 5–19](#) shows how to use this property in the `peristence.xml` file.

**Example 5–19** Using *deploy-on-startup* in *persistence.xml*

```
<property name="eclipselink.deploy-on-startup" value="true" />
```

### See Also

For more information, see:

-



## descriptor.customizer

Use `eclipselink.descriptor.customizer` as a prefix for a property to configure a `DescriptorCustomizer`. Use this class's `customize` method, which takes an `org.eclipse.persistence.descriptors.ClassDescriptor`, to programmatically access advanced EclipseLink descriptor and mapping API for the descriptor associated with the JPA entity.

### Values

[Table 5–33](#) describes this persistence property's values.

**Table 5–33** Valid Values for *descriptor.customizer*

Value	Description
name	Full name for a class which implements <code>DescriptorCustomizer</code>

### Usage

You cannot use multiple descriptor customizers.

### Examples

[Example 5–20](#) shows how to use this property in the `persistence.xml` file.

**Example 5–20** Using *descriptor.customizer* in *persistence.xml*

```
<property name="eclipselink.descriptor.customizer.Order"
value="acme.sessions.MyDescriptorCustomizer"/>
```

[Example 5–21](#) shows how to use this property with a property map.

**Example 5–21** Using *descriptor.customizer* in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.DEScriptor_CUSTOMIZER+".Order",
"acme.sessions.MyDescriptorCustomizer");
```

### See Also

For more information, see:

- "Descriptors"  
[http://wiki.eclipse.org/Introduction\\_to\\_Descriptors\\_%28ELUG%29#Descriptor\\_Customization](http://wiki.eclipse.org/Introduction_to_Descriptors_%28ELUG%29#Descriptor_Customization)
- Section 8.1, "Entity" in the JPA Specification  
<http://jcp.org/en/jsr/detail?id=220>



## drop-ddl-jdbc-file-name

Use `eclipselink.drop-ddl-jdbc-file-name` to specify the name of the DDL file generated by EclipseLink that contains the SQL statements to drop tables for JPA entities.

### Values

[Table 5–34](#) describes this persistence property's values.

**Table 5–34** Valid Values for *drop-ddl-jdbc-file-name*

Value	Description
File name	A file name valid for your operating system.  You can prefix the file name with a file path if a concatenation of <code>eclipselink.application-location</code> + <code>eclipselink.create-ddl-jdbc-file-name</code> is valid for your operating system.

### Usage

If `eclipselink.ddl-generation` is set to `create-tables`, EclipseLink writes this file to the location specified by `eclipselink.application-location`.

### Examples

See [Example 5–17](#) for information on how to use this property in the `persistence.xml` file.

### See Also

For more information, see:

- ["ddl-generation"](#) on page -66





## exception-handler

Use `eclipselink.exception-handler` to specify the EclipseLink exception handler class: a Java class that implements the `org.eclipse.persistence.exceptions.ExceptionHandler` interface and provides a default (zero-argument) constructor.

### Values

[Table 5–35](#) describes this persistence property's values.

**Table 5–35** Valid Values for exception-handler

Value	Description
ExceptionHandler class	Use the <code>handleException</code> method of the class, which takes a <code>java.lang.RuntimeException</code> , to: <ul style="list-style-type: none"><li>■ Re-throw the exception</li><li>■ Throw a different exception</li><li>■ Retry the query or database operation.</li></ul>

### Usage

The `ExceptionHandler` class name must be fully qualified by its package name.

### Examples

[Example 5–22](#) shows how to use this persistence property extension in the `persistence.xml` file.

**Example 5–22** Using exception-handler in persistence.xml

```
<property name="eclipselink.exception-handler"
value="my.package.MyExceptionHandler">
```

[Example 5–23](#) shows how to use this extension in a property map

**Example 5–23** Using exception-handler in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.EXCEPTION_HANDLER_CLASS,
"my.package.MyExceptionHandler");
```

### See Also

For more information, see:

- ["orm.throw.exceptions"](#) on page -152
- Exception Handlers  
[http://wiki.eclipse.org/Introduction\\_to\\_EclipseLink\\_Sessions\\_%28ELUG%29#Exception\\_Handlers](http://wiki.eclipse.org/Introduction_to_EclipseLink_Sessions_%28ELUG%29#Exception_Handlers)



## exclude-eclipselink-orm

Use `eclipselink.exclude-eclipselink-orm` to exclude an EclipseLink ORM mapping file for a specific persistence unit.

### Values

[Table 5–36](#) describes this persistence property's values.

**Table 5–36** Valid Values for `exclude-eclipselink-orm`

Value	Description
true	
false	(Default) EclipseLink uses the <code>eclipselink-orm.xml</code> file.

### Usage

By default the first file found at the resource name: `META-INF/eclipselink-orm.xml` is processed and overrides configurations specified in annotations and standard mapping files.

### Examples

**Example 5–24** Using `exclude-eclipselink-orm` in `persistence.xml`

```
<property name="eclipselink.exclude-eclipselink-orm" value="true"/>
```

### See Also

For more information, see:

-



## flush-clear.cache

Use `eclipselink.flush-clear.cache` to specify the EclipseLink `EntityManager` cache behavior when a `clear` method follows the `flush` method.

### Values

[Table 5–37](#) describes this persistence property's values.

**Table 5–37** Valid Values for *flush-clear.cache*

Value	Description
Drop	EclipseLink drops the entire <code>EntityManager</code> cache.  Although this is the fastest mode and uses the least memory, the shared cache may potentially contain stale data after performing the commit.
DropInvalidate	EclipseLink drops the entire <code>EntityManager</code> cache. Classes that have at least one updated or deleted object become invalid in the shared cache after performing the commit.  This mode is slower than <code>Drop</code> , but as efficient (in terms of memory usage) and prevents stale data.
Merge	EclipseLink drops objects the <code>EntityManager</code> cache that have not been flushed.  Although this mode leaves the shared cache in a perfect state after performing the commit, it is the least memory-efficient. In a very large transaction you may run out of memory.

### Usage

You can specify this property when creating an `EntityManagerFactory` (in the map passed to the `createEntityManagerFactory` method or in the `persistence.xml` file), or an `EntityManager` (in the map passed to the `createEntityManager` method).

Note that the latter overrides the former.

### Examples

[Example 5–25](#) shows how to use this persistence property extension in the `persistence.xml` file.

**Example 5–25** Using *flush-clear.cache* in *persistence.xml*

```
<property name="eclipselink.flush-clear.cache" value="Drop"/>
```

[Example 5–26](#) shows how to use this extension in a property map

**Example 5–26** Using *flush-clear.cache* in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.FLUSH_CLEAR_CACHE,
FlushClearCache.Drop);
```

### See Also

For more information, see:

- ["@Cache"](#) on page -16

- Cache Coordination Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/CacheCoordination>
- "Clustering and Cache Coordination"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Caching/Coordination](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Caching/Coordination)

## id-validation

Use `eclipselink.id-validation` to define which primary key components values are considered invalid.

### Values

[Table 5–38](#) describes this persistence property's values.

**Table 5–38** *Valid Values for id-validation*

Value	Description
Negative	Null, 0 and negative values are invalid for IDs extending Number and primitive int and long IDs.
None	EclipseLink performs no ID validation.
Null	Null is invalid All other values are valid.
Zero	Null, 0 and negative values are invalid for primitive int and long IDs.

### Usage

Identity and sequencing (with `shouldAlwaysOverrideExistingValue` configured as `true`) will override any existing ID value.

### Examples

**Example 5–27** *Using id-validation in persistence.xml*

```
<property name="eclipselink.id-validation" value="NULL"/>
```

### See Also

For more information, see:

- ["@PrimaryKey"](#) on page -136





## jdbc.allow-native-sql-queries

Use `eclipselink.jdbc.allow-native-sql-queries` to specify if user-defined (that is, native) SQL is allowed within a persistence unit.

### Values

[Table 5–39](#) describes this persistence property's values.

**Table 5–39** Valid Values for `jdbc.allow-native-sql-queries`

Value	Description
true	(Default) EclipseLink allows native SQL.
false	EclipseLink does not allow native SQL.

### Usage

Within a multitenant, use this option to minimize the potential impact of revealing multitenant information. By default, any persistence unit with a multitenant entity causes EclipseLink to set `eclipselink.jdbc.allow-native-sql-queries` as false.

### Examples

**Example 5–28** Using `jdbc.allow-native-sql-queries` in `persistence.xml`

```
<property name="eclipselink.jdbc.allow-native-sql-queries" value="false" />
```

### See Also

For more information, see:



## jdbc.batch-writing

Use `eclipselink.jdbc.batch-writing` to configure the type of batch-writing to use.

### Values

[Table 5–40](#) describes this persistence property's values.

**Table 5–40** Valid Values for `jdbc.batch-writing`

Value	Description
<code>jdbc</code>	Use JDBC batch writing.
<code>buffered</code>	Do not use JDBC batch writing or the platform's native batch writing.
<code>oracle-jdbc</code>	Use the Oracle platform's native batch writing. In a property map, use <code>OracleJDBC</code> . <b>Note:</b> This requires an Oracle JDBC driver.
<code>none</code>	(Default) Do not use batch writing (that is, turn it off).

### Usage

With batch writing, EclipseLink can optimize transactions with multiple write functions. Use `eclipselink.jdbc.batch-writing.size` to specify the batch size.

### Examples

**Example 5–29** Using `jdbc.batch-writing` in `persistence.xml`

```
<property name="eclipselink.jdbc.batch-writing" value="Oracle-JDBC"/>
```

**Example 5–30** Using `jdbc.batch-writing` in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.BATCH_WRITING,
BatchWriting.OracleJDBC);
```

### See Also

For more information, see:

- ["jdbc.batch-writing.size"](#) on page -88



---

## jdbc.batch-writing.size

Use `eclipselink.jdbc.batch-writing.size` to configure the batch size used for batch writing.

### Values

[Table 5–41](#) describes this persistence property's values.

**Table 5–41** Valid Values for

Value	Description
batch size	For <b>parameterized</b> batch writing, this value is the number of statements to batch (default: 100).  For <b>dynamic</b> batch writing, this value is the size of the batched SQL buffer (default: 32k).

### Usage

### Examples

**Example 5–31** Using `jdbc.batch-writing.size` in `persistence.xml`

```
<property name="eclipselink.jdbc.batch-writing.size" value="1000"/>
```

### See Also

For more information, see:

- ["jdbc.batch-writing"](#) on page -86



## jdbc.cache-statements

Use `eclipselink.jdbc.cache-statements` to specify if JDBC statements should be cached.

### Values

[Table 5–42](#) describes this persistence property's values.

**Table 5–42** Valid Values for `jdbc.cache-statements`

Value	Description
true	Enable internal statement caching.
false	(Default) Disable internal statement caching.

### Usage

You should use this property when using EclipseLink's internal connection pooling. See ["connection-pool"](#) on page -56 for more information.

### Examples

**Example 5–32** Using `jdbc.cache-statements` in `persistence.xml`

```
<property name="eclipselink.jdbc.cache-statements" value="false"/>
```

**Example 5–33** Using `jdbc.cache-statements` in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.CACHE_STATEMENTS, "false");
```

### See Also

For more information, see:

- ["jdbc.cache-statements.size"](#) on page -92
- ["connection-pool"](#) on page -56





## jdbc.cache-statements.size

Use `eclipselink.jdbc.cache-statements.size` to specify the number of statements held when using internal statement caching.

### Values

[Table 5–43](#) describes this persistence property's values.

**Table 5–43** Valid Values for `jdbc.cache-statements.size`

Value	Description
size	A string value containing a positive integer or zero (default: 50) The maximum value may vary, depending on your JDBC driver.

### Usage

### Examples

**Example 5–34** Using `jdbc.cache-statements.size` in `persistence.xml`

```
<property name="eclipselink.jdbc.cache-statements.size" value="100"/>
```

**Example 5–35** Using `jdbc.cache-statements.size` in `Property Map`

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.CACHE_STATEMENTS_SIZE, "100");
```

### See Also

For more information, see:

- ["jdbc.cache-statements"](#) on page -90



## jdbc.connector

Use `eclipselink.jdbc.connector` to define a custom connector to connect to the database.

### Values

[Table 5–44](#) describes this persistence property's values.

**Table 5–44** Valid Values for `jdbc.connector`

Value	Description

### Usage

You can use this property to connect to a non-standard connection pool, or provide customized details on how to obtain a connection.

This property is not required when using a `DataSource` or `JDBC DriverManager` is used.

### Examples

**Example 5–36** Using `jdbc.connector` in `persistence.xml`

**Example 5–37** Using `jdbc.connector` in a Property Map

### See Also

For more information, see:

- 
-



## jdbc.exclusive-connection.is-lazy

Use `eclipselink.jdbc.exclusive-connection.is-lazy` to specify if EclipseLink acquires write connections lazily.

### Values

[Table 5–45](#) describes this persistence property's values.

**Table 5–45** Valid Values for `jdbc.exclusive-connection.is-lazy`

Value	Description
true	(Default) Acquire write connections lazily.
false	Do not acquire write connections lazily.

### Usage

### Examples

**Example 5–38** Using `jdbc.exclusive-connection.is-lazy` in `persistence.xml`

```
<property name="eclipselink.jdbc.exclusive-connection.is-lazy" value="false"/>
```

**Example 5–39** Using `jdbc.exclusive-connection.is-lazy` in Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.EXCLUSIVE_CONNECTION_IS_LAZY,
    "false");
```

### See Also

For more information, see:

- Auditing  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Auditing>
- 
-



## jdbc.exclusive-connection.mode

Use `eclipselink.jdbc.exclusive-connection.mode` to specify when EclipseLink performs reads through the write connection.

### Values

Table 5–46 describes this persistence property's values.

**Table 5–46** Valid Values for `jdbc.exclusive-connection.mode`

Value	Description
Transactional	<p>(Default) Create an isolated client session if some or all entities require isolated cache, otherwise create a client session.</p> <p><b>Notes:</b></p> <ul style="list-style-type: none"> <li>■ EclipseLink keeps the connection exclusive for the duration of the transaction.</li> <li>■ <i>Inside</i> the transaction, EclipseLink performs all writes and reads through the exclusive connection.</li> <li>■ <i>Outside</i> the EclipseLink transaction, a new connection is acquired from the connection pool for each read and released back immediately after the query is executed.</li> </ul>
Isolated	<p>Create an exclusive isolated client session if reading an isolated entity, otherwise raise an error.</p> <p><b>Notes:</b></p> <ul style="list-style-type: none"> <li>■ EclipseLink keeps the connection exclusive for the lifetime of the owning <code>EntityManager</code>.</li> <li>■ <i>Inside</i> the transaction, EclipseLink performs all writes and reads through the exclusive connection.</li> <li>■ <i>Outside</i> the EclipseLink transaction, only isolated entities are read through the exclusive connection. For non-isolated entities, EclipseLink acquires a new connection from the connection pool for each read and immediately releases the connection after executing the query.</li> </ul>
Always	<p>Create an exclusive isolated client session if reading an isolated entity, otherwise create an exclusive client session.</p> <p><b>Note:</b> EclipseLink keeps the connection exclusive for the lifetime of the owning <code>EntityManager</code> and performs all writes and reads through the exclusive connection.</p>

### Usage

You can set this property while creating either an `EntityManagerFactory` (either in the map passed to the `createEntityManagerFactory` method, or in the `persistence.xml` file), or an `EntityManager` (in the map passed to the `createEntityManager` method). Note that the latter overrides the former.

### Examples

**Example 5–40** Using `jdbc.exclusive-connection.mode` in `persistence.xml`

```
property name="eclipselink.jdbc.exclusive-connection.mode" value="Always"/>
```

**Example 5–41** Using `jdbc.exclusive-connection.mode` in Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.EXCLUSIVE_CONNECTION_MODE, "Always");
```



**See Also**

For more information, see:

- ["jdbc.exclusive-connection.is-lazy"](#) on page -96
-

## jdbc.native-sql

Use `eclipselink.jdbc.native-sql` to specify if EclipseLink uses generic SQL or includes platform-specific (that is, "native") SQL statements.

### Values

[Table 5–47](#) describes this persistence property's values.

**Table 5–47** Valid Values for *jdbc.native-sql*

Value	Description
true	(Default) Use platform-specific ("native" ) SQL.
false	Use generic SQL.

### Usage

When using platform-specific SQL (`eclipselink.jdbc.native-sql = true`), EclipseLink uses platform-specific SQL to customize join syntax, date operators, using sequencing, and so on.

### Examples

**Example 5–42** Using *jdbc.native-sql* in *persistence.xml*

```
<property name="eclipselink.jdbc.native-sql" value="true"/>
```

**Example 5–43** Using *jdbc.native-sql* in *Property Map*

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.NATIVE_SQL, "true");
```

### See Also

For more information, see:

-



---

## jdbc.property

Use `eclipselink.jdbc.property` to pass JDBC driver-specific connection properties to EclipseLink.

### Usage

Append the JDBC driver specific property name to this property prefix.

### Examples

***Example 5–44 Using jdbc.property in persistence.xml***

```
<property name="eclipselink.jdbc.property.defaultRowPrefetch" value="25" />
```

### See Also

For more information, see:



---

## jdbc.sql-cast

Use `eclipselink.jdbc.sql-cast` to specify if EclipseLink uses platform-specific (that is, "native") CAST SQL operations.

### Values

[Table 5–48](#) describes this persistence property's values.

**Table 5–48** Valid Values for `jdbc.sql-cast`

Value	Description
true	Use platform-specific CAST operations.
false	Do not use platform-specific CAST operations

### Usage

---

---

**Note:** normally, casting is not required. Using it may cause issues.

---

---

### Examples

### See Also

For more information, see:

-



## jdbc.uppercase-columns

Use `eclipselink.jdbc.uppercase-columns` to force column names from the metadata to be uppercase.

### Values

[Table 5–49](#) describes this persistence property's values.

**Table 5–49** *Valid Values for jdbc.uppercase-columns*

Value	Description

### Usage

When using native SQL queries, the JDBC metadata may return column names in lower case on some platforms. If the column names are uppercase in the mappings (default), they will not match. You should use this parameter to force all column names from the metadata to uppercase.

### Examples

### See Also

For more information, see:

- ["jpa.uppercase-column-names"](#) on page -108





## jpa.uppercase-column-names

Use `eclipselink.jpa.uppercase-column-names` to specify JPA processing to uppercase all column name definitions (simulating case insensitivity).

### Values

[Table 5–50](#) describes this persistence property's values.

**Table 5–50** Valid Values for `jpa.uppercase-column-names`

Value	Description
true	Sets <code>eclipselink.jdbc.uppercase-columns</code> to true, requiring that JDBC metadata returned from the database is returned in uppercase, ensuring fields are the same case.
false	(Default)

### Usage

Use this property to correct situations in which user-defined fields do not match the case returned by the database for native queries

### Examples

### See Also

For more information, see:

- ["jdbc.uppercase-columns"](#) on page -106



---

## jpql.parser

Use `eclipselink.jpql.parser` to configure the JPQL parser parameters.

### Values

[Table 5–51](#) describes this persistence property's values.

**Table 5–51** Valid Values for *jpql.uppercase-column-names*

Value	Description
<code>org.eclipse.persistence.internal.jpa.jpql.HermesParser</code>	(Default) Current parser, starting with EclipseLink 2.4, that provides extended JPQL support.
<code>org.eclipse.persistence.queries.ANTLRQueryBuilder</code>	Old parser, used for backward compatibility (prior to EclipseLink 2.4).

### Usage

### Examples

### See Also

For more information, see:

- ["jpql.validation"](#) on page -112



## jpql.validation

Use `eclipselink.jpql.parser` to configure the JPQL parser validation level to be configured.

### Values

[Table 5–52](#) describes this persistence property's values.

**Table 5–52** Valid Values for `jpa.uppercase-column-names`

Value	Description
EclipseLink	(Default) Allows EclipseLink JPAL extensions.
JPA 1.0	Allows valid JPA 1.0 JPQL only.
JPA 2.0	Allows valid JPA 2.0 JPQL only.
JPA 2.1	Allows valid JPA 2.1 JPQL only.
None	No JPQL validation.

### Usage

This parameter applies only when `eclipselink.jpql.parser` is `HermesParser`.

### Examples

### See Also

For more information, see:

- ["jpql.parser"](#) on page -110
- ["Java Persistence Query Language Extensions"](#) on page 3-1



---

## logging.connection

### Values

[Table 5–53](#) describes this persistence property's values.

**Table 5–53** *Valid Values for logging.connection*

Value	Description
true	(Default)
false	

### Usage

### Examples

### See Also

For more information, see:

- Logging Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Logging>
- "[logging.level](#)" on page -120





## logging.exceptions

Use `eclipselink.logging.exceptions` to specify if exceptions are logged when the are thrown, before returning the exception to the calling application.

### Values

[Table 5–54](#) describes this persistence property's values.

**Table 5–54** Valid Values for `logging.exceptions`

Value	Description
true	(Default)
false	

### Usage

Using this property ensures that all exceptions are logged and not masked by the application code.

### Examples

[Example 5–45](#) shows how to use this property in the `persistence.xml` file.

**Example 5–45** Using `logging.exceptions` in `persistence.xml` file

```
<property name="eclipselink.logging.exceptions" value="true" />
```

[Example 5–46](#) shows how to use this property in a property map.

**Example 5–46** Using `logging.exceptions` in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.LOGGING_EXCEPTIONS, "true");
```

### See Also

For more information, see:

- Logging Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Logging>
- `"logging.level"` on page -120



## logging.file

Use `eclipselink.logging.file` to specify a file location in which to output the log instead of the standard out.

### Values

[Table 5–55](#) describes this persistence property's values.

**Table 5–55** Valid Values for *logging.file*

Value	Description
directory name	A string location to a directory in which you have write access. The location may be relative to your current working directory or an absolute location.

### Usage

This property applies when used in a Java SE environment.

### Examples

[Example 5–47](#) shows how to use this property in the `persistence.xml` file.

**Example 5–47** Using *logging.file* in *persistence.xml* file

```
<property name="eclipselink.logging.file" value="C:\myout\" />
```

[Example 5–48](#) shows how to use this property in a property map.

**Example 5–48** Using *logging.file* in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.LOGGING_FILE, "C:\myout");
```

### See Also

For more information, see:

- Logging Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Logging>



## logging.level

Use `eclipselink.logging.level` to specify a specific logging level and control the amount and detail EclipseLink writes to the log.

### Values

[Table 5–56](#) describes this persistence property's values.

**Table 5–56** Valid Values for `logging.level`

Value	Description
OFF	Disables logging. You may want to use <code>OFF</code> during production in order to avoid the overhead of logging.
SEVERE	Logs exceptions indicating that EclipseLink cannot continue, as well as any exceptions generated during login. This includes a stack trace.
WARNING	Logs exceptions that <i>do not</i> force EclipseLink to stop, including all exceptions not logged with <code>SEVERE</code> level. This does not include a stack trace.
INFO	(Default) Logs the login/logout per sever session, including the user name. After acquiring the session, detailed information is logged.
CONFIG	Logs only login, JDBC connection, and database information. You may want to use this log level at deployment time.
FINE	Logs all SQL You may want to use this log level during debugging and testing, but not at production time.
FINER	Similar to <code>WARNING</code> , but includes stack trace. You may want to use this log level during debugging and testing, but not at production time.
FINEST	Similar to <code>FINER</code> , but includes additional low level information. You may want to use this log level during debugging and testing, but not at production time.
ALL	Logs at the same level as <code>FINEST</code> .

### Usage

### Examples

[Example 5–49](#) shows how to use this property in the `persistence.xml` file.

**Example 5–49** Using `logging.level` in `persistence.xml` file

```
<property name="eclipselink.logging.level" value="OFF" />
```

[Example 5–50](#) shows how to use this property in a property map.

**Example 5–50** Using `logging.level` in a Property Map

```
import java.util.logging.Level;
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.LOGGING_LEVEL, Level.OFF);
```

## See Also

For more information, see:

- Logging Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Logging>

## logging.logger

Use `eclipselink.logging.logger` to define the type of logger to use.

### Values

[Table 5–57](#) describes this persistence property's values.

**Table 5–57** Valid Values for `logging.logger`

Value	Description
Custom logger	Fully qualified class name of a custom logger which implements <code>org.eclipse.persistence.logging.SessionLog</code>
JavaLogger	Uses <code>java.util.logging</code>
ServerLogger	Integrates with the application server's logging
DefaultLogger	(Default) Uses EclipseLink's native logger, <code>DefaultSessionLog</code>

### Examples

**Example 5–51** Using `logging.logger` in `persistence.xml`

```
<property name="eclipselink.logging.logger" value="JavaLogger"/>
```

**Example 5–52** Using `logging.logger` in `Property Map`

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.LOGGING_LOGGER,
"acme.loggers.MyCustomLogger" />
```

### See Also

For more information, see:

- Logging examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Logging>
- Custom logger  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/CustomLogger>
-





## logging.parameters

Use `eclipselink.logging.parameters` to define if SQL bind parameters are included in exceptions and logs.

---

---

**Note:** This parameter applies to bind parameters only. Parameters are always displayed when not using binding.

---

---

### Values

[Table 5–58](#) describes this persistence property's values.

**Table 5–58** *Valid Values for logging.parameters*

Value	Description
true	Display the parameters.
false	Do not display the parameters.

### Usage

By default, when using `logging.level` of `FINE` (or greater), SQL bind parameters are displayed. Use this parameter to override the default behavior.

### Examples

**Example 5–53** *Using logging.parameters in persistence.xml*

**Example 5–54** *Using logging.parameters in a Property Map*

### See Also

For more information, see:

- ["logging.level"](#) on page -120
- Logging Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Logging>
-



## logging.session

Use `eclipselink.logging.session` to specify if EclipseLink should include session identifier in each log message.

### Values

[Table 5–59](#) describes this persistence property's values.

**Table 5–59** Valid Values for `logging.session`

Value	Description
true	(Default) Log a session identifier.
false	Do not log a session identifier

### Usage

This setting is applicable to messages that require a database connection such as SQL and the transaction information to determine on which underlying session (if any) the message was sent.

### Examples

[Example 5–55](#) shows how to use this property in the `persistence.xml` file.

**Example 5–55** Using `logging.session` in `persistence.xml` file

```
<property name="eclipselink.logging.session" value="false" />
```

[Example 5–56](#) shows how to use this property in a property map.

**Example 5–56** Using `logging.session` in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.LOGGING_SESSION, "false");
```

### See Also

For more information, see:

- Logging Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Logging>
- "[logging.level](#)" on page -120



## logging.thread

Use `eclipselink.logging.thread` to specify if EclipseLink should include thread identifier in each log message.

### Values

[Table 5–60](#) describes this persistence property's values.

**Table 5–60** Valid Values for `logging.thread`

<b>true</b>	<b>(Default)</b>
true	(Default) Log a thread identifier.
false	Do not log a thread identifier

### Usage

You should use this property when running multi-threaded applications. EclipseLink will include a hashcode of the thread.

### Examples

[Example 5–57](#) shows how to use this property in the `persistence.xml` file.

**Example 5–57** Using `logging.thread` in `persistence.xml` file

```
<property name="eclipselink.logging.thread" value="false" />
```

[Example 5–58](#) shows how to use this property in a property map.

**Example 5–58** Using `logging.thread` in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.LOGGING_THREAD, "false");
```

### See Also

For more information, see:

- ["logging.level"](#) on page -120
- Logging Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Logging>



## logging.timestamp

Use `eclipselink.logging.timestamp` to specify if EclipseLink should include a timestamp in each log message.

### Values

[Table 5–61](#) describes this persistence property's values.

**Table 5–61** Valid Values for *logging.timestamp*

Value	Description
true	(Default) Log a timestamp.
false	Do not log a timestamp.

### Usage

### Examples

[Example 5–59](#) shows how to use this property in the `persistence.xml` file.

**Example 5–59** Using *logging.timestamp* in *persistence.xml* file

```
<property name="eclipselink.logging.timestamp" value="false" />
```

[Example 5–60](#) shows how to use this property in a property map.

**Example 5–60** Using *logging.timestamp* in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.LOGGING_TIMESTAMP, "false");
```

### See Also

For more information, see:

- Logging Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Logging>
- "logging.level" on page -120





## metadata-source

Use `eclipselink.metadata-source` to specify `MetadataSource` implementation EclipseLink uses to read metadata.

### Values

[Table 5–62](#) describes this persistence property's values.

**Table 5–62** Valid Values for `metadata-source`

Value	Description
XML	Use <code>XMLMetadataSource</code> .
Custom metadata source	A custom class name which implements <code>MetadataSource</code> .

### Usage

Use this property with `eclipselink.metadata-source.xml.file` to access an external mapping file at a fixed URL for a persistence unit.

### Examples

[Example 5–61](#) shows how to use this property in the `persistence.xml` file.

**Example 5–61** Using `metadata-source` in `persistence.xml`

```
<property name="eclipselink.metadata-source" value="mypackage.MyMetadataSource"/>
<property name="eclipselink.metadata-source.xml.url" value="foo://bar"/>
```

### See Also

For more information, see:

- ["metadata-source.send-refresh-command"](#) on page -136
- ["metadata-source.xml.file"](#) on page -138
- Metadata Source Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/MetadataSource/>
- "Extensible Entities"  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/Extensible\\_Entities](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/Extensible_Entities)



---

## metadata-source.properties.file

Use `eclipselink.metadata-source.properties.file` to specify the name of the metadata repository properties file to read from, using classloader to find the resource.

### Values

[Table 5–63](#) describes this persistence property's values.

**Table 5–63**    *Valid Values for metadata-repository.properties.file*

Value	Description
Filename	Name of the metadata source XML file.

### Usage

Use this property with `eclipselink.metadata-source` when using an XML repository.

### Examples

### See Also

For more information, see:

- ["metadata-source"](#) on page -132
- Metadata Source Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/MetadataSource/>
-



## metadata-source.send-refresh-command

Use `eclipselink.metadata-source.send-refresh-command` with cache coordination for a clustered environment to control how EclipseLink sends RCM refresh metadata commands to the cluster.

### Values

[Table 5–64](#) describes this persistence property's values.

**Table 5–64** Valid Values for `metadata-source.send-refresh-command`

Value	Description
true	(Default) To propagate refresh commands to the cluster, you must configure RCM and use the <code>eclipselink.deploy-on-startup</code> property.
false	

### Usage

If cache coordination is configured and the session is deployed on startup, this property controls the sending of RCM refresh metadata commands to the cluster.

These commands will cause the remote instances to refresh their metadata.

### Examples

[Example 5–61](#) shows how to use this property.

### See Also

For more information, see:

- ["metadata-source"](#) on page -132
- ["deploy-on-startup"](#) on page -70
- Metadata Source Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/MetadataSource/>



## metadata-source.xml.file

Use `eclipselink.metadata-repository.xml.file` to specify the name of the metadata repository XML file to read from, using classloader to find the resource.

### Values

[Table 5–65](#) describes this persistence property's values.

**Table 5–65** Valid Values for *metadata-repository.xml.file*

Value	Description

### Usage

Use this property with the `eclipselink.metadata-source` property when using an XML repository.

### Examples

### See Also

For more information, see:

- ["metadata-source"](#) on page -132
- Metadata Source Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/MetadataSource/>
-





## metadata-source.xml.url

Use `eclipselink.metadata-source.xml.url` to specify the location of an external mapping file.

### Values

[Table 5–66](#) describes this persistence property's values.

**Table 5–66** *Valid Values for metadata-source*

Value	Description
	Specify a custom class name which implements <code>MetadataSource</code> .

### Usage

### Examples

[Example 5–61](#) shows how to use this property.

### See Also

For more information, see:

- ["metadata-source"](#) on page -132
- Metadata Source Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/MetadataSource/>



## multitenant.tenants-share-cache

Use `eclipselink.multitenant.tenants-share-cache` to specify if multitenant entities will share the L2 cache.

### Values

[Table 5–67](#) describes this persistence property's values.

**Table 5–67** Valid Values for `multitenant.tenants-share-cache`

Value	Description
true	Multitenant entities will use an <b>protected</b> cache.
false	(Default) Multitenant entities will use an <b>isolated</b> cache.

### Usage

---

---

**WARNING:** When this setting is **false**, queries that use the cache may return data from other tenants when using the **PROTECTED** setting.

---

---

### Examples

**Example 5–62** Using `multitenant.tenants-share-cache` in `persistence.xml`

```
<property name="eclipselink.multitenant.tenants-share-cache" value="true" />
```

**Example 5–63** Using `multitenant.tenants-share-cache` in a *Property Map*

### See Also

For more information, see:

- ["@Multitenant"](#) on page -82
- Multitenant examples:  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Multitenant>
-



---

## multitenant.tenants-share-emf

Use `eclipselink.multitenant.shared-emf` to specify if multitenant entities will be used within a shared entity manager factory.

### Values

[Table 5–68](#) describes this persistence property's values.

**Table 5–68** Valid Values for *multitenant.tenants-share-emf*

Value	Description
true	(Default)
false	You must provide a unique session name.

### Usage

When setting it to false, users are required to provide a unique session name. .

### Examples

**Example 5–64** Using *multitenant.tenants-share-emf* in *persistence.xml*

```
<property name="eclipselink_multitenant_tenants_share_emf" value="true" />
```

**Example 5–65** Using *multitenant.tenants-share-emf* in a *Property Map*

### See Also

For more information, see:

- ["@Multitenant"](#) on page -82
- Multitenant examples:  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Multitenant>
-



## nosql.connection-factory

Use `eclipselink.nosql.connection-factory` to specify the JNDI name of a JCA ConnectionFactory or a JCA ConnectionFactory class name that connects to the NoSQL data-source.

### Values

[Table 5–69](#) describes this persistence property's values.

**Table 5–69** Valid Values for `nosql.connection-factory`

Value	Description

### Usage

This property allows the JCA ConnectionFactory to be used with a NoSql or EIS adapter for a NoSQL datasource (that is, a non-relationship datasource such as a legacy database, NoSQL database, XML database, transactional and messaging systems, or ERP systems).

### Examples

**Example 5–66** Using `nosql.connection-factory` in `persistence.xml`

**Example 5–67** Using `nosql.connection-factory` in a Property Map

### See Also

For more information, see:

- ["@NoSql"](#) on page -108
- ["nosql.property"](#) on page -150
- NoSQL Persistence Units  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/NoSQL/Persistence\\_Units](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/NoSQL/Persistence_Units)
- Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/NoSQL>
- .





## nosql.connection-spec

Use `eclipselink.nosql.connection-spec` to specify an `EISConnectionSpec` class name that defines how to connect to the NoSQL datasource.

### Values

[Table 5–70](#) describes this persistence property's values.

**Table 5–70** Valid Values for *nosql.connection-spec*

Value	Description

### Usage

### Examples

See [Example 5–68](#) for information on how to use this property.

### See Also

For more information, see:

- ["@NoSql"](#) on page -108
- ["nosql.property"](#) on page -150
- NoSQL Persistence Units  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/NoSQL/Persistence\\_Units](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/NoSQL/Persistence_Units)
- Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/NoSQL>
-



# nosql.property

Use `eclipselink.nosql.property` to set NoSQL-specific connection properties. Append the NoSQL-specific property name to this parameter.

## Values

[Table 5–71](#) describes this persistence property’s values.

**Table 5–71** Valid Values for *nosql.property*

Value	Description
value	

## Usage

## Examples

**Example 5–68** Using *nosql.property* in *persistence.xml*

```
<persistence xmlns="http://java.sun.com/xml/ns/persistence"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://java.sun.com/xml/ns/persistence persistence_2_0.xsd"
version="2.0">
  <persistence-unit name="acme" transaction-type="RESOURCE_LOCAL">
    <provider>org.eclipse.persistence.jpa.PersistenceProvider</provider>
    <exclude-unlisted-classes>false</exclude-unlisted-classes>
    <properties>
      <property name="eclipselink.target-database"
value="org.eclipse.persistence.nosql.adapters.mongo.MongoPlatform"/>
      <property name="eclipselink.nosql.connection-spec"
value="org.eclipse.persistence.nosql.adapters.mongo.MongoConnectionSpec"/>
      <property name="eclipselink.nosql.property.mongo.port" value="27017,
27017"/>
      <property name="eclipselink.nosql.property.mongo.host" value="host1,
host2"/>
      <property name="eclipselink.nosql.property.mongo.db" value="acme"/>
    </properties>
  </persistence-unit>
</persistence>
```

## See Also

For more information, see:

- ["@NoSql"](#) on page -108

- NoSQL Persistence Units  
[http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced\\_JPA\\_Development/NoSQL/Persistence\\_Units](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Advanced_JPA_Development/NoSQL/Persistence_Units)
- Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/NoSQL>
- "nosql.connection-factory" on page -146
- "nosql.connection-spec" on page -148

## orm.throw.exceptions

Use `eclipselink.orm.throw.exceptions` to specify if EclipseLink throws an exception or logs a warning when encountering a problem with any of the file in the `<mapping-file>` element of the `persistence.xml` file.

### Values

[Table 5–72](#) describes this persistence property's values.

**Table 5–72** Valid Values for `orm.throw.exceptions`

Value	Description
true	Throw an exception
false	Log a warning only.

### Examples

[Example 5–69](#) shows how to use this persistence property extension in the `persistence.xml` file.

**Example 5–69** Using `orm.throw.exceptions` in `persistence.xml`

```
<property name="oracle.orm.throw.exceptions" value="false"/>
```

[Example 5–70](#) shows how to use this extension in a property map

**Example 5–70** Using `orm.throw.exceptions` in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.ECLIPSELINK_ORM_THROW_EXCEPTIONS,
"false");
```

### See Also

For more information, see:

- ["exception-handler"](#) on page -76



## oracle.proxy-type

Use `eclipselink.oracle.proxy-type` to specify the proxy type to be passed to the `OracleConnection.openProxySession` method.

### Values

[Table 5–73](#) describes this persistence property's values.

**Table 5–73** Valid Values for *oracle.proxy-type*

Value	Description
USER_NAME	
DISTINGUISHED_NAME	
CERTIFICATE	

### Usage

This property requires Oracle JDBC version 10.1.0.2 or later and `eclipselink.target-database` must be configured to use Oracle9 or later.

Typically, you should set this property into `EntityManager`, through a `createEntityManager` method or by using proprietary `setProperties` method on `EntityManagerImpl`. This causes `EntityManager` to use proxy connection for writing and reading inside transaction.

If `proxy-type` and the corresponding `proxy` property set into `EntityManagerFactory`, all connections created by the factory will be proxy connections.

### Examples

**Example 5–71** Using *eclipselink.oracle.proxy-type* with *EntityManager*

```
Map emProperties = new HashMap();
emProperties.put("eclipselink.oracle.proxy-type", OracleConnection.PROXYTYPE_USER_
NAME);
emProperties.put(OracleConnection.PROXY_USER_NAME, "john");
EntityManager em = emf.createEntityManager(emProperties);
```

With injection:

```
entityManager.setProperty("eclipselink.oracle.proxy-type",
OracleConnection.PROXYTYPE_USER_NAME);
entityManager.setProperty(OracleConnection.PROXY_USER_NAME, "john");
```

### See Also

For more information, see:

- ["target-database"](#) on page -188
- Oracle Proxy Authentication Example  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Oracle/Proxy>



- Auditing example  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Auditing>
-

---

# orm.validate.schema

The one-line description here.

## Values

[Table 5–74](#) describes this persistence property’s values.

**Table 5–74**    *Valid Values for orm.validate.schema*

Value	Description

## Usage

Para.

## Examples

Para

**Example 5–72**    *Using orm.validate.schema in persistence.xml*

**Example 5–73**    *Using orm.validate.schema in a Property Map*

## See Also

Para.



## partitioning

Use `eclipselink.partitioning` to set the default `PartitioningPolicy` for a persistence unit. The value must be the name of an existing, defined `PartitioningPolicy`.

### Values

[Table 5–75](#) describes this persistence property's values.

**Table 5–75**    *Valid Values for partitioning*

Value	Description
name	An existing, defined <code>PartitioningPolicy</code> .

### Usage

Use this property to partition data for a class across multiple different databases or across a database cluster such as Oracle RAC. Partitioning may provide improved scalability by allowing multiple database machines to service requests.

If multiple partitions are used to process a single transaction, use JTA (Java Transaction API) for proper XA transaction support.

### Examples

**Example 5–74**    *Using partitioning in persistence.xml*

```
<property name="eclipselink.partitioning" value="Replicate" />
```

### See Also

For more information, see:

- Partitioning Examples  
<http://wiki.eclipse.org/EclipseLink/Examples/JPA/Partitioning>
- `"@Partitioning"` on page -124



---

## partitioning.callback

The one-line description here.

### Values

[Table 5–76](#) describes this persistence property’s values.

**Table 5–76** *Valid Values for eclipselink.partitioning.callback*

Value	Description

### Usage

Para.

### Examples

Para

**Example 5–75** *Using partitioning.callback in persistence.xml*

**Example 5–76** *Using partitioning.callback in a Property Map*

### See Also

Para.



## persistence-context.close-on-commit

Use `eclipselink.persistence-context.close-on-commit` to specify if the `EntityManager` will be closed or not used after commit (not extended).

### Values

[Table 5–77](#) describes this persistence property's values.

**Table 5–77** Valid Values for *persistence-context.close-on-commit*

Value	Description
true	
false	(Default)

### Usage

For a container managed `EntityManager` and most application managed, normally set this property to `false`, in order to avoid additional performance overhead of resuming the persistence context after a `commit()` transaction.

The property set in `persistence.xml` or passed to `createEntityManagerFactory` affects *all* `EntityManager`s created by the factory. Alternatively, to apply the property to *specific* `EntityManager`s, pass it to `createEntityManager` method.

### Examples

### See Also

For more information, see:

-





## persistence-context.commit-without-persist-rules

Use `eclipselink.persistence-context.commit-without-persist-rules` to specify if the `EntityManager` will search all managed objects and persist any related non-managed new objects that are found ignoring any absence of `CascadeType.PERSIST` settings.

### Values

[Table 5–78](#) describes this persistence property's values.

**Table 5–78** Valid Values for *persistence-context.commit-without-persist-rules*

Value	Description
true	
false	(Default)

### Usage

When set to true, Entity life-cycle `Persist` operation *will not* be cascaded to related entities. This replicates the traditional EclipseLink native functionality.

### Examples

### See Also

For more information, see:

-



## persistence-context.flush-mode

Use `eclipselink.persistence-context.flush-mode` to configure the `EntityManager FlushMode` to be set as a persistence property and specify when flushing occurs.

### Values

[Table 5–79](#) describes this persistence property's values.

**Table 5–79** Valid Values for *persistence-context.flush-mode*

Value	Description
auto	(Default) Flushing occurs at query execution.
commit	Flushing occurs at transaction commit.

### Usage

The property set in `persistence.xml` or passed to `createEntityManagerFactory` affects *all* `EntityManager`s created by the factory. To apply the property to *specific* `EntityManager`s pass it to `createEntityManager` method.

### Examples

[Example 5–77](#) shows how to use this property in the `persistence.xml` file.

**Example 5–77** Using *persistence-context.flush-mode* in *persistence.xml*

```
<property name="eclipselink.persistence-context.flush-mode" value="commit" />
```

### See Also

For more information, see:

- ["flush"](#) on page -22



## persistence-context.persist-on-commit

Use `eclipselink.persistence-context.persist-on-commit` to specify if the `EntityManager` searches all managed objects and persists any related non-managed new objects that are cascade persist. This can be used to avoid the cost of performing this search if persist is always used for new objects.

### Values

[Table 5–80](#) describes this persistence property's values.

**Table 5–80** Valid Values for `persistence-context.persist-on-commit`

Value	Description
true	(Default)
false	

### Usage

The property set in `persistence.xml` or passed to `createEntityManagerFactory` affects *all* `EntityManager`s created by the factory. To apply the property to *specific* `EntityManager`s pass it to `createEntityManager` method.

### Examples

[Example 5–78](#) shows how to use this property in the `persistence.xml` file.

**Example 5–78** Using `persistence-context.persist-on-commit` in `persistence.xml`

```
<property name="eclipselink.persistence-context.persist-on-commit" value="false"/>
```

### See Also

For more information, see:

-



## persistence-context.reference-mode

Use `eclipselink.persistence-context.reference-mode` to specify if hard or soft (that is, weak) references are used within the Persistence Context.

### Values

[Table 5–81](#) describes this persistence property's values.

**Table 5–81** Valid Values for `persistence-context.reference-mode`

Value	Description
hard	(Default) EclipseLink references all objects through <b>hard</b> references. These objects <i>will not</i> be available for garbage collection until the referencing artifact (such as the persistence context or unit of work) is released/cleared or closed.
weak	<p>References to objects supporting active attribute change tracking (see "<a href="#">@ChangeTracking</a>" on page -30) will be held by <b>weak</b> references. That is, any object no longer referenced directly or indirectly will be available for garbage collection. When a change is made to a change-tracked object, that object is moved to a hard reference and will not be available for garbage collection until flushed.</p> <p><b>Note:</b> Any changes that have not been flushed in these entities will be lost.</p> <p>New and removed objects, as well as objects that do not support active attribute change tracking, will also be held by hard references and will not be available for garbage collection.</p>
force_weak	<p>All objects, including non-change-tracked objects, are to be held by <b>weak</b> references. When a change is made to a change-tracked object (see "<a href="#">@ChangeTracking</a>" on page -30), that object is moved to a hard reference and will not be available for garbage collection until flushed. However, any objects that do not support active attribute change tracking may be garbage collected before their changes are flushed to a database, which can potentially result in a loss of changes.</p> <p>New and removed objects will be held by hard references and will not be available for garbage collection.</p>

### Usage

The property set in `persistence.xml` or passed to `createEntityManagerFactory` affects *all* `EntityManager`s created by the factory. To apply the property to *specific* `EntityManager`s pass it to `createEntityManager` method.

### Examples

[Example 5–79](#) shows how to use this property in a `persistence.xml` file.

**Example 5–79** Using `persistence-context.reference-mode` in `persistence.xml`

```
<property name="eclipselink.persistence-context.reference-mode" value="FORCE_WEAK" />
```

[Example 5–79](#) shows how to use this property in a property map.

**Example 5–80** Using `persistence-context.reference-mode` in Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.PERSISTENCE_CONTEXT_REFERENCE_MODE,
ReferenceMode.FORCE_WEAK);
```



## See Also

For more information, see:

- ["@ChangeTracking"](#) on page -30
- "Using EclipseLink JPA Extensions for Tracking Changes"  
[http://wiki.eclipse.org/index.php?title=Using\\_EclipseLink\\_JPA\\_Extensions\\_%28ELUG%29&oldid=310588#Using\\_EclipseLink\\_JPA\\_Extensions\\_for\\_Tracking\\_Changes](http://wiki.eclipse.org/index.php?title=Using_EclipseLink_JPA_Extensions_%28ELUG%29&oldid=310588#Using_EclipseLink_JPA_Extensions_for_Tracking_Changes)

---

## persistenceunits

Use the `eclipselink.persistenceunits` to specify the set of persistence unit names that will be processed when generating the canonical model. By default, EclipseLink uses all persistence units available in all persistence XML files.

### Values

[Table 5–82](#) describes this persistence property's values.

**Table 5–82**    *Valid Values for persistenceunits*

Value	Description
names	A comma separated list of persistence units  <b>Note:</b> When specifying multiple persistence units, you cannot include a comma ( , ) in the name of a persistence unit.

### Usage

### Examples

### See Also

For more information, see:

-



## persistence.xml

Use `eclipselink.persistence.xml` to specify the full resource name in which to look for the persistence XML files. If omitted, EclipseLink uses the default location: `META-INF/persistence.xml`.

---

**Note:** Currently, this property is used only for the canonical model generator. In the future, it may be used for customizing weaving and application bootstrapping.

---

### Values

[Table 5–83](#) describes this persistence property's values.

**Table 5–83** Valid Values for *persistence.xml*

Value	Description

### Usage

This property is only used by EclipseLink when it is locating the configuration file. When used within an EJB/Spring container in container managed mode the locating and reading of this file is done by the container and will not use this configuration.

### Examples

### See Also

For more information, see:

- "Using the Canonical Model Generator"  
[http://wiki.eclipse.org/UserGuide/JPA/Using\\_the\\_Canonical\\_Model\\_Generator\\_%28ELUG%29](http://wiki.eclipse.org/UserGuide/JPA/Using_the_Canonical_Model_Generator_%28ELUG%29)
-



## profiler

Use `eclipselink.profiler` to specify which performance profiler to use in order to capture runtime statistics.

### Values

[Table 5–84](#) describes this persistence property's values.

**Table 5–84** Valid Values for profiler

Value	Description
NoProfiler	Do not use a performance profiler.
PerformanceProfiler	Use EclipseLink performance profiler (org.eclipse.persistence.tools.profiler.PerformanceProfiler class).
QueryMonitor	Monitor query executions and cache hits (org.eclipse.persistence.tools.profiler.QueryMonitor class).  This option provides a simple low-overhead means for measuring performance of query executions and cache hits. You may want to use this option for performance analysis in a complex system.
Custom profiler	Specify a custom profiler class name which implements SessionProfiler and provides a no-argument constructor.

### Usage

### Examples

[Example 5–81](#) shows how to use this property in the `persistence.xml` file.

**Example 5–81 Using profiler in persistence.xml**

```
<property name="eclipselink.profiler" value="PerformanceProfiler"/>
```

[Example 5–82](#) shows how to use this property in a property map.

**Example 5–82 Using profiler in Property Map**

```
import org.eclipse.persistence.config.ProfilerType;
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.PROFILER,
ProfilerType.PerformanceProfiler);
```

### See Also

For more information, see:

- "Measuring Performance with the EclipseLink Profiler"  
[http://wiki.eclipse.org/Optimizing\\_the\\_EclipseLink\\_Application\\_%28ELUG%29#Measuring\\_EclipseLink\\_Performance\\_with\\_the\\_EclipseLink\\_Profiler](http://wiki.eclipse.org/Optimizing_the_EclipseLink_Application_%28ELUG%29#Measuring_EclipseLink_Performance_with_the_EclipseLink_Profiler)



## session.customizer

Use `eclipselink.session.customizer` to specify an EclipseLink session customizer class, a Java class that implements the `org.eclipse.persistence.config.SessionCustomizer` interface and provides a default (zero-argument) constructor.

### Values

[Table 5–85](#) describes this persistence property’s values.

**Table 5–85** Valid Values for *session.customizer*

Value	Description
class name	Fully qualified class name of a <code>SessionCustomizer</code> class

### Usage

You can use the `customize` method of the class (which takes an `org.eclipse.persistence.sessions.Session`) to programmatically access advanced EclipseLink session API.

### Examples

[Example 5–83](#) shows how to use this property in the `persistence.xml` file.

**Example 5–83** Using *session.customizer* in *persistence.xml*

```
<property name="eclipselink.session.customizer"
value="acme.sessions.MySessionCustomizer"/>
```

[Example 5–84](#) shows how to use this property in a property map.

**Example 5–84** Using *session.customizer* in *Property Map*

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.SESSION_CUSTOMIZER,
"acme.sessions.MySessionCustomizer");
```

### See Also

For more information, see:

-





## session.include.descriptor.queries

Use `eclipselink.session.include.descriptor.queries` to specify if the copying of all descriptor named queries to the session are to be usable from the entity manager.

### Values

[Table 5–86](#) describes this persistence property's values.

**Table 5–86** Valid Values for `session.include.descriptor.queries`

Value	Description
true	(Default) Enable copying.
false	Disable copying.

### Usage

### Examples

[Example 5–85](#) shows how to use this property in the `persistence.xml` file.

**Example 5–85** Using `session.include.descriptor.queries` in `persistence.xml`

```
<property name="eclipselink.session.include.descriptor.queries" value="false"/>
```

[Example 5–86](#) shows how to use this property in a property map.

**Example 5–86** Using `session.include.descriptor.queries` in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.INCLUDE_DESCRIPTOR_QUERIES, "false");
```

### See Also

For more information, see:

-



## session-event-listener

Use `eclipselink.session-event-listener` to specify a descriptor event listener to be added during bootstrapping.

### Values

[Table 5–87](#) describes this persistence property's values.

**Table 5–87** Valid Values for *session-event-listener*

Value	Description
Class name	A qualified class name for a class that implements the <code>org.eclipse.persistence.sessions.SessionEventListener</code> interface.

### Usage

### Examples

[Example 5–87](#) shows how to use this property in a `persistence.xml` file.

**Example 5–87 Using session-event-listener in persistence.xml**

```
<property name="eclipselink.session-event-listener"
value="mypackage.MyClass.class" />
```

[Example 5–87](#) shows how to use this property in a property map.

**Example 5–88 Using session-event-listener in Property Map**

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.SESSION_EVENT_LISTENER_CLASS,
"mypackage.MyClass.class");
```

### See Also

For more information, see:

- "Obtaining an Entity Manager Factory in Java SE Environment"  
[http://wiki.eclipse.org/Developing\\_Applications\\_Using\\_EclipseLink\\_JPA\\_%28ELUG%29#Obtaining\\_an\\_Entity\\_Manager\\_Factory\\_in\\_Java\\_SE\\_Environment](http://wiki.eclipse.org/Developing_Applications_Using_EclipseLink_JPA_%28ELUG%29#Obtaining_an_Entity_Manager_Factory_in_Java_SE_Environment)



---

## session-name

Use `eclipselink.session-name` to configure a unique name to use when storing the singleton server session within the `SessionManager`.

### Values

[Table 5–88](#) describes this persistence property's values.

**Table 5–88** *Valid Values for session.name*

Value	Description
Name	Unique session name to use instead of the default, EclipseLink-generated session name.

### Usage

By default, EclipseLink generates a unique session name. You can provide a custom, unique, session name with this property.

When using a `sessions.xml` file, you must include this session name as the name of the session in the `sessions.xml` file.

### Examples

[Example 5–89](#) shows how to use this property in the `persistence.xml` file.

**Example 5–89** *Using session-name in persistence.xml*

```
<property name="eclipselink.session-name" value="MySession"/>
```

[Example 5–90](#) shows how to use this property in a property map.

**Example 5–90** *Using session-name in a Property Map*

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.SESSION_NAME, "MySession");
```

### See Also

For more information, see:

- ["sessions.xml"](#) on page -186



# sessions-xml

Use `eclipselink.sessions-xml` to use a specified native `sessions.xml` configuration file (which references a `project.xml` file) to load configuration and mapping information instead of JPA annotations or EclipseLink XML (as shown in [Figure 5-1](#)).

## Values

[Table 5-89](#) describes this persistence property's values.


**Table 5-89** Valid Values for *sessions-xml*

Value	Description
configuration file	The resource name of the sessions XML file. If you do not specify the value for this property, it will not be used.

## Usage

You can use the `eclipselink.sessions-xml` property as an alternative to using annotations and deployment XML. With this property, EclipseLink builds an in-memory EclipseLink session and project based on this metadata (as shown in [Figure 5-1](#)). You can acquire a persistence manager and use it, having defined all entities and so on using only EclipseLink `sessions.xml`.

**Figure 5-1** Using the *eclipselink.sessions-xml* Persistence Property



## Examples

[Example 5-91](#) shows how to use this property in a `persistence.xml` file.

**Example 5-91** Using *sessions-xml* in the *persistence.xml* file

```
<property name="eclipselink.sessions-xml" value="mysession.xml"/>
```

[Example 5-91](#) shows how to use this property in a property map.

**Example 5-92** Using *sessions-xml* in Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.SESIONS_XML, "mysession.xml");
```



**See Also**

For more information, see:

- ["Overriding and Merging"](#) on page 6-1

## target-database

Use the `eclipselink.target-database` property to specify the database to use, controlling custom operations and SQL generation for the specified database.

### Values

[Table 5–90](#) describes this persistence property's values.

**Table 5–90** Valid Values for target-database

Value	Description
Defined in the <code>TargetDatabase</code> class or a fully qualified class name that extends <code>DatabasePlatform</code>	<p>Specify your database:</p> <ul style="list-style-type: none"><li>▪ <b>Attunity</b></li><li>▪ <b>Auto</b> (Default): EclipseLink attempts to access the database and the JDBC metadata to determine the target database.</li><li>▪ <b>Cloudscape</b></li><li>▪ <b>Database</b>: Use a generic database, if your target database is not listed and your JDBC driver does not support the metadata required for <b>Auto</b>.</li><li>▪ <b>DB2</b></li><li>▪ <b>DB2Mainframe</b></li><li>▪ <b>DBase</b></li><li>▪ <b>Derby</b></li><li>▪ <b>HSQL</b></li><li>▪ <b>Informix</b></li><li>▪ <b>JavaDB</b></li><li>▪ <b>MaxDB</b></li><li>▪ <b>MySQL</b></li><li>▪ <b>MySQL4</b></li><li>▪ <b>Oracle</b></li><li>▪ <b>Oracle10</b></li><li>▪ <b>Oracle11</b></li><li>▪ <b>Oracle8</b></li><li>▪ <b>Oracle9</b></li><li>▪ <b>PointBase</b></li><li>▪ <b>PostgreSQL</b></li><li>▪ <b>SQLAnywhere</b></li><li>▪ <b>SQLServer</b></li><li>▪ <b>Sybase</b></li><li>▪ <b>Symfoware</b></li><li>▪ <b>TimesTen</b></li></ul>

### Usage

If `eclipselink.validation-only` = true, you must not use an **Auto** class name or short name.

## Examples

[Example 5-93](#) shows how to use this property in the `persistence.xml` file.

**Example 5-93 Using target-database in persistence.xml**

```
<property name="eclipselink.target-database" value="Oracle"/>
```

or

```
<property name="eclipselink.target-database"
value="org.eclipse.persistence.platform.database.HSQLPlatform"/>
```

[Example 5-94](#) shows how to use this property in the `persistence.xml` file.

**Example 5-94 Using target-database in a Property Map**

```
import org.eclipse.persistence.config.TargetDatabase;
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.TARGET_DATABASE,
TargetDatabase.Oracle);
```

## See Also

For more information, see:

- ["validation-only"](#) on page -196

## target-server

Use the `eclipselink.target-server` persistence property to configure the `ServerPlatform` that will be used to enable integration with a host container.

### Values

[Table 5–91](#) describes this persistence property's values.

**Table 5–91** Valid Values for target-server

Value	Description
Defined in the <code>TargetServer</code> class	Specify your application server: <ul style="list-style-type: none"><li>▪ <b>JBoss</b>: JBoss Application Server</li><li>▪ <b>OC4J</b>: OC4J persistence provider</li><li>▪ <b>SAPNetWeaver_7_1</b>: SAP NetWeaver Application Server 7.1 (and higher)</li><li>▪ <b>SunAS9</b>: Sun Application Server 9</li><li>▪ <b>WebLogic</b>: Oracle WebLogic Server</li><li>▪ <b>WebLogic_10</b>: Oracle WebLogic Server 10</li><li>▪ <b>WebLogic_9</b>: Oracle WebLogic Server 9</li><li>▪ <b>WebSphere</b>: IBM WebSphere</li><li>▪ <b>WebSphere_6_1</b>: IBM WebSphere 6.1</li><li>▪ <b>WebSphere_7</b>: IBM WebSphere 7</li><li>▪ <b>Default</b> (<code>TargetServer.None</code>)</li></ul>

### Usage

In addition to the supplied values, you can specify a custom server platform by supply the full class name for the platform.

Specifying a name of the class implementing `ExternalTransactionController` sets `CustomServerPlatform` with this controller.

### Examples

[Example 5–95](#) shows how to use this property in a `persistence.xml` file.

**Example 5–95** Using target-server in persistence.xml

```
<property name="eclipselink.target-server" value="OC4J_10_1_3"/>
```

[Example 5–96](#) shows how to use this property in a property map.

**Example 5–96** Using target-server in a Property Map

```
import org.eclipse.persistence.config.TargetServer;
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.TARGET_SERVER, TargetServer.OC4J_10_1_3);
```

## See Also

For more information, see:

- "Integrating EclipseLink with an Application Server"  
[http://wiki.eclipse.org/Integrating\\_EclipseLink\\_with\\_an\\_Application\\_Server\\_%28ELUG%29](http://wiki.eclipse.org/Integrating_EclipseLink_with_an_Application_Server_%28ELUG%29)

---

## transaction.join-existing

Use `eclipselink.transaction.join-existing` to

### Values

[Table 5–92](#) describes this persistence property's values.

**Table 5–92**    *Valid Values for target-server*

Value	Description
true	Forces persistence context to read through JTA-managed ("write") connection in case there is an active transaction
false	(Default)

### Usage

The property set in `persistence.xml` or passed to `createEntityManagerFactory` affects all `EntityManager`s created by the factory. If the property set to `true`, objects read during transaction *will not* be placed into the shared cache unless they have been updated. Alternatively, to apply the property only to some `EntityManager`s pass it to `createEntityManager` method.

### Examples

### See Also

For more information, see:

-



---

## validate-existence

Use the `eclipselink.validate-existence` persistence property configures to specify if EclipseLink should verify an object's existence on `persist()`.

### Values

[Table 5–93](#) describes this persistence property's values.

**Table 5–93** *Valid Values for validate-existence*

Value	Description
true	EclipseLink verifies the object's existence.
false	(Default) EclipseLink assumes the object is new, if it is not in the persistence context.

### Usage

EclipseLink will throw an error if a validated object is not in the persistence context.

### Examples

### See Also

For more information, see:

-





## validation-only

Use the `eclipselink.validation-only` persistence property to validate deployments by initializing descriptors but not connecting to the data source.

### Values

[Table 5–94](#) describes this persistence property's values.

**Table 5–94** Valid Values for validation-only

Value	Description
true	EclipseLink will initialize the descriptors but not log in.
false	(Default) EclipseLink will initialize the descriptors and log in.

### Usage

When setting `eclipselink.validation-only` to `true`, you must also configure `eclipselink.target-database` with a non-Auto class name or a short name.

### Examples

[Example 5–97](#) show how to use this property in the `persistence.xml` file.

**Example 5–97** Using validation-only in persistence.xml

```
<property name="eclipselink.validation-only" value="true"/>
```

### See Also

For more information, see:

- ["target-database"](#) on page -188



## weaving

Use `eclipselink.weaving` to specify if EclipseLink weaves the entity classes. EclipseLink JPA uses weaving to enhance JPA entities for such things as lazy loading, change tracking, fetch groups, and internal optimizations.

### Values

[Table 5–95](#) describes this persistence property's values.

**Table 5–95** Valid Values for weaving

Value	Description
true	Weave the entity classes dynamically.
false	Do not weave the eneity classes.
static	Weave the entity classes statically

### Examples

[Example 5–98](#) shows how to use this persistence property extension in the `persistence.xml` file.

**Example 5–98** Using weaving in persistence.xml

```
<property name="eclipselink.weaving" value="false"/>
```

[Example 5–99](#) shows how to use this extension in a property map

**Example 5–99** Using weaving in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.WEAVING, "false");
```

### See Also

For more information, see:

- "Using Weaving"  
[http://wiki.eclipse.org/Introduction\\_to\\_EclipseLink\\_Application\\_Development\\_%28ELUG%29#Using\\_Weaving](http://wiki.eclipse.org/Introduction_to_EclipseLink_Application_Development_%28ELUG%29#Using_Weaving)
- ["weaving.eager"](#) on page -200
- ["weaving.internal"](#) on page -202
- ["@ChangeTracking"](#) on page -30



## weaving.eager

Use `eclipselink.weaving.eager` to specify if EclipseLink uses indirection on eager relationships.

### Values

[Table 5–96](#) describes this persistence property's values.

**Table 5–96** Valid Values for *weaving.eager*

Value	Description
true	Enables indirection on eager relationships through weaving.
false	(Default) Disables indirection on eager relationships through weaving.

### Usage

One-to-one and many-to-one mappings, even when configured with `FetchType.EAGER`, will effectively become "lazy."

You can use this extension only if [weaving](#) is configured to true or static. See ["weaving"](#) on page -198 for more information.

### Examples

[Example 5–100](#) shows how to use this persistence property extension in the `persistence.xml` file.

**Example 5–100** Using weaving in *persistence.xml*

```
<property name="eclipselink.weaving.eager" value="true"/>
```

[Example 5–101](#) shows how to use this extension in a property map

**Example 5–101** Using weaving in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.WEAVING_EAGER, "true");
```

### See Also

For more information, see:

- ["weaving"](#) on page -198
-



## weaving.internal

Use `eclipselink.weaving.internal` to specify if EclipseLink uses internal optimizations through weaving.

### Values

[Table 5–97](#) describes this persistence property's values.

**Table 5–97** Valid Values for *weaving.internal*

Value	Description
true	(Default) Enables internal optimizations through weaving.
false	Disables internal optimizations through weaving.

### Usage

You can use this extension only if [weaving](#) is configured to true or static. See ["weaving"](#) on page -198 for more information.

### Examples

[Example 5–102](#) shows how to use this persistence property extension in the `persistence.xml` file.

**Example 5–102** Using weaving in *persistence.xml*

```
<property name="eclipselink.weaving.internal" value="false"/>
```

[Example 5–103](#) shows how to use this extension in a property map

**Example 5–103** Using weaving in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.WEAVING_INTERNAL, "false");
```

### See Also

For more information, see:

- ["weaving"](#) on page -198
-





## weaving.lazy

Use `eclipselink.weaving.lazy` to specify if EclipseLink uses lazy one-to-one and many-to-one mappings.

### Values

[Table 5–98](#) describes this persistence property's values.

**Table 5–98** Valid Values for *weaving.lazy*

Value	Description
true	(Default) Enables lazy one-to-one and many-to-one mappings through weaving.
false	Disables lazy one-to-one and many-to-one mappings through weaving.

### Usage

You can use this extension only if [weaving](#) is configured to true or static. See ["weaving"](#) on page -198 for more information.

### Examples

[Example 5–104](#) shows how to use this persistence property extension in the `persistence.xml` file.

**Example 5–104** Using weaving in *persistence.xml*

```
<property name="eclipselink.weaving.lazy" value="false"/>
```

[Example 5–105](#) shows how to use this extension in a property map

**Example 5–105** Using weaving in a Property Map

```
import org.eclipse.persistence.config.PersistenceUnitProperties;
propertiesMap.put(PersistenceUnitProperties.WEAVING_LAZY, "false");
```

### See Also

For more information, see:

- ["weaving"](#) on page -198
-

---

## eclipselink-orm.xml Schema Reference

You can use EclipseLink's native metadata XML file, `eclipselink-orm.xml`, to override mappings defined in the JPA configuration file (`orm.xml`) and to provide extended ORM features.

---

**Note:** Using the `eclipselink-orm.xml` mapping file enables many EclipseLink advanced features, but it may prevent the persistence unit from being portable to other JPA implementations.

---

The `eclipselink-orm.xml` file defines object-relational mapping metadata for EclipseLink. It has the same basic structure as the `orm.xml` file, which makes it more intuitive, requires minimum configuration, and makes it easy to override.

For more information, see:

- Section 12.2 "XML Overriding Rules" in the JPA Specification
- [http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic\\_JPA\\_Development/Configuration/JPA/orm.xml](http://wiki.eclipse.org/EclipseLink/UserGuide/JPA/Basic_JPA_Development/Configuration/JPA/orm.xml)

The schema for EclipseLink is `eclipselink_orm_X_X.xsd` where `X_X` is the current EclipseLink version number (such as `2_4` for **2.4**). All EclipseLink schemas are available from <http://wiki.eclipse.org/EclipseLink/XSDs>.

This chapter contains the following sections:

- [Overriding and Merging](#)

### Overriding and Merging

To override the `orm.xml` file's mapping, you must define the `META-INF/eclipselink-orm.xml` file in the project. When both `orm.xml` and `eclipselink-orm.xml` are specified, the contents of `eclipselink-orm.xml` will override `orm.xml` and any other JPA mapping file specified in the persistence unit. If there are overlapping specifications in multiple ORM files, the files are merged if they are no conflicting entities.

---

**Note:** The order of files defined in `persistence.xml` *does not* define the order of their processing. The files are processed, merged, and overridden as determined by the rules on page 6-2.

---

See the following sections for more information:

- [Rules for Overriding and Merging](#)
- [Examples of Overriding and Merging](#)

## Rules for Overriding and Merging

EclipseLink provides specific overriding and merging rules for the following elements defined in the `orm.xml` file:

- [Persistence Unit Metadata](#)
- [Entity Mappings](#)
- [Mapped Superclasses](#)
- [Entity override and merging rules](#)
- [Embeddable](#)

### Persistence Unit Metadata

In `eclipselink-orm.xml`, a `persistence-unit-metadata` element merges or overrides the values of existing `persistence-unit-metadata` specification as defined in [Table 6–1](#).

**Table 6–1** *Overriding and Merging Persistence Unit Metadata*

entity-mappings/ persistence-unit-metadata	Rule	Description
xml-mapping-metadata-complete	Full override	If specified, the complete set of mapping metadata for the persistence unit is contained in the XML mapping files for the persistence unit.
persistence-unit-defaults/schema	Full override	If a schema setting exists, then the <code>eclipselink-orm.xml</code> schema setting overrides the existing setting or creates a new schema setting.
persistence-unit-defaults/catalog	Full override	If a catalog setting exists, then the <code>eclipselink-orm.xml</code> catalog setting overrides the existing setting or creates a new catalog setting.
persistence-unit-defaults/access	Full override	If an access setting exists, then the <code>eclipselink-orm.xml</code> access setting overrides the existing setting, or creates a new access setting.
entity-mappings/persistence-unit-metadata/persistence-unit-defaults/cascade-persist	Full override	If a cascade-persist setting exists, then the <code>eclipselink-orm.xml</code> cascade-persist setting overrides the existing setting or creates a new cascade-persist setting.
entity-mappings/persistence-unit-metadata/persistence-unit-defaults/entity-listeners	Merge	If an entity-listeners exists, then the <code>eclipselink-orm.xml</code> entity-listeners will be merged with the list of all entity-listeners from the persistence unit.

### Entity Mappings

Entities, embeddables and mapped superclasses are defined within the `entity-mappings` section. The `eclipselink-orm.xml` entities, embeddables and mapped superclasses are added to the persistence unit as defined in [Table 6–2](#).

**Table 6–2** *Overriding and Merging Entity Mappings*

entity-mappings/	Rule	Description
package	None	The package element specifies the package of the classes listed within the subelements and attributes of the same mapping file only. It is only applicable to those entities that are fully defined within the eclipselink-orm.xml file, else its usage remains local and is same as described in the JPA specification.
catalog	None	The catalog element applies only to the subelements and attributes listed within the eclipselink-orm.xml file that are not an extension to another mapping file. Otherwise, the use of the catalog element within the eclipselink-orm.xml file remains local and is same as described in the JPA specification.
schema	None	The schema element applies only to the subelements and attributes listed within the eclipselink-orm.xml file that are not an extension to another mapping file. Otherwise, the use of the schema element within the eclipselink-orm.xml file remains local and is same as described in the JPA specification.
access	None	The access element applies only to the subelements and attributes listed within the eclipselink-orm.xml file that are not an extension to another mapping file. Otherwise, the use of the access element within the eclipselink-orm.xml file remains local and is same as described in the JPA specification.
sequence-generator	Full override	A sequence-generator is unique by name. The sequence-generator defined in the eclipselink-orm.xml will override a sequence-generator of the same name defined in another mapping file. Outside of the overriding case, an exception is thrown if two or more sequence-generators with the same name are defined in one or across multiple mapping files.
table-generator	Full override	A table-generator is unique by name. The table-generator defined in the eclipselink-orm.xml will override a table-generator of the same name defined in another mapping file. Outside of the overriding case, an exception is thrown if two or more table-generators with the same name are defined in one or across multiple mapping files.
named-query	Full override	A named-query is unique by name. The named-query defined in the eclipselink-orm.xml will override a named-query of the same name defined in other mapping files. Outside of the overriding case, an exception is thrown if two or more named-queries with the same name are defined in one or across multiple mapping file.
named-native-query	Full override	A named-native-query is unique by name. The named-native-query defined in the eclipselink-orm.xml will override a named-native-query of the same name defined in other mapping files. Outside of the overriding case, an exception is thrown if two or more named-native-queries with the same name are defined in one or across multiple mapping files.
sql-result-set-mapping	Full override	A sql-result-set-mapping is unique by name. The sql-result-set-mapping defined in the eclipselink-orm.xml will override a sql-result-set-mapping of the same name defined in other mapping files. Outside of the overriding case, an exception is thrown if two or more sql-result-set-mapping entities with the same name are defined in one or across multiple mapping files.

### Mapped Superclasses

A mapped-superclass can be defined completely, or with specific elements to provide extensions to a mapped-superclass from another mapping file. [Table 6–3](#) lists individual override and merging rules:

**Table 6–3** *Overriding and Merging Mapped Superclasses*

<b>entity-mappings/mapped-superclass</b>	<b>Rule</b>	<b>Description</b>
id-class	Full override	If an id-class exists, then the eclipselink-orm.xml id-class setting overrides the existing setting, or creates a new id-class setting.
exclude-default-listeners	Full override	If an exclude-default-listeners exists, then the eclipselink-orm.xml exclude-default-listeners setting will be applied. If the exclude-default-listeners setting is not specified, it will not override an existing setting, that is essentially turning it off.
exclude-superclass-listeners	Full override	If an exclude-superclass-listeners setting exists, then the eclipselink-orm.xml exclude-superclass-listeners setting will be applied. If exclude-superclass-listeners setting is not specified, it will not override an existing setting, that is essentially turning it off.
entity-listeners	Merge and full override	<p>If an entity-listeners setting exists, then the eclipselink-orm.xml entity-listeners setting will override and merge with an existing setting, or creates a new entity-listeners setting all together.</p> <p><b>Note:</b> An entity listener override must be complete. All lifecycle methods of that listener must be specified and no merging of individual lifecycle methods of an entity listener is allowed. The class name of the listener is the key to identify the override.</p>
pre-persist	Full override	If a pre-persist setting exists, then the eclipselink-orm.xml pre-persist setting overrides the existing setting, or creates a new pre-persist setting.
post-persist	Full override	If a post-persist setting exists, then the eclipselink-orm.xml post-persist setting overrides the existing setting, or creates a new post-persist setting.
pre-remove	Full override	If a pre-remove setting exists, then the eclipselink-orm.xml's pre-remove setting overrides the existing setting, or creates a new pre-remove setting.
post-remove	Full override	If a post-remove setting exists, then the eclipselink-orm.xml's post-remove setting overrides the existing setting, or creates a new post-remove setting.
pre-update	Full override	If a pre-update setting exists, then the eclipselink-orm.xml's pre-update setting overrides the existing setting, or creates a new pre-update setting.
post-update	Full override	If a post-update setting exists, then the eclipselink-orm.xml's post-update setting overrides the existing setting, or creates a new post-update setting.
post-load	Full override	If a post-load setting exists, then the eclipselink-orm.xml's post-load setting overrides the existing setting, or creates a new post-load setting.
attributes	Merge and mapping level override	If the attribute settings (such as id, embedded-id, basic, version, many-to-one, one-to-many, or one-to-one) exist at the mapping level, then the eclipselink-orm.xml attributes merges or overrides the existing settings, else creates new attributes.

**Table 6–3 (Cont.) Overriding and Merging Mapped Superclasses**

entity-mappings/mapped-superclass	Rule	Description
class	None	
access	Full override	If an access setting exists, then the eclipselink-orm.xml's access setting overrides the existing setting, or creates a new access setting. It also overrides the default class setting.
metadata-complete	Full override	If a metadata-complete setting exists, then the eclipselink-orm.xml's metadata-complete setting will be applied. If metadata-complete setting is not specified, it will not override an existing setting, that is essentially turning it off.

### Entity override and merging rules

An entity can be defined completely, or with specific elements to provide extensions to an entity from another mapping file. The following table lists individual override and merging rules:

**Table 6–4 Overriding and Merging Entities**

entity-mappings/entity	Rule	Description
table	Full override	The table definition overrides any other table setting (with the same name) for this entity. There is no merging of individual table values.
secondary-table	Full override	The secondary-table definition overrides another secondary-table setting (with the same name) for this entity. There is no merging of individual secondary-table(s) values.
primary-key-join-column	Full override	The primary-key-join-column(s) definition overrides any other primary-key-join-column(s) setting for this entity. There is no merging of the primary-key-join-column(s). The specification is assumed to be complete and these primary-key-join-columns are the source of truth.
id-class	Full override	If an id-class setting exists, then the eclipselink-orm.xml's id-class setting overrides the existing setting, or creates a new id-class .
inheritance	Full override	If an inheritance setting exists, then the eclipselink-orm.xml's inheritance setting overrides the existing setting, or creates a new inheritance setting.
discriminator-value	Full override	If a discriminator-value setting exists, then the eclipselink-orm.xml's discriminator-value setting overrides the existing setting, or creates a new discriminator-value setting.
discriminator-column	Full override	If a discriminator-column setting exists, then the eclipselink-orm.xml's discriminator-column setting overrides the existing setting, or creates a new discriminator-column setting.
sequence-generator	Full override	A sequence-generator is unique by name. The sequence-generator defined in eclipselink-orm.xml overrides sequence-generator of the same name defined in other mapping files. Outside of the overriding case, an exception is thrown if two or more sequence-generators with the same name are defined in one or across multiple mapping files.

**Table 6–4 (Cont.) Overriding and Merging Entities**

entity-mappings/entity	Rule	Description
table-generator	Full override	A table-generator is unique by name. The table-generator defined in eclipselink-orm.xml overrides table-generator of the same name defined in other mapping files. Outside of the overriding case, an exception is thrown if two or more table-generators with the same name are defined in one or across multiple mapping files.
named-query	Merge and full override	A named-query is unique by name. The named-query defined in eclipselink-orm.xml overrides any named-query of the same name defined in other mapping files. Outside of the overriding case, an exception is thrown if two or more named-query elements with the same name are defined in one or across multiple mapping files.
named-native-query	Merge and full override	A named-native-query is unique by name. The named-native-query defined in eclipselink-orm.xml overrides named-native-query of the same name defined in other mapping files. Outside of the overriding case, an exception is thrown if two or more named-native-query elements with the same name are defined in one or across multiple mapping files.
sql-result-set-mapping	Merge and full override	A sql-result-set-mapping is unique by name. sql-result-set-mapping defined in eclipselink-orm.xml overrides sql-result-set-mapping of the same name defined in other mapping files. Outside of the overriding case, an exception is thrown if two or more sql-result-set-mapping elements with the same name are defined in one or across multiple mapping files.
exclude-default-listeners	Full override	If an exclude-default-listeners setting exists, then the eclipselink-orm.xml's exclude-default-listeners setting will be applied. If an exclude-default-listeners setting is not specified, it will not override an existing setting, that is essentially turning it off.
exclude-superclass-listeners	Full override	If an exclude-superclass-listeners setting exists, then the eclipselink-orm.xml's exclude-superclass-listeners setting will be applied. If an exclude-superclass-listeners setting is not specified, it will not override an existing setting, that is essentially turning it off.
entity-listeners	Full override	<p>If an entity-listeners setting exists, then the eclipselink-orm.xml's entity-listeners setting will override and merge with an existing setting, or creates a new entity-listeners setting all together.</p> <p><b>Note:</b> An entity listener override must be complete. All lifecycle methods of that listener must be specified and no merging of individual lifecycle methods of an entity listener is allowed. The class name of the listener is the key to identify the override.</p>
pre-persist	Full override	If a pre-persist setting exists, then the eclipselink-orm.xml's pre-persist setting overrides the existing setting, or creates a new pre-persist setting.
post-persist	Full override	If a post-persist setting exists, then the eclipselink-orm.xml's post-persist setting overrides the existing setting, or creates a new post-persist setting.



**Table 6–4 (Cont.) Overriding and Merging Entities**

entity-mappings/entity	Rule	Description
pre-remove	Full override	If a pre-remove setting exists, then the eclipselink-orm.xml's pre-remove setting overrides the existing setting, or creates a new pre-remove setting.
post-remove	Full override	If a post-remove setting exists, then the eclipselink-orm.xml's post-remove setting overrides the existing setting, or creates a new post-remove setting.
pre-update	Full override	If a pre-update setting exists, then the eclipselink-orm.xml's pre-update setting overrides the existing setting, or creates a new pre-update setting.
post-update	Full override	If a post-update setting exists, then the eclipselink-orm.xml's post-update setting overrides the existing setting, or creates a new post-update setting.
post-load	Full override	If a post-load setting exists, then the eclipselink-orm.xml's post-load setting overrides the existing setting, or creates a new post-load setting.
attributes	Merge and mapping level override	If the attribute settings (id, embedded-id, basic, version, many-to-one, one-to-many, one-to-one) exist at the mapping level, then the eclipselink-orm.xml's attributes merges or overrides the existing settings, else creates new attributes.
association-override	Merge and mapping level override	If an association-override setting exists, then the eclipselink-orm.xml's association-override setting overrides the existing setting, or creates a new association-override setting.
name	Full override	If a name setting exists, then the eclipselink-orm.xml's name setting overrides the existing setting, or creates a new name setting.
class	None	
access	Full override	If an access setting exists, then the eclipselink-orm.xml's access setting overrides the existing setting, or creates a new access setting. It also overrides the default class setting
metadata-complete	Full override	If a metadata-complete setting exists, then the eclipselink-orm.xml's metadata-complete setting will be applied. If a metadata-complete setting is not specified, it will not override an existing setting, that is essentially turning it off.

### Embeddable

An embeddable can be defined wholly or may be defined so as to provide extensions to an embeddable from another mapping file. Therefore, we will allow the merging of that class' metadata. [Table 6–4](#) lists the individual override rules Embeddable classes.

**Table 6–5** *Overriding and Merging Embeddable Classes*

entity-mappings/ embeddable	Rule	Description
attributes	Override and merge	If the attribute settings (id, embedded-id, basic, version, many-to-one, one-to-many, one-to-one, many-to-many, embedded, transient) exist at the mapping level, then the eclipselink-orm.xml's attributes merges or overrides the existing settings, or creates new attributes.
class	None	
access	Full override	If an access setting exists, then the eclipselink-orm.xml's access setting overrides the existing setting, or creates a new access setting. It also overrides the default class setting.
metadata-complete	Full override	If a metadata-complete setting exists, then the eclipselink-orm.xml's metadata-complete setting will be applied. If a metadata-complete setting is not specified, it will not override an existing setting, that is essentially turning it off.

## Examples of Overriding and Merging

### **Example 6–1** *Overriding/Merging Example 1*

In this example, your EclipseLink project contains:

- META-INF/orm.xml – Defines Entity **A** with the mappings **b** and **c**
- META-INF/eclipselink-orm.xml – Defines Entity **A** with the mappings **c** and **d**

Results in:

- Entity **A** containing:
  - mapping **b** (from orm.xml)
  - mappings **c** and **d** (from eclipselink-orm.xml)

### **Example 6–2** *Overriding/Merging Example 2*

In this example, your EclipseLink project contains:

- META-INF/orm.xml – Defines Entity **A** with mappings **b** and **c**
- META-INF/some-other-mapping-file.xml – Defines Entity **B** with mappings **a** and **b**
- META-INF/eclipselink-orm.xml – Defines Entity **A** with the mappings **c** and **d**, and Entity **B** with mapping **b** and **c**

Results in:

- Entity **A** containing:
  - mapping **b** (from orm.xml)
  - mappings **c** and **d** (from eclipselink-orm.xml)
- Entity **B** containing:
  - mapping **a** (from some-other-mapping-file)
  - mappings **b** and **c** (from eclipselink-orm.xml)

**Example 6-3 Overriding/Merging Example 3**

In this example, your EclipseLink project contains:

- META-INF/orm.xml – Defines Entity **A** with mappings **b** and **c**.
- META-INF/eclipselink-orm.xml – Defines Entity **A** with mappings **c** and **d**.
- META-INF/some-other-mapping-file.xml – Defines Entity **A** with mapping **x**.

Results in:

- Entity **A** containing:
  - mapping **b** (from orm.xml)
  - mappings **c** and **d** (from eclipselink-orm.xml)
  - mapping **x** (from some-other-mapping-file.xml)

**Example 6-4 Overriding/Merging Example 4**

In this example, your EclipseLink project contains:

- META-INF/orm.xml – Defines Entity **A** with mappings **b** and **c**.
- META-INF/extensions/eclipselink-orm.xml – Defines defines Entity **A** with mappings **c** and **d**.

Note: The file is added through a `<mapping-file>` tag in the `persistence.xml` file.

Results in an exception, due to conflicting specifications for mapping **c**.

**Example 6-5 Overriding/Merging Example 5**

In this example, your EclipseLink project contains:

- META-INF/orm.xml – Defines Entity **A** with mappings **b** and **c**
- META-INF/jpa-mapping-file.xml – Defines Entity **A** with mappings **a** and **d**
- META-INF/extensions/eclipse-mapping-file.xml – Defines defines Entity **A** with mappings **c** and **d**

Results in an exception, due to conflicting specifications for mapping **c** or **d** (which ever is processed first).