



EclipseWorld 2007  
November 6-8, 2007

## Eclipse JPA

Building JPA Applications with EclipseLink and Dali

Neil Hauge, Oracle

Dali Project co-Lead

Doug Clarke, Oracle

EclipseLink Project co-Lead

# Agenda

- JPA Primer
- Eclipse JPA Projects
  - WTP's JPA Tooling Project : Dali
  - Eclipse Persistence Services Project  
“EclipseLink”
- Eclipse JPA in action ... the demo
- Where are we headed?

# About Java Persistence API (JPA)

- Separate document bundled as part of EJB 3.0 specification
- Suitable for use in different modes
  - Standalone in Java SE environment
  - Hosted within a Java EE Container
- Standardization of current persistence practices
- Merging of expertise from persistence vendors and communities including: TopLink, Hibernate, JDO, EJB vendors and individuals

# JPA—in a Nutshell

- A Java standard that defines:
  - how Java objects are stored in relational databases (specified using a standard set of mappings)
  - a programmer API for reading, writing, and querying persistent Java objects (“Entities”)
  - a full featured query language
  - a container contract that supports plugging any JPA runtime in to any compliant container.

# Implementations

- Persistence provider vendors include:
  - Oracle, Sun / TopLink Essentials (RI)
  - Eclipse JPA – EclipseLink Project
  - BEA Kodo / Apache OpenJPA
  - RedHat / JBoss Hibernate
  - SAP JPA
  - Oracle TopLink
- JPA containers:
  - GlassFish/SunAS, OracleAS, SAP, BEA, JBoss, Spring 2.0
- IDE: Eclipse, MyEclipse, NetBeans™, IntelliJ, Oracle JDeveloper

# JPA—POJO Entities

- Concrete classes
- No required interfaces
  - No required business interfaces
  - No required callback interfaces
- `new()` for instance creation
- Direct access or getter/setter methods
  - Can contain logic (e.g. for validation, etc.)
- “Managed” by an `EntityManager`
- Can leave the Container (become “detached”)

# Object-Relational Mappings

- Core JPA Mappings
  - Id
  - Basic
  - Relationships
    - OneToOne
    - OneToMany/ManyToOne
    - ManyToMany
  - And more...
- Can be specified using Annotations or XML

# JPA Entity—Mappings on Fields

```
@Entity public class Customer {  
  
    @Id  
    private String name;  
    @OneToOne  
    private Account account;  
  
    public String getName() { return name; }  
    public void setName(String name) {  
        this.name = name;  
    }  
    public Account getAccount() { return account; }  
    public void setAccount(Account account) {  
        this.account = account;  
    }  
}
```



# JPA Entity—Mappings on Properties

9


```
@Entity public class Customer {  
  
    private String name;  
    private Account account;  
  
    @Id  
    public String getName() { return name; }  
    public void setName(String name) {  
        this.name = name;  
    }  
    @OneToOne  
    public Account getAccount() { return account; }  
    public void setAccount(Account account) {  
        this.account = account;  
    }  
}
```

# JPA Entity—Mappings in XML

```
<entity-mappings
  xmlns="http://java.sun.com/xml/ns/persistence/orm"
...
<entity class="Customer">
  <attributes>
    <id name="name"/>
    <one-to-one name="account"/>
  </attributes>
</entity>
...
</entity-mappings>
```


# Why do you need JPA Tools?

- JPA runtime combines:
  - Java Classes
  - Mapping Metadata
  - Database schema



# Why do you need JPA Tools?

- How can you tell if they all match?
  - Deploy and run tests?
    - ✗ slow
    - ✗ find one problem at a time (fix, run, fix, ...)
    - ✓ definitive
  - Design time validation?
    - ✓ quick
    - ✓ finds all issues
    - ✓ validates against spec
    - ✗ runtime may not match spec



# About Dali


- Support for the definition, editing, and deployment of Object-Relational (O/R) mappings for JPA Entities
- Simplify mapping definition and editing through:
  - intelligent mapping assistance
  - dynamic problem identification
  - Mapping generation
- Extensible frameworks and tools so vendors and open source projects can provide specific support for their JPA runtimes
- A subproject of the Web Tools Platform (WTP)

# Dali Goals

- **Simplicity**
  - Intelligent mapping assistance and automated generation
- **Intuitiveness**
  - Use existing and consistent modeling and tooling practices in Eclipse
  - Light-weight views offer assistance but don't get in the way of power users
- **Compliance**
  - Support any and all EJB 3.0 compliant runtime implementations
  - Test using EJB 3.0 Reference Implementation
- **Extensibility**
  - Provide the ability for vendors and open source projects to seamlessly add their own value-add features

# Why ‘Dali’?

- JPA supports “The Persistence of Memory”—which is the title of a well known Salvador Dali painting.



Salvador Dali. *The Persistence of Memory*. 1931.

© 2005 Salvador Dali, Gala-Salvador Dali Foundation/Artists Rights Society (ARS), New York




## The Dali Value Proposition

You don't need Dali to build JPA applications—but you're going to be way more productive if you do!




# Dali Contributions to Eclipse

- JPA Mapping Validation
- JPA Structure and Details Views
- Java Source Editor enhancements



# Mapping Validation

- Annotations and/or XML used to define JPA Entities.
- JDT validates syntax, but doesn't understand what the annotations *mean*.



# Mapping Validation

- Java Source Editor enhancements
- Mapping Problem Markers


The screenshot illustrates a mapping validation issue in Eclipse. The Java source editor shows the following code:

```
@Entity
public class Address {
    @Id
    private int id;
    private String street;
    private String city;
    private String province;
    private String country;
}
```

The database table 'ADDRESS' has columns: ID, STREET, and STATE. A red dashed arrow points from the 'province' field in the code to the 'STATE' column in the table, with the text 'Default mapping won't work!' next to it. Below the code, the Eclipse Problems view shows an error: 'The column province cannot be found on table Address'.

# Mapping Assistance

- JPA Details View





# JPA Structure View






- Provides a JPA specific view of Java Class or ORM XML Mapping File
- A thumbnail sketch of how an Entity is mapped
- Supports navigation between mappings
- Automatically adjusts to either property or field mapping in Java
- Represents structure in Java and XML artifacts



# JPA Perspective—all your JPA


23

## Views




# Synchronizing Persistence.xml

- In Java SE environment, persistence.xml must list the Entities—Dali offers synchronization



The screenshot shows the content of a file named 'persistence.xml'. The XML code is as follows:

```
<?xml version="1.0" encoding="UTF-8"?>
<persistence xmlns="http://java.sun.com
  <persistence-unit name="jdj"/>
</persistence>
```





# Synchronizing Persistence.xml

A screenshot of an Eclipse IDE window. The title bar of the window is labeled 'persistence.xml'. The window displays the following XML code:

```
<?xml version="1.0" encoding="UTF-8"?>
<persistence xmlns="http://java.sun.com/xml
  <persistence-unit name="jddj">
    <class>model.Customer</class>
    <class>model.CustomerInfo</class>
    <class>model.Invoice</class>
    <class>model.Phone</class>
  </persistence-unit>
</persistence>
```

# Integrated F1 Help

- In any Dali view you can hit F1 to get context specific help.

The screenshot shows the Eclipse IDE's integrated F1 help system. The top bar indicates the current view is 'Persistence Outline'. The main content area displays the 'One-to-one mapping' help page. The page includes a table of properties for one-to-one mapping and a 'Go To:' section with links to All Topics, Search, Related Topics, Bookmarks, and Index.

Property	Description	Default
Target Entity	The entity to which this attribute is mapped.	null You do not need to explicitly specify the target entity, since it can be inferred from the type of object being referenced.
Cascade Type	See " <a href="#">Cascade Type</a> " for details. <ul style="list-style-type: none"> <li>• Default</li> <li>• All</li> <li>• Persist</li> <li>• Merge</li> <li>• Remove</li> </ul>	Default
Fetch Type	Defines how data is loaded from the database.	Eager

Go To: [All Topics](#) [Search](#) [Related Topics](#) [Bookmarks](#) [Index](#)

# Dali 0.5 Features

- Support for majority of annotations including relationships
- Integration with WTP RDB components
- JPA Details view supports mapping using database schema with table and column drop downs
- Design time validation of mappings against object and data model (including unspecified default mappings)
- Problems markers (e.g., Entity missing @Id)
- Wizards for basic Entity generation from tables

# Dali 1.0 Features

- Support for XML Mapping File (orm.xml)  
configuration
  - Uses same views as JPA Annotation editing
- Integration with Data Tools Platform (DTP) for database meta-data
- Facet based functionality for better integration with various WTP project types
- Enhanced design-time validation for XML and Java Annotations mappings as well as the combination as defined by the spec.
- Extensibility for vendor specific extensions

# JPA Application Development Scenarios

29

## Possible Approaches using Dali

- Meet in the Middle
  - existing object and data models
- Bottom Up
  - generate mapped object model from data model
- Top Down
  - generate data model from mapped object model

# Meet In the Middle (MITM)

- The advantage of MITM is that you can focus on getting your object model and data models correct.
  - Table != Class
    - 1 Table could be N classes (using embedded)
    - N tables could be 1 class (with secondary table)
  - Use Java language features like inheritance not present in relational model
- Dali's validation makes MITM practical
  - Avoids map, deploy, debug cycle
  - Provides access to database schema to provide valid choices

# Bottom Up

- Generate Entities from Tables
  - Great way to bootstrap a JPA application from an existing database
  - Uses an Entity == Table approach
  - Do it once and then modify the generated Entities
    - Dali mapping validation will help identify issues resulting from modifications to Entities

# Top Down

- Generate DDL from Entities
  - Some support in Dali 0.5 release
  - Removed in 1.0 in favor of using full featured support implemented by JPA runtimes.
  - Extension point in Dali to allow for plugging in runtime DDL generation.



# Dali Adoption

- Oracle
  - Providing resources for Dali project
  - Building extensions to Dali for EclipseLink
- RedHat/JBoss
  - Plans to bundle/integrate with Dali for Hibernate Tools
  - Dali project member
- IBM
  - Incorporating Dali into future tooling products
- SAP
  - Shipped Dali in Eclipse based SAP NetWeaver Developer Studio Java EE 5 preview

# Dali 2.0 Plans

- Themes
  - Extensibility
  - Comprehensive JPA configuration
  - Enhanced Validation
  - Usability/Integration
- Related requirements
  - Public API for adopters
  - Persistence.xml UI
  - Named Query definition
  - Project Explorer

# Dali Summary

- JPA—the new Java EE standard for object-relational mapping (inside and outside of a container)
- Dali—the WTP project bringing developer productivity to JPA
  - Mapping validation to avoid the map, deploy, debug cycle
  - Intelligent mapping assistance to avoid problems and speed up the process of mapping
  - Integrated with WTP to support development for Java SE and EE

# Eclipse Persistence Services

## Project – “*EclipseLink*”

Java SE

Java EE

OSGi


Spring

ADF

JPA



MOXy



EIS




SDO




DBWS  
XML-RDBMS



Eclipse Persistence Services Project (EclipseLink)




Databases



XML Data



Legacy Systems



# EclipseLink JPA Extensions

- Query Hints
  - Pessimistic Locking (*toplink-pessimistic-lock*)
  - Refresh (*toplink.refresh*)
- Persistence Unit Properties
  - JDBC connection pooling
  - Logging
  - DDL Generation
  - Platforms
  - Customization callbacks
  - Caching
- Weaving

# JDBC Connection Settings

- Resource-level JDBC technology settings are vendors responsibility
- Need to specify the four basic JDBC technology properties to obtain driver connections
  - Driver class, URL, username, password
- The property keys will be different, but the values for a given JDBC technology data source will be the same for all vendors
- Used when not in a container, or when managed data sources are not available or not desired

# JDBC Connection Settings

```
<properties>
...
<property name="eclipselink.jdbc.driver"
    value="oracle.jdbc.Driver"/>

<property name="eclipselink.jdbc.url"
    value="jdbc:oracle:thin:@localhost:1521:XE"/>

<property name="eclipselink.jdbc.user"
    value="scott"/>

<property name="eclipselink.jdbc.password"
    value="tiger"/>
```

# Logging

- Users want to control over logging, but vendors use different logging APIs
- Can usually configure to use one of the well-known logging APIs
  - `java.util.logging`, `log4j`, etc.
- Common requirement is to configure the logging level to show the generated SQL



# Logging

```
<properties>
```

```
...
```

```
<property
```

```
    name="eclipseLink.logging.level"
```

```
    value="FINE" />
```

```
...
```

```
</properties>
```

# DDL Generation

- Standard enables it but does not currently dictate that providers support it
- Mapping metadata specifies how DDL should be generated
- Vendors may offer differing levels of support, including:
  - Generating DDL to a file only
  - Generating and executing DDL in DB
  - Dropping existing tables before creating new ones

# DDL Generation

```
<properties>
```

```
...
```

```
<property
```

```
    name="eclipseLink.ddl-generation"
```

```
    value="create-tables" />
```

```
...
```

```
</properties>
```

# Database Platform

XML:

```
<properties>
<property
    name="eclipseLink.target-database"
    value="Derby" />
</properties>
```

API:

```
properties.put(
    EclipseLinkProperties.TARGET_DATABASE,
    TargetDatabase.ORACLE);
```

# Target Database Options

```

public class TargetDatabase {
    public static final String Auto = "Auto";
    public static final String Oracle = "Oracle";
    public static final String DB2 = "DB2";
    public static final String DB2Mainframe = "DB2Mainframe";
    public static final String Derby = "Derby";
    public static final String HSQL = "HSQL";
    public static final String Informix = "Informix";
    public static final String JavaDB = "JavaDB";
    public static final String MySQL4 = "MySQL4";
    public static final String PointBase = "PointBase";
    public static final String PostgreSQL = "PostgreSQL";
    public static final String SQLAnywhere = "SQLAnywhere";
    public static final String SQLServer = "SQLServer";
    public static final String Sybase = "Sybase";
    public static final String TimesTen = "TimesTen";
}

```

# Server Platform

- Enables simplified configuration of the target application server
- Used to enable integration with:
  - JTA transaction manager
  - Logging
  - JDBC connection un-wrapping

```
<property name="eclipseLink.target-server"  
          value="SunAS9"/>
```

- Supported options: *None, SunAS9, OC4J\_10\_1\_3*

# Customization Using Properties

```
<properties>
```

```
...
```

```
<property
```

```
    name="toplink.session.customizer"
```

```
    value="acme.MySessionCustomizer"/>
```

```
<property
```

```
    name="toplink.descriptor.customizer.Employee"
```

```
    value="acme.MyDescriptorCustomizer"/>
```

```
...
```

```
</properties>
```

# Descriptor & Session Customizers

```
public class MySessionCustomizer
    implements SessionCustomizer {

    public void customize(Session session) {
        session.setProfiler(new PerformanceProfiler());
    }
}

public class MyDescriptorCustomizer
    implements DescriptorCustomizer {


    public void customize(ClassDescriptor desc) {
        desc.disableCacheHits();
    }
}
```



# Concurrency Protection - Locking

- Optimistic concurrency is built into JPA, but no support for pessimistic locking is specified
- Will likely be addressed in a future JPA release
- All credible JPA implementations support pessimistic locks in some way or another
- EntityManager lock() method can be used with optimistic locking, and error handling
- EclipseLink query hint for pessimistic locking  
`query.setHint(PESSIMISTIC_LOCK, LockNowait);`

# EclipseLink Caching



# Cache Configuration

- Cache Shared/Isolated

```
<property name="eclipselink.cache.shared.default" value="true"/>
```

- Cache Type & Size

- SoftWeak, HardWeak
- Weak
- Full
- None

```
<property name="eclipselink.cache.type.default" value="Full"/>
```

```
<property name="eclipselink.cache.type.MyEntity" value="Weak"/>
```

# Minimize stale cache

1. Configure the cache relative to application data's usage
  - Is the data shared between users/processes?
  - Is the data volatile?
    - Only through JPA application?
    - Through direct DB modification?
2. Ensure you protect any data that can be concurrently modified with a locking strategy
  - Must handle optimistic lock failures on flush/commit
3. Use query refreshing to minimize optimistic lock failures

# Weaving Support

- EclipseLink makes use of Weaving (ASM) to introduce additional functionality into the JPA entity classes
  - Needed for M:1 and 1:1 lazy fetching
  - Integrated with OC4J 10.1.3.1 and Spring 2.0
  - Available for Java SE using JDK/JRE's `-javaagent:`
  - Optional
  - Static weaving also supported
    - Weaving of .class files before deployment

# EclipseLink Status

- Incubating Technology Project
- Initial contribution of Oracle TopLink complete
- 1.0 Milestone 1 Features
  - Automated test and build
  - JPA 1.0 compliance verified by Oracle
  - MOXy
  - SDO
  - Wiki Content to help early adopters

# Getting Started with Eclipse JPA

- EJB 3.0 & JPA Specification
  - JPA 1.0: [www.jcp.org/en/jsr/detail?id=220](http://www.jcp.org/en/jsr/detail?id=220)
  - JPA 2.0: [www.jcp.org/en/jsr/detail?id=317](http://www.jcp.org/en/jsr/detail?id=317)
- Dali Project
  - [www.eclipse.org/dali](http://www.eclipse.org/dali)
- EclipseLink
  - [www.eclipse.org/eclipselink](http://www.eclipse.org/eclipselink)