

[Home \(/\)](#)[Developers \(/developers\)](#)[Admin \(/admin/users\)](#)[Account \(/account\)](#)[Logout \(/users/sign_out\)](#)

DEVELOPERS

[Documentation \(/developers\)](#)[My Apps \(/oauth/applications\)](#)

OAuth

[Authorization Code](#)[Access Token](#)

ACCOUNT

[Show](#)

RESOURCES

[List](#)

DATA

[List](#)[Latest](#)[Upload](#)

SESSIONS

[List](#)[Create](#)[Get](#)[Delete](#)

SESSION LOGS

[List](#)[Create](#)

DEVICES

[List](#)[Register](#)[Unregister](#)[Update](#)

DATA ACCESS WINDOWS

[List](#)[Create](#)

GROUPS

[List](#)[Create](#)[Delete](#)

GROUP MEMBERS

[List](#)[Add User](#)[Remove User](#)[Make Public](#)[Make Private](#)

Igtimi API

Introduction

All API calls, with the exception of the OAuth 2 calls, require an Oauth access_token parameter for the user to be passed as either a GET or POST parameter.

OAuth 2

Authorize

DESCRIPTION Authenticates the user and authorizes the application to access the user's Igtimi Account

URL STRUCTURE `https://www.igtimi.com/oauth/authorize`

PARAMETERS **response_type** ("code" or "token") - The requested OAuth grant type.

client_id (string) - The client id you received when you registered the application.

redirect_uri (string) - The URI to redirect to after the user has authenticated. Must match URI registered with the application.

METHOD GET

RETURNS 302 Redirect to the application's redirect_uri. Redirect contains an access_code, or access_token, depending on the OAuth grant type requested

Access Token

DESCRIPTION Obtains an access token

URL STRUCTURE `https://www.igtimi.com/oauth/token`

PARAMETERS **grant_type** ("authorization_code" or "client_credentials") - The requested OAuth grant type.

client_id (string) - The client id you received when you registered the application.

client_secret (string) - The client secret you received when you registered the application.

code (string) - The access_code, as returned by the Authorize API call. Required for "authorization_code" grant type only.

redirect_uri (string) - The URI to redirect to after the user has authenticated. Must match URI registered with the application. Required for "authorization_code" grant type only.

METHOD POST

RETURNS The access token

Account

Show

DESCRIPTION Returns the user's account details.

URL STRUCTURE

https://www.igtimi.com/api/v1/account

METHOD GET

RETURNS The details of the user

Sample JSON response

```
{
  "user": {
    "id": 2,
    "first_name": "Michael",
    "surname": "Scott",
    "email": "michael@scott.com"
  }
}
```

Resources

List

DESCRIPTION Lists all the resources the user can see.

URL STRUCTURE

https://www.igtimi.com/api/v1/resources

PARAMETERS

permission ("read" or "modify") - Gets resources with the given permission.

start_time (millisecond unix timestamp) *optional* - Gets the resources created since the given date/time.

end_time (millisecond unix timestamp) *optional* - Gets the resources created before the given date/time.

serial_numbers (array of serial_numbers) *optional if requesting "modify" permissions* - The serial numbers to request data for.

METHOD GET

RETURNS The requested resources the user has permission to use

Sample JSON response

```
{
  "resources": [
    {
      "resource": {
        "id": 1,
        "start_time": 1360197740000,
        "end_time": 1360198040000,
        "device_serial_number": "AA-AA-AAAA",
        "data_types": [1, 2, 3],
        "permissions": {
          "read": true,
          "modify": true
        }
      }
    }
  ]
}
```

Return value definitions

Field	Description
device_id	The internal id of the resource.

device_serial_number	The serial number of the device.
data_types	The types of data contained within the bounds of the resource.
read	If true the user can request data from the resource.
modify	If true the user can share the resource with others.

Data

List

DESCRIPTION Returns data from the specified devices

URL STRUCTURE `https://www.igtimi.com/api/v1/resources/data`

PARAMETERS

- start_time** (millisecond unix timestamp) - Gets the data since the given date/time.
- end_time** (millisecond unix timestamp) - Gets the data since before the given date/time.
- serial_numbers** (Array of serial_numbers) - The serial numbers to request data for.
- types** (Hash of data types and compression values) - Gets data of given data types and compresses it at the given value.

METHOD GET

RETURNS The requested data the user has permission to see

Sample JSON response

```
{
  "AA-AA-AAA-5":{
    "1":{
      "t":[
        1360618858970
      ],
      "1":[
        172.04
      ],
      "2":[
        -45.02
      ]
    }
  }
}
```

Latest

DESCRIPTION Returns the latest datum for the specified devices

URL STRUCTURE `https://www.igtimi.com/api/v1/resources/data/latest`

PARAMETERS

- serial_numbers** (Array of serial_numbers) - The serial numbers to request data for.
- type** (integer) - The type of data you're looking for.

METHOD GET

RETURNS The latest datum for the given devices

Sample JSON response

```
{
  "AA-AA-AAA-5":{
    "1":{
      "t":[
        1360618858970
      ],
      "1":[
        172.04
      ],
      "2":[
        -45.02
      ]
    }
  }
}
```

Upload

DESCRIPTION Uploads and stores a file in a resource

URL STRUCTURE `https://www.igtimi.com/api/v1/resource_data/upload`

PARAMETERS **file** (file) - The file to be uploaded.

start_time (millisecond unix timestamp) - The start time of the file.

end_time (millisecond unix timestamp) - The end time of the file.

resource_id (integer) - the id of the resource to add the file to.

HEADERS **Content-Type** - Provide the content type of the file

METHOD POST

RETURNS The resource_id, md5 hash and source of the inserted file

Sample JSON response

```
{
  "resource_datum":{
    "resource_id":1,
    "md5":"98330e72eeef4fcae7fa8b339ffc2c69",
    "source":null
  }
}
```

Sessions

Session value definitions

Field	Description
owner_id	The id of the user that created the session
session_group_id	The id of the group for the session
admin_session_group_id	The id of the admin group for the session
read	If true the user can request the session log data
modify	If true the user can update session details

List

DESCRIPTION Lists all the sessions a user has created and/or been shared.

URL STRUCTURE

https://www.igtimi.com/api/v1/sessions

METHOD GET

PARAMETERS **ids** (integer array) *optional* - If supplied it will filter the results by the given session ids.

RETURNS The user's sessions

Sample JSON response

```
{
  "sessions":[
    {
      "session":{
        "id":1,
        "name":"Example Session",
        "start_time":1362361340333.454,
        "end_time":1362361640335.23,
        "owner_id":2,
        "session_group_id":4,
        "admin_session_group_id":5,
        "permissions":{
          "read":true,
          "modify":true
        }
      }
    }
  ]
}
```

Create

DESCRIPTION Creates a new session and returns the id. To add start/end times, session name etc. use session logs.

URL STRUCTURE

https://www.igtimi.com/api/v1/sessions

METHOD POST

RETURNS The new session data

Sample JSON response

```
{
  "session":{
    "id":1,
    "name": null,
    "start_time": null,
    "end_time": null,
    "owner_id":2,
    "session_group_id":4,
    "admin_session_group_id":5,
    "permissions":{
      "read":true,
      "modify":true
    }
  }
}
```

Get

DESCRIPTION Gets a session.

URL STRUCTURE

https://www.igtimi.com/api/v1/sessions/:session_id

METHOD GET

RETURNS The requested session

Sample JSON response

```
{
  "session":{
    "id":1,
    "name":"Example Session",
    "start_time":1362361340333.454,
    "end_time":1362361640335.23,
    "owner_id":2,
    "session_group_id":4,
    "admin_session_group_id":5,
    "permissions":{
      "read":true,
      "modify":true
    }
  }
}
```

ERRORS 401 - The user does not have modify permission on the session.

Delete

DESCRIPTION Deletes a session.

URL STRUCTURE

```
https://www.igtimi.com/api/v1/sessions/:session_id
```

METHOD DELETE

RETURNS True on success

Sample JSON response

```
{
  "success": true
}
```

ERRORS 401 - The user does not have modify permission on the session.

Session Logs

List

DESCRIPTION Lists the logs for a session.

URL STRUCTURE

```
https://www.igtimi.com/api/v1/sessions/:session_id/logs
```

METHOD GET

PARAMETERS **start_time** (millisecond unix timestamp) *optional* - Get the logs created since a given date/time.

RETURNS The session logs in XML format. See the Understanding Session Logs (/developers/session_log_doc) guide for more information.

Create

DESCRIPTION Adds session logs to a session.

URL STRUCTURE

```
https://www.igtimi.com/api/v1/sessions/:session_id/logs
```

METHOD	POST
REQUEST BODY	XML document with the session logs additons. See Understand Session Logs (/developers/session_log_doc) for a detailed explanation
RETURNS	True on success
Sample JSON response	
<pre>{ "success": true }</pre>	
ERROR	403 - The session logs were not in the right format. An error message is returned in the body explaining why.

Devices

List

DESCRIPTION	Lists the devices for a user
URL STRUCTURE	<pre>https://www.igtimi.com/api/v1/devices</pre>
METHOD	GET
PARAMETERS	serial_numbers (string array) <i>optional</i> - If supplied it will filter the results by the given serial numbers. You can give a serial number the user doesn't have permissions on to get the public information.
RETURNS	A list of devices
Sample JSON response	
<pre>{ "devices":[{ "device":{ "id":1, "name":"my device", "serial_number":"AA-AA-AAAA", "service_tag":"abcdef", "owner_id":4, "device_user_group_id":4, "admin_device_user_group_id": 3, "permissions":{ "read":true, "modify":true } } }] }</pre>	

Register

DESCRIPTION	Register a device to the user
URL STRUCTURE	<pre>https://www.igtimi.com/api/v1/devices/register</pre>
METHOD	POST
RETURNS	The device
Sample JSON response	

```
{
  "device":{
    "id":1,
    "name":"my_device",
    "serial_number":"AAAA-AA-AA",
    "service_tag":"ABCDEF",
    "permissions":{
      "read":true,
      "modify":true
    }
  }
}
```

Unregister

DESCRIPTION Unregister's a device from the user

URL STRUCTURE `https://www.igtimi.com/api/v1/devices/:serial_number/unregister`

METHOD DELETE

RETURNS Success

Sample JSON response

```
{
  "success":true
}
```

Update

DESCRIPTION Updates a device

URL STRUCTURE `https://www.igtimi.com/api/v1/devices/:serial_number`

METHOD PUT

PARAMETERS **name** (string) - New name for device.

RETURNS Success

Sample JSON response

```
{
  "success":true
}
```

Data Access Windows

List

DESCRIPTION Lists the data access windows

URL STRUCTURE `https://www.igtimi.com/api/v1/devices/data_access_windows`

METHOD GET

PARAMETERS **type** (read or modify) - The type of data access window you want to get.

start_time (millisecond unix timestamp) *optional* - Filters results to be data access windows after this time.

end_time (millisecond unix timestamp) *optional* - Filters results to be data access windows before this time.

RETURNS A list of data access windows

Sample JSON response

```
{
  "data_access_windows": [
    {
      "data_access_window": {
        "start_time": 1361756171928.4912,
        "end_time": 4517429771979.67,
        "device_serial_number": "AA-AA-AAAA",
        "permissions": {
          "read": true,
          "modify": true
        }
      }
    }
  ]
}
```

Create

DESCRIPTION Creates a data access window

URL STRUCTURE `https://www.igtimi.com/api/v1/devices/:serial_number/data_access_window`

METHOD POST

PARAMETERS **start_time** (millisecond unix timestamp) - Start time of the data access window.
end_time (millisecond unix timestamp) - End time of the data access window.
user_id (integer) - Id of the user to create the data access window for.
read (boolean) - Give read permission.
modify (boolean) - Give modify permission.

RETURNS Success

Sample JSON response

```
{
  "success": true
}
```

Groups

List

DESCRIPTION Lists the groups the user is in.

URL STRUCTURE `https://www.igtimi.com/api/v1/groups`

METHOD GET

RETURNS The groups the user is in.

Sample JSON response

```
{
  "groups":[
    {
      "group":{
        "id":3,
        "name":"_members",
        "hidden":true,
        "permissions":{
          "read":true,
          "modify":false
        }
      }
    },
    {
      "group":{
        "id":2,
        "name":"_public",
        "hidden":true,
        "permissions":{
          "read":true,
          "modify":false
        }
      }
    },
    {
      "group":{
        "id":4,
        "name":"test",
        "hidden":false,
        "permissions":{
          "read":true,
          "modify":true
        }
      }
    }
  ]
}
```

Create

DESCRIPTION Creates a group of users.

URL STRUCTURE `https://www.igtimi.com/api/v1/groups`

METHOD POST

PARAMETERS **name** (string) - Name of the group.

RETURNS The group details.

Sample JSON response

```
{
  "group":{
    "name":"my_group",
    "id":4
  }
}
```

ERRORS 401 - The user does not have modify permission on the device.

Delete

DESCRIPTION Deletes a group. You must have modify permissions on the group to delete it.

URL STRUCTURE

```
https://www.igtimi.com/api/v1/groups/:group_id
```

METHOD DELETE**RETURNS** Success**Sample JSON response**

```
{
  "success":true
}
```

ERRORS 401 - The user does not have modify permission on the group.

Group Members

List

DESCRIPTION Lists the users in the group**URL STRUCTURE**

```
https://www.igtimi.com/api/v1/groups/:group_id/members
```

METHOD GET**RETURNS** Success**Sample JSON response**

```
{
  "members":[
    {
      "user":{
        "id":1,
        "first_name":"Bob",
        "surname":"Smith",
        "email":"bob@example.com"
      }
    },
    {
      "public": true
    }
  ]
}
```

ERRORS 401 - The user does not have read permission on the group.

Add User

DESCRIPTION Adds a member to a group**URL STRUCTURE**

```
https://www.igtimi.com/api/v1/groups/:group_id/members
```

METHOD POST**RETURNS** Success**Sample JSON response**

```
{
  "success":true
}
```

ERRORS 401 - The user does not have modify permission on the group.

Remove User

DESCRIPTION Removes a user from the group

URL STRUCTURE `https://www.igtimi.com/api/v1/groups/:group_id/members`

METHOD DELETE

RETURNS Success

Sample JSON response

```
{
  "success":true
}
```

ERRORS 401 - The user does not have modify permission on the group.

Make Public

DESCRIPTION Makes the group public

URL STRUCTURE `https://www.igtimi.com/api/v1/groups/:group_id/make_public`

METHOD POST

RETURNS Success

Sample JSON response

```
{
  "success":true
}
```

ERRORS 401 - The user does not have modify permission on the group.

Make Private

DESCRIPTION Makes the group private

URL STRUCTURE `https://www.igtimi.com/api/v1/groups/:group_id/make_private`

METHOD POST

RETURNS Success

Sample JSON response

```
{
  "success":true
}
```

ERRORS 401 - The user does not have modify permission on the group.