

1. Start tracking.

This service allows the user to start the tracking for a race.

URL	http://em.event.tractrac.com/start_tracking
Accepted methods	POST
Attended	Inmediatelly
Parameters	
eventid	Event UUID
raceid	Race UUID
username	E-mail used to access to the Event Manager.
password	Password used to access to the Event Manager.
tracking_start_time	Unix Timestamp in UTC Timezone with the desired tracking start time. This parameter is optional. In case it's not defined the server will use the reception time as the new tracking start time.

1.1. Examples

1.1.1. Request

```
curl --data "eventid=fdb7b130-da1e-0133-eb12-3c970ecf283a&raceid=fc14c280-da1f-0133-eb4f-3c970ecf283a&username=user@domain.com&password=****&tracking_start_time=1461229625000" "http://em.event.tractrac.com/start_tracking"
```

1.1.2. Resonse

```
{
  "status": "DONE",
  "message" : "Tracking started"
}
```

2. End tracking.

This service allows the user to stop the tracking for a race. The request will be queued. It will not be applied until an operator authorizes it.

URL	http://em.event.tractrac.com/end_tracking
Accepted methods	POST
Attended	Requires that the administrator confirms the request in the dashboard.
Parameters	
eventid	Event UUID
raceid	Race UUID
username	E-mail used to access to the Event Manager.
password	Password used to access to the Event Manager.
tracking_end_time	Unix Timestamp in UTC Timezone with the desited tracking end time. This parameter is optinal. In case it's not defined the server will use the reception time as the new tracking start time.

2.1. Examples.

2.1.1. Request

```
curl --data "eventid=fdb7b130-da1e-0133-eb12-3c970ecf283a&raceid=fc14c280-da1f-0133-eb4f-3c970ecf283a&username=user@domain.com&password=*****&tracking_end_time=1461229625000" "http://em.event.tractrac.com/end_tracking"
```

2.1.2. Response

```
{
  "status": "DONE",
  "message" : "Request stored"
}
```

3. Set race start time.

This service sets the race start time for a race.

URL	http://em.event.tractrac.com/update_race_start_time
Accepted methods	GET
Attended	Immediately
Parameters	
eventid	Event UUID
raceid	Race UUID
username	E-mail used to access to the Event Manager.
password	Password used to access to the Event Manager.
race_start_time	Unix timestamp in UTC time zone.

3.1. Examples.

3.1.1. Request.

```
curl "http://em.event.tractrac.com/update_race_start_time?eventid=fdb7b130-da1e-0133-eb12-3c970ecf283a&raceid=fc14c280-da1f-0133-eb4f-3c970ecf283a&race_start_time=1461230915000&username=user@domain.com&password=*****"
```

3.1.2. Response.

```
{
  "status": "DONE",
  "message" : "Race start time changed successfully to 1461230915000"
}
```

4. Reset race start time.

Postpones the given race.

URL	http://em.event.tractrac.com/resetStartTime
Accepted methods	GET
Attended	Inmediatelly
Parameters	
eventid	Event UUID
raceid	Race UUID
username	E-mail used to access to the Event Manager.
password	Password used to access to the Event Manager.

4.1. Examples.

4.1.1. Request.

```
curl "http://em.event.tractrac.com/resetStartTime?eventid=fdb7b130-da1e-0133-eb12-3c970ecf283a&raceid=fc14c280-da1f-0133-eb4f-3c970ecf283a&race_start_time=1461230915000&username=user@domain.com&password=*****"
```

4.1.2. Response.

```
{
  "status": "DONE",
  "message" : "Reset the race start time"
}
```

5. Abandon race.

Abandons a race. The race will be left uninitialized. All mark passing stored before the request_timestamp will be deleted too. The system validates that the difference between when the event was generated at the client side and when we received it is less than 5 minutes. Otherwise the event will be discarded.

This validity threshold is a parameter that is set in the event manager during the event setup.

URL	http://em.event.tractrac.com/abandon_race
Accepted methods	GET
Attended	Requires that the administrator confirms the request in the dashboard.
Parameters	
eventid	Event UUID
raceid	Race UUID
request_timestamp	Client timestamp. If not sent or sent empty the default is the current timestamp.
username	E-mail used to access to the Event Manager.
password	Password used to access to the Event Manager.

5.1. Examples

5.1.1. Request

```
curl "http://em.event.tractrac.com/abandon_race?eventid=fdb7b130-da1e-0133-eb12-3c970ecf283a&raceid=fc14c280-da1f-0133-eb4f-3c970ecf283a&request_timestamp=1462179854324&username=user@domain.com&password=**  
**"
```

5.1.2. Response

```
{  
  "status": "DONE",  
  "message" : "Request stored"  
}
```

5.1.3. Response when request is rejected because of late delivery.

```
{  
  "status": "FAILURE",  
  "message" : "The event time validity threshold for this request has expired and thus will be discarded."  
}
```

6. Update race status.

Allows the user to change the status of a race.

URL	http://em.event.tracrac.com/update_race_status
Accepted methods	GET
Attended	Depends on the target status.
Parameters	
eventid	Event UUID
raceid	Race UUID
username	E-mail used to access to the Event Manager.
password	Password used to access to the Event Manager.
race_status	Values accepted: • ABANDONED or ABORTED: It will abandon the race. This action needs to be confirmed by an operator. • POSTPONED or RESET: It will clear the race start time. This action will happen immediately.
request_timestamp	Client timestamp. If not sent or sent empty the default is the current timestamp. Only required for status ABANDONED or ABORTED.

6.1. Examples.

6.1.1. Request

```
curl "http://em.event.tracrac.com/update_race_status?eventid=fdb7b130-da1e-0133-eb12-3c970ecf283a&raceid=fc14c280-da1f-0133-eb4f-3c970ecf283a&username=user@domain.com&password=****&race_status=RESET"
```

6.1.2. Response

```
{
  "status": "DONE",
  "message" : "The status of the race has been changed successfully to RESET"
}
```

7. Course update.

URL	http://em.event.tractrac.com/update_course
Accepted methods	POST
Attended	Requires that the administrator confirms the request in the dashboard.
Parameters	
eventid	Event UUID
raceid	Race UUID
username	E-mail used to access to the Event Manager.
password	Password used to access to the Event Manager.
raw_post_date	JSON that contains the details of the new course.

7.1. Examples.

7.1.1. Request.

```
curl -X POST \
  -d eventid=fdb7b130-da1e-0133-eb12-3c970ecf283a \
  -d raceid=fc14c280-da1f-0133-eb4f-3c970ecf283a \
  -d username=user@domain.com \
  -d password=**** \
  -d raw_post_data='{ "course": { "name": "CourseTemplate", "waypoints":
[ { "name": "S", "passingSide": "STARBOARD", "controlPoint":
{ "@class": "Mark", "name": "wales", "id": "6b6b8900-da1f-0133-eb3e-
3c970ecf283a", "type": "BUOY" } } ] } }' \
http://em.event.tractrac.com/update\_course
```

7.1.2. Response

```
{
  "status": "DONE",
  "message": "File parsed successfully"
}
```