## An Assessment of Annual Load Estimation Methods in Small Watersheds for Cross Site Comparisons

**Nicholas J Gubbins<sup>1</sup>**, Weston M Slaughter<sup>2</sup>, Michael J. Vlah<sup>2</sup>, Spencer Rhea<sup>2</sup>, Emily S Bernhardt<sup>2</sup>, Matthew RV Ross<sup>1</sup>

<sup>1</sup>Colorado State University, Fort Collins, CO; <sup>2</sup>Duke University, Durham, North Carolina


**Near Daily-Weekly** 



Annual load is the amount of some solute of interest that moves past a point in a stream. It is calculated from discharge (Q) and solute concentration (C) data.


$$L = \int C(t)Q(t)dt$$

Solutes are sampled at varying intervals, both within sites as technology advances and between sites as research questions and funding differ. How frequently we sample informs our C:Q knowledge for the solute at the site.



To estimate annual load, researchers must fill in gaps using one of a variety of methods. All methods introduce error to load estimation. Selecting the most appropriate method is mostly dependent on the sampling frequency, C:Q relationship of the solute and the autocorrelation of samples through time.

Q (Lps)



## **Funding and Acknowledgments**

Q (Lps)

This work was funded by NSF Grant #1926420. Thanks to Hubbard Brook Experimental Forest for sensor data.

## **Works Cited**

Appling et al, 2015, "Reducing bias and quantifying uncertainty in watershed flux estimates: The R package loadflex"

Aulenbach et al, 2016, "Approaches to stream solute load estimation for solutes with varying dynamics from five diverse small watersheds".

Nava et al, 2019, "An R package for estimating river compound load using different methods"

Load estimates are greatly improved with high frequency sampling, complete C:Q knowledge, and proper method selection. Solutes with low variability can estimated accurately with sparse data, but dynamic solutes require more frequent monitoring or effective modeling to accurately estimate.

