

Table 1.--~~Discharge~~ characteristics of selected springs and spring-fed streams

Measurement site number	Classi- fication	Elevation of measurement site (feet)	Median measured discharge (gpm)	P. ₁₀ (gpm)	P. ₉₀ (gpm)	Ratio $\frac{P_{10}}{P_{90}}$
1	2	3	4	5	6	7
2	Spring	2,700	5.4	17	1.2	14
18	do	1,900	7.2	10	3.2	3
*20 & 21	do	1,700	7.2	13	3.7	3.5
28	do	1,250	12	37	3.3	11
31	do	425	39	94	28	3.5
33	Stream	500	33	64	15	4
35	Spring	800	54	158	25	6
36	do	600	3.2	15	1.3	12
49	Stream	425	4.9	28	.51	55
50	do	520	425	1,410	149	9.5
59	do	1,100	58	331	1.0	331
61	do	190	31	90	7.6	12
65	do	800	162	830	21	40
70	Spring	100	94	630	2.7	233
85	Stream	400	111	260	42	6
93	Spring	2,320	6.7	15	3.1	5
94	do	2,350	1.4	2.7	.6	4.5
100	do	2,025	3.8	34	.32	106
106a	do	1,100	.75	2.5	.29	8.5
110a	Stream	950	28	176	4.5	39
122	do	1,600	6.7	45	1.1	41
132	Spring	1,250	2.6	10	.43	23
136	do	970	1.5	6.4	.36	18
140	do	1,150	47	262	6.2	42
142	do	980	.15	.41	.001	410
143	Stream	2,200	45	130	17	7.5
147	Spring	1,750	.85	1.25	.40	3
153	do	1,150	.56	2.0	.044	45

* Combined

Note.-P.₁₀ refers to measured discharge that is equalled or exceeded 10 percent of the time.

P.₉₀ refers to measured discharge that is equalled or exceeded 90 percent of the time.

Sheet _____ of _____ Sheets

Table 2.—Monthly and annual precipitation, in inches, at Santa Barbara, Calif.

[illegible]