# Package compilation

### Emmanuelle Comets

02/02/2021

#### Mail Romain 11

# Compilation

- structure
  - tests: removed all other folders and files except testthat from the package otherwise warnings about RDS files
  - data: removed remifentanil example from data folder
- roxygen documentation
  - warnings for ggplot (no visible global function definition)
  - added import command for pnorm (found in distribution plot) and median (found nowhere, so suspect it's the name median used in the ggplot plots, but added it all the same)
- package size: still 5.9 Mb so much too large for CRAN
  - the 3 simulated data files for warfarin and viral load data are all around 5Mb, consider making them available only on bookdown/website
- necessary files
  - added a DESCRIPTION file
  - added a CHANGES file
- for compilation:
  - removed NAMESPACE
  - removed man pages
- Compilation steps from Build menu
  - Document => create NAMESPACE, DESCRIPTION (update collate directive), create man pages
  - Check => update documentation, create NAMESPACE

```
setwd(file.path(workDir,"npde"))
system("rm man/*")
roxygenise()
```

```
## Loading npde

## Writing NAMESPACE

## Writing NpdeSimData-class.Rd

## Writing extract-methods.Rd

## Writing NpdeData-class.Rd

## Writing read.Rd

## Writing show.Rd

## Writing npdeData.Rd

## Writing npdeSimData.Rd

## Writing print.NpdeData.Rd

## Writing showall.Rd

## Writing summary.NpdeData.Rd
```

```
## Writing subset.NpdeData.Rd
## Writing NpdeRes-class.Rd
## Writing kurtosis.Rd
## Writing skewness.Rd
## Writing gof.test.Rd
## Writing NpdeObject-class.Rd
## Writing dist.pred.sim.Rd
## Writing computenpde.Rd
## Writing npde.decorr.method.Rd
## Writing computepd.Rd
## Writing compute.ploq.Rd
## Writing autonpde.Rd
## Writing pdemenu.Rd
## Writing npde.main.Rd
## Writing npde.save.Rd
## Writing npde.graphs.Rd
## Writing npde-package.Rd
## Writing theopp.Rd
## Writing simtheopp.Rd
## Writing warfarin.Rd
## Writing virload.Rd
## Writing npde.cens.method.Rd
## Writing npdeControl.Rd
## Writing set.plotoptions.Rd
## Writing replace.plotoptions.Rd
## Writing npde.binning.Rd
## Writing npde.plot.covariate.Rd
## Writing npde.plot.dist.Rd
## Writing npde.plot.loq.Rd
## Writing plot.NpdeData.Rd
## Writing plot.NpdeRes.Rd
## Writing plot.NpdeObject.Rd
## Writing npde.plot.select.Rd
## Writing default.npde.plots.Rd
## Writing npde.plot.covariates.Rd
## Writing npde.plot.npde.Rd
## Writing npde.plot.data.Rd
## Writing npde.plot.default.Rd
## Writing npde.plot.scatterplot.Rd
setwd(workDir)
system("R CMD build npde")
system("R CMD check --as-cran npde_3.0.tar.gz")
```

Apres correction, la compilation du package passe sans erreurs et avec 2 notes restantes.

### notes

- package size too large (recommended size less than 5Mb): reduce nb of simulations for warfarin ?
- $-\,$ ggplot variables (rien a faire pour ça)
- warnings corriges
  - jeux de donnees non documentes: removed remifentanil, added virload documentation (used to be a specific man page, reintegrated them into roxygen format in npde.R like warfarin)
  - duplicated alias: fixed!

#### Warnings

• ggplot warnings

Undefined global functions or variables:

```
geom_bar geom_boxplot geom_crossbar geom_line geom_point geom_ribbon
    ggplot ggtitle grid.arrange group grp guides labs lower name obs.inf
    obs.median obs.sup pinf.lower pinf.median pinf.upper pmid.lower
   pmid.median pmid.upper psup.lower psup.median psup.upper
    scale_fill_manual scale_x_continuous scale_x_log10 scale_y_continuous
    scale_y_log10 theme upper value x x1 x2 x_area_0.25 x_area_0.5
   x_area_0.975 xcent xlab y y1 y2 y_area_0.25 y_area_0.5 y_area_0.975
   ylab
  • Warnings in first compilation (solved)
W checking Rd metadata ...
  Rd files with duplicated alias 'aux.npdeplot.computepi':
     'npde.plot.default.Rd' 'npde.plot.scatterplot.Rd'
   Rd files with duplicated alias 'compute.bands':
     'npde.plot.default.Rd' 'npde.plot.scatterplot.Rd'
  Rd files with duplicated alias 'compute.bands.true':
     'npde.plot.default.Rd' 'npde.plot.scatterplot.Rd'
  Rd files with duplicated alias 'npde':
     'npde-package.Rd' 'npde.Rd'
  checking Rd line widths ...
  checking Rd cross-references ...
  checking for missing documentation entries (346ms)
  Undocumented code objects:
     'remifent' 'simremifent' 'simremifent_base' 'simvirload' 'virload'
     'virload20', 'virload50', 'virloadMDV20',
  Undocumented data sets:
     'remifent' 'simremifent' 'simremifent base' 'simvirload' 'virload'
     'virload20', 'virload50', 'virloadMDV20',
   All user-level objects in a package should have documentation entries.
  See chapter 'Writing R documentation files' in the 'Writing R
   Extensions' manual.
```

.x X2.5. X50. X97.5. Y0.025 Y0.025.1 Y0.5 Y0.5.1 Y0.975 Y0.975.1 aes annotation\_logticks category coord\_cartesian coord\_flip element\_blank element\_line element\_rect element\_text expand\_limits facet\_wrap

#### Bugs to sort

## plot.NpdeRes (dans plotNpde-methods.R)

- Romain TODO: la fonction devrait prendre un objet NpdeRes et pas un objet NpdeObject (NpdeRes n'a pas d'element data, c'est juste le slot res d'un element NpdeObject !!!)
  - il faut lui donner des defauts pour xlab, ylab (et la possiblite de passer outre en passant des arguments en ...)
  - normalement il doit y avoir l'equivalent de xobs dans le dataframe res de l'objet
  - pas sure qu'on ait not.miss mais dans ce cas le reconstruire (a tester +++)
  - il n'y a pas de liste plot.opt donc prendre des defauts dans set.default.options()
- faire un test that pour verifier que cette fonction marche par elle-meme (use test that for class to generate an object npdeData and plot it)

# $plot.NpdeData\ (dans\ plotNpde-methods.R)$

• Romain TODO: faire un test that pour veeifier que la fonction et les options passent (use test that for class to generate an object npdeData and plot it)