① R2 - Storage → traffic-inventory.csv → Tool

② Tool → Map → Asset layer → Traffic inventory
→ Regulatory
- stop
- Yield
etc.
→ Asset
(All the parent tab)

③ Tool → New tab called Sign Deficiency → Existing sign
(near to Traffic inventory tab)
(called same input function traffic-inventory.csv)

→

Different crash data type
Angle crash → Recommend signal
stop signs
(if no existing signal/ stop)

(tool has intersection item we can consider that)

→ we need to identify the intersection using OSM node/ any other API

→ Based on MUTCD signal (warrt 7) or stop criteria we can show candidate location based on timeframe (12 month or 36 month)

Scanned with CamScanner

→ Goal is to pro-actively identify the candidate location for signal / stop signs where no existing signal / stop signs are ~~not~~ present.

→ similar for street light - FHWA has day / Night crash ratio → Based on that if no street light present Recommend for street light.

→ Animal crash → if animal warning signs are absent → we can recommend.

→ school signs → Based on near to school zone → we if school signs absent → Based on crash we can recommend

→ For pedstrian crash → if crosswalk absent we can recom crosswalk or peds signs.

→ similar for Bicycle →

Scanned with CamScanner

④ Sign Deficiency tab →

Should have a openstreet map similar to Traffic inventory map where it will show candidate location for - Signal, Stop, Street light, crosswalk School signs, Bike, animal signs etc. with crash profile.

→ it will not show the existing signal, Stop, Street light, crosswalk, School signs, Bike, animal location

→ Similar to Traffic inventory - user can turn on/ off

→ consider speed lowering - if Posted speed signs ≥ 35 mph & speed related crash → Recommend for speed limit lowering (check guideline for crash & speed limit for speed management)

Scanned with CamScanner

(5) We have warrant tab for - signal, stop, street lighting, if a location is candidate navigate user to the warrant - signal / stop / light warrant tab for further investigation.

(6) In the footer - mention - Engineerig review & field observation needed. The tool only provides location where focus can be needed. This is not final engineerig deci.

(7) Think for reporting such as - PDF report. KML, CSV, geojason for the candidate location.

(8) the map center should be based on upload Data tab - user selected jurisdiction.

(9) Think like a world class developer & traffic Engineer

Scanned with CamScanner