

1 Open the recording

Identify the platform from the folder path.
Estimate duration: frame count / FPS.
Start the first segment at time zero.

2 Read and prepare one frame

Decode with OpenCV; resize to 960 pixels high, keeping the aspect ratio.
Bright-pixel mask $\rightarrow$ grayscale $\rightarrow$ close small gaps in the shapes
Cleanup runs separately for each detector; Instagram also fills and filters contours.

3 Locate interface cues and test for a cut

Use the rows for the recording's platform.

Platform / check

Find the visual evidence

A cut requires BOTH conditions

Instagram: icons

First check

Match heart, comment and share templates.
Normalized score ≥ 0.85 ; first match with $x > 360$ px.

Any icon passes its vertical-position rule
AND more than **0.4 s** since the last cut.

Instagram: layout

Second check

Find wide, four-corner contours
in the cleaned feed layout.

The contour passes position and size limits
AND more than **1 s** since the last cut.

TikTok: icons

Match heart, share and save templates.
Normalized score ≥ 0.85 ; first match with $x > 360$ px.

Any icon passes its own position rule
AND more than **0.4 s** since the last cut.

Instagram runs both checks in order. Each accepted cut immediately updates their shared segment start.

No rule passes

Keep scanning

Keep the current segment start unchanged.
Read the next frame and repeat the checks.

A rule passes

4 Export the accepted segment

FFmpeg cuts the original recording from the segment start to this cut time.
Save the next numbered MP4 with video and audio; move the segment start to this cut.
Finish this frame's remaining checks, then read the next frame.

5 Finish: when frame reading ends, export the remaining interval to the estimated recording duration.

Icon rules use positions in the current frame. The output is candidate feed-item clips for review.