Maps between zoo models

Simon Frost

Table of contents

1 Overview 1

2 Forgetting what a model only records 2

3 A management model and its base model 3

4 Percolation inside a viral front 4

5 Quotients of models with callbacks 4

6 A short run can hide a dependence 5

7 What a quotient cannot express 6

8 Summary 7

References 7

1 Overview

The vignette on maps between models used small examples written for the purpose. This one tries the same ideas on the published models of EcologicalCellularAutomata, where the rules were written for other reasons and much of the dynamics lives outside them. Several relations turn out to hold exactly, and the attempt shows what a map of models cannot see.

A map of models compares rules, but a zoo problem is more than its rule: it may have covariates, kernel fields and callbacks acting on the whole lattice. So there are two checks. `is_model_map(f)` tests the rules on local configurations. `is_model_map(f, prob)` runs both models on one problem and compares every saved state exactly, and is the only one that sees the rest. Its `true` holds for that problem.

This is a research extension, beyond the papers the package implements. The package does not depend on the zoo; only this vignette loads it.

```
ENV["GKSwstype"] = "100"
using CategoricalCellularAutomata
using EcologicalCellularAutomata
using CellularAutomataCore: CellularAutomataCore, CAProblem, solve, remake, Torus
using Catlab: codom
using Plots
```

2 Forgetting what a model only records


The *Tuta absoluta* model follows the leafminer's spread across Asia on monthly climate data (Guimapi et al. 2020). Each land cell is susceptible, exposed or invaded, and two more layers record the months it was first reached and invaded. `forget_layers` builds the model without them from the same rule, so no second copy of the rule can drift from the first. Whether the result is a map is a real question, answered here by running 300 months over the real climate:

```
tuta = build(:tuta_absoluta_asia)
plain_tuta = forget_layers(tuta, :reached, :invaded)
tprob = problem(:tuta_absoluta_asia)
(codomain=codom(plain_tuta).name, months=tprob.tspan[2],
 is_model_map=is_model_map(plain_tuta, tprob),
 land_can_be_forgotten=is_model_map(forget_layers(tuta, :land), tprob))
```

```
(codomain = :tuta_absoluta_asia_without_reached_invaded, months = 300, is_model_map
= true, land_can_be_forgotten = false)
```

The records add nothing to the dynamics, only a history that the smaller model cannot give: the figure sets the month each cell was reached beside the stage that the smaller model holds at the end. Forgetting `land` instead is not a map, since the rule reads it.

```
u = solve(tprob).u[end]
small = pushforward(plain_tuta, u)
northup(a) = reverse(a; dims=1)
plot(heatmap(northup(map(x -> x < 0 ? NaN : Float64(x), u.reached)); c=:viridis,
             title="full model: month first reached", titlefontsize=10),
     heatmap(northup(map((s, l) -> l ? Float64(s) : NaN, small.state, small.land));
             c=:viridis, colorbar=false, clims=(0, 2),
             title="without the records, month 300: purple S, green E, yellow I",
             titlefontsize=10);
     layout=(1, 2), size=(900, 300), ticks=false, framestyle=:box)
```



3 A management model and its base model

The management model of the emerald ash borer (Mercader et al. 2011b) extends the base model (Mercader et al. 2011a) with two layers and three treatments. The two are separate pieces of code, each with its own rule and its own callback. With no treatment the management model should be the base model. Mapping a cell to the base model's layers states that exactly. The parameters map by name, which is the default.

The base model has a callback of its own, and each callback belongs to its own model, so the map does not carry one across. `callback=` names the codomain's:

```
management, base = build(:eab_management), build(:emerald_ash_borer)
layers = Tuple(s.name for s in base.states)
reduce_to_base = ModelMap(management, base, c -> NamedTuple{layers}(c))
map((:none, :girdling, :insecticide, :ash_reduction)) do treatment
    prob = problem(:eab_management; n=60, years=12, treatment)
    (; treatment, is_map=is_model_map(reduce_to_base, prob;
callback=eab_callback()))
end
```

```
((treatment = :none, is_map = true), (treatment = :girdling, is_map = false),
(treatment = :insecticide, is_map = false), (treatment = :ash_reduction, is_map =
false))
```

Without treatment the two programs agree exactly at every saved state of a twelve-year spread, including a callback that disperses beetles across the whole landscape. Each treatment breaks the map, as it should.

The stress bias shows why the two checks differ. It changes only how beetles disperse, in the callback, and the rule never reads it. The local check, given cell states from a real run, sees nothing wrong, and only running the problem exposes the difference:

```
biased = problem(:eab_management; n=60, years=12, stress_bias=true)
seen = solve(biased).u
all_layers = keys(seen[1])
cells = unique(reduce(vcat,
                      [vec(map((xs...) -> NamedTuple{all_layers}(xs), values(u)...))
                       for u in seen]))
(cell_states=length(cells),
 rules_commute=is_model_map(reduce_to_base; cells, p=biased.p, samples=5000),
 the_run_commutes=is_model_map(reduce_to_base, biased; callback=eab_callback()))
```

```
(cell_states = 36919, rules_commute = true, the_run_commutes = false)
```

4 Percolation inside a viral front

The multicomponent Domany–Kinzel model of a viral front (Capitán et al. 2011) gives each cell a replicative ability `r` in `0:R`. Its documentation says that without mutation, and with every cell at `R`, it is directed bond percolation. As a map, that claim has content: `r ↦ R r` sends the model with `R = 1` into the model with `R`, provided that the resistance is rescaled. A cell with `n` offspring resists with probability `π^n`, and multiplying abilities by `R` multiplies `n` by `R`, so `π` must become `π^(1/R)`. The parameter map does the work:

```
map((2, 3, 6)) do R
    bond, front = build_domany_kinzel_viral(; R=1), build_domany_kinzel_viral(; R)
    embed = ModelMap(bond, front, r -> Int8(R * r);
                     parameters=p -> (π=p.π^(1 / R), p=0.0, q=0.0))
    still = (π=0.3, p=0.0, q=0.0)
    prob = CAProblem(bond, (; r=Int8(1)), 400, still; space=Torus(500), seed=3)
    (; R, without_mutation=is_model_map(embed; p=still, contexts=2000, dims=1),
     with_mutation=is_model_map(embed; p=(π=0.3, p=0.2, q=0.0), contexts=2000,
dims=1),
     a_run=is_model_map(embed, prob))
end
```

```
((R = 2, without_mutation = true, with_mutation = false, a_run = true), (R = 3,
without_mutation = true, with_mutation = false, a_run = true), (R = 6,
without_mutation = true, with_mutation = false, a_run = true))
```

These are checks of the random numbers at 2000 contexts and over one run, not a proof. The proof is the algebra above, up to rounding: `π^n` and `(π^(1/R))^(R n)` can differ in their last bits, so a draw could in principle fall between them, though that has a chance of order `10^-16` per draw.

5 Quotients of models with callbacks

Fourteen of the zoo's models do much of their work in callbacks: decisions on the whole lattice, dispersal, individuals acting one at a time. A callback reads the whole state, so forgetting a layer

needs a callback for the smaller state, and `callback=:lift` builds it. After each step the state is lifted, with the forgotten layer at its default, the original callback acts on the lifted state, and the result is mapped down. The Lean library proves the construction: it commutes exactly when the callback does not depend on what is forgotten, and it is then the only callback that does (`Lumping.liftCallback`, `Lumping.callback_unique`, `Lumping.runWith_quotient`). Whether that holds for a given model is what running it tells us:

```
function forgets(id, layer; kw=(;))
    return (model=id, layer, setting=join(("$k=$v" for (k, v) in pairs(kw) if k !=
    :n), ", "),
            is_map=is_model_map(forget_layers(build(id), layer), problem(id; kw...);
                                callback=:lift))
end
[forgets(:cassava_mealybug, :loss), forgets(:cassava_mealybug, :since),
 forgets(:potato_moth_farmers, :source), forgets(:potato_moth_farmers, :carriers),
 forgets(:western_x_orchard, :age), forgets(:western_x_orchard, :clock),
 forgets(:eab_management, :large; kw=(; n=40)),
 forgets(:eab_management, :large; kw=(; n=40, treatment=:girdling)),
 forgets(:eab_management, :phloem0; kw=(; n=40)),
 forgets(:eab_management, :phloem0; kw=(; n=40, stress_bias=true))]
```

```
10-element Vector{@NamedTuple{model::Symbol, layer::Symbol, setting::String,
is_map::Bool}}:
 (model = :cassava_mealybug, layer = :loss, setting = "", is_map = 1)
 (model = :cassava_mealybug, layer = :since, setting = "", is_map = 0)
 (model = :potato_moth_farmers, layer = :source, setting = "", is_map = 1)
 (model = :potato_moth_farmers, layer = :carriers, setting = "", is_map = 0)
 (model = :western_x_orchard, layer = :age, setting = "", is_map = 1)
 (model = :western_x_orchard, layer = :clock, setting = "", is_map = 0)
 (model = :eab_management, layer = :large, setting = "", is_map = 1)
 (model = :eab_management, layer = :large, setting = "treatment=girdling", is_map =
 0)
 (model = :eab_management, layer = :phloem0, setting = "", is_map = 1)
 (model = :eab_management, layer = :phloem0, setting = "stress_bias=true", is_map =
 0)
```

Each `true` has a reason in the model's code. The mealybug's `loss` is written by the rule and read only by a summary of the yield. The potato moth's `source`, the origin of a cell's moths, is the published counterpart of the lineage label in the previous vignette: it is copied from a neighbour or set when a farmer's team brings moths in, and it never decides anything. In the western X orchard, `age` sets yields and costs in the economic summary but not the epidemic. The ash borer's layers show that the answer belongs to the problem as well as the model: `large` matters once there is a treatment, and `phloem0` only under the stress bias.

6 A short run can hide a dependence

A `false` disproves a map, but a `true` holds only for the problem and the span that was run. The grapevine leafroll model has an `age` layer, and forgetting it looks harmless at first:

```
vine = problem(:grapevine_leafroll)
forget_age = forget_layers(build(:grapevine_leafroll), :age)
full = solve(vine)
down = solve(pushforward(forget_age, vine; callback=:lift))
(first_month_that_differs=full.t[findfirst(i -> pushforward(forget_age, full.u[i])
!=
                                                down.u[i], eachindex(full.u))],
 months=vine.tspan[2],
 is_map_over=map(T -> T ⇒ is_model_map(forget_age, remake(vine; tspan=(0, T));
                                       callback=:lift), (40, 60, 100, 600)))
```

```
(first_month_that_differs = 61, months = 600, is_map_over = (40 => true, 60 => true,
100 => false, 600 => false))
```

How long an exposed vine takes to become infective depends on whether it is younger than 60 months, and the lift makes every vine a new one, so the two runs agree until the first vines come of age. No run shorter than that could tell them apart.

7 What a quotient cannot express

Some layers matter within a step and not between steps. The ash borer's `larvae1` is written by the rule and read by the callback in the same step, and the next rule overwrites it without reading it, so what a saved state holds in that layer is never used. Even so, forgetting it is not a map of this kind:

```
forgets(:emerald_ash_borer, :larvae1; kw=(; n=41))
```

```
(model = :emerald_ash_borer, layer = :larvae1, setting = "", is_map = false)
```

The quotient maps down between the rule and the callback, so the larvae are gone before the callback can see them. A map here would have to treat the rule and the callback as one step, which `forget_layers` does not do.

Other limits:

- A layer that never leaves its default passes vacuously. `rogued` and `tested` in the grapevine model are like that at its default settings, which says nothing about the runs that use them.
- Block rules, such as the three-layer Bt crop model's, are not stepped cell by cell, and `quotient` refuses them.
- A callback may refuse to run on what is left. Forgetting `farmers` in the potato moth model raises the model's own error, and that is an answer too.
- The dune model with `speedup = 0` is not an example: it is one model at another parameter value, not a second model.

8 Summary

relation	check	result
Tuta forgetting its record layers	run, 300 months on real climate	a map
Tuta forgetting `land`	run	not a map
ash borer management, no treatment ? base model	run, with the base model's callback	a map
ash borer management, any treatment ? base model	run	not a map
ash borer management, stress bias ? base model	rules; run	rules commute, the run does not
viral front `R = 1` ? `R`, no mutation, `π ↦ π^(1/R)`	rules at 2000 contexts; run	a map
the same, with mutation	rules	not a map
mealybug without `loss`, potato moth without `source`, orchard without `age`	run, lifted callback	a map
grapevine without `age`	run, lifted callback	not a map, from month 61
ash borer without `larvae1`	run, lifted callback	not a map: read between rule and callback

References

Capitán, José A., José A. Cuesta, Susanna C. Manrubia, and Jacobo Aguirre. 2011. "Severe Hindrance of Viral Infection Propagation in Spatially Extended Hosts." *PLoS ONE* 6 (8): e23358. https://doi.org/10.1371/journal.pone.0023358.

Guimapi, Ritter A., Ramasamy Srinivasan, Henri E. Tonnang, Paola Sotelo-Cardona, and Samira A. Mohamed. 2020. "Exploring the Mechanisms of the Spatiotemporal Invasion of Tuta absoluta in Asia." *Agriculture* 10 (4): 124. https://doi.org/10.3390/agriculture10040124.

Mercader, Rodrigo J., Nathan W. Siegert, Andrew M. Liebhold, and Deborah G. McCullough. 2011a. "Influence of Foraging Behavior and Host Spatial Distribution on the Localized Spread of the Emerald Ash Borer, *Agrilus Planipennis*." *Population Ecology* 53 (2): 271–85. https://doi.org/10.1007/s10144-010-0233-6.

Mercader, Rodrigo J., Nathan W. Siegert, Andrew M. Liebhold, and Deborah G. McCullough. 2011b. "Simulating the Effectiveness of Three Potential Management Options to Slow the Spread of Emerald Ash Borer (*Agrilus Planipennis*) Populations in Localized Outlier Sites." *Canadian Journal of Forest Research* 41 (2): 254–64. https://doi.org/10.1139/X10-201.