Hybrid models with Ark.jl

Simon Frost

Table of contents

1 Overview 1

2 The crop 2

3 Aphids as entities 2

4 One entity per plant 4

5 Choosing a backend 7

1 Overview

Ark.jl is an entity component system (ECS): a `World` holds entities, each entity is a set of components (plain immutable structs), and the model's behaviour is written as functions ("systems") that loop over queries such as "every entity with an `Aphid` component". `ArkBackend` keeps the state of a cellular automaton in such a world, so that mobile agents written as entities can share it.

This vignette writes the aphid-borne virus of the previous vignette in ECS style, then uses the one-entity-per-cell mode to let a scouting system tag diseased plants with a component and rogue them later. It ends by comparing the cost of the agent backends.

```
ENV["GKSwstype"] = "100"
using CellularAutomataCore
using Ark
using Plots
using Random
using Statistics
```

2 The crop

The crop is the same cellular automaton as before: healthy (0), latent (1) and symptomatic (2) plants, with slow spread by root contact.

```
crop = LocalRule(VonNeumann(1)) do cell, nbrs, ctx
    if cell == 0
        k = count(==(2), nbrs)
        return bernoulli(ctx, 1 - (1 - ctx.p.ε)^k, 1) ? Int8(1) : Int8(0)
    elseif cell == 1
        return bernoulli(ctx, 1 / ctx.p.τ, 2) ? Int8(2) : Int8(1)
    end
    return cell
end

n = 80
u0 = zeros(Int8, n, n)
for (i, j) in ((20, 20), (60, 30), (40, 65))
    u0[i, j] = 2
end
p = (ε=0.02, τ=5, inoculation=0.4, acquisition=0.6, loss=0.1, flight=3,
     emigration=0.03, immigrants=40)
prob = CAProblem(crop, u0, 90, p; seed=1)
```

```
CAProblem(LocalRule(<anonymous function>, VonNeumann(1)) on Torus((80, 80)),
tspan=(0, 90))
```

3 Aphids as entities

An aphid is an entity with one component, holding its position and whether it carries the virus. Components are immutable, so a system that changes an aphid writes a new component in its place.

```
struct Aphid
    pos::NTuple{2,Int}
    viruliferous::Bool
end
```

The behaviour is three systems. A flight lands on one of the cells exactly `flight` cells away (in the maximum norm), as Agents.jl's `randomwalk!` does on a grid, so this is the model of the previous vignette. The world holds a `Xoshiro` random number generator as a resource, seeded from the problem's seed, and the systems reach the crop through `read_cell(world, pos)` and `write_cell!(world, pos, value)`. Entities cannot be removed while a query over them is running, so emigrants are collected first and removed afterwards.

```
function arrive!(world, k)
    rng = get_resource(world, Xoshiro)
    for _ in 1:k
        new_entity!(world, (Aphid((rand(rng, 1:n), rand(rng, 1:n)), false),))
    end
end

function emigrate!(world, p)
    rng = get_resource(world, Xoshiro)
    leaving = Entity[]
    for (es, aphids) in Query(world, (Aphid,))
        for i in eachindex(es)
            rand(rng) < p.emigration && push!(leaving, es[i])
        end
    end
    foreach(e -> remove_entity!(world, e), leaving)
end

function fly_and_probe!(world, p)
    rng = get_resource(world, Xoshiro)
    f = p.flight
    ring = [(dx, dy) for dx in -f:f for dy in -f:f if max(abs(dx), abs(dy)) == f]
    for (es, aphids) in Query(world, (Aphid,))
        for i in eachindex(es)
            a = aphids[i]
            pos = mod1.(a.pos .+ rand(rng, ring), (n, n))
            plant = read_cell(world, pos)
            if a.viruliferous && plant == 0 && rand(rng) < p.inoculation
                write_cell!(world, pos, 1)
            end
            carries = plant == 2 && rand(rng) < p.acquisition ? true :
                      rand(rng) < p.loss ? false : a.viruliferous
            aphids[i] = Aphid(pos, carries)
        end
    end
end


function aphids!(world, p, t)
    emigrate!(world, p)
    fly_and_probe!(world, p)
    arrive!(world, p.immigrants)
end
```

```
aphids! (generic function with 1 method)
```

`ArkBackend` takes the component types of the mobile agents (the world must know them when it is created), an `init!(world, p)` that creates the first aphids, and an `update!(world, p, t)` that runs after each sweep of the crop with the new time.

```
backend = ArkBackend(:grid; components=(Aphid,), init! =(w, p) -> arrive!(w, 1500),
                     update! =aphids!)
```

```
sol = solve(prob; backend, saveat=30)
plot([plot(sol; snapshot=i, c=[:palegreen, :orange, :darkred], clims=(0, 2),
           colorbar=false, title="day $(sol.t[i])") for i in eachindex(sol.t)]...;
     layout=(1, 4), size=(950, 270))
```



This is the same model as the Agents.jl version, but the two draw their random numbers in a different order (here all emigrants are chosen before any aphid flies), so they agree in distribution, not run by run. The fraction of plants infected at day 60, over 40 runs, can be compared with the untreated histogram of the previous vignette:

```
day60 = EnsembleProblem(remake(prob; tspan=(0, 60));
                        output_func=(s, ctx) -> (count(>(0), final_state(s)) / n^2,
false))
runs = solve(day60, Synchronous(), EnsembleThreads(); trajectories=40, backend,
             save_everystep=false)
(mean=mean(runs.u), sd=std(runs.u))
```

```
(mean = 0.320546875, sd = 0.07415514734260763)
```

`agent_model(integ)` returns the world, for callbacks or for inspection.

```
integ = init(prob; backend)
step!(integ, 30)
world = agent_model(integ)
carriers = count(a -> a.viruliferous,
                 (a for (es, aphids) in Query(world, (Aphid,)) for a in aphids))
(aphids=count_entities(Query(world, (Aphid,))), carriers=carriers)
```

```
(aphids = 1394, carriers = 80)
```

4 One entity per plant

With `ArkBackend(:cells)` every plant is an entity with a `CACell` component, which holds the plant's linear index and state. The run is the same as with the grid:

```
cellular = ArkBackend(:cells; components=(Aphid,), init! =(w, p) -> arrive!(w,
1500),
                      update! =aphids!)
solve(prob; backend=cellular, saveat=30).u == sol.u
```

```
true
```

Because plants are entities, systems can query them like any other entity and give them components of their own. Here a scout walks the field once a week, finds each symptomatic plant with probability one half and tags it with a `Flagged` component recording the day. Three days later a crew rogues every flagged plant, which becomes an empty cell (3) that neither infects nor can be infected. The rogue system writes the new state straight into the plant's `CACell` component, and the next sweep of the crop reads it from there. Components are added outside the query, as entities cannot change while one runs.

```
struct Flagged
    day::Int
end


function scout!(world, t)
    t % 7 == 0 || return
    rng = get_resource(world, Xoshiro)
    found = Entity[]
    for (es, plants) in Query(world, (CACell{Int8},); without=(Flagged,))
        for i in eachindex(es)
            plants[i].state == 2 && rand(rng) < 0.5 && push!(found, es[i])
        end
    end
    foreach(e -> add_components!(world, e, (Flagged(t),)), found)
end

function rogue!(world, t)
    for (es, plants, flags) in Query(world, (CACell{Int8}, Flagged))
        for i in eachindex(es)
            t - flags[i].day >= 3 && (plants[i] = CACell(plants[i].index, Int8(3)))
        end
    end
end


managed = ArkBackend(:cells; components=(Aphid, Flagged),
                     init! =(w, p) -> arrive!(w, 1500),
                     update! =(w, p, t) -> (aphids!(w, p, t); scout!(w, t);
rogue!(w, t)))
rogued = solve(prob; backend=managed, saveat=5)
```

```
CASolution with 19 saved states at t = 0:…:90, retcode Success (LocalRule(<anonymous
function>, VonNeumann(1)))
```

```
untreated = solve(prob; backend, saveat=5)
infected(s) = [count(∈((1, 2)), u) / n^2 for u in s.u]
removed(s) = [count(==(3), u) / n^2 for u in s.u]
plot(untreated.t, infected(untreated); label="infected, untreated", lw=2,
     xlabel="day", ylabel="fraction of plants", legend=:topleft)
plot!(rogued.t, infected(rogued); label="infected, scouted and rogued", lw=2)
plot!(rogued.t, removed(rogued); label="rogued", lw=2, ls=:dash)
```




```
plot(rogued; snapshot=length(rogued.t), c=[:palegreen, :orange, :darkred, :white],
     clims=(0, 3), colorbar=false, title="day 90, scouted and rogued", size=(400,
380))
```



At day 90:

```
healthy(s) = count(==(0), final_state(s)) / n^2
(untreated=(healthy=healthy(untreated), infected=infected(untreated)[end]),
 rogued=(healthy=healthy(rogued), infected=infected(rogued)[end],
         removed=removed(rogued)[end]))
```

```
(untreated = (healthy = 0.05359375, infected = 0.94640625), rogued = (healthy =
0.173125, infected = 0.236875, removed = 0.59))
```

Roguing keeps the infected plants left standing to about a quarter of the field, against nearly all of it untreated, but mostly by removing them: well over half the crop has been rogued, and at the end about one plant in six is healthy, against one in twenty untreated. With aphids flying in all season, the virus reaches healthy plants faster than weekly scouting can find the sick ones.

5 Choosing a backend

Without mobile agents every agent backend gives exactly the result of `ArrayBackend`, because they all sweep the same array engine. What differs is where the state is kept between steps, and so the overhead. Here are 50 steps of Life on a 200×200 torus:

```
using Agents: Agents
life = CAProblem(Life(), rand(Xoshiro(1), Int8[0, 1], 200, 200), 50)
backends = [ArrayBackend(), AgentsBackend(:grid), AgentsBackend(:cells),
            ArkBackend(:grid), ArkBackend(:cells)]
labels = ["ArrayBackend()", "AgentsBackend(:grid)", "AgentsBackend(:cells)",
          "ArkBackend(:grid)", "ArkBackend(:cells)"]
reference = final_state(solve(life; save_everystep=false))
all(b -> final_state(solve(life; backend=b, save_everystep=false)) == reference,
backends)
```

```
true
```

```
ms_per_step(b) = 1000 * minimum(@elapsed(solve(life; backend=b,
save_everystep=false))
                                for _ in 1:3) / 50
[label ⇒ round(ms_per_step(b); digits=3) for (label, b) in zip(labels, backends)]
```

```
5-element Vector{Pair{String, Float64}}:
        "ArrayBackend()" => 0.195
  "AgentsBackend(:grid)" => 0.185
 "AgentsBackend(:cells)" => 0.476
     "ArkBackend(:grid)" => 0.166
    "ArkBackend(:cells)" => 0.354
```

In `:grid` mode the agent backends cost nothing over `ArrayBackend`. In `:cells` mode each step also gathers the cells into an array and scatters them back, which for a rule as cheap as Life costs several times the sweep itself; for a rule that does more work per cell the difference shrinks. Use `:cells` when the cells themselves need to be agents or entities: to give them components, query them alongside other entities, or use Agents.jl's tools on them.