

Markov categories as a GATlab theory

Simon Frost

Table of contents

1	Overview	1
2	What is a Markov category?	2
3	Setup	2
4	Free expressions	4
5	FinStoch as a model	6
6	Evaluating expressions	6
7	The Markov axiom in FinStoch	7
8	Summary	8
9	References	8

1 Overview

`MarkovCategories.jl` states the operations on finite stochastic kernels of `FiniteKernels.jl` (whose “Finite stochastic kernels” vignette introduces them) as a GATlab *theory*, so that Catlab’s symbolic expressions, wiring diagrams and `@instance` mechanism apply to conditional probability tables ([Patterson et al. 2022](#)). This vignette shows the theory hierarchy, builds free (symbolic) string-diagram expressions, evaluates them in `FinStoch`, and checks the Markov axiom numerically.

2 What is a Markov category?

A Markov category ([Fritz 2020](#)), whose copy-discard fragment is the CD category of ([Cho and Jacobs 2019](#)), is a symmetric monoidal category $(\mathcal{C}, \otimes, I)$ in which every object X carries a commutative comonoid

$$\Delta_X : X \rightarrow X \otimes X, \quad !_X : X \rightarrow I,$$

compatible with the tensor product, and such that discarding is natural: $f \cdot !_Y = !_X$ for every morphism $f : X \rightarrow Y$. Morphisms are thought of as stochastic maps; Δ copies a value and $!$ forgets it. Copying is deliberately *not* required to be natural, because for a stochastic f , “sample once and copy” ($f \cdot \Delta_Y$) differs from “sample twice” ($\Delta_X \cdot (f \otimes f)$). A symmetric monoidal category in which both Δ and $!$ are natural is *cartesian* – this is Fox’s theorem ([Fox 1976](#)) – and there every morphism is deterministic. The same axioms are stated in Lean in Mathlib’s `CopyDiscardCategory` and `MarkovCategory` ([The mathlib Community 2020](#)), which the proofs/ development of `FiniteKernels.jl` follows.

`MarkovCategories.jl` expresses this hierarchy with GATlab theories, reusing Catlab’s monoidal-category theories so that Catlab’s expression and wiring-diagram tooling applies unchanged:

theory	adds
<code>ThSymmetricMonoidalCategory</code> (Catlab)	<code>otimes</code> , <code>munit</code> , <code>braid</code>
<code>ThCopyDiscardCategory</code> = <code>ThMonoidalCategoryWithDiagonals</code> (Catlab)	<code>mcop</code> y, <code>delete</code> and the comonoid and coherence axioms
<code>ThMarkovCategory</code> (this package)	naturality of <code>delete</code>
<code>ThCartesianCategory</code> (Catlab)	naturality of <code>mcop</code> y as well

3 Setup

```
using MarkovCategories
using Catlab
```

```
ThMarkovCategory
```

```
MarkovCategories.ThMarkovCategory
```

The theory carries all the axioms of its parents; the last one is the Markov axiom. (Source-location comments are dropped from the printout.)

```

for line in split(sprint(show, ThMarkovCategory.Meta.theory), '\n')
  occursin("#=", line) || println(line)
end

```

```

GAT(ThMarkovCategory):
  Ob::TYPE → []
  Hom(dom, codom)::TYPE → [dom::Ob, codom::Ob]
  compose(f, g)::Hom(a, c) → [a::Ob, b::Ob, c::Ob, f::Hom(a, b), g::Hom(b, c)]
  (assoc := compose(compose(f, g), h) == compose(f, compose(g, h))) → [a::Ob, b::Ob,
  c::Ob, d::Ob, f::Hom(a, b), g::Hom(b, c), h::Hom(c, d)]
  id(a)::Hom(a, a) → [a::Ob]
  (idl := compose(id(a), f) == f) → [a::Ob, b::Ob, f::Hom(a, b)]
  (idr := compose(f, id(b)) == f) → [a::Ob, b::Ob, f::Hom(a, b)]
  otimes(A, B)::Ob → [A::Ob, B::Ob]
  otimes(f, g)::Hom(otimes(A, C), otimes(B, D)) → [A::Ob, B::Ob, C::Ob, D::Ob,
  f::Hom(A, B), g::Hom(C, D)]
  munit():Ob → []
  (otimes(otimes(A, B), C) == otimes(A, otimes(B, C))) → [A::Ob, B::Ob, C::Ob]
  (otimes(munit(), A) == A) → [A::Ob]
  (otimes(A, munit()) == A) → [A::Ob]
  (otimes(otimes(f, g), h) == otimes(f, otimes(g, h))) → [A::Ob, B::Ob, C::Ob,
  X::Ob, Y::Ob, Z::Ob, f::Hom(A, X), g::Hom(B, Y), h::Hom(C, Z)]
  (otimes(id(munit()), f) == f) → [A::Ob, B::Ob, f::Hom(A, B)]
  (otimes(f, id(munit()))) == f → [A::Ob, B::Ob, f::Hom(A, B)]
  (compose(otimes(f, g), otimes(h, k)) == otimes(compose(f, h), compose(g, k))) →
  [A::Ob, B::Ob, C::Ob, X::Ob, Y::Ob, Z::Ob, f::Hom(A, B), h::Hom(B, C), g::Hom(X,
  Y), k::Hom(Y, Z)]
  (id(otimes(A, B)) == otimes(id(A), id(B))) → [A::Ob, B::Ob]
  braid(A, B)::Hom(otimes(A, B), otimes(B, A)) → [A::Ob, B::Ob]
  (compose(braid(A, B), braid(B, A)) == id(otimes(A, B))) → [A::Ob, B::Ob]
  (braid(A, otimes(B, C)) == compose(otimes(braid(A, B), id(C)), otimes(id(B),
  braid(A, C)))) → [A::Ob, B::Ob, C::Ob]
  (braid(otimes(A, B), C) == compose(otimes(id(A), braid(B, C)), otimes(braid(A, C),
  id(B)))) → [A::Ob, B::Ob, C::Ob]
  (braid(A, munit()) == id(A)) → [A::Ob]
  (braid(munit(), A) == id(A)) → [A::Ob]
  (compose(otimes(f, g), braid(B, D)) == compose(braid(A, C), otimes(g, f))) →
  [A::Ob, B::Ob, C::Ob, D::Ob, f::Hom(A, B), g::Hom(C, D)]
  mcopy(A)::Hom(A, otimes(A, A)) → [A::Ob]
  delete(A)::Hom(A, munit()) → [A::Ob]
  (compose(mcopy(A), otimes(mcopy(A), id(A))) == compose(mcopy(A), otimes(id(A),
  mcopy(A)))) → [A::Ob]
  (compose(mcopy(A), otimes(delete(A), id(A))) == id(A)) → [A::Ob]
  (compose(mcopy(A), otimes(id(A), delete(A))) == id(A)) → [A::Ob]
  (compose(mcopy(A), braid(A, A)) == mcopy(A)) → [A::Ob]
  (mcopy(otimes(A, B)) == compose(otimes(mcopy(A), mcopy(B)), otimes(otimes(id(A),
  braid(A, B)), id(B)))) → [A::Ob, B::Ob]
  (delete(otimes(A, B)) == otimes(delete(A), delete(B))) → [A::Ob, B::Ob]
  (mcopy(munit()) == id(munit())) → []
  (delete(munit()) == id(munit())) → []
  (compose(f, delete(B)) == delete(A)) → [A::Ob, B::Ob, f::Hom(A, B)]

```

4 Free expressions

`FreeMarkovCategory` is the symbolic model of `ThMarkovCategory`, built with Catlab's `@symbolic_model` in the same way as `FreeSymmetricMonoidalCategory`. Objects and generating morphisms are declared by name, and the operations build expressions with composition and tensor normalised to be strictly associative and unital.

```
X, Y, Z = Ob(FreeMarkovCategory, :X, :Y, :Z)
f = Hom(:f, X, Y)
g = Hom(:g, X, Z)
p = Hom(:p, munit(FreeMarkovCategory.Ob), X)
```

$$p : I \rightarrow X$$

A fan-out, in which one value of X feeds both f and g :

```
fanout = compose(mcopy(X), otimes(f, g))
```

$$\Delta_X \cdot (f \otimes g) : X \rightarrow Y \otimes Z$$

```
dom(fanout), codom(fanout)
```

```
(X, otimes(Y,Z))
```

Expressions have Unicode and LaTeX renderings:

```
show_unicode(fanout)
```

```
mcopy{X} \cdot (f \otimes g)
```

```
show_latex(fanout)
```

```
\Delta_{\{X\}} \cdot \left( f \otimes g \right)
```

Catlab can turn an expression into a wiring diagram (copies are drawn as a wire fanning out and deletions as a wire ending), and lay it out as TikZ or Graphviz:

```
wd = to_wiring_diagram(compose(p, fanout))
nboxes(wd), nwires(wd)
```

```
(3, 4)
```

```

using Catlab.Graphics
using Logging: NullLogger, with_logger
# Catlab warns that the optional Convex/SCS port layout is unavailable; the
# fixed layout is fine here.
tikz = with_logger(NullLogger()) do
    to_tikz(compose(p, fanout); labels=true)
end
lines = split(sprint(Catlab.Graphics.TikZ.pprint, tikz), '\n')
println(join(lines[1:min(end, 12)], '\n'), "\n...")

```


```

\usepackage{amssymb}
\usetikzlibrary{calc}
\usetikzlibrary{shapes.geometric}
\usetikzlibrary{decorations.markings}
\begin{tikzpicture}[unit
length/.code={{\newdimen\tikzunit}\setlength{\tikzunit}{#1}},unit length=4mm,x=\tikzunit,y=\tikzunit,semithick,box/.style={rectangle,draw,solid,rounded corners},junction/.style={circle,draw,fill,inner sep=0},outer box/.style={draw=none},wire/.style={draw,postaction={decorate},decoration={markings,mark=at position 0.5 with {#1}}}]
\node[outer box,minimum width=12.5\tikzunit,minimum height=7\tikzunit] (root) at (0,0) {};
\node[box,minimum size=2\tikzunit] (n1) at (-3.25,0) {$p$};
\node[junction,minimum size=0.5\tikzunit] (n2) at (0,0) {};
\node[box,minimum size=2\tikzunit] (n3) at (3.25,1.5) {$f$};
\node[box,minimum size=2\tikzunit] (n4) at (3.25,-1.5) {$g$};
\path[wire] (n2.-30) to[out=-30,in=-180] (n4.west);
\path[wire] (n2.30) to[out=30,in=-180] (n3.west);
...

```

The preceding block shows generated TikZ source. This cell renders the Graphviz drawing itself, rather than printing the graph object's type:

```
to_graphviz(wd; labels=true)
```



5 FinStoch as a model

The finite stochastic category is registered with `@instance ThMarkovCategory{FiniteSpace, FiniteKernel}`, so every operation in the theory hierarchy dispatches on spaces and kernels, including the operator aliases:

```
SX = FiniteSpace(:X, [:x0, :x1])
SY = FiniteSpace(:Y, [:y0, :y1, :y2])
SZ = FiniteSpace(:Z, [:z0, :z1])
k = cpt(factors(SX)[1], factors(SY)[1], [0.7 0.2 0.1; 0.1 0.3 0.6])
h = deterministic(SX, SZ, x -> x == :x0 ? :z0 : :z1)
Δ(SX) · (k ⊗ h) == compose(mcopy(SX), otimes(k, h))
```

true

6 Evaluating expressions

`evaluate(expr, generators)` interprets a free expression in FinStoch by the structure-preserving functor determined by the images of the generators (Catlab's functor with the FinStoch instance supplying every non-generator node). Generators may be keyed by name or by expression.

```
prior = state(SX, [0.3, 0.7])
gens = Dict{:X ⇒ SX, :Y ⇒ SY, :Z ⇒ SZ, :f ⇒ k, :g ⇒ h, :p ⇒ prior}
evaluate(compose(p, fanout), gens)
```

```
FiniteKernel{Float64}(I → Y{y0,y1,y2} ⊗ Z{z0,z1})
  ()
  y0,z0  0.21
  y1,z0  0.06
  y2,z0  0.03
  y0,z1  0.07
  y1,z1  0.21
  y2,z1  0.42
```

The result is exactly the direct computation:

```
evaluate(compose(p, fanout), gens) ≈ compose(prior, mcopy(SX), otimes(k, h))
```

true

A chain $X \rightarrow Y \rightarrow Z$ written as an expression and as a matrix product:

```

l = cpt(factors(SY)[1], factors(SZ)[1], [0.9 0.1; 0.5 0.5; 0.2 0.8])
chain = compose(Hom(:k, X, Y), Hom(:l, Y, Z))
direct = compose(k, l)
evaluate(chain, Dict(:X ⇒ SX, :Y ⇒ SY, :Z ⇒ SZ, :k ⇒ k, :l ⇒ l)) ≈ direct,
kernel_matrix(direct) ≈ kernel_matrix(l) * kernel_matrix(k)

```

```
(true, true)
```

Generators without an image raise a typed error:

```

try
    evaluate(chain, Dict(:X ⇒ SX, :Y ⇒ SY, :Z ⇒ SZ, :k ⇒ k))
catch err
    showerror(stdout, err)
end

```

```
UnboundGeneratorError: no kernel or space bound to generator :l
```

7 The Markov axiom in FinStoch

Because the instance is a model of `ThMarkovCategory`, the axioms hold numerically. Naturality of discard holds for every kernel built by the public constructors, since they are normalised:

```
evaluate(compose(f, delete(Y)), gens) ≈ evaluate(delete(X), gens)
```

```
true
```

Naturality of copy, the extra cartesian axiom, holds for the deterministic `h` but not for the stochastic `k`:

```

copy_natural(m) = compose(m, mcopy(codom(m))) ≈ compose(mcopy(dom(m)), otimes(m, m))
copy_natural(h), copy_natural(k)

```

```
(true, false)
```

This is the formal content of “copy once is not two samples” from the `FiniteKernels.jl` vignette, and the reason Bayesian-network semantics must live in a Markov category rather than a cartesian one.

8 Summary

`ThMarkovCategory` is Catlab's `ThMonoidalCategoryWithDiagonals` plus the single axiom that discarding is natural; `FreeMarkovCategory` builds string-diagram expressions over that theory, and the `FinStoch @instance` makes the same operations run on conditional probability tables, so `evaluate` is an honest functor from expressions to kernels. Naturality of copy, the extra axiom that would make the category cartesian, holds only for deterministic kernels, which is why Bayesian-network semantics need a Markov category. `CategoricalBayesianNetworks.jl` compiles the `ACSet` structures supplied by `BayesianNetworks.jl` into these expressions. The ordinary model and inference packages remain independent of Catlab and this categorical adapter.

9 References

- Cho, Kenta, and Bart Jacobs. 2019. “Disintegration and Bayesian Inversion via String Diagrams.” *Mathematical Structures in Computer Science* 29 (7): 938–71. <https://doi.org/10.1017/S0960129518000488>.
- Fox, Thomas. 1976. “Coalgebras and Cartesian Categories.” *Communications in Algebra* 4 (7): 665–67. <https://doi.org/10.1080/00927877608822127>.
- Fritz, Tobias. 2020. “A Synthetic Approach to Markov Kernels, Conditional Independence and Theorems on Sufficient Statistics.” *Advances in Mathematics* 370: 107239. <https://doi.org/10.1016/j.aim.2020.107239>.
- Patterson, Evan, Owen Lynch, and James Fairbanks. 2022. “Categorical Data Structures for Technical Computing.” *Compositionality* 4 (5). <https://doi.org/10.32408/compositionality-4-5>.
- The mathlib Community. 2020. “The Lean Mathematical Library.” *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs (CPP 2020)*, 367–81. <https://doi.org/10.1145/3372885.3373824>.