

DLMs and GAMs for comparison

DLMs and GAMs for comparison

```
#install.packages('marssTMB', repos = c('https://atsa-es.r-universe.dev', #'https://cloud.r-  
library(MARSS)  
library(mgcv)  
library(dplyr)  
library(forecast)  
library(ggplot2)  
library(lubridate)  
library(marssTMB)  
library(paletteer)  
library(ggpubr)  
library(grid)  
col<-paletteer_d("nationalparkcolors::Everglades")
```

Data

```
dat_lakewa <- readRDS("data_for_lakeWA_example.rds")  
dat_aksalmon <- readRDS("data_for_AK_salmon_example.rds")  
  
# renaming  
dat_lakewa <- dplyr::rename(dat_lakewa,  
                           response = y_adj,  
                           driver = lagged_zp)  
dat_aksalmon <- dplyr::rename(dat_aksalmon,  
                             response = salmon_DFA,  
                             driver = z_sst,  
                             date = year)
```

DLM with time-varying intercepts and time-varying slopes

Define the model – this block is basically copied from the MARSS book (salmon survival case study). First for the Lake WA example:

```
dat <- dat_lakewa
m <- 2
TT <- nrow(dat)
B <- diag(m) ## 2x2; Identity
U <- matrix(0, nrow = m, ncol = 1) ## 2x1; both elements = 0
Q <- matrix(list(0), m, m) ## 2x2; all 0 for now
diag(Q)[1] <- c("q.alpha")
diag(Q)[2] <- c("q.beta")
Z <- array(NA, c(1, m, TT)) ## NxMxT; empty for now
Z[1, 1, ] <- rep(1, TT) ## Nx1; 1's for intercept
Z[1, 2, ] <- dat$driver ## Nx1; predictor variable
A <- matrix(0) ## 1x1; scalar = 0
R <- matrix("r") ## 1x1; scalar = r
## only need starting values for regr parameters
inits_list <- list(x0 = matrix(c(0, 0), nrow = m))
## list of model matrices & vectors
mod_list <- list(B = B, U = U, Q = Q, Z = Z, A = A, R = R)
# convert response to matrix
dat_mat <- matrix(dat$response, nrow = 1)
# fit the model -- crank up the maxit to ensure convergence
dlm_lakewa_1 <- MARSS(dat_mat, inits = inits_list, model = mod_list,
  control = list(maxit=4000), method="TMB")
```

MARSS fit is

Estimation method: TMB

Estimation converged in 42 iterations.

Log-likelihood: -143.7477

AIC: 297.4954 AICc: 297.9466

	Estimate
R.r	1.49e-01
Q.q.alpha	2.15e-01
Q.q.beta	2.07e-11
x0.X1	1.64e+00
x0.X2	6.92e-02

Initial states (x0) defined at t=0

Standard errors have not been calculated.
 Use MARSSparamCIs to compute CIs and bias estimates.

```
# Fit a second model with just time-varying slope
diag(Q)[1] <- 1e-10
mod_list <- list(B = B, U = U, Q = Q, Z = Z, A = A, R = R)
dlm_lakewa_2 <- MARSS(dat_mat, inits = inits_list, model = mod_list,
  control = list(maxit=4000), method="TMB")
```

MARSS fit is
 Estimation method: TMB
 Estimation converged in 18 iterations.
 Log-likelihood: -155.082
 AIC: 318.164 AICc: 318.4625

	Estimate
R.r	0.226
Q.q.beta	0.235
x0.X1	0.498
x0.X2	1.422

Initial states (x0) defined at t=0

Standard errors have not been calculated.
 Use MARSSparamCIs to compute CIs and bias estimates.

Now for the AK salmon example

```
dat <- dat_aksalmon
m <- 2
TT <- nrow(dat)
B <- diag(m) ## 2x2; Identity
U <- matrix(0, nrow = m, ncol = 1) ## 2x1; both elements = 0
Q <- matrix(list(0), m, m) ## 2x2; all 0 for now
diag(Q)[1] <- c("q.alpha")
diag(Q)[2] <- c("q.beta")
Z <- array(NA, c(1, m, TT)) ## NxMxT; empty for now
Z[1, 1, ] <- rep(1, TT) ## Nx1; 1's for intercept
Z[1, 2, ] <- dat$driver ## Nx1; predictor variable
A <- matrix(0) ## 1x1; scalar = 0
```

```

R <- matrix("r") ## 1x1; scalar = r
## only need starting values for regr parameters
inits_list <- list(x0 = matrix(c(0, 0), nrow = m))
## list of model matrices & vectors
mod_list <- list(B = B, U = U, Q = Q, Z = Z, A = A, R = R)
# convert response to matrix
dat_mat <- matrix(dat$response, nrow = 1)
# fit the model -- crank up the maxit to ensure convergence
dmlm_aksalmon_1 <- MARSS(dat_mat, inits = inits_list, model = mod_list,
                        control = list(maxit=4000), method="TMB")

```

MARSS fit is

Estimation method: TMB

Estimation converged in 34 iterations.

Log-likelihood: -67.30025

AIC: 144.6005 AICc: 145.7543

	Estimate
R.r	4.37e-09
Q.q.alpha	5.43e-01
Q.q.beta	1.27e-02
x0.X1	-3.52e+00
x0.X2	8.37e-01

Initial states (x0) defined at t=0

Standard errors have not been calculated.

Use MARSSparamCIs to compute CIs and bias estimates.

```

# Fit a second model with just time-varying slope
diag(Q)[1] <- 1e-10
mod_list <- list(B = B, U = U, Q = Q, Z = Z, A = A, R = R)
dmlm_aksalmon_2 <- MARSS(dat_mat, inits = inits_list, model = mod_list,
                        control = list(maxit=4000), method="TMB")

```

MARSS fit is

Estimation method: TMB

Estimation converged in 16 iterations.

Log-likelihood: -114.4286

AIC: 236.8572 AICc: 237.6119

	Estimate
R.r	2.143
Q.q.beta	0.365
x0.X1	1.269
x0.X2	6.343

Initial states (x0) defined at t=0



Standard errors have not been calculated.
 Use MARSSparamCIs to compute CIs and bias estimates.

Time varying models with MGCV


```
K_WA <- round(0.99*nrow(dat_lakewa))
K_AK <- round(0.99*nrow(dat_aksalmon))
dat_lakewa$n_date <- seq(1,nrow(dat_lakewa))
gam_lakewa_1 <- gam(response ~ s(n_date,k=K_WA) + s(n_date, by = driver, bs = "gp",k=K_WA), c
gam_lakewa_2 <- gam(response ~ s(n_date, by = driver, bs = "gp",k=K_WA), data = dat_lakewa)

dat_aksalmon$n_date <- seq(1,nrow(dat_aksalmon))
gam_aksalmon_1 <- gam(response ~ s(n_date,k=K_AK) + s(n_date, by = driver, bs = "gp",k=K_AK)
gam_aksalmon_2 <- gam(response ~ s(n_date, by = driver, bs = "gp",k=K_AK), data = dat_aksalmon)


# extract the smooth estimates with SEs to compare to DLM
plot_1 <- plot(gam_lakewa_1, seWithMean = TRUE, n = nrow(dat_lakewa))
```




```
plot_2 <- plot(gam_lakewa_2, seWithMean = TRUE, n = nrow(dat_lakewa))
```




```
plot_3 <- plot(gam_aksalmon_1, seWithMean = TRUE, n = nrow(dat_aksalmon))
```





```
plot_4 <- plot(gam_aksalmon_2, seWithMean = TRUE, n = nrow(dat_aksalmon))
```



```
summary(gam_lakewa_2)
```

Family: gaussian

Link function: identity

Formula:

response ~ s(n_date, by = driver, bs = "gp", k = K_WA)

Parametric coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	0.5209	0.1237	4.21	5.29e-05 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Approximate significance of smooth terms:

	edf	Ref.df	F	p-value
s(n_date):driver	29.66	30.07	21.96	<2e-16 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Rank: 32/139

R-sq.(adj) = 0.821 Deviance explained = 86%

GCV = 0.38449 Scale est. = 0.29967 n = 139

```
dat_aksalmon$date <- paste0(dat_aksalmon$date, "-01-01")
```

```
coef_dlm_lakeWA1 <- data.frame(date = dat_lakewa$date,
                                int_est = dlm_lakewa_1$states[1,],
                                int_se = dlm_lakewa_1$states.se[1,],
                                slope_est = dlm_lakewa_1$states[2,],
                                slope_se = dlm_lakewa_1$states.se[2,],
                                time_varying = "Intercept + slope",
                                dataset = "Lake Washington : DLM")
coef_dlm_lakeWA2 <- data.frame(date = dat_lakewa$date,
                                int_est = 0,
                                int_se = 0,
                                slope_est = dlm_lakewa_2$states[2,],
                                slope_se = dlm_lakewa_2$states.se[2,],
                                time_varying = "Slope",
                                dataset = "Lake Washington : DLM")
```

```

coef_dlm_AK1 <- data.frame(date = dat_aksalmon$date,
                           int_est = dlm_aksalmon_1$states[1,],
                           int_se = dlm_aksalmon_1$states.se[1,],
                           slope_est = dlm_aksalmon_1$states[2,],
                           slope_se = dlm_aksalmon_1$states.se[2,],
                           time_varying = "Intercept + slope",
                           dataset = "Alaska salmon : DLM")
coef_dlm_AK2 <- data.frame(date = dat_aksalmon$date,
                           int_est = 0,
                           int_se = 0,
                           slope_est = dlm_aksalmon_2$states[2,],
                           slope_se = dlm_aksalmon_2$states.se[2,],
                           time_varying = "Slope",
                           dataset = "Alaska salmon : DLM")

coef_gam_lakeWA1 <- data.frame(date = dat_lakewa$date,
                               int_est = plot_1[[1]]$fit,
                               int_se = plot_1[[1]]$se,
                               slope_est = plot_1[[2]]$fit,
                               slope_se = plot_1[[2]]$se,
                               time_varying = "Intercept + slope",
                               dataset = "Lake Washington : GAM")
coef_gam_lakeWA2 <- data.frame(date = dat_lakewa$date,
                               int_est = 0,
                               int_se = 0,
                               slope_est = plot_2[[1]]$fit,
                               slope_se = plot_2[[1]]$se,
                               time_varying = "Slope",
                               dataset = "Lake Washington : GAM")
coef_gam_AK1 <- data.frame(date = dat_aksalmon$date,
                           int_est = plot_3[[1]]$fit,
                           int_se = plot_3[[1]]$fit,
                           slope_est = plot_3[[2]]$fit,
                           slope_se = plot_3[[2]]$fit,
                           time_varying = "Intercept + slope",
                           dataset = "Alaska salmon : GAM")
coef_gam_AK2 <- data.frame(date = dat_aksalmon$date,
                           int_est = 0,
                           int_se = 0,
                           slope_est = plot_4[[1]]$fit,
                           slope_se = plot_4[[1]]$se,

```

```

        time_varying = "Slope",
        dataset = "Alaska salmon : GAM")


coefs <- rbind(coef_dlm_lakeWA1, coef_dlm_lakeWA2, coef_dlm_AK1, coef_dlm_AK2,
              coef_gam_lakeWA1, coef_gam_lakeWA2, coef_gam_AK1, coef_gam_AK2)

annotate_Slope<-data.frame(label=c("A.", "B.", "E.", "F"),
                           date=c(1975,1975,dat_lakewa$date[25],dat_lakewa$date[25]),
                           y=c(7.5,10,4.5,7.75), time_varying=c("slope","slope","slope","slope"))

slope_panel <-ggplot(coefs, aes(date, slope_est, group = time_varying, fill=time_varying, col=
  geom_ribbon(aes(ymin=slope_est-2*slope_se, ymax = slope_est+2*slope_se), alpha=0.3, col = 1
  geom_line(aes(lty=time_varying)) +
  ylab(" ") +
  xlab("") + theme_classic() +
  ggtitle("Slope")+
  #ylim(c(-5,11))+
  facet_wrap(~ dataset, scale="free") +
  #scale_color_viridis_d(option="magma",begin=0.2, end=0.8, name = "Time-varying") +
  #scale_fill_viridis_d(option="magma",begin=0.2, end=0.8, name = "Time-varying") +
  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+
  guides(fill="none",colour="none",lty="none")+
  theme(
    strip.background = element_rect(fill = "white"),
    plot.title = element_text(hjust = 0.5)
  )
slope_panel


```

Slope




```
int_panel <- ggplot(coefs, aes(date, int_est, group = time_varying, fill=time_varying, col=t.
  geom_ribbon(aes(ymin=int_est-2*int_se, ymax = int_est+2*int_se), alpha=0.3, col = NA) +
  geom_line(aes(lty=time_varying)) +
  ylab(" ") +
  xlab("") + theme_classic() +
  facet_wrap(~ dataset, scale="free") +
  ggtitle("Intercept")+
  #ylim(-20,10.5)+
  #scale_color_viridis_d(option="magma",begin=0.2, end=0.8, name = "Time-varying") +
  #scale_fill_viridis_d(option="magma",begin=0.2, end=0.8, name = "Time-varying") +
  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+

  theme(
    strip.background = element_rect(fill = "white"),
    plot.title = element_text(hjust = 0.5)
  )
int_panel
```



```
Fig4<-ggarrange(slope_panel,int_panel, nrow=1,ncol=2, widths=c(1,1.25))
annotate_figure(Fig4, bottom = textGrob("Year", gp = gpar(cex = 1)))
```



```
ggsave("Figure_5_dlmgam_comparison.png", height = 7, width = 11)
```

```
ggsave("Figure_5_dlmgam_comparison.pdf", height = 7, width = 11)
```

```
#ggsave("Figure_2_dlmgam_comparison.png", height = 7, width = 7)
```

```
panel_a<-ggplot(coefs%>%filter(dataset=="Alaska salmon : DLM"), aes(date, slope_est, group =  
  geom_ribbon(aes(ymin=slope_est-2*slope_se, ymax = slope_est+2*slope_se), alpha=0.3, col = 1  
  geom_line(aes(lty=time_varying)) +  
  ylab("") +  
  xlab("") + theme_classic() +  
  ylim(c(-3.5,11))+  
  scale_fill_manual(values=c(col[4],col[5]))+  
  scale_colour_manual(values=c(col[4],col[5]))+  
  guides(fill="none",colour="none",lty="none")+  
  theme(  
    strip.background = element_rect(fill = "white"),  
    plot.title = element_text(hjust = 0.5)  
  )
```

```
panel_b<-ggplot(coefs%>%filter(dataset=="Alaska salmon : GAM"), aes(date, slope_est, group =  
  geom_ribbon(aes(ymin=slope_est-2*slope_se, ymax = slope_est+2*slope_se), alpha=0.3, col = 1  
  geom_line(aes(lty=time_varying)) +  
  ylab("") +  
  xlab("") + theme_classic() +  
  ylim(c(-3.5,11))+  
  scale_fill_manual(values=c(col[4],col[5]))+  
  scale_colour_manual(values=c(col[4],col[5]))+  
  guides(fill="none",colour="none",lty="none")+  
  theme(  
    strip.background = element_rect(fill = "white"),  
    plot.title = element_text(hjust = 0.5)  
  )
```

```
panel_e <- ggplot(coefs%>%filter(dataset=="Lake Washington : DLM"), aes(date, slope_est, group =  
  geom_ribbon(aes(ymin=slope_est-2*slope_se, ymax = slope_est+2*slope_se), alpha=0.3, col = 1  
  geom_line(aes(lty=time_varying)) +  
  ylab("") +  
  xlab("") + theme_classic() +  
  #ylim(c(-1.5,5.1))+  
  ylim(c(-7,8))+  
  scale_fill_manual(values=c(col[4],col[5]))+
```

```

scale_colour_manual(values=c(col[4],col[5]))+
guides(fill="none",colour="none",lty="none")+
theme(
  strip.background = element_rect(fill = "white"),
  plot.title = element_text(hjust = 0.5)
)

panel_f <-ggplot(coefs%>%filter(dataset=="Lake Washington : GAM"), aes(date, slope_est, group = t)) +
  geom_ribbon(aes(ymin=slope_est-2*slope_se, ymax = slope_est+2*slope_se), alpha=0.3, col = "red")+
  geom_line(aes(lty=time_varying)) +
  ylab("") +
  xlab("") + theme_classic() +
  #ylim(c(-1.5,5.1))+
  ylim(c(-7,8))+
  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+
  guides(fill="none",colour="none",lty="none")+
  theme(
    strip.background = element_rect(fill = "white"),
    plot.title = element_text(hjust = 0.5)
  )

fig_slope=ggarrange(panel_a, panel_b, panel_e,panel_f, nrow=2,ncol=2,
  labels = c("A.", "B.", "E.", "F."))
fig_slope_y<-annotate_figure(fig_slope, left = textGrob("Time-varying slope",rot=90,gp = gpar(size=12)))

panel_c<-ggplot(coefs%>%filter(dataset=="Alaska salmon : DLM"), aes(date, int_est, group = t)) +
  geom_ribbon(aes(ymin=int_est-2*int_se, ymax = int_est+2*int_se), alpha=0.3, col = NA) +
  geom_line(aes(lty=time_varying)) +
  ylab("") +
  xlab("") + theme_classic() +
  ylim(-16,11)+
  guides(fill="none",colour="none",lty="none")+
  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+
  theme(
    strip.background = element_rect(fill = "white"),
    plot.title = element_text(hjust = 0.5)
  )

```

```

panel_d<-ggplot(coefs%>%filter(dataset=="Alaska salmon : GAM"), aes(date, int_est, group = t.
  geom_ribbon(aes(ymin=int_est-2*int_se, ymax = int_est+2*int_se), alpha=0.3, col = NA) +
  geom_line(aes(lty=time_varying)) +
  ylab("") +
  xlab("") + theme_classic() +
  ylim(-16,11)+
  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+
  guides(fill="none",colour="none",lty="none")+

  theme(
    strip.background = element_rect(fill = "white"),
    plot.title = element_text(hjust = 0.5)
  )

panel_g<-ggplot(coefs%>%filter(dataset=="Lake Washington : DLM"), aes(date, int_est, group =
  geom_ribbon(aes(ymin=int_est-2*int_se, ymax = int_est+2*int_se), alpha=0.3, col = NA) +
  geom_line(aes(lty=time_varying)) +
  ylab("") +
  xlab("") + theme_classic() +
  ylim(-8.5,4.5)+
  guides(fill="none",colour="none",lty="none")+
  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+
  theme(
    strip.background = element_rect(fill = "white"),
    plot.title = element_text(hjust = 0.5)
  )

panel_h<-ggplot(coefs%>%filter(dataset=="Lake Washington : GAM"), aes(date, int_est, group =
  geom_ribbon(aes(ymin=int_est-2*int_se, ymax = int_est+2*int_se), alpha=0.3, col = NA) +
  geom_line(aes(lty=time_varying)) +
  ylab("") +
  xlab("") + theme_classic() +
  ylim(-8.5,4.5)+
  guides(fill="none",colour="none",lty="none")+
  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+
  theme(
    strip.background = element_rect(fill = "white"),
    plot.title = element_text(hjust = 0.5)
  )

```

```

CG<-ggarrange(panel_c, panel_g, nrow=2,ncol=1,
              labels = c("C.", "G."))%>%
annotate_figure(top = textGrob("DLM",gp = gpar(cex = 1)))

DH<-ggarrange(panel_d, panel_h,nrow=2,ncol=1,
              labels = c("D.", "H."))%>%
annotate_figure(top = textGrob("GAM",gp = gpar(cex = 1)))
intercepts<-ggarrange(CG, DH,nrow=1,ncol=2)%>%
annotate_figure(left = textGrob("Intercept Estimates",rot=90,gp = gpar(cex = 1)))

AE<-ggarrange(panel_a, panel_e, nrow=2,ncol=1,
              labels = c("A.", "E."))%>%
annotate_figure(top = textGrob("DLM",gp = gpar(cex = 1)))
BF<-ggarrange(panel_b, panel_f,nrow=2,ncol=1,
              labels = c("B.", "F."))%>%
annotate_figure(top = textGrob("GAM",gp = gpar(cex = 1)))
slopes<-ggarrange(AE, BF,nrow=1,ncol=2)%>%
annotate_figure(left = textGrob("Slope Estimates",rot=90,gp = gpar(cex = 1)))

```

```

coefs<-coefs%>%mutate(year=as.numeric(format(date, "%Y")))

annotateGoA<-data.frame(label=c("High AL \n Variability",
                                "Low AL \n Variability",
                                "Marine \n HW"),
                        date=c(1975, 2000,2019),
                        y=c(10,10,10), Anomalies=c("z_sst","z_sst","z_sst"))

```

```

annotateWA<-data.frame(label=c("Sewage \n Inputs", "Water \n Treatment"),
                        date=c(dat_lakewa$date[25],dat_lakewa$date[100]),
                        y=c(4,4), TimeSeries=c("TP","TP"))

```

```

panel_a<-ggplot(coefs%>%filter(dataset=="Alaska salmon : DLM"), aes(x=year, y=int_est)) +
  geom_ribbon(aes(ymin=int_est-2*int_se, ymax = int_est+2*int_se, group = time_varying, fill=
  geom_line(aes(lty=time_varying, group = time_varying, col=time_varying)) +
  ylab("Intercept Estimate") +
  ggtitle("DLM")+
  xlab("") + theme_classic() +
  ylim(-16,11)+
  #xlim(1965,2030)+

```

```

geom_vline(xintercept=c(1989,2014), lty=c(2,2),col='grey')+
geom_text(data=annotateGoA, aes(x = date, y = y,
                                label = label),
          col='black',fontface = "italic",cex=2.6)+
geom_hline(yintercept=0, lty=3,col=col[5])+

guides(fill="none",colour="none",lty="none")+
scale_fill_manual(values=c(col[4],col[5]))+
scale_colour_manual(values=c(col[4],col[5]))+
theme(
  strip.background = element_rect(fill = "white"),
  plot.title = element_text(hjust = 0.5),axis.title.x=element_blank(),
  axis.text.x=element_blank(),
  axis.ticks.x=element_blank()
)

panel_e<-ggplot(coefs%>%filter(dataset=="Alaska salmon : DLM"), aes(year, slope_est, group =
  geom_ribbon(aes(ymin=slope_est-2*slope_se, ymax = slope_est+2*slope_se), alpha=0.3, col = 1
  geom_line(aes(lty=time_varying)) +
  ylab("Slope Estimate") +
  xlab("") + theme_classic() +
  ylim(c(-3.5,11))+
  geom_vline(xintercept=c(1989,2014), lty=c(2,2),col='grey')+

  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+
  guides(fill="none",colour="none",lty="none")+
  theme(
    strip.background = element_rect(fill = "white"),
    plot.title = element_text(hjust = 0.5)
  )

panel_f<-ggplot(coefs%>%filter(dataset=="Alaska salmon : GAM"), aes(year, slope_est, group =
  geom_ribbon(aes(ymin=slope_est-2*slope_se, ymax = slope_est+2*slope_se), alpha=0.3, col = 1
  geom_line(aes(lty=time_varying)) +
  ylab("") +
  geom_vline(xintercept=c(1989,2014), lty=c(2,2),col='grey')+

  xlab("") + theme_classic() +
  ylim(c(-3.5,11))+
  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+

```

```

guides(fill="none",colour="none",lty="none")+
theme(
  strip.background = element_rect(fill = "white"),
  plot.title = element_text(hjust = 0.5),
  axis.title.y=element_blank(),
  axis.text.y=element_blank(),
  axis.ticks.y=element_blank()
)

panel_g <- ggplot(coefs%>%filter(dataset=="Lake Washington : DLM"), aes(date, slope_est, group)) +
  geom_ribbon(aes(ymin=slope_est-2*slope_se, ymax = slope_est+2*slope_se), alpha=0.3, col = "red") +
  geom_line(aes(lty=time_varying)) +
  ylab("") +
  geom_vline(xintercept=dat_lakewa$date[56], lty=2,col='grey')+

  xlab("") + theme_classic() +
  #ylim(c(-1.5,5.1))+
  ylim(c(-7,8))+
  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+
  guides(fill="none",colour="none",lty="none")+
  theme(
    strip.background = element_rect(fill = "white"),
    plot.title = element_text(hjust = 0.5)
  )

panel_h <-ggplot(coefs%>%filter(dataset=="Lake Washington : GAM"), aes(date, slope_est, group)) +
  geom_ribbon(aes(ymin=slope_est-2*slope_se, ymax = slope_est+2*slope_se), alpha=0.3, col = "red") +
  geom_line(aes(lty=time_varying)) +
  ylab("") +
  geom_vline(xintercept=dat_lakewa$date[56], lty=2,col='grey')+

  xlab("") + theme_classic() +
  #ylim(c(-1.5,5.1))+
  ylim(c(-7,8))+
  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+
  guides(fill="none",colour="none",lty="none")+
  theme(
    strip.background = element_rect(fill = "white"),
    plot.title = element_text(hjust = 0.5),
    axis.title.y=element_blank(),

```

```

    axis.text.y=element_blank(),
    axis.ticks.y=element_blank()
  )

fig_slope=ggarrange(panel_e, panel_f, panel_g,panel_h, nrow=1,ncol=4,
                    labels = c("E.", "F.", "G.", "H.))

fig_slope_y<-annotate_figure(fig_slope, left = textGrob("Time-varying slope",rot=90,gp = gpar(
  size=12,color="black",fontface="italic",fontfamily="serif")))

panel_b<-ggplot(coefs%>%filter(dataset=="Alaska salmon : GAM"), aes(year, int_est, group = time_varying)) +
  geom_ribbon(aes(ymin=int_est-2*int_se, ymax = int_est+2*int_se), alpha=0.3, col = NA) +
  geom_line(aes(lty=time_varying)) +
  ylab("") +
  xlab("") + theme_classic() +
  ylim(-16,11)+
  ggtitle("GAM")+
  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+
  guides(fill="none",colour="none",lty="none")+
  geom_vline(xintercept=c(1989,2014), lty=c(2,2),col='grey')+

  theme(
    strip.background = element_rect(fill = "white"),
    plot.title = element_text(hjust = 0.5),axis.title.x=element_blank(),
    axis.text.x=element_blank(),
    axis.ticks.x=element_blank(),
    axis.title.y=element_blank(),
    axis.text.y=element_blank(),
    axis.ticks.y=element_blank()
  )

panel_c<-ggplot(coefs%>%filter(dataset=="Lake Washington : DLM"), aes(date, int_est)) +
  geom_ribbon(aes(ymin=int_est-2*int_se, ymax = int_est+2*int_se, group = time_varying, fill=time_varying)) +
  geom_line(aes(lty=time_varying, group = time_varying, fill=time_varying, col=time_varying)) +
  ylab("") +

```

```

xlab("") + theme_classic() +
ylim(-8.5,4.5)+
geom_vline(xintercept=dat_lakewa$date[56], lty=2,col='grey')+
geom_text(data=annotateWA, aes(x = date, y = y,
                                label = label), col='black',fontface = "italic", cex=2.8)+

ggtitle("DLM")+
guides(fill="none",colour="none",lty="none")+
scale_fill_manual(values=c(col[4],col[5]))+
scale_colour_manual(values=c(col[4],col[5]))+
theme(
  strip.background = element_rect(fill = "white"),
  plot.title = element_text(hjust = 0.5),axis.title.x=element_blank(),
  axis.text.x=element_blank(),
  axis.ticks.x=element_blank()
)

panel_d<-ggplot(coefs%>%filter(dataset=="Lake Washington : GAM"), aes(date, int_est, group =
  geom_ribbon(aes(ymin=int_est-2*int_se, ymax = int_est+2*int_se), alpha=0.3, col = NA) +
  geom_line(aes(lty=time_varying)) +
  ylab("") +
  xlab("") + theme_classic() +
    geom_vline(xintercept=dat_lakewa$date[56], lty=2,col='grey')+

  ylim(-8.5,4.5)+
  ggtitle("GAM")+
  guides(fill="none",colour="none",lty="none")+
  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+
  theme(
    strip.background = element_rect(fill = "white"),
    plot.title = element_text(hjust = 0.5),axis.title.x=element_blank(),
    axis.text.x=element_blank(),
    axis.ticks.x=element_blank(),
    axis.title.y=element_blank(),
    axis.text.y=element_blank(),
    axis.ticks.y=element_blank()
  )

fig_int=ggarrange(panel_a, panel_b, panel_c,panel_d, nrow=1,ncol=4,
  labels = c("A.", "B.", "C.", "D."))

```


```

fig_left=ggarrange(panel_a, panel_b, panel_e,panel_f, nrow=2,ncol=2,
                    labels = c("A.", "B.", "E.", "F."), widths=c(1.25,1))%>%
  annotate_figure(top = textGrob("Gulf of Alaska Dataset",gp = gpar(cex = 1)))

fig_right=ggarrange(panel_c, panel_d, panel_g,panel_h, nrow=2,ncol=2,
                    labels = c("C.", "D.", "G.", "H."), widths=c(1.25,1))%>%
  annotate_figure(top = textGrob("Lake WA Dataset",gp = gpar(cex = 1)))

panel_z<-ggplot(coefs%>%filter(dataset=="Lake Washington : GAM"), aes(date, int_est, group =
  geom_ribbon(aes(ymin=int_est-2*int_se, ymax = int_est+2*int_se), alpha=0.3, col = NA) +
  geom_line(aes(lty=time_varying)) +
  ylab("") +
  xlab("") + theme_classic() +
  ylim(-8.5,4.5)+
  ggtitle("GAM")+
  guides(fill="none")+
  scale_fill_manual(values=c(col[4],col[5]))+
  scale_colour_manual(values=c(col[4],col[5]))+
  labs(colour = "Time-Varying Parameter(s)", lty="Time-Varying Parameter(s)")+
  theme(
    strip.background = element_rect(fill = "white"),
    plot.title = element_text(hjust = 0.5),
    axis.title.x=element_blank(),
    axis.text.x=element_blank(),
    axis.ticks.x=element_blank(),
    legend.position = "bottom",
    legend.title = element_text(size = 12), # Adjust size for the legend title
    legend.text = element_text(size = 10)
  )
panel_z

```




```
g_legend <- function(a.gplot){
  tmp <- ggplot_gtable(ggplot_build(a.gplot))
  leg <- which(sapply(tmp$grobs, function(x) x$name) == "guide-box")
  legend <- tmp$grobs[[leg]]
  legend
}

legend <- g_legend(panel_z)

grid.newpage()
grid.draw(legend)
```

Time-Varying Parameter(s) — Intercept + slope ---- Slope

```
ggarrange(fig_left,fig_right, nrow=1,ncol=2)%>%
  annotate_figure(bottom = textGrob("Year",gp = gpar(cex =1)))%>%
  ggarrange(legend, nrow=2,ncol=1, heights=c(10,1))
```



Time-Varying Parameter(s) — Intercept + slope ---- Slope

```
ggsave("Figure_4_dlmgam_comparison.png", height = 5, width = 11, bg = "white")
```