
ECS Administration Manual

Release 0 TODO:use git id

Latex Author Name

Apr 05, 2017

Contents

1	Requirements	1
2	Deploy Appliance	6
3	Configure Appliance	8
4	Maintenance	13
5	Digital signed pdf documents	17
6	Development	19

The ecs appliance is a selfservice production setup virtual machine builder and executor. it can be stacked on top of the developer vm, but is independent of it.

Requirements

The ecs software is designed to run as an external available internet web-service, reachable by everyone.

Hosting Requirements

- a Virtual Machine on a supported hypervisor or Hardware sized according to the [Assessment](#) Chapter
- a Backup space (for encrypted backup data) accessable by one of 25 supported storage protocols explained under [Backup Storage](#)
- DNS A Record pointing to a fixed public IPV4 address,a MX Record and a reverse PTR Record as described under [DNS Setup](#)
- incoming tcp ports 22,25,80,443,465 of a fixed public IPV4 address and IPV4 and internet connectivity for the vm as described under [Internet Connectivity](#)
- Working HTTPS including HTTP-Client Certificate support. See common challenges described under [Security Products](#)

Hypervisor

- The base of the virtual machine is a Ubuntu Xenial (16.04 LTS) 64Bit Standard Cloud Image.
- The appliance was tested on the following hypervisors: xen,kvm,vmware sphere,virtualbox
 - hyperv is not tested but is expected to work
 - rollouts to amazon ec2, google gce or openstack clouds are not tested but meta data gathering from ec2, gce or openstack compatible meta data services is implemented but probably need some tweaking.
- Follow the Assessment Chapter for the right sizing of CPU-cores, memory and harddisk.

Backup Storage

- For storing backup data the appliance needs a storage space accessible via one of the 24 duplicity supported storage protocols.
- In addition to the supported duplicity protocols the appliance has support for **cifs** (windows file sharing attached volumes, including automatic mount and unmount)
- Tested protocols so far: localfile, ftp, ftpssl, ssh/scp, ssh/sftp, http/webdav, cifs
- For Details see: [Duplicity Manual - Section URL-Format](#)
- Storage at Rest: All backup data is encrypted before it leaves the machine using gpg (GnuPG) and is saved without any prior decryption on the target space.
- The storage space may be hosted internal or external, using the same provider as the machine hosting or using a different provider. The hosting provider may be a trusted or untrusted third-party.
- Rotation and Retention is automatic, the backup process is unattended.
- See [Assessment](#) for the correct storage space size.

DNS Setup

- a dns [sub]domain with a A and a MX Entry and the reverse ptr of the public IPv4-Address set to the domain name
 - a A Record pointing to the public IP
 - a MX Record pointing to the A Record
 - a reverse PTR Record pointing to the domain name.

Warning: Both MX Record and reverse PTR Record are important to setup. Eg. failing to setup reverse PTR will result in broken email sending, because the target mailserver will think the emails are spam and will bounce messages.

Examples for domains “https://whatever.me” and “https://another.sub.domain.me”:

```
whatever.me. IN A 1.2.3.4
whatever.me. IN MX 10 whatever.me
4.3.2.1.in-addr.arpa. IN PTR whatever.me.

another.sub.domain.me. IN A 5.6.7.8
another.sub.domain.me. IN MX 10 another.sub.domain.me
8.7.6.5.in-addr.arpa. IN PTR another.sub.domain.me
```

Internet Connectivity

- permanent internet connectivity with a big (>50Mbit) upload channel

- an IPv4 address and dns server settings need to be served to the machine by DHCP for automatic configuration
 - this can be any internal or the public IPv4 Address if the hosting location needs this, but it must be served by DHCP
 - Unusable internal nets are 172.17.X.X and 10.0.3.X, because these are used by the appliance itself
- a public IPv4-Address or the incoming TCP ports 22,25,80,443,465 and ICMP/ping of this address forwarded to the machine
 - port 22 - ssh: ssh publickey authentication is used. this connection is used for installation and optional support
 - port 25,465 - smtp: the incoming email server of the appliance will receive emails from answers of forwarded ecs communication. if the hosting locations policy does not permit this, the ecs will work without it, but loses email answering functionality
 - port 80 - http: the appliance communicates only over https, but needs http for letsencrypt client certificate renewal and for redirecting to the https site
 - port 443 - https: the appliance uses letsencrypt to issue a host certificate and lets internal user administer https client certificates in self-service
 - * ICMP/ping - ping: for monitoring the system

“Firewall”/Endpointprotection/“Antivirus” Security Products:

Warning: many security products are known to disturb/break HTTPS Host Certificate and Client Certificate validation and weaken the transport protocols on the wire. See the findings of [the Security Impact of HTTPS Interception Paper](#).

Firewall

The appliance does not need a firewall but works as long as the incoming ports listed are forwarded to the machine and outgoing traffic from the machine is permitted.

Host Certificates

The appliance uses LetsEncrypt to issue https/ssl host certificates and also takes care of the renewal of these host certificates. There is no IT-administration task involved in this process.

Client Certificates

The ecs appliance uses https client certificates for protection of elevated user rights. Https client certificates are issued by the appliance itself and can be done in selfservice as an internal ecs webfrontend user. There is no IT-Administration task involved in this process.

Warning: If the hosting location has some mandatory security product, you probably need some extra configuration in the security product to fix support for Client Certificates.

This may also apply to to the pc’s of internal ecs desktops. Some desktop “antivirus” products may need similar extra configuration to have working https client certificate support. So far there have been findings of Kaspersky and McAfee products to need extra configuration.

Cores, Memory, Harddisk & Backup Space Assessment

All data size units in this document are 1024 based.

- 1 GB = 1024 MB, 1 MB = 1024 KB , 1 KB = 1024 bytes

As a guideline, if you have more memory available, add some extra memory.

Warning: If you deviate from the example values below, be sure to add the needed memory per core if you add more cores, because many of the appliance processes get scaled to the number of cores.

- Minimum CPU/Memory: 2 Cores, 4GB

Core Calculation:

- 20 Studies per Month: 2 Cores
- 40 Studies per Month: 2-4 Cores
- 100-250 Studies per Month: 4-8 Cores

Memory Calculation:

- 2GB Base + 1GB per Core + Disk-size of Database (eg. 2GB)
- eg. 2 Cores = 4 GB + 1 GB Database= 5GB
- eg. 8 Cores = 10 GB + 8 GB Database= 18GB

Storage Calculation (10 Years):

- System: 5GB
- Temporary Workspace: 30GB
- Database: (Studies-per-Month/ 12,5)GB
- Document-Storage: (120 * Studies-per-Month * 17)MB

Backup Space Calculation (10 Years):

- Data: 2 (Fullbackups) * max(Document-Storage) + max(Database) + 2 Months delta grow

Limits: The current ecs implementation can sustain 250 Studies per Month for 10 years. Larger implementations are possible with some refactoring in certain parts of the ecs.

10 Years Calculation

After 10 Years, the values noted will be reached.

100 Studies per Month

Items	Size	Calculation
Base & Temp	50GB	
Database	8GB	4074220 / 59 * 120
Document-Storage	195GB	100684328 / 59 * 120
Disksize	253GB	52428800 + 8286549 + 204781684
Backup	444GB	2 x 204781684+ 52428800+ 204781684/120*2
recommended Cores	6	
recommended Memory	16GB+	2+ 8+ 6

250 Studies per Month

Items	Size
Base & Temp	50GB
Database	20GB
Document-Storage	500GB
Disksize	570GB
Backup	1332GB
recommended Cores	8
recommended Memory	30GB+

40 Studies per Month

Items	Size
Base & Temp	50GB
Database	3,2GB
Document-Storage	78GB
Disksize	131GB
Backup	178GB
recommended Cores	4
recommended Memory	9,5GB+

20 Studies per Month

Items	Size
Base & Temp	50GB
Database	1,6GB
Document-Storage	40GB
Disksize	92GB
Backup	89GB
recommended Cores	2
recommended Memory	6GB+

Test Instance

Items	Size
Disksize	20-40GB
recommended Cores	1-2
recommended Memory	4GB+

Research data

- EC with ~100 Studies per Month
- Runtime: ~5 Years (59 month) (15.1.2012 - 15.12.2016 ~ 4 Years, 11 Months)
- Studies: 5861 in 59 Months, or ~100 (99,339) Studies per Month

Document Storage:

- Current space used: 97GB (100684328KB)
- Directories: 69K Directories
- Files: 296K Files

- Files per Directory: Peak at 4-6 Files per Directory
- average 339KB per File
- average space per study: 17178KB ~ 16,78MB

Postgres Database:

- compressed migrated production dump: 475MB
- disk space used: ~4GB (4074220 KB, 1GB pg_xlog)

Client Desktop Requirements

- As a submitter one of the following browsers is needed:
 - Mozilla Firefox
 - Google Chrome
 - Apple Safari
 - Microsoft Edge
 - Microsoft Internetexplorer
- Internal User need:
 - Mozilla Firefox
 - Working HTTPS including HTTP-Client Certificate support. See common challenges described under *Security Products*
- Signing User need:
 - Mozilla Firefox ESR
 - Sun Java with Firefox Plugin

Deploy Appliance

The base of the appliance is Ubuntu Xenial (16.04 LTS). Installation is done unattended using ssh to login into the machine.

As a Virtual Machine

You either need:

- a standard ubuntu cloud image from [Ubuntu Xenial Cloud Images](#)
 - a cloud-init cidata iso volume with your public key
 - * use the prebuilt cidata iso with the vagrant user and the insecure vagrant ssh key or password
 - [vagrant-publickey-growroot.iso](#)
 - [vagrant-password-growroot.iso](#)
 - * you can build your own seed iso using github.com/ecs-org/cidata-seed
- an already running empty Ubuntu Xenial and a ssh key to login
 - eg. if your rootserver hoster has a default xenial image
- a local development machine with vagrant and a hypervisor for vagrant installed.
 - vagrant will setup the base machine for you

Start the new virtual machine and login via ssh.

On Hardware or other custom Configurations

Needed:

- an already running empty Ubuntu Xenial and a ssh key to login
 - eg. if your rootserver hoster has a default xenial image

In a typical root server hosting setup there are two harddisks per machine. These should be configured as a raid1 (mirroring) setup with lvm on top of it.

Example:

- Hardware: [Hetzner px61nvme Rootserver](#)
 - hetzner setup config:

```
DRIVE1 /dev/nvme1n1
DRIVE2 /dev/nvme0n1
SWRAID 1
SWRAIDLEVEL 1
BOOTLOADER grub
HOSTNAME Ubuntu-1604-xenial-64-minimal
PART /boot ext3 512M
PART lvm vg0 all
LV vg0 root / ext4 300G
IMAGE /root/.oldroot/nfs/install/./images/Ubuntu-1604-xenial-64-minimal.tar.gz
```

Network attached Storage

For a virtual machine deployment it is best to stick to the default xenial cloud images layout, unless there is good reason to deviate.

- The appliance supports two external network attached storage volumes, one for permanent data and one for volatile data.
- To have separate volatile and/or data partitions, change storage:ignore:volatile and/or storage:ignore:data to false.
- The volatile volume must be labeled “ecs-volatile”, the data volume “ecs-data”.
- Setup will add mountpoints for /data and /volatile and mount them on startup.
- Use appliance:extra:states and :packages if storage setup needs additional packages installed.

Install via ssh to an empty Xenial VM

ssh into target vm:

```
export DEBIAN_FRONTEND=noninteractive
apt-get -y update; apt-get -y install git
git clone https://github.com/ecs-org/ecs-appliance /app/appliance
cd /
mkdir -p /etc/salt
cp /app/appliance/salt/minion /etc/salt/minion
curl -o /tmp/bootstrap_salt.sh -L https://bootstrap.saltstack.com
chmod +x /tmp/bootstrap_salt.sh
for i in apt-daily.service apt-daily.timer unattended-upgrades.service; do
    systemctl disable $i; systemctl stop $i; ln -sf /dev/null /etc/systemd/system/
done
↪ $i
done
```

```
/tmp/bootstrap_salt.sh -X
salt-call state.highstate pillar='{"appliance": {"enabled": true}}'
```

Testinstall using Vagrant

on your local machine:

```
git clone https://github.com/ecs-org/ecs-appliance ~/ecs-appliance
cd ~/ecs-appliance
vagrant up
```

Upgrade a developer vm

Requirement: you need at least 3gb total memory for the appliance, 4gb minimum if you want metrics active.

on a developer vm:

```
# clone from public repository
git clone https://github.com/ecs-org/ecs-appliance /app/appliance
# install saltstack and start appliance install
curl -o /tmp/bootstrap_salt.sh -L https://bootstrap.saltstack.com
sudo bash -c "mkdir -p /etc/salt; cp /app/appliance/salt/minion /etc/salt/minion; \
  chmod +x /tmp/bootstrap_salt.sh; /tmp/bootstrap_salt.sh -X"
sudo salt-call state.highstate pillar='{"appliance": {"enabled": true}}'
```

if you also want the builder (for building the appliance image) installed:

```
sudo salt-call state.highstate pillar='{"builder": {"enabled": true}, "appliance": \
→ {"enabled": true}}'
```

Configure Appliance

The Appliance is configured using a yaml configuration file which can be placed in one of the following locations:

- local file at `/app/env.yml` (no-cloud config)
- a attached drive with label `cidata` (cloud-init: no-cloud)
- a attached drive with label `config-2` (cloud-init: openstack)
- aws-ec2 meta-data server (amazon elastic computing cloud)
- gce meta-data server (google compute engine)

It will be copied to `/run/active-env.yml` (ramdisk) on each appliance startup.

warning: Do **not** reuse an already existing configuration for a different domain/instance, **always** create a new configuration, to not leak secrets between domains.

Create a new Configuration

on an installed but unconfigured appliance:

- enter installed but empty appliance
- make a new `env.yml`: `env-create.sh domainname.domain ~/domainname.domain/`
- edit settings in “`~/domainname.domain/env.yml`”, see comments inside file
- optional, package `env` into different formats


```
- env-package.sh --requirements; env-package.sh ~/domainname.domain/env.yml
```

- transfer, print out “~/domainname.domain/env.yml.pdf” and store in a safe place.
- save a encrypted copy of env.yml in safe place.
- **Important:** The **env.yml** contains **all needed secrets** for a working appliance and is **the only relevant piece of information** if you want to recover from backup in case of a storage failure.

for offline environment creation, using your local machine:

- have saltstack installed (minion does not need to run)
- ```
git clone https://github.com/ecs-org/ecs-appliance
~/path-to-project/ecs-appliance
```
- use `env-create.sh` and `env-package.sh` like explained below, but add `~/path-to-project/ecs-appliance/salt/common/` to the callpath.
- copy `~/domainname.domain/env.yml` to appliance machine at `/app/env.yml`

```
ssh root@target.vm.ip '/bin/bash -c "mkdir -p /app/"'
scp env.yml root@target.vm.ip:/app/env.yml
```

for a development server:

- run `cp /app/appliance/salt/pillar/default-env.sls /app/env.yml` and edit settings in “/app/env.yml”.

## Modify Configuration

Any applied change in the config file will reconfigure the appliance on the next appliance restart run to the new values found in the configuration.

Eg. if you want to change your backup target to a different location, just change the value and restart the appliance, it will detect and configure all needed changes to the environment.

See the comments in the configuration for different possibilities for the appliance configuration.

```
#cloud-config
XXX keep the "#cloud-config" line first and unchanged, software expects this_
→header

ssh_authorized_keys:
 # # you can put your ssh keys here, this is also used by cloud-init
 # - "ssh-rsa and some long glibberish somebody@somewhere"
ssh_deprecated_keys:
 # # you can copy deprecated keys here,
 # # state.highstate will remove these keys from allowed login,
 # # additionally this section serves as log of past access keys
 # - "ssh-rsa and some long glibberish somebody@somewhere"
disable_root: false
disable_root set to false for cloud-init compatibility, appliance expects root_
→to be usable

appliance:
 # # standby: default false, if set appliance will not activate
 # standby: true
 domain: {{ domain }}
 allowed_hosts: {{ domain }}
 ssl:
 letsencrypt:
 enabled: true
 # # client_certs_mandatory, default false, if true, always need a client_
→certificate
```

```

client_certs_mandatory: true
client_certs_mandatory: false
key: if set ssl key for https host will be used, default empty
key: filename-key.pem
cert: if set ssl key for https host will be used, default empty
cert: filename-cert.pem
sentry:dsn set to your sentry url, may be the same as ecs:settings:SENTRY_DSN
sentry:
dsn: 'https://url'
metric:
exporter: false
server: false
gui: false
pghero: false
git:
default see appliance.include
branch: master
source: git_url
extra: # write out extra files on appliance configure
files:
- path: /path/of/filename
content: |
Your content here
owner: user:group
permissions: "0600"
states: # include extra states at state.highstate
- qrcode
packages: # include extra packages at state.highstate
- ghostscript
update:oncalendar: # set a different update timer than default: "*-*-* 06:30:
→00"
update:automatic: # default to true, to disable automatic update set to false
XXX: do not update in the time between 00:30 and 06:30 because backup runs
→at this time
update:
automatic: true
oncalendar: Sun *-*-* 06:30:00
storage:
setup: optional, will be executed by appliance.storage.setup if volatile
→or data can not be found
setup: |
proxy_cache: true
default false, if true 10 additional GB disk space are used
for operating polipo, a http proxy cache
ignore: # default false, if true: will not look for ecs-volatile or ecs-data
→filesystem
 volatile: true
 data: true
backup:
 url: file:///volatile/ecs-backup-test/
 # options: "string of options directly passed to duplicity"
 # # mount default empty, script will mount & unmount source to target on
→backup run
 # mount:
 # type: "cifs"
 # source: "//1.2.3.4/datavolume"
 # target: "/mnt/appliance-backup-mount"
 # options: "user=username,pass=password"
 # # options are passed to mount via "-o"
 encrypt: |
 a ascii armored GPG Key
ecs:
git: # default see appliance.include

```

```
branch: stable
source: git_url
userswitcher:
 enabled: false
 # set userswitcher to enabled on a test instance to change to different users
settings: |
 DOMAIN = '{{ domain }}'
 ABSOLUTE_URL_PREFIX = 'https://{}/'.format(DOMAIN)
 ALLOWED_HOSTS = [DOMAIN,]
 PDFAS_SERVICE = ABSOLUTE_URL_PREFIX + '/pdf-as-web/'
 # use PDFAS_SERVICE = "mock:" for mock signing
 SECURE_PROXY_SSL = True
 ECS_REQUIRE_CLIENT_CERTS = True
 DEBUG = False
 # SENTRY_DSN = 'https://url' # set to sentry url if available
 ETHICS_COMMISSION_UUID = 'ececececececececececececececececece'
 # set ETHICS_COMMISSION_UUID to the desired UUID of the target commission

 SECRET_KEY = '{{ ssl_secret() }}'
 REGISTRATION_SECRET = '{{ ssl_secret() }}'
 PASSWORD_RESET_SECRET = '{{ ssl_secret() }}'

 EMAIL_BACKEND = 'django.core.mail.backends.console.EmailBackend'
 EMAIL_BACKEND_UNFILTERED = 'django.core.mail.backends.smtp.EmailBackend'
 EMAIL_UNFILTERED_DOMAINS = () # = ('example.com',)

 SMTPD_CONFIG['listen_addr'] = ('0.0.0.0', 8025)
 SMTPD_CONFIG['domain'] = DOMAIN

 # User registration, password reset, send client certificate and mail to
 # receivers at a domain included in EMAIL_UNFILTERED_DOMAINS will be sent via
 # EMAIL_BACKEND_UNFILTERED. All other mail will be sent via EMAIL_BACKEND.
 #
 # Backend to use to NOT sent email but log email to console:
 # django.core.mail.backends.console.EmailBackend
 #
 # Backend to use to send via EMAIL_* smtp settings:
 # django.core.mail.backends.smtp.EmailBackend
 #

vault_encrypt: |
 a ascii armored GPG Key

vault_sign: |
 a ascii armored GPG Key
```

## Ethics Commission UUID's

|                                   |                                                                                      |
|-----------------------------------|--------------------------------------------------------------------------------------|
| 23d805c6b5f14d8b9196a12005fd296f  | Ethikkommission der Medizinischen Universität Wien                                   |
| 7b51f38bde8a4161a0dc34647fc7e65   | Ethikkommission Krankenhaus Barmh.Brüder - Wien                                      |
| 85dc386061584f8e8549ce4e4d828fb   | Ethikkommission der Stadt Wien gemäß KAG, AMG und MPG                                |
| d6a22c635a584521b107481ac18318f   | Ethikkommission Forschungsinstitut des Wiener Roten Kreuzes                          |
| 55ae93ec9df04d6abfc8d233ec5ccf8e  | Ethikkommission Krankenhaus Barmh.Schwestern - Wien                                  |
| 7cd6d52120b3474ba502931b9f60a5f   | Ethikkommission Confraternität-Priv.Klin. Josefstadt und Priv.Klin. Döbling          |
| 7df9ebaf15434709b09c3def9a6c8769  | Ethikkommission St.Anna Kinderspital                                                 |
| f122f144616541d391fde2dcc761aff4  | Ethikkommission Österreichische Arbeitsgemeinschaft für Klinische Pharmakologie      |
| 25b6744780434a3f96a1e43b405d384   | Ethikkommission Privatkrankenanstalt Rudolfinerhaus                                  |
| d542994ced34403db841786a1c1ab892  | Ethikkommission Rheuma-Zentrum Wien-Oberlaa                                          |
| 5615df-baf8c8445d960d1e2cd9c00dc3 | Ethikkommission Krankenhaus des Göttlichen Heilandes                                 |
| 4d3a2d5f138940f293ee87fe6ec1d5b2  | Ethikkommission Evangelisches Krankenhaus                                            |
| 8d2950e3a0294f68bde647a54df6d82b  | Ethikkommission der Allgemeinen Unfallversicherungsanstalt                           |
| 9f6b509e716e413f865d95bdd630e9b6  | Ethikkommission Immunologische Tagesklinik                                           |
| b17f32f604fa4452b5ff3a2baa9e0704  | Ethikkommission des Landes Niederösterreich                                          |
| 6688ce16a3b84d42b1531389e603989f  | Ethikkommission Krankenhaus Elisabethinen                                            |
| e4dcd05a31ad475ca72dea7b84ef030e  | Ethikkommission des Landes Oberösterreich                                            |
| e269491bb9c040aaad6a5f11df343f38  | Ethikkommission Krankenhaus Barmh.Brüder - Linz                                      |
| 1cca34032077445d95dabf7802fade28  | Ethikkommission Krankenhaus Barmh.Schwestern - Linz                                  |
| 39cbb589ef044d27bceb6ee5ac796ae   | Ethikkommission für das Bundesland Salzburg                                          |
| 280414583b894c809a9baa8134d7fe4b  | Ethikkommission der Medizinischen Universität Innsbruck                              |
| 183881da8200493aa7edd8bebeea75b9  | Ethikkommission des Landes Vorarlberg                                                |
| 95821eba88f34b2195f96e747d7f6b16  | Ethikkommission des Landes Burgenland gemäß KAG, AMG und MPG                         |
| 6e7cfab5f8cd40df83c9de4fac9bb20f  | Ethikkommission des Landes Steiermark gemäß AMG und MPG                              |
| 75b5a9714f354a5b842aa01029148036  | Ethikkommission Krankenhaus Barmh.Brüder - Graz                                      |
| 9287fb0878b94f9f9d90b5582d1cefc4  | Ethikkommission Krankenhaus Barmh.Brüder - Eggenberg                                 |
| e17ee744e4e840778f316cf3f79de6b4  | Ethikkommission der Medizinischen Universität Graz                                   |
| ec9f179a52a04a7aa52446232c3fd4bd  | Ethikkommission des Landes Kärnten                                                   |
| c890205dcb7543c8a76bf324512c5f8e  | Ethikkommission des Krankenhaus St. Josef                                            |
| dc1b115d9809461ba3ea9450b079dd46  | Kommission für Scientific Integrity und Ethik der Karl Landsteiner Privatuniversität |

## Activate Configuration

on the target vm:

```
create a empty ecs database
sudo -u postgres createdb ecs -T template0 -l de_DE.utf8

activate env and apply new environment settings
chmod 0600 /app/env.yml
cp /app/env.yml /run/active-env.yml
reboot
```

After the appliance has rebooted, it configures itself to the new environment. See the progress of the preparation by browsing to <https://domainname.domain> .

## First Internal User setup

After the appliance is ready and shows the login screen, login via ssh to create the first internal office user, with a corresponding client certificate and disable test user.

```
create first internal office user (f=female, m=male)
create-internal-user.sh useremail@domain.name "First Name" "Second Name" "f"
create and send matching client certificate
create-client-cert.sh useremail@domain.name cert_name [daysvalid]
Communicate certificate transport password over a secure channel

disable test user
cat << EOF | docker exec -i ecs_ecs.web_1 /start run ./manage.py shell
from django.contrib.auth.models import User
User.objects.filter(profile__is_testuser=True).update(is_active=False)
EOF
```

## Maintenance

### Reconfigure a running Appliance

- edit /app/env.yml
- optional, build new env package:
  - first time requisites install, call `env-package.sh --requirements`
  - build new env package call `env-package.sh /app/env.yml`
- activate changes into current environment, call `env-update.sh`
- restart and apply new environment: `systemctl restart appliance`

### Start, Stop & Update Appliance

- Start appliance: `systemctl start appliance`
- Stop appliance: `systemctl stop appliance`
- Update Appliance (appliance and ecs): `systemctl start appliance-update`

### Recover from failed state

if the `appliance.service` enters fail state, it creates a file named “/run/appliance\_failed”.

After resolving the issue, remove this file using `rm /run/appliance_failed` before running the service again using `systemctl restart appliance`.

### Desaster Recovery from backup

- install a new unconfigured appliance as described in chapter install
- copy old saved env.yml to new target machine at /app/env.yml
- reboot new target machine, appliance will configure but stop because of empty database
- ssh into new target machine, execute `recover-from-backup.sh --yes-i-am-sure`

## Automatic Updates

Updates are scheduled depending appliance:update:oncalendar once per day at 06:30 per default.

Depending the types of updates available the update will take between 1 and 5 minutes in most cases, 5-10 minutes if the ecs container will be rebuild and up to 30 minutes if there are database migrations to be executed.

The following items are updated:

- appliance source will be updated and executed
- all system packages are updated, special precautions are taken for docker, postgresql and the kernel including a reboot if needed
- lets encrypt certificates are updated
- ecs source will be updated and rebuild
  - the ecs-docs source will be updated
  - the corresponding support container will be updated
  - database migrations will be executed (including a dump before doing so)

**Warning:** Automatic updates are intended to run with Metric and Alert support, so you will get alerts to react and can investigate using the Metric Server to find the root cause. **If you do not make metric recording and alerting, we recommend updating only manual.** To do this, enter “False” under appliance:update:automatic in the file env.yml. For a manual update run call `systemctl start appliance-update`

## Backup Configuration

- Backup is done using duplicity, see [Duplicity Manual](#)
- Cycle: Backup is done once per day around 00:30
- Contents: It consists of a current database dump and the contents of /data/ecs-storage-vault
- Type, Rotation & Retention:
  - Backup will start with a full backup and do incremental backups afterwards
  - 2 Months after the first full backup a second full backup will be created
  - Rotation: Every Backup (full or incremental) will be purged after 4 Months

## Logging Configuration

Container:

- all container log to stdout and stderr
- docker has the logs of every container available
  - look at a log stream using eg. `docker logs ecs_ecs.web_1`
- journald will get the container logs via the appliance.service which calls docker-compose
  - this includes backend nginx, uwsgi, beat, worker, smtpd, redis, memcached, pdfas, mocca
  - to follow use `journalctl -u appliance -f`

Host:

- all logging (except postgres) is going through journald
- follow whole journal: `journalctl -f`
- only follow service, eg. prepare-appliance: `journalctl -u prepare-appliance -f`
- follow frontend nginx: `journalctl -u nginx -f`

- search for salt-call output: `journalctl $(which salt-call)`

## Metrics Collection

- if `appliance:metric:exporter` is set, metrics are exported from the subsystems
  - export metrics of: frontend nginx, redis, memcached, uwsgi, cadvisor, process details(uwsgi, postgres, nginx, celery), prometheus node(diskstats, entropy, filefd, filesystem, hwmon, loadavg, mdadm, meminfo, netdev, netstat, stat, textfile, time, uname, vmstat)
  - additional service metrics from: appliance-backup, appliance-update
- if `appliance:metric:server` is set, these exported metrics are collected and stored by a prometheus server and alerts are issued using email to root using the prometheus alert server
  - there are alerts for: NodeRebootsTooOften, NodeFilesystemFree, NodeMemoryUsageHigh, NodeLoadHigh
    - \* for a detailed alert list look at the [alert.rules sourcefile](#)
  - the prometheus gui is at <http://172.17.0.1:9090>
  - the prometheus alert gui is at <http://172.17.0.1:9093>
- if `appliance:metric:gui` is set, a grafana server is started to display the collected metrics
  - grafana is available at <http://localhost:3000>
- if `appliance:metric:pghero` is set, start a pghero instance for postgres inspection
  - pghero is available at <http://localhost:5081>

Use ssh port forwarding to access these ports, eg. for 172.17.0.1:9090 use `ssh root@hostname -L 9090:172.17.0.1:9090`

## Alerting Setup

if `ecs:settings["SENTRY_DSN"]` and `appliance:sentry:dsn` are defined, the appliance will report the following items to sentry:

- python exceptions in web, worker, beat, smtpd
- salt-call exceptions and state returns with error states
- systemd service exceptions where appliance-failed or service-failed is triggered
- shell calls to appliance.include: appliance\_failed, appliance\_exit, sentry\_entry
- internal mails to root, eg. prometheus alerts

## Email Challenges

### Mail send from ECS to Emailserver doing greylisting

Issue: Emails send from the appliance to a target mailserver that does greylisting will always delay mails and sometimes completely fail to deliver email at all.

Resolution: To make ECS working with these email domains, the greylisting whitelist of the target mailserver has to be extended with the domain of the ecs appliance.

Technical Background: The reason for this is that the appliance always uses a new unique email address for each outgoing mail and greylisting always delays the first email from an email address and sometimes blocks access to a whole domain if there are too many email addresses from one domain.

## maintenance commands in a running ecs container

for most ecs commands it is not important to which instance (web,worker) you connect to, “ecs\_ecs.web\_1” is used as example.

- image = ecs, mocca, pdfas, memcached, redis
- ecs.startcommand = web, worker, beat, smtpd
- as root `docker exec -it ecs_image[.startcommand]_1 /path/to/command`
  - eg. `docker exec -it ecs_ecs.web_1 /bin/bash`
- shell as app user with activated environment
  - `docker exec -it ecs_ecs.web_1 /start run /bin/bash`
- manually create a celery task:
  - `docker exec -it ecs_ecs.web_1 /start run celery --serializer=pickle -A ecs call ecs.integration.tasks.clearsessions`
- celery events console
  - `docker exec -it ecs_ecs.web_1 /start run /bin/bash -c "TERM=screen celery -A ecs events"`
- enter a django shell\_plus as app user in a running container
  - `docker exec -it ecs_ecs.web_1 /start run ./manage.py shell_plus`
- make all workflow graphs

```
docker exec -it ecs_ecs.web_1 /start run /bin/bash
./manage.py workflow_dot core.submission | dot -Tpng -osubmission.png
./manage.py workflow_dot notifications.notification | dot -Tpng -onotification.png
./manage.py workflow_dot votes.vote | dot -Tpng -ovote.png
```

- generate ECX-Format Documentation

```
docker exec -it ecs_ecs.web_1 /start run /bin/bash
./manage.py ecx_format -t html -o ecx-format.html
./manage.py ecx_format -t pdf -o ecx-format.pdf
```

## maintenance commands for the appliance host

All snippets expect root.

- destroy and recreate database:

```
gosu app dropdb ecs
gosu postgres createdb ecs -T template0 -l de_DE.utf8
rm /app/etc/tags/last_running_ecs
systemctl restart appliance
```

- get latest dump from backup to /root/ecs.pgdump.gz:
  - `duply /root/.duply/appliance-backup fetch ecs-pgdump/ecs.pgdump.gz /root/ecs.pgdump.gz`
- quick update appliance code:
  - `cd /app/appliance; gosu app git pull; salt-call state.highstate pillar='{"appliance":{"enabled":true}}' 2>&1; rm /var/www/html/503.html`
- check which system packages are available for update:



- /usr/lib/update-notifier/apt-check -p
- cleanup last activity stamps for unattended upgrades, so unattended-upgrades will do all activity again
  - rm /var/lib/apt/periodic/\*
  - or touch /app/etc/flags/force.update.system before systemctl start appliance-update
- list active systemd timer: systemctl list-timers --all
- display systemd service change: journalctl -m \_PID=1 -f
- manual run letsencrypt client (do not call as root): gosu app dehydrated --help
- display revoked certificates serials:
  - openssl crl -inform PEM -text -noout -in /app/etc/crl.pem
- get cumulative cpu,mem,net,disk statistics of container:
  - docker stats \$(docker ps|grep -v "NAMES"|awk '{ print \$NF }'|tr "\n" " ")
- read details of a container in yaml:
  - docker inspect 1b17069fe3ba | python -c 'import sys,yaml,json; yaml.safe\_dump(json.load(sys.stdin),sys.stdout,default\_flow\_style=False)' | less
- activate /run/active-env.yml in current shell of appliance vm:
  - . /usr/local/share/appliance/env.include; ENV\_YML=/run/active-env.yml userdata\_to\_env ecs,appliance
  - to also set \*GIT\_SOURCE defaults: . /usr/local/share/appliance/appliance.include
- most time spent in state.highstate:
  - journalctl -u appliance-update | grep -B 5 -E "Duration: [0-9]{3,5}\."
  - journalctl -u appliance-update | grep "ID:" -A6 | grep -E "(ID:|Function:|Duration:)" | sed -r "s/.\*(ID:|Function:|Duration)(.\*)/\1 \2/g" | paste -s -d ' \n' - | sed -r "s/ID: +([^\ ]+) Function: +([^\ ]+) Duration : ([^\ ]+ ms)/\3 \2 \1/g" | sort -n
- check send emails
  - for a in sent deferred bounced; do echo "#### \$a"; journalctl -u postfix | grep "status=\$a" | awk '{print \$7}' | sed 's/to=<\/g' | sed 's/>,\/g' | sort -n; done

## Digital signed pdf documents

The ECS uses Mocca and PDF-AS to create digital signed pdf documents.

Mocca and PDF-AS are developed by EGIZ, the eGovernment Innovation Centre of Austria a joint initiative of the Federal Chancellery and the Graz University of Technology, at the Institute for Applied Information Processing and Communications Technology (IAIK).

- [EGIZ Mocca](#) - a modular, open source citizen card environment
- [EGIZ PDF-AS](#) - a java framework for creating digital signatures on PDF documents

## Mocca

### Info:

- [Current Mocca: 1.3.23 \(2016-04-01\)](#)
- [Mocca Description](#)
- [Mocca Homepage](#)
- [bkucommon Configuration](#)
- [BKUOnline](#)
- [BKUOnline Deployment](#)
- [BKUOnline Configuration](#)
- [BKUOnline Upgrade Info](#)
- [Security Analysis of the Austrian Citizen Card Environment MOCCA and E-Card](#)

### Download:

- [Download Site](#)
- [bkuonline-1.3.23.war](#)

```
sha256=f43f49cbd7ef4df56741097ff5f0637a83cf6cb64701bc484633257ec122dc6a bkuonline-
→1.3.23.war
```

- Optional: [bkuwebstart-1.3.23.zip](#)

### Sourcecode:

- <http://git.egiz.gv.at/mocca>

## PDF-AS

### Info:

- [Current PDF-AS: 4.0.11 \(2016-07-01\)](#)
- [PDF-AS Description](#)
- [Documenation - DE](#)
- [Web Interface Documenation - DE](#)
- [External Service Documentation - DE](#)
- [Profile Documentation - DE](#)
- [Goverment Profile Documentation - DE](#)
- [PDF-AS Workshop Part 1 - DE](#)
- [PDF-AS Workshop Part 2 - DE](#)
- [Government sponsored Digital Signature Test Site - DE](#)

### Download:

- [Download Site](#)
- [pdf-as-web-4.0.11.war](#)

```
sha256=2008e413032fc926e30b2d666f4363707328a5171a4b170c0fb0599a4e894421 pdf-as-
→web-4.0.11.war
```

- Optional:

- pdf-as-web.properties
- defaultConfig.zip

Sourcecode:

- <http://git.egiz.gv.at/pdf-as-4/>
- automated builds from source

## Development

### Service Architecture

- Base: Ubuntu Xenial (16.04 LTS) 64Bit Standard Cloud Image
- saltstack salt is used for system installation
- letsencrypt is used for ssl host certificates
- Services running on the host system
  - Webserver: NGINX 1.10 - [nginx.conf](#)
  - Database: Postgresql 9.5 Database [postgres config](#)
  - SMTP/SSL Proxy: Stunnel - [stunnel.conf](#)
  - SSH Daemon: openssh [ssh config](#)
  - SMTP Outgoing: postfix - [main.cf](#)
- Services running inside docker container
  - The ECS Application (Web, Worker, incoming Mail)
    - \* Django is served via uwsgi inside the web container
    - \* Celery is used for asynchronous worker & beat
    - \* python smtpd is used for incoming Mail processing
  - Redis for Queuing Services
  - Memcache for Caching Services
  - tomcat running PDF/AS for Electronic Signed PDF Generation
  - tomcat running Mocca for accessing the Digital ID-Card used for signed PDF-Generation



## Repository Layout

| Path                                         | Description                                               |
|----------------------------------------------|-----------------------------------------------------------|
| /pillar/*.sls                                | salt environment                                          |
| /pillar/top.sls                              | defines the root of the environment tree                  |
| /pillar/default-env.sls                      | fallback env yaml and example localhost ecs config        |
| /salt/*.sls                                  | salt states (to be executed)                              |
| /salt/top.sls                                | defines the root of the state tree                        |
| /salt/common/init.sls                        | common install                                            |
| /salt/common/env-template.yml                | template used to generate a new env.yml                   |
| /salt/common/env-create.sh                   | cli for env generation                                    |
| /salt/common/env-package.sh                  | cli for building pdf,iso,tar.gz.gpg out of env            |
| /salt/common/env-update.sh                   | get env, test conversion and write to /run/active-env.yml |
| /salt/appliance/init.sls                     | ecs appliance install                                     |
| /salt/appliance/scripts/prepare-env.sh       | script started first to read environment                  |
| /salt/appliance/scripts/prepare-appliance.sh | script started next to setup services                     |
| /salt/appliance/scripts/prepare-ecs.sh       | script started next to build container                    |
| /salt/appliance/update/appliance-update.sh   | script triggerd from appliance-update.service             |
| /salt/appliance/ecs/docker-compose.yml       | main container group definition                           |
| /salt/appliance/systemd/appliance.service    | systemd appliance service that ties all together          |

## Execution Order

```
[on start]
|
|-- prepare-env
|-- prepare-appliance
| |
| |-- optional: call salt-call state.sls appliance.storage.setup
|---|
|
|-- prepare-ecs
|-- appliance
| |
| |-- docker-compose up
:
: (post-start)
|-- appliance-cleanup

[on error]
|
|-- appliance-failed

[on update]
|
|-- appliance-update
| |
| |-- salt-call state.highstate
| |-- letsencrypt update
| |-- apt-daily unattended-upgrades
? ?-- optional reboot
| |-- systemctl restart appliance
```

## Runtime Layout

Application:

| Path                       | Description                                                                       |
|----------------------------|-----------------------------------------------------------------------------------|
| /app/env.yml               | local (nocloud) environment configuration                                         |
| /app/ecs                   | ecs repository used for container creation                                        |
| /app/appliance             | ecs-appliance repository active on host                                           |
| /app/etc                   | runtime configuration (symlink of /data/etc)                                      |
| /app/etc/tags              | runtime tags                                                                      |
| /app/etc/flags             | runtime flags                                                                     |
| /app/ecs-ca                | client certificate ca and crt directory (symlink of /data/ecs-ca)                 |
| /app/ecs-gpg               | storage-vault gpg keys directory (symlink of /data/ecs-gpg)                       |
| /app/ecs-cache             | temporary storage directory (symlink of /volatile/ecs-cache)                      |
| /run/active-env.yml        | current activated configuration                                                   |
| /run/appliance-failed      | flag that needs to be cleared, before a restart of a failed appliance is possible |
| /usr/local/share/appliance | scripts from the appliance salt source                                            |
| /usr/local/[s]bin          | user callable programs                                                            |

Data:

| Path                    | Description                                       |
|-------------------------|---------------------------------------------------|
| /data                   | data to keep                                      |
| /data/ecs-ca            | symlink target of /app/ecs-ca                     |
| /data/ecs-gpg           | symlink target of /app/ecs-gpg                    |
| /data/ecs-storage-vault | symlink target of /app/ecs-storage-vault          |
| /data/etc               | symlink target of /app/etc                        |
| /data/ecs-pgdump        | database migration dump and backup dump directory |
| /data/postgresql        | referenced from moved /var/lib/postgresql         |

Volatile:

| Path                      | Description                                     |
|---------------------------|-------------------------------------------------|
| /volatile                 | data that can get deleted                       |
| /volatile/docker          | referenced from moved /var/lib/docker           |
| /volatile/ecs-cache       | Shared Cache Directory                          |
| /volatile/ecs-backup-test | default target directory of unconfigured backup |
| /volatile/redis           | redis container database volume                 |

## Container Volume Mapping

| Host-Path                | Container   | Container-Path                 |
|--------------------------|-------------|--------------------------------|
| /data/ecs-ca             | ecs         | /app/ecs-ca                    |
| /data/ecs-gpg            | ecs         | /app/ecs-gpg                   |
| /data/ecs-storage-vault  | ecs         | /app/ecs-storage-vault         |
| /volatile/ecs-cache      | ecs         | /app/ecs-cache                 |
| /app/etc/server.cert.pem | pdfas/mocca | /app/import/server.cert.pem:ro |

## Environment Mapping

Types of environments:

- saltstack get the environment as pillar either from /run/active-env.yml or from a default
- shell-scripts and executed programs from these shellscrips get a flattened yaml representation in the environment (see flatyaml.py) usually restricted to ecs,appliance tree of the yaml file

Buildtime Environment:

- the build time call of `salt-call state.highstate` does not need an environment, but will use /run/active-env.yml if available

Runtime Environment:

- prepare-env

- get a environment yaml from all local and network sources
  - writes the result to /run/active-env.yml
- appliance-update, prepare-appliance, prepare-ecs, appliance.service
  - parse /run/active-env.yml
  - include defaults from appliance.include (GIT\_SOURCE\*)
- Storage Setup (salt-call state.sls appliance.storage.setup) parses /run/active-env.yml
- appliance-update will call salt-call state.highstate which will use /run/active-env.yml
- appliance.service calls docker-compose up with active env from /run/active-env.yml
  - docker compose passes the following to the ecs/ecs\* container
    - \* service\_urls.env, database\_url.env
    - \* ECS\_SETTINGS
  - docker compose passes the following to the mocca and pdfas container
    - \* APPLIANCE\_DOMAIN as HOSTNAME