

Forget to remember
Remember to forget

Long Short Term Memories and Gated Recurrent Units


Kate Farrahi

Vision, Learning and Control
University of Southampton


Some of the slides, images and animations used here were originally designed by Jonathon Hare and Adam Prügel-Bennett.

Recap: RNN


one to one




one to many




many to one



many to many



many to many




Example Applications: image classification, image captioning, video classification, machine translation, language modeling

Image from <http://karpathy.github.io/2015/05/21/rnn-effectiveness/>

Recap: Vanilla or Elman RNN

Excluding bias terms



$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$$

$$y_t = W_{hy}h_t$$

Image from <https://web.eecs.umich.edu>

Recap: RNN Computational Graph (with Losses)

RNN Computational Graph (Many to Many)




Image from <https://web.eecs.umich.edu>

Example: Character-level language modelling






Image from <http://karpathy.github.io/2015/05/21/rnn-effectiveness/>

Vanishing and Exploding Gradients


$$y(t) = w_1 (x(t) + w_2 y(t-1))$$




Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$

$$w_1 = w_2 = 0.9$$




$x(t)$




Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$

$$w_1 = w_2 = 0.9$$





$x(t)$
 $y(t)$



Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



$$w_1 = w_2 = 0.9$$



Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



$$w_1 = w_2 = 0.9$$



Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



$$w_1 = w_2 = 0.9$$



Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



$$w_1 = w_2 = 0.9$$



Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



$$w_1 = w_2 = 0.9$$



Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



$$w_1 = w_2 = 0.9$$



Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



$$w_1 = w_2 = 0.9$$



Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



$$w_1 = w_2 = 0.9$$



Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



$$w_1 = w_2 = 0.9$$



Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



$$w_1 = w_2 = 1.1$$



Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



$$w_1 = w_2 = 1.1$$



Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



$$w_1 = w_2 = 1.1$$



Vanishing and Exploding Gradients


$$y(t) = w_1 (x(t) + w_2 y(t-1))$$

$$w_1 = w_2 = 1.1$$




Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$





$$w_1 = w_2 = 1.1$$





Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$





Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



Vanishing and Exploding Gradients

$$y(t) = w_1 (x(t) + w_2 y(t-1))$$



Vanishing and Exploding Gradients




Image from <https://web.eecs.umich.edu>

- LSTMs (long-short term memory) were designed to solve this problem

- LSTMs (long-short term memory) were designed to solve this problem
- Key ideas: to retain a 'long-term memory' requires

$$\mathbf{c}(t) = \mathbf{c}(t - 1)$$

- LSTMs (long-short term memory) were designed to solve this problem
- Key ideas: to retain a 'long-term memory' requires

$$\mathbf{c}(t) = \mathbf{c}(t - 1)$$

- Sometimes we have to forget and sometimes we have to change a memory

- LSTMs (long-short term memory) were designed to solve this problem
- Key ideas: to retain a 'long-term memory' requires

$$\mathbf{c}(t) = \mathbf{c}(t - 1)$$

- Sometimes we have to forget and sometimes we have to change a memory
- To do this we should use 'gates' that saturate at 0 and 1

- LSTMs (long-short term memory) were designed to solve this problem
- Key ideas: to retain a 'long-term memory' requires

$$\mathbf{c}(t) = \mathbf{c}(t - 1)$$


- Sometimes we have to forget and sometimes we have to change a memory
- To do this we should use 'gates' that saturate at 0 and 1
- Sigmoid functions naturally saturate at 0 and 1

LSTM Architecture




LSTM


LSTM Architecture




LSTM Architecture




LSTM Architecture




LSTM Architecture




LSTM Architecture




LSTM Architecture




LSTM Architecture




LSTM Architecture




LSTM Architecture




LSTM Architecture




LSTM Architecture




LSTM Architecture




LSTM Architecture




LSTM Architecture




LSTM Architecture



LSTM Architecture



LSTM Architecture



Update Equations

Initially, for $t = 0$, $\mathbf{h}(0) = \mathbf{0}$

- Inputs $\mathbf{z}(t) = (\mathbf{x}(t), \mathbf{h}(t - 1))$

Update Equations

Initially, for $t = 0$, $\mathbf{h}(0) = \mathbf{0}$

- Inputs $\mathbf{z}(t) = (\mathbf{x}(t), \mathbf{h}(t-1))$
- Network updates (\mathbf{W}_* and \mathbf{b}_* are the learnable parameters)

$$\mathbf{f}(t) = \sigma(\mathbf{W}_f \mathbf{z}(t) + \mathbf{b}_f)$$

$$\mathbf{i}(t) = \sigma(\mathbf{W}_i \mathbf{z}(t) + \mathbf{b}_i)$$

$$\mathbf{g}(t) = \tanh(\mathbf{W}_g \mathbf{z}(t) + \mathbf{b}_g)$$

$$\mathbf{o}(t) = \sigma(\mathbf{W}_o \mathbf{z}(t) + \mathbf{b}_o)$$

Update Equations

Initially, for $t = 0$, $\mathbf{h}(0) = \mathbf{0}$

- Inputs $\mathbf{z}(t) = (\mathbf{x}(t), \mathbf{h}(t-1))$
- Network updates (\mathbf{W}_* and \mathbf{b}_* are the learnable parameters)

$$\begin{aligned}\mathbf{f}(t) &= \sigma(\mathbf{W}_f \mathbf{z}(t) + \mathbf{b}_f) & \mathbf{i}(t) &= \sigma(\mathbf{W}_i \mathbf{z}(t) + \mathbf{b}_i) \\ \mathbf{g}(t) &= \tanh(\mathbf{W}_g \mathbf{z}(t) + \mathbf{b}_g) & \mathbf{o}(t) &= \sigma(\mathbf{W}_o \mathbf{z}(t) + \mathbf{b}_o)\end{aligned}$$

- Long-term memory update

$$\mathbf{c}(t) = \mathbf{f}(t) \odot \mathbf{c}(t-1) + \mathbf{g}(t) \odot \mathbf{i}(t)$$

Update Equations

Initially, for $t = 0$, $\mathbf{h}(0) = \mathbf{0}$

- Inputs $\mathbf{z}(t) = (\mathbf{x}(t), \mathbf{h}(t-1))$
- Network updates (\mathbf{W}_* and \mathbf{b}_* are the learnable parameters)

$$\begin{aligned}\mathbf{f}(t) &= \sigma(\mathbf{W}_f \mathbf{z}(t) + \mathbf{b}_f) & \mathbf{i}(t) &= \sigma(\mathbf{W}_i \mathbf{z}(t) + \mathbf{b}_i) \\ \mathbf{g}(t) &= \tanh(\mathbf{W}_g \mathbf{z}(t) + \mathbf{b}_g) & \mathbf{o}(t) &= \sigma(\mathbf{W}_o \mathbf{z}(t) + \mathbf{b}_o)\end{aligned}$$

- Long-term memory update

$$\mathbf{c}(t) = \mathbf{f}(t) \odot \mathbf{c}(t-1) + \mathbf{g}(t) \odot \mathbf{i}(t)$$

- Output $\mathbf{h}(t) = \mathbf{o}(t) \odot \tanh(\mathbf{c}(t))$

- We can train an LSTM by unwrapping it in time.

- We can train an LSTM by unwrapping it in time.
- Note that it involves four dense layers with sigmoidal (or tanh) outputs.

- We can train an LSTM by unwrapping it in time.
- Note that it involves four dense layers with sigmoidal (or tanh) outputs.
- This means that typically it is very slow to train.


- We can train an LSTM by unwrapping it in time.
- Note that it involves four dense layers with sigmoidal (or tanh) outputs.
- This means that typically it is very slow to train.
- There are a few variants of LSTMs, but all are very similar. The most popular is probably the Gated Recurrent Unit (GRU).

LSTM Success Stories

- LSTMs have been used to win many competitions in speech and handwriting recognition.
- Major technology companies including Google, Apple, and Microsoft are using LSTMs as fundamental components in products.
- Google used LSTM for speech recognition on the smartphone, for Google Translate.
- Apple uses LSTM for the "Quicktype" function on the iPhone and for Siri.
- Amazon uses LSTM for Amazon Alexa.
- In 2017, Facebook performed some 4.5 billion automatic translations every day using long short-term memory networks¹.

¹https://en.wikipedia.org/wiki/Long_short-term_memory

Gated Recurrent Unit (GRU)



Gated Recurrent Unit (GRU)

- $\mathbf{x}(t)$: input vector
- $\mathbf{h}(t)$: output vector (and 'hidden state')
- $\mathbf{r}(t)$: reset gate vector
- $\mathbf{z}(t)$: update gate vector
- $\mathbf{n}(t)$: new state vector (before update is applied)
- \mathbf{W} and \mathbf{b} : parameter matrices and biases

Gated Recurrent Unit (GRU)

Initially, for $t = 0$, $\mathbf{h}(0) = \mathbf{0}$

$$\mathbf{z}(t) = \sigma(\mathbf{W}_z(\mathbf{x}(t), \mathbf{h}(t-1)) + \mathbf{b}_z)$$

$$\mathbf{r}(t) = \sigma(\mathbf{W}_r(\mathbf{x}(t), \mathbf{h}(t-1)) + \mathbf{b}_r)$$

$$\mathbf{n}(t) = \tanh(\mathbf{W}_n(\mathbf{x}(t), \mathbf{r}(t) \odot \mathbf{h}(t-1)) + \mathbf{b}_h)$$

$$\mathbf{h}(t) = (1 - \mathbf{z}(t)) \odot \mathbf{h}(t-1) + \mathbf{z}(t) \odot \mathbf{n}(t)$$

Most implementations follow the original paper and swap $(1 - \mathbf{z}(t))$ and $(\mathbf{z}(t))$ in the $\mathbf{h}(t)$ update; this doesn't change the operation of the network, but does change the interpretation of the update gate, as the gate would have to produce a 0 when an update was to occur, and a 1 when no update is to happen (which is somewhat counter-intuitive)!

GRU or LSTM?

- GRUs have two gates (reset and update) whereas LSTM has three gates (input/output/forget)
- GRU performance on par with LSTM but computationally more efficient (less operations & weights).
- In general, if you have a very large dataset then LSTMs will likely perform slightly better.
- GRUs are a good choice for smaller datasets.