

Lesson 7: Make Friends with Trees



Binary trees, binary search trees, sets, tree iterators

AICE1005

Algorithms and Analysis

1

Trees

- Trees are one of the major ways of structuring data
- They are used in a vast number of data structures
 - Binary search trees
 - B-trees
 - splay trees
 - heaps
 - tries
 - suffix trees
- We shall cover most of these


AICE1005

Algorithms and Analysis

3

Borrowing from Nature

- We often impose an ordering on the nodes (or a direction on the edges)—known as a rooted tree
- Borrowing from nature, we recognise one node as the **root** node
- Nodes have **children** nodes living beneath them
- Each child has a **parent** node above them except the root
- Nodes with no children are **leaf** nodes




AICE1005

Algorithms and Analysis

5

Subtrees

- We can think of the tree made up of **subtrees**



AICE1005

Algorithms and Analysis

7

- Trees
 - Binary Trees
 - Implementing Binary Trees
 - Binary Search Trees
 - Definition
 - Implementing a Set
 - Tree Iterators




AICE1005

Algorithms and Analysis

2

Defining Trees


- Mathematically a tree is an **acyclic undirected graph**
 - graph**: a structure consisting of **nodes** or **vertices** joined by **edges**
 - undirected**: the edges goes both ways
 - acyclic**: there are no cycles in the graph



graph



undirected graph



tree = acyclic undirected graph


AICE1005

Algorithms and Analysis

4

Spot the Error

- One small biological inconsistency
- Yep!, computer scientists draw there trees upside down
 - root at the top
 - leaves at the bottom




AICE1005

Algorithms and Analysis

6

Level of Nodes

- It is useful to label different levels of the tree
- We take the **level** of a node in a tree as its distance from the root
- We take the **height** of a tree to be the number of levels



AICE1005

Algorithms and Analysis

7

AICE1005

Algorithms and Analysis


8

1. Trees
2. **Binary Trees**
 - Implementing Binary Trees
3. Binary Search Trees
 - Definition
 - Implementing a Set
4. Tree Iterators




- A **binary tree** is a tree where each node can have zero, one or two children
- The total number of possible nodes at level l is 2^l
- The total number of possible nodes of a tree of height h is

$$1 + 2 + \dots + 2^{h-1} = 2^h - 1$$



Uses of Binary Trees

- Binary trees have a huge number of applications
- For example, they are used as **expression trees** to represent formulae



Implementation


- We wish to build a generic binary tree class with each node housing an element
- Again we use a `Node<T>` class as the building block for our data structure—in this case a node of the tree
- The `Node<T>` class will contain a pointer to left and right children
- To help navigate the tree each node will contain a pointer to its parent

C++ Code

```
template <typename T>
class binary_tree {
private:
    class Node {
    public:
        T element;
        Node* parent;
        Node* left = 0;
        Node* right = 0;

        Node(const T& value, Node* parent_node) {
            element = value;
            parent = parent_node;
        }
    };

    unsigned no_elements = 0;
    Node* root = 0;
};
```



Outline


1. Trees
2. **Binary Trees**
 - Implementing Binary Trees
3. **Binary Search Trees**
 - Definition
 - Implementing a Set
4. Tree Iterators



Binary Search Trees

- We will concentrate on one of the most important binary trees, namely the **binary search tree**
- The binary search tree keeps the elements ordered
- We can define a binary search tree recursively
 1. Each element in the left subtree is less than the root element
 2. Each element in the right subtree is greater than the root element
 3. Both left and right subtrees are binary search trees

Example Binary Search Tree




Searching A Binary Search Tree

- Searching a binary search tree is easy

- Start at the root

- Compare with element

- If less than element go left
- If greater than element go right
- If equal to element found




AIICE1005

Algorithms and Analysis

17

Speed of Search

- The number of comparisons necessary to find an element in a binary tree depends on the level of the node in the tree
- The worst case number of comparisons is therefore the height of the tree
- This depends on the density of the tree



AIICE1005

Algorithms and Analysis

18

Implementing a Set

- A set is a fundamental abstract data type
- It is a collection of things with no repetition and no order
- Ironically because order doesn't matter we can order the elements

$\{1, 3, 5, 5, 3, 4\} = \{5, 3, 4, 1\} = \{1, 3, 4, 5\}$

- This allows rapid search—a feature we care about
- Binary trees are one of the efficient ways of implementing a set

AIICE1005

Algorithms and Analysis

19

Fitting In

- The standard template library provides a class `std::set<T>`
- This contains many functions like

- Constructors
- `size()`
- `insert(T o)`
- `find(Object o)`
- `erase(Object o)`
- `begin()` and `end()`

AIICE1005

Algorithms and Analysis

20

Comparable

- To sort any objects they must be comparable
- In the STL the set implementation has a second template parameter: `std::set<T, Compare = less<T> >`
- by default this is defined to be `less<T>` (which is a function already defined for most common types) which you can define
- If you have a set of complex objects you will have to define `Compare`

```
bool MyCompare(MyObject left, MyObject right) {
    return something;
}

mySet = set<MyObject, MyCompare>;
```

AIICE1005

Algorithms and Analysis

21

Find an Element

- One of the core operations of a binary tree is to find a node

```
iterator find(const T& element) {
    Node* current = root;
    while (current!=0) {
        if (current->element == element) {
            return iterator(current);
        }
        if (element < current->element) {
            current = current->left;
        } else {
            current = current->right;
        }
    }
    return iterator(0);
}
```

AIICE1005

Algorithms and Analysis

22

Add an Element

```
pair<iterator, bool> insert(const T& element) {
    if (no_elements==0) {
        root = new Node(element, 0);
        ++no_elements;
        return pair<iterator, bool>(iterator(root), true);
    }
    Node* parent = 0;
    Node* current = root;
    while(current != 0) {
        if (current->element == element) {
            return pair<iterator, bool>(iterator(0), false);
        }
        parent = current;
        if (element < current->element) {
            current = current->left;
        } else {
            current = current->right;
        }
    }
}
```

```
current = new Node(element, parent);
if (element < parent->element) {
    parent->left = current;
} else {
    parent->right = current;
}
++no_elements;
return pair<iterator, bool>(iterator(current), true);
}
```

AIICE1005

Algorithms and Analysis


23

AIICE1005

Algorithms and Analysis

24

Tree in Action



Shape of Tree

- The structure of the tree depends on the order in which we add elements to it
- Suppose we add
*To be, or not to be: that is the question:
Whether 'tis nobler in the mind to suffer
The slings and arrows of outrageous fortune,
Or to take arms against a sea of troubles,*
- Ignoring punctuation we get the following tree

AIICE1005

Algorithms and Analysis


25

AIICE1005

Algorithms and Analysis

26

Hamlet



AIICE1005

Algorithms and Analysis

27

Outline

- Trees
- Binary Trees
 - Implementing Binary Trees
- Binary Search Trees
 - Definition
 - Implementing a Set
- Tree Iterators



AIICE1005

Algorithms and Analysis

28

Tree Iterators

- As with most container classes it is very useful to define iterators
- `begin()` should return a "pointer" to the start of the tree
- `end()` provides a "pointer" past the end
- `operator*()` returns the element
- `operator++()` increments the "pointer"
- `operator!=(lhs, rhs)` is used to compare iterators

```

set<int> mySet;
...
for(auto pt=mySet.begin(), pt!=mySet.end(), ++pt) {
    cout << *pt;
}

```


AIICE1005

Algorithms and Analysis

29

Successor

- To find the successor we first start in the left most branch
- We follow two rules
 - If right child exist **then** move right once and then move as far left as possible
 - else** go **up** to the left as far as possible and then move up right



AIICE1005

Algorithms and Analysis

30

Lessons

- Trees and particularly binary trees are one of the most important tools of a computer scientist
- Conceptually they are quite simple
- However, there are a lot of details that need to be understood
- Coding even simple trees needs great care
- As we will see things get more complicated

AIICE1005

Algorithms and Analysis

31