

# Algorithms and Analysis

## Lesson 5: *Use Arrays*



*Variable length arrays, implementing stacks*

# Outline

1. **Why Arrays?**
2. Variable Length Arrays
3. Programming Language
4. Implementing Stacks



# Use Arrays

- An array is a contiguous chunk of memory
- In C we can create arrays using  
`int *array = new int[20]`
- The array has an access time of  $\Theta(1)$
- The constant factor is small (i.e. access time  $\approx 1$  time step)
- Arrays provide a very efficient use of memory
- 95% of the time using arrays is going to give you the best performance

# Use Arrays

- An array is a contiguous chunk of memory
- In C we can create arrays using  
`int *array = new int[20]`
- The array has an access time of  $\Theta(1)$
- The constant factor is small (i.e. access time  $\approx 1$  time step)
- Arrays provide a very efficient use of memory
- 95% of the time using arrays is going to give you the best performance

# Use Arrays

- An array is a contiguous chunk of memory
- In C we can create arrays using

```
int *array = new int[20]
```
- The array has an access time of  $\Theta(1)$
- The constant factor is small (i.e. access time  $\approx 1$  time step)
- Arrays provide a very efficient use of memory
- 95% of the time using arrays is going to give you the best performance

# Use Arrays

- An array is a contiguous chunk of memory
- In C we can create arrays using  
`int *array = new int[20]`
- The array has an access time of  $\Theta(1)$
- The constant factor is small (i.e. access time  $\approx 1$  time step)
- Arrays provide a very efficient use of memory
- 95% of the time using arrays is going to give you the best performance

# Use Arrays

- An array is a contiguous chunk of memory
- In C we can create arrays using

```
int *array = new int[20]
```
- The array has an access time of  $\Theta(1)$
- The constant factor is small (i.e. access time  $\approx 1$  time step)
- Arrays provide a very efficient use of memory
- 95% of the time using arrays is going to give you the best performance

# Use Arrays

- An array is a contiguous chunk of memory
- In C we can create arrays using

```
int *array = new int[20]
```
- The array has an access time of  $\Theta(1)$
- The constant factor is small (i.e. access time  $\approx 1$  time step)
- Arrays provide a very efficient use of memory
- 95% of the time using arrays is going to give you the best performance



# Use Arrays

- An array is a contiguous chunk of memory
- In C we can create arrays using

```
int *array = new int[20]
```
- The array has an access time of  $\Theta(1)$
- The constant factor is small (i.e. access time  $\approx 1$  time step)
- Arrays provide a very efficient use of memory
- 95% of the time using arrays is going to give you the best performance, **although never use raw arrays!**

# Disadvantages of Arrays

- Arrays have a fixed length
- Very often we don't know how big an array we want
  - ★ E.g. reading words from a file
- Adding or deleting elements from the middle of an array is costly
- Sorted arrays are expensive to maintain
- Arrays don't know how big they are

# Disadvantages of Arrays

- Arrays have a fixed length
- Very often we don't know how big an array we want
  - ★ E.g. reading words from a file
- Adding or deleting elements from the middle of an array is costly
- Sorted arrays are expensive to maintain
- Arrays don't know how big they are

# Disadvantages of Arrays

- Arrays have a fixed length
- Very often we don't know how big an array we want
  - ★ E.g. reading words from a file
- Adding or deleting elements from the middle of an array is costly
- Sorted arrays are expensive to maintain
- Arrays don't know how big they are

# Disadvantages of Arrays

- Arrays have a fixed length
- Very often we don't know how big an array we want
  - ★ E.g. reading words from a file
- Adding or deleting elements from the middle of an array is costly
- Sorted arrays are expensive to maintain
- Arrays don't know how big they are

# Disadvantages of Arrays

- Arrays have a fixed length
- Very often we don't know how big an array we want
  - ★ E.g. reading words from a file
- Adding or deleting elements from the middle of an array is costly
- Sorted arrays are expensive to maintain
- Arrays don't know how big they are

# Disadvantages of Arrays

- Arrays have a fixed length
- Very often we don't know how big an array we want
  - ★ E.g. reading words from a file
- Adding or deleting elements from the middle of an array is costly
- Sorted arrays are expensive to maintain
- Arrays don't know how big they are—**annoying**

# Outline

1. Why Arrays?
2. **Variable Length Arrays**
3. Programming Language
4. Implementing Stacks





# Variable Length Arrays

- We want a variable length array
- Initially a variable length array would have length zero
- We should be able to
  - ★ Add an element to an array
  - ★ Access any element in the array
  - ★ Change an element
  - ★ Delete elements
  - ★ Know how many elements we have

# Variable Length Arrays

- We want a variable length array
- Initially a variable length array would have length zero
- We should be able to
  - ★ Add an element to an array
  - ★ Access any element in the array
  - ★ Change an element
  - ★ Delete elements
  - ★ Know how many elements we have

# Variable Length Arrays

- We want a variable length array
- Initially a variable length array would have length zero
- We should be able to
  - ★ Add an element to an array
  - ★ Access any element in the array
  - ★ Change an element
  - ★ Delete elements
  - ★ Know how many elements we have

# ADT for a List

- What do we want of a list of `ints`?

# ADT for a List

- What do we want of a list of **ints**?
  - ★ **void** push\_back(**int** value)

# ADT for a List

- What do we want of a list of **ints**?
  - ★ **void** `push_back(int value)`
  - ★ random access `array[i]`

# ADT for a List

- What do we want of a list of **ints**?
  - ★ **void** push\_back(**int** value)
  - ★ random access `array[i]`
  - ★ **int** size()

# ADT for a List

- What do we want of a list of **ints**?
  - ★ **void** push\_back(**int** value)
  - ★ random access `array[i]`
  - ★ **int** size()
- It would be useful if it resized



# ADT for a List

- What do we want of a list of **ints**?
  - ★ **void** push\_back(**int** value)
  - ★ random access `array[i]`
  - ★ **int** size()
- It would be useful if it resized
- It would be great to have some algorithms (e.g. sort) that can be run on a list

# Implementation

- How should we implement a list?

# Implementation

- How should we implement a list?
- Use an array, of course!

# Implementation

- How should we implement a list?
- Use an array, of course!
- We need to distinguish between
  - ★ the number of elements in the list `size()`
  - ★ the number of elements in the array `capacity()`

# Implementation

- How should we implement a list?
- Use an array, of course!
- We need to distinguish between
  - ★ the number of elements in the list `size()`
  - ★ the number of elements in the array `capacity()`
- If the number of elements grows larger than the capacity then we need to increase the capacity

# Initial Capacity

- We could prevent resizing arrays by using a huge initial capacity
- However, how big is big enough?
- What happens when we have an array of arrays?
- Memory like time is resource we should care about
- In an analogy with **time complexity** we also care about **space complexity** (i.e. how much memory we need)
- If we want to store  $n$  elements it is reasonable to expect that we use  $cn$  bits of memory where we want to keep  $c$  small

# Initial Capacity

- We could prevent resizing arrays by using a huge initial capacity
- However, how big is big enough?
- What happens when we have an array of arrays?
- Memory like time is resource we should care about
- In an analogy with **time complexity** we also care about **space complexity** (i.e. how much memory we need)
- If we want to store  $n$  elements it is reasonable to expect that we use  $cn$  bits of memory where we want to keep  $c$  small

# Initial Capacity

- We could prevent resizing arrays by using a huge initial capacity
- However, how big is big enough?
- What happens when we have an array of arrays?
- Memory like time is resource we should care about
- In an analogy with **time complexity** we also care about **space complexity** (i.e. how much memory we need)
- If we want to store  $n$  elements it is reasonable to expect that we use  $cn$  bits of memory where we want to keep  $c$  small



# Initial Capacity

- We could prevent resizing arrays by using a huge initial capacity
- However, how big is big enough?
- What happens when we have an array of arrays?
- Memory like time is resource we should care about
- In an analogy with **time complexity** we also care about **space complexity** (i.e. how much memory we need)
- If we want to store  $n$  elements it is reasonable to expect that we use  $cn$  bits of memory where we want to keep  $c$  small

# Initial Capacity


- We could prevent resizing arrays by using a huge initial capacity
- However, how big is big enough?
- What happens when we have an array of arrays?
- Memory like time is resource we should care about
- In an analogy with **time complexity** we also care about **space complexity** (i.e. how much memory we need)
- If we want to store  $n$  elements it is reasonable to expect that we use  $cn$  bits of memory where we want to keep  $c$  small

# Initial Capacity

- We could prevent resizing arrays by using a huge initial capacity
- However, how big is big enough?
- What happens when we have an array of arrays?
- Memory like time is resource we should care about
- In an analogy with **time complexity** we also care about **space complexity** (i.e. how much memory we need)
- If we want to store  $n$  elements it is reasonable to expect that we use  $cn$  bits of memory where we want to keep  $c$  small


# Resizing Memory

- We start with some reasonable capacity




# Resizing Memory

- We start with some reasonable capacity
- We can add elements




# Resizing Memory

- We start with some reasonable capacity
- We can add elements



# Resizing Memory


- We start with some reasonable capacity
- We can add elements

`list.push_back(85)` 

31	35	85	
----	----	----	--

# Resizing Memory

- We start with some reasonable capacity
- We can add elements


`list.push_back(23)` 

31	35	85	23
----	----	----	----



# Resizing Memory


- We start with some reasonable capacity
- We can add elements until we reach the capacity

`list.push_back(62)` 

31	35	85	23
----	----	----	----

# Resizing Memory

- We start with some reasonable capacity
- We can add elements until we reach the capacity
- A simple method for resizing memory is
  - ★ create a new array with double the capacity of the old array



# Resizing Memory

- We start with some reasonable capacity
- We can add elements until we reach the capacity
- A simple method for resizing memory is
  - ★ create a new array with double the capacity of the old array
  - ★ copy the existing elements from the old array to the new array

`list.push_back(62)` → 

31	35	85	23
----	----	----	----



# Resizing Memory

- We start with some reasonable capacity
- We can add elements until we reach the capacity
- A simple method for resizing memory is
  - ★ create a new array with double the capacity of the old array
  - ★ copy the existing elements from the old array to the new array

`list.push_back(62)` → 

31	35	85	23
----	----	----	----

31	35						
----	----	--	--	--	--	--	--

# Resizing Memory

- We start with some reasonable capacity
- We can add elements until we reach the capacity
- A simple method for resizing memory is
  - ★ create a new array with double the capacity of the old array
  - ★ copy the existing elements from the old array to the new array

`list.push_back(62)` → 

31	35	85	23
----	----	----	----

31	35	85					
----	----	----	--	--	--	--	--

# Resizing Memory

- We start with some reasonable capacity
- We can add elements until we reach the capacity
- A simple method for resizing memory is
  - ★ create a new array with double the capacity of the old array
  - ★ copy the existing elements from the old array to the new array

`list.push_back(62)` → 

31	35	85	23
----	----	----	----

31	35	85	23				
----	----	----	----	--	--	--	--

# Resizing Memory

- We start with some reasonable capacity
- We can add elements until we reach the capacity
- A simple method for resizing memory is
  - ★ create a new array with double the capacity of the old array
  - ★ copy the existing elements from the old array to the new array

`list.push_back(62)` 

31	35	85	23				
----	----	----	----	--	--	--	--

# Resizing Memory

- We start with some reasonable capacity
- We can add elements until we reach the capacity
- A simple method for resizing memory is
  - ★ create a new array with double the capacity of the old array
  - ★ copy the existing elements from the old array to the new array

`list.push_back(62)` 

31	35	85	23	62			
----	----	----	----	----	--	--	--



# Amortised Time Analysis

- How efficient is resizing?
- Most `push_back(elem)` operations are  $\Theta(1)$
- When we are at full capacity we have to copy all elements
- Adding to a full array is slow but it is **amortised** by other quick adds

**amortised:** effect of a single operations 'deadened' by other operations

# Amortised Time Analysis

- How efficient is resizing?
- Most `push_back(elem)` operations are  $\Theta(1)$
- When we are at full capacity we have to copy all elements
- Adding to a full array is slow but it is **amortised** by other quick adds

**amortised:** effect of a single operations 'deadened' by other operations

# Amortised Time Analysis

- How efficient is resizing?
- Most `push_back(elem)` operations are  $\Theta(1)$
- When we are at full capacity we have to copy all elements
- Adding to a full array is slow but it is **amortised** by other quick adds

**amortised:** effect of a single operations 'deadened' by other operations

# Amortised Time Analysis

- How efficient is resizing?
- Most `push_back(elem)` operations are  $\Theta(1)$
- When we are at full capacity we have to copy all elements
- Adding to a full array is slow but it is **amortised** by other quick adds

**amortised:** effect of a single operations 'deadened' by other operations

# Amortised Time Analysis

- How efficient is resizing?
- Most `push_back(elem)` operations are  $\Theta(1)$
- When we are at full capacity we have to copy all elements
- Adding to a full array is slow but it is **amortised** by other quick adds

**amortised:** effect of a single operations 'deadened' by other operations

# Example

- If we have an initial capacity of 10 and add 100 elements then the number of operations needed is
  - ★ adds: 100

# Example

- If we have an initial capacity of 10 and add 100 elements then the number of operations needed is
  - ★ adds: 100
  - ★ copies: 10

# Example

- If we have an initial capacity of 10 and add 100 elements then the number of operations needed is
  - ★ adds: 100
  - ★ copies:  $10+20$



# Example

- If we have an initial capacity of 10 and add 100 elements then the number of operations needed is
  - ★ adds: 100
  - ★ copies:  $10+20+40$

# Example

- If we have an initial capacity of 10 and add 100 elements then the number of operations needed is
  - ★ adds: 100
  - ★ copies:  $10+20+40+80$

# Example

- If we have an initial capacity of 10 and add 100 elements then the number of operations needed is
  - ★ adds: 100
  - ★ copies:  $10+20+40+80=150$

# Example

- If we have an initial capacity of 10 and add 100 elements then the number of operations needed is
  - ★ adds: 100
  - ★ copies:  $10+20+40+80=150$
  - ★ **new int []**: 4

# Example


- If we have an initial capacity of 10 and add 100 elements then the number of operations needed is
  - ★ adds: 100
  - ★ copies:  $10+20+40+80=150$
  - ★ **new int** [ ]: 4
- 250 adds and copies operations + 4 **new** operations

# General Time Analysis

- If we perform  $N$  adds with an initial capacity of  $n$

# General Time Analysis


- If we perform  $N$  adds with an initial capacity of  $n$
- We must perform  $m$  copies where



$$n \times 2^{m-1} < N \leq n \times 2^m$$

# General Time Analysis

- If we perform  $N$  adds with an initial capacity of  $n$
- We must perform  $m$  copies where




$$n \times 2^{m-1} < N \leq n \times 2^m \quad \text{i.e.} \quad m = \left\lceil \log_2 \left( \frac{N}{n} \right) \right\rceil$$



# General Time Analysis

- If we perform  $N$  adds with an initial capacity of  $n$
- We must perform  $m$  copies where




$$n \times 2^{m-1} < N \leq n \times 2^m \quad \text{i.e.} \quad m = \left\lceil \log_2 \left( \frac{N}{n} \right) \right\rceil$$

- The number of elements copied is

$$n + 2n + 4n + \cdots + 2^{m-1}n$$

# General Time Analysis

- If we perform  $N$  adds with an initial capacity of  $n$
- We must perform  $m$  copies where




$$n \times 2^{m-1} < N \leq n \times 2^m \quad \text{i.e.} \quad m = \left\lceil \log_2 \left( \frac{N}{n} \right) \right\rceil$$

- The number of elements copied is

$$n + 2n + 4n + \cdots + 2^{m-1}n = n(1 + 2 + \cdots + 2^{m-1})$$

# General Time Analysis

- If we perform  $N$  adds with an initial capacity of  $n$
- We must perform  $m$  copies where




$$n \times 2^{m-1} < N \leq n \times 2^m \quad \text{i.e.} \quad m = \left\lceil \log_2 \left( \frac{N}{n} \right) \right\rceil$$

- The number of elements copied is

$$n + 2n + 4n + \cdots + 2^{m-1}n = n(1 + 2 + \cdots + 2^{m-1}) = n(2^m - 1)$$

# General Time Analysis

- If we perform  $N$  adds with an initial capacity of  $n$
- We must perform  $m$  copies where



$$n \times 2^{m-1} < N \leq n \times 2^m \quad \text{i.e.} \quad m = \left\lceil \log_2 \left( \frac{N}{n} \right) \right\rceil$$

- The number of elements copied is


$$n + 2n + 4n + \dots + 2^{m-1}n = n(1 + 2 + \dots + 2^{m-1}) = n(2^m - 1)$$

- Total number of operations is (using  $\lceil \log(a) \rceil < \log(a) + 1$ )

$$N + n(2^m - 1)$$

# General Time Analysis

- If we perform  $N$  adds with an initial capacity of  $n$
- We must perform  $m$  copies where



$$n \times 2^{m-1} < N \leq n \times 2^m \quad \text{i.e.} \quad m = \left\lceil \log_2 \left( \frac{N}{n} \right) \right\rceil$$

- The number of elements copied is


$$n + 2n + 4n + \dots + 2^{m-1}n = n(1 + 2 + \dots + 2^{m-1}) = n(2^m - 1)$$

- Total number of operations is (using  $\lceil \log(a) \rceil < \log(a) + 1$ )

$$N + n(2^m - 1) = N + n2^{\lceil \log_2(\frac{N}{n}) \rceil} - n$$

# General Time Analysis

- If we perform  $N$  adds with an initial capacity of  $n$
- We must perform  $m$  copies where



$$n \times 2^{m-1} < N \leq n \times 2^m \quad \text{i.e.} \quad m = \left\lceil \log_2 \left( \frac{N}{n} \right) \right\rceil$$

- The number of elements copied is


$$n + 2n + 4n + \dots + 2^{m-1}n = n(1 + 2 + \dots + 2^{m-1}) = n(2^m - 1)$$

- Total number of operations is (using  $\lceil \log(a) \rceil < \log(a) + 1$ )

$$N + n(2^m - 1) = N + n2^{\lceil \log_2(\frac{N}{n}) \rceil} - n < N + 2N - n$$

# General Time Analysis

- If we perform  $N$  adds with an initial capacity of  $n$
- We must perform  $m$  copies where



$$n \times 2^{m-1} < N \leq n \times 2^m \quad \text{i.e.} \quad m = \left\lceil \log_2 \left( \frac{N}{n} \right) \right\rceil$$

- The number of elements copied is

$$n + 2n + 4n + \dots + 2^{m-1}n = n(1 + 2 + \dots + 2^{m-1}) = n(2^m - 1)$$

- Total number of operations is (using  $\lceil \log(a) \rceil < \log(a) + 1$ )

$$N + n(2^m - 1) = N + n2^{\lceil \log_2(\frac{N}{n}) \rceil} - n < N + 2N - n < 3N$$

# Insertion and Deletion

- `vector<T>` is very useful and very fast for lots of things
- But if you try to insert or delete an element anywhere other than the end then you have to shove all the subsequent elements one space forward
- This is not the right data structure if you want to keep elements in order
- Linked lists allow you to splice in a sublist into a list in constant time



# Insertion and Deletion

- `vector<T>` is very useful and very fast for lots of things
- But if you try to insert or delete an element anywhere other than the end then you have to shove all the subsequent elements one space forward
- This is not the right data structure if you want to keep elements in order
- Linked lists allow you to splice in a sublist into a list in constant time

# Insertion and Deletion

- `vector<T>` is very useful and very fast for lots of things
- But if you try to insert or delete an element anywhere other than the end then you have to shove all the subsequent elements one space forward
- This is not the right data structure if you want to keep elements in order
- Linked lists allow you to splice in a sublist into a list in constant time

# Insertion and Deletion

- `vector<T>` is very useful and very fast for lots of things
- But if you try to insert or delete an element anywhere other than the end then you have to shove all the subsequent elements one space forward
- This is not the right data structure if you want to keep elements in order (binary trees will do that for you much more efficiently)
- Linked lists allow you to splice in a sublist into a list in constant time

# Insertion and Deletion

- `vector<T>` is very useful and very fast for lots of things
- But if you try to insert or delete an element anywhere other than the end then you have to shove all the subsequent elements one space forward
- This is not the right data structure if you want to keep elements in order (binary trees will do that for you much more efficiently)
- Linked lists allow you to splice in a sublist into a list in constant time

# Insertion and Deletion

- `vector<T>` is very useful and very fast for lots of things
- But if you try to insert or delete an element anywhere other than the end then you have to shove all the subsequent elements one space forward
- This is not the right data structure if you want to keep elements in order (binary trees will do that for you much more efficiently)
- Linked lists allow you to splice in a sublist into a list in constant time **although linked lists have a lot of drawbacks**

# Outline

1. Why Arrays?
2. Variable Length Arrays
3. **Programming Language**
4. Implementing Stacks



# Computer Languages

- Different computer languages are designed for different roles and have different advantages and disadvantages
- **C++** was designed to be fast (as fast as C)
- **Java** was designed to be very safe (avoiding lots of bugs)
- **Python** was designed so you can rapidly write powerful programmes with a small amount of code

# Computer Languages

- Different computer languages are designed for different roles and have different advantages and disadvantages
- **C++** was designed to be fast (as fast as C)
- **Java** was designed to be very safe (avoiding lots of bugs)
- **Python** was designed so you can rapidly write powerful programmes with a small amount of code



# Computer Languages

- Different computer languages are designed for different roles and have different advantages and disadvantages
- **C++** was designed to be fast (as fast as C), it pays the price of allowing bugs that hard to detect
- **Java** was designed to be vary safe (avoiding lots of bugs)
- **Python** was designed so you can rapidly write powerful programmes with a small amount of code

# Computer Languages

- Different computer languages are designed for different roles and have different advantages and disadvantages
- **C++** was designed to be fast (as fast as C), it pays the price of allowing bugs that hard to detect
- **Java** was designed to be very safe (avoiding lots of bugs)
- **Python** was designed so you can rapidly write powerful programmes with a small amount of code

# Computer Languages

- Different computer languages are designed for different roles and have different advantages and disadvantages
- **C++** was designed to be fast (as fast as C), it pays the price of allowing bugs that hard to detect
- **Java** was designed to be vary safe (avoiding lots of bugs), **but is not fast and a bit long winded**
- **Python** was designed so you can rapidly write powerful programmes with a small amount of code

# Computer Languages

- Different computer languages are designed for different roles and have different advantages and disadvantages
- **C++** was designed to be fast (as fast as C), it pays the price of allowing bugs that hard to detect
- **Java** was designed to be vary safe (avoiding lots of bugs), but is not fast and a bit long winded
- **Python** was designed so you can rapidly write powerful programmes with a small amount of code

# Computer Languages

- Different computer languages are designed for different roles and have different advantages and disadvantages
- **C++** was designed to be fast (as fast as C), it pays the price of allowing bugs that hard to detect
- **Java** was designed to be vary safe (avoiding lots of bugs), but is not fast and a bit long winded
- **Python** was designed so you can rapidly write powerful programmes with a small amount of code, but it is not fast or safe

# Problems with C++

- Amongst a number of issues that make C++ dangerous are
  - ★ Memory management
  - ★ Writing to parts of memory that you should not
  - ★ Multiple inheritance
- However, by using existing data structures (STL) and following established programming patterns these don't have to be an issue

# Problems with C++

- Amongst a number of issues that make C++ dangerous are
  - ★ Memory management
  - ★ Writing to parts of memory that you should not
  - ★ Multiple inheritance, **although you seldom need to do this**
- However, by using existing data structures (STL) and following established programming patterns these don't have to be an issue

# Problems with C++

- Amongst a number of issues that make C++ dangerous are
  - ★ Memory management
  - ★ Writing to parts of memory that you should not
  - ★ Multiple inheritance, although you seldom need to do this
- However, by using existing data structures (STL) and following established programming patterns these don't have to be an issue



# Memory Management

- Most programming languages have two types of memory

**The Stack:** is the area of memory controlled by compiler for local variables, function calls, etc.

**The Heap:** is area that the programmer (you) can request

# Memory Management

- Most programming languages have two types of memory

**The Stack:** is the area of memory controlled by compiler for local variables, function calls, etc.

**The Heap:** is area that the programmer (you) can request

# Memory Management

- Most programming languages have two types of memory

**The Stack:** is the area of memory controlled by compiler for local variables, function calls, etc.

**The Heap:** is area that the programmer (you) can request, which is nice

# Memory Management

- Most programming languages have two types of memory

**The Stack:** is the area of memory controlled by compiler for local variables, function calls, etc.

**The Heap:** is area that the programmer (you) can request, which is nice

- In C++ you are given the **right** to ask for memory

```
int *storage = new int[n];
```

# Memory Management

- Most programming languages have two types of memory

**The Stack:** is the area of memory controlled by compiler for local variables, function calls, etc.

**The Heap:** is area that the programmer (you) can request, which is nice

- In C++ you are given the **right** to ask for memory

```
int *storage = new int[n];
```

- You have **responsibility** to free the memory

```
delete[] storage;
```

# Trouble with Memory Management

- If you don't release memory acquired with `new` using `delete` you cause a **memory leak**
- Often memory leaks are no concern, but in large programs memory leaks will rapidly exhaust the computer's memory, slowing down the code and eventually leading to the programme crashing
- To release a block of memory we can use:  
`delete[] storage;`
- Now `storage` is a **dangling pointer** and must not be used as it is no longer valid
- If we accidentally delete the storage twice we get an *undefined behaviour*, but often the programme will crash

# Trouble with Memory Management

- If you don't release memory acquired with `new` using `delete` you cause a **memory leak**
- Often memory leaks are no concern, but in large programs memory leaks will rapidly exhaust the computer's memory, slowing down the code and eventually leading to the programme crashing
- To release a block of memory we can use:  
`delete[] storage;`
- Now `storage` is a **dangling pointer** and must not be used as it is no longer valid
- If we accidentally delete the storage twice we get an *undefined behaviour*, but often the programme will crash

# Trouble with Memory Management

- If you don't release memory acquired with `new` using `delete` you cause a **memory leak**
- Often memory leaks are no concern, but in large programs memory leaks will rapidly exhaust the computer's memory, slowing down the code and eventually leading to the programme crashing
- To release a block of memory we can use:  
`delete [] storage;`
- Now `storage` is a **dangling pointer** and must not be used as it is no longer valid
- If we accidentally delete the storage twice we get an *undefined behaviour*, but often the programme will crash



# Trouble with Memory Management

- If you don't release memory acquired with `new` using `delete` you cause a **memory leak**
- Often memory leaks are no concern, but in large programs memory leaks will rapidly exhaust the computer's memory, slowing down the code and eventually leading to the programme crashing
- To release a block of memory we can use:  
`delete[] storage;`
- Now `storage` is a **dangling pointer** and must not be used as it is no longer valid
- If we accidentally delete the storage twice we get an *undefined behaviour*, but often the programme will crash

# Trouble with Memory Management

- If you don't release memory acquired with `new` using `delete` you cause a **memory leak**
- Often memory leaks are no concern, but in large programs memory leaks will rapidly exhaust the computer's memory, slowing down the code and eventually leading to the programme crashing
- To release a block of memory we can use:  
`delete[] storage;`
- Now `storage` is a **dangling pointer** and must not be used as it is no longer valid
- If we accidentally delete the storage twice we get an *undefined behaviour*, but often the programme will crash

# Trouble with Memory Management

- If you don't release memory acquired with `new` using `delete` you cause a **memory leak**
- Often memory leaks are no concern, but in large programs memory leaks will rapidly exhaust the computer's memory, slowing down the code and eventually leading to the programme crashing
- To release a block of memory we can use:  
`delete[] storage;`
- Now `storage` is a **dangling pointer** and must not be used as it is no longer valid
- If we accidentally delete the storage twice we get an *undefined behaviour*, but often the programme will crash

# Resource Acquisition is Initialisation (RAII)

- Java and Python use garbage collectors which automatically checks whether memory can be accessed and if not it is removed
- In C++ this is your responsibility
- But there is a standard **programming pattern** to elevate the problem known as **Resource Acquisition is Initialisation (RAII)**

*Wrap all resources in classes. Request the resources in the constructor and release the resource in the destructor*

- When the object goes out of scope (you leave a `for` loop, function call, etc.) the destructor is called and the resource is safely released

# Resource Acquisition is Initialisation (RAII)

- Java and Python use garbage collectors which automatically checks whether memory can be accessed and if not it is removed
- In C++ this is your responsibility
- But there is a standard **programming pattern** to elevate the problem known as **Resource Acquisition is Initialisation (RAII)**

*Wrap all resources in classes. Request the resources in the constructor and release the resource in the destructor*

- When the object goes out of scope (you leave a `for` loop, function call, etc.) the destructor is called and the resource is safely released

# Resource Acquisition is Initialisation (RAII)

- Java and Python use garbage collectors which automatically checks whether memory can be accessed and if not it is removed
- In C++ this is your responsibility
- But there is a standard **programming pattern** to elevate the problem known as **Resource Acquisition is Initialisation (RAII)**

*Wrap all resources in classes. Request the resources in the constructor and release the resource in the destructor*

- When the object goes out of scope (you leave a `for` loop, function call, etc.) the destructor is called and the resource is safely released

# Resource Acquisition is Initialisation (RAII)

- Java and Python use garbage collectors which automatically checks whether memory can be accessed and if not it is removed
- In C++ this is your responsibility
- But there is a standard **programming pattern** to elevate the problem known as **Resource Acquisition is Initialisation (RAII)**

*Wrap all resources in classes. Request the resources in the constructor and release the resource in the destructor*

- When the object goes out of scope (you leave a `for` loop, function call, etc.) the destructor is called and the resource is safely released

# Resource Acquisition is Initialisation (RAII)

- Java and Python use garbage collectors which automatically checks whether memory can be accessed and if not it is removed
- In C++ this is your responsibility
- But there is a standard **programming pattern** to elevate the problem known as **Resource Acquisition is Initialisation (RAII)**

*Wrap all resources in classes. Request the resources in the constructor and release the resource in the destructor*

- When the object goes out of scope (you leave a `for` loop, function call, etc.) the destructor is called and the resource is safely released



# Writing over Memory

- In C++ the following will compile and run

```
int *array = new int[4];  
int *a = new int[2];  
double *darray = new double[4];  
array[4] = 4;
```

- However `array[4]` has not been assigned (unlike `array[0]`, `array[1]`, `array[2]` and `array[3]`)
- The memory on the heap corresponding to the address of `array[4]` might have been assigned to `a[0]` in which case you may inadvertently have set `a[0]` to 4 leading to the program not doing what you want
- It might be that you have put an `int` into `darray[0]` which will then crash the system when you read `darray[0]`

# Writing over Memory

- In C++ the following will compile and run

```
int *array = new int[4];  
int *a = new int[2];  
double *darray = new double[4];  
array[4] = 4;
```

- However `array[4]` has not been assigned (unlike `array[0]`, `array[1]`, `array[2]` and `array[3]`)
- The memory on the heap corresponding to the address of `array[4]` might have been assigned to `a[0]` in which case you may inadvertently have set `a[0]` to 4 leading to the program not doing what you want
- It might be that you have put an `int` into `darray[0]` which will then crash the system when you read `darray[0]`

# Writing over Memory

- In C++ the following will compile and run

```
int *array = new int[4];  
int *a = new int[2];  
double *darray = new double[4];  
array[4] = 4;
```

- However `array[4]` has not been assigned (unlike `array[0]`, `array[1]`, `array[2]` and `array[3]`)
- The memory on the heap corresponding to the address of `array[4]` might have been assigned to `a[0]` in which case you may inadvertently have set `a[0]` to 4 leading to the program not doing what you want
- It might be that you have put an `int` into `darray[0]` which will then crash the system when you read `darray[0]`

# Writing over Memory

- In C++ the following will compile and run

```
int *array = new int[4];  
int *a = new int[2];  
double *darray = new double[4];  
array[4] = 4;
```

- However `array[4]` has not been assigned (unlike `array[0]`, `array[1]`, `array[2]` and `array[3]`)
- The memory on the heap corresponding to the address of `array[4]` might have been assigned to `a[0]` in which case you may inadvertently have set `a[0]` to 4 leading to the program not doing what you want
- It might be that you have put an `int` into `darray[0]` which will then crash the system when you read `darray[0]`

# Guarding Against Mistakes

- These are really hard problems to debug because where the program goes wrong or crashes can be very far from the assignment that caused the error
- Java takes the approach that it always tests whether you are writing in valid memory
- By default C++ doesn't even for data structures—making this check slows down random access
- Checks can also make pipeline optimisations harder to make
- The onus is on the user to use the memory correctly

# Guarding Against Mistakes

- These are really hard problems to debug because where the program goes wrong or crashes can be very far from the assignment that caused the error
- Java takes the approach that it always tests whether you are writing in valid memory
- By default C++ doesn't even for data structures—making this check slows down random access
- Checks can also make pipeline optimisations harder to make
- The onus is on the user to use the memory correctly

# Guarding Against Mistakes

- These are really hard problems to debug because where the program goes wrong or crashes can be very far from the assignment that caused the error
- Java takes the approach that it always tests whether you are writing in valid memory
- By default C++ doesn't even for data structures—making this check slows down random access
- Checks can also make pipeline optimisations harder to make
- The onus is on the user to use the memory correctly

# Guarding Against Mistakes

- These are really hard problems to debug because where the program goes wrong or crashes can be very far from the assignment that caused the error
- Java takes the approach that it always tests whether you are writing in valid memory
- By default C++ doesn't even for data structures—making this check slows down random access
- Checks can also make pipeline optimisations harder to make
- The onus is on the user to use the memory correctly



# Guarding Against Mistakes

- These are really hard problems to debug because where the program goes wrong or crashes can be very far from the assignment that caused the error
- Java takes the approach that it always tests whether you are writing in valid memory
- By default C++ doesn't even for data structures—making this check slows down random access
- Checks can also make pipeline optimisations harder to make
- The onus is on the user to use the memory correctly

# Guarding Against Mistakes

- These are really hard problems to debug because where the program goes wrong or crashes can be very far from the assignment that caused the error
- Java takes the approach that it always tests whether you are writing in valid memory
- By default C++ doesn't even for data structures—making this check slows down random access
- Checks can also make pipeline optimisations harder to make
- The onus is on the user to use the memory correctly

# Follow Programming Idioms

- Using common data structures and following common idioms will prevent most errors

```
int n = 5;  
vector<int> array(n);
```

```
for(int i=0; i<array.size(); ++i) {  
    array[i] = i;  
}
```

```
for(auto pt=array.begin(); pt != array.end(); ++pt){  
    *pt *= 2  
}
```

```
for(int& element: array) {  
    element += 2;  
}
```

# Follow Programming Idioms

- Using common data structures and following common idioms will prevent most errors

```
int n = 5;  
vector<int> array(n);
```

```
for(int i=0; i<array.size(); ++i) {  
    array[i] = i;  
}
```

```
for(auto pt=array.begin(); pt != array.end(); ++pt){  
    *pt *= 2  
}
```

```
for(int& element: array) {  
    element += 2;  
}
```

# Follow Programming Idioms

- Using common data structures and following common idioms will prevent most errors

```
int n = 5;  
vector<int> array(n);
```

```
for(int i=0; i<array.size(); ++i) {  
    array[i] = i;  
}
```

```
for(auto pt=array.begin(); pt != array.end(); ++pt){  
    *pt *= 2  
}
```

```
for(int& element: array) {  
    element += 2;  
}
```

# Outline

1. Why Arrays?
2. Variable Length Arrays
3. Programming Language
4. **Implementing Stacks**



# Stacks

- Lets look at implementing a stack
- Remember a stack has methods
  - ★ `push (Object )`
  - ★ `pop ()`
  - ★ `top ()`
  - ★ `empty ()`

# Stacks

- Lets look at implementing a stack
- Remember a stack has methods
  - ★ `push (Object )`
  - ★ `pop ()`
  - ★ `top ()`
  - ★ `empty ()`



# Implementation of Stack

```
template <typename T>
class MyStack
{
private:
    std::vector<T> stack;

public:
    void push(const T& obj) {stack.push_back(obj);}

    T top() const {return stack.back();}

    T pop() {
        T tmp = stack.back();
        stack.pop_back();
        return tmp;
    }

    T empty() {return stack.size()==0;}
};
```

# Implementation of Stack

```
template <typename T>
class MyStack
{
private:
    std::vector<T> stack;

public:
    void push(const T& obj) {stack.push_back(obj);}

    T top() const {return stack.back();}

    T pop() {
        T tmp = stack.back();
        stack.pop_back();
        return tmp;
    }

    T empty() {return stack.size()==0;}
};
```

# Implementation of Stack

```
template <typename T>
class MyStack
{
private:
    std::vector<T> stack;

public:
    void push(const T& obj) {stack.push_back(obj);}

    T top() const {return stack.back();}

    T pop() {
        T tmp = stack.back();
        stack.pop_back();
        return tmp;
    }

    T empty() {return stack.size()==0;}
};
```

# Implementation of Stack

```
template <typename T>
class MyStack
{
private:
    std::vector<T> stack;

public:
    void push(const T& obj) {stack.push_back(obj);}

    T top() const {return stack.back();}

    T pop() {
        T tmp = stack.back();
        stack.pop_back();
        return tmp;
    }

    T empty() {return stack.size()==0;}
};
```

# Implementation of Stack

```
template <typename T>
class MyStack
{
private:
    std::vector<T> stack;

public:
    void push(const T& obj) {stack.push_back(obj);}

    T top() const {return stack.back();}

    T pop() {
        T tmp = stack.back();
        stack.pop_back();
        return tmp;
    }

    T empty() {return stack.size()==0;}
};
```

# Notes on Implementation

- I don't need to write a constructor as C++ generates a default constructor that will initialise the stack correctly
- I don't need to write a desctuctor because by default the destructor for `vector<T>` will be called which releases memory
- I've written the `pop` command, that I like, but if I run

```
stack<Widget> widget_stack;  
Widget w;  
widget_stack.push(w);  
Widget w1(widget.pop());
```

if the last command throws an exception then the last term on the stack is lost for ever

# Notes on Implementation

- I don't need to write a constructor as C++ generates a default constructor that will initialise the stack correctly
- I don't need to write a desctuctor because by default the destructor for `vector<T>` will be called which releases memory
- I've written the `pop` command, that I like, but if I run

```
stack<Widget> widget_stack;  
Widget w;  
widget_stack.push(w);  
Widget w1(widget.pop());
```

if the last command throws an exception then the last term on the stack is lost for ever

# Notes on Implementation

- I don't need to write a constructor as C++ generates a default constructor that will initialise the stack correctly
- I don't need to write a desctuctor because by default the destructor for `vector<T>` will be called which releases memory
- I've written the `pop` command, that I like, but if I run

```
stack<Widget> widget_stack;  
Widget w;  
widget_stack.push(w);  
Widget w1(widget.pop());
```

if the last command throws an exception then the last term on the stack is lost for ever



# Why not use a vector

- Surely it is mad to use `MyStack<T>` as I could just use the more powerful `vector<T>`
- I can make `MyStack<T>` as efficient as `vector<T>` by inlining function calls
- But why would I want to lose functional?
- By using `MyStack<T>` I am **declaring my intention** of using this data structure as a stack
- I'm not going to do something weird like modify an element inside the stack
- My code becomes self-explanatory

# Why not use a vector

- Surely it is mad to use `MyStack<T>` as I could just use the more powerful `vector<T>`
- I can make `MyStack<T>` as efficient as `vector<T>` by inlining function calls
- But why would I want to lose functional?
- By using `MyStack<T>` I am **declaring my intention** of using this data structure as a stack
- I'm not going to do something weird like modify an element inside the stack
- My code becomes self-explanatory

# Why not use a vector

- Surely it is mad to use `MyStack<T>` as I could just use the more powerful `vector<T>`
- I can make `MyStack<T>` as efficient as `vector<T>` by inlining function calls
- But why would I want to lose functional?
- By using `MyStack<T>` I am **declaring my intention** of using this data structure as a stack
- I'm not going to do something weird like modify an element inside the stack
- My code becomes self-explanatory

# Why not use a vector

- Surely it is mad to use `MyStack<T>` as I could just use the more powerful `vector<T>`
- I can make `MyStack<T>` as efficient as `vector<T>` by inlining function calls
- But why would I want to lose functional?
- By using `MyStack<T>` I am **declaring my intention** of using this data structure as a stack
- I'm not going to do something weird like modify an element inside the stack
- My code becomes self-explanatory

# Why not use a vector

- Surely it is mad to use `MyStack<T>` as I could just use the more powerful `vector<T>`
- I can make `MyStack<T>` as efficient as `vector<T>` by inlining function calls
- But why would I want to lose functional?
- By using `MyStack<T>` I am **declaring my intention** of using this data structure as a stack
- I'm not going to do something weird like modify an element inside the stack
- My code becomes self-explanatory

# Why not use a vector

- Surely it is mad to use `MyStack<T>` as I could just use the more powerful `vector<T>`
- I can make `MyStack<T>` as efficient as `vector<T>` by inlining function calls
- But why would I want to lose functional?
- By using `MyStack<T>` I am **declaring my intention** of using this data structure as a stack
- I'm not going to do something weird like modify an element inside the stack
- My code becomes self-explanatory

# Why not use a vector

- Surely it is mad to use `MyStack<T>` as I could just use the more powerful `vector<T>`
- I can make `MyStack<T>` as efficient as `vector<T>` by inlining function calls
- But why would I want to lose functional?
- By using `MyStack<T>` I am **declaring my intention** of using this data structure as a stack
- I'm not going to do something weird like modify an element inside the stack
- My code becomes self-explanatory—I don't need to write comments as it is clear what I am doing

# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial



# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications


# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file


you can cage a swallow can't you



# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

can cage a swallow can't you



# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

cage a swallow can't you



can  
you

# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

a swallow can't you

cage  
can  
you

# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

swallow can't you

a  
cage  
can  
you

# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

can't you

swallow  
a  
cage  
can  
you



# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

you

can't  
swallow  
a  
cage  
can  
you

# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

you  
can't  
swallow  
a  
cage  
can  
you

# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

you

can't  
swallow  
a  
cage  
can  
you

# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file


you can't

swallow  
a  
cage  
can  
you

# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

you can't swallow



a  
cage  
can  
you

# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

you can't swallow a



cage  
can  
you

# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

you can't swallow a cage




can  
you

# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

you can't swallow a cage can






# Using MyStack

- Implementing a stack using a dynamically re-sizable array is trivial
- Stacks have many applications
- E.g. suppose we want to write a program to reverse the order of strings in a file

you can't swallow a cage can you



# Reversing Strings in File

```
#include <stack>
#include <iostream>
#include <fstream>
using namespace std;

int main(int argc, char *argv[]) {
    ifstream in(argv[1]);

    stack<string> stack;

    string word;
    while (in >> word)
        stack.push(word);

    while(!stack.empty()) {
        cout << stack.top() << ' ';
        stack.pop();
    }
}
```

# Lessons

- Arrays are very efficient both in space (memory) and access time
- Resizing an array is not that costly
- insertion and deletion are expensive,  $O(n)$
- Arrays are often the simplest way to implement many other data structures, e.g. stacks
- Use (dynamically re-sizable) arrays (vector) frequently!

# Lessons

- Arrays are very efficient both in space (memory) and access time
- Resizing an array is not that costly
- insertion and deletion are expensive,  $O(n)$
- Arrays are often the simplest way to implement many other data structures, e.g. stacks
- Use (dynamically re-sizable) arrays (vector/T<sub>i</sub>) frequently!

# Lessons

- Arrays are very efficient both in space (memory) and access time
- Resizing an array is not that costly
- insertion and deletion are expensive,  $O(n)$
- Arrays are often the simplest way to implement many other data structures, e.g. stacks
- Use (dynamically re-sizable) arrays (vector) frequently!

# Lessons

- Arrays are very efficient both in space (memory) and access time
- Resizing an array is not that costly
- insertion and deletion are expensive,  $O(n)$
- Arrays are often the simplest way to implement many other data structures, e.g. stacks
- Use (dynamically re-sizable) arrays (vector) frequently!

# Lessons

- Arrays are very efficient both in space (memory) and access time
- Resizing an array is not that costly
- insertion and deletion are expensive,  $O(n)$
- Arrays are often the simplest way to implement many other data structures, e.g. stacks
- Use (dynamically re-sizable) arrays (vector,  $\text{ArrayList}$ ) frequently!