

Lesson 16: *Analyse!*

Pseudo code, binary search, insertion sort, selection sort, lower bound complexity

AICE1005

Algorithms and Analysis

1

Algorithm Analysis

- We've covered most of the basic data structures
- The rest of the course is going to focus more on algorithms
- We will look predominantly at
 - ★ Searching
 - ★ Sorting
 - ★ Graph Algorithms
- Emphasise general solution strategies

AICE1005

Algorithms and Analysis

3

Pseudo Code

- There is no standard for pseudo code
- The commands are not too dissimilar to C++
- The one strange convention is that assignments use an arrow \leftarrow
- Arrays are written in bold a with elements a_i
- In pseudo-code you are free to invent any operations that can be easily interpreted

AICE1005

Algorithms and Analysis

5

Dumb Search

```

DUMBSEARCH(a, x)
{
  /* search array a = (a1, ..., an) */
  /* for x return true */
  /* if successful else false */
  for i ← 1 to n
    if (ai = x)
      return true
    endif
  endfor
  return false
}


```

```

bool search(T a[], T x)
{
  for (int i=0; i<n; i++) {
    if (a[i] == x)
      return true;
  }
  return false;
}

```

find(12) \rightarrow false



AICE1005

Algorithms and Analysis

7

1. Algorithm Analysis
2. Search
3. Simple Sort
 - Insertion Sort
 - Selection Sort
4. Lower Bound



AICE1005

Algorithms and Analysis

2

Code and Pseudo Code

- C++ code is often difficult to read—there are often programming details we don't care about
- It contains details such as throwing exception which are repetitive and often depends on who you are writing the code for
- Algorithms are not language dependent (data structures are a bit more language dependent)
- To focus on what is important we will use a stylised programming language called **pseudo code**

AICE1005

Algorithms and Analysis

4

Outline

1. Algorithm Analysis
2. Search
3. Simple Sort
 - Insertion Sort
 - Selection Sort
4. Lower Bound



AICE1005

Algorithms and Analysis

6

Time Complexity

- Worst case:
 - ★ The worst case for a successful search is when the element is in the last location in the array
 - ★ This takes n comparisons: worst case is $\Theta(n)$
- Best case:
 - ★ The best case is when the element is in the first location
 - ★ This takes 1 comparison: best case is $\Theta(1)$
- Average case:
 - ★ Assume every location is equally likely to hold the key

$$\frac{1 + 2 + \dots + n}{n} = \frac{1}{n} \sum_{i=1}^n i = \frac{1}{n} \times \frac{n(n+1)}{2} = \frac{n+1}{2}$$

- For an unsuccessful search n comparison are necessary

AICE1005

Algorithms and Analysis

8

Binary Search

- If the array is ordered we can do better

- At each step we bisect the array

```
BINARYSEARCH(a, x)
```

```
{
  low ← 1
  high ← n
  while (low ≤ high)
    mid ← ⌊(low + high)/2⌋
    if x > amid
      low ← mid + 1
    elseif x < amid
      high ← mid - 1
    else
      return true
    endif
  endwhile
  return false
}
```

★ Based on a **divide-and-conquer** strategy

★ We check the middle of the array

$a_1, a_2, \dots, a_{m-1}, \overbrace{a_m}^{x=a_m}, a_{m+1}, \dots, a_n$

$x < a_m$ $x > a_m$

★ Based on a recursive idea

AIICE1005

Algorithms and Analysis

9

Analysis

- We count the number of comparisons (counting each if/else if statement as a single comparison)
- Let $C(n)$ be the number of comparisons needed to search in an array of size n
- After one comparison we are left (in the worst case) with having to search an array not larger than $\lfloor n/2 \rfloor$ thus

$$C(n) < C(\lfloor n/2 \rfloor) + 1$$

- We've seen this relation before (lesson on Recursion)
- Easy to show $C(n) < \lfloor \log_2(n) \rfloor + 1 = O(\log(n))$

AIICE1005

Algorithms and Analysis

11

Sort Characteristics

- Sort is one of the best studied algorithms. We care about stability, space and time complexity
- A sort algorithm is said to be **stable** if it does not change the order of elements that have the same value
- Space Complexity. Sort is said to be
 - ★ **In-place** if the memory used is $O(1)$
- Time Complexity. In particular we are interested in
 - ★ Worst case
 - ★ Average case
 - ★ Best case

AIICE1005

Algorithms and Analysis

13

Properties of Insertion Sort

- Insertion sort is **stable**. We only swap the ordering of two elements if one is strictly less than the other
- It is **in-place**
- Worst time complexity
 - ★ Occurs when the array is in inverse order
 - ★ Every element has to be moved to front of the array
 - ★ Number of comparisons for an array of size $C_w(n)$

$$C_w(n) = \sum_{i=2}^n (i-1) = 1 + 2 + \dots + n-1 = \frac{n(n-1)}{2} \in \Theta(n^2)$$

AIICE1005

Algorithms and Analysis

15

Binary Search in Action

BINARYSEARCH(a, 90)

not found

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low		high	mid	high	mid		high	mid	low			mid	high	low	mid	high	mid	high	low

AIICE1005

Algorithms and Analysis

10

Outline

- Algorithm Analysis
- Search
- Simple Sort
 - ★ Insertion Sort
 - ★ Selection Sort
- Lower Bound



AIICE1005

Algorithms and Analysis

12

Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
```

```
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```

23	37	39	50	66	69	69	74	84	90
----	----	----	----	----	----	----	----	----	----

sorted unsorted

AIICE1005

Algorithms and Analysis

14

Time Complexity

- Average Time Complexity
 - ★ On average we can expect that each new element being sorted moves half the way down sorted list
 - ★ This gives us an average time complexity, $C_a(n)$ of half the worst time

$$C_a(n) = \frac{n(n-1)}{4} \in \Theta(n^2)$$

- Best Time Complexity
 - ★ This occurs if the array is already sorted
 - ★ In this case we only need $C_b(n) = n - 1 \in \Theta(n)$ comparisons
- Insertion sort is a good sort for small arrays because it is stable, in-place and is efficient when the arrays are almost sorted

AIICE1005


Algorithms and Analysis

16

Selection Sort


- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n-1
    min ← i
    for j ← i+1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```




Analysis of Selection Sort

- Selection sort is in-place
- It isn't stable



- Selection sort always requires $n(n-1)/2$ comparisons so has the same worst case, but worse average case and best case complexity as insertion sort
- It only performs $n-1$ swaps—this makes it attractive (insertion sort moved more elements)

Insertion versus Selection Sort



Bubble Sort

- There are many other simple sort strategies
- One popular one is bubble sort—keep on swapping neighbours until the array is sorted
- It is stable and in-place
- This again has $O(n^2)$ complexity
- This isn't bad for a simple sort, but it does do more work than insertion sort and selection sort
- Apart from its name it just doesn't have anything going for it


Outline

1. Algorithm Analysis
2. Search
3. Simple Sort
 - Insertion Sort
 - Selection Sort
4. Lower Bound



How Well Can You Do?


- Given a problem we would like to know what is the time complexity of the best possible program
- Usually there is no way of knowing this
- We can get an upper bound—if we know the time complexity of any algorithm that solves the problem we have an upper bound
- Lower bounds are far trickier
- A lower bound of $f(n)$ is a guarantee that we spend at least $f(n)$ operations to solve the problem



Decision Trees

- Decision trees are a way to visualise (at least, in principle) many algorithms
- They will eventually give us a lower bound on the time complexity of sort using binary decisions
- A decision tree shows the series of decisions made during an algorithm
- For sort based on binary comparisons the decision tree shows what the algorithm does after every comparison

Decision Tree for Insertion Sort



- Note there is one leaf for every possible way of sorting the list

Decision Trees and Time Complexity

- The time taken to complete the task is the depth of the tree at which we finish (i.e. the leaf nodes)
- We can thus read of the time complexity
 - ★ worst case time: depth of the deepest of leaf
 - ★ best case time: depth of the shallowest of leaf
 - ★ average case time: average depth of leaves
- Different sort strategies will have different decision trees
- Decision trees are usually far too large to write out ☹



AIICE1005

Algorithms and Analysis

25

Minimum Number of Leaves

- There must be, at least, one leaf node of the decision tree for each possible permutation of the list
- How many permutations are there of a list of size n ?
- Start with a sequence (a_1, a_2, \dots, a_n)
- To create a new permutation we can choose any member of the list as the first element
- We can choose any of the remaining $n - 1$ elements of the list as the second element of the permutation
- The total number of permutation is $n \times (n - 1) \times (n - 2) \times \dots \times 2 \times 1 = n!$

AIICE1005

Algorithms and Analysis

27

How Big is $\log_2(n!)$

- We showed in the second lecture that

$$\left(\frac{n}{2}\right)^{n/2} < n! < n^n$$

- It is not too difficult to show that asymptotically (i.e. as $n \rightarrow \infty$) that $n!$ approaches $\sqrt{2\pi n} \left(\frac{n}{e}\right)^n$ —this is known as **Stirling's approximation**
- Thus

$$\begin{aligned} \log_2(n!) &\approx n \log_2(n) - n \log_2(e) + \frac{\log_2(n)}{2} + \frac{\log_2(2\pi)}{2} \\ &= \Theta(n \log_2(n)) \end{aligned}$$


AIICE1005

Algorithms and Analysis

29

Lessons

- Analysis of algorithms is hard
- Analysis is important: without it we don't know if we have a good algorithm or whether we should try to find a more efficient one
- Lower bounds are particularly important



AIICE1005

Algorithms and Analysis

31

Requirements of Correct Sort

- Any sort based on binary comparisons must have a leaf of the tree for every possible way of sorting the list
- The array $[a, b, c]$ must be arranged differently for all combinations
 - $[1, 2, 3], [1, 3, 2], [2, 1, 3], [2, 3, 1], [3, 1, 2], [3, 2, 1]$
- That is they must go through a different path of the decision tree
- If not sort won't work

AIICE1005

Algorithms and Analysis

26

Lower Bound Time Complexity for Sorting

- Any sort algorithm using binary comparisons must have a decision tree with at least $n!$ leaf nodes
- This will be a binary tree with some depth d
- The number of leaves at depth d is 2^d
- Thus the smallest depth tree must have a depth d such that $2^d \geq n!$
- That is, the depth of the decision tree satisfies $d \geq \log_2(n!)$
- But this is the number of comparisons needed in our sort
- We are left with a lower bound on the time complexity of $\log_2(n!)$

AIICE1005

Algorithms and Analysis

28

Complexity of Sorting

- We therefore have a lower bound on the time complexity of $\Omega(n \log(n))$
- This is true for any sort using binary comparisons
- We will see in the next lecture there exists algorithms with time complexity $O(n \log(n))$
- This means our lower bound is tight—i.e. it is the true cost of the best algorithm
- Having a lower bound we know we are not going to obtain a substantially faster algorithm

AIICE1005

Algorithms and Analysis

30