


# Algorithms and Analysis


## Lesson 13: *Analyse!*



*Pseudo code, binary search, insertion sort, selection sort, lower bound complexity*

# Outline

1. **Algorithm Analysis**
2. Search
3. Simple Sort
  - Insertion Sort
  - Selection Sort
4. Lower Bound



# Algorithm Analysis

- We've covered most of the basic data structures
- The rest of the course is going to focus more on algorithms
- We will look predominantly at
  - ★ Searching
  - ★ Sorting
  - ★ Graph Algorithms
- Emphasise general solution strategies

# Algorithm Analysis

- We've covered most of the basic data structures
- The rest of the course is going to focus more on algorithms
- We will look predominantly at
  - ★ Searching
  - ★ Sorting
  - ★ Graph Algorithms
- Emphasise general solution strategies

# Algorithm Analysis

- We've covered most of the basic data structures
- The rest of the course is going to focus more on algorithms
- We will look predominantly at
  - ★ Searching
  - ★ Sorting
  - ★ Graph Algorithms
- Emphasise general solution strategies

# Algorithm Analysis

- We've covered most of the basic data structures
- The rest of the course is going to focus more on algorithms
- We will look predominantly at
  - ★ Searching
  - ★ Sorting
  - ★ Graph Algorithms
- Emphasise general solution strategies

# Code and Pseudo Code

- C++ code is often difficult to read—there are often programming details we don't care about
- It contains details such as throwing exception which are repetitive and often depends on who you are writing the code for
- Algorithms are not language dependent (data structures are a bit more language dependent)
- To focus on what is important we will use a stylised programming language called **pseudo code**

# Code and Pseudo Code

- C++ code is often difficult to read—there are often programming details we don't care about
- It contains details such as throwing exception which are repetitive and often depends on who you are writing the code for
- Algorithms are not language dependent (data structures are a bit more language dependent)
- To focus on what is important we will use a stylised programming language called **pseudo code**



# Code and Pseudo Code

- C++ code is often difficult to read—there are often programming details we don't care about
- It contains details such as throwing exception which are repetitive and often depends on who you are writing the code for
- Algorithms are not language dependent (data structures are a bit more language dependent)
- To focus on what is important we will use a stylised programming language called **pseudo code**

# Code and Pseudo Code

- C++ code is often difficult to read—there are often programming details we don't care about
- It contains details such as throwing exception which are repetitive and often depends on who you are writing the code for
- Algorithms are not language dependent (data structures are a bit more language dependent)
- To focus on what is important we will use a stylised programming language called **pseudo code**

# Pseudo Code

- There is no standard for pseudo code
- The commands are not too dissimilar to C++
- The one strange convention is that assignments use an arrow  $\leftarrow$
- Arrays are written in bold  $\mathbf{a}$  with elements  $a_i$
- In pseudo-code you are free to invent any operations that can be easily interpreted

# Pseudo Code

- There is no standard for pseudo code
- The commands are not too dissimilar to C++
- The one strange convention is that assignments use an arrow  $\leftarrow$
- Arrays are written in bold  $a$  with elements  $a_i$
- In pseudo-code you are free to invent any operations that can be easily interpreted

# Pseudo Code

- There is no standard for pseudo code
- The commands are not too dissimilar to C++
- The one strange convention is that assignments use an arrow  $\leftarrow$
- Arrays are written in bold  $\mathbf{a}$  with elements  $a_i$
- In pseudo-code you are free to invent any operations that can be easily interpreted

# Pseudo Code


- There is no standard for pseudo code
- The commands are not too dissimilar to C++
- The one strange convention is that assignments use an arrow  $\leftarrow$
- Arrays are written in bold  $\mathbf{a}$  with elements  $a_i$
- In pseudo-code you are free to invent any operations that can be easily interpreted

# Pseudo Code

- There is no standard for pseudo code
- The commands are not too dissimilar to C++
- The one strange convention is that assignments use an arrow  $\leftarrow$
- Arrays are written in bold  $\mathbf{a}$  with elements  $a_i$
- In pseudo-code you are free to invent any operations that can be easily interpreted

# Outline

1. Algorithm Analysis
2. Search
3. Simple Sort
  - Insertion Sort
  - Selection Sort
4. Lower Bound





# Dumb Search

```
DUMBSEARCH(a, x)
{
  /* search array a = ( $a_1, \dots, a_n$ ) */
  /* for x return true */
  /* if successful else false */
  for i ← 1 to n
    if ( $a_i = x$ )
      return true
    endif
  endfor

  return false
}
```

# Dumb Search

DUMBSEARCH (***a***, *x*)

```
{  
  /* search array a = (a1, ... an) */  
  /* for x return true */  
  /* if successful else false */  
  for i ← 1 to n  
    if (ai = x)  
      return true  
    endif  
  endfor  
  
  return false  
}
```

```
bool search(T a[], T x)  
{  
  for (int i=0; i<n; i++) {  
    if (a[i] == x)  
      return true;  
  }  
  
  return false;  
}
```

# Dumb Search

DUMBSEARCH(***a***, *x*)

```
{  
  /* search array a = ( $a_1, \dots, a_n$ ) */  
  /* for x return true */  
  /* if successful else false */  
  for i ← 1 to n  
    if ( $a_i = x$ )  
      return true  
    endif  
  endfor  
  
  return false  
}
```

```
bool search(T a[], T x)  
{  
  for (int i=0; i<n; i++) {  
    if (a[i] == x)  
      return true;  
  }  
  
  return false;  
}
```

56	26	62	60	53	53	77	91	60	41
----	----	----	----	----	----	----	----	----	----


# Dumb Search

DUMBSEARCH(*a*, *x*)

```
{  
  /* search array a = (a1, ..., an) */  
  /* for x return true */  
  /* if successful else false */  
  for i ← 1 to n  
    if (ai = x)  
      return true  
    endif  
  endfor  
  
  return false  
}
```

```
bool search(T a[], T x)  
{  
  for (int i=0; i<n; i++) {  
    if (a[i] == x)  
      return true;  
  }  
  
  return false;  
}
```

find(53) → true




# Dumb Search

```
DUMBSEARCH(a, x)
```

```
{  
  /* search array a = (a1, ..., an) */  
  /* for x return true */  
  /* if successful else false */  
  for i ← 1 to n  
    if (ai = x)  
      return true  
    endif  
  endfor  
  
  return false  
}
```

```
bool search(T a[], T x)  
{  
  for (int i=0; i<n; i++) {  
    if (a[i] == x)  
      return true;  
  }  
  
  return false;  
}
```

find(60) → true




# Dumb Search

DUMBSEARCH(*a*, *x*)

```
{  
  /* search array a = (a1, ..., an) */  
  /* for x return true */  
  /* if successful else false */  
  for i ← 1 to n  
    if (ai = x)  
      return true  
    endif  
  endfor  
  
  return false  
}
```

```
bool search(T a[], T x)  
{  
  for (int i=0; i<n; i++) {  
    if (a[i] == x)  
      return true;  
  }  
  
  return false;  
}
```

find(12) → false



# Time Complexity

- Worst case:

- ★ The worst case for a successful search is when the element is in the last location in the array
- ★ This takes  $n$  comparisons: worst case is  $\Theta(n)$

- Best case:

- ★ The best case is when the element is in the first location
- ★ This takes 1 comparison: best case is  $\Theta(1)$

- Average case:

- ★ Assume every location is equally likely to hold the key

$$\frac{1 + 2 + \dots + n}{n} = \frac{1}{n} \sum_{i=1}^n i = \frac{1}{n} \times \frac{n(n+1)}{2} = \frac{n+1}{2}$$

- For an unsuccessful search  $n$  comparison are necessary

# Time Complexity

- Worst case:
  - ★ The worst case for a successful search is when the element is in the last location in the array
  - ★ This takes  $n$  comparisons: worst case is  $\Theta(n)$
- Best case:
  - ★ The best case is when the element is in the first location
  - ★ This takes 1 comparison: best case is  $\Theta(1)$
- Average case:
  - ★ Assume every location is equally likely to hold the key

$$\frac{1 + 2 + \dots + n}{n} = \frac{1}{n} \sum_{i=1}^n i = \frac{1}{n} \times \frac{n(n+1)}{2} = \frac{n+1}{2}$$

- For an unsuccessful search  $n$  comparison are necessary



# Time Complexity

- Worst case:
  - ★ The worst case for a successful search is when the element is in the last location in the array
  - ★ This takes  $n$  comparisons: worst case is  $\Theta(n)$
- Best case:
  - ★ The best case is when the element is in the first location
  - ★ This takes 1 comparison: best case is  $\Theta(1)$
- Average case:
  - ★ Assume every location is equally likely to hold the key

$$\frac{1 + 2 + \dots + n}{n} = \frac{1}{n} \sum_{i=1}^n i = \frac{1}{n} \times \frac{n(n+1)}{2} = \frac{n+1}{2}$$

- For an unsuccessful search  $n$  comparison are necessary

# Time Complexity

- Worst case:
  - ★ The worst case for a successful search is when the element is in the last location in the array
  - ★ This takes  $n$  comparisons: worst case is  $\Theta(n)$
- Best case:
  - ★ The best case is when the element is in the first location
  - ★ This takes 1 comparison: best case is  $\Theta(1)$
- Average case:
  - ★ Assume every location is equally likely to hold the key

$$\frac{1 + 2 + \dots + n}{n} = \frac{1}{n} \sum_{i=1}^n i = \frac{1}{n} \times \frac{n(n+1)}{2} = \frac{n+1}{2}$$

- For an unsuccessful search  $n$  comparison are necessary

# Time Complexity

- Worst case:
  - ★ The worst case for a successful search is when the element is in the last location in the array
  - ★ This takes  $n$  comparisons: worst case is  $\Theta(n)$
- Best case:
  - ★ The best case is when the element is in the first location
  - ★ This takes 1 comparison: best case is  $\Theta(1)$
- Average case:
  - ★ Assume every location is equally likely to hold the key

$$\frac{1 + 2 + \dots + n}{n} = \frac{1}{n} \sum_{i=1}^n i = \frac{1}{n} \times \frac{n(n+1)}{2} = \frac{n+1}{2}$$

- For an unsuccessful search  $n$  comparison are necessary

# Time Complexity

- Worst case:
  - ★ The worst case for a successful search is when the element is in the last location in the array
  - ★ This takes  $n$  comparisons: worst case is  $\Theta(n)$
- Best case:
  - ★ The best case is when the element is in the first location
  - ★ This takes 1 comparison: best case is  $\Theta(1)$
- Average case:
  - ★ Assume every location is equally likely to hold the key

$$\frac{1 + 2 + \dots + n}{n} = \frac{1}{n} \sum_{i=1}^n i = \frac{1}{n} \times \frac{n(n+1)}{2} = \frac{n+1}{2}$$

- For an unsuccessful search  $n$  comparison are necessary

# Time Complexity

- Worst case:
  - ★ The worst case for a successful search is when the element is in the last location in the array
  - ★ This takes  $n$  comparisons: worst case is  $\Theta(n)$
- Best case:
  - ★ The best case is when the element is in the first location
  - ★ This takes 1 comparison: best case is  $\Theta(1)$
- Average case:
  - ★ Assume every location is equally likely to hold the key

$$\frac{1 + 2 + \dots + n}{n} = \frac{1}{n} \sum_{i=1}^n i = \frac{1}{n} \times \frac{n(n+1)}{2} = \frac{n+1}{2}$$

- For an unsuccessful search  $n$  comparison are necessary

# Time Complexity

- Worst case:
  - ★ The worst case for a successful search is when the element is in the last location in the array
  - ★ This takes  $n$  comparisons: worst case is  $\Theta(n)$
- Best case:
  - ★ The best case is when the element is in the first location
  - ★ This takes 1 comparison: best case is  $\Theta(1)$
- Average case:
  - ★ Assume every location is equally likely to hold the key

$$\frac{1 + 2 + \dots + n}{n} = \frac{1}{n} \sum_{i=1}^n i = \frac{1}{n} \times \frac{n(n+1)}{2} = \frac{n+1}{2}$$

- For an unsuccessful search  $n$  comparison are necessary

# Time Complexity

- Worst case:
  - ★ The worst case for a successful search is when the element is in the last location in the array
  - ★ This takes  $n$  comparisons: worst case is  $\Theta(n)$
- Best case:
  - ★ The best case is when the element is in the first location
  - ★ This takes 1 comparison: best case is  $\Theta(1)$
- Average case:
  - ★ Assume every location is equally likely to hold the key

$$\frac{1 + 2 + \dots + n}{n} = \frac{1}{n} \sum_{i=1}^n i = \frac{1}{n} \times \frac{n(n+1)}{2} = \frac{n+1}{2}$$

- For an unsuccessful search  $n$  comparison are necessary

# Time Complexity

- Worst case:
  - ★ The worst case for a successful search is when the element is in the last location in the array
  - ★ This takes  $n$  comparisons: worst case is  $\Theta(n)$
- Best case:
  - ★ The best case is when the element is in the first location
  - ★ This takes 1 comparison: best case is  $\Theta(1)$
- Average case:
  - ★ Assume every location is equally likely to hold the key

$$\frac{1 + 2 + \dots + n}{n} = \frac{1}{n} \sum_{i=1}^n i = \frac{1}{n} \times \frac{n(n+1)}{2} = \frac{n+1}{2}$$

- For an unsuccessful search  $n$  comparison are necessary



# Time Complexity

- Worst case:
  - ★ The worst case for a successful search is when the element is in the last location in the array
  - ★ This takes  $n$  comparisons: worst case is  $\Theta(n)$
- Best case:
  - ★ The best case is when the element is in the first location
  - ★ This takes 1 comparison: best case is  $\Theta(1)$
- Average case:
  - ★ Assume every location is equally likely to hold the key

$$\frac{1 + 2 + \dots + n}{n} = \frac{1}{n} \sum_{i=1}^n i = \frac{1}{n} \times \frac{n(n+1)}{2} = \frac{n+1}{2}$$

- For an unsuccessful search  $n$  comparison are necessary

# Time Complexity

- Worst case:
  - ★ The worst case for a successful search is when the element is in the last location in the array
  - ★ This takes  $n$  comparisons: worst case is  $\Theta(n)$
- Best case:
  - ★ The best case is when the element is in the first location
  - ★ This takes 1 comparison: best case is  $\Theta(1)$
- Average case:
  - ★ Assume every location is equally likely to hold the key

$$\frac{1 + 2 + \dots + n}{n} = \frac{1}{n} \sum_{i=1}^n i = \frac{1}{n} \times \frac{n(n+1)}{2} = \frac{n+1}{2}$$

- For an unsuccessful search  $n$  comparison are necessary

# Binary Search

- If the array is ordered we can do better
- At each step we bisect the array

```
BINARYSEARCH(a, x)
```

```
{  
  low ← 1  
  high ← n  
  while (low ≤ high)  
    mid ← ⌊(low + high)/2⌋  
    if x > amid  
      low ← mid + 1  
    elseif x < amid  
      high ← mid - 1  
    else  
      return true  
    endif  
  endwhile  
  return false  
}
```

★ Based on a **divide-and-conquer** strategy

★ We check the middle of the array

$$\underbrace{a_1, a_2, \dots, a_{m-1}}_{x < a_m}, \overbrace{a_m}^{x = a_m}, \underbrace{a_{m+1}, \dots, a_n}_{x > a_m}$$

★ Based on a recursive idea

# Binary Search

- If the array is ordered we can do better
- At each step we bisect the array

```
BINARYSEARCH(a, x)
{
  low ← 1
  high ← n
  while (low ≤ high)
    mid ← ⌊(low + high)/2⌋
    if x > amid
      low ← mid + 1
    elseif x < amid
      high ← mid - 1
    else
      return true
    endif
  endwhile
  return false
}
```

★ Based on a **divide-and-conquer** strategy

★ We check the middle of the array

$$\underbrace{a_1, a_2, \dots, a_{m-1}}_{x < a_m}, \overbrace{a_m}^{x = a_m}, \underbrace{a_{m+1}, \dots, a_n}_{x > a_m}$$

★ Based on a recursive idea

# Binary Search

- If the array is ordered we can do better
- At each step we bisect the array

`BINARYSEARCH(a, x)`

```
{  
  low ← 1  
  high ← n  
  while (low ≤ high)  
    mid ← ⌊(low + high)/2⌋  
    if x > amid  
      low ← mid + 1  
    elseif x < amid  
      high ← mid - 1  
    else  
      return true  
    endif  
  endwhile  
  return false  
}
```

★ Based on a **divide-and-conquer** strategy

★ We check the middle of the array

$$\underbrace{a_1, a_2, \dots, a_{m-1}}_{x < a_m}, \overbrace{a_m}^{x = a_m}, \underbrace{a_{m+1}, \dots, a_n}_{x > a_m}$$

★ Based on a recursive idea

# Binary Search

- If the array is ordered we can do better
- At each step we bisect the array

```
BINARYSEARCH(a, x)
```

```
{  
  low ← 1  
  high ← n  
  while (low ≤ high)  
    mid ← ⌊(low + high)/2⌋  
    if x > amid  
      low ← mid + 1  
    elseif x < amid  
      high ← mid - 1  
    else  
      return true  
    endif  
  endwhile  
  return false  
}
```

★ Based on a **divide-and-conquer** strategy

★ We check the middle of the array

$$\underbrace{a_1, a_2, \dots, a_{m-1}}_{x < a_m}, \overbrace{a_m}^{x = a_m}, \underbrace{a_{m+1}, \dots, a_n}_{x > a_m}$$

★ Based on a recursive idea

# Binary Search

- If the array is ordered we can do better
- At each step we bisect the array

```
BINARYSEARCH(a, x)
```

```
{  
  low ← 1  
  high ← n  
  while (low ≤ high)  
    mid ← ⌊(low + high)/2⌋  
    if x > amid  
      low ← mid + 1  
    elseif x < amid  
      high ← mid - 1  
    else  
      return true  
    endif  
  endwhile  
  return false  
}
```

★ Based on a **divide-and-conquer** strategy

★ We check the middle of the array

$$\underbrace{a_1, a_2, \dots, a_{m-1}}_{x < a_m}, \overbrace{a_m}^{x = a_m}, \underbrace{a_{m+1}, \dots, a_n}_{x > a_m}$$

★ Based on a recursive idea

# Binary Search

- If the array is ordered we can do better
- At each step we bisect the array

```
BINARYSEARCH(a, x)
```

```
{  
  low ← 1  
  high ← n  
  while (low ≤ high)  
    mid ← ⌊(low + high)/2⌋  
    if x > amid  
      low ← mid + 1  
    elseif x < amid  
      high ← mid - 1  
    else  
      return true  
    endif  
  endwhile  
  return false  
}
```

★ Based on a **divide-and-conquer** strategy

★ We check the middle of the array

$$\underbrace{a_1, a_2, \dots, a_{m-1}}_{x < a_m}, \overbrace{a_m}^{x = a_m}, \underbrace{a_{m+1}, \dots, a_n}_{x > a_m}$$

★ Based on a recursive idea



# Binary Search

- If the array is ordered we can do better
- At each step we bisect the array

```
BINARYSEARCH(a, x)
```

```
{  
  low ← 1  
  high ← n  
  while (low ≤ high)  
    mid ← ⌊(low + high)/2⌋  
    if x > amid  
      low ← mid + 1  
    elseif x < amid  
      high ← mid - 1  
    else  
      return true  
    endif  
  endwhile  
  return false  
}
```

★ Based on a **divide-and-conquer** strategy

★ We check the middle of the array

$$\underbrace{a_1, a_2, \dots, a_{m-1}}_{x < a_m}, \overbrace{a_m}^{x = a_m}, \underbrace{a_{m+1}, \dots, a_n}_{x > a_m}$$

★ Based on a recursive idea

# Binary Search

- If the array is ordered we can do better
- At each step we bisect the array

```
BINARYSEARCH(a, x)
```

```
{  
  low ← 1  
  high ← n  
  while (low ≤ high)  
    mid ← ⌊(low + high)/2⌋  
    if x > amid  
      low ← mid + 1  
    elseif x < amid  
      high ← mid - 1  
    else  
      return true  
    endif  
  endwhile  
  return false  
}
```

★ Based on a **divide-and-conquer** strategy

★ We check the middle of the array

$$\underbrace{a_1, a_2, \dots, a_{m-1}}_{x < a_m}, \overbrace{a_m}^{x = a_m}, \underbrace{a_{m+1}, \dots, a_n}_{x > a_m}$$

★ Based on a recursive idea

# Binary Search

- If the array is ordered we can do better
- At each step we bisect the array

```
BINARYSEARCH(a, x)
```

```
{  
  low ← 1  
  high ← n  
  while (low ≤ high)  
    mid ← ⌊(low + high)/2⌋  
    if x > amid  
      low ← mid + 1  
    elseif x < amid  
      high ← mid - 1  
    else  
      return true  
    endif  
  endwhile  
  return false  
}
```

★ Based on a **divide-and-conquer** strategy

★ We check the middle of the array

$$\underbrace{a_1, a_2, \dots, a_{m-1}}_{x < a_m}, \overbrace{a_m}^{x = a_m}, \underbrace{a_{m+1}, \dots, a_n}_{x > a_m}$$

★ Based on a recursive idea

# Binary Search

- If the array is ordered we can do better
- At each step we bisect the array

```
BINARYSEARCH(a, x)
{
  low ← 1
  high ← n
  while (low ≤ high)
    mid ← ⌊(low + high)/2⌋
    if x > amid
      low ← mid + 1
    elseif x < amid
      high ← mid - 1
    else
      return true
    endif
  endwhile
  return false
}
```

★ Based on a **divide-and-conquer** strategy

★ We check the middle of the array

$$\underbrace{a_1, a_2, \dots, a_{m-1}}_{x < a_m}, \overbrace{a_m}^{x = a_m}, \underbrace{a_{m+1}, \dots, a_n}_{x > a_m}$$

★ Based on a recursive idea

# Binary Search in Action

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

# Binary Search in Action

BINARYSEARCH(**a**, 27)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low																			high

# Binary Search in Action

BINARYSEARCH(**a**, 27)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low									mid										high

# Binary Search in Action

BINARYSEARCH(a, 27)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low								high											



# Binary Search in Action

BINARYSEARCH(a, 27)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low				mid				high											

# Binary Search in Action

BINARYSEARCH(a, 27)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low			high																

# Binary Search in Action

BINARYSEARCH(a, 27)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low	mid		high																

# Binary Search in Action

BINARYSEARCH(**a**, 27)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
		low	high																

# Binary Search in Action

BINARYSEARCH(**a**, 27)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
		low	mid																
			high																

# Binary Search in Action

BINARYSEARCH(**a**, 27)          found

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
		low	mid																
			high																

# Binary Search in Action

BINARYSEARCH(**a**, 20)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low																			high

# Binary Search in Action

BINARYSEARCH(**a**, 20)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low									mid										high



# Binary Search in Action

BINARYSEARCH(**a**, 20)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low								high											

# Binary Search in Action

BINARYSEARCH(**a**, 20)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low				mid				high											

# Binary Search in Action

BINARYSEARCH(**a**, 20)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low			high																

# Binary Search in Action

BINARYSEARCH(**a**, 20)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low	mid		high																

# Binary Search in Action

BINARYSEARCH(**a**, 20)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
		low	high																

# Binary Search in Action

BINARYSEARCH(**a**, 20)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
		low	mid																
			high																

# Binary Search in Action

BINARYSEARCH(**a**, 20)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
	high	low																	

# Binary Search in Action

BINARYSEARCH(**a**, 20)      not found

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
	high	low																	



# Binary Search in Action

BINARYSEARCH(**a**, 84)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low																			high

# Binary Search in Action

BINARYSEARCH(**a**, 84)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low									mid										high

# Binary Search in Action

BINARYSEARCH(**a**, 84)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
										low									high

# Binary Search in Action

BINARYSEARCH(**a**, 84)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
										low				mid					high

# Binary Search in Action

BINARYSEARCH(**a**, 84)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
															low				high

# Binary Search in Action

BINARYSEARCH(**a**, 84)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
															low		mid		high

# Binary Search in Action

BINARYSEARCH(**a**, 84)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
															low	high			

# Binary Search in Action

BINARYSEARCH(**a**, 84)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
															low	mid	high		



# Binary Search in Action

BINARYSEARCH(**a**, 84)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

high  
low

# Binary Search in Action

BINARYSEARCH(**a**, 84)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

high  
mid  
low

# Binary Search in Action

BINARYSEARCH(**a**, 84)          found

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

high  
mid  
low

# Binary Search in Action

BINARYSEARCH(**a**, 99)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low																			high

# Binary Search in Action

BINARYSEARCH(**a**, 99)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
low									mid										high

# Binary Search in Action

BINARYSEARCH(**a**, 99)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
										low									high

# Binary Search in Action

BINARYSEARCH(**a**, 99)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
										low				mid					high

# Binary Search in Action

BINARYSEARCH(**a**, 99)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
															low				high



# Binary Search in Action

BINARYSEARCH(**a**, 99)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
															low		mid		high

# Binary Search in Action

BINARYSEARCH(**a**, 99)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
																		low	high

# Binary Search in Action

BINARYSEARCH(**a**, 99)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
																		low	high

# Binary Search in Action

BINARYSEARCH(**a**, 99)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

low high

# Binary Search in Action

BINARYSEARCH(**a**, 99)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

high  
mid  
low

# Binary Search in Action

BINARYSEARCH(**a**, 99)

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

high  
low

# Binary Search in Action

BINARYSEARCH(**a**, 99)      not found

14	19	27	33	36	39	47	51	55	60	62	63	71	76	78	79	84	91	91	95
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

high  
low

# Analysis

- We count the number of comparisons (counting each `if/else if` statement as a single comparison)
- Let  $C(n)$  be the number of comparisons needed to search in an array of size  $n$
- After one comparison we are left (in the worst case) with having to search an array not larger than  $\lfloor n/2 \rfloor$ , thus

$$C(n) < C(\lfloor n/2 \rfloor) + 1$$

- We've seen this relation before (lesson on Recursion)
- Easy to show  $C(n) < \lfloor \log_2(n) \rfloor + 1 = O(\log(n))$



# Analysis

- We count the number of comparisons (counting each `if/else if` statement as a single comparison)
- Let  $C(n)$  be the number of comparisons needed to search in an array of size  $n$
- After one comparison we are left (in the worst case) with having to search an array not larger than  $\lfloor n/2 \rfloor$ , thus

$$C(n) < C(\lfloor n/2 \rfloor) + 1$$

- We've seen this relation before (lesson on Recursion)
- Easy to show  $C(n) < \lfloor \log_2(n) \rfloor + 1 = O(\log(n))$

# Analysis

- We count the number of comparisons (counting each `if/else if` statement as a single comparison)
- Let  $C(n)$  be the number of comparisons needed to search in an array of size  $n$
- After one comparison we are left (in the worst case) with having to search an array not larger than  $\lfloor n/2 \rfloor$ , thus

$$C(n) < C(\lfloor n/2 \rfloor) + 1$$

- We've seen this relation before (lesson on Recursion)
- Easy to show  $C(n) < \lfloor \log_2(n) \rfloor + 1 = O(\log(n))$

# Analysis

- We count the number of comparisons (counting each `if/else if` statement as a single comparison)
- Let  $C(n)$  be the number of comparisons needed to search in an array of size  $n$
- After one comparison we are left (in the worst case) with having to search an array not larger than  $\lfloor n/2 \rfloor$ , thus

$$C(n) < C(\lfloor n/2 \rfloor) + 1$$

- We've seen this relation before (lesson on Recursion)
- Easy to show  $C(n) < \lfloor \log_2(n) \rfloor + 1 = O(\log(n))$

# Analysis

- We count the number of comparisons (counting each `if/else if` statement as a single comparison)
- Let  $C(n)$  be the number of comparisons needed to search in an array of size  $n$
- After one comparison we are left (in the worst case) with having to search an array not larger than  $\lfloor n/2 \rfloor$ , thus

$$C(n) < C(\lfloor n/2 \rfloor) + 1$$

- We've seen this relation before (lesson on Recursion)
- Easy to show  $C(n) < \lfloor \log_2(n) \rfloor + 1 = O(\log(n))$

# Analysis


- We count the number of comparisons (counting each `if/else if` statement as a single comparison)
- Let  $C(n)$  be the number of comparisons needed to search in an array of size  $n$
- After one comparison we are left (in the worst case) with having to search an array not larger than  $\lfloor n/2 \rfloor$ , thus

$$C(n) < C(\lfloor n/2 \rfloor) + 1$$

- We've seen this relation before (lesson on Recursion)
- Easy to show  $C(n) < \lfloor \log_2(n) \rfloor + 1 = O(\log(n))$

# Outline

1. Algorithm Analysis
2. Search
3. **Simple Sort**
  - Insertion Sort
  - Selection Sort
4. Lower Bound



# Sort Characteristics

- Sort is one of the best studied algorithms. We care about stability, space and time complexity
- A sort algorithm is said to be **stable** if it does not change the order of elements that have the same value
- Space Complexity. Sort is said to be
  - ★ **In-place** if the memory used is  $O(1)$
- Time Complexity. In particular we are interested in
  - ★ Worst case
  - ★ Average case
  - ★ Best case

# Sort Characteristics

- Sort is one of the best studied algorithms. We care about stability, space and time complexity
- A sort algorithm is said to be **stable** if it does not change the order of elements that have the same value
- Space Complexity. Sort is said to be
  - ★ **In-place** if the memory used is  $O(1)$
- Time Complexity. In particular we are interested in
  - ★ Worst case
  - ★ Average case
  - ★ Best case



# Sort Characteristics

- Sort is one of the best studied algorithms. We care about stability, space and time complexity
- A sort algorithm is said to be **stable** if it does not change the order of elements that have the same value
- Space Complexity. Sort is said to be
  - ★ **In-place** if the memory used is  $O(1)$
- Time Complexity. In particular we are interested in
  - ★ Worst case
  - ★ Average case
  - ★ Best case

# Sort Characteristics

- Sort is one of the best studied algorithms. We care about stability, space and time complexity
- A sort algorithm is said to be **stable** if it does not change the order of elements that have the same value
- Space Complexity. Sort is said to be
  - ★ **In-place** if the memory used is  $O(1)$
- Time Complexity. In particular we are interested in
  - ★ Worst case
  - ★ Average case
  - ★ Best case

# Sort Characteristics

- Sort is one of the best studied algorithms. We care about stability, space and time complexity
- A sort algorithm is said to be **stable** if it does not change the order of elements that have the same value
- Space Complexity. Sort is said to be
  - ★ **In-place** if the memory used is  $O(1)$
- Time Complexity. In particular we are interested in
  - ★ Worst case
  - ★ Average case
  - ★ Best case

# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT (a)
{
  for  $i \leftarrow 2$  to  $n$ 
     $v \leftarrow a_i$ 
     $j \leftarrow i - 1$ 
    while  $j \geq 1$  and  $a_j > v$ 
       $a_{j+1} \leftarrow a_j$ 
       $j \leftarrow j - 1$ 
    endwhile
     $a_{j+1} \leftarrow v$ 
  endfor
}
```

# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```

# Insertion Sort


- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```

# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```




sorted

unsorted

# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```





# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```

37	66	23	69	74	90	39	84	69	50
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```



# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```

23	37	66	69	74	90	39	84	69	50
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```



# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```

23	37	66	69	74	90	39	84	69	50
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```



# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```

23	37	66	69	74	90	39	84	69	50
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```





# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```

23	37	66	69	74	90	39	84	69	50
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```



# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```

23	37	39	66	69	74	90	84	69	50
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```



# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```

23	37	39	66	69	74	84	90	69	50
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```



# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```

23	37	39	66	69	69	74	84	90	50
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)  
{  
  for i ← 2 to n  
    v ← ai  
    j ← i - 1  
    while j ≥ 1 and aj > v  
      aj+1 ← aj  
      j ← j - 1  
    endwhile  
    aj+1 ← v  
  endfor  
}
```





# Insertion Sort

- In insertion sort we keep a subsequence of elements on the left in sorted order
- This subsequence is increased by *inserting* the next element into its correct position

```
INSERTIONSORT(a)
{
  for i ← 2 to n
    v ← ai
    j ← i - 1
    while j ≥ 1 and aj > v
      aj+1 ← aj
      j ← j - 1
    endwhile
    aj+1 ← v
  endfor
}
```

23	37	39	50	66	69	69	74	84	90
----	----	----	----	----	----	----	----	----	----

sorted

unsorted

# Properties of Insertion Sort

- Insertion sort is **stable**. We only swap the ordering of two elements if one is strictly less than the other
- It is **in-place**
- Worst time complexity
  - ★ Occurs when the array is in inverse order
  - ★ Every element has to be moved to front of the array
  - ★ Number of comparisons for an array of size  $C_w(n)$

$$C_w(n) = \sum_{i=2}^n (i-1) = 1 + 2 + \cdots + n - 1 = \frac{n(n-1)}{2} \in \Theta(n^2)$$

# Properties of Insertion Sort

- Insertion sort is **stable**. We only swap the ordering of two elements if one is strictly less than the other
- It is **in-place**
- Worst time complexity
  - ★ Occurs when the array is in inverse order
  - ★ Every element has to be moved to front of the array
  - ★ Number of comparisons for an array of size  $C_w(n)$

$$C_w(n) = \sum_{i=2}^n (i-1) = 1 + 2 + \cdots + n - 1 = \frac{n(n-1)}{2} \in \Theta(n^2)$$

# Properties of Insertion Sort

- Insertion sort is **stable**. We only swap the ordering of two elements if one is strictly less than the other
- It is **in-place**
- Worst time complexity
  - ★ Occurs when the array is in inverse order
  - ★ Every element has to be moved to front of the array
  - ★ Number of comparisons for an array of size  $C_w(n)$

$$C_w(n) = \sum_{i=2}^n (i-1) = 1 + 2 + \cdots + n - 1 = \frac{n(n-1)}{2} \in \Theta(n^2)$$

# Properties of Insertion Sort

- Insertion sort is **stable**. We only swap the ordering of two elements if one is strictly less than the other
- It is **in-place**
- Worst time complexity
  - ★ Occurs when the array is in inverse order
  - ★ Every element has to be moved to front of the array
  - ★ Number of comparisons for an array of size  $C_w(n)$

$$C_w(n) = \sum_{i=2}^n (i-1) = 1 + 2 + \cdots + n-1 = \frac{n(n-1)}{2} \in \Theta(n^2)$$

# Properties of Insertion Sort

- Insertion sort is **stable**. We only swap the ordering of two elements if one is strictly less than the other
- It is **in-place**
- Worst time complexity
  - ★ Occurs when the array is in inverse order
  - ★ Every element has to be moved to front of the array
  - ★ Number of comparisons for an array of size  $C_w(n)$

$$C_w(n) = \sum_{i=2}^n (i-1) = 1 + 2 + \cdots + n-1 = \frac{n(n-1)}{2} \in \Theta(n^2)$$

# Properties of Insertion Sort

- Insertion sort is **stable**. We only swap the ordering of two elements if one is strictly less than the other
- It is **in-place**
- Worst time complexity
  - ★ Occurs when the array is in inverse order
  - ★ Every element has to be moved to front of the array
  - ★ Number of comparisons for an array of size  $C_w(n)$

$$C_w(n) = \sum_{i=2}^n (i - 1) = 1 + 2 + \cdots + n - 1 = \frac{n(n - 1)}{2} \in \Theta(n^2)$$

# Properties of Insertion Sort

- Insertion sort is **stable**. We only swap the ordering of two elements if one is strictly less than the other
- It is **in-place**
- Worst time complexity
  - ★ Occurs when the array is in inverse order
  - ★ Every element has to be moved to front of the array
  - ★ Number of comparisons for an array of size  $C_w(n)$

$$C_w(n) = \sum_{i=2}^n (i-1) = 1 + 2 + \cdots + n - 1 = \frac{n(n-1)}{2} \in \Theta(n^2)$$



# Properties of Insertion Sort

- Insertion sort is **stable**. We only swap the ordering of two elements if one is strictly less than the other
- It is **in-place**
- Worst time complexity
  - ★ Occurs when the array is in inverse order
  - ★ Every element has to be moved to front of the array
  - ★ Number of comparisons for an array of size  $C_w(n)$

$$C_w(n) = \sum_{i=2}^n (i-1) = 1 + 2 + \cdots + n-1 = \frac{n(n-1)}{2} \in \Theta(n^2)$$

# Properties of Insertion Sort

- Insertion sort is **stable**. We only swap the ordering of two elements if one is strictly less than the other
- It is **in-place**
- Worst time complexity
  - ★ Occurs when the array is in inverse order
  - ★ Every element has to be moved to front of the array
  - ★ Number of comparisons for an array of size  $C_w(n)$

$$C_w(n) = \sum_{i=2}^n (i-1) = 1 + 2 + \cdots + n-1 = \frac{n(n-1)}{2} \in \Theta(n^2)$$

# Time Complexity

- Average Time Complexity

- ★ On average we can expect that each new element being sorted moves half the way down sorted list
- ★ This gives us an average time complexity,  $C_a(n)$  of half the worst time

$$C_a(n) = \frac{n(n-1)}{4} \in \Theta(n^2)$$

- Best Time Complexity

- ★ This occurs if the array is already sorted
- ★ In this case we only need  $C_b(n) = n - 1 \in \Theta(n)$  comparisons

- Insertion sort is a good sort for small arrays because it is stable, in-place and is efficient when the arrays are almost sorted

# Time Complexity

- Average Time Complexity
  - ★ On average we can expect that each new element being sorted moves half the way down sorted list
  - ★ This gives us an average time complexity,  $C_a(n)$  of half the worst time

$$C_a(n) = \frac{n(n-1)}{4} \in \Theta(n^2)$$

- Best Time Complexity
  - ★ This occurs if the array is already sorted
  - ★ In this case we only need  $C_b(n) = n - 1 \in \Theta(n)$  comparisons
- Insertion sort is a good sort for small arrays because it is stable, in-place and is efficient when the arrays are almost sorted

# Time Complexity

- Average Time Complexity
  - ★ On average we can expect that each new element being sorted moves half the way down sorted list
  - ★ This gives us an average time complexity,  $C_a(n)$  of half the worst time

$$C_a(n) = \frac{n(n-1)}{4} \in \Theta(n^2)$$

- Best Time Complexity
  - ★ This occurs if the array is already sorted
  - ★ In this case we only need  $C_b(n) = n - 1 \in \Theta(n)$  comparisons
- Insertion sort is a good sort for small arrays because it is stable, in-place and is efficient when the arrays are almost sorted

# Time Complexity

- Average Time Complexity

- ★ On average we can expect that each new element being sorted moves half the way down sorted list
- ★ This gives us an average time complexity,  $C_a(n)$  of half the worst time

$$C_a(n) = \frac{n(n-1)}{4} \in \Theta(n^2)$$

- Best Time Complexity

- ★ This occurs if the array is already sorted
- ★ In this case we only need  $C_b(n) = n - 1 \in \Theta(n)$  comparisons

- Insertion sort is a good sort for small arrays because it is stable, in-place and is efficient when the arrays are almost sorted

# Time Complexity

- Average Time Complexity

- ★ On average we can expect that each new element being sorted moves half the way down sorted list
- ★ This gives us an average time complexity,  $C_a(n)$  of half the worst time

$$C_a(n) = \frac{n(n-1)}{4} \in \Theta(n^2)$$

- Best Time Complexity

- ★ This occurs if the array is already sorted
- ★ In this case we only need  $C_b(n) = n - 1 \in \Theta(n)$  comparisons

- Insertion sort is a good sort for small arrays because it is stable, in-place and is efficient when the arrays are almost sorted

# Time Complexity

- Average Time Complexity

- ★ On average we can expect that each new element being sorted moves half the way down sorted list
- ★ This gives us an average time complexity,  $C_a(n)$  of half the worst time

$$C_a(n) = \frac{n(n-1)}{4} \in \Theta(n^2)$$

- Best Time Complexity

- ★ This occurs if the array is already sorted
- ★ In this case we only need  $C_b(n) = n - 1 \in \Theta(n)$  comparisons

- Insertion sort is a good sort for small arrays because it is stable, in-place and is efficient when the arrays are almost sorted



# Time Complexity

- Average Time Complexity

- ★ On average we can expect that each new element being sorted moves half the way down sorted list
- ★ This gives us an average time complexity,  $C_a(n)$  of half the worst time

$$C_a(n) = \frac{n(n-1)}{4} \in \Theta(n^2)$$

- Best Time Complexity

- ★ This occurs if the array is already sorted
- ★ In this case we only need  $C_b(n) = n - 1 \in \Theta(n)$  comparisons

- Insertion sort is a good sort for small arrays because it is stable, in-place and is efficient when the arrays are almost sorted

# Time Complexity

- Average Time Complexity
  - ★ On average we can expect that each new element being sorted moves half the way down sorted list
  - ★ This gives us an average time complexity,  $C_a(n)$  of half the worst time

$$C_a(n) = \frac{n(n-1)}{4} \in \Theta(n^2)$$

- Best Time Complexity
  - ★ This occurs if the array is already sorted
  - ★ In this case we only need  $C_b(n) = n - 1 \in \Theta(n)$  comparisons
- Insertion sort is a good sort for small arrays because it is stable, in-place and is efficient when the arrays are almost sorted

# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```

# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```

# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```

# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```

41	82	30	83	58	84	40	33	83	63
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n-1
    min ← i
    for j ← i+1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```



# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n-1
    min ← i
    for j ← i+1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```

30	82	41	83	58	84	40	33	83	63
----	----	----	----	----	----	----	----	----	----

sorted


unsorted



# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n-1
    min ← i
    for j ← i+1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```



# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```

30	33	41	83	58	84	40	82	83	63
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```



# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```

30	33	40	83	58	84	41	82	83	63
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n-1
    min ← i
    for j ← i+1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```



# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```

30	33	40	41	58	84	83	82	83	63
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```



# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```

30	33	40	41	58	84	83	82	83	63
----	----	----	----	----	----	----	----	----	----

sorted


unsorted



# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```



# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```

30	33	40	41	58	63	83	82	83	84
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```



# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```

30	33	40	41	58	63	82	83	83	84
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```



# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```

30	33	40	41	58	63	82	83	83	84
----	----	----	----	----	----	----	----	----	----


sorted

unsorted

# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```



# Selection Sort

- A more direct **brute force** method is to find the least element iteratively
- We can make this an in-place method by swapping the least element with the first element, the second least element with the second element, etc.

```
SELECTIONSORT(a)
{
  for i ← 1 to n - 1
    min ← i
    for j ← i + 1 to n
      if  $a_j < a_{min}$ 
        min ← j
      end if
    end for
    swap  $a_i$  and  $a_{min}$ 
  end for
}
```

30	33	40	41	58	63	82	83	83	84
----	----	----	----	----	----	----	----	----	----

sorted

unsorted



# Analysis of Selection Sort

- Selection sort is in-place
- It isn't stable



- Selection sort always requires  $n(n - 1)/2$  comparisons so has the same worst case, but worse average case and best case complexity as insertion sort
- It only performs  $n - 1$  swaps—this makes it attractive (insertion sort moved more elements)

# Analysis of Selection Sort

- Selection sort is in-place
- It isn't stable



- Selection sort always requires  $n(n - 1)/2$  comparisons so has the same worst case, but worse average case and best case complexity as insertion sort
- It only performs  $n - 1$  swaps—this makes it attractive (insertion sort moved more elements)

# Analysis of Selection Sort

- Selection sort is in-place
- It isn't stable



- Selection sort always requires  $n(n - 1)/2$  comparisons so has the same worst case, but worse average case and best case complexity as insertion sort
- It only performs  $n - 1$  swaps—this makes it attractive (insertion sort moved more elements)


# Analysis of Selection Sort

- Selection sort is in-place
- It isn't stable



- Selection sort always requires  $n(n - 1)/2$  comparisons so has the same worst case, but worse average case and best case complexity as insertion sort
- It only performs  $n - 1$  swaps—this makes it attractive (insertion sort moved more elements)

# Insertion versus Selection Sort



# Bubble Sort

- There are many other simple sort strategies
- One popular one is bubble sort—keep on swapping neighbours until the array is sorted
- It is stable and in-place
- This again has  $O(n^2)$  complexity
- This isn't bad for a simple sort, but it does do more work than insertion sort and selection sort
- Apart from its name it just doesn't have anything going for it

# Bubble Sort

- There are many other simple sort strategies
- One popular one is bubble sort—keep on swapping neighbours until the array is sorted
- It is stable and in-place
- This again has  $O(n^2)$  complexity
- This isn't bad for a simple sort, but it does do more work than insertion sort and selection sort
- Apart from its name it just doesn't have anything going for it

# Bubble Sort

- There are many other simple sort strategies
- One popular one is bubble sort—keep on swapping neighbours until the array is sorted
- It is stable and in-place
- This again has  $O(n^2)$  complexity
- This isn't bad for a simple sort, but it does do more work than insertion sort and selection sort
- Apart from its name it just doesn't have anything going for it



# Bubble Sort

- There are many other simple sort strategies
- One popular one is bubble sort—keep on swapping neighbours until the array is sorted
- It is stable and in-place
- This again has  $O(n^2)$  complexity
- This isn't bad for a simple sort, but it does do more work than insertion sort and selection sort
- Apart from its name it just doesn't have anything going for it

# Bubble Sort

- There are many other simple sort strategies
- One popular one is bubble sort—keep on swapping neighbours until the array is sorted
- It is stable and in-place
- This again has  $O(n^2)$  complexity
- This isn't bad for a simple sort, but it does do more work than insertion sort and selection sort
- Apart from its name it just doesn't have anything going for it

# Bubble Sort

- There are many other simple sort strategies
- One popular one is bubble sort—keep on swapping neighbours until the array is sorted
- It is stable and in-place
- This again has  $O(n^2)$  complexity
- This isn't bad for a simple sort, but it does do more work than insertion sort and selection sort
- Apart from its name it just doesn't have anything going for it

# Bubble Sort

- There are many other simple sort strategies
- One popular one is bubble sort—keep on swapping neighbours until the array is sorted
- It is stable and in-place
- This again has  $O(n^2)$  complexity
- This isn't bad for a simple sort, but it does do more work than insertion sort and selection sort
- Apart from its name it just doesn't have anything going for it


# Outline

1. Algorithm Analysis
2. Search
3. Simple Sort
  - Insertion Sort
  - Selection Sort
4. **Lower Bound**




# How Well Can You Do?

- Given a problem we would like to know what is the time complexity of the best possible program
- Usually there is no way of knowing this
- We can get an upper bound—if we know the time complexity of any algorithm that solves the problem we have an upper bound
- Lower bounds are far trickier
- A lower bound of  $f(n)$  is a guarantee that we spend at least  $f(n)$  operations to solve the problem




# How Well Can You Do?

- Given a problem we would like to know what is the time complexity of the best possible program
- Usually there is no way of knowing this
- We can get an upper bound—if we know the time complexity of any algorithm that solves the problem we have an upper bound
- Lower bounds are far trickier
- A lower bound of  $f(n)$  is a guarantee that we spend at least  $f(n)$  operations to solve the problem



# How Well Can You Do?


- Given a problem we would like to know what is the time complexity of the best possible program
- Usually there is no way of knowing this
- We can get an upper bound—if we know the time complexity of any algorithm that solves the problem we have an upper bound
- Lower bounds are far trickier
- A lower bound of  $f(n)$  is a guarantee that we spend at least  $f(n)$  operations to solve the problem






# How Well Can You Do?

- Given a problem we would like to know what is the time complexity of the best possible program
- Usually there is no way of knowing this
- We can get an upper bound—if we know the time complexity of any algorithm that solves the problem we have an upper bound
- Lower bounds are far trickier
- A lower bound of  $f(n)$  is a guarantee that we spend at least  $f(n)$  operations to solve the problem




# How Well Can You Do?

- Given a problem we would like to know what is the time complexity of the best possible program
- Usually there is no way of knowing this
- We can get an upper bound—if we know the time complexity of any algorithm that solves the problem we have an upper bound
- Lower bounds are far trickier
- A lower bound of  $f(n)$  is a guarantee that we spend at least  $f(n)$  operations to solve the problem



# How Well Can You Do?

- Given a problem we would like to know what is the time complexity of the best possible program
- Usually there is no way of knowing this
- We can get an upper bound—if we know the time complexity of any algorithm that solves the problem we have an upper bound
- Lower bounds are far trickier
- A lower bound of  $f(n)$  is a guarantee that we spend at least  $f(n)$  operations to solve the problem



# Decision Trees

- Decision trees are a way to visualise (at least, in principle) many algorithms
- They will eventually give us a lower bound on the time complexity of sort using binary decisions
- A decision tree shows the series of decisions made during an algorithm
- For sort based on binary comparisons the decision tree shows what the algorithm does after every comparison

# Decision Trees

- Decision trees are a way to visualise (at least, in principle) many algorithms
- They will eventually give us a lower bound on the time complexity of sort using binary decisions
- A decision tree shows the series of decisions made during an algorithm
- For sort based on binary comparisons the decision tree shows what the algorithm does after every comparison


# Decision Trees

- Decision trees are a way to visualise (at least, in principle) many algorithms
- They will eventually give us a lower bound on the time complexity of sort using binary decisions
- A decision tree shows the series of decisions made during an algorithm
- For sort based on binary comparisons the decision tree shows what the algorithm does after every comparison

# Decision Trees

- Decision trees are a way to visualise (at least, in principle) many algorithms
- They will eventually give us a lower bound on the time complexity of sort using binary decisions
- A decision tree shows the series of decisions made during an algorithm
- For sort based on binary comparisons the decision tree shows what the algorithm does after every comparison


# Decision Tree for Insertion Sort



- Note there is one leaf for every possible way of sorting the list




# Decision Tree for Insertion Sort



- Note there is one leaf for every possible way of sorting the list


# Decision Trees and Time Complexity

- The time taken to complete the task is the depth of the tree at which we finish (i.e. the leaf nodes)
- We can thus read of the time complexity
  - ★ worst case time: depth of the deepest of leaf
  - ★ best case time: depth of the shallowest of leaf
  - ★ average case time: average depth of leaves
- Different sort strategies will have different decision trees
- Decision trees are usually far too large to write out ☹️




# Decision Trees and Time Complexity

- The time taken to complete the task is the depth of the tree at which we finish (i.e. the leaf nodes)
- We can thus read of the time complexity
  - ★ worst case time: depth of the deepest of leaf
  - ★ best case time: depth of the shallowest of leaf
  - ★ average case time: average depth of leaves
- Different sort strategies will have different decision trees
- Decision trees are usually far too large to write out ☹️




# Decision Trees and Time Complexity

- The time taken to complete the task is the depth of the tree at which we finish (i.e. the leaf nodes)
- We can thus read of the time complexity
  - ★ worst case time: depth of the deepest of leaf
  - ★ best case time: depth of the shallowest of leaf
  - ★ average case time: average depth of leaves
- Different sort strategies will have different decision trees
- Decision trees are usually far too large to write out ☹️




# Decision Trees and Time Complexity

- The time taken to complete the task is the depth of the tree at which we finish (i.e. the leaf nodes)
- We can thus read of the time complexity
  - ★ worst case time: depth of the deepest of leaf
  - ★ best case time: depth of the shallowest of leaf
  - ★ average case time: average depth of leaves
- Different sort strategies will have different decision trees
- Decision trees are usually far too large to write out ☹️




# Decision Trees and Time Complexity

- The time taken to complete the task is the depth of the tree at which we finish (i.e. the leaf nodes)
- We can thus read of the time complexity
  - ★ worst case time: depth of the deepest of leaf
  - ★ best case time: depth of the shallowest of leaf
  - ★ average case time: average depth of leaves
- Different sort strategies will have different decision trees
- Decision trees are usually far too large to write out ☹️



# Decision Trees and Time Complexity

- The time taken to complete the task is the depth of the tree at which we finish (i.e. the leaf nodes)
- We can thus read of the time complexity
  - ★ worst case time: depth of the deepest of leaf
  - ★ best case time: depth of the shallowest of leaf
  - ★ average case time: average depth of leaves
- Different sort strategies will have different decision trees
- Decision trees are usually far too large to write out ☹️



# Requirements of Correct Sort

- Any sort based on binary comparisons must have a leaf of the tree for every possible way of sorting the list
- The array  $[a, b, c]$  must be arranged differently for all combinations

$[1, 2, 3], [1, 3, 2], [2, 1, 3], [2, 3, 1], [3, 1, 2], [3, 2, 1]$

- That is they must go through a different path of the decision tree
- If not sort won't work



# Requirements of Correct Sort

- Any sort based on binary comparisons must have a leaf of the tree for every possible way of sorting the list
- The array  $[a, b, c]$  must be arranged differently for all combinations

$[1, 2, 3], [1, 3, 2], [2, 1, 3], [2, 3, 1], [3, 1, 2], [3, 2, 1]$

- That is they must go through a different path of the decision tree
- If not sort won't work

# Requirements of Correct Sort

- Any sort based on binary comparisons must have a leaf of the tree for every possible way of sorting the list
- The array  $[a, b, c]$  must be arranged differently for all combinations

$[1, 2, 3], [1, 3, 2], [2, 1, 3], [2, 3, 1], [3, 1, 2], [3, 2, 1]$

- That is they must go through a different path of the decision tree
- If not sort won't work

# Requirements of Correct Sort

- Any sort based on binary comparisons must have a leaf of the tree for every possible way of sorting the list
- The array  $[a, b, c]$  must be arranged differently for all combinations

$[1, 2, 3], [1, 3, 2], [2, 1, 3], [2, 3, 1], [3, 1, 2], [3, 2, 1]$

- That is they must go through a different path of the decision tree
- If not sort won't work

# Minimum Number of Leaves

- There must be, at least, one leaf node of the decision tree for each possible permutation of the list
- How many permutations are there of a list of size  $n$ ?
- Start with a sequence  $(a_1, a_2, \dots, a_n)$
- To create a new permutation we can choose any member of the list as the first element
- We can choose any of the remaining  $n - 1$  elements of the list as the second element of the permutation
- The total number of permutation is
$$n \times (n - 1) \times (n - 2) \times \dots \times 2 \times 1 = n!$$

# Minimum Number of Leaves

- There must be, at least, one leaf node of the decision tree for each possible permutation of the list
- How many permutations are there of a list of size  $n$ ?
- Start with a sequence  $(a_1, a_2, \dots, a_n)$
- To create a new permutation we can choose any member of the list as the first element
- We can choose any of the remaining  $n - 1$  elements of the list as the second element of the permutation
- The total number of permutation is
$$n \times (n - 1) \times (n - 2) \times \dots \times 2 \times 1 = n!$$

# Minimum Number of Leaves

- There must be, at least, one leaf node of the decision tree for each possible permutation of the list
- How many permutations are there of a list of size  $n$ ?
- Start with a sequence  $(a_1, a_2, \dots, a_n)$
- To create a new permutation we can choose any member of the list as the first element
- We can choose any of the remaining  $n - 1$  elements of the list as the second element of the permutation
- The total number of permutation is
$$n \times (n - 1) \times (n - 2) \times \dots \times 2 \times 1 = n!$$

# Minimum Number of Leaves

- There must be, at least, one leaf node of the decision tree for each possible permutation of the list
- How many permutations are there of a list of size  $n$ ?
- Start with a sequence  $(a_1, a_2, \dots, a_n)$
- To create a new permutation we can choose any member of the list as the first element
- We can choose any of the remaining  $n - 1$  elements of the list as the second element of the permutation
- The total number of permutation is
$$n \times (n - 1) \times (n - 2) \times \dots \times 2 \times 1 = n!$$

# Minimum Number of Leaves

- There must be, at least, one leaf node of the decision tree for each possible permutation of the list
- How many permutations are there of a list of size  $n$ ?
- Start with a sequence  $(a_1, a_2, \dots, a_n)$
- To create a new permutation we can choose any member of the list as the first element
- We can choose any of the remaining  $n - 1$  elements of the list as the second element of the permutation
- The total number of permutation is
$$n \times (n - 1) \times (n - 2) \times \dots \times 2 \times 1 = n!$$



# Minimum Number of Leaves

- There must be, at least, one leaf node of the decision tree for each possible permutation of the list
- How many permutations are there of a list of size  $n$ ?
- Start with a sequence  $(a_1, a_2, \dots, a_n)$
- To create a new permutation we can choose any member of the list as the first element
- We can choose any of the remaining  $n - 1$  elements of the list as the second element of the permutation
- The total number of permutation is  
$$n \times (n - 1) \times (n - 2) \times \dots \times 2 \times 1 = n!$$

# Lower Bound Time Complexity for Sorting

- Any sort algorithm using binary comparisons must have a decision tree with at least  $n!$  leaf nodes
- This will be a binary tree with some depth  $d$
- The number of leaves at depth  $d$  is  $2^d$
- Thus the smallest depth tree must have a depth  $d$  such that  $2^d \geq n!$
- That is, the depth of the decision tree satisfies  $d \geq \log_2(n!)$
- But this is the number of comparisons needed in our sort
- We are left with a lower bound on the time complexity of  $\log_2(n!)$

# Lower Bound Time Complexity for Sorting

- Any sort algorithm using binary comparisons must have a decision tree with at least  $n!$  leaf nodes
- This will be a binary tree with some depth  $d$
- The number of leaves at depth  $d$  is  $2^d$
- Thus the smallest depth tree must have a depth  $d$  such that  $2^d \geq n!$
- That is, the depth of the decision tree satisfies  $d \geq \log_2(n!)$
- But this is the number of comparisons needed in our sort
- We are left with a lower bound on the time complexity of  $\log_2(n!)$

# Lower Bound Time Complexity for Sorting

- Any sort algorithm using binary comparisons must have a decision tree with at least  $n!$  leaf nodes
- This will be a binary tree with some depth  $d$
- The number of leaves at depth  $d$  is  $2^d$
- Thus the smallest depth tree must have a depth  $d$  such that  $2^d \geq n!$
- That is, the depth of the decision tree satisfies  $d \geq \log_2(n!)$
- But this is the number of comparisons needed in our sort
- We are left with a lower bound on the time complexity of  $\log_2(n!)$

# Lower Bound Time Complexity for Sorting

- Any sort algorithm using binary comparisons must have a decision tree with at least  $n!$  leaf nodes
- This will be a binary tree with some depth  $d$
- The number of leaves at depth  $d$  is  $2^d$
- Thus the smallest depth tree must have a depth  $d$  such that  $2^d \geq n!$
- That is, the depth of the decision tree satisfies  $d \geq \log_2(n!)$
- But this is the number of comparisons needed in our sort
- We are left with a lower bound on the time complexity of  $\log_2(n!)$

# Lower Bound Time Complexity for Sorting

- Any sort algorithm using binary comparisons must have a decision tree with at least  $n!$  leaf nodes
- This will be a binary tree with some depth  $d$
- The number of leaves at depth  $d$  is  $2^d$
- Thus the smallest depth tree must have a depth  $d$  such that  $2^d \geq n!$
- That is, the depth of the decision tree satisfies  $d \geq \log_2(n!)$
- But this is the number of comparisons needed in our sort
- We are left with a lower bound on the time complexity of  $\log_2(n!)$

# Lower Bound Time Complexity for Sorting

- Any sort algorithm using binary comparisons must have a decision tree with at least  $n!$  leaf nodes
- This will be a binary tree with some depth  $d$
- The number of leaves at depth  $d$  is  $2^d$
- Thus the smallest depth tree must have a depth  $d$  such that  $2^d \geq n!$
- That is, the depth of the decision tree satisfies  $d \geq \log_2(n!)$
- But this is the number of comparisons needed in our sort
- We are left with a lower bound on the time complexity of  $\log_2(n!)$

# Lower Bound Time Complexity for Sorting

- Any sort algorithm using binary comparisons must have a decision tree with at least  $n!$  leaf nodes
- This will be a binary tree with some depth  $d$
- The number of leaves at depth  $d$  is  $2^d$
- Thus the smallest depth tree must have a depth  $d$  such that  $2^d \geq n!$
- That is, the depth of the decision tree satisfies  $d \geq \log_2(n!)$
- But this is the number of comparisons needed in our sort
- We are left with a lower bound on the time complexity of  $\log_2(n!)$



# How Big is $\log_2(n!)$

- We showed in the second lecture that

$$\left(\frac{n}{2}\right)^{n/2} < n! < n^n$$

- It is not too difficult to show that asymptotically (i.e. as  $n \rightarrow \infty$ ) that  $n!$  approaches  $\sqrt{2\pi n} \left(\frac{n}{e}\right)^n$ —this is known as **Stirling's approximation**
- Thus

$$\begin{aligned}\log_2(n!) &\approx n \log_2(n) - n \log_2(e) + \frac{\log_2(n)}{2} + \frac{\log_2(2\pi)}{2} \\ &= \Theta(n \log_2(n))\end{aligned}$$

# How Big is $\log_2(n!)$

- We showed in the second lecture that

$$\left(\frac{n}{2}\right)^{n/2} < n! < n^n$$

- It is not too difficult to show that asymptotically (i.e. as  $n \rightarrow \infty$ ) that  $n!$  approaches  $\sqrt{2\pi n} \left(\frac{n}{e}\right)^n$ —this is known as **Stirling's approximation**
- Thus

$$\begin{aligned}\log_2(n!) &\approx n \log_2(n) - n \log_2(e) + \frac{\log_2(n)}{2} + \frac{\log_2(2\pi)}{2} \\ &= \Theta(n \log_2(n))\end{aligned}$$

# How Big is $\log_2(n!)$

- We showed in the second lecture that

$$\left(\frac{n}{2}\right)^{n/2} < n! < n^n$$

- It is not too difficult to show that asymptotically (i.e. as  $n \rightarrow \infty$ ) that  $n!$  approaches  $\sqrt{2\pi n} \left(\frac{n}{e}\right)^n$  —this is known as **Stirling's approximation**
- Thus

$$\begin{aligned}\log_2(n!) &\approx n \log_2(n) - n \log_2(e) + \frac{\log_2(n)}{2} + \frac{\log_2(2\pi)}{2} \\ &= \Theta(n \log_2(n))\end{aligned}$$

# How Big is $\log_2(n!)$

- We showed in the second lecture that

$$\left(\frac{n}{2}\right)^{n/2} < n! < n^n$$

- It is not too difficult to show that asymptotically (i.e. as  $n \rightarrow \infty$ ) that  $n!$  approaches  $\sqrt{2\pi n} \left(\frac{n}{e}\right)^n$ —this is known as **Stirling's approximation**
- Thus

$$\begin{aligned}\log_2(n!) &\approx n \log_2(n) - n \log_2(e) + \frac{\log_2(n)}{2} + \frac{\log_2(2\pi)}{2} \\ &= \Theta(n \log_2(n))\end{aligned}$$

# How Big is $\log_2(n!)$

- We showed in the second lecture that

$$\left(\frac{n}{2}\right)^{n/2} < n! < n^n$$

- It is not too difficult to show that asymptotically (i.e. as  $n \rightarrow \infty$ ) that  $n!$  approaches  $\sqrt{2\pi n} \left(\frac{n}{e}\right)^n$ —this is known as **Stirling's approximation**
- Thus

$$\begin{aligned}\log_2(n!) &\approx n \log_2(n) - n \log_2(e) + \frac{\log_2(n)}{2} + \frac{\log_2(2\pi)}{2} \\ &= \Theta(n \log_2(n))\end{aligned}$$

# Complexity of Sorting

- We therefore have a lower bound on the time complexity of  $\Omega(n \log(n))$
- This is true for any sort using binary comparisons
- We will see in the next lecture there exists algorithms with time complexity  $O(n \log(n))$
- This means our lower bound is tight—i.e. it is the true cost of the best algorithm
- Having a lower bound we know we are not going to obtain a substantially faster algorithm

# Complexity of Sorting

- We therefore have a lower bound on the time complexity of  $\Omega(n \log(n))$
- This is true for any sort using binary comparisons
- We will see in the next lecture there exists algorithms with time complexity  $O(n \log(n))$
- This means our lower bound is tight—i.e. it is the true cost of the best algorithm
- Having a lower bound we know we are not going to obtain a substantially faster algorithm

# Complexity of Sorting

- We therefore have a lower bound on the time complexity of  $\Omega(n \log(n))$
- This is true for any sort using binary comparisons
- We will see in the next lecture there exists algorithms with time complexity  $O(n \log(n))$
- This means our lower bound is tight—i.e. it is the true cost of the best algorithm
- Having a lower bound we know we are not going to obtain a substantially faster algorithm



# Complexity of Sorting

- We therefore have a lower bound on the time complexity of  $\Omega(n \log(n))$
- This is true for any sort using binary comparisons
- We will see in the next lecture there exists algorithms with time complexity  $O(n \log(n))$
- This means our lower bound is tight—i.e. it is the true cost of the best algorithm
- Having a lower bound we know we are not going to obtain a substantially faster algorithm

# Complexity of Sorting


- We therefore have a lower bound on the time complexity of  $\Omega(n \log(n))$
- This is true for any sort using binary comparisons
- We will see in the next lecture there exists algorithms with time complexity  $O(n \log(n))$
- This means our lower bound is tight—i.e. it is the true cost of the best algorithm
- Having a lower bound we know we are not going to obtain a substantially faster algorithm

# Complexity of Sorting

- We therefore have a lower bound on the time complexity of  $\Omega(n \log(n))$
- This is true for any sort using binary comparisons
- We will see in the next lecture there exists algorithms with time complexity  $O(n \log(n))$
- This means our lower bound is tight—i.e. it is the true cost of the best algorithm
- Having a lower bound we know we are not going to obtain a substantially faster algorithm


# Lessons

- Analysis of algorithms is hard
- Analysis is important: without it we don't know if we have a good algorithm or whether we should try to find a more efficient one
- Lower bounds are particularly important



# Lessons

- Analysis of algorithms is hard
- Analysis is important: without it we don't know if we have a good algorithm or whether we should try to find a more efficient one
- Lower bounds are particularly important



# Lessons

- Analysis of algorithms is hard
- Analysis is important: without it we don't know if we have a good algorithm or whether we should try to find a more efficient one
- Lower bounds are particularly important

