

Algorithms and Analysis

Lesson 7: *Iterate*



Array iteration, iterators

Outline

1. **Iterators**
2. The C++ Iterator Pattern
3. Linked-List Iterators
4. Generic Programming



Iterators

- One common task you want to do on a collection of objects is to iterate through each component■
- If we have a standardised method for all collections then it is much easier to remember what to do■
- But we can also write code that works for any collection that follows this pattern■
- This pattern is known as the **iterator pattern**■
- The pattern was first developed in C++, but is commonly used in many other languages■

Iterating Over C Arrays

- In C we would typically use a for-loop to iterate over an array

```
int n = 10;                                // size of array
int* begin = malloc(n*sizeof(10));          // malloc returns beginning of array
int* end = begin + n;                       // address past end of array

int sum = 0;
for(int* pt = begin; pt != end; pt++) {
    sum += *pt;                             // need to dereference pointer
}
```

- Ugly, but efficient

Outline

1. Iterators
2. **The C++ Iterator Pattern**
3. Linked-List Iterators
4. Generic Programming



C++ Iterator Pattern

- The C++ iterator pattern says for every `container<T>` we create a nested class called

`container::iterator`

which acts as a pointer (for arrays this could just be a pointer to the array)■

- The class should implement

- ★ a dereferencing operator `T operator* ()`■

- ★ an increment operator `operator++ ()`■

- ★ a not equal function

`bool operator!=(const ITER&, const ITER&)`

where `ITER` is `container::iterator`

A Beginning and an Ending

- In addition the container should have two methods

- ★ `begin()`

- ★ `end()`

that return iterators representing the first element and an iterator representing one position past the last element■

- Wow! That seems awfully complicated■
- Don't panic!■ We can hack this■

Array-based iterators

- For array based containers such as vector we don't actually need to create an iterator class as we can just use the normal pointer

```
template <typename T>
class Array {
private:
    T *data;
    unsigned length;
    unsigned capacity;
public:
    ...
    T* begin() {return data;}
    T* end() {return data+length;}
};
```

- That's all we need