



Understand Mappings

Mappings, Linear Maps, Solving Linear Systems

Adam Prügel-Bennett AICE3001/6002 Mathematics of Machine Learning <https://ecs-vlc.github.io/aice3001/>**Transforming Data**


- In the last lecture we spent time developing a sophisticated view of vector spaces and operators
- At a mathematical level machine learning can be viewed as performing an inverse mapping



- Although our mappings are not necessarily linear in either direction we learn a lot by understanding linear operators

Adam Prügel-Bennett AICE3001/6002 Mathematics of Machine Learning <https://ecs-vlc.github.io/aice3001/>**Linear Regression**


- $\mathbf{x}_k^T \mathbf{w}$ depends on distance from separating



- If $m > p$ then $\mathbf{X}$ isn't square so doesn't have an inverse
- Worse unless the data is accurate $\mathbf{y} \approx \mathbf{X}\mathbf{w} \Rightarrow$ no "solution"
- Problem solved by Gauss to predict the orbit of the asteroid Ceres

Adam Prügel-Bennett AICE3001/6002 Mathematics of Machine Learning <https://ecs-vlc.github.io/aice3001/>**Finding a Minimum**

- The minima of a one dimensional function, $f(x)$, are given by $f'(x) = 0$




- The minima of an n -dimensions function $f(\mathbf{x})$ are given by the set of equations

$$\frac{\partial f(\mathbf{x})}{\partial x_i} = 0 \quad \forall i = 1, \dots, n$$

Adam Prügel-Bennett AICE3001/6002 Mathematics of Machine Learning <https://ecs-vlc.github.io/aice3001/>

- Mappings**
- Linear Maps**

Adam Prügel-Bennett AICE3001/6002 Mathematics of Machine Learning <https://ecs-vlc.github.io/aice3001/>**Inverse Problems**

- Given m observations $\{(\mathbf{x}_k, y_k) | k = 1, \dots, m\}$ and p unknown $\mathbf{w} = (w_1, w_2, \dots, w_p)^T$ such that $\mathbf{x}_k^T \mathbf{w} = y_k$ then to find $\mathbf{w}$
- Define the *design matrix* as the matrix of feature vectors

$$\mathbf{X} = \begin{pmatrix} \mathbf{x}_1^T \\ \mathbf{x}_2^T \\ \vdots \\ \mathbf{x}_m^T \end{pmatrix} = \begin{pmatrix} x_{11} & x_{12} & \cdots & x_{1p} \\ x_{21} & x_{22} & \cdots & x_{2p} \\ \vdots & \vdots & \ddots & \vdots \\ x_{m1} & x_{m2} & \cdots & x_{mp} \end{pmatrix}$$

- and the target vector $\mathbf{y} = (y_1, y_2, \dots, y_m)^T$
- Then if $m = p$ we have $\mathbf{y} = \mathbf{X}\mathbf{w}$ or $\mathbf{w} = \mathbf{X}^{-1}\mathbf{y}$

Adam Prügel-Bennett AICE3001/6002 Mathematics of Machine Learning <https://ecs-vlc.github.io/aice3001/>**Linear Least Squares**

- The error of input pattern $\mathbf{x}_k$ is

$$\epsilon_k = \mathbf{x}_k^T \mathbf{w} - y_k$$

- The squared error

$$E(\mathbf{w}|\mathcal{D}) = \sum_{k=1}^m (\mathbf{x}_k^T \mathbf{w} - y_k)^2 = \sum_{k=1}^m \epsilon_k^2 = \|\epsilon\|^2$$

- We can define the error vector

$$\epsilon = \mathbf{X}\mathbf{w} - \mathbf{y}$$

(note that $\epsilon_k = \mathbf{x}_k^T \mathbf{w} - y_k$)

- Minimising this error is known as the least squares problem

Adam Prügel-Bennett AICE3001/6002 Mathematics of Machine Learning <https://ecs-vlc.github.io/aice3001/>**Gradients**

- The **grad** operator ∇ is the gradient operator in high dimensions

$$\nabla f(\mathbf{x}) = \begin{pmatrix} \frac{\partial f(\mathbf{x})}{\partial x_1} \\ \frac{\partial f(\mathbf{x})}{\partial x_2} \\ \vdots \\ \frac{\partial f(\mathbf{x})}{\partial x_n} \end{pmatrix}$$

- The partial derivatives (curly d's)

$$\frac{\partial f(\mathbf{x})}{\partial x_i}$$

means differentiate with respect to x_i treating all other components x_j as constantsAdam Prügel-Bennett AICE3001/6002 Mathematics of Machine Learning <https://ecs-vlc.github.io/aice3001/>

Least Squares Solution

- The least squared solution is give by

$$\begin{aligned}\nabla E(w|\mathcal{D}) &= \nabla \|\epsilon\|^2 = \nabla \|Xw - y\|^2 \\ &= \nabla (w^T X^T X w - 2w^T X^T y + y^T y) \\ &= 2(X^T X w - X^T y) = 0\end{aligned}$$

- Or

$$w = (X^T X)^{-1} X^T y = X^+ y$$

- $X^+ = (X^T X)^{-1} X^T$ is known as the pseudo inverse

Computing Gradients

- To understand gradients we sometimes need to go back to components

$$\begin{aligned}\nabla w^T M w &= \begin{pmatrix} \frac{\partial}{\partial w_1} \\ \frac{\partial}{\partial w_2} \\ \frac{\partial}{\partial w_3} \\ \vdots \end{pmatrix} \sum_{i,j} w_i M_{ij} w_j = \begin{pmatrix} \sum_j M_{1j} w_j + \sum_i w_i M_{i1} \\ \sum_j M_{2j} w_j + \sum_i w_i M_{i2} \\ \sum_j M_{3j} w_j + \sum_i w_i M_{i3} \\ \vdots \end{pmatrix} \\ &= M w + M^T w\end{aligned}$$


- It is tedious to compute these things component-wise, but when you need to understand what is going on then go back to the basics

Solving Inverse Problems

- Gauss showed us how to solve **over-constrained** problems (we have more observations than parameters)
- We seek a solution which isn't necessarily exact but minimises an error
- But, what if we have more parameters than observations
- That is, we are **under-constrained**
- Note that in some directions you might be over-constrained and in other directions under-constrained
- This is very typical of most machine learning problems

What is the Inverse?

- Many points can map to the same points



Missing Bits of the Mathematics

- Note that $\|a\|^2 = a^T a = \sum_i a_i^2$

$$\begin{aligned}\|Xw - y\|^2 &= (Xw - y)^T (Xw - y) = (w^T X^T - y^T) (Xw - y) \\ &= w^T X^T X w - 2w^T X^T y + y^T y\end{aligned}$$

- Where we have used $w^T X^T y = y^T X w = \sum_{i,j} w_i X_{ji} y_j = \sum_{i,j} y_i X_{ij} w_j$


- Also $\nabla w^T M w = M w + M^T w$

- If $M = M^T$ (i.e. M is symmetric) then $\nabla w^T M w = 2M w$

- As $(AB)^T = B^T A^T$ then $(X^T X)^T = X^T X^{TT} = X^T X$ and $X^T X$ is symmetric


Outline

- Mappings
- Linear Maps



Under Constrained Systems

- If we have less data-points than parameters then there will be multiple solutions



Under-constrained Systems

- The system is **under-constrained**
- We have more unknowns than equations
- The inverse is not unique
- Solving the inverse problem $(w = (X^T X)^{-1} X^T y)$ is said to be **ill-posed**
- The inverse $(X^T X)^{-1}$ doesn't exist
- If we have a complicated learning machine and not sufficient data we often end with an ill-posed inverse problem (there are lots of sets of parameters that explain the data)


III-Conditions

- Singular matrices are rare (although they occur when we don't have enough data), but matrices that are close to being singular are common
- If a matrix is close to singular it is ill-conditioned
- Ill-conditioned matrices have some small eigenvalues
- All points get contracted towards a plane
- Large matrices are very often ill conditioned

III-Conditioning in ML

- Ill-conditioning in machine learning occurs when a very small change in the learning data causes a large change in the predictions of the learning machine
- In linear regression the matrix $X^T X$ is typically ill-conditioned when we have as many data points as parameters
- Much of machine learning is concerned with making learning machines better conditioned
- Adding regularisers is one approach to achieve this

III-Conditioned Matrices



Summary

- Linear mappings are commonly used in machine learning algorithms such as regression
- We will often meet the pseudo-inverse involving inverting $X^T X$
- They can be inherently unstable to noise in the inputs