

Mathematics of Machine Learning

Symmetry



Inductive Bias, Symmetry, Invariance, Group theory

Outline

1. **Inductive Bias**
2. Invariance
3. Group Theory




Inductive Bias

- Learning machines differ in how they split up the space of inputs■
- Perceptrons split the space using a hyperplane, RBFs split the space depending on some set of centres, MLPs successive split the world at different layers■
- These differences are known as the **inductive bias** of the machine■
- The different inductive bias lead to different performance■
- How can we exploit the inductive bias to get good performance?■

The Real World

- The problems that we care about come from a highly structured world where the solutions inherit some of the properties of that world■
- Usually similar input have similar outputs (we don't expect to change one pixel in an image and that it should be classified differently)■
- The classes are often quite well separated■



Smoothness

- A natural assumption is smoothness (the classification surface or regression surface changes slowly as we change the input)■
- Often there is a hyperparameter that controls this
 - ★ The kernel parameter γ in SVMs (or ℓ in Gaussian Processes)
 - ★ k in k -nearest neighbours
 - ★ The size of the L_2 regularisation term in neural networks■
- We often have to choose these using trial and error (using a validation set)■

Outline


1. Inductive Bias
2. **Invariance**
3. Group Theory



Symmetry

- There are sometimes symmetries in the world we can exploit■
- In image classification we consider an object should be classified the same wherever it is in the image■
- The classification should be invariant to translations (scaling and perhaps rotations)■
- The classification function possesses a translational symmetry■
- Learning machines that respect translational invariance have far less propensity to overfit■—they don't need to learn that the same object in a different part of the image is the same■

Convolutional Neural Networks



Equivariance


- CNNs are not translationally invariant■
- The output will be different if we shift the input■
- They are (up to edge effects) **equivariant** in that we would get the same result if we shifted both the input and the output in the same way■
- They are not perfectly equivariant (they break at the pixel level and at the full image level—due to edges)■
- But they are sufficient good that CNNs have dominated computer vision for years■(ignoring visual transformers)■

Other Symmetries

- The identity of an object should not change if we move the camera further away or rotate the camera■
- CNNs are not naturally scale or rotationally invariant■ (although there are attempts to remedy this)■
- Rotation invariance doesn't always reflect “the world”■ —people usually stand on their feet not on their heads■
- Although you want rotational invariance when interpreting aerial images■

Scale Symmetry


- CNNs are not scale invariant■
- There are various pyramid image processing techniques to try and build in approximate scale invariance■
- However, in many image classification tasks we concentrate on the object in the foreground■
- Many datasets rescale objects in the image so they are roughly the same size■



Learning Invariance

- Currently we are not smart enough to come up with networks that are scale invariant or rotational invariant or invariant to small distortions
- We therefore hope that our networks learn this by training on objects of different sizes, orientations, lighting conditions, etc.
- Knowing this is an invariance we want, it is now common practice to do data augmentation where we perform transformations that replicate physical plausible changes in the data
- We are removing spurious rules by (artificially) increasing our dataset size

Augmentations



- Data augmentation is standard practice in deep learning for images and makes a very considerable difference

Other Symmetries Exist

- In NLP it is now common to translate sentences to a foreign language and back to the original language to learn invariance to minor changes in the words used■
- There are cases where we care about sets of objects, but not their ordering■
- An example might be sets of objects in an image or vertices in a graph■
- Here constructing operators that are equivariant (the same if we permute the inputs and outputs) can again reduce overfitting■

Normalisation

- Sometimes clever normalisation can make a lot of difference to the performance of an algorithm■
- We might do this by feature engineering■ (divide the length on the nose by the width between the persons eyes)■
- We might do this by normalising the output■—use cosine similarity rather than distance

$$\cos(\theta) = \frac{a^T b}{\|a\| \|b\|} \quad \blacksquare$$

- These make the results invariant■ to the distance of the camera■ or the length of a and b ■

Outline

1. Inductive Bias
2. Invariance
3. **Group Theory**



Group Theory

- Symmetries are very well studied in mathematics■
- The language of symmetries are **groups**■
- These capture the structure of transformations that represent some symmetry■
- Group theory is highly abstract and it is easy to lose sight of its connection to symmetry, but it has proved itself extraordinarily powerful in revealing structures■

Groups


- Groups consists of a set (we can think of the elements as transformations), $\mathcal{G} = \{a, b, \dots\}$ ■
- And an operator “.” (which we can often think of as composition)■
- That is, $a \cdot b$ we can interpret as apply transformation b and then apply transformation a ■
- The set and transform form a group if they satisfy four axioms
 - ★ closure: for all $a, b \in \mathcal{G}$ then $a \cdot b \in \mathcal{G}$
 - ★ associativity: $a \cdot (b \cdot c) = (a \cdot b) \cdot c$
 - ★ existence of an identity e such that $a \cdot e = a$ for all a
 - ★ Every element, a , has an inverse a^{-1} such that $a^{-1} \cdot a = e$ ■

Tossing a coin

- We consider a coin with two actions
 - ★ flip the coin: f
 - ★ leave the coin alone: e ■
- These form a group (the cyclic group C_2)
 - ★ Closure is obvious $f \cdot e = f$, $f \cdot f = e$, $e \cdot e = e$ and $e \cdot f = f$
 - ★ Associativity: e.g. $(e \cdot f) \cdot f = e \cdot (f \cdot f)$
 - ★ e is the identity
 - ★ $e^{-1} = e$ and $f^{-1} = f$ ■

The Four Group


- A slightly less trivial example represents the set of transformations that leaves a rectangle invariant



	e	v	h	r
e	e	v	h	r
v	v	e	r	h
h	h	r	e	v
r	r	h	v	e

Non-commutativity

- Not all groups commute
- For 3-d rotations : $R_x \cdot R_z \neq R_z \cdot R_x$



Associativity

- We can think of the elements of a group as transformations acting on some object (e.g. rotations of a book)■
- We consider $\cdot$ to denote composition so $a \cdot b$ denotes apply action b then action a ■
- When we say $c = a \cdot b$ we mean that action c is equivalent to apply action b followed by action a ■
- Suppose $g = a \cdot b$ and $h = b \cdot c$ then

$$g \cdot c = a \cdot h$$

$$(a \cdot b) \cdot c = a \cdot (b \cdot c)$$

- These correspond to an equivalent set of actions■

Permutations

- The set of permutations of n objects form a group (known as the symmetric group S_n)■
- The composition of a permutation is a permutation■
- There is an identity (do nothing)■
- For every permutation there is an inverse permutation■
- Obviously S_n has $n!$ elements■(you can reorder elements in $n!$ ways)■
- Permutations have a lot of structure (in terms of elements cycling, subgroups, etc.)■

Infinite Groups

- The set of integers under addition form a group■
- Its closed, has an identity, 0, and each element n has an inverse $-n$ ■
- The group describes the set of discrete shifts■
- The set of rational number under addition also forms a group■
- Nothing new here, you've known about these since you were a toddler■

Continuous Groups

- The set of reals under addition form a group and describes translations in one dimension■
- The set of reals excluding 0 form a group under multiplication with an identity 1 and inverse of x being $1/x$ ■
- These describe scale transformation■
- These are not terrifically interesting groups■(or at least groups you are so familiar with that they are now boring)■
- Things get more interesting in high dimensional space■

Lie Groups

- Continuous groups are known as Lie Groups■
- They describe things like general translational invariance, rotational invariance, relativistic invariance■
- The transformations can be represented by a set of matrices■
- To study these one looks at infinitesimal transformations and the algebra between these infinitesimal transformations (Lie algebras)■
- This is much studied in physics and occasionally studied in machine learning, although more on the sidelines■

Rotations $SO(n)$

- The set of $n \times n$ orthogonal matrices (matrices, $\mathbf{M}$, such that $\mathbf{M}^T \mathbf{M} = \mathbf{M} \mathbf{M}^T = \mathbf{I}$) form a group $O(n)$ ■
- Note that $\det(\mathbf{M}) = \pm 1$ ■
- These correspond to rotations and reflections■
- The group of matrices that don't correspond to reflections (where $\det(\mathbf{M}) = 1$) form a subgroup $SO(n)$ ■
- $SO(2)$ consist of the 2-d rotation matrices

$$\begin{pmatrix} \cos(\theta) & \sin(\theta) \\ -\sin(\theta) & \cos(\theta) \end{pmatrix} \blacksquare$$

Summary

- Invariances are important as if a machine properly captures a true invariance it can massively limit the space of functions being approximated—reducing the chances of finding spurious rules
- Often it is hard to build-in invariances into the machine learning model and practitioners will often resort to data augmentation in the hope that these invariances can be learned
- There is a mathematical language around describing the structure of symmetries: **group theory**
- You should know *group theory* exists, it is occasionally used in machine learning, but not that much
- I'm not going to expect you to know any details about group theory