


Boosting, AdaBoost, Gradient Boosting

1. **Boosting**
2. **AdaBoost**
3. **Gradient Boosting**



Boosting

- In boosting we make a **strong learner** by using a weighted sum of **weak learners**

$$C_n(\mathbf{x}) = \sum_{i=1}^n \alpha_i \hat{h}_i(\mathbf{x})$$


- Weak learners, $\hat{h}_i(\mathbf{x})$, are learning machine that do a little better than chance
- The trick is to choose the weights, α_i
- Because the weak learners do little better than chance we (miraculously) **don't** overfit that much

Shallow Trees

- One of the most effective type of weak learner are very shallow trees
- Sometimes we just use one variable (the stump) although usually we would use slightly deeper trees
- There are different algorithms for choosing the weights
 - ★ **adaboost**—a classic algorithm for binary classification
 - ★ **gradient boosting**—used for regression, trains a weak learner on the residual errors

Outline

1. **Boosting**
2. **AdaBoost**
3. **Gradient Boosting**



Boosting a Binary Classifier

- Suppose we have a binary classification task with data $\mathcal{D} = \{(\mathbf{x}^\mu, y^\mu) | \mu = 1, 2, \dots, m\}$ with $y^\mu \in \{-1, 1\}$
- Our i^{th} weak learner provides a prediction $\hat{h}_i(\mathbf{x}^\mu) \in \{-1, 1\}$
- We ask, can we find a linear combination


$$C_n(\mathbf{x}) = \alpha_1 \hat{h}_1(\mathbf{x}) + \alpha_2 \hat{h}_2(\mathbf{x}) + \dots + \alpha_n \hat{h}_n(\mathbf{x})$$

- So that $\text{sgn}(C_n(\mathbf{x}))$ is a strong learner?
- Note we want $y^\mu C_n(\mathbf{x}^\mu) > 0$

AdaBoost

- AdaBoost is a classic solution to this problem
- It assigns an “loss function”

$$L_n = \sum_{\mu=1}^m e^{-y^\mu C_n(\mathbf{x}^\mu)}$$



- This punishes examples where there is an errors more than correct classifications

Iterative Learning

- We build up a strong learner iteratively (greedily)

$$C_n(\mathbf{x}) = C_{n-1}(\mathbf{x}) + \alpha_n \hat{h}_n(\mathbf{x})$$

- Defining $w_1^\mu = 1$ and $w_n^\mu = e^{-y^\mu C_{n-1}(\mathbf{x}^\mu)}$ then


$$\begin{aligned} L_n(\alpha_n) &= \sum_{\mu=1}^m e^{-y^\mu C_n(\mathbf{x}^\mu)} = \sum_{\mu=1}^m e^{-y^\mu (C_{n-1}(\mathbf{x}^\mu) + \alpha_n \hat{h}_n(\mathbf{x}^\mu))} \\ &= \sum_{\mu=1}^m w_n^\mu e^{-\alpha_n y^\mu \hat{h}_n(\mathbf{x}^\mu)} = e^{-\alpha_n} \sum_{\mu: y^\mu \neq \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu + e^{\alpha_n} \sum_{\mu: y^\mu = \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu \\ &= e^{-\alpha_n} \sum_{\mu=1}^m w_n^\mu + (e^{\alpha_n} - e^{-\alpha_n}) \sum_{\mu: y^\mu \neq \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu \end{aligned}$$

Choosing a Weak Classifier

- To minimise the loss

$$L_n(\alpha_n) = e^{-\alpha_n} \sum_{\mu=1}^m w_n^\mu + (e^{\alpha_n} - e^{-\alpha_n}) \sum_{\mu: y^\mu \neq \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu$$

- We choose the weak learner with the lowest value of

$$\sum_{\mu: y^\mu \neq \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu = \sum_{\mu: y^\mu \neq \hat{h}_n(\mathbf{x}^\mu)} e^{-y^\mu C_{n-1}(\mathbf{x}^\mu)}$$



- That is, it misclassifies only where the other learners classify well

Algorithm


- Start with a set of weak learners \mathcal{W}
- Associate a weight, w_n^μ , with every data point (\mathbf{x}^μ, y^μ) , $\mu = 1, 2, \dots, m$
- Initially $w_1^\mu = 1$ (large weight, w_n^μ means (\mathbf{x}^μ, y^μ) is poorly classified)
- Choose the weak learning, $\hat{h}_n(\mathbf{x}) \in \mathcal{W}$, that minimises $\sum_{\mu: y^\mu \neq \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu$
- Update predictor $C_n(\mathbf{x}) = C_{n-1}(\mathbf{x}) + \alpha_n \hat{h}_n(\mathbf{x})$ where
$$\alpha_n = \frac{1}{2} \log \left(\frac{\sum_{\mu: y^\mu = \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu}{\sum_{\mu: y^\mu \neq \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu} \right)$$
- Update $w_{n+1}^\mu = w_n^\mu e^{-y^\mu \alpha_n \hat{h}_n(\mathbf{x}^\mu)}$
- Go to 4

Outline

- Boosting
- AdaBoost
- Gradient Boosting



Fitting a Sin Wave



Choosing Weights

- We now choose the weight α_n to minimise the loss $L_n(\alpha_n)$

$$\frac{\partial L_n(\alpha_n)}{\partial \alpha_n} = e^{\alpha_n} \sum_{\mu: y^\mu \neq \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu - e^{-\alpha_n} \sum_{\mu: y^\mu = \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu = 0$$

- That is

$$e^{2\alpha_n} = \frac{\sum_{\mu: y^\mu = \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu}{\sum_{\mu: y^\mu \neq \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu} \quad \text{or} \quad \alpha_n = \frac{1}{2} \log \left(\frac{\sum_{\mu: y^\mu = \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu}{\sum_{\mu: y^\mu \neq \hat{h}_n(\mathbf{x}^\mu)} w_n^\mu} \right)$$

Performance


- Adaboost works well with weak learners, usually out-performing bagging
- It doesn't work well with strong learners (tends to over-fit)
- It is limited to binary classification (there are generalisation, but they are difficult to get to work)
- It has fallen from fashion
- In contrast **gradient boosting** used for regression is very popular

Gradient Boosting


- In gradient boosting we again build a strong learner as a linear combination of weak learners

$$C_n(\mathbf{x}) = C_{n-1}(\mathbf{x}) + \hat{h}_n(\mathbf{x})$$

- Gradient boosting used on regression (again using decision trees)
- At each step $\hat{h}_n(\mathbf{x})$ is trained to predict the residual error, $\Delta_{n-1} = y - C_{n-1}(\mathbf{x})$, (i.e. the target minus the current prediction)
- (This difference looks a bit like a gradient hence the rather confusing name)



- We can keep on going




- But we will over-fit eventually

XGBoost

- XGBoost is an implementation of gradient boosting that won the Higg's Boson challenge and regularly wins Kaggle competitions
- XGBoost stands for eXtreme Gradient Boosting
- It was much faster than most gradient boosting algorithms and scales to billions of training data points—although GBM is often better
- It uses a cleverly chosen regularisation term to favour simple trees
- Finds a clever way to approximately minimise error plus regulariser very fast
- Rather a bodge of optimisation hacks

- Like many algorithms we often get better results by early stopping



- Use cross-validation against a validation set to decide when to stop

Conclusion

- Ensemble methods have proved themselves to be very powerful
- Tend to work best with very simple models (true of random forest and boosting)—seems to reduce over-fitting
- XGBoost or GBM are currently the best methods for tabular data (particular for large training sets)—probably
- For images, signal and speech deep learning can give very significant advantage
- Probabilistic models can be better if you have a good model