


# Advanced Machine Learning


## *When Machine Learning Works*



*When ML Works, Bias Variance*

# Outline

1. **What Makes a Good Learning Machine?**
2. Bias-Variance Dilemma



# What Makes a Good Learning Machine?

- We want to understand why some machine learning techniques work well and other don't
- To understand why these works we need to understand what makes a good learning machine
- For this we have to get conceptual and think about **generalisation** performance

*generalisation: how well do we do on unseen data as opposed to the training data*

# What Makes a Good Learning Machine?

- We want to understand why some machine learning techniques work well and other don't
- To understand why these works we need to understand what makes a good learning machine
- For this we have to get conceptual and think about **generalisation** performance

*generalisation: how well do we do on unseen data as opposed to the training data*

# What Makes a Good Learning Machine?

- We want to understand why some machine learning techniques work well and other don't
- To understand why these works we need to understand what makes a good learning machine
- For this we have to get conceptual and think about **generalisation** performance

*generalisation: how well do we do on unseen data as opposed to the training data*

# What Makes a Good Learning Machine?

- We want to understand why some machine learning techniques work well and other don't
- To understand why these works we need to understand what makes a good learning machine
- For this we have to get conceptual and think about **generalisation** performance

*generalisation: how well do we do on unseen data as opposed to the training data*

# What Makes Machine Learning Hard?

- Typically work in high dimensions (i.e. have many features)
- The problem can be over-constrained (i.e. we have conflicting data to deal with)
- The problem can be under-constrained (i.e. there are many possible solutions that are consistent with the data)
- Typically in machine learning the data will be over-constrained in some dimensions and under-constrained in others
- We can't visualise the data to know what is going on

# What Makes Machine Learning Hard?

- Typically work in high dimensions (i.e. have many features)
- The problem can be over-constrained (i.e. we have conflicting data to deal with)
- The problem can be under-constrained (i.e. there are many possible solutions that are consistent with the data)
- Typically in machine learning the data will be over-constrained in some dimensions and under-constrained in others
- We can't visualise the data to know what is going on



# What Makes Machine Learning Hard?

- Typically work in high dimensions (i.e. have many features)
- The problem can be over-constrained (i.e. we have conflicting data to deal with)—**solve by minimising an error function**
- The problem can be under-constrained (i.e. there are many possible solutions that are consistent with the data)
- Typically in machine learning the data will be over-constrained in some dimensions and under-constrained in others
- We can't visualise the data to know what is going on

# What Makes Machine Learning Hard?

- Typically work in high dimensions (i.e. have many features)
- The problem can be over-constrained (i.e. we have conflicting data to deal with)—solve by minimising an error function
- The problem can be under-constrained (i.e. there are many possible solutions that are consistent with the data)
- Typically in machine learning the data will be over-constrained in some dimensions and under-constrained in others
- We can't visualise the data to know what is going on

# What Makes Machine Learning Hard?

- Typically work in high dimensions (i.e. have many features)
- The problem can be over-constrained (i.e. we have conflicting data to deal with)—solve by minimising an error function
- The problem can be under-constrained (i.e. there are many possible solutions that are consistent with the data)—need to choose a plausible solution
- Typically in machine learning the data will be over-constrained in some dimensions and under-constrained in others
- We can't visualise the data to know what is going on

# What Makes Machine Learning Hard?

- Typically work in high dimensions (i.e. have many features)
- The problem can be over-constrained (i.e. we have conflicting data to deal with)—solve by minimising an error function
- The problem can be under-constrained (i.e. there are many possible solutions that are consistent with the data)—need to choose a plausible solution
- Typically in machine learning the data will be over-constrained in some dimensions and under-constrained in others
- We can't visualise the data to know what is going on

# What Makes Machine Learning Hard?

- Typically work in high dimensions (i.e. have many features)
- The problem can be over-constrained (i.e. we have conflicting data to deal with)—solve by minimising an error function
- The problem can be under-constrained (i.e. there are many possible solutions that are consistent with the data)—need to choose a plausible solution
- Typically in machine learning the data will be over-constrained in some dimensions and under-constrained in others
- We can't visualise the data to know what is going on

# Least Squared Errors

- Suppose we want to learn some output  $y$  for a feature vector  $\mathbf{x}$
- We construct a learning machine that makes a prediction  $\hat{f}(\mathbf{x}|\boldsymbol{\theta})$
- We typically choose the machine to minimise a *training loss*

$$L_T(\mathcal{D}) = \sum_{(\mathbf{x}, y) \in \mathcal{D}} \left( \hat{f}(\mathbf{x}|\boldsymbol{\theta}) - y \right)^2$$

# Least Squared Errors

- Suppose we want to learn some output  $y$  for a feature vector  $\mathbf{x}$
- We construct a learning machine that makes a prediction  $\hat{f}(\mathbf{x}|\boldsymbol{\theta})$
- We typically choose the machine to minimise a *training loss*

$$L_T(\mathcal{D}) = \sum_{(\mathbf{x}, y) \in \mathcal{D}} \left( \hat{f}(\mathbf{x}|\boldsymbol{\theta}) - y \right)^2$$

# Least Squared Errors

- Suppose we want to learn some output  $y$  for a feature vector  $\mathbf{x}$
- We construct a learning machine that makes a prediction  $\hat{f}(\mathbf{x}|\boldsymbol{\theta})$
- We typically choose the machine to minimise a *training loss*

$$L_T(\mathcal{D}) = \sum_{(\mathbf{x}, y) \in \mathcal{D}} \left( \hat{f}(\mathbf{x}|\boldsymbol{\theta}) - y \right)^2$$



# Least Squared Errors

- Suppose we want to learn some output  $y$  for a feature vector  $\mathbf{x}$
- We construct a learning machine that makes a prediction  $\hat{f}(\mathbf{x}|\boldsymbol{\theta})$
- We typically choose the machine to minimise a *training loss*

$$L_T(\mathcal{D}) = \sum_{(\mathbf{x}, y) \in \mathcal{D}} \left( \hat{f}(\mathbf{x}|\boldsymbol{\theta}) - y \right)^2 = \sum_{i=1}^m \left( \hat{f}(\mathbf{x}_i) - y_i \right)^2$$

where  $\mathcal{D} = \{(\mathbf{x}_i, y_i)\}_{i=1}^m$  is a set of size  $m$ , sampled a probability distribution  $\mu(\mathbf{x}, y)$

# Least Squared Errors

- Suppose we want to learn some output  $y$  for a feature vector  $\mathbf{x}$
- We construct a learning machine that makes a prediction  $\hat{f}(\mathbf{x}|\boldsymbol{\theta})$
- We typically choose the machine to minimise a *training loss*

$$L_T(\mathcal{D}) = \sum_{(\mathbf{x}, y) \in \mathcal{D}} \left( \hat{f}(\mathbf{x}|\boldsymbol{\theta}) - y \right)^2 = \sum_{i=1}^m \left( \hat{f}(\mathbf{x}_i) - y_i \right)^2$$


where  $\mathcal{D} = \{(\mathbf{x}_i, y_i)\}_{i=1}^m$  is a set of size  $m$ , sampled a probability distribution  $\mu(\mathbf{x}, y)$

- We call this machine  $\hat{f}(\mathbf{x}|\boldsymbol{\theta}_{\mathcal{D}})$

# Generalisation Error

- We want to minimise the *generalisation loss* which in this case is

$$L_G(\mathcal{D}) = \sum_{(\mathbf{x}, y) \in \mathcal{Z}} \mu(\mathbf{x}, y) \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - y \right)^2$$




(we can estimate this if we have some labelled examples  $(\mathbf{x}_i, y_i)$  which we have not trained on)

- We want to minimise  $L_G(\mathcal{D})$  but in practice we are minimising  $L_T(\mathcal{D})$ , *what could possibly go wrong?*

# Generalisation Error

- We want to minimise the *generalisation loss* which in this case is

$$L_G(\mathcal{D}) = \sum_{(\mathbf{x}, y) \in \mathcal{Z}} \mu(\mathbf{x}, y) \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - y \right)^2$$




(we can estimate this if we have some labelled examples  $(\mathbf{x}_i, y_i)$  which we have not trained on)

- We want to minimise  $L_G(\mathcal{D})$  but in practice we are minimising  $L_T(\mathcal{D})$ , *what could possibly go wrong?*

# Generalisation Error

- We want to minimise the *generalisation loss* which in this case is

$$L_G(\mathcal{D}) = \sum_{(\mathbf{x}, y) \in \mathcal{Z}} \mu(\mathbf{x}, y) \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - y \right)^2$$



(we can estimate this if we have some labelled examples  $(\mathbf{x}_i, y_i)$  which we have not trained on)


- We want to minimise  $L_G(\mathcal{D})$  but in practice we are minimising  $L_T(\mathcal{D})$ , *what could possibly go wrong?*

# Too Simple or Too Complex?

- Fit  $\hat{f}(x|\boldsymbol{\theta}_{\mathcal{D}})$  to data


# Too Simple or Too Complex?

- Fit  $\hat{f}(x|\theta_{\mathcal{D}})$  to data



# Too Simple or Too Complex?


- Fit  $\hat{f}(x|\theta_{\mathcal{D}})$  to data





# Too Simple or Too Complex?


- Fit  $\hat{f}(x|\theta_{\mathcal{D}})$  to data



# Too Simple or Too Complex?


- Fit  $\hat{f}(x|\theta_{\mathcal{D}})$  to data

$$y = 0.12 + 0.82 x^1 - 1.5 x^2 + 0.052 x^3 + 2.7 x^4 - 0.17 x^5 - 1.6 x^6 + 0.056 x^7 + 0.36 x^8 - 0.0051 x^9 - 0.027 x^{10}$$




# Measuring Generalisation Error for Regression

- Consider the regression example. The root mean squared error is



# Outline

1. What Makes a Good Learning Machine?
2. **Bias-Variance Dilemma**



# Expected Generalisation Performance

- Our generalisation performance will depend on our training set,  $\mathcal{D}$
- To reason about generalisation we can ask what is the *expected generalisation loss*, when we average over all different data sets of size  $m$  drawn independently from  $\mu(\mathbf{x}, y)$
- For each data set,  $\mathcal{D}$ , we would learn a different approximator  $\hat{f}(\mathbf{x}|\boldsymbol{\theta}_{\mathcal{D}})$
- Note that in practice we only get one data set. We might be lucky and do better than the expected generalisation or we might be unlucky and do worse

# Expected Generalisation Performance

- Our generalisation performance will depend on our training set,  $\mathcal{D}$
- To reason about generalisation we can ask what is the *expected generalisation loss*, when we average over all different data sets of size  $m$  drawn independently from  $\mu(\mathbf{x}, y)$
- For each data set,  $\mathcal{D}$ , we would learn a different approximator  $\hat{f}(\mathbf{x}|\boldsymbol{\theta}_{\mathcal{D}})$
- Note that in practice we only get one data set. We might be lucky and do better than the expected generalisation or we might be unlucky and do worse

# Expected Generalisation Performance


- Our generalisation performance will depend on our training set,  $\mathcal{D}$
- To reason about generalisation we can ask what is the *expected generalisation loss*, when we average over all different data sets of size  $m$  drawn independently from  $\mu(\mathbf{x}, y)$
- For each data set,  $\mathcal{D}$ , we would learn a different approximator  $\hat{f}(\mathbf{x}|\boldsymbol{\theta}_{\mathcal{D}})$
- Note that in practice we only get one data set. We might be lucky and do better than the expected generalisation or we might be unlucky and do worse

# Expected Generalisation Performance


- Our generalisation performance will depend on our training set,  $\mathcal{D}$
- To reason about generalisation we can ask what is the *expected generalisation loss*, when we average over all different data sets of size  $m$  drawn independently from  $\mu(\mathbf{x}, y)$
- For each data set,  $\mathcal{D}$ , we would learn a different approximator  $\hat{f}(\mathbf{x}|\boldsymbol{\theta}_{\mathcal{D}})$
- Note that in practice we only get one data set. We might be lucky and do better than the expected generalisation or we might be unlucky and do worse




# Approximation and Estimation Errors




# Approximation and Estimation Errors




# Approximation and Estimation Errors




# Approximation and Estimation Errors




# Approximation and Estimation Errors




# Approximation and Estimation Errors



# Approximation and Estimation Errors




# Approximation and Estimation Errors







# Approximation and Estimation Errors




# Approximation and Estimation Errors




# Approximation and Estimation Errors




# Approximation and Estimation Errors




# Approximation and Estimation Errors




# Approximation and Estimation Errors



# Approximation and Estimation Errors




# Approximation and Estimation Errors






# Approximation and Estimation Errors



# Approximation and Estimation Errors



# Mean Machine

- To help understand generalisation we can consider the mean prediction with respect to machines trained with all data sets of size  $m$

$$\hat{f}_m(\mathbf{x}) = \mathbb{E}_{\mathcal{D}} \left[ \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) \right]$$

- We can define the **bias** to be generalisation performance of the mean machine

$$B = \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \left( \hat{f}_m(\mathbf{x}) - y \right)^2$$

# Mean Machine


- To help understand generalisation we can consider the mean prediction with respect to machines trained with all data sets of size  $m$

$$\hat{f}_m(\mathbf{x}) = \mathbb{E}_{\mathcal{D}} \left[ \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) \right]$$


- We can define the **bias** to be generalisation performance of the mean machine

$$B = \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \left( \hat{f}_m(\mathbf{x}) - y \right)^2$$


# Regression Example $n = 1$




# Regression Example $n = 1$



# Regression Example $n = 1$




# Regression Example $n = 1$







# Regression Example $n = 5$




# Regression Example $n = 5$



# Regression Example $n = 5$



# Regression Example $n = 5$



# Bias and Variance

Consider the expected generalisation for data sets of size  $|\mathcal{D}| = m$

$$\bar{L}_G = \mathbb{E}_{\mathcal{D}}[L_G(\mathcal{D})]$$

# Bias and Variance

Consider the expected generalisation for data sets of size  $|\mathcal{D}| = m$

$$\bar{L}_G = \mathbb{E}_{\mathcal{D}}[L_G(\mathcal{D})] = \mathbb{E}_{\mathcal{D}} \left[ \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - y \right)^2 \right]$$

# Bias and Variance

Consider the expected generalisation for data sets of size  $|\mathcal{D}| = m$

$$\begin{aligned}\bar{L}_G &= \mathbb{E}_{\mathcal{D}}[L_G(\mathcal{D})] = \mathbb{E}_{\mathcal{D}} \left[ \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - y \right)^2 \right] \\ &= \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - y \right)^2 \right]\end{aligned}$$

# Bias and Variance

Consider the expected generalisation for data sets of size  $|\mathcal{D}| = m$

$$\begin{aligned}\bar{L}_G &= \mathbb{E}_{\mathcal{D}}[L_G(\mathcal{D})] = \mathbb{E}_{\mathcal{D}} \left[ \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - y \right)^2 \right] \\ &= \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - y \right)^2 \right] \\ &= \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) + \hat{f}_m(\mathbf{x}) - y \right)^2 \right]\end{aligned}$$



# Bias and Variance

Consider the expected generalisation for data sets of size  $|\mathcal{D}| = m$

$$\begin{aligned}\bar{L}_G &= \mathbb{E}_{\mathcal{D}}[L_G(\mathcal{D})] = \mathbb{E}_{\mathcal{D}} \left[ \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - y \right)^2 \right] \\ &= \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - y \right)^2 \right] \\ &= \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right) + \left( \hat{f}_m(\mathbf{x}) - y \right) \right)^2 \right]\end{aligned}$$

# Bias and Variance

Consider the expected generalisation for data sets of size  $|\mathcal{D}| = m$

$$\begin{aligned}\bar{L}_G &= \mathbb{E}_{\mathcal{D}}[L_G(\mathcal{D})] = \mathbb{E}_{\mathcal{D}} \left[ \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \left( \hat{f}(\mathbf{x}|\boldsymbol{\theta}_{\mathcal{D}}) - y \right)^2 \right] \\&= \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x}|\boldsymbol{\theta}_{\mathcal{D}}) - y \right)^2 \right] \\&= \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \left( \hat{f}(\mathbf{x}|\boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right) + \left( \hat{f}_m(\mathbf{x}) - y \right) \right)^2 \right] \\&= \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \left( \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x}|\boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right)^2 \right] + \left( \hat{f}_m(\mathbf{x}) - y \right)^2 \right. \\&\quad \left. + 2 \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x}|\boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right) \left( \hat{f}_m(\mathbf{x}) - y \right) \right] \right)\end{aligned}$$

# Cross Term

- The cross term vanishes

$$C = \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right) \left( \hat{f}_m(\mathbf{x}) - y \right) \right]$$

# Cross Term

- The cross term vanishes

$$\begin{aligned} C &= \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right) \left( \hat{f}_m(\mathbf{x}) - y \right) \right] \\ &= \left( \mathbb{E}_{\mathcal{D}} \left[ \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) \right] - \hat{f}_m(\mathbf{x}) \right) \left( \hat{f}_m(\mathbf{x}) - y \right) \end{aligned}$$

# Cross Term

- The cross term vanishes

$$\begin{aligned} C &= \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right) \left( \hat{f}_m(\mathbf{x}) - y \right) \right] \\ &= \left( \mathbb{E}_{\mathcal{D}} \left[ \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) \right] - \hat{f}_m(\mathbf{x}) \right) \left( \hat{f}_m(\mathbf{x}) - y \right) \\ &= \left( \hat{f}_m(\mathbf{x}) - \hat{f}_m(\mathbf{x}) \right) \left( \hat{f}_m(\mathbf{x}) - y \right) \end{aligned}$$

# Cross Term

- The cross term vanishes

$$\begin{aligned} C &= \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right) \left( \hat{f}_m(\mathbf{x}) - y \right) \right] \\ &= \left( \mathbb{E}_{\mathcal{D}} \left[ \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) \right] - \hat{f}_m(\mathbf{x}) \right) \left( \hat{f}_m(\mathbf{x}) - y \right) \\ &= \left( \hat{f}_m(\mathbf{x}) - \hat{f}_m(\mathbf{x}) \right) \left( \hat{f}_m(\mathbf{x}) - y \right) \\ &= 0 \end{aligned}$$

# Cross Term

- The cross term vanishes

$$\begin{aligned} C &= \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x}|\boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right) \left( \hat{f}_m(\mathbf{x}) - y \right) \right] \\ &= \left( \mathbb{E}_{\mathcal{D}} \left[ \hat{f}(\mathbf{x}|\boldsymbol{\theta}_{\mathcal{D}}) \right] - \hat{f}_m(\mathbf{x}) \right) \left( \hat{f}_m(\mathbf{x}) - y \right) \\ &= \left( \hat{f}_m(\mathbf{x}) - \hat{f}_m(\mathbf{x}) \right) \left( \hat{f}_m(\mathbf{x}) - y \right) \\ &= 0 \end{aligned}$$

- Thus

$$\bar{L}_G = \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x}|\boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right)^2 + \left( \hat{f}_m(\mathbf{x}) - y \right)^2 \right]$$

# Bias and Variance

- We can write the expected generalisation loss as

$$\begin{aligned}\mathbb{E}_{\mathcal{D}}[L_G(\mathcal{D})] &= \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right)^2 \right] \\ &\quad + \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \left( \hat{f}_m(\mathbf{x}) - y \right)^2 = V + B\end{aligned}$$

- Where  $B$  is the bias and  $V$  is the variance defined by

$$V = \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right)^2 \right]$$



# Bias and Variance

- We can write the expected generalisation loss as

$$\begin{aligned}\mathbb{E}_{\mathcal{D}}[L_G(\mathcal{D})] &= \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right)^2 \right] \\ &\quad + \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \left( \hat{f}_m(\mathbf{x}) - y \right)^2 = V + B\end{aligned}$$

- Where  $B$  is the bias and  $V$  is the variance defined by

$$V = \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right)^2 \right]$$

# Bias and Variance

- We can write the expected generalisation loss as

$$\begin{aligned}\mathbb{E}_{\mathcal{D}}[L_G(\mathcal{D})] &= \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right)^2 \right] \\ &\quad + \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \left( \hat{f}_m(\mathbf{x}) - y \right)^2 = V + B\end{aligned}$$

- Where  $B$  is the bias and  $V$  is the variance defined by

$$V = \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right)^2 \right]$$

# Bias-Variance Dilemma

- The bias measure the generalisation performance of the *mean machine* and is large if the machine is too simple to capture the changes in the function we want to learn
- The variance measures the variation in the prediction of the machine as we change the data set we train on

$$V = \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right)^2 \right]$$

- The variance is usually large if we have a complex machine
- Striking the right balance is often the key to getting good results

# Bias-Variance Dilemma

- The bias measure the generalisation performance of the *mean machine* and is large if the machine is too simple to capture the changes in the function we want to learn
- The variance measures the variation in the prediction of the machine as we change the data set we train on

$$V = \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right)^2 \right]$$

- The variance is usually large if we have a complex machine
- Striking the right balance is often the key to getting good results

# Bias-Variance Dilemma

- The bias measure the generalisation performance of the *mean machine* and is large if the machine is too simple to capture the changes in the function we want to learn
- The variance measures the variation in the prediction of the machine as we change the data set we train on

$$V = \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right)^2 \right]$$

- The variance is usually large if we have a complex machine
- Striking the right balance is often the key to getting good results

# Bias-Variance Dilemma

- The bias measure the generalisation performance of the *mean machine* and is large if the machine is too simple to capture the changes in the function we want to learn
- The variance measures the variation in the prediction of the machine as we change the data set we train on

$$V = \sum_{\mathbf{x} \in \mathcal{X}} \mu(\mathbf{x}, y) \mathbb{E}_{\mathcal{D}} \left[ \left( \hat{f}(\mathbf{x} | \boldsymbol{\theta}_{\mathcal{D}}) - \hat{f}_m(\mathbf{x}) \right)^2 \right]$$

- The variance is usually large if we have a complex machine
- Striking the right balance is often the key to getting good results

# Balancing Bias and Variance

- We want to choose a learning machine that is complex enough to capture the underlying function we are trying to learn, but otherwise as simple as possible
- There are a number of tricks to achieve this balance
- Some require us to preprocess the data to reduce the number of inputs
- Some machines cleverly adjust their own complexity
- This course looks at machines that achieve this balance

# Balancing Bias and Variance

- We want to choose a learning machine that is complex enough to capture the underlying function we are trying to learn, but otherwise as simple as possible
- There are a number of tricks to achieve this balance
- Some require us to preprocess the data to reduce the number of inputs
- Some machines cleverly adjust their own complexity
- This course looks at machines that achieve this balance



# Balancing Bias and Variance

- We want to choose a learning machine that is complex enough to capture the underlying function we are trying to learn, but otherwise as simple as possible
- There are a number of tricks to achieve this balance
- Some require us to preprocess the data to reduce the number of inputs
- Some machines cleverly adjust their own complexity
- This course looks at machines that achieve this balance

# Balancing Bias and Variance

- We want to choose a learning machine that is complex enough to capture the underlying function we are trying to learn, but otherwise as simple as possible
- There are a number of tricks to achieve this balance
- Some require us to preprocess the data to reduce the number of inputs
- Some machines cleverly adjust their own complexity
- This course looks at machines that achieve this balance

# Balancing Bias and Variance

- We want to choose a learning machine that is complex enough to capture the underlying function we are trying to learn, but otherwise as simple as possible
- There are a number of tricks to achieve this balance
- Some require us to preprocess the data to reduce the number of inputs
- Some machines cleverly adjust their own complexity
- This course looks at machines that achieve this balance

# Lessons

- This course is about understanding machine learning techniques that work well
- Which one to use will depend on the data set
- One of the most useful intuitions about what works is the bias-variance framework
- The bias is high for simple machines that can't capture the data
- The variance is high for complex machines that are sensitive to the training set
- Good machines are powerful enough to capture complex data sets, but they can control their own capacity (ability to (over-)fit the data)

# Lessons

- This course is about understanding machine learning techniques that work well
- Which one to use will depend on the data set
- One of the most useful intuitions about what works is the bias-variance framework
- The bias is high for simple machines that can't capture the data
- The variance is high for complex machines that are sensitive to the training set
- Good machines are powerful enough to capture complex data sets, but they can control their own capacity (ability to (over-)fit the data)

# Lessons

- This course is about understanding machine learning techniques that work well
- Which one to use will depend on the data set
- One of the most useful intuitions about what works is the bias-variance framework
- The bias is high for simple machines that can't capture the data
- The variance is high for complex machines that are sensitive to the training set
- Good machines are powerful enough to capture complex data sets, but they can control their own capacity (ability to (over-)fit the data)

# Lessons

- This course is about understanding machine learning techniques that work well
- Which one to use will depend on the data set
- One of the most useful intuitions about what works is the bias-variance framework
- The bias is high for simple machines that can't capture the data
- The variance is high for complex machines that are sensitive to the training set
- Good machines are powerful enough to capture complex data sets, but they can control their own capacity (ability to (over-)fit the data)

# Lessons

- This course is about understanding machine learning techniques that work well
- Which one to use will depend on the data set
- One of the most useful intuitions about what works is the bias-variance framework
- The bias is high for simple machines that can't capture the data
- The variance is high for complex machines that are sensitive to the training set
- Good machines are powerful enough to capture complex data sets, but they can control their own capacity (ability to (over-)fit the data)



# Lessons

- This course is about understanding machine learning techniques that work well
- Which one to use will depend on the data set
- One of the most useful intuitions about what works is the bias-variance framework
- The bias is high for simple machines that can't capture the data
- The variance is high for complex machines that are sensitive to the training set
- Good machines are powerful enough to capture complex data sets, but they can control their own capacity (ability to (over-)fit the data)