

parameter passing techniques.

#include <iostream.h>

#include <conio.h>

call by value

call by pointer

call by reference

class demo

{

Public :

void add (int);

void mul (int *);

void sub (int &);

};

void demo :: add (int a)

{

a = a + 10;

cout << "value of a" << a << endl

}

void demo :: sub (int *P)

{

*P = *P - 10;

cout << "value of P" << *P << endl

}

void demo :: mul (int &x)

{

x = x * 10;

cout << "value of x =" << x << endl

}

void main ()

{

demo d;

int P = 20;

int *Z = &P;

d.add(P);

// call by value

d.^{sub}mul(Z);

// call by pointer

d.mul(P);

getch();

}

o/p :: value of a = 30
 value of P = 70
 value of x = 200

* passing object as parameter to the function and returning object from the function.

```
#include <iostream.h>
#include <conio.h>
class emp
{
    int emp-no;
    char emp-name[20];
public:
    emp get();
    void show(emp);
};

emp emp emp::get()
{
    emp e;
    cout << "enter emp-no";
    cin >> emp-no;
    cout << "employee name" << " ";
    cin >> emp-name;
    return e;
}

emp void :: show(emp)
{
    cout << "emp-no" << emp-no << endl;
    cout << "emp-name" << emp-name << endl;
}

void main()
{
    emp x, y; clrscr();
    y = x.get();
    x.show(y);
    getch(); }
```


array of object.

classname object-name [size];

```
#include <iostream.h>
```

```
#include <conio.h>
```

```
class demo
```

```
{
```

```
    int a, b, c;
```

```
    public :
```

```
        void get();
```

```
        void show();
```

```
};
```

```
void demo :: get()
```

```
{
```

```
    cout << "enter value for a & b" << endl;
```

```
    cin >> a >> b;
```

```
void demo :: show()
```

```
{
```

```
    c = a + b;
```

```
    cout << "addition = " << c << endl;
```

```
}
```

```
void main()
```

```
{
```

```
    demo d[3];
```

```
    clrscr();
```

```
    for (int i = 0; i < 3; i++)
```

```
        d[i].getdata();
```

```
for (int i = 0; i < 3; i++)
```

```
    for (int i = 0; i < 3; i++)
```

```
        d[i].show();
```

```
    getch();
```

```
}
```

~~pointer to~~
object to pointer.

Syntax

datatype * pointer-name
class-name * object-name;

```
#include <iostream.h>
```

```
#include <conio.h>
```

```
class demo
```

```
{
```

```
    int a, b, c;
```

```
    public:
```

```
        void get();
```

```
        void show();
```

```
}
```

```
void demo::get()
```

```
{
```

```
    cout << "enter value for a & b";
```

```
    cin >> a >> b;
```

```
}
```

```
void demo::show()
```

```
{
```

```
    c = a + b;
```

```
    cout << c;
```

```
}
```

```
void main()
```

```
{
```

```
    demo *d;
```

```
    demo p;
```

```
    clrscr;
```

```
    d = &p;
```

```
    d->get();
```

```
    d->show();
```

```
}
```

```
getch.
```

O/P

enter value for a & b = 5.

10

15