Finding Many Stable Molecular Arrangements

Conformational Searching with Genetic Algorithms

Evan Curtin
December 2, 2016

University of Illinois at Urbana-Champaign

Outline

- 1. Background Information
- 2. The Genetic Algorithm
- 3. Finding Low Energy Conformers of Dipeptides
- 4. Concluding Remarks


Primary Resource

First-Principles Molecular Structure Search with a Genetic Algorithm Supady, A.P¹; Blum, V.¹; Baldauf, C. J.^{1,2} Chem. Inf. Model. 2015, 55 (11), 23382348.

- 1. Fritz-Haber-Institut der Max-Planck-Gesellschaft, Berlin
- 2. Department of Mechanical Engineering & Materials Science, Duke University


Background Information

• Protein folding is important




Reddy, G.; Liu, Z.; Thirumalai, D. Proc. Natl. Acad. Sci. 2012, 109 (44), 1783217838.

- Protein folding is important
- Peptides are building blocks of protein




Reddy, G.; Liu, Z.; Thirumalai, D. Proc. Natl. Acad. Sci. 2012, 109 (44), 1783217838.

- Protein folding is important
- Peptides are building blocks of protein
- ullet Peptide conformations o protein folding



Reddy, G.; Liu, Z.; Thirumalai, D. Proc. Natl. Acad. Sci. 2012, 109 (44), 1783217838.

- Protein folding is important
- Peptides are building blocks of protein
- ullet Peptide conformations o protein folding
- How do we understand peptide conformations?



Reddy, G.; Liu, Z.; Thirumalai, D. Proc. Natl. Acad. Sci. 2012, 109 (44), 1783217838.

Computational methods require knowledge of molecular structure

We need to find the lowest energy structure

Computational methods require knowledge of molecular structure

We need to find the lowest energy structure

The potential energy surface (PES) is high dimensional and has many minima We can't tell for sure if we've found the global minimum



Computational methods require knowledge of molecular structure

We need to find the lowest energy structure

The potential energy surface (PES) is high dimensional and has many minima We can't tell for sure if we've found the global minimum

We may need information about one or more low-energy conformations

• Ok, let's find them all!



Computational methods require knowledge of molecular structure

We need to find the lowest energy structure

The potential energy surface (PES) is high dimensional and has many minima We can't tell for sure if we've found the global minimum

We may need information about one or more low-energy conformations

- Ok, let's find them all!
- Under a cutoff



Possible Solutions

• Many techniques are well established

Method	Implented in
grid-based	CEASAR, Open Babel, Confab,
	MacroModel, MOE
rule-based	ALFA, CONFECT, CORINA,
	ROTATE, COSMOS, OMEGA
population-based	Balloon, Cyndi
basin-hopping	ASE, GMIN, TINKER SCAN

Possible Solutions

•	Many techniques	are
	well established	

• None are perfect

Method	Implented in
grid-based	CEASAR, Open Babel, Confab,
	MacroModel, MOE
rule-based	ALFA, CONFECT, CORINA,
	ROTATE, COSMOS, OMEGA
population-based	Balloon, Cyndi
basin-hopping	ASE, GMIN, TINKER SCAN

What Algorithmic Properties do we want for conformer search?

1. Accurate energies & Structures

- 1. Accurate energies & Structures
- 2. Minimize # of geometry optimizations

- 1. Accurate energies & Structures
- 2. Minimize # of geometry optimizations
- 3. Find many low energy conformations


- 1. Accurate energies & Structures
- 2. Minimize # of geometry optimizations
- 3. Find many low energy conformations
- 4. Minimize human bias

- 1. Accurate energies & Structures
- 2. Minimize # of geometry optimizations
- 3. Find many low energy conformations
- 4. Minimize human bias
- 5. Parallel

The Genetic Algorithm

Outline

- Inspired by biological evolution
- Evolve a population over generations
- Survival of the fittest
- Requirements:
 - Represent individuals as vector
 - Fitness function
- $V = (x_1 y_1 z_1 x_2 y_2 z_2 \cdots x_N y_N z_N)$
- $F = \frac{E_{\text{max}} E}{F_{\text{max}} F_{\text{min}}}$




2. (7428 Citations) Morris, G. et al. J. Comput. Chem. 1998, 19 (14), 16391662. Du V. Song C. Lin 7 | Comput Cham 2016 27 (12) 121/1222


^{1.} Carwright, H. Reviews in Computational Chemistry 2007 (25), pp 349-389.

The Many Representations of a Molecule

2D Image



3D Image



Name

(3Z)-3,4-Dimethyl-3-hexene

SMILES

CCC(C)=C(C)CC

InChl

1S/C8H16/c1-5-7(3)8(4)6-2/h5-6H2,1-4H3/b8-7-

Cartesian Coords


	X	У	Z
C	0.90	-0.25	0.02
C	2.35	0.15	-0.17
C	2.91	1.30	-0.67

Internal Coords

		r		θ
C				
C	1	1.51		
C	2	1.38	1	131

^{1.} Supady, A.; Blum, V.; Baldauf, C. J. Chem. Inf. Model. 2015, 55 (11), 23382348.

The Many Representations of a Molecule



(3Z)-3,4-Dimethyl-3-hexene **SMILES** CCC(C)=C(C)CC1S/C8H16/c1-5-7(3)8(4)6-2/h5-6H2,1-4H3/b8-7-

Cartesian Coords

	^	У	_
C	0.90	-0.25	0.02
C	2.35	0.15	-0.17
C	2.91	1.30	-0.67


Internal Coords

		r		θ
C				
C	1	1.51		
C	2	1.38	1	131

Equivalent in theory

^{1.} Supady, A.; Blum, V.; Baldauf, C. J. Chem. Inf. Model. 2015, 55 (11), 23382348.

The Many Representations of a Molecule



Name (3Z)-3,4-Dimethyl-3-hexene SMILES CCC(C)=C(C)CC InChl 1S/C8H16/c1-5-7(3)8(4)6-2/h5-

6H2,1-4H3/b8-7-

Cartesian Coords

	X	У	Z
C	0.90	-0.25	0.02
C	2.35	0.15	-0.17
C	2.91	1.30	-0.67

Internal Coords

		r		θ
C				
C	1	1.51		
C	2	1.38	1	131

Equivalent in theory

^{1.} Supady, A.; Blum, V.; Baldauf, C. J. Chem. Inf. Model. 2015, 55 (11), 23382348. 2. http://www.chemspider.com/Chemical-Structure.2298795.html

Roulette Wheel Method

1. Reinforce good characteristics


- 1. Reinforce good characteristics
- 2. Still give losers a chance

- 1. Reinforce good characteristics
- 2. Still give losers a chance
- 3. 'Breed' pairs of winners


- 1. Reinforce good characteristics
- 2. Still give losers a chance
- 3. 'Breed' pairs of winners




- 1. Reinforce good characteristics
- 2. Still give losers a chance
- 3. 'Breed' pairs of winners



- 1. Reinforce good characteristics
- 2. Still give losers a chance
- 3. 'Breed' pairs of winners



The Next Generation




1. Generate N random, sensible geometries



sensible

1. Generate N random, sensible geometries



sensible



utter nonsense

- 1. Generate N random, sensible geometries
- 2. Optimize



sensible



utter nonsense

- 1. Generate N random, sensible geometries
- 2. Optimize
- 3. Select Parents



sensible



utter nonsense

- 1. Generate N random, sensible geometries
- 2. Optimize
- 3. Select Parents
- 4. Crossover & Mutate



sensible



utter nonsense

- 1. Generate N random, sensible geometries
- 2. Optimize
- 3. Select Parents
- 4. Crossover & Mutate
- 5. Add Children to population



sensible



utter nonsense

- 1. Generate N random, sensible geometries
- 2. Optimize
- 3. Select Parents
- 4. Crossover & Mutate
- 5. Add Children to population
- 6. Remove the unfit



sensible



utter nonsense

- 1. Generate N random, sensible geometries
- 2. Optimize
- 3. Select Parents
- 4. Crossover & Mutate
- 5. Add Children to population
- 6. Remove the unfit
- 7. If converged:
 - Done!



sensible



utter nonsense

- 1. Generate N random, sensible geometries
- 2. Optimize
- 3. Select Parents
- 4. Crossover & Mutate
- 5. Add Children to population
- 6. Remove the unfit
- 7. If converged:
 - Done!

Otherwise:

• Go to 2



sensible



utter nonsense

Finding Low Energy Conformers

of Dipeptides

"Dipeptide" Structures

"We use the term dipeptide for amino acids with an acetylated N terminus and an amino-methylated C terminus"

Combinatorics


•	GA beats other
	methods if space
	is large

Space gets large fast

		# Notatable +	
Molecule	N	# Cis/Trans Bonds	# Conformers
Gly	19	2 + 2	15
Ala	22	2 + 2	28
Phe	32	4 + 2	64
Val	28	3 + 2	60
Trp	36	4 + 2	141
Leu	31	4 + 2	183
lle	31	4 + 2	176

Rotatable 4


- Smaller systems are reliably sampled
- As # of conformers increases, miss more and more
- Is there a pattern to what is missed?




Proportion of conformers found with increasing runs of the GA

¹⁾ Supady, A.; Blum, V.; Baldauf, C. J. Chem. Inf. Model. 2015, 55 (11), 23382348. 2) Ropo, M.; Schneider, M.; Baldauf, C.; Blum, V. Sci. Data 2016, 3, 160009.

 Most misses are very high energy




- Most misses are very high energy
- Algorithm favors low energy areas of the space




- New Found by GA
- In Reference & GA

- Most misses are very high energy
- Algorithm favors low energy areas of the space
- Features low in energy are favored and recombined




- Missed by the GA
- New Found by GA
 - In Reference & GA

Energy Cutoff




Mycophenolic Acid



Energy Cutoff

Mycophenolic Acid


 GA is more sensitive to energy cutoff



Energy Cutoff

Mycophenolic Acid

- GA is more sensitive to energy cutoff
- For finding low energy ensemble, GA outperforms purely stochastic/deterministic method



Review

• Conformational searching is expensive

- Conformational searching is expensive
- The Genetic Algorithm is a guided global search

- Conformational searching is expensive
- The Genetic Algorithm is a guided global search
- It shines when asked to find many low energy solutions

- Conformational searching is expensive
- The Genetic Algorithm is a guided global search
- It shines when asked to find many low energy solutions
- GA can be used with any electronic structure package

- Conformational searching is expensive
- The Genetic Algorithm is a guided global search
- It shines when asked to find many low energy solutions
- GA can be used with any electronic structure package
- This one is available under the GNU Lesser General Public License: https://github.com/adrianasupady/fafoom



Backup slide

 Geometry optimization step makes the algorithm more Lamarckian (Jean Baptiste Larmarck, [1744-1829])

Genetic Algorithm Parameters

Geometry Optimization: DFT PBE + VdW, tier1 basis in FHI-aims¹. Convergence at 0.005 eV /Å

	parameter	value
molecule	SMILES	CC(=O)N[C@H](C(=O)NC)[C@H](CC)C
	distance_cutoff_1	1.2 Å
	distance_cutoff_2	2.0 Å
	rmsd_cutoff_uniq	0.2 Å
	chiral	true
run settings	max_iter	10
	iter_limit_conv	10
	energy_diff_conv	0.001 eV
GA settings	popsize	5
	energy_var	0.001 eV
	selection	roulette wheel
	fitness_sum_limit	1.2
	prob_for_crossing	0.95
	cross_trial	20
	prob_for_mut_cistrans	0.5
	prob_for_mut_rot	0.5
	max_mutations_cistrans	1
	max_mutations_torsions	2
	mut trial	100

GA Parameters for Isoleucine Dipeptide²

⁽¹⁾ Blum, V. et. 'ál., M. Comput. Phys. Commun. 2009, 180 (11), 21752196. (2) Supady, A.; Blum, V.; Baldauf, C. J. Chem. Inf. Model. 2015, 55 (11), 23382348.