

Finding Many Stable Molecular Arrangements

Conformational Searching with Genetic Algorithms

Evan Curtin

October 10, 2016

University of Illinois at Urbana-Champaign

Outline

1. Background Information
2. The Genetic Algorithm
3. Finding Low Energy Conformers of Dipeptides
4. Concluding Remarks

Background Information

The Problem

Computational methods require knowledge of molecular structure

The Problem

Computational methods require knowledge of molecular structure

⇒ We need to find the lowest energy structure

The Problem

Computational methods require knowledge of molecular structure

⇒ We need to find the lowest energy structure

The potential energy surface (PES) is high dimensional and has many minima

The Problem

Computational methods require knowledge of molecular structure

⇒ We need to find the lowest energy structure

The potential energy surface (PES) is high dimensional and has many minima

⇒ We can't tell for sure if we've found the **global** minimum

The Problem

Computational methods require knowledge of molecular structure

⇒ We need to find the lowest energy structure

The potential energy surface (PES) is high dimensional and has many minima

⇒ We can't tell for sure if we've found the **global** minimum

We may need information about one or more low-energy conformations

The Problem

Computational methods require knowledge of molecular structure

⇒ We need to find the lowest energy structure

The potential energy surface (PES) is high dimensional and has many minima

⇒ We can't tell for sure if we've found the **global** minimum

We may need information about one or more low-energy conformations

⇒ Ok, let's find them all!

Many techniques are well established

method	description	implemented, e.g., in
grid-based	based on grids of selected Cartesian or internal coordinates (e.g., grids of different torsional angle values of a molecule)	CAESAR, ⁹ Open Babel , ¹⁰ Confab , ¹¹ MacroModel, ¹² MOE ¹³
rule/knowledge-based	use known (e.g., from experiments) structural preferences of compounds	ALFA , ¹⁴ CONFECT , ¹⁵ CORINA and ROTATE, ^{16,17} COSMOS , ^{18,19} OMEGA ²⁰
population-based metaheuristic	improve candidate solutions in a guided search	Balloon , ²¹ Cyndi ²²
distance geometry	based on a matrix with permitted distances between pairs of atoms	RDKit ²³
basin-hopping ²⁴ / minima hopping ²⁵	based on moves across the PES combined with local relaxation	ASE , ²⁶ GMIN , ²⁷ TINKER SCAN ²⁸

^aNames of freely available programs are highlighted in boldface.

Possible Solutions

Many techniques are well established

None are perfect

method	description	implemented, e.g., in
grid-based	based on grids of selected Cartesian or internal coordinates (e.g., grids of different torsional angle values of a molecule)	CAESAR, ⁹ Open Babel , ¹⁰ Confab , ¹¹ MacroModel, ¹² MOE ¹³
rule/knowledge-based	use known (e.g., from experiments) structural preferences of compounds	ALFA , ¹⁴ CONFECT , ¹⁵ CORINA and ROTATE, ^{16,17} COSMOS , ^{18,19} OMEGA ²⁰
population-based metaheuristic	improve candidate solutions in a guided search	Balloon , ²¹ Cyndi ²²
distance geometry	based on a matrix with permitted distances between pairs of atoms	RDKit ²³
basin-hopping ²⁴ / minima hopping ²⁵	based on moves across the PES combined with local relaxation	ASE , ²⁶ GMIN , ²⁷ TINKER SCAN ²⁸

^aNames of freely available programs are highlighted in boldface.

- Accurate energies & Structures, *ab initio* or DFT

- Accurate energies & Structures, *ab initio* or DFT
- Minimize number of geometry optimizations

- Accurate energies & Structures, *ab initio* or DFT
- Minimize number of geometry optimizations
- Find the entire low energy population of conformations


- Accurate energies & Structures, *ab initio* or DFT
- Minimize number of geometry optimizations
- Find the entire low energy population of conformations
- Minimal human input

- Accurate energies & Structures, *ab initio* or DFT
- Minimize number of geometry optimizations
- Find the entire low energy population of conformations
- Minimal human input
- Parallel-Scalable

The Genetic Algorithm

Outline

- Inspired by biological evolution
- Evolve a population over generations
- Survival of the fittest
- Requirements:
 - Represent individuals as vector
 - Fitness function
- $V = (x_1 \ y_1 \ z_1 \ x_2 \ y_2 \ z_2 \ \dots \ x_N \ y_N \ z_N)$
- $F = \frac{E_{max} - E}{E_{max} - E_{min}}$




From Structure to Vector

- Several Ways to Define Structure

Cartesian

Internal Coordinates (bond length, angle ...)

SMILES, InChI



Representations of
(3Z)-3,4-Dimethyl-3-hexene¹

1. Supady, A.; Blum, V.; Baldauf, C. J. Chem. Inf. Model. 2015, 55 (11), 23382348.
2. <http://www.chemspider.com/Chemical-Structure.2298795.html>

From Structure to Vector

- Several Ways to Define Structure


Cartesian

Internal Coordinates (bond length, angle ...)

SMILES, InChI

- InChI²=

1S/C8H16/c1-5-7(3)8(4)6-
2/h5-6H2,1-4H3/b8-7-



Representations of
(3Z)-3,4-Dimethyl-3-hexene¹

From Structure to Vector

- Several Ways to Define Structure

Cartesian


Internal Coordinates (bond length, angle ...)

SMILES, InChI

- InChI²=

1S/C8H16/c1-5-7(3)8(4)6-2/h5-6H2,1-4H3/b8-7-

- Equivalent in theory



Representations of
(3Z)-3,4-Dimethyl-3-hexene¹

From Structure to Vector

- Several Ways to Define Structure

Cartesian


Internal Coordinates (bond length, angle ...)

SMILES, InChI

- InChI²=

1S/C8H16/c1-5-7(3)8(4)6-2/h5-6H2,1-4H3/b8-7-

- Equivalent **in theory**



Representations of
(3Z)-3,4-Dimethyl-3-hexene¹

Selecting Parents

- Several methods are common

Selecting Parents

- Several methods are common
- Reinforce good characteristics

Selecting Parents


- Several methods are common
- Reinforce good characteristics
- Still give losers a chance

Selecting Parents

- Several methods are common
- Reinforce good characteristics
- Still give losers a chance
- 'Breed' pairs of winners


Selecting Parents

- Several methods are common
- Reinforce good characteristics
- Still give losers a chance
- 'Breed' pairs of winners
- 'Roulette Wheel' Method




Selecting Parents


- Several methods are common
- Reinforce good characteristics
- Still give losers a chance
- 'Breed' pairs of winners
- 'Roulette Wheel' Method



The Next Generation



The Next Generation



Crossover distinguishes this from Monte Carlo

The Whole Algorithm

1. Generate N random, sensible geometries

The Whole Algorithm

1. Generate N random, sensible geometries
2. Add each to blacklist

The Whole Algorithm

1. Generate N random, sensible geometries
2. Add each to blacklist
3. Optimize each geometry

The Whole Algorithm

1. Generate N random, sensible geometries
2. Add each to blacklist
3. Optimize each geometry
4. Select Parents

The Whole Algorithm

1. Generate N random, sensible geometries
2. Add each to blacklist
3. Optimize each geometry
4. Select Parents
5. Crossover & Mutate into sensible geometry

The Whole Algorithm

1. Generate N random, sensible geometries
2. Add each to blacklist
3. Optimize each geometry
4. Select Parents
5. Crossover & Mutate into sensible geometry
6. Add Children to population

The Whole Algorithm

1. Generate N random, sensible geometries
2. Add each to blacklist
3. Optimize each geometry
4. Select Parents
5. Crossover & Mutate into sensible geometry
6. Add Children to population
7. Remove High energy individuals

The Whole Algorithm

1. Generate N random, sensible geometries
2. Add each to blacklist
3. Optimize each geometry
4. Select Parents
5. Crossover & Mutate into sensible geometry
6. Add Children to population
7. Remove High energy individuals
8. If converged:

The Whole Algorithm


1. Generate N random, sensible geometries
2. Add each to blacklist
3. Optimize each geometry
4. Select Parents
5. Crossover & Mutate into sensible geometry
6. Add Children to population
7. Remove High energy individuals
8. If converged:
 - Done!

The Whole Algorithm


1. Generate N random, sensible geometries
2. Add each to blacklist
3. Optimize each geometry
4. Select Parents
5. Crossover & Mutate into sensible geometry
6. Add Children to population
7. Remove High energy individuals
8. If converged:
 - Done!Otherwise:

The Whole Algorithm

1. Generate N random, sensible geometries
2. Add each to blacklist
3. Optimize each geometry
4. Select Parents
5. Crossover & Mutate into sensible geometry
6. Add Children to population
7. Remove High energy individuals
8. If converged:
 - Done!Otherwise:
 - Go to 2




sensible



utter nonsense

Finding Low Energy Conformers of Dipeptides

Dipeptide Structures




- GA beats other methods if space is large
- Space gets large **fast**

amino acid dipeptide	abbr	no. of atoms	no. of rotatable bonds + no. of cis/trans bonds	no. of conformers (below 0.4 eV \approx 38.6 kJ/mol)
glycine	Gly	19	2 + 2	15 (15)
alanine	Ala	22	2 + 2	28 (17)
phenylalanine	Phe	32	4 + 2	64 (37)
valine	Val	28	3 + 2	60 (40)
tryptophan	Trp	36	4 + 2	141 (77)
leucine	Leu	31	4 + 2	183 (103)
isoleucine	Ile	31	4 + 2	176 (107)


Coverage

- Smaller systems are reliably sampled
- As # of conformers increases, miss more and more
- Is there a pattern to what is missed?



Coverage


- Most misses are very high energy



— Missed by the GA
— New Found by GA
— In Reference & GA

Coverage


- Most misses are very high energy
- Algorithm favors low energy areas of the space




— Missed by the GA
— New Found by GA
— In Reference & GA

Coverage


- Most misses are very high energy
- Algorithm favors low energy areas of the space
- Features low in energy are favored and recombined




Energy Cutoff



Mycophenolic Acid




Energy Cutoff




Mycophenolic Acid

- GA is more sensitive to energy cutoff




Energy Cutoff



Mycophenolic Acid

- GA is more sensitive to energy cutoff
- For finding low energy ensemble, GA outperforms purely stochastic/deterministic method



Concluding Remarks

Concluding Remarks

- Finding all the low energy conformers for a molecule is hard

Concluding Remarks

- Finding all the low energy conformers for a molecule is hard
- In order to get accurate energies/structures, computationally expensive methods should be employed

Concluding Remarks

- Finding all the low energy conformers for a molecule is hard
- In order to get accurate energies/structures, computationally expensive methods should be employed
- These take time, so we want to minimize how many of these we do

Concluding Remarks

- Finding all the low energy conformers for a molecule is hard
- In order to get accurate energies/structures, computationally expensive methods should be employed
- These take time, so we want to minimize how many of these we do
- The Genetic Algorithm provides a framework for a refined global search

Concluding Remarks

- Finding all the low energy conformers for a molecule is hard
- In order to get accurate energies/structures, computationally expensive methods should be employed
- These take time, so we want to minimize how many of these we do
- The Genetic Algorithm provides a framework for a refined global search
- It shines when asked to find a host of low energy solutions

Concluding Remarks

- Finding all the low energy conformers for a molecule is hard
- In order to get accurate energies/structures, computationally expensive methods should be employed
- These take time, so we want to minimize how many of these we do
- The Genetic Algorithm provides a framework for a refined global search
- It shines when asked to find a host of low energy solutions
- GA wrapper can be interfaced with a variety of electronic structure packages(NWChem, ORCA) and is available under the GNU Lesser General Public License at <https://github.com/adrianasupady/fafoom>

Questions?

- Geometry optimization step makes the algorithm more Lamarckian (Jean Baptiste Lamarck, [1744-1829])

Genetic Algorithm Parameters

Geometry Optimization: DFT PBE + VdW, *tier1* basis in FHI-aims¹.
Convergence at 0.005 eV / Å

	parameter	value
molecule	SMILES	<chem>CC(=O)N[C@H](C(=O)NC)[C@H](CC)C</chem>
	distance_cutoff_1	1.2 Å
	distance_cutoff_2	2.0 Å
	rmsd_cutoff_uniq	0.2 Å
	chiral	true
run settings	max_iter	10
	iter_limit_conv	10
	energy_diff_conv	0.001 eV
GA settings	popsize	5
	energy_var	0.001 eV
	selection	roulette wheel
	fitness_sum_limit	1.2
	prob_for_crossing	0.95
	cross_trial	20
	prob_for_mut_cistrans	0.5
	prob_for_mut_rot	0.5
	max_mutations_cistrans	1
	max_mutations_torsions	2
	mut_trial	100

GA Parameters for Isoleucine Dipeptide²

(1) Blum, V. et. al., M. Comput. Phys. Commun. 2009, 180 (11), 21752196.

(2) Supady, A.; Blum, V.; Baldauf, C. J. Chem. Inf. Model. 2015, 55 (11), 23382348.