
OPTIMIZING GLM-ASR INFERENCE WITH CUSTOM TRITON KERNELS: FLASH ATTENTION, KERNEL FUSION, AND FP16 PIPELINING

Anonymous authors

Paper under double-blind review

1 INTRODUCTION

1.1 MOTIVATION

Current computational demands of transformer-based ASR models and limited inference budgets have driven the need for efficient GPU kernel implementations that can process audio faster than playback speed. This has instigated the investigation and development of custom kernel optimizations for real-time speech recognition, particularly for latency-constrained applications such as live captioning, voice assistants, and conference transcription. GLM-ASR is a multimodal encoder-decoder model that converts raw audio waveforms into text through a pipeline of compute-intensive transformer layers. Its inference workload is dominated by matrix multiplications, attention computations, and element-wise operations—all of which are amenable to GPU acceleration through custom kernels.

GPU kernel optimization matters because default PyTorch operators do not exploit hardware-specific features such as extended shared memory, tensor-core-friendly data layouts, or operation fusion across kernel boundaries. We design and optimize a complete working implementation using Triton (Tillet et al., 2019) to create custom GPU kernels. By writing custom kernels, we can fuse multiple operations into a single kernel launch, tune tile sizes to the GPU’s shared memory capacity, and select data types that maximize throughput—eliminating the intermediate video RAM (VRAM) round-trips that dominate latency in the default implementation.

The principal constraint is the kernel design space, as tile dimensions, warp counts, pipeline stages, and data types interact in non-obvious ways, and a configuration that works on one GPU architecture may fail or regress on another. We validated our parameter choices through a 22-configuration ablation study on the H200 (Section 5).

1.2 SYSTEM OVERVIEW

We determine that our optimal approach is to implement the compute-intensive operations as fused Triton kernels while delegating matrix multiplications to cuBLAS, following the **Triton track** with all required kernels in `layers.py`, `attention.py`, and `rope.py`. Table 1 lists the ten kernels implemented, and Figure 1 illustrates where they operate in the inference pipeline. We test each component individually and integrate them in a bottom-up fashion, verifying correctness at each stage before proceeding to performance tuning.

In addition to the required kernels, we implement four additional optimizations: (1) a KV-cached generation loop (`generate_v8b`) that reduces decoding from $O(n^2)$ to $O(n)$, (2) an end-to-end fp16 precision pipeline that halves memory traffic, (3) a `GPUProfile` system that adapts tile sizes to the target GPU at import time, and (4) a PyTorch Scaled Dot-Product Attention (SDPA) fallback for single-token decode steps where kernel launch overhead exceeds computation cost. Each subcomponent is modular in order to produce a robust, adaptable and portable system.

Headline results. Upon completion of this project, our final implementation achieves **204.8 ms** end-to-end latency on an H200 MIG 3g.71gb partition (baseline: 464.1 ms), a **2.27 $\times$ speedup** with **100% transcription accuracy**. On an RTX 5090, the same code achieves **100.4 ms** (2.61 $\times$).

054
055
056
057
058
059
060
061
062
063
064
065
066
067
068
069
070
071
072
073
074
075
076
077
078
079
080
081
082
083
084
085
086
087
088
089
090
091
092
093
094
095
096
097
098
099
100
101
102
103
104
105
106
107

Table 1: Implemented Triton kernels and their roles.

Kernel	File	Phase	Purpose
gelu.kernel	layers.py	Encoder MLP	GELU activation
silu.kernel	layers.py	Decoder MLP	SiLU activation
rmsnorm.kernel	layers.py	Decoder norms	RMSNorm + fp16 output
layernorm.kernel	layers.py	Encoder norms	LayerNorm + fp16 output
linear.kernel.tf32	layers.py	Matmul	General Matrix Multiply (GEMM)
fused.swiglu.kernel	layers.py	Decoder MLP	Fused SwiGLU
fused.linear.gelu.kernel	layers.py	Encoder MLP	Fused Linear+GELU
flash.attention.kernel	attention.py	Attention	Flash Attention
fused.rope.pair.kernel	rope.py	Attention	Fused Q+K RoPE
compute.freqs.kernel	rope.py	Attention	Frequency precompute




Figure 1: GLM-ASR pipeline. Shaded stages use our Triton kernels (or cuBLAS for matmul).

2 IMPLEMENTATION

2.1 IMPLEMENTATION SUMMARY

The GLM-ASR inference pipeline (Figure 1) has five computational phases, each with distinct performance characteristics. We employ a performance-budgeting technique to attribute latency to each stage and identify where optimization effort would yield the largest gains.

Phase 1: Mel Spectrogram + Conv1D Subsampling. Converts raw 16 kHz audio to 128-bin Mel features and downsamples $4\times$ via strided 1D convolutions. These are PyTorch built-in operations (read-only `conv.py`), which we do not modify. The phase is bandwidth-bound due to large feature maps with simple arithmetic.

Phase 2: Audio Encoder (32 layers). Each layer applies LayerNorm, self-attention (20 heads, $d_k=64$), and a two-layer multi-layer perceptron (MLP) with GELU activation. Rotary Position Embedding (RoPE) (Su et al., 2024) is applied to 50% of head dimensions (the first 32 of 64 are rotated, as specified by the model architecture). On the H200, our flash attention kernel achieves an AI of ~ 112 for encoder attention (Section 4), well above the GPU’s ridge point—the threshold where compute and memory bandwidth are equally limiting. This makes encoder attention compute-bound (limited by arithmetic throughput) on the H200, but a naive 3-kernel implementation (AI ~ 16) would be bandwidth-bound on consumer GPUs with higher ridge points. The linear projections (1280×5120) are compute-bound on all architectures.

Phase 3: Multi-modal Projector. **CHANGED** Pools 4 encoder frames and projects $5120 \rightarrow 4096 \rightarrow 2048$ through two linear layers with GELU. In the warmup-corrected H200 component profile, this phase is very small and latency-dominated (0.14 ms, $< 0.1\%$ of the isolated component total).

Phase 4: Text Decoder Prefill (28 layers). Processes the full concatenated sequence (audio embeddings + prompt tokens) through 28 decoder layers with RMSNorm, Grouped Query Attention (GQA, 16 query / 4 KV heads, $d_k=128$) (Ainslie et al., 2023), and SwiGLU MLP (Shazeer, 2020). Bandwidth-bound for attention, compute-bound for the large linear projections (2048×5632).

Phase 5: Autoregressive Decoding. **CHANGED** Generates tokens one at a time. With the baseline’s $O(n^2)$ `generate()` function, this phase dominates wall-clock time, as each step reprocesses the full growing sequence from scratch. Our KV-cached `generate_v8b` stores key/value projections for all previous tokens, processing only the new token each step. In the warmup-corrected component profile, 50 decode steps still dominate the isolated operator total at 92.1%, while the full end-to-end benchmark confirms that KV caching is essential to reaching 204.8 ms overall.

2.2 DESIGN CHOICES

Block/tile sizes. Tile dimensions are the primary tuning parameter, constrained by shared memory capacity. Our flash attention kernel loads Q, K, and V tiles into shared memory; the required capacity is:

$$\text{smem} = (\text{BLOCK_M} + 2 \cdot \text{BLOCK_N}) \cdot d_k \cdot 4 + \sim 20 \text{ KB overhead} \quad (1)$$

On the H200 (~ 228 KB opt-in shared memory), this allows 128×128 tiles for the encoder ($d_k=64$, needing ~ 116 KB) and 128×64 for the decoder ($d_k=128$, needing ~ 151 KB). On the RTX 5090 (~ 99 KB), we are constrained to 64×64 and 32×32 respectively.

For matmul, the fused SwiGLU kernel loads three tile buffers (input, gate weight, up weight): $\text{TILE_K} \cdot (\text{TILE_M} + 2 \cdot \text{TILE_N}) \cdot 4 + \text{overhead}$. H200 uses $128 \times 128 \times 64$; RTX 5090 uses $64 \times 64 \times 32$.

Element-wise kernels (GELU, SiLU, norms) use `BLOCK_SIZE=1024`, which saturates memory bandwidth with minimal register pressure. **CHANGED** In order to best satisfy the correctness requirements while minimizing latency, we selected configurations that fit the shared-memory budget and performed well in end-to-end testing, while noting that some micro-benchmark optima did not transfer cleanly to the full pipeline.

num_warps and num_stages. We use `num_warps=8` for large tiles (≥ 4096 elements) and 4 otherwise. More warps hide memory latency but increase register pressure. Ablation testing confirms `num_warps=8` is optimal: 4 warps costs +12.0 ms, 16 warps costs +4.3 ms (Table 5). For `num_stages`: the H200’s ~ 228 KB shared memory accommodates double-buffering (`num_stages=2`), overlapping tile loads with computation for higher throughput on memory-bound kernels. Consumer GPUs (RTX 5090, ~ 99 KB) must use single-buffering (`num_stages=1`), since double-buffering the same tiles would require ~ 136 KB—exceeding the available shared memory.

Data layout and GQA. All tensors are stored in `(batch×heads, seq, dim)` layout for coalesced access. For GQA in the text decoder (16 query heads, 4 KV heads), we expand KV heads by a factor of 4 before the attention kernel. When tested, PyTorch SDPA’s native `enable_gqa=True` regressed by +13 ms. Manual expansion gives explicit control over data layout.

Precision pipeline. Our largest single optimization is the end-to-end fp16 pipeline. The original codebase called `.float()` after every Linear layer (~ 120 call sites), doubling data size. This is redundant: Triton kernels already compute in fp32 internally via `tl.load(...).to(tl.float32)` and cast back on output. Removing these conversions and keeping all VRAM-resident data in fp16 halved memory traffic, saving **11.5 ms** (Section 5).

3 PERFORMANCE PROFILING

3.1 SETUP

All primary measurements use the Edinburgh teaching cluster node `saxa.inf.ed.ac.uk` with an NVIDIA H200 MIG 3g.71gb partition (Hopper architecture, 60 Streaming Multiprocessors (SMs), 70 GB HBM3e, ~ 228 KB opt-in shared memory). The software stack is CUDA 13.0, PyTorch 2.10.0, Triton 3.6.0, Python 3.11. Jobs are submitted via SLURM: `srun -p Teaching`

`-w saxa --gres gpu:3g.71gb:1 --mem=32G`. The test input is a 3.5 s WAV file (“Concord returned to its place amidst the tents”).

The baseline implementation is benchmarked under identical conditions, and the Triton cache is cleared before the first run to ensure compilation occurs during warmup, not during timing. Each student benchmark run uses 2 warmup iterations followed by 5 timed iterations. We report the mean and standard deviation across 5 independent benchmark invocations (25 timed iterations total).

3.2 END-TO-END EVALUATION

Table 2 summarizes the end-to-end results on the teaching cluster. Run 4 shows slightly higher latency (209.4 ms), likely due to MIG partition contention from concurrent cluster users. All other runs cluster tightly around 203–204 ms.

Table 2: End-to-end student benchmark results (H200 MIG 3g.71gb, 5 runs).

Run	Time (ms)	σ (ms)	ms/tok	Tokens	Accuracy
1	203.4	1.6	15.65	13	100%
2	204.0	1.6	15.69	13	100%
3	203.4	2.1	15.64	13	100%
4	209.4	1.7	16.11	13	100%
5	203.9	1.4	15.68	13	100%
Mean	204.8	1.7	15.75	13	100%

LATEST CHANGE Source: `benchmarks/benchmarks.md`; script: `hw1-asr/benchmark_student.py`; raw log: `logs/h200_e2e.2225992/benchmark_raw_output.txt`.

3.3 COMPONENT/OPERATOR-LEVEL BREAKDOWN

CHANGED Table 2 measures end-to-end latency with KV-cached $O(n)$ generation (13 tokens). Table 3 profiles each component in isolation using `benchmark_detailed.py`: individual forward passes through each stage with single-token decode steps (no KV history). The detailed benchmark now uses 1 full warmup benchmark pass discarded and averages 3 measured benchmark passes, with 5 timed runs per component inside each pass.

Table 3: **CHANGED** Component-level profiling (H200 MIG, isolated forward passes, 1 warmup benchmark discarded, average of 3 measured benchmark passes).

Component	Time (ms)	% Total	Bound
Audio Encoder (32 layers)	36.53	5.8%	Mixed
Multi-modal Projector	0.14	0.0%	Latency
Decoder Prefill (28 layers)	12.97	2.1%	Mixed
Decoder Decode (50 steps)	580.45	92.1%	Bandwidth
Total	630.09	100%	

LATEST CHANGE Source: `benchmarks/benchmarks_detailed.md`; script: `hw1-asr/benchmark_detailed.py` via `hw1-asr/benchmark_detailed_job.sh`; raw logs: `logs/h200_detailed.2236079/`.

CHANGED Decoder decode now accounts for 92.1% of the warmup-corrected isolated component total, at ~ 0.41 ms per layer per step, confirming that autoregressive generation remains the primary bottleneck even after optimization.

4 BOTTLENECK ANALYSIS

4.1 COMPUTE-BOUND VS MEMORY-BOUND CLASSIFICATION

We classify each kernel using the roofline model (Williams et al., 2009), which plots achievable throughput against AI to produce a roof-shaped curve: a sloped bandwidth-limited region meeting a flat compute-limited ceiling. The ridge point where they meet equals peak FLOPS divided by peak bandwidth. We compute AI analytically from tensor dimensions and algorithm structure (FLOP counts from matrix multiply sizes, DRAM bytes from tensor shapes in fp16). Hardware profiling via Nsight Compute was attempted but restricted by cluster permissions.

For the H200 MIG 3g.71gb, the full GPU has 132 SMs at ~ 67 TFLOPS FP32. Our 60-SM partition achieves $(60/132) \times 67 \approx 30.5$ TFLOPS. The partition receives 4 of 8 HBM3e memory slices, giving $(4/8) \times 4.8 \approx 2.4$ TB/s. The ridge point is:

$$AI_{\text{ridge}} = \frac{\text{Peak FLOPS}}{\text{Peak BW}} = \frac{30.5 \times 10^{12}}{2.4 \times 10^{12}} \approx 12.7 \text{ FLOP/byte} \quad (2)$$

Operations with $AI < 12.7$ are bandwidth-bound. Those above are compute-bound.

Table 4: Arithmetic intensity classification for key operations (H200 MIG).

Operation	AI (FLOP/B)	Classification	Rationale
GELU / SiLU	~ 2.5	Bandwidth	10 FLOPs / 4 bytes per elem
RMSNorm / LN	$\sim 4\text{--}8$	Bandwidth	Reduction + scale over D dims
Flash Attn (enc, $N=750$)	~ 112	Compute	Score matrix in SRAM, not DRAM
Flash Attn (dec, $N_q=1$)	~ 1.0	Bandwidth	Full KV cache read, 1 query row
Linear (cuBLAS)	$\sim 170\text{--}360$	Compute	$2MK N$ FLOPs, high data reuse
Fused SwiGLU	~ 197	Compute	Two GEMMs, input loaded once
RoPE	~ 0.5	Bandwidth	6 FLOPs / 12 bytes per elem

LATEST CHANGE Source: docs/ai_manual_calculation.md for the analytic FLOP/byte derivations behind the Table 4 values; docs/ai_calculations_with_nsight_validation.md for the H200 ridge-point calculation and Nsight Systems cross-checks.

Flash attention dramatically increases encoder attention AI from ~ 16 (3-kernel pipeline, which materializes the score matrix) to ~ 112 (fused, score matrix stays in SRAM). Both are compute-bound on the H200 (ridge=12.7), but on consumer GPUs (RTX 5090, ridge ≈ 58.5) the 3-kernel pipeline would be bandwidth-bound while flash attention remains compute-bound. Decode-time attention (AI ~ 1.0) is bandwidth-bound on all architectures due to the single-row query against the full KV cache.

4.2 OVERALL BOTTLENECK

The dominant bottleneck is **memory bandwidth during autoregressive decoding**. Each decode step processes a single-token query against a growing KV cache through 28 decoder layers. The attention kernel reads the full KV cache (proportional to sequence length) but performs only $O(d)$ FLOPs per cached token—a classic bandwidth-bound pattern with AI ~ 1.0 , well below the ridge point on *all* GPU architectures.

Non-kernel overheads are also significant: with ~ 10 kernel launches per layer $\times 28$ layers $\times 13$ decode steps, launch latency ($\sim 5\text{--}15 \mu\text{s}$ each) accounts for $\sim 2\text{--}5$ ms. We mitigate this through kernel fusion (Section 5.2), which eliminates ~ 84 launches per inference, and through the SDPA fallback for single-token decoding.

5 OPTIMIZATION ATTEMPTS

We evaluated 13 optimizations using a **Hypothesis** $\rightarrow$ **Change** $\rightarrow$ **Result** methodology. Each was tested independently on an RTX 5090 for rapid iteration (all timings in this section refer to that GPU unless noted), then validated on the H200 teaching cluster (Section 6). Figure 2 summarizes the cumulative impact.




Figure 2: Optimization progression (development GPU, RTX 5090). Each bar shows end-to-end latency after applying all optimizations up to that step. Optimizations validated on H200 at 204.8 ms (Section 6). Full breakdown in Appendix Table 9.

5.1 TILE/BLOCK SIZE TUNING

Hypothesis: Larger tiles amortize memory access overhead and improve compute utilization, but are constrained by shared memory capacity.

Change: We tested all valid tile configurations for the flash attention kernel—(128, 128), (128, 64), (64, 64), (64, 32), (32, 32), (16, 16)—computing shared memory usage via Eq. 1 for each. We also built an autotune system (~95 lines) that benchmarked each valid configuration at runtime.

Result: Initially, we used Triton’s built-in `@triton.autotune` to select optimal tile configurations at runtime. However, when tested, the autotune system selected `BLOCK_M=16` as optimal in micro-benchmarks, but the full-pipeline benchmark showed **101.6 ms vs. 98.5 ms** for our hand-tuned 64×64 configuration—a 3.1 ms regression. We determined that the micro-benchmark methodology is too unreliable to capture full-pipeline cache effects. In response, we developed a `GPUProfile` (`layers.py:89`) system with pre-tested configurations stored in `_KNOWN_CONFIGS` (`layers.py:23`). Unknown GPUs use dynamic computation largest-to-smallest against the shared memory budget.

We validated these choices through ablation testing on the H200 (Table 5), confirming that double-buffering and 8 warps are each worth ~12 ms, while fp16 contributes only +1.5 ms on H200 (vs. -11.5 ms on RTX 5090).

Table 5: H200 ablation: top-impact parameter changes (baseline: 205.2 ms).

Change	Time (ms)	Δ	Insight
Disable fused RoPE	234.1	+28.9	Most impactful fused kernel
<code>num_stages=1</code>	217.4	+12.2	Double-buffering essential
<code>num_warps=4</code>	217.2	+12.0	128×128 needs 8 warps
Decoder attn 32×32	212.8	+7.6	Small tiles hurt
<code>num_warps=16</code>	209.5	+4.3	Register pressure
SDPA fallback off	208.6	+3.4	Custom kernel slow for <code>seq_q=1</code>
fp32 pipeline	206.7	+1.5	Minimal on H200 (HBM3e)
Triton matmul	206.2	+1.0	cuBLAS only slightly faster
MLP fusion off	204.5	-0.7	Neutral (cuBLAS already fast)

LATEST CHANGE Source: `benchmarks/benchmarks_ablation.md`; script: `hw1-asr/ablation.test.py` via `hw1-asr/ablation.job.sh`; generated artifacts: `hw1-asr/ablation_results.{json,md}` and `hw1-asr/ablation_output.log`.

5.2 KERNEL FUSION

Hypothesis: Fusing the SwiGLU pattern— $\text{SiLU}(\mathbf{xW}_g) \odot (\mathbf{xW}_u)$ —into a single kernel eliminates two intermediate VRAM round-trips and three kernel launches per MLP layer.

Change: We wrote `swiglu_fused_kernel` (`layers.py:546`) that loads tiles of $\mathbf{x}$, $\mathbf{W}_g$, and $\mathbf{W}_u$ into shared memory, computes both matrix products in registers, applies SiLU and the element-wise multiply, and writes only the final result to VRAM. The unfused path requires 5 kernel launches and 4 VRAM round-trips; the fused path requires 1 launch and 1 round-trip.

Result: With 28 decoder layers, fusion eliminates ~ 84 kernel launches per inference. For very small inputs (single-token decode, where $M < \text{TILE_M}$), we fall back to cuBLAS, which has lower launch overhead for small matrices. On the H200, MLP fusion contributes only -0.7 ms (Table 5), because cuBLAS already saturates compute throughput for these matrix sizes.

5.3 FLASHATTENTION-STYLE ATTENTION

Hypothesis: The naive 3-kernel attention approach materializes the full $N_q \times N_k$ score matrix in VRAM, consuming $O(N_q \cdot N_k)$ memory and bandwidth. A fused kernel with online softmax (Mikalov & Gimelshein, 2018) eliminates this materialization.

Change: We replaced the original 3-kernel pipeline (`attention_scores`, `softmax_inplace`, `attention_output`) with a single `flash_attention_kernel` (`attention.py:34`) (Dao, 2023; Ringlein et al., 2025). The kernel processes K/V in tiles of `BLOCK_N` rows, maintaining running statistics m_i (row-wise max) and l_i (sum of exponentials) that are corrected as new tiles arrive. The Q tile and accumulator O reside in registers; only the final output is written to VRAM.

Causal masking is handled via a compile-time `IS_CAUSAL` flag that skips tiles entirely above the diagonal, avoiding wasted computation. For single-token KV-cached decode (`seq_q ≤ 4`), we fall back to PyTorch’s `scaled_dot_product_attention`, which has lower launch overhead for this degenerate case.

Result: LATEST CHANGE

Latest update: Section 5.3 now uses canonical rerun 2238022, and `auto` is defined explicitly as the deployed mixed dispatch (flash for larger queries, SDPA fallback for tiny KV-cached decode steps), not as flash-only attention.

We later reintroduced the original 3-kernel path behind `GLM_ASR_ATTENTION_MODE=three_kernel` and benchmarked it against the current deployed path. Here, `auto` does *not* mean “flash everywhere”: it is the real deployed mixed dispatch, using the Triton flash kernel for larger `seq_q` and PyTorch SDPA only for tiny KV-cached decode steps (`seq_q ≤ 4`). In the updated same-codebase rerun, the student benchmark now also discards one full cold benchmark pass and averages three measured passes. Under that methodology, the current path is slightly faster end-to-end (210.9 ms vs. 212.0 ms) while preserving 100% accuracy. The warmup-corrected detailed benchmark tells the same story: isolated component time falls from 641.09 ms to 625.04 ms (1.03×), with lower prefill (13.36→12.82 ms) and 50-step decode cost (591.41→575.89 ms). We therefore treat FlashAttention-style dispatch as a modest but consistent same-codebase improvement rather than a dramatic standalone headline result. The clean end-to-end justification for keeping the SDPA fallback remains Table 5: disabling it costs +3.4 ms.

LATEST CHANGE Source: `benchmarks/benchmarks_attention.md`; script: `hw1-asr/flash-vs-three_kernel_job.sh`; raw logs: `logs/h200-attention.2238022/`.

5.4 OTHER OPTIMIZATIONS

fp16-throughout pipeline. The original code called `.float()` after every Linear layer (~ 120 calls), doubling data size at each point. Removing these conversions and keeping the entire pipeline in fp16 saves 11.5 ms on the development GPU (RTX 5090). On the H200, fp16 contributes only +1.5 ms (Table 5), reflecting HBM3e’s superior bandwidth. Internal computation remains fp32 for numerical stability.

KV-cache decoding (generate_v8b). The stock `generate()` reprocesses the full growing sequence on every decode step ($O(n^2)$). We implemented a KV-cached generation loop that processes only the new token each step, appending its K/V to a cache. This is monkey-patched onto the

model via `_try_patch_v8b()` (`layers.py:1482`), called during `Linear.__init__`. Impact on development GPU: -7.6 ms.

Fused Q+K RoPE kernel. RoPE requires applying the same rotation to both Q and K. The baseline uses two separate kernel launches. We fuse them into `fused_rope_pair_kernel` (`rope.py:189`), halving launch overhead. On the H200, this is the most impactful single optimization: disabling it costs $+28.9$ ms (Table 5). On the development GPU, impact was -11.8 ms.

6 COMPARISON

6.1 DATA COLLECTION

We benchmark on the provided `test_audio.wav` (3.5 s, 16 kHz, expected output: “CONCORD RETURNED TO ITS PLACE AMIDST THE TENTS”). Accuracy is measured by exact string match (case-insensitive) against the reference. Each benchmark invocation runs 2 warmup + 5 timed iterations; we report 5 invocations (25 timed iterations total). Both our implementation and the baseline are benchmarked under identical conditions.

6.2 END-TO-END COMPARISON

Table 6: End-to-end comparison on H200 MIG 3g.71gb (teaching cluster).

Implementation	Time (ms)	ms/tok	Accuracy	Speedup
Example baseline	464.1	35.70	100%	1.00×
Our template (fp16)	204.8	15.75	100%	2.27×

LATEST CHANGE Source: `benchmarks/benchmarks.md`; script: `hw1-asr/benchmark_student.py`; raw log: `logs/h200_e2e_2225992/benchmark_raw_output.txt`.

6.3 PER-OPERATOR COMPARISON

CHANGED Table 7 reports component-level timings on the H200 MIG 3g.71gb partition using `benchmark_detailed.py` with one full warmup benchmark pass discarded and three measured benchmark passes averaged (each pass uses 5 timed runs per component). These are isolated forward passes with 50 decode steps and *no KV history*, so they measure steady-state operator latency rather than the algorithmic benefit of KV-cached generation.

Table 7: **CHANGED** Per-component comparison on H200 MIG 3g.71gb (isolated forward passes, 50 decode steps, 1 warmup benchmark discarded, average of 3 measured benchmark passes).

Component	Ours (ms)	Baseline (ms)	Speedup
Audio Encoder	36.53	167.02	4.57×
Projector	0.14	1.11	7.93×
Decoder Prefill	12.97	20.51	1.58×
Decoder Decode (50 steps)	580.45	817.09	1.41×
Total	630.09	1005.73	1.60×

LATEST CHANGE Source: `benchmarks/benchmarks_detailed.md`; script: `hw1-asr/benchmark_detailed.py` via `hw1-asr/benchmark_detailed_job.sh`; raw logs: `logs/h200_detailed_2236079/`.

6.4 ROOT CAUSE ANALYSIS

All optimizations preserve full transcription accuracy: fp16 introduces no degradation because internal kernel computation remains in fp32, and KV-cached decoding produces identical token sequences to the stock path.

CHANGED In the steady-state H200 component profile, our implementation is faster in every stage. The largest absolute saving comes from decoder decode (817.09 ms $\rightarrow$ 580.45 ms over 50 steps), while audio encoding and the projector also improve substantially once Triton compilation warmup is removed from the measurement.

CHANGED The isolated component table understates the full end-to-end speedup because `benchmark_detailed.py` does not use KV-cached generation. Table 6, by contrast, uses the full student benchmark with `generate_v8b`. The end-to-end result therefore benefits from both faster steady-state kernels *and* the algorithmic reduction from quadratic reprocessing to linear-time cached decode. This explains why the per-component total speedup is $1.60\times$ while the full H200 pipeline reaches $2.27\times$.

CHANGED 1. Faster steady-state kernels in both encoder and decoder. Flash attention, fused RoPE, fp16 norms, and fused MLP kernels reduce operator time throughout the pipeline. On H200 this appears as $4.57\times$ faster audio encoding, $1.58\times$ faster decoder prefill, and $1.41\times$ faster decode steps in isolated profiling.

CHANGED 2. KV-cached generation in the end-to-end path. The detailed benchmark measures single-step decode without KV history, but the full inference benchmark uses our KV-cached `generate_v8b`. That cached path avoids recomputing attention over the full growing sequence at every token and therefore contributes additional end-to-end speedup beyond the isolated operator table.

Cross-GPU generalization. To verify portability, we evaluated on both the teaching cluster (H200 MIG) and a consumer GPU (RTX 5090). The `GPUProfile` system correctly adapts tile sizes and pipeline stages to each architecture’s shared memory budget. Table 8 confirms consistent speedups across both GPUs.

Table 8: Cross-GPU comparison: teaching cluster vs. consumer GPU.

GPU	SMs	VRAM	Ours (ms)	Baseline (ms)	Speedup
H200 MIG 3g.71gb	60	70 GB	204.8	464.1	$2.27\times$
RTX 5090 (full)	170	32 GB	100.4	262.2	$2.61\times$

LATEST CHANGE Source: H200 row from `benchmarks/benchmarks.md`
`(logs/h200_e2e.2225992/benchmark_raw.output.txt);` RTX 5090
row from `benchmarks/benchmarks_5090.md` (embedded transcript from
`hw1-asr/benchmark_student.py`).

CHANGED The RTX 5090 row in Table 8 comes from a later confirmation rerun (100.4 ms vs. 262.2 ms), whereas Appendix Table 9 preserves the original development benchmark chain (261.3 ms $\rightarrow$ 98.5 ms). We keep the full progression table on a single coherent benchmark session so that the per-step deltas remain meaningful.

7 CONCLUSION

Most impactful optimization. On the H200, our optimizations reduced inference from 464.1 ms to 204.8 ms ($2.27\times$). Ablation testing (Table 5) revealed that fused RoPE (+28.9 ms when disabled), double-buffering (+12.2 ms), and warp count (+12.0 ms) collectively account for >53 ms—kernel launch reduction and memory-latency hiding dominate over precision or tile-size changes on this architecture.

Key lessons. (1) The pipeline is overwhelmingly *memory-bandwidth-bound*: halving data types (fp32 $\rightarrow$ fp16) and eliminating intermediate writes (kernel fusion, flash attention) provided the largest gains. (2) Attention is the most challenging kernel to optimize because tile size, shared memory, warp count, and pipeline stages are tightly coupled; the H200’s 228 KB shared memory accommodates 128×128 tiles with double-buffering, while consumer GPUs with ~ 99 KB require 64×64 with single-buffering—demonstrating the need for a portable `GPUProfile` system. **CHANGED** (3) Profile before optimizing: warmup-corrected component profiling confirms that decoder decode, not the compute-heavy linear projections, remains the dominant bottleneck—decode steps (bandwidth-bound attention + KV reads) still consume 92.1% of the isolated component total on H200 even

486 [after optimization](#). (4) Testing each kernel independently is straightforward; however, problems
487 arise when kernels are composed in the full pipeline, as cache interactions between adjacent kernels
488 produce behaviors not visible in isolated benchmarks.

489 **Surprising findings.** Autotune found *worse* configs than hand-tuning (micro-benchmarks miss
490 cache effects). Encoder attention is compute-bound on H200 but bandwidth-bound on con-
491 sumer GPUs—the same kernel has different bottlenecks across architectures. **Future work:**
492 `torch.compile`, speculative decoding, FP8 quantization, and per-architecture SDPA threshold
493 tuning.
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539

REFERENCES

- Joshua Ainslie, James Lee-Thorp, Michiel de Jong, Yury Zemlyanskiy, Federico Lebrón, and Sumit Sanghai. Gqa: Training generalized multi-query transformer models from multi-head checkpoints. *arXiv preprint arXiv:2305.13245*, 2023.
- Tri Dao. Flashattention-2: Faster attention with better parallelism and work partitioning, 2023. URL <https://arxiv.org/abs/2307.08691>.
- Maxim Milakov and Natalia Gimelshein. Online normalizer calculation for softmax. In *arXiv preprint arXiv:1805.02867*, 2018.
- Burkhard Ringlein, Jan van Lunteren, Radu Stoica, and Thomas Parnell. The anatomy of a triton attention kernel. *arXiv preprint arXiv:2511.11581*, 2025.
- Noam Shazeer. Glu variants improve transformer. *arXiv preprint arXiv:2002.05202*, 2020.
- Jianlin Su, Murtadha Ahmed, Yu Lu, Shengfeng Pan, Wen Bo, and Yunfeng Liu. Roformer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063, 2024.
- Philippe Tillet, Hsiang-Tsung Kung, and David Cox. Triton: an intermediate language and compiler for tiled neural network computations. In *Proceedings of the 3rd ACM SIGPLAN International Workshop on Machine Learning and Programming Languages*, pp. 10–19, 2019.
- Samuel Williams, Andrew Waterman, and David Patterson. Roofline: an insightful visual performance model for multicore architectures. *Communications of the ACM*, 52(4):65–76, 2009.

A APPENDIX

A.1 FULL OPTIMIZATION PROGRESSION

CHANGED Table 9 shows every optimization step from the original RTX 5090 development benchmark chain. These step-by-step values are intentionally kept from one session (261.3 ms baseline to 98.5 ms final) rather than mixed with the later 100.4 ms confirmation rerun used in Table 8.

Table 9: Complete optimization progression (RTX 5090, 3.5 s audio, 13 tokens).

#	Change	Time	Δ	Mechanism
0	Baseline	261.3	—	fp32, 3-kernel attn, $O(n^2)$
1	Triton kernels + cuBLAS + TF32	209.8	−51.5	Custom kernels + tensor cores
2	bf16 weights + Flash Attention	136.4	−73.4	Half bandwidth + fused attn
3	Fused Q+K RoPE pair kernel	124.6	−11.8	Halved RoPE launches
4	bf16 RMSNorm output	120.7	−3.9	Eliminated type conversion
5	bf16 LayerNorm output	121.1	−0.7	Same for encoder norms
6	KV cache (generate_v8b)	113.5	−7.6	$O(n)$ decoding
7	SDPA fallback (seq_q ≤ 4)	110.0	−3.5	Lower overhead for decode
8	fp16 cuBLAS HGEMM	109.6	−0.4	fp16 slightly faster than bf16
9	Remove .float() casts	102.1	−7.5	Eliminated ~120 fp32 casts
10	Remove activation fp32 casts	98.4	−3.7	SiLU/GELU stay fp16
11	Remove norm fp32 casts	98.1	−0.3	Norms output fp16 directly
12	fp16 embeddings + fused MLP	98.5	+0.4	Pipeline complete (noise)

LATEST CHANGE Source: benchmarks/benchmarks.history.md; historical RTX 5090 development record extracted from pre-cleanup docs at branch base f8c2f36.

A.2 REJECTED OPTIMIZATIONS

LATEST CHANGE Source: benchmarks/benchmarks.history.md; historical RTX 5090 development record extracted from pre-cleanup docs at branch base f8c2f36.

Table 10: Optimizations tested and rejected with measured results.

Optimization	Impact	Reason for Rejection
Grid swizzling (SwiGLU)	+18 ms	RTX 5090 L2 (98 MB) already has good locality
@triton.autotune (GELU/SiLU)	+0.7 ms	Tuning warmup exceeds possible gain
Flash Attn num_stages=2	Crash	RTX 5090 99 KB cannot hold two tile buffers
SDPA for all attention	+6 ms	Custom kernel faster for long sequences
SDPA enable_gqa	+13 ms	Manual KV expansion is faster
Warmup autotune	+3.1 ms	Micro-benchmarks chose suboptimal configs

A.3 BENCHMARK SOURCE MAP

Table 11 provides a direct trace from the main benchmark-backed report claims to their canonical benchmark documents, scripts, and raw artifacts. The intended lookup path is: report table → canonical benchmark doc → script/runner → raw artifact or generated result file.

Table 11: **LATEST CHANGE** Benchmark source map for the main report claims.

Report element	Canonical doc	Script / runner	Artifact
tab:e2e,	benchmarks.md	benchmark_student.py	logs/h200-e2e-2225992/...
tab:comparison			
tab:detailed,	benchmarks_detailed.md	benchmark_detailed.py	logs/h200-detailed-2236079/...
tab:peroperator		/ benchmark_detailed_job.sh	
tab:ablation	benchmarks_ablation.md	ablation_test.py / ablation_job.sh	hw1-asr/ablation-results.{json,md}
tab:crossgpu_main (H200)	benchmarks.md	benchmark_student.py	logs/h200-e2e-2225992/...
tab:crossgpu_main (RTX 5090)	benchmarks_5090.md	benchmark_student.py	embedded transcript
Section 5.3	benchmarks_attention_three_kernels.md		logs/h200-attention-2238022/...
tab:progression,	benchmarks_historical	development	extracted history at
tab:rejected		runs	f8c2f36

A.4 CODE MAP

LATEST CHANGE

Following the C4 model’s idea of creating “maps of your code” through progressively higher-level abstractions, and arc42’s level-1 building-block view, Table 12 groups the supplementary code by building block, responsibility, and primary source location rather than listing every kernel symbol individually. This gives a grader a top-down navigation aid first; Table 11 then provides the trace from report claims to benchmark scripts and artifacts.

LATEST CHANGE Structure based on two documentation patterns: the C4 model’s abstraction-first “maps of your code” and arc42’s level-1 building-block/source-mapping guidance. In practice, that means naming a small set of coherent building blocks, stating each block’s responsibility, and pointing to the 2–3 most important source locations rather than dumping a flat symbol list.

648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701

Table 12: **LATEST CHANGE** Level-1 building-block map of the supplementary code.

Building block		Responsibility	Primary files / entry points	Report use
Benchmark	harness	Runs the end-to-end, detailed, ablation, and attention-backend experiments; writes the logs that feed the benchmark documents.	benchmark.student.py, benchmark.detailed.py, ablation.test.py, flash-vs-three-kernel-job.sh	Tables 2, 3, 5; Sec. 5.3
Optimized	template runtime	Selects GPU-specific tile/configuration choices, wires the fused Triton kernels into the Hugging Face model, and implements KV-cached generation.	template/layers.py: GPUProfile, _compute_attention_tiles, _generate_v8b, _try_patch_v8b	Secs. 3–5, conclusion
Attention	subsystem	Implements the main attention dispatch: FlashAttention for long sequences, SDPA fallback for tiny decode steps, and the reintroduced 3-kernel path for controlled comparison.	template/attention.py: flash.attention.kernel, scaled.dot.product.attention	Sec. 5.3, Table 7
RoPE	subsystem	Applies rotary position embeddings with a fused kernel path and the runtime wrapper used by the decoder.	template/rope.py: fused_rope_pair_kernel, apply_rotary_pos_emb	Kernel-fusion discussion, appendix
Baseline reference	implementation	Provides the comparison target for end-to-end and per-operator speedups against our optimized template.	example/layers.py, example/attention.py, example/rope.py	Tables 6, 7, 8
Evidence	bundle	Stores the canonical benchmark writeups and the pulled raw H200 artifacts used to trace report numbers back to scripts and runs.	benchmarks/*.md, logs/h200.*	Appendix A.2–A.3